Hard-Attention for Scalable Image Classification

Abstract

Can we leverage high-resolution information without the unsustainable quadratic complexity to input scale? We propose TNet (Traversal Network), a novel multi-scale hard-attention architecture, which traverses image scale-space in a top-down fashion, visiting only the most informative image regions along the way. TNet offers an adjustable trade-off between accuracy and complexity, by changing the number of attended image locations. We compare our model against hard-attention baselines on ImageNet, achieving higher accuracy with less resources (FLOPs, processing time and memory). We further test our model on fMoW dataset, where we process satellite images of size up to 896×896 px, getting up to 2.5x faster processing compared to baselines operating on the same resolution, while achieving higher accuracy as well. TNet is modular, meaning that most classification models could be adopted as its backbone for feature extraction, making the reported performance gains orthogonal to benefits offered by existing optimized deep models. Finally, hard-attention guarantees a degree of interpretability to our model's predictions, without any extra cost beyond inference.

1 Introduction

In image classification, deep neural networks (DNNs) are typically designed and optimized for a specific input resolution, e.g. 224×224 px. Using modern DNNs on images of higher resolution (as happens e.g., in satellite or medical imaging) is a non-trivial problem due to the subtlety of scaling model architectures [57], and rapid increase in computational and memory requirements.

A linear increase in the spatial dimensions of the input results in a quadratic increase in computational complexity and memory, and can easily lead to resource bottlenecks. This can be mitigated with careful engineering, e.g., streaming [46] or gradient checkpointing [42]. However, such solutions are content-agnostic, and don't take advantage of the fact that discriminative information may be sparse and distributed across various image scales, deeming processing of the whole input unnecessary.

Our goal it to leverage high resolution information, while dispensing with the unsustainable quadratic complexity to input scale. To this end, we propose TNet (Traversal Network), a multi-scale hard-attention architecture, which traverses image scale-space in a top-down fashion, visiting only the most informative image regions along the way. TNet is recursive, and can be applied to inputs of virtually any resolution; an outline of its processing flow is presented in Fig. 1 (a). Our method draws its intuition from the way humans use saccades to explore the visual world.

TNet offers an adjustable trade-off between accuracy and complexity, by changing the number of attended image regions. This way, complexity increases linearly with the number of attended locations, irrespective of the input resolution. Also, hard-attention explicitly reveals the image regions that our model values the most, providing a certain degree of interpretability (Fig. 1 (c)). Importantly, interpretability comes without any extra cost beyond inference, in contrast to popular attribution methods, which require at least an additional backward pass [53], or numerous forward passes [1].

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 1: (a) Multi-scale processing in TNet. Starting at level 1, features are selectively extracted from image regions at various scales (red cubes), and then, they are combined to create the final image representation used for classification (blue cube). (b) Experimental results on ImageNet [13] with baselines based on [18]. Numeric annotations correspond to the number of attended locations. Our model offers a better trade-off between accuracy and complexity (FLOPs). (c) Examples of attention policy (top 3 locations) learned on ImageNet.

Attention may also reduce data acquisition cost [60], by allowing only a fraction of the high resolution content to be acquired.

TNet is trained end-to-end by employing a modified version of REINFORCE rule [68], while using only classification labels. Our architecture is modular, and most classification models could be adopted as its backbone for feature extraction. This way, we can directly take advantage of various performance benefits offered by existing optimized deep models.

Hard-attention is the mechanism that allows TNet to dispense with quadratic complexity to input scale, and as a result, we evaluate our model against strong hard-attention baselines on ImageNet [18]. A summary of our results is depicted in Fig. 1 (b), where we see that TNet offers a better trade-off between accuracy and complexity measured in FLOPs (similar behavior is observed with actual timings and memory). We extend our experiments to fMoW dataset, which consists of high-resolution satellite images [12]. We process images up to 896×896 px, getting up to 2.5x faster processing compared to baselines operating on the same resolution, while achieving higher accuracy as well.

We find improvements in accuracy surprising, because TNet is processing only part of the input, in contrast to fully convolutional baselines. We primarily attribute this behavior to a novel regularization method, which encourages classification based on individual attended locations. We verify its efficacy through an ablation study.

2   Related work

Attention. Attention has a long history in the artificial neural networks literature [31], and in the modern era of deep learning it has been used very successfully in various problems [36, 14, 4, 70, 22, 67, 55]. Two main forms of attention are: *soft attention* which processes everything but weighs various regions differently; and *hard attention* which selects only a fraction of the data for processing. Hard-attention models address various use-cases, and can be motivated by interpretability [18], reduction of high-resolution data acquisition cost [60], or computational efficiency [33]. Our goal is to offer a single model that takes advantage of all these benefits.

Our model is conceptually similar to glimpse-based models [2, 43, 50, 54, 19, 3]. An important difference is that we don't restrict our attention policy to 2D space, but we consider scale dimension as well. Also, our model parallelizes feature extraction at each processing level, instead of being fully sequential. Furthermore, we don't use recurrent neural networks (RNNs) to combine features from different locations, but instead, we simply average them (see Section 3). This way, gradients flow directly to extracted features, without the need to backpropagate through RNN steps. This is a simpler strategy compared to LSTM in order to avoid vanishing gradients.

Figure 2: Three unrolled processing levels of our architecture. Starting at level 1, the image is processed in the coarsest scale (*Feature Extraction Module*), and the extracted features are used to decide which image locations should be processed in finer detail (*Location Module*). This process is repeated for each selected location to reach level 3, where features from the highest resolution are extracted. All features are enriched with positional information (*Positional Encoding Module*), and then are averaged before the final classification (*Classification Module*).

Recent work explores soft attention mechanisms based on transformers, which originate from the natural language processing community [63]. Transformers have already been used extensively in machine vision [45, 74, 16, 8, 48], and research interest in related directions has increased [6, 11, 5].

Multi-scale representations. We identify four broad categories of multi-scale processing methods. (1) *Image pyramid methods* extract multi-scale features by processing multi-scale inputs [17, 47, 34, 44]. Our model belongs to this category, and due to its recursive nature, it can extract features from an arbitrary number of pyramid levels (see Section 3). (2) *Encoding schemes* take advantage of the inherently hierarchical nature of deep neural nets, and reuse features from different layers, since they contain information of different scale [24, 41, 10]. (3) *Encoding-Decoding schemes* follow up the feed-forward processing (encoding) with a decoder, that gradually recovers the spatial resolution of early feature maps, by combining coarse and fine features [52, 40]. (4) *Spatial modules* are incorporated into the forward pass, to alter feature extraction between layers [71, 9, 65].

Computational efficiency. There are multiple ways to adjust the computational cost of deep neural networks. We organize them into four categories. (1) *Compression methods* aim to remove redundancy from already trained models [38, 26, 72]. (2) *Lightweight design strategies* are used to replace network components with computationally lighter counterparts [32, 30, 51, 27, 66]. (3) *Partial computation methods* selectively utilize parts of a network, creating paths of computation with different costs [37, 20, 73, 29, 69]. (4) *Attention methods* selectively process parts of the input, based on their importance for the task at hand [49, 39, 33, 56]. This is the strategy we follow in our architecture.

3 Architecture

3.1 Processing flow

We present our architecture by walking through the example in Figure 2, where we process an image with original resolution of 896×896 px (① in the top left corner). In the first level, we downscale the image to 224×224 px and pass it through the *feature extraction module*, in order to produce a feature vector V_1 that contains a coarse description of the original image.

To proceed to the next level, we feed an intermediate feature map, F_1, from the *feature extraction module* to the *location module*, which considers a number of candidate locations described by F_1,

and predicts their importance (in this particular example, the candidate locations form a 2×2 regular grid (②), and the *location module* yields 4 predictions). We express region importance as attendance probability, which parametrizes a categorical distribution used for sampling without replacement; in our current example we sample 2 locations (③).

In the 2nd processing level, we crop the selected regions from the full-resolution image, resize them to 224×224 px, and feed them to the *feature extraction module* to obtain the corresponding feature vectors (here V_{21} and V_{23}). The original input resolution allows us to move to a 3rd processing level, where we feed F_{21} and F_{23} to the *location module*, leading to 2 categorical distributions. We sample 1 location from each one of them to get V_{35} and V_{39}.

Features extracted from all levels are passed through a *positional encoding module*, which injects information about the spatial position and scale of the image regions the features describe. The resulting vectors, $\{V_*^{'}\}$, are averaged (④) into a single comprehensive representation, $V^{'}$, that is fed to the *classification module* for the final prediction.

3.2 Modules

The **feature extraction module** receives an image of fixed size as input, and outputs a feature vector V and an intermediate spatial representation F. The input size, a hyperparameter we call *base resolution*, defines the minimum amount of information that can be processed. Hence, it constraints the minimum cost that our model has to pay in computational and memory resources. In our experiments, feature extraction modules are implemented using CNNs.

The **location module** predicts $K = n^2$ probabilities of a Categorical distribution over the locations within a given $n \times n$ grid of candidate image regions. It receives a feature map of size $n \times n \times c$ as input, where each $1 \times 1 \times c$ vector describes the corresponding location of the grid. The feature map is passed through a series of 1×1 convolutions (contextual information is infused as well, e.g., via squeeze and excitation [28]), yielding K logits, which are transformed to relative region importance via a softmax layer.

The **positional encoding module** receives a feature vector f and a positional encoding vector p, and combines them (e.g., through a fully connected layer) to an output feature vector $f^{'}$. We use a variant of the fixed positional encodings based on sine and cosine functions introduced in [63]. Instead of a single dimension of time, we have three: two spatial dimensions and scale.

The **classification module** projects the final feature vector (e.g., via a linear layer) to classification logits. We provide the exact architecture in the Appendix, along with justification of the design choices we made for every module.

4 Training

4.1 Learning rule

Our model is not end-to-end differentiable because of location sampling. We address this problem using a variant of the *REINFORCE* [68] learning rule:

$$L_F = \frac{1}{N \cdot M} \sum_{i=1}^{N \cdot M} \left[\frac{\partial \log p(y_i | l^i, x_i, w)}{\partial w} + \lambda_f (\log p(y_i | l^i, x_i, w) - b) \frac{\partial \log p(l^i | x_i, w)}{\partial w} \right] \quad (1)$$

where x_i is the ith image, y_i is its label, and w are the parameters of our model. $p(l^i | x_i, w)$ is the probability that the sequence of locations l^i is attended for image x_i, and $p(y_i | l^i, x_i, w)$ is the probability of predicting the correct label after attending l^i.

$N \cdot M$ is the total number of examples used for each update. The size of our original batch B is N, and we derive (1) using a Monte Carlo estimator with M samples to approximate the expectation $\sum_{l^i} p(l^i | x_i, w) \left[\frac{\partial \log p(y_i | l^i, x_i, w)}{\partial w} + \log p(y_i | l^i, x_i, w) \frac{\partial \log p(l^i | x_i, w)}{\partial w} \right]$ for each image x_i in B.

b is a baseline used to reduce the variance of our estimator, while we replace $\log p(y_i | l^i, x_i, w)$ with a discrete indicator function R equal to 1 for correct predictions and 0 otherwise. λ_f is a weighting hyperparameter. We provide a detailed derivation of learning rule (1) in the Appendix.

The first term of L_F is used to update the parameters in order to maximize the probability of the correct label. The second term is used to update the location selection process, according to the utility of the attended sequence l^i in the prediction of the correct label.

4.2 Per-feature regularization

When our model attends to a location sequence l_i and makes a correct prediction, we positively reinforce the probability to attend every location in the sequence. This is expressed in the second term of (1), where we use probability $p(l^i|x_i, w)$ of the whole sequence l_i. However, some locations may not contribute to the correct prediction, e.g., if they have missed the object of interest. In such cases, we reinforce the attendance of uninformative regions, encouraging a sub-optimal policy.

To mitigate this problem, for every attended location, we use its feature vector to make a separate classification prediction. Then, we use these predictions to complement our assessment on whether the corresponding image regions have useful content. We modify our learning rule as follows:

$$L_r = L_F^s + \frac{1}{|l^i|} \sum_{k=1}^{|l^i|} L_F^k, \tag{2}$$

$$L_F^s = \frac{1}{N \cdot M} \sum_{i=1}^{N \cdot M} \left[\lambda_c \frac{\partial \log p(y_i|l^i, x_i, w)}{\partial w} + \lambda_f \lambda_r (R^s - b) \frac{\partial \log p(l^i|x_i, w)}{\partial w} \right], \tag{2a}$$

$$L_F^k = \frac{1}{N \cdot M} \sum_{i=1}^{N \cdot M} \left[(1 - \lambda_c) \frac{\partial \log p(y_i|l_k^i, x_i, w)}{\partial w} + \lambda_f (1 - \lambda_r)(R^k - b) \frac{\partial \log p(l_k^i|x_i, w)}{\partial w} \right] \tag{2b}$$

where L_F^s is learning rule (1) with additional weighting hyperparameters $\lambda_c, \lambda_r \in [0, 1]$. L_F^k is learning rule (1) when we attend only to the kth location (l_k^i) from sequence l^i. Also, we introduce weighting factors $(1 - \lambda_c)$ and $(1 - \lambda_r)$. $|l^i|$ is the number of locations in sequence l^i. R^s and R^k are discrete indicator functions equal to 1 when a prediction is correct, and 0 otherwise. L_F^s updates the parameters of our model based on attending l^i, while L_F^k updates them based on l_k^i; λ_c and λ_r specify the relative importance of these updates.

Even though our initial motivation was to improve the attention policy, the first term in (2b) updates feature extraction parameters based on independent predictions from attended image regions. We empirically observed that such updates boost performance, potentially because they lead to features that co-adapt less and generalize better.

5 Experimental evaluation

5.1 Effectiveness of hard-attention mechanism

Data. ImageNet [13] consists of natural images from $1,000$ classes. We use the ILSVRC 2012 version which consists of $1,281,167$ training and $50,000$ validation images.

Models. We use Saccader and DRAM [18] as hard-attention baselines. We use Saccader with BagNet-77-lowD [7] as its backbone for feature extraction. BagNet-77-lowD is based on ResNet-50 [25], with receptive field constrained to 77×77 px. DRAM uses the standard ResNet-50 for feature extraction, with glimpses of 77×77 px.

For fair comparison, we set the base resolution of TNet to 77×77 px, and use BagNet-77, a slightly modified version of BagNet-77-lowD, as the feature extraction module. In the location module, we use a uniform 5×5 grid of overlapping candidate regions. The dimensions of each grid cell span 34.375% of the corresponding image dimensions. This way, for an image of size 224×224 px, the image patches within the grid cells at the 2nd processing level are 77×77 px. We use BagNet-77 as a separate fully convolutional baseline, with inputs of 224×224 px. Additional details about TNet and BagNet-77 are provided in the Appendix.

Training. We train TNet with 2 processing levels on images of 224×224 px using class labels only. We train for 200 epochs using the Adam optimizer [35] with initial learning rate 10^{-4}, that we drop

Table 1: Efficacy of hard-attention mechanism: TNet surpasses all hard-attention baselines [18] on ImageNet, by attending to just 1 location. Higher accuracy can be achieved for less FLOPs, and translates to lower actual run time. Memory savings are obtained compared to BagNet-77 and Saccader as well. TNet has slightly more parameters compared to BagNet-77 due to the additional modules, but has significantly fewer parameters than the hard-attention baselines.

Model	#Locs	Top-1 Acc.	Top-5 Acc.	FLOPs (B)	#Params (M)	Time (msec/im)	Memory (GB)
Saccader	2	67.79%	85.42%	19.5	35.58	7.31 ± 1.55	2.58
	6	70.31%	87.8%	19.5		7.32 ± 1.55	2.52
	20	72.02%	89.51%	19.51		7.36 ± 1.50	2.53
	30	72.27%	89.79%	19.51		7.36 ± 1.49	2.51
DRAM	2	49.72%	73.27%	1.86	45.61	3.43 ± 1.57	0.45
	4	64.26%	84.84%	3.1		3.92 ± 1.56	0.44
	8	67.5%	86.6%	5.58		4.61 ± 1.59	0.45
	20	65.15%	84.58%	13.03		7.58 ± 1.53	0.46
BagNet-77	-	73.42%	91.1%	18.42	20.55	5.94 ± 0.09	2.62
TNet	0	67.29%	87.38%	1.82	21.86	0.74 ± 0.01	0.46
	1	73.12%	90.56%	3.63		1.43 ± 0.01	0.57
	2	74.12%	91.18%	5.43		2.09 ± 0.02	0.69
	3	74.41%	91.4%	7.24		2.74 ± 0.03	0.95
	5	74.62%	91.35%	10.84		3.96 ± 0.04	1.47

once by a factor of 0.1. We use dropout (keep probability 0.5) in the last layer of feature extraction. We use per-feature regularization with $\lambda_c = \lambda_r = 0.3$. We attend to a fixed number of 3 locations.

We train BagNet-77 from scratch, on 224×224 px images. Compared to TNet, we reduce dropout keep probability to 0.375, and we early-stop at 175 epochs. We don't train our own Saccader and DRAM, we use results reported in [18]. Additional training details are provided in the Appendix.

Results. We present our results in Table 1. TNet outperforms Saccader and DRAM by attending to only 1 location, while it surpasses BagNet-77 by attending to 2. Saccader was designed with accuracy and interpretability in mind, which leads to sub-optimal computational efficiency as it processes the entire full-resolution image before attending to locations. As a result, FLOPs stay nearly constant and remain similar to BagNet-77, more that 5 times higher than TNet with 1 attended location. DRAM offers the expected gradual increase in computational cost as the number of attended locations increases, but for FLOPs comparable with TNet - e.g., DRAM for 8 locations (maximum accuracy) and TNet for 2 - our model is superior by more than 6.5%.

TNet has slightly more parameters than BagNet-77, because of the location and positional encoding modules. Saccader and DRAM have significantly heavier attention mechanisms in terms of parameters.

We profile all models to validate correspondence between theoretical FLOPs and real processing speed, and to assess memory requirements. We time inference on batches of 64 images; early batches are discarded to discount code optimization. We use a single NVIDIA Quadro RTX 8000 GPU, with 64 GB of RAM, and 20 CPUs to mitigate data pipeline impact. For Saccader and DRAM we use public implementations [21] in TensorFlow (TF) 1. TNet and BagNet-77 are implemented in TF 2. The difference in TF versions may be a confounding factor in the obtained results. However, TNet and BagNet-77 use the same environment and yield the expected difference in latency. DRAM attends locations sequentially, while TNet processes all locations from the same level in parallel. This leads to fixed memory use in DRAM and monotonic increase in TNet, as number of attended locations increases. We could trade this for latency by switching to fully sequential processing.

5.2 Scalability

Data. Functional Map of the World (fMoW) [12] consists of high-resolution satellite images from 62 classes. They are split in $363,572$ training, $53,041$ validation and $53,473$ testing images. All images have bounding box annotations.

Table 2: TNet effectively scales to images of resolution 448×448 px and 896×896 px on fMoW [12]. It surpasses in accuracy EfficientNet-B0 baselines trained on inputs of the same resolution, while it requires less FLOPs. Differences in FLOPs translate to differences in actual run time, while memory requirements are lower as well. TNet has more parameters compared to EficientNet-B0 due to the additional modules.

Model	Input Size	#Locs	BBoxes	Top-1 Acc.	Top-5 Acc.	FLOPs (B)	#Params (M)	Time (msec/im)	Memory (GB)
EfficientNet-B0	224^2	-	$\checkmark$	69.7%	89.22%	0.39	4.13	0.80 ± 0.01	0.76
ResNet-50 [60]	224^2	-	$\checkmark$	67.3%	-	4.09	23.71	-	-
DenseNet-121 [61]	224^2	-	$\checkmark$	70.7%	-	3	7.1	-	-
EfficientNet-B0	224^2			62.8%	84.97%	0.39		0.80 ± 0.01	0.76
	448^2	-	-	69.83%	90.22%	1.54	4.13	3.04 ± 0.18	2.6
	896^2			70.6%	90.81%	6.18		12.18 ± 0.18	10.35
TNet	224^2	0	-	47.79%	81.14%	0.39		0.84 ± 0.02	0.76
	448^2	1		70.17%	90.99%	0.77		1.74 ± 0.02	1.3
		2	-	71.46%	91.58%	1.16	4.56	2.46 ± 0.03	1.55
		3		71.57%	91.72%	1.55		3.18 ± 0.04	2.03
	896^2	4	-	72.16%	91.98%	1.94		4.71 ± 0.03	3.13
		6		71.92%	91.83%	2.71		6.13 ± 0.05	3.47

Models. We use EfficientNet-B0 (EN-B0) [57] as the feature extraction module of TNet, with base resolution of 224×224 px. In the location module we use a 3×3 grid with overlapping cells (50% overlap). Hence, when processing 2 levels, we use inputs of 448×448 px, and with 3 levels, we use inputs of 896×896 px. Details of the TNet architecture are provided in the Appendix.

We create our first 3 baselines by training EN-B0 with images resized to different resolution; 224×224 px, 448×448 px, and 896×896 px. We use the available bounding boxes to crop the regions of interest, resize them to 224×224 px, and train an additional EN-B0 baseline. Also, we report the best accuracy we find in the literature, achieved by single-model predictions (not network ensembles), and without the use of any meta-data for training. These are the ResNet-50 [60] and DenseNet-121 [61] baselines.

Training. We train TNet using only classification labels. The training proceeds in 2 stages: (1) training from scratch for 40 epochs on 448×448 px inputs, using 2 processing levels, and a fixed number of 2 locations; (2) fine-tuning for 10 more epochs on images of 896×896 px, which allow us to extend processing to 3 levels. We use 4 locations; 2 in the 2nd processing level, plus 1 for each of them in the 3rd. We use per-feature regularization in both stages. All 4 EN-B0 baselines are trained independently, from scratch. The exact hyperparameters are provided in the Appendix.

Results. We present our results in Table 2. TNet surpasses all baselines by attending to 2 locations (2 processing levels), with top-1 accuracy of 71.46%. This requires less FLOPs than the corresponding EN-B0 baseline at the same input size (448×448 px), which achieves accuracy of 69.83%.

Extending processing to 3 levels with 4 attended locations, further increases accuracy to 72.16%, while FLOPs increase by $\sim 67\%$ (from 1.16 to 1.94B FLOPs). The corresponding EN-B0 baseline operating on 896×896 px inputs, achieves 70.6% accuracy, and requires $\sim 300\%$ more FLOPs compared to EN-B0 operating on 448×448 px inputs (from 1.54 to 6.18B FLOPs). This shows that TNet can efficiently leverage high-resolution information.

We profile our models by following the procedure described in Section 5.1, and we show that differences in FLOPs translate to differences in actual run time. TNet also requires less memory, although it has more parameters because of the location and positional encoding modules.

5.3 Modularity and fine-tuning

TNet is a modular architecture, and we would like to test its compatibility with different backbone models, especially when these models are initialized with pre-trained weights, since this is a popular practice [15, 16, 58].

Figure 3: TNet is modular, and different models can be used as its feature extraction module. We plot TNet performance with 3 different backbones (attended locations range from 0 to 5). Stronger backbones lead to the expected increase in accuracy and FLOPs. EN baselines and the feature extraction modules of TNet models are initialized with pre-trained weights, while the rest of the modules are randomly initialized. TNet models achieve similar or better accuracy compared to corresponding baselines, showing that fine-tuning can be an effective practice.

Data. We use 2 fine-grained classification datasets, CUB-200-2011 [64] and NABirds [62], which are commonly used as downstream tasks. CUB-200-2011 has 200 classes of bird species, with $5,994$ training and $5,794$ testing images. NABirds has 555 classes of bird species, with $23,929$ training and $24,633$ testing images. We resize all images to 448×448 px.

Models. We use baselines from the EfficientNet (EN) family [57], EN-Bi, $i \in 0, 1, ..., 4$. We use the same EN models as the feature extraction module of TNet, getting TNet-Bi. All TNet models have base resolution of 224×224 px, attention grid of 5×5, and each grid cell dimension occupies 35% of the corresponding image dimension. Processing extends to 2 levels. For TNet models, we introduce a new *feature weighting module*, which calculates weights to perform a weighted average of the extracted features before the final prediction. More details are provided in the Appendix.

Training. EN baselines and the feature extraction modules of TNet models are initialized with weights pre-trained on ImageNet [59]. The rest of TNet modules are randomly initialized. All models are fine-tuned on the downstream tasks. Training details are provided in the Appendix.

Results. We summarize our results in Figure 3. For clarity, we limit the number of models we plot, and we provide detailed results in the Appendix. We see that performance differences between baselines, translate to similar differences between TNet models with corresponding backbones, e.g., EN-B4 and TNet-B4 achieve considerably better accuracy compared to EN-B0 and TNet-B0 respectively. In addition, as attended locations increase, TNet models achieve similar or better accuracy compared to corresponding baselines (TNet-B4 is also competitive to strong baseline API-Net [75] and state-of-the-art TransFG [23]; see Appendix). This indicates that initialization with pre-trained weights allows TNet to learn useful weights for all modules.

5.4 Attention policy and interpretability

To examine the relative importance between the coarse context and the information from the attended locations, we evaluate TNet on ImageNet, by using features only from attended locations. With 2, 3 and 5 attended locations, TNet achieves top-1 accuracy 67.95%, 69.66% and 71.05% respectively (with contextual information included, the corresponding accuracy values are 74.12%, 74.41% and 74.62%). The Saccader achieves similar accuracy for 2, 4 and 8 locations, with 67.8%, 69.51% and 70.08%. This shows that features extracted from attended locations have discriminative value even without global context. As a result, the attention policy can be valuable for interpreting predictions.

We show examples of attended locations in Fig. 1 (c) and Fig. 4; more examples from all datasets are provided in the Appendix. On ImageNet, the learned policy is highly content dependent and informative as it overlaps with intuitively meaningful regions. The same behavior is observed in CUB-200-2011 and NABirds datasets, where the weights estimated by *feature weighting module* have significant contribution to the interpretability of the predictions. On fMoW, our model predominantly

Figure 4: Examples of attention policy learned on CUB-200-2011. Numeric annotations correspond to weights predicted by *feature weighting module* for the top 3 locations and the downscaled version of the whole image (1st processing level). Weights sum up to 1.

attends to locations at the center, where nearly all objects of interest are located. While this is a correct heuristic implied by the data, it leads to a biased attention policy that is not sensitive to content changes. This demonstrates that sufficient diversity is needed to train fully informative policies.

Hard-attention is also used for reduction of high-resolution data acquisition cost [60]. On fMoW, when our model attends to 4 locations in 3 processing levels, it covers 37.91% of the input in resolution of 448×448 px, and less than 12.5% in the highest resolution of 896×896 px.

5.5 Ablation study

We examine the effect of per-feature regularization by training TNet on ImageNet without it. With 1 attended location, top-1 accuracy drops from 73.12% (Table 1) to 65.21%, while with 3 and 5 locations, accuracy drops from 74.41% and 74.62%, to 67.33% and 68.55% respectively. The drop is substantial, placing TNet below both Saccader and BagNet-77 in terms of accuracy.

Per-feature regularization may have similar impact as cropping-based data augmentation, since it forces the model to make independent predictions with features from every attended location. However, the attention policy is not random, but learned, which is crucial for the quality of the crops. In addition, we don't get one image crop per epoch, but multiple crops in the same training iteration. We hypothesize that this is important to prevent feature co-adaptation, since the model learns to recognize the same object from multiple crops simultaneously.

6 Conclusion

We proposed a novel multi-scale hard-attention architecture, TNet, that can efficiently scale to images of high resolution. By controlling the number of attended locations, the method can adjust the accuracy-computation trade-off dynamically. We demonstrated the efficacy of our method on ImageNet against strong hard-attention baselines, and we further verified its behavior with high-resolution satellite images (fMoW). The attention policy reveals the image regions deemed more informative by our model, and makes its predictions inherently interpretable.

There are multiple research directions that can address current limitations of our method. First, we would like the decision on the number of attended locations to stem from a content-dependent learned policy. In addition, we would like scale-space traversal to be bi-directional, instead of merely top-down, in order for processing to be more adaptive. To the same end, we would like already extracted features to condition the processing of subsequent locations.

On the broader impact of our approach, we hypothesize that under a number of assumptions, hard-attention has the potential to be useful to any intelligent agent that navigates through the immense complexity of the natural visual world. These assumptions are that (1) the available resources are limited (2) there are performance constraints e.g. maximum response time, (3) the available information is practically infinite (4) all bits of information are not equally useful, and can even be misleading, e.g. noise. In this context, it would be beneficial for an intelligent agent to prioritize the expenditure of its resources according to the utility of the available information, in order to reach its performance goals; this is what a learned hard-attention mechanism can facilitate.

References

[1] Marco Ancona, Enea Ceolini, Cengiz Öztireli, and Markus Gross. Towards better understanding of gradient-based attribution methods for deep neural networks. In *International Conference on Learning Representations*, 2018.

[2] Jimmy Ba, Volodymyr Mnih, and Koray Kavukcuoglu. Multiple object recognition with visual attention. *arXiv preprint arXiv:1412.7755*, 2014.

[3] Jimmy Ba, Geoffrey E Hinton, Volodymyr Mnih, Joel Z Leibo, and Catalin Ionescu. Using fast weights to attend to the recent past. In *Advances in Neural Information Processing Systems*, pages 4331–4339, 2016.

[4] Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

[5] Irwan Bello. Lambdanetworks: Modeling long-range interactions without attention. *arXiv preprint arXiv:2102.08602*, 2021.

[6] Irwan Bello, Barret Zoph, Ashish Vaswani, Jonathon Shlens, and Quoc V Le. Attention augmented convolutional networks. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3286–3295, 2019.

[7] Wieland Brendel and Matthias Bethge. Approximating cnns with bag-of-local-features models works surprisingly well on imagenet. *arXiv preprint arXiv:1904.00760*, 2019.

[8] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European Conference on Computer Vision*, pages 213–229. Springer, 2020.

[9] Liang-Chieh Chen, George Papandreou, Florian Schroff, and Hartwig Adam. Rethinking atrous convolution for semantic image segmentation. *arXiv preprint arXiv:1706.05587*, 2017.

[10] Liang-Chieh Chen, George Papandreou, Iasonas Kokkinos, Kevin Murphy, and Alan L Yuille. Deeplab: Semantic image segmentation with deep convolutional nets, atrous convolution, and fully connected crfs. *IEEE transactions on pattern analysis and machine intelligence*, 40(4): 834–848, 2018.

[11] Yunpeng Chen, Yannis Kalantidis, Jianshu Li, Shuicheng Yan, and Jiashi Feng. A^2-nets: Double attention networks. *arXiv preprint arXiv:1810.11579*, 2018.

[12] Gordon Christie, Neil Fendley, James Wilson, and Ryan Mukherjee. Functional map of the world. In *CVPR*, 2018.

[13] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pages 248–255. Ieee, 2009.

[14] Misha Denil, Loris Bazzani, Hugo Larochelle, and Nando de Freitas. Learning where to attend with deep architectures for image tracking. *Neural computation*, 24(8):2151–2184, 2012.

[15] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[16] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[17] David Eigen, Christian Puhrsch, and Rob Fergus. Depth map prediction from a single image using a multi-scale deep network. In *Advances in neural information processing systems*, pages 2366–2374, 2014.

[18] Gamaleldin F Elsayed, Simon Kornblith, and Quoc V Le. Saccader: improving accuracy of hard attention models for vision. *arXiv preprint arXiv:1908.07644*, 2019.

[19] SM Ali Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, David Szepesvari, Geoffrey E Hinton, et al. Attend, infer, repeat: Fast scene understanding with generative models. In *Advances in Neural Information Processing Systems*, pages 3225–3233, 2016.

[20] Michael Figurnov, Maxwell D Collins, Yukun Zhu, Li Zhang, Jonathan Huang, Dmitry Vetrov, and Ruslan Salakhutdinov. Spatially adaptive computation time for residual networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1039–1048, 2017.

[21] google research. *GitHub repository that contains the official Saccader and DRAM implementations*, 2019. URL https://github.com/google-research/google-research/tree/master/saccader.

[22] Karol Gregor, Ivo Danihelka, Alex Graves, Danilo Rezende, and Daan Wierstra. Draw: A recurrent neural network for image generation. In *International Conference on Machine Learning*, pages 1462–1471, 2015.

[23] Ju He, Jie-Neng Chen, Shuai Liu, Adam Kortylewski, Cheng Yang, Yutong Bai, Changhu Wang, and Alan Yuille. Transfg: A transformer architecture for fine-grained recognition. *arXiv preprint arXiv:2103.07976*, 2021.

[24] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Spatial pyramid pooling in deep convolutional networks for visual recognition. In *European conference on computer vision*, pages 346–361. Springer, 2014.

[25] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778, 2016.

[26] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[27] Andrew G Howard, Menglong Zhu, Bo Chen, Dmitry Kalenichenko, Weijun Wang, Tobias Weyand, Marco Andreetto, and Hartwig Adam. Mobilenets: Efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861*, 2017.

[28] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7132–7141, 2018.

[29] Gao Huang, Danlu Chen, Tianhong Li, Felix Wu, Laurens van der Maaten, and Kilian Q Weinberger. Multi-scale dense networks for resource efficient image classification. *arXiv preprint arXiv:1703.09844*, 2017.

[30] Forrest N Iandola, Song Han, Matthew W Moskewicz, Khalid Ashraf, William J Dally, and Kurt Keutzer. Squeezenet: Alexnet-level accuracy with 50x fewer parameters and< 0.5 mb model size. *arXiv preprint arXiv:1602.07360*, 2016.

[31] Laurent Itti, Christof Koch, and Ernst Niebur. A model of saliency-based visual attention for rapid scene analysis. *IEEE Transactions on pattern analysis and machine intelligence*, 20(11): 1254–1259, 1998.

[32] Max Jaderberg, Andrea Vedaldi, and Andrew Zisserman. Speeding up convolutional neural networks with low rank expansions. *arXiv preprint arXiv:1405.3866*, 2014.

[33] Angelos Katharopoulos and François Fleuret. Processing megapixel images with deep attention-sampling models. *arXiv preprint arXiv:1905.03711*, 2019.

[34] Tsung-Wei Ke, Michael Maire, and Stella X Yu. Multigrid neural architectures. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 6665–6673, 2017.

[35] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[36] Hugo Larochelle and Geoffrey E Hinton. Learning to combine foveal glimpses with a third-order boltzmann machine. In *Advances in neural information processing systems*, pages 1243–1251, 2010.

[37] Gustav Larsson, Michael Maire, and Gregory Shakhnarovich. Fractalnet: Ultra-deep neural networks without residuals. *arXiv preprint arXiv:1605.07648*, 2016.

[38] Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pages 598–605, 1990.

[39] Hila Levi and Shimon Ullman. Efficient coarse-to-fine non-local module for the detection of small objects. *arXiv preprint arXiv:1811.12152*, 2018.

[40] Tsung-Yi Lin, Piotr Dollár, Ross B Girshick, Kaiming He, Bharath Hariharan, and Serge J Belongie. Feature pyramid networks for object detection. In *CVPR*, volume 1, page 4, 2017.

[41] Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *European conference on computer vision*, pages 21–37. Springer, 2016.

[42] Francesco Marra, Diego Gragnaniello, Luisa Verdoliva, and Giovanni Poggi. A full-image full-resolution end-to-end-trainable cnn framework for image forgery detection. *IEEE Access*, 8:133488–133502, 2020.

[43] Volodymyr Mnih, Nicolas Heess, Alex Graves, et al. Recurrent models of visual attention. In *Advances in neural information processing systems*, pages 2204–2212, 2014.

[44] Mahyar Najibi, Bharat Singh, and Larry S Davis. Autofocus: Efficient multi-scale inference. *arXiv preprint arXiv:1812.01600*, 2018.

[45] Niki Parmar, Ashish Vaswani, Jakob Uszkoreit, Lukasz Kaiser, Noam Shazeer, Alexander Ku, and Dustin Tran. Image transformer. In *International Conference on Machine Learning*, pages 4055–4064. PMLR, 2018.

[46] Hans Pinckaers, Bram van Ginneken, and Geert Litjens. Streaming convolutional neural networks for end-to-end learning with multi-megapixel images. *arXiv preprint arXiv:1911.04432*, 2019.

[47] Pedro HO Pinheiro and Ronan Collobert. Recurrent convolutional neural networks for scene labeling. In *31st International Conference on Machine Learning (ICML)*, number EPFL-CONF-199822, 2014.

[48] Prajit Ramachandran, Niki Parmar, Ashish Vaswani, Irwan Bello, Anselm Levskaya, and Jonathon Shlens. Stand-alone self-attention in vision models. *arXiv preprint arXiv:1906.05909*, 2019.

[49] Jason Ramapuram, Maurits Diephuis, Russ Webb, and Alexandros Kalousis. Variational saccading: Efficient inference for large resolution images. *arXiv preprint arXiv:1812.03170*, 2018.

[50] Marc'Aurelio Ranzato. On learning where to look. *arXiv preprint arXiv:1405.5488*, 2014.

[51] Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks. In *European Conference on Computer Vision*, pages 525–542. Springer, 2016.

[52] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[53] Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE international conference on computer vision*, pages 618–626, 2017.

[54] Pierre Sermanet, Andrea Frome, and Esteban Real. Attention for fine-grained categorization. *arXiv preprint arXiv:1412.7054*, 2014.

[55] Yiqiu Shen, Nan Wu, Jason Phang, Jungkyu Park, Kangning Liu, Sudarshini Tyagi, Laura Heacock, S Gene Kim, Linda Moy, Kyunghyun Cho, et al. An interpretable classifier for high-resolution breast cancer screening images utilizing weakly supervised localization. *Medical Image Analysis*, page 101908, 2020.

[56] Yiqiu Shen, Nan Wu, Jason Phang, Jungkyu Park, Kangning Liu, Sudarshini Tyagi, Laura Heacock, S Gene Kim, Linda Moy, Kyunghyun Cho, et al. An interpretable classifier for high-resolution breast cancer screening images utilizing weakly supervised localization. *Medical image analysis*, 68:101908, 2021.

[57] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *International Conference on Machine Learning*, pages 6105–6114. PMLR, 2019.

[58] Mingxing Tan and Quoc V Le. Efficientnetv2: Smaller models and faster training. *arXiv preprint arXiv:2104.00298*, 2021.

[59] tensorflow. *GitHub repository that contains the official EfficientnNet implementation*, 2021. URL `https://github.com/tensorflow/tpu/tree/master/models/official/efficientnet`.

[60] Burak Uzkent and Stefano Ermon. Learning when and where to zoom with deep reinforcement learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 12345–12354, 2020.

[61] Burak Uzkent, Evan Sheehan, Chenlin Meng, Zhongyi Tang, Marshall Burke, David Lobell, and Stefano Ermon. Learning to interpret satellite images in global scale using wikipedia. *arXiv preprint arXiv:1905.02506*, 2019.

[62] Grant Van Horn, Steve Branson, Ryan Farrell, Scott Haber, Jessie Barry, Panos Ipeirotis, Pietro Perona, and Serge Belongie. Building a bird recognition app and large scale dataset with citizen scientists: The fine print in fine-grained dataset collection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 595–604, 2015.

[63] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *arXiv preprint arXiv:1706.03762*, 2017.

[64] Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. 2011.

[65] Huiyu Wang, Aniruddha Kembhavi, Ali Farhadi, Alan L Yuille, and Mohammad Rastegari. Elastic: Improving cnns with dynamic scaling policies. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2258–2267, 2019.

[66] Min Wang, Baoyuan Liu, and Hassan Foroosh. Factorized convolutional neural networks. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 545–553, 2017.

[67] Xiaolong Wang, Ross Girshick, Abhinav Gupta, and Kaiming He. Non-local neural networks. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 7794–7803, 2018.

[68] Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3-4):229–256, 1992.

[69] Zuxuan Wu, Tushar Nagarajan, Abhishek Kumar, Steven Rennie, Larry S Davis, Kristen Grauman, and Rogerio Feris. Blockdrop: Dynamic inference paths in residual networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 8817–8826, 2018.

[70] Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron Courville, Ruslan Salakhudinov, Rich Zemel, and Yoshua Bengio. Show, attend and tell: Neural image caption generation with visual attention. In *International conference on machine learning*, pages 2048–2057, 2015.

[71] Fisher Yu and Vladlen Koltun. Multi-scale context aggregation by dilated convolutions. *arXiv preprint arXiv:1511.07122*, 2015.

[72] Ruichi Yu, Ang Li, Chun-Fu Chen, Jui-Hsin Lai, Vlad I Morariu, Xintong Han, Mingfei Gao, Ching-Yung Lin, and Larry S Davis. Nisp: Pruning networks using neuron importance score propagation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 9194–9203, 2018.

[73] Amir R Zamir, Te-Lin Wu, Lin Sun, William B Shen, Bertram E Shi, Jitendra Malik, and Silvio Savarese. Feedback networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 1308–1317, 2017.

[74] Hengshuang Zhao, Jiaya Jia, and Vladlen Koltun. Exploring self-attention for image recognition. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10076–10085, 2020.

[75] Peiqin Zhuang, Yali Wang, and Yu Qiao. Learning attentive pairwise interaction for fine-grained classification. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 13130–13137, 2020.