Probing structural constraints of negation in Pretrained Language Models

Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymouser Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Anonymousest Author
Affiliation / Address line 1
Affiliation / Address line 2
Affiliation / Address line 3
email@domain

Abstract

Contradictory results about the encoding of the semantic impact of negation in pretrained language models (PLMs) have been drawn recently (e.g. Kassner and Schütze (2020); Gubelmann and Handschuh (2022)).

In this paper we focus rather on the way PLMs encode negation and its formal impact, through the phenomenon of the Negative Polarity Item (NPI) licensing in English. More precisely, we use probes to identify which contextual representations best encode 1) the presence of negation in a sentence, and 2) the polarity of a neighboring masked polarity item.

We find that contextual representations of tokens inside the negation scope do allow for (i) a better prediction of the presence of *not* compared to those outside the scope and (ii) a better prediction of the right polarity of a masked polarity item licensed by *not*, although the magnitude of the difference varies from PLM to PLM. Importantly, in both cases the trend holds even when controlling for distance to *not*.

We thus confirm that the embeddings of these models do reflect the notion of negation scope, and do encode the impact of negation on NPI licensing. The subtle difference between licensing scope and negation scope, however, does not seem to be captured.

1 Introduction

Negation has recently been the focus of various works aiming at determining the abilities of Pretrained Language Models (PLMs) to capture linguistic knowledge.

Some works investigate the 'semantic impact' of negation, namely its impact in terms of truth values, by interpreting how the presence of negation impacts the probability distribution at a masked position. The rationale is that negating a verb reverses the truth value of its clause, which should be reflected in the probability distribution at certain positions. Ettinger (2020); Kassner and Schütze (2020) use factual statements such as (1), and report that models output similar distributions for the positive and negative variants of (1), and conclude that models largely ignore negation.

(1)   *A robin is (not) a [MASK]*

Gubelmann and Handschuh (2022) chose to avoid factual statements and focus rather on multi-sentence self-contained examples, such that, given the context provided by the first sentence, one particular word is either likely (in positive items) or ruled out (in negative items) at a masked position in the second sentence. Because this particular word is substantially less often the top-1 prediction in the negative items than in the positive items, the authors draw the opposite conclusion that PLMs do show sensitivity to negation.

A different line of works focused on finding out to what extent negation is encoded in PLM embeddings. Celikkanat et al. (2020) train classifiers taking as input the contextual embedding of a verb or its subject or direct object, and predicting whether the verb is negated or not. The resulting high accuracy allows them to conclude that these tokens' embeddings do contain "traces" of *not*. More generally, several authors have investigated whether the contextual representation of a token encodes information about surrounding tokens. To ease further reading, we will talk of a classifier taking as input an **input embedding**, namely the contextual representation of an **input token**, and predicting some **target information** about another token

in the sentence. For instance, Klafka and Ettinger (2020) study how input embeddings encode animacy, gender, and number of surrounding words in a specific SVO context. Li et al. (2022) target the number feature of French participles in the context of object-past participle agreement. They show that the performance of the classifier depends on the syntactic position of the input token in the sentence. We will build on their idea to compare performance at predicting target information depending on the syntactic zone the input token belongs to.

In this paper, we focus on how the information about negation encoded in contextual embeddings is used. Our aim is to study PLMs' ability to capture and encode structural information concerning negation (namely negation scope), and also their ability to actually *mobilize* the encoding in order to capture phenomena that are direct consequences of the presence of negation. To do so, we focus on the licensing of Negative Polarity Items (NPI) by *not* modifying a verb. Polarity Items (PI), either positive (e.g. *some*), or negative (e.g. *any*), are words or expressions that are constrained in their distribution (Homer, 2020). A NPI will require that a word or a construction, called the **licensor**, be in the vicinity. And the licensor itself grammatically defines a zone of the sentence, called the **licensing scope**, in which the NPI can appear. The adverb *not* modifying a verb is one such licensor. While *any* is licensed by negation in (2-a) *vs.* (2-b), it is not licensed in (2-c), even though the verb is negated, arguably because it is not in the licensing scope[1].

(2) a. Sam didn't find any books.
     b. *Sam found any books.

Jumelet and Hupkes (2018) have shown that LSTM embeddings do encode the notion of licensing scope (given an input embedding, a classifier can predict the structural zone the input token belongs to), a finding later confirmed for transformer-based PLMs (Warstadt et al., 2019). Focusing on when the licensor is a verb-modifying *not*, we rather investigate whether this demonstrated encoding of the zones *go as far as* enabling a better prediction of a PI's polarity from *inside* the licensing scope compared to *outside* the scope. So instead of the question *"Is this input embed-*

ding the embedding of a token that is within, before or after the licensing scope?", we rather ask the question *"Given a masked PI position, and an input embedding of a neighboring token, what is the polarity of the PI?"*, and we study whether this question is better answered when the input embedding is inside or outside the licensing or negation scopes.

Note that our methodology differs from that of Jumelet and Hupkes (2018), who, given an input token, predict the zone this token belongs to. We instead predict the polarity of a neighboring masked polarity item and then compare accuracies depending on the input token's zone. Our motivation is that the polarity, being a lexical information, requires less linguistic preconception, and hence our probing method is a more direct translation of the NPI licensing phenomenon: we study whether and where the information of "*which PIs are licit where?*" is encoded, in the context of sentence negation. This method also allows us to better control the confounding factor of distance between the input embedding and the licensor *not*.

In the following we start in section 2 by defining the linguistic notions of negation scope and NPI licensing scope, and by showing how we actually identified them in English sentences. In section 3, we define our probing experiments and discuss their results, both for the encoding of *not* (section 3.1), and the encoding of NPI licensing (section 3.2). We conclude in section 4.

2 Defining and identifying scopes

2.1 Negation scope

From a linguistic point of view, the scope of a negation cue is the area of the sentence whose propositional content's truth value is reversed by the presence of the cue. While in many cases it is sufficient to use the syntactic structure to recover the scope, in some cases semantics or even pragmatics come into play[2]. Nevertheless, annotation guidelines usually offer syntactic approximations of negation scope.

To identify the negation scope for a *not*[3] modifying a verb, we followed the syntactic constraints that emerge from the guidelines of Morante and Blanco (2012). Note though that these guide-

---

[1] We leave aside the uses of *any* and the like having *free choice* interpretations, as for instance in *"Pick any card"*.

[2] For instance in *Kim did not go to the party because Bob was there.*, negation may scope only over the matrix clause or include the causal subordinate clause.

[3] In all this article, *not* stands for either *not* or *n't*.

Id	Pattern	Example and zones
1/2	(VP (VB*/MD) (RB not) VP)	I have my taxi and I 'm not going anywhere but my brother will leave Spain because he has a degree.
3	(VP (VB*) (RB not) NP/PP/ADJP)	Since it is kind of this fairy-tale land, there aren't any rules of logic so you can do anything, she says.
5*	(S (RB not) VP)	I went in early, not wanting anyone to see me and hoping for no line at the counter.

Table 1: The "**neg-patterns**": patterns adapted from Jumelet and Hupkes (2018), which we used to identify some cases of *not* licensing a NPI and to build the *not*+NPI test set. **Col1**: pattern id in Jumelet and Hupkes (2018). **Col2**: syntactic pattern (defined as a phrase-structure subtree, using the Penn Treebank's annotation scheme), with the licensing scope appearing in blue. **Col3**: examples with colors for the four zones: pink for tokens in the PRE zone (before both scopes), purple for PRE-IN (to the left of the licensing scope, but within the negation scope), blue for IN (within both scopes) and green for POST (after both scopes). The NPI licensor is *not*, and appears in yellow.

lines restrict the annotation to factual eventualities, leaving aside e.g. negated future verbs. We did not retain such a restriction, hence our identification of the negation scope is independent from verb tense or modality.

2.2 NPI licensing scope

Polarity items are a notoriously complex phenomenon. To identify the NPI licensing scope, we focus on specific syntactic patterns defined by Jumelet and Hupkes (2018), retaining only those involving *not* as licensor.[4] Table 1 shows an example for each retained pattern (hereafter the **neg-patterns**), with the NPI licensing scope in blue.

Importantly, in the neg-patterns, the licensing scope is strictly included in the negation scope: within the clause of the negated verb, the tokens to its left belong to the negation scope but not to the licensing scope. E.g. in (3), *anyone* is not licit as a subject of *going*, whether the location argument is itself a plain PP, a NPI or a PPI (3-b).

(3) a. I'm not going anywhere.
     b. *Anyone is not going to the party/ somewhere/anywhere.

We thus defined 4 zones for the *not*+NPI sentences, exemplified in Table 1: **PRE** (tokens before both scopes), **PRE-IN** (to the left of the licensing scope, but within the negation scope), **IN** (in both scopes), and **POST** (after both scopes).

We note though that the restriction exemplified in (3-b) only holds for non-embedded NPIs (de Swart, 1998), so examples like (4), with an embedded NPI in the subject of the negated verb

(hence belonging to our **PRE-IN** zone), are theoretically possible.

(4) Examples with any relevance to that issue didn't come up in the discussion.

Yet in practice, we found that they are extremely rare: using the Corpus of Contemporary American English (COCA, Davies 2015)[5], we extracted sentences matching one of the neg-patterns, and among these, sentences having *any* or *any-body/one/thing/time/where* in the IN zone, the PRE-IN zone or both. As shown in Table 2, *any** in the PRE-IN zone are way rarer than in the classical licensing scope (IN zone)[6]. Hence we sticked to the usual notion of direct NPI licensing scope, as illustrated in Table 1.

Total	IN	PRE-IN	both
45,157	35,938	711	58

Table 2: Number of sentences from the COCA corpus, matching the neg-patterns of Table 1: **Col1**: total number, **Col2-4**: number having a *any** in the IN zone, the PRE-IN zone, and in both zones respectively.

---

[4]We ignored pattern 4 (*never* instead of *not* as licensor), and 6 (too few occurrences in our data). We merged patterns 1 and 2, and corrected an obvious minor error in pattern 5.

[5]We used a version with texts from 1990 to 2012. COCA is distributed with some tokens in some sentences voluntarily masked, varying across distributions. We ignored such sentences.

[6]More precisely, the figures in Table 2 correspond to an upper bound, because of (i) potential syntactic parsing errors impacting the identification of the zones, (ii) cases in which the NPI licensor is different from the *not* targeted by the patterns, and (iii) cases in which the *any** is a free choice item and not a NPI (as in "*Pick any one*"). We inspected 250 examples of *any** in the PRE-IN zone, and 250 examples in the IN zone. In the former, we found that almost all cases fall under (i), (ii) or (iii), less than 3% corresponding to examples such as (4). In contrast, in the IN zone the proportion of NPIs actually licensed by the target *not* is 92%.

2.3 Building the not+NPI test set

Having defined these structural zones, we can use them to probe the traces they carry and compare the magnitude of these traces across the four zones. To do so, we built a test set of COCA sentences containing a *not* licensing a NPI (hereafter the ***not*+NPI** test set), matching one of the neg-patterns of Table 1, and having at least one *any, anybody, anyone, anything, anytime* or *anywhere* within the licensing scope.

The scope of negation has been implemented through an approximation using dependency parses (from the Stanza parser (Qi et al., 2020)), which proved more convenient than phrase-structure parses: we took the subtree of the negated verb, excluding *not* itself, and excluding dependents corresponding to sentential or verbal conjuncts and to sentential parentheticals.

More precisely, we identified the token having *not* as dependent (which, given our patterns, can be either the negated verb or a predicative adjective in case of a negated copula). Then, we retrieved the children of this head, except those attached to it with a "conj", "parataxis", "mark" or "discourse" dependency. In the complete subtrees of the selected dependents, all tokens were annotated as being inside the negation scope.

Genre	Mag	Acad	Fict	News	Total
# with *not*	537	383	830	536	2285
# and a NPI	31	21	58	34	143

Table 3: Thousands of sentences in COCA: Line 1: containing a *not*. Line 2: containing a *not* and at least one NPI (among *any-∅/body/one/where/time/thing*), anywhere in the sentence.

For the licensing scope, we parsed the corpus using the PTB-style parser "Supar Parser"[7] of Zhang et al. (2020), and further retained only the sentences (i) matching the neg-patterns of Table 1 and (ii) having a NPI within the licensing scope (IN zone, shown in blue in Table 1).

We finally obtained a *not*+NPI test set, whose statistics are provided in Table 4.

3 Probing for the scopes

Our objective is to study how a transformer-based PLM (i) encodes the presence of a negation

Pattern	Mag	Acad	Fict	News	Total
1/2	6.56	1.69	16.49	6.16	30.90
3	0.57	0.14	1.33	0.49	2.53
*5**	0.22	0.08	0.58	0.15	1.02

Table 4: Statistics of the *not*+NPI test set: thousands of COCA sentences matching the neg-patterns (cf. Table 1), and having at least one *any** in the IN zone (licensing scope), broken down by corpus genre.

(the "traces" of negation) and (ii) models lexico-syntactic constraints imposed by negation, such as the modeling of a NPI licensing scope. Using the terminology introduced in section 1, we will probe whether input embeddings encode as target information (i) the presence of *not* elsewhere in the sentence, and (ii) the polarity of a masked PI. The former focuses on a plain encoding of negation, whereas the latter focuses on whether the encoding of negation can be mobilized to reflect a property (NPI licensing) that is directly imposed by negation. To investigate whether such an encoding matches linguistic notions of scopes, we will contrast results depending on the zone the input token belongs to (among the four zones defined for a *not* licensing a NPI, namely PRE, PRE-IN, IN, POST) and its distance to *not*.

We study four PLMs: BERT-base-case, BERT-large-case (Devlin et al., 2019) and ROBERTA-base and ROBERTA-large (Liu et al., 2019). All our experiments were done with each of these models, and for a given model, each experiment was repeated three times. All the sentences we used for training, tuning and testing were extracted from the COCA corpus.

3.1 Probing for the negation scope

In preliminary experiments, we extend Celikkanat et al. (2020)'s study by investigating the traces of *not* in the contextual embedding of all the tokens of a sentence containing *not* (instead of just the verb, subject and object).

3.1.1 Training neg-classifiers

We train binary classifiers (hereafter the **m-neg-classifiers**, with *m* the name of the studied PLM) taking an input contextual embedding, and predicting the presence or absence of at least one *not* in the sentence. We train 3 classifiers for each of the 4 tested PLMs. To train and evalu-

---

[7] https://parser.yzhang.site/en/latest/index.html

ate these classifiers, we randomly extract 40,000 sentences containing exactly one *not*, and 40,000 sentences not containing any *not*. We BERT- and ROBERTA-tokenized these sentences and for each model, we randomly selected one PLM token in each sentence to serve as input token. For these input tokens, we ignored any token *not*, plus all PLM tokens associated to a contracted negation: for instance *don't* is BERT-tokenized into *don + ' + t*, and ROBERTA-tokenized into *don' + t*. We ignore all these tokens, as they are too obvious a clue for the presence of a verbal negation. Furthermore, in order to homogenize the handling of negation whether contracted or not, we also set aside any modal or auxiliary that can form a negated contracted form. Hence, in *She did leave*, *She did not leave* or *She didn't leave*, the only candidate input tokens are those for *She* and *leave*[8]. We use 64k sentences for training (**neg-train-sets**), and the remaining 16k for testing (**neg-test-set**).

We provide the obtained accuracies on this neg-test-set in Table 5, which shows that performance is significantly above chance.

Model	BERT$_b$	BERT$_l$	ROB.$_b$	ROB.$_l$
Accur.	74.3	73.1	72.1	76.6

Table 5: Accuracies of the neg-classifiers on the neg-test-set for each PLM (averaged over 3 runs).

3.1.2 Studying results on the *not*+NPI test set

To probe the negation scope, we then use the *not*+NPI test set (cf. section 2), and compare accuracies in PRE-IN versus PRE, and in IN versus POST.

Note though that distance to *not* is also likely to impact the classifiers' accuracy. Indeed, by definition the structural zones obviously correlate with distance to *not*. For instance, a token at distance 3 to the right of *not* is more likely to be in the licensing scope than a token at distance 20. Hence, to study the impact of the input token's zone, we need to control for distance to the negation clue.

We thus break down our classifiers' accuracy on the *not*+NPI test set, not only according to the input token's zone, but also according to its relative position to the negation cue. Table 6 shows an example of *not*+NPI sentence, and the zone and

---

[8]COCA sentences are tokenized and tagged. We detokenized them before BERT/ROBERTA tokenization, in order to get closer to a standard input.

relative position to *not* of each token. The target *not* has position 0, and so do all the PLMs' sub-word tokens involved in the negation complex, and all preceding modal or auxiliary, to homogenize across PLMs and across contracted/plain negation. By construction, the PRE and PRE-IN zones correspond to negative positions, whereas IN and POST correspond to positive ones.

The break-down by position for ROBERTA-large is shown in Figure 1 (results for other models are in Appendix C). Two effects can be observed, for all the 4 PLMs: firstly, there is a general decrease of the accuracy as moving away from *not*, for the four zones. This contrasts with the findings of Klafka and Ettinger (2020), who did not observe a distance effect in their experiments, when probing whether the contextual representation of e.g. a direct object encodes e.g. the animacy of the subject. The decrease is more rapid before *not* than after it, which remains to be explained. It might come from the negation scope being shorter before *not* than after it.

Secondly, when looking at fixed relative distances, there is a slight but almost systematic effect that when the input token is in the negation scope (either PRE-IN or IN), the accuracy is higher than when it is outside (PRE and POST) (the differences are statistically significant at $p < 0.001$, cf. Appendix B). This tendency is more marked for the PRE *vs.* PRE-IN distinction than for the POST *vs.* IN distinction.

This observation can be summarized by computing the average **accuracy gap**, namely the accuracy differences averaged across positions (the average of the purple minus pink bars, and of blue minus green bars in Figure 3), which provide an average difference when a token is within or outside the negation scope. The average accuracy gaps for the four tested models are given in Table 7. It confirms that input embeddings of tokens inside the negation scope do allow for a slightly better prediction of the presence of *not* than those outside the scope. Note that the average difference is stable across models, whose size does not seem to matter. It shows that the strength of the encoding of *not* in contextual representations matches the linguistic notion of negation scope.

BERT tokens	I	see	I	don	'	t	know	anyone	here	,	I	must	leave	.
Zones	PRE	PRE	PRE-IN	not	not	not	IN	IN	IN	IN	POST	POST	POST	POST
Distance	-3	-2	-1	0	0	0	1	2	3	4	5	6	7	8

ROBERTA tokens	I	see	I	don'	t	know	anyone	here	,	I	must	leave	.
Zones	PRE	PRE	PRE-IN	not	not	IN	IN	IN	IN	POST	POST	POST	POST
Distance	-3	-2	-1	0	0	1	2	3	4	5	6	7	8

Table 6: Example sentence from the *not*+NPI test set: structural zones and relative positions to *not*. Any auxiliary or modal preceding the target *not* has position 0 too, to homogenize contracted and plain negation, and BERT versus ROBERTA's tokenization.

Figure 1: Accuracy of the ROBERTA-large-neg-classifier (average on 3 runs) on the *not*+NPI test set, broken down by zone (colors of the bars) and by relative position to *not* (horizontal axis). Further distances are omitted for clarity. No licensing scope contains less than 2 tokens, hence positions 1 and 2 are always in the IN zone. The bar differences at each position and run are statistically significant at $p < 0.001$ (cf. Appendix B). Figures for the other 3 models are provided in Appendix C.

$BERT_b$	$BERT_l$	ROB_b	ROB_l
3.0 (0.6)	3.5 (0.2)	2.6 (0.2)	2.6 (1.3)

Table 7: Accuracy gaps for the neg-classifiers on the *not*+NPI test set, for each tested PLM, averaged over 14 relative positions and 3 runs (stdev within brackets).

We also observe that the biggest difference occurs at position -1. This corresponds mostly to a contrast between a finite *vs.* non-finite negated verb (neg-patterns 1/2/3 *vs.* neg-pattern 5 in Table 1), which seems well reflected in PLMs' embeddings.

3.2 Probing for the licensing scope

We then focused on whether this encoding of *not* can actually be **mobilized** to capture the licensing of a NPI. We built classifiers (hereafter the **m-pol-classifiers**, with *m* the name of the studied PLM), taking an input contextual embedding, and predicting as target information the polarity of a masked position, originally filled with a positive or negative PI. Importantly, the input embedding in the training set is randomly chosen in the sentence, and can correspond to a position that is or isn't linguistically related to the polarity of the PI (cf. figure 2). This avoids using linguistic preconceptions while building the classifiers.

We train on sentences originally having either a PPI or a NPI, which we mask before running each

Figure 2: Illustration of the training of the pol-classifiers.

studied PLM. More precisely, in each COCA sub-corpus (each genre), and for each of the 6 NPI/PPI pairs listed by Jumelet and Hupkes (2018)[9], we randomly took at most 2,000 sentences containing the NPI, and the same amount of sentences containing the corresponding PPI[10]. In each of these, we masked the PI, randomly selected one token per sentence to serve as input token (excluding the masked position) and split these into 63,529 examples for training (**pol-train-set**) and 15,883 for testing (**pol-test-set**).

Model	BERT$_b$	BERT$_l$	ROB.$_b$	ROB.$_l$
Accur.	64.2	63.7	56.6	68.6

Table 8: Accuracies of the pol-classifiers on the pol-test-set for each PLM (averaged over 3 runs).

Accuracies on the pol-test-set for each PLM are shown in Table 8. While still above chance, we observe that it doesn't exceed 69%, which is quite lower than the accuracies of the neg-classifiers (Table 5). This is not surprising since the task is more difficult. First, as stressed above, some of the training input tokens are independent, from the linguistic point of view, of the PI's polarity. Second, the cues for predicting the polarity are diverse. And third, in numerous contexts, both polarities are indeed possible, even though not equally likely. We did not control the training for this, on purpose not to introduce any additional bias in the data. We can thus interpret the pol-classifier's scores as how likely a given polarity is.

Next, we applied these classifiers on the **not+NPI** test set. The objective is to compare the classifiers' accuracy depending on the structural

---

[9] *(any/some)(∅/where/one/body/thing/time)*

[10] For *any/some(∅/one/thing)*, we took 2 × 2000 occurrences. For *any/some(body/time/where)*, less occurrences were available in some of the subcorpora. We took as many as possible, but keeping a strict balance between NPI and PPI sentences (between 2 × 169 and 2 × 958 depending on the corpus genre and on the NPI/PPI pair).

zone the input token belongs to. If PLMs have a notion of licensing scope, then the polarity prediction should be higher when using an input token from the IN zone.

3.2.1 Results

Once more, we control for distance of the input embedding to *not*. The break-down by position and structural zone for ROBERTA-large is provided in Figure 3 (results for other models are in Appendix C).

Again, we observe a general accuracy decrease as moving away from *not*, and this decrease is faster than for the previous experiment. We also note that the decrease is more rapid in the PRE-IN zone than in the IN zone (for instance at distance -4 in PRE-IN, the accuracy is less than 70%, whereas it is still above it at distance 8 in the IN zone). This tends to indicate that the traces of *not* are more *robust* in the licensing scope.

Secondly, as for the previous experiment, for each relative position, **when the input token is in the negation scope (either PRE-IN or IN), the accuracy is higher than when it is outside (PRE and POST)**. Even though we cannot exclude that the relatively high overall accuracies may be explained by the classifier catching some regularities of the sentences containing a NPI rather than a PPI (independently of the presence of *not*), it remains that for the *not*+NPI sentences, accuracy is higher when the input token is in the negation scope than outside it. Moreover, this trend is much more marked than for the previous experiment.

Thirdly, the amplitude of this observation depends on the model. We provide the accuracy gaps for each PLM in Table 9. We observe that the trend is marked for ROBERTA-large and BERT-base (gap of 8.7 and 7.4 accuracy points, actually much higher than the accuracy gaps for predicting the presence of *not*), but lower for ROBERTA-base and BERT-large.

BERT$_b$	BERT$_l$	ROB$_b$	ROB$_l$
7.4 (0.5)	3.1 (0.4)	1.4 (0.2)	8.7 (0.6)

Table 9: Accuracy gaps for the pol-classifiers on the *not*+NPI test set, averaged over 14 relative positions and 3 runs (stdev within brackets).

This leads us to conclude that (i) PLMs do encode structural constraints imposed by *not* (NPI licensing), but to varying degrees across the PLMs

Figure 3: Accuracy of the ROBERTA-large-pol-classifier (average on 3 runs) on the *not*+NPI test set, broken down by zone (colors of the bars) and by relative position to *not* (horizontal axis). Further distances are omitted for clarity. No licensing scope contains less than 2 tokens, hence positions 1 and 2 are always in the IN zone. The bar differences at each position and run are statistically significant at $p < 0.001$ (cf. Appendix B).

we tested, and (ii) that this encoding is stronger in the negation scope than outside it, independently of the distance to *not*. This only partially matches the linguistic expectation that the strongest zone should be the licensing scope rather than the entire negation scope.

4 Conclusion

In this paper, we studied the way negation and its scope are encoded in contextual representations of PLMs and to what extent this encoding is used to model NPI licensing.

Classifiers were trained to predict the presence of negation in a sentence from the contextual representation of a random token. We also trained classifiers to predict the polarity of a masked polar item from the contextual representation of a random token. A test set of sentences was designed with *not* licensing an NPI, inside which we identified the negation scope (roughly the clause), and the licensing scope (roughly the VP).

For these sentences, we found that the contextual embeddings of tokens within the scope of a negation allow a better prediction of the presence of *not*. These embedding also allow a better prediction of the (negative) polarity of a masked PI. These results hold even when controlling for the distance to *not*.

We conclude that the PLMs which were tested indeed encode a notion of negation scope in their contextual representations. We could not find however a consistent encoding of the narrower (and probably more difficult to define) notion of negative polarity licensing scope. Moreover, variation across PLMs remains to be explained through further studies.

References

Hande Celikkanat, Sami Virpioja, Jörg Tiedemann, and Marianna Apidianaki. 2020. Controlling the Imprint of Passivization and Negation in Contextualized Representations. In *Proceedings of the Third BlackboxNLP Workshop on Analyzing and Interpreting Neural Networks for NLP*, pages 136–148, Online. Association for Computational Linguistics.

Mark Davies. 2015. Corpus of Contemporary American English (COCA).

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Re-

ichart. 2018. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1383–1392, Melbourne, Australia. Association for Computational Linguistics.

Allyson Ettinger. 2020. What BERT Is Not: Lessons from a New Suite of Psycholinguistic Diagnostics for Language Models. *Transactions of the Association for Computational Linguistics*, 8:34–48.

Reto Gubelmann and Siegfried Handschuh. 2022. Context matters: A pragmatic study of PLMs' negation understanding. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4602–4621, Dublin, Ireland. Association for Computational Linguistics.

Vincent Homer. 2020. *Negative Polarity*, pages 1–39. John Wiley & Sons, Ltd.

Jaap Jumelet and Dieuwke Hupkes. 2018. Do Language Models Understand Anything? On the Ability of LSTMs to Understand Negative Polarity Items. In *Proceedings of the 2018 EMNLP Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pages 222–231, Brussels, Belgium. Association for Computational Linguistics.

Nora Kassner and Hinrich Schütze. 2020. Negated and Misprimed Probes for Pretrained Language Models: Birds Can Talk, But Cannot Fly. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 7811–7818, Online. Association for Computational Linguistics.

Josef Klafka and Allyson Ettinger. 2020. Spying on Your Neighbors: Fine-grained Probing of Contextual Embeddings for Information about Surrounding Words. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4801–4811, Online. Association for Computational Linguistics.

Bingzhi Li, Guillaume Wisniewski, and Benoit Crabbé. 2022. How distributed are distributed representations? an observation on the locality of syntactic information in verb agreement tasks. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 501–507, Dublin, Ireland. Association for Computational Linguistics.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. 2019. Roberta: A robustly optimized bert pretraining approach. arXiv.

Roser Morante and Eduardo Blanco. 2012. *SEM 2012 Shared Task: Resolving the Scope and Focus of Negation. In *SEM 2012: The First Joint Conference on Lexical and Computational Semantics – Volume 1: Proceedings of the main conference and the shared task, and Volume 2: Proceedings of the Sixth International Workshop on Semantic Evaluation (SemEval 2012)*, pages 265–274, Montréal, Canada. Association for Computational Linguistics.

Peng Qi, Yuhao Zhang, Yuhui Zhang, Jason Bolton, and Christopher D. Manning. 2020. Stanza: A Python natural language processing toolkit for many human languages. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: System Demonstrations*.

Henriëtte de Swart. 1998. Licensing of negative polarity items under inverse scope. *Lingua*, 105(3-4):175–200.

Alex Warstadt, Yu Cao, Ioana Grosu, Wei Peng, Hagen Blix, Yining Nie, Anna Alsop, Shikha Bordia, Haokun Liu, Alicia Parrish, Sheng-Fu Wang, Jason Phang, Anhad Mohananey, Phu Mon Htut, Paloma Jeretic, and Samuel R. Bowman. 2019. Investigating BERT's Knowledge of Language: Five Analysis Methods with NPIs. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 2877–2887, Hong Kong, China. Association for Computational Linguistics.

Yu Zhang, Houquan Zhou, and Zhenghua Li. 2020. Fast and Accurate Neural CRF Constituency Parsing. In *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence*, pages 4046–4053, Yokohama, Japan. International Joint Conferences on Artificial Intelligence Organization.

A Hyperparameter tuning for the neg-classifiers and the pol-classifiers

The PLMs' contextual representations were obtained using a GeForce RTX 2080 Ti GPU.

The neg-classifiers and the pol-classifiers were trained on a CPU, each training taking about 15 min each. Then, testing them on the *not*+NPI test set takes about 5 minutes.

To tune these classifiers, we performed a grid search with: a number of hidden layers included in [1, 2], number of units in each layer in [20, 50, 100 450, 1000], and the learning rate in [1, 0.1, 0.01, 0.001].

We selected a learning rate of 0.001, 2 hidden layers, with size 450 each, based on the accuracies on the neg-test-set and the pol-test-set. Except when the learning rate equaled 1, all hyperparameter combinations resulted in similar performance (less than 1 point of accuracy, in the results of figure 3).

The code and methodology was developed first using the BERT-base model, and then applied to

the other models. Including code and methodology development, we estimate that the experiments reported in this paper correspond to a total of 160 hours of GPU computing.

B   Statistical significance test

In this section we detail the test performed to assess the statistical significance of the accuracy differences illustrated in Figures 3 and 5.

For each of the four tested PLMs, and for each of 3 runs of classifier training,

- for each position from -8 to -1 relative to the *not*,

  - we compare the accuracy of the pol-classifier in the PRE-IN zone versus in the PRE zone (i.e. the difference between the purple bar with respect to the pink one).
  - namely, we test the statistical significance of the following positive difference : accuracy for tokens in PRE-IN zone minus accuracy for tokens in the PRE zone.

- for each position from 3 to 8,

  - we test the statistical significance of the following positive difference : accuracy for tokens in IN zone minus accuracy for tokens in the POST zone (i.e. the difference between the blue bar with respect to the green one)

Each test is an approximate Fisher-Pitman permutation test (with 5000 random permutations, performed using the script of Dror et al. (2018), https://github.com/rtmdrr/testSignificanceNLP.git), and all the differences listed above result as statistically significant at $p < 0.001$.

C   Accuracies of the classifiers on the *not*+NPI test set

The break-downs by position for the three models not presented in the main text (BERT-base, BERT-large and ROBERTA-base) are provided in Figures 4 (neg-classifiers) and 5 (pol-classifiers).

(a) BERT-base-cased

(b) BERT-large-cased

(c) ROBERTA-base

Figure 4: Accuracy (average on 3 runs) of the other neg-classifiers (BERT-base, BERT-large and ROBERTA-base) on the *not*+NPI test set, broken down by zone (colors of the bars) and by relative position to *not* (horizontal axis). Further distances are omitted for clarity. No licensing scope contains less than 2 tokens, hence positions 1 and 2 are always in the IN zone. The bar differences at each position and run are statistically significant at $p < 0.001$ (cf. Appendix B).

(a) BERT-base-cased

(b) BERT-large-cased

(c) ROBERTA-base

Figure 5: Accuracy (average on 3 runs) of the other pol-classifiers (BERT-base, BERT-large and ROBERTA-base) on the *not*+NPI test set, broken down by zone (colors of the bars) and by relative position to *not* (horizontal axis). Further distances are omitted for clarity. No licensing scope contains less than 2 tokens, hence positions 1 and 2 are always in the IN zone. The bar differences at each position and run are statistically significant at $p < 0.001$ (cf. Appendix B).