Rényi Differential Privacy of Propose-Test-Release and Applications to Private and Robust Machine Learning

Abstract

Propose-Test-Release (PTR) is a differential privacy framework that works with local sensitivity of functions, instead of their global sensitivity. This framework is typically used for releasing robust statistics such as median or trimmed mean in a differentially private manner. While PTR is a common framework introduced over a decade ago, using it in applications such as robust SGD where we need many adaptive robust queries is challenging. This is mainly due to the lack of Rényi Differential Privacy (RDP) analysis, an essential ingredient underlying the moments accountant approach for differentially private deep learning. In this work, we generalize the standard PTR and derive the first RDP bound for it. We show that our RDP bound for PTR yields tighter DP guarantees than the directly analyzed (ε, δ)-DP. We also derive the algorithm-specific privacy amplification bound of PTR under subsampling. We show that our bound is much tighter than the general upper bound and close to the lower bound. Our RDP bounds enable tighter privacy loss calculation for the composition of many adaptive runs of PTR. As an application of our analysis, we show that PTR and our theoretical results can be used to design differentially private variants for byzantine robust training algorithms that use robust statistics for gradients aggregation. We conduct experiments on the settings of label, feature, and gradient corruption across different datasets and architectures. We show that PTR-based private and robust training algorithm significantly improves the utility compared with the baseline.

1 Introduction

Privacy is a major concern for deploying machine learning (ML). In response, differential privacy (DP) [DMNS06] has become the de-facto measure of privacy. For a differentially private mechanism, the probability distribution of the mechanism's outputs on a dataset should be close to the distribution of its outputs on the same dataset with any single individual's data replaced. A general recipe for releasing the value of a function f on dataset S in a differentially private way is adding random noise to $f(S)$ (output perturbation), where noise magnitude should scale with f's global sensitivity.

However, it might be over-conservative to add noise scaled with global sensitivity. There is a line of research on whether we can do better (e.g., [NRS07, DL09, TS13, KNRS13]). Propose-Test-Release (PTR) [DL09] is a framework that improves the general recipe with the notion of *local sensitivity*. The main idea of PTR is as follows: instead of adding noise with respect to global sensitivity, we propose an amount of noise that is tolerable for many common queries. When we receive the actual query, we test (in a differentially private way) whether answering the query with the proposed amount of noise is enough for privacy. If the proposed noise is too small for limiting the privacy loss from the actual query, we may refuse to answer the query or respond with a larger noise. PTR works especially well for releasing robust statistics such as median or trimmed mean, as the robust statistics usually have small local sensitivity on most common inputs.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

While PTR is a basic framework that ages back to the early days after the introduction of DP, it has not been used for differentially private optimization before. DP-SGD [ACG+16] is the general backbone for differentially private deep learning and optimization. One major challenge of augmenting SGD with PTR and training DP models is the calculation of privacy parameters after a large number of adaptive compositions. Rényi differential privacy (RDP) and Moment Accountant [Mir17, ACG+16] enable us to calculate tighter privacy parameters for training DP models. Without the RDP bound of PTR, we need to calculate the privacy parameters using the advanced composition theorems [DR+14] that can lead to significantly looser privacy bounds. Besides, we also need the bound of *privacy amplification by subsampling* for PTR, which is the other important support for training DP models. It allows us to exploit the stochasticity of SGD for the interest of stronger privacy guarantees.

Technical Overview. In this work, we derive the Rényi DP bound for PTR, as well as for its Poisson subsampled variant. Our bounds make it possible for us to use PTR framework in augmenting private SGD. PTR could be characterized by three mechanisms. The first mechanism is $\mathcal{M}_1$ that determines which mechanism to run next. Depending on the outcome of $\mathcal{M}_1$ we then either run $\mathcal{M}_2$ or $\mathcal{M}_2'$. It is often the case that the worst-case privacy loss of one of $\mathcal{M}_2$ or $\mathcal{M}_2'$ is much larger than the other. Our bound exploits the fact that the worst-case will happen with small probability. Specifically, instead of considering the worst-case privacy loss between $\mathcal{M}_2$ and $\mathcal{M}_2'$, and naively composing it with $\mathcal{M}_1$, we show that for RDP we can tighten the bound by the *average* privacy loss of $\mathcal{M}_2$ and $\mathcal{M}_2'$ under the distribution imposed by $\mathcal{M}_1$. Direct (ε, δ)-DP analysis does not enjoy this benefit; compared with directly analyzing the (ε, δ)-DP bound of PTR, we show that by first bounding the RDP of PTR and then convert it to (ε, δ)-DP can lead to better privacy guarantee. Our proof could serve as a general recipe for analyzing DP/RDP guarantees for composed mechanisms where the privacy loss of each mechanism is adaptively determined. Additionally, we extend our analysis to the RDP of *subsampled* PTR. Our algorithm-specific analysis (the "white-box bound") allows us to get tighter privacy amplification bounds, compared with the one obtained by general subsampled RDP bound that supports any mechanisms (the "black-box bound") [ZW19]. The proof tackled several additional difficulties compared with the analysis for simple Gaussian mechanism [MTZ19]. By numerical verification, we show that our RDP bound for subsampled PTR is much tighter than the black-box bound, and is close to the lower bound (Figure 2.).

Applications of PTR in ML. PTR is especially suitable for improving the utility of privatizing robust statistics such as trimmed mean, as these functions usually have a much smaller local sensitivity compared to their global sensitivity. A critical application of robust statistics for machine learning is defending against corrupted data. The learning algorithm should be robust in the presence of corrupted data (referred to as *Byzantine failure* [LSP19]). Since privacy and robustness are two major concerns for ML training, developing techniques that achieve both goals simultaneously is desirable. We demonstrate the application of PTR in incorporating differential privacy with robust SGD methods. A popular technique for robustifying SGD is to replace the mean with some robust statistics (e.g., trimmed mean) for gradient aggregation [YCKB18, AHJ+21, GLV21]. We use trimmed mean as an example of showing how to augment robust SGD with DP through PTR. We show that the augmented SGD still maintains the robustness guarantee. We conduct extensive experiments on defending against three kinds of attacks: label, feature, and gradient corruptions, and we show that PTR-based robust SGD achieves much better utility than naively privatizing the robust SGD with global sensitivity.

2 Related Work

Since the seminal work of [DL09], the Propose-Test-Release has become a common DP framework mainly used in statistical inference [BAM20, LKO21]. To the best of our knowledge, this work is the first application of PTR in machine learning.

Several prior works (e.g., [LQS12, BBG18, WBK19, ZW19]) focus the general subsampled DP/RDP bound that supports any mechanisms. [WBK19] derives a general RDP privacy amplification for "sampling without replacement" scheme, and [ZW19] obtains a similar result under Poisson subsampling (i.e., including each data point independently at random with certain probability). Only a small body of recent works study algorithm-specific privacy amplification bound by subsampling. However, most of them focus on subsampled Gaussian mechanism [ACG+16, BDRS18, MTZ19]. This work derives the first subsampled RDP bound specific for flexible algorithms such as PTR.

Designing machine learning and optimization algorithms that achieve both privacy and Byzantine-robustness is certainly an important direction. Nevertheless, there are only few works on this line so far. [GGP+21] considered the problem of achieving privacy and byzantine resilience in distributed

SGD with an untrusted server. The privacy level they considered is essentially local differential privacy, which is orthogonal to our focus. [HKJ20] and [SGA20] aim for both robustness and secure multiparty computation instead of differential privacy. [MZH19] naively applies differential privacy to defend against data poisoning attack. However, they find that DP alone cannot defend adversaries that poison a large fraction of training examples. Aside from the setting of training ML models, [LKKO21] propose a polynomial time algorithm that achieves both goals for mean estimation via privatizing filter-based robust mean estimator [DKK+17]. [EMN21] develop a robust and differentially private mean estimator based on exponential mechanism. However, both of their approaches become inefficient (even in polynomial time asymptotically) in high dimensional settings.

3 Background

In this section, we introduce some background on differential privacy, Rényi differential privacy, and privacy-amplification by subsampling. We will also introduce notations as we proceed.

Differential Privacy. Differential privacy is a framework for protecting privacy when performing statistical releases on a dataset with sensitive information about individuals (see the surveys [DR+14, Vad17]). Specifically, for a differentially private mechanism, the probability distribution of the mechanism's outputs of a dataset should be close to the distribution of its outputs on the same dataset with any single individual's data replaced. To formalize this, we call two datasets S, S', each multisets over a data universe $\mathcal{X}$, *adjacent* if one can be obtained from the other by *adding or removing* a single element of $\mathcal{X}$. Further, we use $d(S, S')$ to denote the number of times of adding/removing of data points to transform S to S'. So S and S' are adjacent if and only if $d(S, S') = 1$.

Definition 3.1 (Differential Privacy [DMNS06])**.** For $\varepsilon, \delta \geq 0$, a randomized algorithm $\mathcal{M} :$ $\mathrm{MultiSets}(\mathcal{X}) \to \mathcal{Y}$ is (ε, δ)-*differentially private* if for every dataset pair $S, S' \in \mathrm{MultiSets}(\mathcal{X})$ such that $d(S, S') = 1$, we have:

$$\forall\, T \subseteq \mathcal{Y}\ \Pr[\mathcal{M}(S) \in T] \leq e^{\varepsilon} \cdot \Pr[\mathcal{M}(S') \in T] + \delta \tag{1}$$

where the randomness is over the coin flips of $\mathcal{M}$.

Rényi Differential Privacy (RDP). Rényi differential privacy (RDP) is a variant of the standard (ε, δ)-DP that uses Rényi-divergence as a distance metric between the output distributions of $\mathcal{M}(S)$ and $\mathcal{M}(S')$, which is particularly useful in training differentially private machine learning models.

Definition 3.2 (Rényi Differential Privacy [Mir17])**.** We say that a mechanism $\mathcal{M}$ is (α, ε)-RDP with order $\alpha \in (1, \infty)$ if for every dataset pair $S, S' \in \mathrm{MultiSets}(\mathcal{X})$ such that $d(S, S') = 1$, we have:

$$D_{\alpha}\left(\mathcal{M}(S)\|\mathcal{M}(S')\right) := \frac{1}{\alpha - 1} \log \mathbb{E}_{o \sim \mathcal{M}(S')}\left[\left(\frac{\mu_{\mathcal{M}(S)}(o)}{\mu_{\mathcal{M}(S')}(o)}\right)^{\alpha}\right] \leq \varepsilon \tag{2}$$

where $\mu_{\mathcal{M}}(\cdot)$ denotes the density function of $\mathcal{M}$'s distribution.

As we can see, (α, ε)-RDP is essentially an upper bound for the moment $\mathbb{E}_{o \sim \mathcal{M}(S')}\left[\left(\frac{\mu_{\mathcal{M}(S)}(o)}{\mu_{\mathcal{M}(S')}(o)}\right)^{\alpha}\right] \leq \exp((\alpha - 1)\varepsilon)$ for all adjacent S, S', where ε can be viewed as a degree of the privacy loss incurred by running $\mathcal{M}$. For convenience, in the following presentation, we denote the bound as a function $f_{\alpha}(\varepsilon) = \exp((\alpha - 1)\varepsilon)$. A different α typically leads to a different privacy bound ε. Following the convention of literature [ZW19], we view ε as a function of α, and the notation $\varepsilon_{\mathcal{M}}(\alpha)$ means the algorithm $\mathcal{M}$ obeys $(\alpha, \varepsilon_{\mathcal{M}}(\alpha))$-RDP. We note that RDP reduces to $(\varepsilon, 0)$-DP when we take $\alpha = \infty$. The current tightest (ε, δ)-DP/RDP transformation we are aware of is by [ALC+21]. A central property of DP/RDP is its behavior under composition. If we run multiple distinct differentially private algorithms on the same dataset, the resulting composed algorithm is also differentially private, with some degradation in the privacy parameters (ε, δ). Specifically, if we run k sequentially chosen (ε, δ)-DP algorithm on a dataset, the overall composed privacy parameter is $\left(\tilde{O}(\sqrt{k}\varepsilon), k\delta + \delta'\right)$-DP by Advanced composition theorem [DR+14]. However, the Advanced composition theorem for (ε, δ)-DP is loose. On the contrary, the composition is trivial for RDP as $\varepsilon_{\mathcal{M}_1 \circ \mathcal{M}_2}(\cdot) = \varepsilon_{\mathcal{M}_1}(\cdot) + \varepsilon_{\mathcal{M}_2}(\cdot)$. The Moment Accountant technique, which composes RDP and then transforms to DP, is a much simpler approach and often produces much more favorable privacy parameters than directly composing (ε, δ)-DP. Therefore, RDP and Moment Accountant are widely used to calculate the privacy guarantee in training differentially private deep learning models.

141 **Privacy amplification by subsampling.** "Privacy amplification by subsampling" is the other booster
142 besides RDP / moments accountant that drives much of the recent progress in differentially private
143 deep learning. Most of the existing works focus on Poisson subsampling [BBG18], which samples
144 each data point independently with a given sampling probability q. The tightest privacy amplification
145 bound we are aware of for general mechanism under Poisson Subsampling is from [ZW19].

4 Propose-Test-Release and Rényi Differential Privacy

147 In this section, we introduce a general version of the Propose-Test-Release framework, present our
148 main results on its RDP bound, and its privacy amplification bound under Poisson subsampling.

149 In our presentation, we use $\mathbb{GS}_f = \sup_{S,S':d(S,S')=1} \|f(S) - f(S')\|$ to denote the global sensitivity
150 of target function f (in ℓ_2 distance), and we use $\mathbb{LS}_f(S) = \sup_{S,S':d(S,S')=1} \|f(S) - f(S')\|$ to
151 denote the local sensitivity of function f on dataset S. Before we present our main results, we would
152 like to remind the readers about the definition of Laplace and Gaussian mechanisms, as well as their
153 DP/RDP bound, which will be referred to in our results.

154 **Laplace Mechanism:** If f's output is 1-dimensional, the Laplace mechanism $\mathcal{M}_{\mathrm{Lap},b}(S) =$
155 $f(S) + \mathrm{Lap}(0, b)$ obeys $(\varepsilon_{\mathrm{Lap}}^{(\tilde{b})}, 0)$-DP for $\varepsilon_{\mathrm{Lap}}^{(\tilde{b})} = e^{1/\tilde{b}}$, and obeys $(\alpha, \varepsilon_{\mathrm{R-Lap}}^{(\tilde{b})}(\alpha))$-RDP for
156 $\varepsilon_{\mathrm{R-Lap}}^{(\tilde{b})}(\alpha) = \frac{1}{\alpha-1} \log \left(\frac{\alpha}{2\alpha-1} \exp\left(\frac{\alpha-1}{\tilde{b}}\right) + \frac{\alpha-1}{2\alpha-1} \exp\left(-\frac{\alpha}{\tilde{b}}\right) \right)$, where $\tilde{b} = b/\mathbb{GS}_f$ (the "noise-
157 to-sensitivity" ratio).

158 **Gaussian Mechanism:** If f's output is d-dimensional, the Gaussian mechanism $\mathcal{M}_{\mathcal{N},\sigma}(S) =$
159 $f(S) + \mathcal{N}(0, \sigma^2 \mathbf{1}_d)$ obeys $(\varepsilon_{\mathcal{N}}^{(\tilde{\sigma})}(\delta), \delta)$-DP for $\varepsilon_{\mathcal{N}}^{(\tilde{\sigma})}(\delta) = \tilde{\sigma}\sqrt{2\log(1.25/\delta)}$, and obeys $(\alpha, \varepsilon_{\mathrm{R-\mathcal{N}}}^{(\tilde{\sigma})}(\alpha))$-
160 RDP for $\varepsilon_{\mathrm{R-\mathcal{N}}}^{(\tilde{\sigma})}(\alpha) = \frac{\alpha}{2\tilde{\sigma}^2}$, where $\tilde{\sigma} = \sigma/\mathbb{GS}_f$ (the "noise-to-sensitivity" ratio).

4.1 Propose-Test-Release

162 Naive use of Laplace/Gaussian mechanism
163 may result in the poor utility of function
164 output, as the global sensitivity of the tar-
165 get function may be intolerably large due
166 to some extreme cases. Meanwhile, ro-
167 bust statistics such as median, mode, Inter-
168 Quantile Range (IQR) are quite insensitive
169 to single data addition/removal for datasets
170 that are i.i.d. drawn from natural distribu-
171 tions. This means that robust statistics may
172 have a small local sensitivity for most input
173 datasets. The seminal work of [DL09] in-
174 troduced Propose-Test-Release framework
175 to reduce the noise addition when the target
176 function has an approximation that is a ro-
177 bust statistic[1]. Here, we introduce a more
178 general and useful version of PTR instan-

Algorithm 1: Propose-Test-Release with Laplace and Gaussian mechanism.

input : S – dataset, f_1 – target function, f_2 – robust statistic, τ – proposed local sensitivity bound of f_2, σ_1, σ_2, b – Gaussian/Laplace noise scales ($\sigma_1 > \sigma_2$), δ_0 – failure probability.

1 $\Delta \leftarrow \min_{\tilde{S} \in \{\tilde{S}: \mathbb{LS}_{f_2}(\tilde{S}) > \tau\}} d\left(S, \tilde{S}\right)$.
2 $\widehat{\Delta} \leftarrow \Delta + \mathrm{Lap}(0, b)$.
3 **if** $\widehat{\Delta} \leq \log(1/(2\delta_0))b$ **then**
4   **return** $f_1(S) + \mathcal{N}(0, \sigma_1^2 \mathbf{1}_d)$
5 **else**
6   **return** $f_2(S) + \mathcal{N}(0, \sigma_2^2 \mathbf{1}_d)$

---

179 tiated by Laplace and Gaussian mechanism. Given a target function f_1 (e.g., mean) and its robust
180 variant f_2 (e.g., median), the PTR framework proceeds as follows: **(1) Propose:** a local sensitivity
181 bound of the target function, τ, is proposed; **(2) Test:** a safety margin $\Delta(S)$, which is the minimum
182 amount of data points that we need to replace for S to have local sensitivity larger than τ, is computed.
183 A private version (via Laplace mechanism) of the safety margin, $\widehat{\Delta}$, is compared with a threshold;
184 **(3) Release:** if the safety margin is large enough, then the algorithm releases $f_2(S)$ via Gaussian
185 mechanism with a smaller noise σ_2 (usually scaled with τ). Otherwise, the algorithm release $f_1(S)$
186 with a larger noise σ_1 (usually scaled with $\mathbb{GS}_{f_1}$). The pseudocode is outlined in Algorithm 1.

187 We make several remarks on Algorithm 1.

188 *Remark* 4.1. **(1)** The traditional version of PTR in the textbooks [DR+14, Vad17] simply refuse to
189 output anything when the noisy safety margin $\widehat{\Delta}$ is small. Algorithm 1 is a more general version

---

[1]Sometimes the robust statistic itself is the target function.

which output $f_1(S) + \mathcal{N}(0, \sigma_1^2 \mathbf{1}_d)$ when the sensitivity test is failed. The textbook PTR can be thought of as a special case of Algorithm 1 where we set $\sigma_1 \to \infty$. **(2)** The mechanism used in the **Test** and **Release** step can be other mechanisms instead of Laplace and Gaussian. In this paper, we present our results for the PTR instantiated by these two mechanisms since we intend to apply it for differentially private SGD later. Our proof can be easily extended to other mechanisms as well. **(3)** The threshold $\log(1/(2\delta_0))b$ in Line 3 is chosen so that $\Pr[\mathrm{Lap}(0, b) > \log(1/(2\delta_0))b] = \delta_0$. **(4)** The global sensitivity of Δ is 1 for any functions. This could be seen by noticing that, for any pair of adjacent S, S', we have $d(S, \tilde{S}) \leq d(S', \tilde{S}) + 1$ for any dataset $\tilde{S}$.

Direct DP Analysis of Propose-Test-Release. We show the DP guarantee for the Propose-Test-Release framework. To prove privacy, we need to find the worst pair of adjacent datasets S and S' that incurs the largest privacy loss. It is clear that the worst possible scenario of PTR is when $f_2(S) - f_2(S') > \tau$, while the algorithm still releases $f_2(S)$ with noise scaled with τ. However, note that this worst possible scenario will only happen when *both* $\mathbb{LS}(S)$ *and* $\mathbb{LS}(S')$ *are greater than* τ. In this case, however, Δ for both S and S' are 0 since there are no data points we need to change for them to have local sensitivity larger than τ, and thus there is no privacy loss from $\widehat{\Delta}$. Moreover, when $\Delta = 0$, the probability that PTR will release $f_2(S) + \mathcal{N}(0, \sigma_2^2 \mathbf{1}_d)$ is at most δ_0, which could be simply added to the δ term in (ε, δ)-DP. If one of $\mathbb{LS}(S)$ and $\mathbb{LS}(S')$ is smaller than τ, then we know that $f_2(S) - f_2(S') \leq \tau$, and the overall privacy parameters could be computed by Basic Composition Theorem [DR$^+$14]. We obtain the following differential privacy guarantee for PTR based on these observations. We defer more details of the proof to the Appendix A.

Theorem 4.2 (Direct DP analysis for PTR). *Suppose* $\mathbb{GS}_{f_1} = \mathbb{GS}_{f_2} = 1$ *and* $\sigma_1 = \sigma_2/\tau$, *then Algorithm 1 is* $(\varepsilon_{\mathrm{Lap}}^{(b)} + \varepsilon_{\mathcal{N}}^{(\sigma_1)}(\delta), \delta_0 + \delta)$*-DP, where* $\varepsilon_{\mathrm{Lap}}^{(b)} = e^{1/b}$ *is the DP guarantee for Laplace mechanism, and* $\varepsilon_{\mathcal{N}}^{(\sigma_1)}(\delta) = \sigma_1 \sqrt{2 \log(1.25/\delta)}$.

4.2 RDP of Propose-Test-Release

We then derive the RDP of Propose-Test-Release framework. The major differences between the proofs of (ε, δ)-DP and RDP bound is that, for (ε, δ)-DP we can move the probability of running into the bad scenario to the δ term, while for RDP we need to consider the "average-case" privacy loss. This is in fact an advantage of RDP. Consider a mechanism $\mathcal{M}$ that randomly selects one of mechanisms $\mathcal{M}_1$ and $\mathcal{M}_2$ to run, each with probability $1 - \delta_0$ and δ_0. Suppose $\mathcal{M}_1$ is $(\varepsilon_1, \delta_1)$-DP and $\mathcal{M}_2$ is $(\varepsilon_2, \delta_2)$-DP. We can only claim that $\mathcal{M}$ is $(\max(\varepsilon_1, \varepsilon_2), (1 - \delta_0)\delta_1 + \delta_0\delta_2)$-DP, or if we know $\varepsilon_2 \gg \varepsilon_1$ we can also move the probability δ_0 to the δ term and obtain $(\varepsilon_1, \delta_0 + \delta_1)$ (which is the case for Theorem 4.2). However, if we know the RDP guarantee of $\mathcal{M}_1$ and $\mathcal{M}_2$ as $\mathbb{E}_{\mathcal{M}_1(S)} \left[\left(\frac{\mu_{\mathcal{M}_1(S')}}{\mu_{\mathcal{M}_1(S)}} \right)^\alpha \right] \leq f_\alpha(\varepsilon_1)$ and $\mathbb{E}_{\mathcal{M}_2(S)} \left[\left(\frac{\mu_{\mathcal{M}_2(S')}}{\mu_{\mathcal{M}_2(S)}} \right)^\alpha \right] \leq f_\alpha(\varepsilon_2)$, then $\mathbb{E}_{\mathcal{M}(S)} \left[\left(\frac{\mu_{\mathcal{M}(S')}}{\mu_{\mathcal{M}(S)}} \right)^\alpha \right]$ can be simply bounded by $(1 - \delta_0)f_\alpha(\varepsilon_1) + \delta_0 f_\alpha(\varepsilon_2)$. Compared with (ε, δ)-DP analysis, there are no extra inequalities used in RDP analysis of $\mathcal{M}$ except for the RDP guarantee of $\mathcal{M}_1$ and $\mathcal{M}_2$. Thus, the RDP bound is tighter than the DP bound, especially when δ_0 is close to the target δ.

Theorem 4.3 (RDP analysis of PTR). *Suppose* $\mathbb{GS}_{f_1} = \mathbb{GS}_{f_2} = 1$ *and* $\sigma_1 = \sigma_2/\tau$. *Then for any* $\alpha > 1$, *Algorithm 1 is* $(\alpha, \varepsilon_{\mathrm{PTR}}(\alpha))$*-RDP for*

$$\varepsilon_{\mathrm{PTR}}(\alpha) \leq \max \left(f_\alpha^{-1} \left((1 - \delta_0)f_\alpha \left(\varepsilon_{\mathrm{R}-\mathcal{N}}^{(\sigma_1)}(\alpha) \right) + \delta_0 f_\alpha \left(\varepsilon_{\mathrm{R}-\mathcal{N}}^{(\sigma_2)}(\alpha) \right) \right), \varepsilon_{\mathrm{R}-\mathcal{N}}^{(\sigma_1)}(\alpha) + \varepsilon_{\mathrm{R}-\mathrm{Lap}}^{(b)}(\alpha) \right)$$

The above result implies that, with appropriately chosen δ_0, the privacy loss of PTR is the same as directly adding up the privacy loss from $\widehat{\Delta}$ and from releasing $f_1(S) + \mathcal{N}(0, \sigma_1^2 \mathbf{1}_d)$ regardless of the value of $\widehat{\Delta}$. Compared with naively releasing $f_1(S) + \mathcal{N}(0, \sigma_1^2 \mathbf{1}_d)$, PTR will only pay an extra cost for privatizing Δ, independent from the privacy cost for the case of releasing $f_2(S) + \mathcal{N}(0, \sigma_2^2 \mathbf{1}_d)$! Thus, the algorithm could potentially add much smaller noise while introducing just a little extra privacy loss. In Figure 1, we convert this RDP bound to (ε, δ)-DP via the RDP-DP conversion formula by [BBG$^+$20], and compare with the (ε, δ)-DP bound obtained through direct analysis in Theorem 4.2. Although due to the loss in RDP-DP conversion, the ε parameter by RDP is worse than the one by direct analysis when δ_0 is far smaller than the target δ, it is tighter when δ_0 is close to δ. A larger δ_0 means PTR has a greater chance to release $f_2(S) + \mathcal{N}(0, \sigma_2^2 \mathbf{1}_d)$, which leads to a better utility. Thus, the privacy parameter converted from the RDP bound is more favorable.

Figure 1: The ε parameter of the (ε, δ)-DP guarantee of PTR when $\delta = 10^{-5}$ for different noise scales. We convert the RDP bound in Theorem 4.3 to (ε, δ)-DP by the RDP-DP conversion formula from [BBG+20], and compare it with the ε obtained from the direct analysis in Theorem 4.2. For the bound converted from RDP, we search for the optimal $\alpha \in [1, 200]$. The bound is constant across different δ_0 since when δ_0 is small, the RDP for PTR will take the second term in (3).

We would like to stress that in the theorem, most of the conditions on the parameters such as $\mathbb{GS}$ or σ_1, σ_2 can be easily relaxed. The conditions in the theorems are mainly used to make the presented bound more clean and interpretable.

4.3 RDP for Poisson Subsampled Propose-Test-Release

We further derive the RDP for Poisson subsampled PTR. Here, "subsampled" means the input dataset will be subsampled first before feeding to PTR. Poisson subsampling means each data point x will be included with probability q independently. One way of obtaining the RDP for any subsampled mechanism is by simply plugging in the RDP bound of the original algorithm into the privacy amplification formula for general mechanisms (e.g., [WBK19, ZW19]). Here, we directly derive the RDP for Poisson subsampled PTR in a white-box manner. Denote $\mathcal{M}_0$ as the random variable for PTR's output on dataset S, and $\mathcal{M}_1$ for PTR's output on dataset $S' = S \cup \{x\}$, and $\mathcal{M} = (1 - q)\mathcal{M}_0 + q\mathcal{M}_1$. Compared with the analysis for subsampled Gaussian mechanism by [MTZ19], there are two main difficulties for extending the arguments of quasi-convexity of Rényi divergence for PTR: **(1)** the distribution of PTR's output may not be centrally symmetric, thus we need to bound both $D_\alpha(\mathcal{M}||\mathcal{M}_0)$ and $D_\alpha(\mathcal{M}_0||\mathcal{M})$. **(2)** the conditional distribution $\mathcal{M}|\widehat{\Delta}$ cannot be decomposed as $(1 - q)\mathcal{M}_0|\widehat{\Delta} + q\mathcal{M}_1|\widehat{\Delta}$. A big part of our novelty in the proof is about addressing these two challenges. We defer details of the proof to Appendix A.

Theorem 4.4 (RDP analysis of sub-sampled PTR (the *"white-box bound"*)). *Let q be the subsampling probability. Suppose $\mathbb{GS}_{f_1} = \mathbb{GS}_{f_2} = 1$ and $\sigma_1 = \sigma_2/\tau$. When $q, \sigma_1, \sigma_2,$ and α satisfy certain conditions, we have*

$$\varepsilon_{\mathrm{PTR \circ PoissonSample}}(\alpha) \leq f_\alpha^{-1}\left(\max(\mathcal{B}_0, \mathcal{B}_1, \mathcal{B}_2)\right)$$

where $\mathcal{B}_0 = 1 + 2q^2\alpha(\alpha - 1)(\frac{1 - \delta_0}{\sigma_1^2} + \frac{\delta_0}{\sigma_2^2})$, $\mathcal{B}_1 = \mathrm{R}_q^{(\alpha)} + 2\alpha(\alpha - 1)[\mathrm{R}_q^{(\alpha)} - 2(1 - q)\mathrm{R}_q^{(\alpha-1)} + (1 - q)^2\mathrm{R}_q^{(\alpha-2)}]$, $\mathcal{B}_2 = \widetilde{\mathrm{R}}_q^{(\alpha)} + 2\alpha(\alpha - 1)[\widetilde{\mathrm{R}}_q^{(\alpha)} - 2(1 - q)\widetilde{\mathrm{R}}_q^{(\alpha+1)} + (1 - q)^2\widetilde{\mathrm{R}}_q^{(\alpha+2)}]$, with $\mathrm{R}_q^{(\alpha)} = \mathbb{E}_{s \sim \mu_0}\left[\left(\frac{\mu(s)}{\mu_0(s)}\right)^\alpha\right]$ and $\widetilde{\mathrm{R}}_q^{(\alpha)} = \mathbb{E}_{s \sim \mu}\left[\left(\frac{\mu_0(s)}{\mu(s)}\right)^\alpha\right]$ for $\mu_0 \sim \mathrm{Lap}(0, b)$ and $\mu \sim (1 - q)\mathrm{Lap}(0, b) + q\mathrm{Lap}(1, b)$.

Remark 4.5. Both $\mathrm{R}_q^{(\alpha)}$ and $\widetilde{\mathrm{R}}_q^{(\alpha)}$ can be computed easily since they either have closed form or can be accurately computed via numerical integration in bounded range.

This bound may not be very interpretable, which is a typical feature for the privacy amplification bounds as they are meant to be implemented in practice. After all, constant matters for differential privacy practitioners! To show the tightness of our bound, we plug in the RDP of original PTR (Theorem 4.3) to the current tightest privacy amplification formula for general mechanisms derived in [ZW19] (the *"black-box bound"*), and compare it with our white-box bound in Theorem 4.4. As we can see from Figure 2, Theorem 4.4 (orange curve) is much tighter than the black-box bound (blue curve). Moreover, it is very close to the lower bound of privacy amplification by [ZW19] (green line), which means that Theorem 4.4 is near optimal. In Figure 3, we illustrate the application of subsampled RDP bound in Moment Accountant. We can see that the privacy parameters for the

Figure 2: The RDP parameter $\varepsilon(\alpha)$ of the subsampled PTR as a function of order α. We compare the white-box bound from Theorem 4.4, and the black-box bound as well as the lower bound by plugging in the RDP of PTR in Theorem 4.3 to the privacy amplification upper/lower bounds for general mechanisms from [ZW19].

Figure 3: Illustration of the use of our Theorem 4.4 in moments accountant. We plot the the privacy loss ε for $\delta = 10^{-5}$ after different rounds of composition. We set $\delta_0 = 10^{-8}$ here to allow more iterations for Strong Composition of (ε, δ)-DP.

composed mechanism obtained based on our white-box bound (Theorem 4.4) is tighter than the one by black-box bound, as well as the one by directly composing Theorem 4.2 with strong composition theorem [KOV15]. We remark that Direct Analysis achieves lower privacy loss with very few iterations since we set $\delta_0 = 10^{-8}$ to allow more iterations for Strong Composition of (ε, δ)-DP, which leads to a better ε for a single iteration (see Figure 1).

An exciting byproduct during our research on subsampled PTR is the privacy amplification bound for a $\mathcal{M}$ that outputs $\mathcal{M}_1(S), \mathcal{M}_2(S)$ sequentially and *independently*. This result is important since such a $\mathcal{M}$ is instantiated in many existing techniques in improving differentially private deep learning. We defer this result to the Appendix.

5 Differentially Private and Robust SGD with Propose-Test-Release

In this section, we demonstrate the application of the RDP for (subsampled) PTR algorithm in privatizing robust SGD algorithms.

Mini-batch SGD is the de-facto method for training deep neural networks. Despite its strong convergence properties in the standard settings, it is well known that even a small fraction of corrupted gradients can lead SGD to an arbitrarily poor solution. This is typically being modeled as *Byzantine failure* [LSP19], meaning that some gradients can be *arbitrarily corrupted*, and the corrupted gradients may be crafted in an adversarial way. A popular class of defense strategies against Byzantine failure is to use robust aggregation rules such as trimmed-mean [GLV21], coordinate-wise median [YCKB18], and geometric median [AHJ+21]. Since both privacy and robustness are essential for ML applications, it is important to develop learning algorithms that achieve differential privacy and robustness simultaneously.

Baseline: privatizing robust SGD with Gaussian Mechanism. A natural (but naive) way to accomplish such a goal for SGD-based algorithms is to privatize each iteration of robust SGD through Gaussian mechanism. Specifically, in each iteration, we add Gaussian noise to the aggregated gradient, where noise magnitude scale with the global sensitivity of the robust aggregation function. The privacy parameter for the entire process is computed through Moment Accountant. The global

sensitivity can be obtained by either upper bounding the Lipschitz constant of the objective function, or clipping each gradient according to a certain threshold. However, this method could potentially add over-conservative noise to the aggregated gradients, as the local sensitivity of robust aggregation functions is usually very low for most input gradient sets.

Privatizing robust SGD with PTR. We improve the naive method with the PTR framework, where we instantiate it by showing how to privatize trimmed-mean SGD method from [GLV21]. We first define trimmed-sum[2] aggregation function, and show that the Δ for trimmed-sum could be computed efficiently. Given a dataset $S = \{x_1, \ldots, x_m\}$, let $x_{(k)}$ denote the kth smallest data point among S in ℓ_2 norm, i.e., $\|x_{(1)}\| \leq \|x_{(2)}\| \leq \ldots \leq \|x_{(m)}\|$. The *F-trimmed sum of S* is defined as $\mathrm{TSUM}_F(S) = \sum_{i=1}^{m-F} x_{(i)}$ if $m > F$, or simply 0 if $m \leq F$. Define $\mathbb{LS}_f^{(r)}(S) = \sup_{S, \tilde{S}: d(S, \tilde{S}) = r} \mathbb{LS}_f(\tilde{S})$, which is the maximum local sensitivity that can be achieved by adding/removing r elements from S. Thus, $\mathbb{LS}_f^{(0)}(S) = \mathbb{LS}_f(S)$, and the safety margin $\Delta(S) = \min\{r : \mathbb{LS}_f^{(r)}(S) > \tau\}$. Therefore, as long as we can efficiently compute $\mathbb{LS}_f^{(r)}(S)$, we can efficiently compute $\Delta(S)$ in linear time by simply enumerate all r from 0 to m and terminate once $\mathbb{LS}_f^{(r)}(S) > \tau$. In fact, $\mathbb{LS}_{\mathrm{TSUM}_F}^{(r)}(S)$ can be computed in $O(1)$ time.

Theorem 5.1. $\mathbb{LS}_{\mathrm{TSUM}_F}^{(r)}(S) = \|x_{(m-F+1+r)}\|$ *if* $r \leq F - 1$*, or* $\mathbb{GS}_{\mathrm{TSUM}_F}$ *if* $r > F - 1$*.*

Back to the goal of designing differentially private and robust SGD. Fix a positive integer F which is a potential upper bound for the number of corrupted gradients. We instantiate a PTR-based gradient aggregation algorithm by instantiating $f_1(\cdot)$ as $\mathrm{SUM}(S) = \sum_{x \in S} x$, and $f_2(\cdot)$ as $\mathrm{TSUM}_F(\cdot)$. We simply plugging in this PTR algorithm as the gradient aggregation function for regular SGD. We show the convergence guarantee of this algorithm in the presence of at most F gradients being corrupted for the case that the loss function is Lipschitz.

Theorem 5.2 (Informal)**.** *When the loss function is Lipschitz in model parameters, SGD with PTR instantiated by* SUM *and* TSUM *provides convergence guarantee for update to F gradients being corrupted arbitrarily for any $F < m/2$.*

We make two remarks of our specific design choices for implementing PTR-based SGD in practice. *Remark* 5.3. **(1)** In practice, F could be adjusted dynamically during the model training, based on the value of $\widehat{\Delta}$. That is, if $\widehat{\Delta} \leq B$, it means that the current gradient batch has many outliers, thus we increase F for the next iteration; if $\widehat{\Delta} > B$, it means that gradients are relatively concentrated and few of them are corrupted, thus we can decrease F afterwards. **(2)** We set f_1 as SUM instead of TSUM since F is usually set to be larger than the actual corrupted gradients; in this case, $\widehat{\Delta} \leq B$ means that there are many benign gradients also have large norms. These benign gradients usually correspond to the data points that are misclassified by the partially trained models, which is important for improving model performance.

The full pseudocode for the algorithm is deferred to the Appendix A.

5.1 Evaluation

In this section, we empirically evaluate the performance of PTR-based private and robust SGD. Specifically, we compare the utility-privacy tradeoff between the algorithm that privatize trimmed mean-based SGD with PTR (TSGD + PTR), and the baseline algorithm that privatize trimmed mean-based SGD with Gaussian mechanism (TSGD + Gaussian).

Experiment Settings. We evaluate the utility-privacy tradeoff of the two robust and differentially private SGD algorithms under three common types of attack: label, feature, and communicated gradient corruption. For label corruption, we randomly flip of label of certain amount of data points. For feature corruption, we add Gaussian noise from $\mathcal{N}(0, 100)$ directly to the corrupted images. For gradient corruption, we add Gaussian noise from $\mathcal{N}(0, 100)$ to the true gradients. We experiment on three classic datasets, MNIST, CIFAR10, and EMNIST. We vary different corruption ratios and privacy parameter ε. Experiment details are deferred to Appendix.

---

[2]We use trimmed-sum instead of trimmed-mean for the ease of analysis, as trimmed-mean essentially just scales the learning rate.

Dataset	Corruption Type	CR	$\varepsilon = 3.0$		$\varepsilon = 5.0$	
			TSGD+Gaussian	TSGD+PTR	TSGD+Gaussian	TSGD+PTR
MNIST	**Label**	**0**	87.53%	91.43% (+3.9%)	81.31%	92.8% (+11.49%)
		0.1	90.15%	93.29% (+3.138%)	89.15%	94.608% (+5.456%)
		0.2	91.33%	92.704% (+1.374%)	92.47%	94.084% (+1.614%)
	Feature	**0.1**	89.47%	92.28% (+2.812%)	86.53%	93.388% (+6.854%)
		0.2	91.71%	92.29% (+0.582%)	86.99%	92.864% (+5.872%)
	Gradient	**0.1**	90.27%	91.7% (+1.43%)	88.41%	91.68% (+3.27%)
		0.2	91.13%	91.45% (+0.32%)	88.70%	90.31% (+1.61%)

			$\varepsilon = 7.0$		$\varepsilon = 10.0$	
			TSGD+Gaussian	TSGD+PTR	TSGD+Gaussian	TSGD+PTR
CIFAR10	**Label**	**0**	57.94%	58.92% (+0.98%)	58.82%	60.13% (+1.31%)
		0.1	55.48%	56.262% (+0.78%)	57.42%	58.218% (+0.8%)
		0.2	49.69%	50.946% (+1.26%)	52.95%	53.106% (+0.152%)
	Feature	**0.1**	55.70%	56.628% (+0.93%)	57.36%	58.678% (+1.318%)
		0.2	55.13%	55.526% (+0.398%)	56.93%	57.336% (+0.404%)
	Gradient	**0.1**	55.81%	57.29% (+1.48%)	57.21%	58.96% (+1.75%)
		0.2	54.45%	56.31% (+1.86%)	56.11%	57.48% (+1.37%)

			$\varepsilon = 2.0$		$\varepsilon = 2.5$	
			TSGD+Gaussian	TSGD+PTR	TSGD+Gaussian	TSGD+PTR
EMNIST	**Label**	**0**	72.94%	76.44% (+3.5%)	79.15%	81.02% (+1.87%)
		0.1	72.60%	75.66% (+3.06%)	79.38%	80.63% (+1.25%)
		0.2	70.03%	72.62% (+2.59%)	77.48%	79.19% (+1.71%)
	Feature	**0.1**	69.60%	74.01% (+4.41%)	77.80%	81.04% (+3.24%)
		0.2	70.04%	74.76% (+4.72%)	78.99%	80.74% (+1.75%)
	Gradient	**0.1**	71.75%	76.19% (+4.44%)	77.32%	77.73% (+0.41%)
		0.2	70.76%	74.65% (+3.89%)	76.68%	77.17% (+0.49%)

Table 1: Model Accuracy under different privacy budgets and corruption settings. Every statistic is averaged over 5 runs with different random seed. The improvement of TSGD + PTR over TSGD + Gaussian is highlighted in the red text. εs are chosen differently for different datasets since the best accuracy-privacy tradeoff point varied for datasets.

Results. The comparison of model test accuracy under given corruption settings and privacy parameters are summarized in Table 1. We highlight the improvement of TSGD + PTR over the baseline TSGD + Gaussian in red texts. As we can see, for all settings, TSGD + PTR outperforms and often works significantly better than TSGD + Gaussian. This demonstrates that, while TSGD + PTR may introduce extra privacy loss in the **test** step, the performance gain from adding smaller noise in the **release** step overshadows it.

We also observe two interesting phenomena in the experiment: **(1)** a higher corruption ratio may not necessarily lead to worse model performance for trimmed mean-based robust SGD, especially for MNIST dataset. This is because the high norm gradients can be either corrupted, or benign but the partially-trained model misclassifies the corresponding data points. The latter case is extremely important for improving model performance compared with the gradients of data points are already being classified correctly. When the corruption ratio is small, more benign gradients are being trimmed, which may lead to worse model performance. **(2)** For TSGD + Gaussian, a larger privacy budget may not lead to better model performance on MNIST dataset. This is because when the training accuracy reaches the peak, there are many trimmed gradients whose corresponding training data points are already correctly classified; continuing training without those data points and with large noise may result in catastrophic forgetting.

6 Limitation and Future Works

This work derives the Rényi Differential Privacy for propose-test-release framework as well as its subsampled version. With the RDP bound for the PTR framework, this work demonstrate the application of PTR in training differentially private and robust models. One limitation of PTR is that it does not work well in privatizing coordinate-wise median in high-dimensional space. The global sensitivity of coordinate-wise median is far greater than the one for mean, which results in huge privacy loss. For future work, we would like to explore whether the robust gradient aggregation could also improve the utility of training differentially private ML models, as they typically exhibit smaller sensitivity than regular mean.

References

[ACG⁺16] Martín Abadi, Andy Chu, Ian J. Goodfellow, H. Brendan McMahan, Ilya Mironov, Kunal Talwar, and Li Zhang. Deep learning with differential privacy. In Edgar R. Weippl, Stefan Katzenbeisser, Christopher Kruegel, Andrew C. Myers, and Shai Halevi, editors, *Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security, Vienna, Austria, October 24-28, 2016*, pages 308–318. ACM, 2016.

[AHJ⁺21] Anish Acharya, Abolfazl Hashemi, Prateek Jain, Sujay Sanghavi, Inderjit S Dhillon, and Ufuk Topcu. Robust training in high dimensions via block coordinate geometric median descent. *arXiv preprint arXiv:2106.08882*, 2021.

[ALC⁺21] Shahab Asoodeh, Jiachun Liao, Flavio P Calmon, Oliver Kosut, and Lalitha Sankar. Three variants of differential privacy: Lossless conversion and applications. *IEEE Journal on Selected Areas in Information Theory*, 2(1):208–222, 2021.

[BAM20] Victor-Emmanuel Brunel and Marco Avella-Medina. Propose, test, release: Differentially private estimation with high probability. *arXiv preprint arXiv:2002.08774*, 2020.

[BBG18] Borja Balle, Gilles Barthe, and Marco Gaboardi. Privacy amplification by subsampling: Tight analyses via couplings and divergences. *Advances in Neural Information Processing Systems*, 31, 2018.

[BBG⁺20] Borja Balle, Gilles Barthe, Marco Gaboardi, Justin Hsu, and Tetsuya Sato. Hypothesis testing interpretations and renyi differential privacy. In *International Conference on Artificial Intelligence and Statistics*, pages 2496–2506. PMLR, 2020.

[BDRS18] Mark Bun, Cynthia Dwork, Guy N Rothblum, and Thomas Steinke. Composable and versatile privacy via truncated cdp. In *Proceedings of the 50th Annual ACM SIGACT Symposium on Theory of Computing*, pages 74–86, 2018.

[DKK⁺17] Ilias Diakonikolas, Gautam Kamath, Daniel M Kane, Jerry Li, Ankur Moitra, and Alistair Stewart. Being robust (in high dimensions) can be practical. In *International Conference on Machine Learning*, pages 999–1008. PMLR, 2017.

[DL09] Cynthia Dwork and Jing Lei. Differential privacy and robust statistics. In *Proceedings of the forty-first annual ACM symposium on Theory of computing*, pages 371–380, 2009.

[DMNS06] Cynthia Dwork, Frank McSherry, Kobbi Nissim, and Adam Smith. Calibrating noise to sensitivity in private data analysis. In *Theory of cryptography conference*, pages 265–284. Springer, 2006.

[DR⁺14] Cynthia Dwork, Aaron Roth, et al. The algorithmic foundations of differential privacy. *Foundations and Trends in Theoretical Computer Science*, 9(3-4):211–407, 2014.

[EMN21] Hossein Esfandiari, Vahab Mirrokni, and Shyam Narayanan. Tight and robust private mean estimation with few users. *arXiv preprint arXiv:2110.11876*, 2021.

[GGP⁺21] Rachid Guerraoui, Nirupam Gupta, Rafael Pinot, Sebastien Rouault, and John Stephan. Combining differential privacy and byzantine resilience in distributed sgd. *arXiv preprint arXiv:2110.03991*, 2021.

[GLV21] Nirupam Gupta, Shuo Liu, and Nitin Vaidya. Byzantine fault-tolerant distributed machine learning with norm-based comparative gradient elimination. In *2021 51st Annual IEEE/IFIP International Conference on Dependable Systems and Networks Workshops (DSN-W)*, pages 175–181. IEEE, 2021.

[HKJ20] Lie He, Sai Praneeth Karimireddy, and Martin Jaggi. Secure byzantine-robust machine learning. *arXiv preprint arXiv:2006.04747*, 2020.

[KNRS13] Shiva Prasad Kasiviswanathan, Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. Analyzing graphs with node differential privacy. In *Theory of Cryptography Conference*, pages 457–476. Springer, 2013.

[KOV15] Peter Kairouz, Sewoong Oh, and Pramod Viswanath. The composition theorem for differential privacy. In *International conference on machine learning*, pages 1376–1385. PMLR, 2015.

[LKKO21] Xiyang Liu, Weihao Kong, Sham Kakade, and Sewoong Oh. Robust and differentially private mean estimation. *Advances in Neural Information Processing Systems*, 34, 2021.

[LKO21] Xiyang Liu, Weihao Kong, and Sewoong Oh. Differential privacy and robust statistics in high dimensions. *arXiv preprint arXiv:2111.06578*, 2021.

[LQS12] Ninghui Li, Wahbeh Qardaji, and Dong Su. On sampling, anonymization, and differential privacy or, k-anonymization meets differential privacy. In *Proceedings of the 7th ACM Symposium on Information, Computer and Communications Security*, pages 32–33, 2012.

[LSP19] Leslie Lamport, Robert Shostak, and Marshall Pease. The byzantine generals problem. In *Concurrency: the Works of Leslie Lamport*, pages 203–226. 2019.

[Mir17] Ilya Mironov. Rényi differential privacy. In *2017 IEEE 30th Computer Security Foundations Symposium (CSF)*, pages 263–275. IEEE, 2017.

[MTZ19] Ilya Mironov, Kunal Talwar, and Li Zhang. Rényi differential privacy of the sampled gaussian mechanism. *arXiv preprint arXiv:1908.10530*, 2019.

[MZH19] Yuzhe Ma, Xiaojin Zhu, and Justin Hsu. Data poisoning against differentially-private learners: Attacks and defenses. *arXiv preprint arXiv:1903.09860*, 2019.

[NRS07] Kobbi Nissim, Sofya Raskhodnikova, and Adam Smith. Smooth sensitivity and sampling in private data analysis. In *Proceedings of the thirty-ninth annual ACM symposium on Theory of computing*, pages 75–84, 2007.

[SGA20] Jinhyun So, Başak Güler, and A Salman Avestimehr. Byzantine-resilient secure federated learning. *IEEE Journal on Selected Areas in Communications*, 39(7):2168–2181, 2020.

[TS13] Abhradeep Guha Thakurta and Adam Smith. Differentially private feature selection via stability arguments, and the robustness of the lasso. In *Conference on Learning Theory*, pages 819–850, 2013.

[Vad17] Salil Vadhan. The complexity of differential privacy. In *Tutorials on the Foundations of Cryptography*, pages 347–450. Springer, 2017.

[VEH14] Tim Van Erven and Peter Harremos. Rényi divergence and kullback-leibler divergence. *IEEE Transactions on Information Theory*, 60(7):3797–3820, 2014.

[WBK19] Yu-Xiang Wang, Borja Balle, and Shiva Prasad Kasiviswanathan. Subsampled rényi differential privacy and analytical moments accountant. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 1226–1235. PMLR, 2019.

[YCKB18] Dong Yin, Yudong Chen, Ramchandran Kannan, and Peter Bartlett. Byzantine-robust distributed learning: Towards optimal statistical rates. In *International Conference on Machine Learning*, pages 5650–5659. PMLR, 2018.

[YZCL21] Da Yu, Huishuai Zhang, Wei Chen, and Tie-Yan Liu. Do not let privacy overbill utility: Gradient embedding perturbation for private learning. *arXiv preprint arXiv:2102.12677*, 2021.

[ZJW18] Xinyang Zhang, Shouling Ji, and Ting Wang. Differentially private releasing via deep generative model (technical report). *arXiv preprint arXiv:1801.01594*, 2018.

[ZW19] Yuqing Zhu and Yu-Xiang Wang. Poission subsampled rényi differential privacy. volume 97 of *Proceedings of Machine Learning Research*, pages 7634–7642, Long Beach, California, USA, 09–15 Jun 2019. PMLR.