Near-Optimal Multi-Agent Learning for Safe Coverage Control

Abstract

In multi-agent coverage control problems, agents navigate their environment to reach locations that maximize the coverage of some density. In practice, the density is rarely known *a priori*, further complicating the original NP-hard problem. Moreover, in many applications, agents cannot visit arbitrary locations due to *a priori* unknown safety constraints. In this paper, we aim to efficiently learn the density to approximately solve the coverage problem while preserving the agents' safety. We first propose a conditionally linear submodular coverage function that facilitates theoretical analysis. Utilizing this structure, we develop MACOPT, a novel algorithm that efficiently trades off the exploration-exploitation dilemma due to partial observability, and show that it achieves sublinear regret. Next, we extend results on single-agent safe exploration to our multi-agent setting and propose SAFEMAC for safe coverage and exploration. We analyze SAFEMAC and give first of its kind results: near optimal coverage in finite time while provably guaranteeing safety. We extensively evaluate our algorithms on synthetic and real problems, including a bio-diversity monitoring task under safety constraints, where SAFEMAC outperforms competing methods.

1 Introduction

In multi-agent coverage control (MAC) problems, multiple agents coordinate to maximize coverage over some spatially distributed events. Their applications abound, from collaborative mapping [1], environmental monitoring [2], inspection robotics [3] to sensor networks [4]. In addition, the coverage formulation can address core challenges in cooperative multi-agent RL [5], e.g., *exploration* [6], by providing high-level goals. In these applications, agents often encounter safety constraints that may lead to critical accidents when ignored, e.g., obstacles [7] or extreme weather conditions [8, 9].

Deploying coverage control solutions in the real world presents many challenges: (*i*) for a given density of relevant events, this is an *NP hard problem* [10]; (*ii*) such *density* is *rarely known* in practice [2] and must be learned from data, which presents a complex active learning problem as the quantity we measure (the density) differs from the one we want to optimize (its coverage); (*iii*) agents often operate under *safety-critical* conditions, [7–9], that may be *unknown a priori*. This requires cautious exploration of the environment to prevent catastrophic outcomes. While prior work addresses subsets of these challenges (see Section 7), we are not aware of methods that address them jointly.

This work makes the following contributions toward efficiently solving safe coverage control with *a-priori* unknown objectives and constraints. **Firstly**, we model this multi-agent learning task as a *conditionally linear* coverage function. We use the *monotonocity* and the *submodularity* of this

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

(a) Disconnected safe regions   (b) Illustration of multi-agent GoOSE

Figure 1: In a) agents are partitioned into two batches. Agent 1 covers D^1 (green), 2 covers D^{2-} (orange) and 3 covers D^{3-} (yellow). In b) SAFEMAC sets a goal $x_t^{g,i}$ $\forall i$ in the optimistic set. It forms a expander region (dark blue) to safely expand the pessimistic safe set, S_t^p, towards the goal.

function to propose MACOPT, a new algorithm for the unconstrained setting that enjoys sublinear cumulative regret and efficiently recommends a near-optimal solution. **Secondly**, we extend GoOSE [11], an algorithm for single agent safe exploration, to the multi-agent case. Combining our extension of GoOSE with MACOPT, we propose SAFEMAC, a novel algorithm for safe multi-agent coverage control. We analyze it and show it attains a near-optimal solution in a finite time. **Finally**, we demonstrate our algorithms on a synthetic and two real world applications: safe biodiversity monitoring and obstacle avoidance. We show SAFEMAC finds better solutions than algorithms that do not actively explore the feasible region and is more sample efficient than competing near-optimal safe algorithms.

2   Problem Statement

We present the safety-constrained multi-agent coverage control problem that we aim to solve.

Coverage control. Coverage control models situations where we want deploy a swarm of dynamic agents to maximize the coverage of a quantity of interest. Formally, given a finite[1] set of possible locations V, the goal of coverage control is to maximize a function $F : 2^V \to \mathbb{R}$ that assigns to each subset, $X \subseteq V$, the corresponding coverage value. For K agents, the resulting problem is $\arg\max_{X:|X|\leq K} F(X)$.

Sensing region. Depending on the application, we may use different definitions of F. Here, we model cases where agent i at location x^i covers a limited sensing region around it, D^i. While D^i can be any connected subset of V, in practice it is often a ball centered at x^i. Given a function $\rho : V \to \mathbb{R}$ denoting the density of a quantity of interest at each $v \in V$, our coverage objective is

$$F(X; \rho, V) = \sum_{x^i \in X} \sum_{v \in D^{i-}} \rho(v)/N, \tag{1}$$

where $D^{i-} := D^i \setminus D^{1:i-1}$ indicates the elements in V covered by agent i but not by agents $1 : i-1$, and N is the largest number of elements in V covered by a sensing region.

Safety. In many real-world problems, agents cannot go to arbitrary locations due to safety concerns. To model this, we introduce a constraint function $q : V \to \mathbb{R}$ and we consider safe all locations v satisfying $q(v) \geq 0$. Such constraint restricts the space of possible solutions of our problem in two ways. First, it prevents agents from monitoring from unsafe locations. Second, depending on its dynamics, agent i may be unable to safely reach a disconnected safe area starting from x_0^i, see Fig. 1a. We denote with $\bar{R}_{\epsilon_q}(\{x_0^i\})$ the largest safely reachable region starting from x_0^i and with $\mathcal{B}$ a collection of batches of agents such that all agents in the same batch B share the same safely reachable set, $\forall i, j \in B : \bar{R}_{\epsilon_q}(\{x_0^i\}) \cap \bar{R}_{\epsilon_q}(\{x_0^j\}) \neq \emptyset$, see Appendix A for formal definitions. Based on this, we define the safely reachable control problem

$$\sum_{B \in \mathcal{B}} \max_{X^B \in \bar{R}_{\epsilon_q}(X_0^B)} F(X^B; \rho, \bar{R}_{\epsilon_q}(X_0^B)), \tag{2}$$

---

[1]Continuous domains can be handled via discretization

64 where, $X_0^B = \{x_0^i\}_{i \in B}$ are the starting locations of all agents in B and $\bar{R}_{\epsilon_q}(X_0^B) = \cup_{i \in B} \bar{R}_{\epsilon_q}(\{x_0^i\})$
65 indicates the largest safely reachable region from any point x_0^i for all i in B.

66 **Unknown density and constraint**. In practice, the density ρ and the constraint q are often unknown
67 *a priori*. However, the agents can iteratively obtain noisy measurements of their values at target
68 locations. We consider synchronous measurements, i.e., we wait until all agents have collected the
69 desired measurement for the current iteration before moving to the next one. Here, we focus on the
70 high-level problem of choosing informative locations, rather than the design of low-level motion
71 planning. Therefore, our goal is to find an approximate solution to the problem in Eq. (2) preserving
72 safety throughout exploration, i.e., at every location visited by the agents, while taking as few
73 measurements as possible in case the dynamics of the agents are deterministic and known as in [11].

74 # 3 Background

75 This section presents foundational ideas that our method builds on. In particular, it discusses (*i*)
76 monotone submodular functions and (*ii*) previous work on single-agent safe exploration.

77 **Submodularity**. Optimizing a function defined over the power set of a finite domain, V, scales com-
78 binatorially with the size of V in general. In special cases, we can exploit the structure of the objective
79 to find approximate solutions efficiently. Monotone submodular functions are one example of this.

80 A set function $F : 2^V \to \mathbb{R}$ is *monotone* if for all $A \subseteq B \subset V$ we have $F(A) \leq F(B)$. It is *submod-*
81 *ular* if $\forall v \in V \setminus B$, we have, $F(A \cup \{v\}) - F(A) \geq F(B \cup \{v\}) - F(B)$. In coverage control, this
82 means adding v to A yields a larger or equal relative coverage improvement than adding v to B, if $A \subseteq$
83 B. Crucially, [12] guarantees that the greedy algorithm produces a solution within a factor of $(1-1/e)$
84 of the optimal solution for problems of the type $\arg \max_{X : |X| \leq K} F(X; \rho, V)$, when F is monotone
85 and submodular. In practice, the greedy algorithm often outperforms this worst-case guarantee [13].

86 The coverage function in Eq. (1) is a conditionally linear, monotone and submodular function (proof
87 in Appendix B), which lets us use the results above to design our algorithm for safe coverage control.

88 **Goal-oriented safe exploration**. GOOSE [11] is a single-agent safe exploration algorithm that extends
89 unconstrained methods to safety-critical cases. Concretely, it maintains an under and an over approx-
90 imation of the feasible set, known as the pessimistic and optimistic safe sets. It preserves safety by re-
91 stricting the agent to the pessimistic safe set. It efficiently explores the objective by letting the original
92 unconstrained algorithm recommend locations within the optimistic safe set. If such recommendations
93 are provably safe, the agent evaluates the objective there. Otherwise, it evaluates the constraint at a se-
94 quence of safe locations to prove that such recommendation is either safe, which allows it to evaluate
95 the objective, or unsafe, which triggers the unconstrained algorithm to provide a new recommendation.

96 **Assumptions**. To guarantee safety, GOOSE makes two main assumptions. First, it assumes there
97 is an initial set of safe locations, X_0, from where the agent can start exploring. Second, it assumes
98 the constraint is sufficiently well-behaved, so that we can use data to infer the safety of unvisited
99 locations. Formally, it assumes the domain V is endowed with a positive definite kernel $k^q(\cdot, \cdot)$,
100 and that the constraint's norm in the associated *Reproducing Kernel Hilbert Space* [14] is bounded,
101 $\|q\|_{k^q} \leq B_q$. This lets us use Gaussian Processes (GPs) [15]to construct high-probability confidence
102 intervals for q. We specify the GP prior over q through a mean function, which we assume to be
103 zero everywhere w.l.o.g., $\mu(v) = 0, \forall v \in V$, and a kernel function, k, that captures the covariance
104 between different locations. If we have access to T measurements, at $V_T = \{v_t\}_{t=1}^T$ perturbed by
105 i.i.d. Gaussian noise, $y_T = \{q(v_t) + \eta\}_{t=1}^T$ with $\eta \sim \mathcal{N}(0, \sigma^2)$, we can compute the posterior mean
106 and covariance over the constraint at unseen locations v, v' as $\mu_T(v) = k_T^\top(v)(K_T + \sigma^2 I)^{-1} y_T$ and
107 $k_t(v, v') = k(v, v') - k_T^\top(v)(K_T + \sigma^2 I)^{-1} k_T(v')$, where $k_T(v) = (k(v_1, v), ..., k(v_T, v))$, K_T is
108 a the positive definite kernel matrix $[k(v, v')]_{v,v' \in V_T}$ and $I \in \mathbb{R}^{T \times T}$ denotes the identity matrix.

109 In this work, we make the same assumptions about the safe seed and the regularity of q and ρ.

110 **Approximations of the feasible set**. Based on the GP posterior above, GOOSE builds monotonic
111 confidence intervals for the constraint at each iteration t as $l_t^q(v) := \max\{l_{t-1}^q(x), \mu_{t-1}^q(v) -$
112 $\beta_t^q \sigma_{t-1}^q(v)\}$ and $u_t^q(v) := \min\{u_{t-1}^q(x), \mu_{t-1}^q(v) + \beta_t^q \sigma_{t-1}^q(v)\}$, which contain the true constraint

function for every $v \in V$ and $t \geq 1$, with high probability if β_t^q is selected as in [16] or Section 5. GoOSE uses these confidence intervals within a set $S \subseteq V$ together with the Lipschitz continuity of q to define operators that determine which locations are safe in a worst and best case scenarios,

$$p_t(S) = \{v \in V, |\exists z \in S : l^q(z) - L_q d(v, z) \geq 0\}, \tag{3}$$

$$o_t^{\epsilon_q}(S) = \{v \in V, |\exists z \in S : u^q(z) - \epsilon_q - L_q d(v, z) \geq 0\}. \tag{4}$$

Notice the pessimistic operator relies on the lower bound, l^q, while the optimistic one on the upper bound, u^q. Moreover, the optimistic one uses a margin ϵ_q to exclude "barely" safe locations as the agent might get stuck learning about them. Finally, to disregard locations the agent could not safely reach or from where it could not safely return, GoOSE introduces the $R^{\text{ergodic}}(\cdot, \cdot)$ operator. $R^{\text{ergodic}}(p_t(S), S)$ indicates locations in S or locations in $p_t(S)$ reachable from S and from where the agent can return to S along a path contained in $p_t(S)$. Combining $p_t(S)$ and $R^{\text{ergodic}}(\cdot, \cdot)$, GoOSE defines the pessimistic and ergodic operator $\tilde{P}_t(\cdot)$, which it uses to update the pessimistic safe set. Similarly, it defines $\tilde{O}_t(\cdot)$ using $o_t^{\epsilon_q}(\cdot)$ to compute the optimistic safe set.

4 MaCOpt and SafeMaC

This section presents MaCOpt and SafeMaC, our algorithms for unconstrained and safety-constrained multi-agent coverage control, which we formally analyze in Section 5.

4.1 MaCOpt: unconstrained multi-agent coverage control

Greedy sensing regions. In sequential optimization, it is crucial to balance exploration and exploitation. GP-UCB [17] is a theoretically sound strategy to strike such a trade-off that works well in practice. Agents evaluate the objective at locations that maximize an upper confidence bound over the objective given by the GP model such that locations with either a high posterior mean (exploitation) or standard deviation (exploration) are visited. We construct a valid confidence upper bound for the coverage $F(X)$ starting from our confidence intervals on ρ, by replacing the true density ρ with its upper bound u_t^ρ in Eq. (1). Next, we apply the greedy algorithm to this upper bound (Line 3 of Algorithm 2) to select K candidate locations for evaluating the density. Unfortunately, this exploration strategy may perform poorly. This is because, to reduce the uncertainty over the coverage F at X, we must learn the density ρ at all locations inside the sensing region, $\cup_{i=1}^K D^i$, rather than simply at X. We say ours is a partial monitoring problem, where the objective F differs from the quantity we measure, i.e., the density ρ. Next, we explain how to choose locations where to observe the density for a given X.

Uncertainty sampling. Given location assignments for the agents, X, we measure the density to learn efficiently about $F(X)$. Intuitively, agent i learns the density where the uncertainty is highest within the area it covers that is not covered by agents $\{1, \ldots, i-1\}$, i.e., D_t^{i-} (Line 4 of Algorithm 1).

Stopping criterion. The algorithm should terminate when a near-optimal solution is achieved. Intuitively, this occurs when the uncertainty about the coverage value of the greedy recommendation is low. Formally, we require the sum of the uncertainties over the sampling targets, $w_t = \sum_{i=1}^K u_{t-1}^\rho(x_t^{g,i}) - l_{t-1}^\rho(x_t^{g,i})$, to be below a threshold, ϵ_ρ (Line 3 of Algorithm 1). Importantly, this stopping criterion requires the confidence intervals to shrink only at regions that potentially maximize the coverage.

MaCOpt. Now, we introduce MaCOpt (Algorithm 1). At round t, we select the sensing locations for the agents, X_t, by greedily optimizing the upper confidence bound of the coverage. Then, each agent i collects noisy density measurements at the points of highest uncertainty within D_t^{i-}. Finally, we update our GP over the density and, if the sum of maximum uncertainties within each sensing region is small, we stop the algorithm.

4.2 SafeMaC: safety-constrained multi-agent coverage control

Intuition. We adopt a perspective similar to GoOSE as we separate the exploration of the safe set from the maximization of the coverage. Given an over and under approximation of the safe set (whose computation is discussed later), we want to explore optimistically optimal goals for each agent, similar

Algorithm 1 MACOPT

1: **Inputs** $X_0, \epsilon_\rho, V, GP_\rho, t \leftarrow 0$
2: $X_1, w_1 \leftarrow \textsc{Greedy}(u_0^\rho, l_0^\rho, [K], V)$
3: **while** $w_t > \epsilon_\rho$ **do**
4: $\quad \forall i, x_t^{g,i} \leftarrow \underset{x \in D_t^{i-}}{\arg\max}\, u_{t-1}^\rho(v) - l_{t-1}^\rho(v)$
5: $\quad \forall i, y_{\rho_t}^i = \rho(x_t^{g,i}) + \eta_\rho$, Update GP
6: $\quad t \leftarrow t + 1$
7: $\quad X_t, w_t \leftarrow \textsc{Greedy}(u_{t-1}^\rho, l_{t-1}^\rho, [K], V)$
8: **Recommend** X_t

Algorithm 2 Greedy UCB (GREEDY)

1: **Inputs** $u_{t-1}^\rho, l_{t-1}^\rho, B, S_t^u$
2: **for** $i = 1, 2, ..., |B|$ **do**
3: $\quad x_t^i \leftarrow \underset{x^i}{\arg\max} \sum_{v \in D^i \setminus D_t^{1:i-1} \cap S_t^u} u_{t-1}^\rho(v)$
4: $\quad x_t^{g,i} \leftarrow \underset{v \in D^i \setminus D_t^{1:i-1} \cap S_t^u}{\arg\max} u_{t-1}^\rho(v) - l_{t-1}^\rho(v)$
5: $\quad w_t \leftarrow \sum_{i=1}^{|B|} u_{t-1}^\rho(x_t^{g,i}) - l_{t-1}^\rho(x_t^{g,i})$
6: **Return** X_t^B, w_t

Algorithm 3 Safe Expansion (SE)

1: **Inputs** $S_t^{o,\epsilon_q}, S_t^p, x_t^g$
2: $A_t(p) \leftarrow \{v \in S_t^{b,\epsilon_q} \backslash p_t(S_t^p) | h(v) = p\}$
3: $W_t^{\epsilon_q} \leftarrow \{v \in S_t^p | u_t^q(v) - l_t^q(v) > \epsilon_q\}$
4: $\alpha^\star \leftarrow \max_\alpha\ s.t.\ |G_t^{\epsilon_q}(\alpha)| > 0$
5: **if** Optimization problem feasible **then**
6: $\quad v_t \leftarrow \arg\max_{v \in G_t^{\epsilon_q}(\alpha^\star)} u_t^q(v) - l_t^q(v)$
7: $\quad$ Update GP with $y_t = q(v_t) + \eta_q$

Algorithm 4 SAFEMAC

1: **Inputs** $X_0, L_q, \epsilon_\rho, V, GP_\rho, GP_q$
2: $\forall i, S_0^{p,i} \leftarrow X_0, S_0^{o,\epsilon_q,i} \leftarrow V, t \leftarrow 0$
3: $X_1, w_1 \leftarrow \textsc{Greedy}(u_0^\rho, l_0^\rho, [K], V)$
4: **while** $\forall i, (S_t^{o,\epsilon_q,i} \backslash S_t^{p,i}) \cap D_t^i \neq \emptyset$ or $w_t > \epsilon_\rho$ **do**
5: $\quad$ **if** $w_t > \epsilon_\rho$ **then**
6: $\quad\quad \forall i, x_t^{g,i} \leftarrow \underset{x \in D_t^{i-}}{\arg\max}\, u_{t-1}^\rho(v) - l_{t-1}^\rho(v)$
7: $\quad$ **else**
8: $\quad\quad \forall i, x_t^{g,i} \leftarrow \underset{x \in (S_{t-1}^{o,\epsilon_q,i} \backslash S_{t-1}^{p,i}) \cap D_t^i}{\arg\max}\, u_{t-1}^q(v) - l_{t-1}^q(v)$
9: $\quad$ **if** *for any* $i \in [K]$, $x_t^{g,i} \notin S_t^{p,i}$ **then**
10: $\quad\quad \text{SE}(S_{t-1}^{o,\epsilon_q,i}, S_{t-1}^{p,i}, x_t^{g,i})$
11: $\quad\quad S_t^{p,i} \leftarrow \tilde{P}_t(S_{t-1}^{p,i}), S_t^{o,\epsilon_q,i} \leftarrow \tilde{O}_t^{\epsilon_q}(S_{t-1}^{p,i})$
12: $\quad\quad t \leftarrow t + 1$
13: $\quad \forall i, \mathcal{B}_t'(i) = \{j \in [K] | S_t^{u,i} \cap S_t^{u,j} \neq \emptyset\}$
14: $\quad \mathcal{B}_t = \bigcup_{i \in [K]} \mathcal{B}_t'(i)$
15: $\quad$ **if** *for any* $B \in \mathcal{B}_t$, $S_t^{u,B} \neq S_{t-1}^{u,B}$ **then**
16: $\quad\quad X_t, w_t \leftarrow \textsc{Greedy}(u_{t-1}^\rho, u_{t-1}^\rho, B, S_t^{u,B})$
17: $\quad\quad \forall i, x_t^{g,i} \leftarrow \underset{x \in D_t^{i-}}{\arg\max}\, u_{t-1}^\rho(v) - l_{t-1}^\rho(v)$
18: $\quad$ **if** $\forall i, x_t^{g,i} \in S_t^{p,i}$ and $w_t > \epsilon_\rho$ **then**
19: $\quad\quad \forall i, y_{\rho_t}^i = \rho(x_t^{g,i}) + \eta_\rho$, Update GP
20: $\quad\quad$ update GP i.e, compute u_t^ρ, l_t^ρ
21: $\quad\quad t \leftarrow t + 1$
22: $\quad\quad X_t, w_t \leftarrow \textsc{Greedy}(u_{t-1}^\rho, u_{t-1}^\rho, B, S_{t-1}^{u,B})$
23: **Recommend** X_t

---

to MACOPT. To this end, we find the maximizers of the density upper bound in the optimistic safe set with the GREEDY algorithm. Then, we define sampling goals to learn the coverage at those locations.

Phases of SAFEMAC. Coverage values depend both on the density and the feasible region (Eq. (2)). Thus, there are two sensible sampling goals given a disk assignment: i) *optimistic coverage*: if we are uncertain about the density within the disks, we target locations with the highest density uncertainty (Line 6 of Algorithm 4); ii) *optimistic exploration*: if we know the density within the disk but there are locations under it that we cannot classify as either safe (in S^p) or unsafe (in $V \setminus S^{o,\epsilon_q}$), we target those with the highest constraint uncertainty among them (Line 8). If all the goal locations are safe with high probability, which can only happen during *optimistic coverage*, we safely evaluate the density there (Line 19). Otherwise, we explore the constraint with a goal directed strategy that aims at classifying them as either safe or unsafe similar to GOOSE (Line 9-12). In case this changes the topological connection of the optimistic feasible set, we recompute the disks as this may change GREEDY's output (Line 15-17). We repeat this loop until we know the feasibility of all the points under the disks recommended by GREEDY and their density uncertainty is low (Line 4). Next, we explain how the multiple agents coordinate their individual safe regions to evaluate a goal (MACOPT *in batches*), how the agents progress toward their goals (*safe expansion*) and finally we describe SAFEMAC *convergence*.

MACOPT in batches. In the multi-agent setting of GOOSE (see Fig. 1b), each agent i maintains $S_t^{p,i}$ a pessimistic (or $S_t^{o,\epsilon_q,i}$ an optimistic) belief of the safe locations, obtained by iteratively applying $\tilde{P}_t(\cdot)$ the pessimistic (or $\tilde{O}_t(\cdot)$ the optimistic) ergodic operators (see Section 3) to the previous pessimistic belief $S_{t-1}^{p,i}$ (Line 11 of Algorithm 4). Since the agents cannot navigate to an arbitrary location in the constrained case, SAFEMAC computes coverage maximizers on a restricted region, obtained by

ignoring the known unsafe locations. To denote such a restricted region, we define a union set $S_t^{u,i} :=$ $S_t^{o,\epsilon_q,i} \cup S_t^{p,i}$, which is the largest set known to be optimistically or pessimistically safe up to time t. Moreover, if the agents are topologically disconnected, they cannot travel from one safe region to another and the best strategy for any batch of agents is to maximize coverage locally. For this, we form a collection of batches $\mathcal{B}_t$, such that any batch $B \in \mathcal{B}_t$ contains agents that lie in topologically connected regions determined by the union set (Line 13-14). SAFEMAC computes a GREEDY solution for each $B \in \mathcal{B}_t$ in their corresponding $S_t^{u,B} := \cup_{i \in B} S_t^{u,i}$. This is the largest set where the agents can find an optimistically safe path to travel. Analogous to $\mathcal{B}_t$, we define $\mathcal{B}_t^p$ as collection of batches where any $B \in \mathcal{B}_t^p$ contains agents which are topologically connected in pessimistic set and $S_t^{p,B} := \cup_{i \in B} S_t^{p,i}$.

Safe expansion. Safe expansion is the sub-routine inspired by GOOSE for goal-oriented exploration of the safe set that we use to learn about the feasibility of sampling targets. It uses a heuristic h to assign priority scores p to points that are optimistically but not pessimistically safe. Those determine locations whose feasibility is relevant to learn that of the sampling targets (Line 2 of Algorithm 3). A simple and effective choice for the heuristic is the inverse of the distance to the targets. Then, it identifies safe locations where the constraint is not yet known ϵ_q-accurately (Line 3). Among them, it determines the α-immediate expanders, i.e., those that could potentially add locations with priority α to the pessimistic set, $G_t^{\epsilon_q}(\alpha) = \{v \in W_t^{\epsilon_q} | \exists z \in A_t(\alpha) : u^q t - L_q d(v, x) \geq 0\}$. In Line 4, it selects the non-empty α-expander set with the highest priority. In Line 6 - 7, the agent evaluates the constraint at the location with the highest uncertainty in this set (see [11] for details).

SAFEMAC convergence. The *optimistic coverage* phase switches to *optimistic exploration* phase, when density uncertainty is under the disks is low ($w_t \leq \epsilon_\rho$). In the exploration, either the topological connection of the optimistic feasible set changes or will classify the uncertain region as pessimistically safe. In the former case, SAFEMAC will recompute a new coverage location and switch to the coverage phase. Alternatively, if the uncertain region is pessimistically safe, SAFEMAC is said to be converged since the density uncertainty in the exploration phase is already low. The phases show an interesting dynamics; SAFEMAC continuously iterates between the *optimistic exploration* and the *optimistic coverage* phase until we know about the feasibility of the disk and their uncertainty is low. In the worst case, SAFEMAC might explore the entire environment. In this case the sample complexity will be similar to a two-stage algorithm, where we explore the whole domain and then optimize coverage in the resulting known environment. However, in practice, SAFEMAC is much better than this worst case.

5 Analysis

This section analyzes MACOPT's convergence and SAFEMAC's optimality and safety properties.

MACOPT. To measure the progress of MACOPT, we study its regret, i.e., the difference between its solution and the one we could find if we knew the true density. Since control coverage consists in maximizing a monotone submodular function, we cannot compute the true optimum even for known densities. However, we can efficiently find a solution that is at least $(1 - 1/e)$ within the optimum. Thus, we quantify performance using the following notion of cumulative regret,

$$Reg_{act}(T) = (1 - \frac{1}{e}) \sum_{t=1}^{T} F(X_\star; \rho, V) - \sum_{t=1}^{T} F(X_t; \rho, V), \tag{5}$$

where $F(X_\star; \rho, V)$ is the optimal coverage. We now state one of our main results, which guarantees that the cumulative regret of MACOPT grows sublinearly in time (proof in Appendix D).

Theorem 1. *Let $\delta \in (0, 1)$ and β_t^ρ as in [16], i.e., $\beta_t^{\rho 1/2} = B_\rho + 4\sigma_\rho \sqrt{\gamma_{t+1}^\rho + \ln(1/\delta)}$. With probability at least $1 - \delta$, MACOPT's regret defined in Eq. (5) is bounded by $\mathcal{O}(\sqrt{T \beta_T^\rho \gamma_{KT}^\rho})$,*

$$Pr\left\{ Reg_{act}(T) \leq K \sqrt{\frac{8T \beta_T^\rho \gamma_{KT}^\rho}{\log(1 + K \sigma_\rho^{-2})}} \right\} \geq 1 - \delta. \tag{6}$$

The proof of Theorem 1 builds on two key ideas. First, we exploit the conditional linearity of the submodular objective to bound the cumulative regret defined in Eq. (5) with a sum of per agent regrets.

Secondly, we bound the per agent regret with the information capacity γ^ρ_{KT}, a quantity that measures the largest reduction in uncertainty about the density that can be obtained from KT noisy evaluations of it. Since γ^ρ_{KT} [18] grows sublinearly with T for commonly used kernels, so does MACOPT's regret in Eq. (6). The immediate corollary of the above theorem, when the MACOPT stopping criteria is reached (Line 3 of Algorithm 1) guarantees a near optimal solution up to ϵ_ρ precision.

Corollary 1. *Let $t^\star_\rho$ be the smallest integer, such that $\frac{t^\star_\rho}{\beta_{t^\star_\rho} \gamma_{K t^\star_\rho}} \leq \frac{8K^2}{\log(1+K\sigma^{-2})\epsilon^2_\rho}$, then there exists a*

$t < t^\star_\rho$ such that w.h.p, MACOPT terminates and achieves, $F(X_t; \rho, V) \geq (1 - \frac{1}{e})F(X_\star; \rho, V) - \epsilon_\rho$.

SAFEMAC. This section presents our main result for safety-constrained multi-agent coverage control. In particular, Theorem 2 (proof in Appendix E) guarantees that SAFEMAC safely achieves near-optimal safe coverage in finite time.

Theorem 2. *Let $\delta \in (0,1)$ and β^ρ_t as in [16], i.e., $\beta^{\rho 1/2}_t = B_\rho + 4\sigma_\rho \sqrt{\gamma_{Kt} + 1 + \ln(1/\delta)}$ and and $t^\star_\rho$ be the smallest integer such that $\frac{t^\star_\rho}{\beta_{t^\star_\rho} \gamma_{K t^\star_\rho}} \geq \frac{8K^2}{\log(1+K\sigma^{-2})\epsilon^2_\rho}$. Let β^q_t and $t^\star_q$ be defined analogously. Then, there exists $t < t^\star_q + t^\star_\rho$, such that with probablity at least $1 - \delta$*

$$\sum_{B \in \mathcal{B}_t} F(X^B_t; \rho, \bar{R}_0(X^B_0)) \geq (1 - \frac{1}{e}) \sum_{B \in \mathcal{B}} F(X^B_\star; \rho, \bar{R}_{\epsilon_q}(X^B_0)) - \epsilon_\rho. \tag{7}$$

The theoretical analysis has two components: (*i*) we show SAFEMAC's coverage is near-optimal at convergence (Lemma 9), and (*ii*) we prove it converges in finite time. Since SAFEMAC learns the constraint *and* the density, we must bound the sample complexity for both to prove (*ii*). For the constraint, we extend the results for single-agent GOOSE to our multi-agent setting (Appendix F). For the density, we use results from Theorem 1 to show that, within a coverage phase, the cumulative regret is sublinear. Next, we use additivity of the information gain (Lemma 12) between any pair of coverage phases to bound the sample complexity of density for the subsequent coverage phases. Combining these results, we obtain Theorem 2.

Intermediate recommendation. Theorem 2 guarantees SAFEMAC converges to a safe and near-optimal solution. Can it also make sensible recommendations before the stopping criteria are met? Ideally, such recommendations should (*i*) be safely reachable and (*ii*) ensure a minimum coverage. To satisfy (*i*), they should be in the pessimistic safe set, S^p_t. To satisfy (*ii*), their coverage should be computed according to $F(\cdot; l^\rho_{t-1}, S^p_t)$, i.e., assuming a worst-case density, l^ρ_{t-1}, and a worst-case feasible set, S^p_t. If the greedy recommendation X_t is in S^p_t, we can recommend it at intermediate steps. However, this is not always the case and we need an alternative. To this end, we compute $X^{l,B}_t$, i.e., the greedy solution w.r.t. the worst-case objective, $F(\cdot; l^\rho_{t-1}, S^{p,B}_t) \forall B \in \mathcal{B}^p_t$. At any time T, SAFEMAC recommends the best of either strategy up to time T according to the worst-case objective. In Appendix E.1, we show that such recommendation is also near optimal at convergence.

6 Experiments

This section compares MACOPT and SAFEMAC to existing methods (or their extensions) on synthetic and real-world problems. We validate our theoretical claims and observe their superiority. We set $\beta^q = 3$ and $\beta^\rho = 3$ for all $t \geq 1$, it ensures safety as well as efficient exploration in practice [11]. Experiment details and extended empirical analysis are in Appendix G.

Environments. We perform our experiments with $K = 3$ agents in a 30×30 grid world where states are evenly spaced over $[0,3]^2$. Each agent's disk is defined as the region an agent can reach in $r = 5$ steps in the defined grid. We normalize coverage with a maximum value $\sum_{v \in \bar{R}_0(X_0)} \rho(v)/N$. Below, we present the 3 environments we consider.

i) In *synthetic data*, both the density ρ and the constrain q are sampled from a GP with zero mean and Matérn Kernel with $\nu = 2.5$, scale $\sigma_k = 1$, and lengthscale $l = 2$. The observations are perturbed by i.i.d noise $\mathcal{N}(0, 10^{-3})$. ii) In *obstacles*, we sample maps with several block-shaped obstacles (Fig. 2a) and we aim to maximize coverage while avoiding dangerous collisions. At v, each agent senses the

(a) Obstacles environment   (b) Gorilla nest environment   (c) Coverage on gorilla nests (Sunny day)

Figure 2: The contours in: a) show the synthetic density and the obstacles marked by the black blocks, b) show the Gorilla nests distribution with weather constraints marked by the black dashed line, and its contours with grey dashed line. c) Compares MACOPT with UCB in the safe gorilla environment.

distance to the nearest obstacle $d_m(v)$, which could be given by sensors such 1D-Lidars. We use $q'(v) = 1/(1 + \exp(-1.5d_m(v)))$, to map the distance between $[0, 3]$ and saturate the constraint value for large distances, and we set $q(v) = q'(v) - 0.5$ to avoid collisions. The density is sampled from the same GP as the synthetic case. iii) In *gorilla nest*, we simulate a bio-diversity monitoring task, where we aim to cover areas with high density of gorilla nests with a quadrotor in the Kagwene Gorilla Sanctuary (Fig. 2b) . Regions affected by adverse weather (e.g. rain and storms) are unsafe for the drone due to higher chances of crashes and should be avoided. As a proxy for bad weather, we use the cloud coverage data over the KGS from OpenWeather [19]. The nest density is obtained by fitting a smooth rate function [20] over Gorilla nest counts [21].

MACOPT. We compare MACOPT to UCB, a baseline that skips the uncertainty sampling step from Section 4.1 and obtains measurements at locations as per GREEDY sensing region.Fig. 2c shows comparison in the *gorilla* environment on a day of good weather, i.e., when everywhere is safe. We see that UCB gets stuck in a local optimum as it does not reduce the uncertainty of the density, whereas MACOPT explores more and achieves a higher coverage value.

SAFEMAC. We compare SAFEMAC with two baselines, i) a two-stage algorithm [22], that first fully explores the feasible region, and then uses MACOPT to maximize the coverage ii) PASSIVEMAC, a baseline inspired by [23] that runs MACOPT in the pessimistic set and passively measures the constraint in the process. Figs. 3a and 3b show the coverage at convergence and the number of samples to converge for SAFEMAC and the two baselines across all the environments. PASSIVEMAC converges quickly but gets stuck in a local optimum as it does not actively explore the constraint. SAFEMAC and Two-Stage converge to much higher coverage values. However, SAFEMAC is more sample efficient thanks to its goal-oriented exploration. The results are averaged over 50 instances produced using different seeds and samples for every environment. Fig. 3c shows the coverage value of the intermediate safe recommendations (Section 5) in the *gorilla* environment as a function of the number of samples. It confirms the previous results: SAFEMAC finds solutions comparable to Two-Stage more efficiently and PASSIVEMAC gets stuck in a local optimum.

7 Related work

Our work is at the intersection of multiple fields. This section highlights the most relevant connections to them but is not an exhaustive overview (we reference surveys whenever possible).

Bayesian optimization. In BO, an agent evaluates an objective at a sequence of inputs to maximize it [24]. In contrast, in our setting the quantity we measure differs from our objective. Partial monitoring [25] addresses this kind of issues with randomized algorithms rooted in information theory [26, 27]. In coverage control with unknown density, this challenge is often addressed by learning the density uniformly over the domain [28, 29]. In contrast, MACOPT learns the density only at promising locations.

Coverage control. MAC with known densities is a well-studied NP hard [30] problem. Many algorithms use efficient heuristics to converge quickly to a local optimum. One popular strategy is Lloyd's

(a) Coverage at convergence   (b) Total number of samples   (c) Coverage on Gorilla nests (Rainy day)

Figure 3: Comparison of SAFEMAC with PASSIVEMAC and Two-Stage in all environments at convergence (a) and (b) and during optimization for the gorilla environment in (c).

algorithm [31], which has been studied in different settings, e.g., with known densities [32, 33], *a-priori* unknown densities [29, 34–36], taking into account agent's dynamics and constraints [37], or in case of non-identical robots [38]. These methods apply to continuous state and action space and show convergence to a local optimum but lack optimality guarantees [28, 29, 37] and do not provide sample complexity bounds. Moreover, their extension to non-convex, disconnected domains is not trivial [39].

Submodular optimization. Submodular functions are ubiquitous in machine learning [40] as they can be efficiently approximately maximized under different kinds of constraints [41]. For example, the GREEDY algorithm can be used in case of cardinality constraints [12], which capture problems like mutual information [42] or weighted coverage maximization [43]. Online submodular maximization aims at optimizing unknown submodular functions from noisy measurements. It has multipls applications, including optimization of numerical solvers [44] and information gathering [45]. Particularly related to ours is the work in [46], which proposes an algorithm for contextual news recommendation for linear user preferences with strong regret guarantees. In contrast to that setting, we consider dynamic agents and have access to partial feedback.

Safety. Depending on the safety formulation and the assumptions, many algorithms have been proposed for safe learning in dynamical systems, e.g., based on model predictive control [47], curriculum learning [48], Lyapunov functions [49, 50], reachability [51], CMDPs [52], behavioral system theory [53], and more [54–56]. Here, we focus on the setting that is most closely related to ours, i.e., one with unknown but sufficiently regular instantaneous constraints that must be satisfied at all times. For stateless problems, e.g. BO, [23, 57] propose algorithms with safety and optimality guarantees with different exploration strategies. For stateful problems, [58] studies the pure exploration case, while [22] extends the two-stage approach from [57]. All these approaches may be sample inefficient as they may explore the constraint in regions that are not relevant for the objective. GOOSE [11] addresses this problem for both the stateful and stateless setting. The only work in this context that addresses multi-agent problems is [59]. However, they have a different objective from ours and do not have safety guarantees.

8 Conclusion

We present two novel algorithms for multi-agent coverage control in unconstrained (MACOPT) and safety critical environments (SAFEMAC). We show MACOPT achieves sublinear cumulative regret, despite the challenge of partial observability. Moreover, we prove SAFEMAC achieves near optimal coverage in finite time while navigating safely. We demonstrate the superiority of our algorithms in terms of sample efficiency and coverage in real-world applications such as safe biodiversity monitoring.

Currently, our algorithms choose informative targets but do not plan informative trajectories, which is crucial in robotics. We aim to address this in future work. Finally, while in many real-world applications the density and the constraints are as regular as assumed here, in some they are not. In these cases, our optimality and safety guarantees would not apply.

References

[1] Miquel Kegeleirs, Giorgio Grisetti, and Mauro Birattari. Swarm slam: Challenges and perspectives. *Frontiers in Robotics and AI*, 8, 2021. ISSN 2296-9144. doi: 10.3389/frobt.2021.618268. URL https://www.frontiersin.org/article/10.3389/frobt.2021.618268.

[2] Alan Mainwaring, David Culler, Joseph Polastre, Robert Szewczyk, and John Anderson. Wireless sensor networks for habitat monitoring. In *Proceedings of the 1st ACM International Workshop on Wireless Sensor Networks and Applications*, WSNA '02, page 88–97, New York, NY, USA, 2002. Association for Computing Machinery. ISBN 1581135890. doi: 10.1145/570738.570751. URL https://doi.org/10.1145/570738.570751.

[3] Mahmoud Tavakoli, Gonçlo Cabrita, Ricardo Faria, Lino Marques, and Anibal T. de Almeida. Cooperative multi-agent mapping of three-dimensional structures for pipeline inspection applications. *The International Journal of Robotics Research*, 31(12):1489–1503, 2012. doi: 10.1177/0278364912461536. URL https://doi.org/10.1177/0278364912461536.

[4] Bang Wang. *Coverage Control in Sensor Networks*. Springer Publishing Company, Incorporated, 1st edition, 2010. ISBN 1849960585.

[5] Ryan Lowe, Yi Wu, Aviv Tamar, Jean Harb, Pieter Abbeel, and Igor Mordatch. Multi-agent actor-critic for mixed cooperative-competitive environments. *CoRR*, abs/1706.02275, 2017. URL http://arxiv.org/abs/1706.02275.

[6] Iou-Jen Liu, Unnat Jain, Raymond A Yeh, and Alexander Schwing. Cooperative exploration for multi-agent deep reinforcement learning. In *International Conference on Machine Learning*, pages 6826–6836. PMLR, 2021.

[7] Pericle Salvini, Diego Paez Granados, and Aude Billard. Safety concerns emerging from robots navigating in crowded pedestrian areas. *International Journal of Social Robotics*, 14, 03 2022. doi: 10.1007/s12369-021-00796-4.

[8] Yuliya Averyanova and E. Znakovskaja. Weather hazards analysis for small uass durability enhancement. In *2021 IEEE 6th International Conference on Actual Problems of Unmanned Aerial Vehicles Development (APUAVD)*, pages 41–44, 2021. doi: 10.1109/APUAVD53804.2021.9615440.

[9] Mozhou Gao, Chris H Hugenholtz, Thomas A Fox, Maja Kucharczyk, Thomas E Barchyn, and Paul R Nesbit. Weather constraints on global drone flyability. *Scientific reports*, 11(1):1–13, 2021.

[10] Andreas Krause and Carlos Guestrin. Submodularity and its applications in optimized information gathering. *ACM Trans. Intell. Syst. Technol.*, 2(4), jul 2011. ISSN 2157-6904. doi: 10.1145/1989734.1989736. URL https://doi.org/10.1145/1989734.1989736.

[11] Matteo Turchetta, Felix Berkenkamp, and Andreas Krause. Safe exploration for interactive machine learning, 2019.

[12] George Nemhauser, Laurence Wolsey, and M. Fisher. An analysis of approximations for maximizing submodular set functions. *Mathematical Programming*, 14:265–294, 12 1978. doi: 10.1007/BF01588971.

[13] Jure Leskovec, Andreas Krause, Carlos Guestrin, Christos Faloutsos, Jeanne VanBriesen, and Natalie Glance. Cost-effective outbreak detection in networks. In *Proceedings of the 13th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, KDD '07, page 420–429, New York, NY, USA, 2007. Association for Computing Machinery. ISBN 9781595936097. doi: 10.1145/1281192.1281239. URL https://doi.org/10.1145/1281192.1281239.

[14] Bernhard Schlkopf, Alexander J. Smola, and Francis Bach. *Learning with Kernels: Support Vector Machines, Regularization, Optimization, and Beyond*. The MIT Press, 2018. ISBN 0262536579.

[15] Carl Edward Rasmussen and Christopher K. I. Williams. *Gaussian Processes for Machine Learning (Adaptive Computation and Machine Learning)*. The MIT Press, 2005. ISBN 026218253X.

[16] Sayak Ray Chowdhury and Aditya Gopalan. On kernelized multi-armed bandits. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 844–853. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/chowdhury17a.html`.

[17] Niranjan Srinivas, Andreas Krause, Sham M. Kakade, and Matthias W. Seeger. Information-theoretic regret bounds for gaussian process optimization in the bandit setting. *IEEE Transactions on Information Theory*, 58(5):3250–3265, 2012. doi: 10.1109/TIT.2011.2182033.

[18] Sattar Vakili, Kia Khezeli, and Victor Picheny. On information gain and regret bounds in gaussian process bandits. In Arindam Banerjee and Kenji Fukumizu, editors, *Proceedings of The 24th International Conference on Artificial Intelligence and Statistics*, volume 130 of *Proceedings of Machine Learning Research*, pages 82–90. PMLR, 13–15 Apr 2021. URL `https://proceedings.mlr.press/v130/vakili21a.html`.

[19] Open weather. `https://openweathermap.org/`.

[20] Mojmír Mutný and Andreas Krause. Sensing cox processes via posterior sampling and positive bases. *CoRR*, abs/2110.11181, 2021. URL `https://arxiv.org/abs/2110.11181`.

[21] Neba Funwi-gabga and Jorge Mateu. Understanding the nesting spatial behaviour of gorillas in the kagwene sanctuary, cameroon. *Stochastic Environmental Research and Risk Assessment*, 26, 08 2011. doi: 10.1007/s00477-011-0541-1.

[22] Akifumi Wachi and Yanan Sui. Safe reinforcement learning in constrained markov decision processes. In *ICML*, pages 9797–9806, 2020. URL `http://proceedings.mlr.press/v119/wachi20a.html`.

[23] Yanan Sui, Alkis Gotovos, Joel Burdick, and Andreas Krause. Safe exploration for optimization with gaussian processes. In Francis Bach and David Blei, editors, *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pages 997–1005, Lille, France, 07–09 Jul 2015. PMLR. URL `https://proceedings.mlr.press/v37/sui15.html`.

[24] Bobak Shahriari, Kevin Swersky, Ziyu Wang, Ryan P. Adams, and Nando de Freitas. Taking the human out of the loop: A review of bayesian optimization. *Proceedings of the IEEE*, 104 (1):148–175, 2016. doi: 10.1109/JPROC.2015.2494218.

[25] Tor Lattimore and Csaba Szepesvári. *Partial Monitoring*, page 423–451. Cambridge University Press, 2020. doi: 10.1017/9781108571401.046.

[26] Tor Lattimore and Csaba Szepesvári. An information-theoretic approach to minimax regret in partial monitoring. In *Conference on Learning Theory*, pages 2111–2139. PMLR, 2019.

[27] Johannes Kirschner, Tor Lattimore, and Andreas Krause. Information directed sampling for linear partial monitoring. In *Conference on Learning Theory*, pages 2328–2369. PMLR, 2020.

[28] Lai Wei, Andrew McDonald, and Vaibhav Srivastava. Regret analysis of distributed gaussian process estimation and coverage. *CoRR*, abs/2101.04306, 2021. URL `https://arxiv.org/abs/2101.04306`.

[29] Andrea Carron, Marco Todescato, Ruggero Carli, Luca Schenato, and Gianluigi Pillonetto. Multi-agents adaptive estimation and coverage control using gaussian regression. In *2015 European Control Conference (ECC)*, pages 2490–2495, 2015. doi: 10.1109/ECC.2015.7330912.

[30] Andreas Krause, Ajit Singh, and Carlos Guestrin. Near-optimal sensor placements in gaussian processes: Theory, efficient algorithms and empirical studies. *J. Mach. Learn. Res.*, 9:235–284, jun 2008. ISSN 1532-4435.

[31] S. Lloyd. Least squares quantization in pcm. *IEEE Transactions on Information Theory*, 28(2): 129–137, 1982. doi: 10.1109/TIT.1982.1056489.

[32] Jorge Cortes, Sonia Martinez, Timur Karatas, and Francesco Bullo. Coverage control for mobile sensing networks. *IEEE Transactions on robotics and Automation*, 20(2):243–255, 2004.

[33] Francois Lekien and Naomi Ehrich Leonard. Nonuniform coverage and cartograms. *SIAM Journal on Control and Optimization*, 48(1):351–372, 2009. doi: 10.1137/070681120. URL https://doi.org/10.1137/070681120.

[34] Yunfei Xu and Jongeun Choi. Adaptive sampling for learning gaussian processes using mobile sensor networks. *Sensors (Basel, Switzerland)*, 11:3051–66, 12 2011. doi: 10.3390/s110303051.

[35] Wenhao Luo and Katia Sycara. Adaptive sampling and online learning in multi-robot sensor coverage with mixture of gaussian processes. pages 6359–6364, 05 2018. doi: 10.1109/ICRA. 2018.8460473.

[36] Alessia Benevento, María Santos, Giuseppe Notarstefano, Kamran Paynabar, Matthieu Bloch, and Magnus Egerstedt. Multi-robot coordination for estimation and coverage of unknown spatial fields. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 7740–7746, 2020. doi: 10.1109/ICRA40945.2020.9197487.

[37] Andrea Carron and Melanie N. Zeilinger. Model predictive coverage control∗∗this work was supported by the swiss national centre of competence in research nccr digital fabrication, and by the eth career seed grant 19-18-2. *IFAC-PapersOnLine*, 53(2):6107–6112, 2020. ISSN 2405-8963. doi: https://doi.org/10.1016/j.ifacol.2020.12.1686. URL https://www.sciencedirect.com/science/article/pii/S2405896320322898. 21st IFAC World Congress.

[38] Soobum Kim, María Santos, Luis Guerrero-Bonilla, Anthony Yezzi, and Magnus Egerstedt. Coverage control of mobile robots with different maximum speeds for time-sensitive applications. *IEEE Robotics and Automation Letters*, 7(2):3001–3007, 2022. doi: 10.1109/LRA.2022. 3146593.

[39] Francesco Bullo, Ruggero Carli, and Paolo Frasca. Gossip coverage control for robotic networks: Dynamical systems on the space of partitions. *SIAM Journal on Control and Optimization*, 50 (1):419–447, 2012.

[40] Jeff Bilmes. Submodularity in machine learning and artificial intelligence. *arXiv preprint arXiv:2202.00132*, 2022.

[41] Andreas Krause and Daniel Golovin. Submodular function maximization. *Tractability*, 3: 71–104, 2014.

[42] Andreas Krause and Carlos Guestrin. Near-optimal nonmyopic value of information in graphical models. In *Proceedings of the Twenty-First Conference on Uncertainty in Artificial Intelligence*, UAI'05, page 324–331. AUAI Press, 2005. ISBN 0974903914.

[43] Uriel Feige. A threshold of ln n for approximating set cover. *J. ACM*, 45(4):634–652, jul 1998. ISSN 0004-5411. doi: 10.1145/285055.285059. URL https://doi.org/10.1145/285055. 285059.

[44] Matthew Streeter, Daniel Golovin, and Stephen F Smith. Combining multiple heuristics online. In *AAAI*, pages 1197–1203, 2007.

[45] Daniel Golovin, Andreas Krause, and Matthew Streeter. Online submodular maximization under a matroid constraint with application to learning assignments. *arXiv preprint arXiv:1407.1082*, 2014.

[46] Yisong Yue and Carlos Guestrin. Linear submodular bandits and their application to diversified retrieval. In J. Shawe-Taylor, R. Zemel, P. Bartlett, F. Pereira, and K.Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 24. Curran Associates, Inc., 2011. URL `https://proceedings.neurips.cc/paper/2011/file/33ebd5b07dc7e407752fe773eed20635-Paper.pdf`.

[47] Lukas Hewing, Kim P Wabersich, Marcel Menner, and Melanie N Zeilinger. Learning-based model predictive control: Toward safe learning in control. *Annual Review of Control, Robotics, and Autonomous Systems*, 3:269–296, 2020.

[48] Matteo Turchetta, Andrey Kolobov, Shital Shah, Andreas Krause, and Alekh Agarwal. Safe reinforcement learning via curriculum induction. *Advances in Neural Information Processing Systems*, 33:12151–12162, 2020.

[49] Felix Berkenkamp, Matteo Turchetta, Angela Schoellig, and Andreas Krause. Safe model-based reinforcement learning with stability guarantees. *Advances in neural information processing systems*, 30, 2017.

[50] Yinlam Chow, Ofir Nachum, Edgar Duenez-Guzman, and Mohammad Ghavamzadeh. A lyapunov-based approach to safe reinforcement learning. *Advances in neural information processing systems*, 31, 2018.

[51] Jaime F Fisac, Anayo K Akametalu, Melanie N Zeilinger, Shahab Kaynama, Jeremy Gillula, and Claire J Tomlin. A general safety framework for learning-based control in uncertain robotic systems. *IEEE Transactions on Automatic Control*, 64(7):2737–2752, 2018.

[52] Joshua Achiam, David Held, Aviv Tamar, and Pieter Abbeel. Constrained policy optimization. In *International conference on machine learning*, pages 22–31. PMLR, 2017.

[53] Jeremy Coulson, John Lygeros, and Florian Dorfler. Distributionally robust chance constrained data-enabled predictive control. *IEEE Transactions on Automatic Control*, 2021.

[54] Lukas Brunke, Melissa Greeff, Adam W Hall, Zhaocong Yuan, Siqi Zhou, Jacopo Panerati, and Angela P Schoellig. Safe learning in robotics: From learning-based control to safe reinforcement learning. *Annual Review of Control, Robotics, and Autonomous Systems*, 5, 2021.

[55] Alex Ray, Joshua Achiam, and Dario Amodei. Benchmarking safe exploration in deep reinforcement learning. *arXiv preprint arXiv:1910.01708*, 7:1, 2019.

[56] Jan Leike, Miljan Martic, Victoria Krakovna, Pedro A Ortega, Tom Everitt, Andrew Lefrancq, Laurent Orseau, and Shane Legg. Ai safety gridworlds. *arXiv preprint arXiv:1711.09883*, 2017.

[57] Yanan Sui, Vincent Zhuang, Joel W. Burdick, and Yisong Yue. Stagewise safe bayesian optimization with gaussian processes, 2018. URL `https://arxiv.org/abs/1806.07555`.

[58] Matteo Turchetta, Felix Berkenkamp, and Andreas Krause. Safe exploration in finite markov decision processes with gaussian processes. *Advances in Neural Information Processing Systems*, 29, 2016.

[59] Zheqing Zhu, Erdem Bıyık, and Dorsa Sadigh. Multi-agent safe planning with gaussian processes. In *International Conference on Intelligent Robots and Systems (IROS)*, pages 6260–6267, 10 2020. doi: 10.1109/IROS45743.2020.9341169.