Concrete Score Matching: Generalized Score Matching for Discrete Data

Abstract

Representing probability distributions by the gradient of their density functions has proven effective in modeling a wide range of continuous data modalities. However, this representation is not applicable in discrete domains where the gradient is undefined. To this end, we propose an analogous score function called the "Concrete score", a generalization of the (Stein) score for discrete settings. Given a predefined neighborhood structure, the Concrete score of any input is defined by the rate of change of the probabilities with respect to local directional changes of the input. This formulation allows us to recover the (Stein) score in continuous domains when measuring such changes by the Euclidean distance, while using the Manhattan distance leads to our novel score function in discrete domains. Finally, we introduce a new framework to learn such scores from samples called Concrete Score Matching (CSM), and propose an efficient training objective to scale our approach to high dimensions. Empirically, we demonstrate the efficacy of CSM on density estimation tasks on a mixture of synthetic, tabular, and high-dimensional image datasets, and demonstrate that it performs favorably relative to existing baselines for modeling discrete data.

1 Introduction

When estimating a statistical model, the representation of the underlying probability distribution has profound implications on the downstream modeling task. Likelihood-based model families such as Variational Autoencoders (VAEs) [1, 2, 3, 4], normalizing flows [5, 6, 7, 8, 9, 10], and diffusion models [11, 12, 13] are forced to either approximate the intractable normalizing constant or utilize restrictive model architectures; implicit models [14, 15, 16, 17] try to capture the underlying sampling process by relying on unstable adversarial training procedures. On the other hand, representing the distribution as the gradient of the log probability density function—also known as the (Stein) score—allows us to circumvent such issues. This is key to score matching's success on a wide range of continuous data modalities [18, 19, 20]. In fact, its recent resurgence has led to significant advances in machine learning applications of density estimation, such as image generation [21, 13] and audio synthesis [22, 23], among others.

However, score matching approaches that rely on modeling the gradient of the data distribution are inherently designed for continuous data; such methods hinge on the *existence* of the gradient, which is undefined for discrete domains [19]. Given the ubiquitous nature of structured, discrete data in our world today such as graphs, text, genomic sequences, images, we desire an approach that would allow us to expand the successes of score-based generative models into discrete domains.

To address this challenge, we first introduce the Concrete score: a generalization of the (Stein) score that is amenable to both continuous and discrete data types[1]. Given a predefined neighborhood structure, the Concrete score leverages structural information in the data to construct *surrogate gradient information* about the discrete space by considering the similarity between two neighboring examples. More precisely, the Concrete score of any input is defined by the rate of change of the probabilities with respect to directional changes of the input. In direct analogy to the continuous (Stein) score, the intuition is that the Concrete score should remain small when two examples are "close" to one another; when the two examples are very different, the Concrete score will be large. We find that measuring such changes by the Euclidean distance recovers the (Stein) score in continuous domains, while using the Manhattan distance leads to our novel score function in discrete domains.

Using this definition of the Concrete score, we then introduce a framework to learn such scores from samples called Concrete Score Matching (CSM). To successfully scale our method to high dimensions, we also propose an efficient training objective as well as several variations of our approach that improve performance in practice. Empirically, we demonstrate the efficacy of CSM on a wide range of density estimation tasks on a mixture of synthetic, tabular, and high-dimensional image datasets, and demonstrate that it performs favorably relative to existing baselines for discrete data.

The contributions of our work can be summarized as follows:

1. We propose the Concrete score, a generalization of the (Stein) score to discrete domains. We construct the Concrete score such that it leverages structural information in the data to capture surrogate "gradient" information over discrete spaces.

2. We introduce a novel score matching framework for estimating such scores from samples called Concrete Score Matching (CSM). We then outline several connections between CSM and existing (continuous) score matching techniques, such denoising score matching (DSM).

3. We propose efficient learning objectives that allow our method to scale gracefully to high-dimensional datasets, and show how to port over the recent successes in continuous score matching approaches to discrete domains.

2 Preliminaries

Let $p_{\mathrm{data}}(\mathbf{x})$ be the unknown data distribution over $\mathcal{X} \in \mathbb{R}^D$, for which we have access to i.i.d. samples $\{\mathbf{x}_i\}_{i=1}^N \sim p_{\mathrm{data}}(\mathbf{x})$. The (Stein) score of $p_{\mathrm{data}}(\mathbf{x})$ is the first order derivative of the log data density function $\boldsymbol{s}(\mathbf{x}) = \nabla_{\mathbf{x}} \log p(\mathbf{x})$. The goal of score matching is to learn an unnormalized density $q_\theta(\mathbf{x})$ indexed by $\theta \in \Theta$ such that the estimated score function $\boldsymbol{s}_\theta(\mathbf{x}) = \nabla_{\mathbf{x}} \log q_\theta(\mathbf{x})$ is close to $\boldsymbol{s}(\mathbf{x})$.

In practice, we leverage a *score network* $\boldsymbol{s}_\theta : \mathbb{R}^D \to \mathbb{R}^D$ that is trained to minimize the Fisher divergence between $q_\theta(\mathbf{x})$ and $p_{\mathrm{data}}(\mathbf{x})$ [20, 21]. Although the original objective is intractable to compute due to its dependence on the ground truth data scores $\boldsymbol{s}(\mathbf{x})$, we can leverage integration by parts [18] to simplify the objective as follows:

$$\mathcal{J}_{SM}(\theta) = \mathbb{E}_{p_{\mathrm{data}}(\mathbf{x})} \left[\frac{1}{2} \|\boldsymbol{s}_\theta(\mathbf{x})\|_2^2 + \mathrm{tr}(\nabla_{\mathbf{x}} \boldsymbol{s}_\theta(\mathbf{x})) \right] + \mathrm{const.} \tag{1}$$

where $\mathrm{tr}(\cdot)$ denotes the matrix trace, and the optimal score model satisfies $\boldsymbol{s}_{\theta^*}(\mathbf{x}) \approx \boldsymbol{s}(\mathbf{x})$. While the trace term in Eq. 1 remains problematic—it requires an expensive evaluation of the Hessian of the log-density function—recent works [20, 13] leverage the Skilling-Hutchinson trace estimator [25, 26] or directional derivatives [27] to efficiently approximate the training objective.

Despite their key role in successfully scaling score-based generative models to high-dimensional datasets, we note two critical limitations of existing score matching techniques: (1) $\mathcal{X}$ must be continuous; and (2) the density function $p_{\mathrm{data}}(\mathbf{x})$ must be differentiable. This poses a significant challenge in discrete domains, where both requirements break down.

3 The Concrete Score

The above limitations prevent the direct application of score matching techniques to discrete data. We thus propose the Concrete score, a generalization of the (Stein) score for discrete settings. The

---

[1]We borrow the terminology from "concrete mathematics" [24].

key intuition is that although the gradient is undefined in discrete spaces, we can still construct a *surrogate* for the gradient by leveraging local directional changes to the input. We do so by exploiting special neighborhood structures in the data, and elaborate upon the necessary conditions on these structures to guarantee that our surrogate gradient indeed recovers a valid score function that (1) completely characterizes the distribution, and (2) is amenable for parameter estimation.

3.1 Constructing Surrogate Gradients for Discrete Data

To be more precise, let $p_{\text{data}}(\mathbf{x})$ be the data distribution over $\mathcal{X}$. We denote $\mathcal{N} : \mathcal{X} \to \mathcal{X}^K$ as the function mapping each example $\mathbf{x} \in \mathcal{X}$ to a set of neighbors, such that $\mathcal{N}(\mathbf{x}) = \{\mathbf{x}_{n_1}, ..., \mathbf{x}_{n_k}\}$ and $K = |\mathcal{N}(\mathbf{x})|$ [2]. This neighborhood induces a particular graphical structure onto the support of $p_{\text{data}}(\mathbf{x})$, which we call the "neighborhood-induced graph", that will play a key role in constructing the surrogate gradient. We provide a formal definition below.

Definition 1 (Neighborhood-induced graph). *Let $p_{\text{data}}(\mathbf{x})$ be the data distribution over $\mathcal{X}$ and $\mathcal{N}$ be the function mapping each node $\mathbf{x} \in \mathcal{X}$ to its set of neighbors. The neighborhood-induced graph $\mathcal{G}$ is the directed graph which results from adding a directed edge from $\mathbf{x}$ to each node in its neighborhood set $\mathbf{x}_n \in \mathcal{N}(\mathbf{x})$, for all $\mathbf{x} \in \text{supp}(\text{p}_{\text{data}}(\mathbf{x}))$.*

An important point is that the neighborhood structure can be asymmetric, since the neighborhood-induced graph is a directed graph. This implies that there may exist cases where $\mathcal{N}(\mathbf{x}) = \{\mathbf{x}_1\}$ does not necessarily imply that $\mathcal{N}(\mathbf{x}_1) = \{\mathbf{x}\}$. We provide an intuitive example below.

Example 1. *When $\mathcal{X} = \{\mathbf{x}_0, \mathbf{x}_1, \ldots, \mathbf{x}_5\}$, and the neighborhood structure $\mathcal{N}$ is defined as: $\mathcal{N}(\mathbf{x}_0) = \{\emptyset\}$ and $\mathcal{N}(\mathbf{x}_i) = \{\mathbf{x}_0\} \; \forall i = 1, \ldots, 5$, the neighborhood-induced graph is the star graph in Figure 1.*

There exist a wide range of neighborhood structures, all of which yield different neighborhood-induced graphs. We visualize five common structures in Figure 1.

| Star | Complete graph | Single bit flip | Chain | Grid |

Figure 1: Examples of common neighborhood structures and their corresponding (connected) neighborhood-induced graphs, where the arrows point to the neighbors of a given node. Note that the neighborhood structure is directed.

Such graphs provide insight into the kinds of neighborhood structures that are amenable to our framework. One necessary characteristic of such graphs is *connectedness*. In fact, the five common graphical structures (among others) shown in Figure 1 are all weakly connected graphs. We emphasize that connectedness does not take the directionality of the underlying graph $\mathcal{G}$'s edges into account—it does not matter whether a node $\mathbf{x}$ has an incoming or outgoing edge.

With the above definitions in place, we can now define the surrogate gradient as the local differences between a set of examples (similar to directional derivative in the continuous case). Using this notion of the "gradient", we construct the Concrete score as the rate of change of the probabilities with respect to these local directional changes in the input $\mathbf{x}$ as defined below.

Definition 2 (Concrete score). *Let $\mathcal{N}$ be a function mapping each point $\mathbf{x}$ to its set of neighbors $\mathcal{N}(\mathbf{x}) = \{\mathbf{x}_{n_1}, ..., \mathbf{x}_{n_k}\}$. Then, the Concrete score $\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N}) : \mathcal{X} \to \mathbb{R}^{|\mathcal{N}(\mathbf{x})|}$ for a given distribution $p_{\text{data}}(\mathbf{x})$ evaluated at $\mathbf{x}$ is:*

$$\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N}) \triangleq \left[\frac{p_{\text{data}}(\mathbf{x}_{n_1}) - p_{\text{data}}(\mathbf{x})}{p_{\text{data}}(\mathbf{x})}, ..., \frac{p_{\text{data}}(\mathbf{x}_{n_k}) - p_{\text{data}}(\mathbf{x})}{p_{\text{data}}(\mathbf{x})} \right]^T. \tag{2}$$

---

[2] We consider a fixed number of neighbors K for each $\mathbf{x}$ to simplify our notation, but note that this can be generalized to a variable number of neighbors for every $\mathbf{x}$.

Although we have defined the Concrete score, we have yet to justify whether it is indeed a suitable score function for estimating $p_{\text{data}}(\mathbf{x})$. The necessary condition, which we call *completeness* [28], ensures that the Concrete score preserves enough information about $p_{\text{data}}(\mathbf{x})$ such that we can successfully learn $p_{\text{data}}(\mathbf{x})$ from data samples using score matching. We make this statement more precise in the following theorem.

Theorem 1 (Completeness). *Let $p_{\text{data}}(\mathbf{x})$ be a (discrete) data distribution. Denote $\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$ as the Concrete score of $p_{\text{data}}(\mathbf{x})$ with neighboring structure $\mathcal{N}$, and $\boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})$ the Concrete score for a distribution $p_\theta(\mathbf{x})$ parameterized by $\theta \in \Theta$. When the graph induced by the neighborhood structure $\mathcal{N}$ is connected, $c_\theta(\mathbf{x}; \mathcal{N}) = \boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$ implies that $p_\theta(\mathbf{x}) = p_{\text{data}}(\mathbf{x}) \; \forall \mathbf{x} \in \mathcal{X}$.*

Proof sketch. If two nodes $\mathbf{x}$ and $\mathbf{x}'$ in a neighborhood-induced graph $\mathcal{G}$ share an edge, then their density ratio $p_{\text{data}}(\mathbf{x}')/p_{\text{data}}(\mathbf{x})$ can be uniquely identified using $\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$. Thus when $\mathcal{G}$ is connected, the density ratio between any node pairs in $\mathcal{G}$ is uniquely identified given $\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$. Therefore, knowing the density ratio between any two points uniquely identifies $p_{\text{data}}(\mathbf{x})$. $\qquad\square$

We provide the full proof in Appendix B. We emphasize here that the connectedness of the neighborhood-induced graph (a kind of regularity condition on $\mathcal{N}$ and $p_{\text{data}}(\mathbf{x})$) was crucial for demonstrating the completness of the Concrete score.

Note that Theorem 1 only requires the neighborhood-induced graph to be connected. This implies that given a connected graph, we can augment it with additional edges—the new graph will still remain complete, but contain additional information in the augmented neighborhood structure that may help parameter estimation in practice. This is a phenomenon that we observe empirically in Section 5.3.

3.2 Connection to Stein Scores and Existing Score Matching Techniques

The form of the Concrete score in Eq. 2 suggests a natural connection with the Stein score in continuous domains. In the following proposition, we illustrate the connection between the two when we define the neighborhood structure to be similar to the grid in Figure 1. In particular, as the distance between neighboring nodes shrinks to zero, our Concrete score converges to the Stein score up to a multiplicative constant.

Proposition 1. *For $\mathbf{x} \in \mathbb{R}^D$, $p(\mathbf{x}) \in \mathcal{P}(\mathbb{R}^D)$, and $\delta > 0$, let the neighborhood structure $\mathcal{N}_\delta(\mathbf{x}) = \{\mathbf{x} + \delta \boldsymbol{e}_i\}_{i=1}^D$. Then, we have:*

$$\lim_{\delta \to 0} \frac{\boldsymbol{c}_p(\mathbf{x}; \mathcal{N}_\delta)}{\delta} = \nabla_\mathbf{x} \log p(\mathbf{x}). \tag{3}$$

We note that while from this perspective the Concrete score can be seen as a finite-difference approximation to the continuous (Stein) score, CSM is different from finite difference score matching (FD-SM) [27]. We introduce a new family of score functions generalizable to discrete domains in the form of $(p(\mathbf{x} + \mathbf{v}) - p(\mathbf{x}))/p(\mathbf{x})$, where $\mathbf{v}$ is the direction from $\mathbf{x}$ pointing to its neighbor with length δ. On the other hand, FD-SM still attempts to match the Stein score, and approximates directional derivatives with finite difference using two neighbors in the form of $\log p(\mathbf{x} + \mathbf{v}) - \log p(\mathbf{x} - \mathbf{v})$. Nevertheless, the differences between the two forms are $o(\delta)$ as $\delta \to 0$.

3.3 Inference with Concrete Scores

To perform inference, we note that there exist several ways to define Markov Chain Monte Carlo (MCMC) samplers that only rely on the Concrete score—we highlight the simplest setting of Metropolis-Hastings [29, 30, 31] for clarity of exposition. We first note that, by definition:

$$\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N}) + \mathbf{1} = \left[\frac{p_{\text{data}}(\mathbf{x}_{n_1})}{p_{\text{data}}(\mathbf{x})}, ..., \frac{p_{\text{data}}(\mathbf{x}_{n_k})}{p_{\text{data}}(\mathbf{x})} \right]^T \tag{4}$$

This implies that we can obtain the density ratios between the neighboring pairs $p_{\text{data}}(\mathbf{x}_{n_1})/p_{\text{data}}(\mathbf{x})$ and $p_{\text{data}}(\mathbf{x})/p_{\text{data}}(\mathbf{x}_{n_1})$ given the Concrete score. Given a proposal distribution q, our sampler will accept the proposed update $\mathbf{x}'$ with acceptance probability $A(\mathbf{x}'|\mathbf{x}) = \min\left(1, \frac{p_{\text{data}}(\mathbf{x}')q(\mathbf{x}|\mathbf{x}')}{p_{\text{data}}(\mathbf{x})q(\mathbf{x}'|\mathbf{x})}\right)$. Specifically, we can choose q to sample uniformly among $\mathcal{N}(\mathbf{x})$ given a particular $\mathbf{x}$. When the neighborhood structure is symmetric, this selection leads to a simplified acceptance probability $A(\mathbf{x}'|\mathbf{x}) =$

$\min \left(1, \frac{p_{\text{data}}(\mathbf{x}')}{p_{\text{data}}(\mathbf{x})}\right)$. We note that when the underlying graph is connected, the chain is aperiodic (due to the presence of a rejection step), irreducible, and positive recurrent (since there is a finite number of discrete states), so the Markov chain is guaranteed to converge in the limit to the model distribution.

4 Learning Concrete Scores with Concrete Score Matching

4.1 The Concrete Score Matching Objective

Next, under the assumption that $\mathcal{N}$ induces a weakly connected graph over the support of $p_{\text{data}}(\mathbf{x})$, we propose a new score matching framework called Concrete Score Matching (CSM) for estimating Concrete scores from data samples. To do so, we estimate $\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$ with a score model $\boldsymbol{c}_\theta(\cdot; \mathcal{N})$: $\mathbb{R}^D \to \mathbb{R}^{|\mathcal{N}(\mathbf{x})|}$, where $|\mathcal{N}(\mathbf{x})|$ denotes the size of the neighborhood of $\mathbf{x}$. Our proposed training objective is quite natural, as it measures the average ℓ_2 difference between our score model $\boldsymbol{c}_\theta(\cdot; \mathcal{N})$ and the true score $\boldsymbol{c}_{p_{\text{data}}}(\cdot; \mathcal{N})$ similar to (continuous) score matching:

$$\mathcal{L}_{\text{CSM}}(\theta) = \sum_{\mathbf{x}} p_{\text{data}}(\mathbf{x}) \left\| \boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N}) - \boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N}) \right\|_2^2 \tag{5}$$

In the following theorem, we demonstrate that Eq. 5 is indeed a principled learning objective: the estimated θ^* is a consistent estimator for the true underlying distribution $p_{\text{data}}(\mathbf{x})$.

Theorem 2 (Consistency). *In the limit of infinite data and infinite model capacity, the optimal θ^* that minimizes Eq. 5 recovers the true Concrete score, or satisfies $\boldsymbol{c}_{\theta^*}(\mathbf{x}; \mathcal{N}) = \boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$.*

Theorem 1 implies that the estimated (underlying) $p_{\theta^*}(\mathbf{x})$ from $c_{\theta^*}(\mathbf{x}; \mathcal{N})$ satisfies $p_{\theta^*}(\mathbf{x}) = p_{\text{data}}(\mathbf{x}) \ \forall \mathbf{x} \in \mathcal{X}$. Next, we note that Eq. 5 can be simplified to an objective that we can tractably optimize by removing its dependence on the unknown $\boldsymbol{c}_{p_{\text{data}}}(\mathbf{x}; \mathcal{N})$, similar in spirit to Eq. 1. Although the added flexibility of the score model may potentially lead to situations where it does not correspond to a valid probability distribution—similar to how continuous score models do not necessarily form a conservative vector field—this does not appear to hurt CSM's performance empirically.

Theorem 3. *Optimizing Equation* (5) *is equivalent to optimizing:*

$$\mathcal{J}_{\text{CSM}}(\theta) = \underbrace{\sum_{\mathbf{x}} \sum_{i=1}^{|\mathcal{N}(\mathbf{x})|} p_{\text{data}}(\mathbf{x}) \left(\boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})_i^2 + 2\boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})_i \right)}_{\mathcal{J}_1} - \underbrace{\sum_{\mathbf{x}} \sum_{i=1}^{|\mathcal{N}(\mathbf{x})|} 2p_{\text{data}}(\mathbf{x}_{n_i}) \boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})_i}_{\mathcal{J}_2} \tag{6}$$

where $\mathcal{N}(\mathbf{x}) = \{\mathbf{x}_{n_1}, ..., \mathbf{x}_{n_k}\}$ is the set of neighbors of $\mathbf{x}$.

We note that in Eq. 6, the objective $\mathcal{J}_{\text{CSM}}(\theta)$ can be approximated using Monte Carlo samples. We elaborate on the empirical training details in Section 4.2.

4.2 Efficient Training via Monte Carlo

In practice, Eq. 6 is still inefficient; it involves a summation over all $|\mathcal{N}(\mathbf{x})|$ neighbors for $\mathbf{x}$, which can be expensive for high-dimensional datasets. Therefore, we propose several modifications to the original training objective that we found to be crucial for scaling up and improving our approach.

We begin with the leftmost term $\mathcal{J}_1$. First, we approximate the outer expectation w.r.t. $p_{\text{data}}(\mathbf{x})$ with Monte Carlo samples from the empirical data distribution. Next, rather than evaluating the objective for all $|\mathcal{N}(\mathbf{x})|$ neighbors, we sample a neighbor $\mathbf{x}_{n_i}$ uniformly at random among $\mathcal{N}(\mathbf{x}_i)$ for every $\mathbf{x}_i$ in a mini-batch. We then upweight the output from the model using this sample by $|\mathcal{N}(\mathbf{x})|$. We provide the unbiased training algorithm for the leftmost term in Algorithm 1. We note that is similar in spirit to sliced score matching [20], an approximation technique to make continuous score matching scalable to higher dimensions.

Next, we turn to the rightmost term $\mathcal{J}_2$. Similar to $\mathcal{J}_1$, we can estimate $\mathcal{J}_2$ using an unbiased estimator based on samples as demonstrated in Algorithm 2. We define $\mathcal{N}^{-1}(\mathbf{x}') = \{(\mathbf{x}, i) | \mathcal{N}(\mathbf{x})_i = \mathbf{x}'\}$ as the "reverse neighborhood" set, where an element $(\mathbf{x}, i) \in \mathcal{N}^{-1}(\mathbf{x}')$ indicates that $\mathbf{x}'$ is the i-th neighbor of $\mathbf{x}$. There could be multiple $\mathbf{x}$ with the same i in $\mathcal{N}^{-1}(\mathbf{x}')$ as in the case of the star graph.

Computing and storing $\mathcal{N}^{-1}$ as a hash table mapping $\mathbf{x}$ to the set of $\mathcal{N}^{-1}(\mathbf{x})$ has a time and space complexity of at most $O(\sum_{\mathbf{x}} |\mathcal{N}(\mathbf{x})|)$ (*i.e.*, the number of edges). For special structures (*e.g.*, grid), we can design specific algorithms that bypass this process. We provide more details in Appendix C.

Algorithm 1 An unbiased estimator of $\mathcal{J}_1$	**Algorithm 2** An unbiased estimator of $\mathcal{J}_2$
Input: $p_{\text{data}}, \mathcal{N}, \boldsymbol{c}_\theta$ (model).	**Input:** $p_{\text{data}}, \mathcal{N}, \boldsymbol{c}_\theta$ (model).
1. Sample $\mathbf{x} \sim p_{\text{data}}(\mathbf{x})$.	1. Sample $\mathbf{x}' \sim p_{\text{data}}(\mathbf{x})$.
2. Sample $i \sim \text{Uniform}\{1, \ldots, |\mathcal{N}(\mathbf{x})|\}$.	2. Sample $(\mathbf{x}, i) \sim \text{Uniform}(\mathcal{N}^{-1}(\mathbf{x}'))$.
Output: $|\mathcal{N}(\mathbf{x})| \cdot \left(\boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})_i^2 + 2\boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})_i\right)$.	**Output:** $2 \cdot |\mathcal{N}^{-1}(\mathbf{x}')| \cdot \boldsymbol{c}_\theta(\mathbf{x}; \mathcal{N})_i$.

We leverage the grid structure in our experiments, where the neighbors of $\mathbf{x}$ are defined to be $\mathcal{N}(\mathbf{x}) = \{\mathbf{x} \pm \mathbf{e}_d\}_{d=1}^D$. Algorithm 1 and Algorithm 2 allow us to efficiently train the model by sampling a dimension $d \in [D]$ and flipping the bit for the dth entry of $\mathbf{x}$ for each $\mathbf{x}_n$.

4.3 Denoising Concrete Score Matching

Finally, we propose another training objective to approximate Eq. 6, with a focus on computational efficiency. Similar to denoising score matching (DSM) for (Stein) score estimation [19], we derive a denoising counterpart for Concrete score estimation called "Denoising Concrete Score Matching" (D-CSM). Specifically, given a discrete data distribution $p_{\text{data}}(\mathbf{x})$ and a discrete noise distribution $\tilde{q}(\tilde{\mathbf{x}}|\mathbf{x})$, we define the perturbed data distribution $\tilde{p}(\tilde{\mathbf{x}}) = \sum_{\mathbf{x}} p_{\text{data}}(\mathbf{x})\tilde{q}(\tilde{\mathbf{x}}|\mathbf{x})$, and the posterior $q(\mathbf{x}|\tilde{\mathbf{x}}) = \frac{p_{\text{data}}(\mathbf{x})\tilde{q}(\tilde{\mathbf{x}}|\mathbf{x})}{\tilde{p}(\tilde{\mathbf{x}})}$. Then, we can show that the Concrete score of the perturbed data distribution $\tilde{p}(\tilde{\mathbf{x}})$ can be obtained via $\boldsymbol{c}_{\tilde{p}(\tilde{\mathbf{x}})}(\tilde{\mathbf{x}}; \mathcal{N}) = \sum_{\mathbf{x}} \boldsymbol{c}_{\tilde{q}(\tilde{\mathbf{x}}|\mathbf{x})}(\tilde{\mathbf{x}}; \mathcal{N}) q(\mathbf{x}|\tilde{\mathbf{x}})$. This property allows us to obtain the D-CSM objective, as shown in the following theorem:

Theorem 4 (Denoising Concrete Score Matching). *The objective:*

$$\mathcal{J}_{\text{D-CSM}}(\theta) = \sum_{\mathbf{x}, \tilde{\mathbf{x}}} p_{\text{data}}(\mathbf{x})\tilde{q}(\tilde{\mathbf{x}}|\mathbf{x}) \left\| \boldsymbol{c}_\theta(\tilde{\mathbf{x}}; \mathcal{N}) - \boldsymbol{c}_{q(\tilde{\mathbf{x}}|\mathbf{x})}(\tilde{\mathbf{x}}; \mathcal{N}) \right\|_2^2 \tag{7}$$

is minimized when $\boldsymbol{c}_\theta(\tilde{\mathbf{x}}; \mathcal{N}) = \boldsymbol{c}_{p(\tilde{\mathbf{x}})}(\tilde{\mathbf{x}}; \mathcal{N})$.

We draw a direct analogy to DSM in order to provide additional insight into D-CSM. Recall that in DSM, there exists a noise distribution $q(\tilde{\mathbf{x}}|\mathbf{x})$ (*i.e.* $\mathcal{N}(\tilde{\mathbf{x}}|\mathbf{x}, \sigma^2 I)$) such that the magnitude of Stein scores captures the distance between the perturbed $\tilde{\mathbf{x}}$ and its clean counterpart $\mathbf{x}$. D-CSM enjoys a similar interpretation. In particular, consider an input space $\mathbf{x} \in \mathcal{X} \subseteq \mathbb{Z}^D$ with the neighborhood structure $\mathcal{N}(\mathbf{x}) = \{\mathbf{x} + \mathbf{v} | \mathbf{v} \in \{-1, 0, 1\}^D\}$. If we define $q(\tilde{\mathbf{x}}|\mathbf{x}) = \frac{1}{2^{D+k}}$ where k is the Manhattan distance between $\tilde{\mathbf{x}}$ and $\mathbf{x}$, then the Concrete score $\boldsymbol{c}_{\tilde{p}(\tilde{\mathbf{x}})}(\tilde{\mathbf{x}}; \mathcal{N})$ captures how close $\mathbf{x}$ is to $\tilde{\mathbf{x}}$ as measured by the Manhattan distance. Therefore, D-CSM can also be understood through the lens of a denoiser.

5 Experimental Results

In this section, we evaluate the performance of CSM on synthetic, tabular, and discrete image datasets on a variety of sampling and density estimation tasks. We provide additional details on specific experimental settings and hyperparameter configurations in Appendix C.

5.1 Baselines

In our experiments, we compare CSM to two relevant baselines for modeling discrete data: Ratio Matching and Discrete Score Matching with Marginalization (`Discrete Marginalization`). For conciseness, we provide additional details and derivations for their training objectives in Appendix D.

Ratio Matching. Similar to score matching, Ratio Matching [28] leverages the fact that ratios of probabilities are independent of the intractable normalizing constant (due to cancellation). The method then seeks to match the ground truth density ratios $\frac{p_{\text{data}}(\mathbf{x})}{p_{\text{data}}(\mathbf{x}_{-d})} = \frac{q_\theta(\mathbf{x})}{q_\theta(\mathbf{x}_{-d})}$ where $\mathbf{x}_{-d}$ denotes the vector $\mathbf{x}$ with the dth entry bit-flipped (e.g. from 0 to 1).

Discrete Score Matching with Marginalization (Discrete Marginalization). The Discrete Marginalization baseline is another way of estimating discrete probability distributions with score matching as

237 in [28]. However, we note that this approach is difficult to scale because it requires us to marginalize
238 over dimensions in the data, which may also cause instabilities during training.

5.2   1-D Discrete Data

240 In this experiment, we consider a 16-category 1-D data distribution as shown in Figure 2. We
241 parameterize our Concrete score model $c_\theta(\mathbf{x}, \mathcal{N})$ using a shallow MLP model with Tanh activations,
242 and use a Cycle neighborhood structure during training. We demonstrate that the learned Concrete
243 score model can faithfully capture the true data distribution when trained with CSM. As shown on
244 the left side of Figure 2, we find that CSM generates samples (blue) using MH that almost perfectly
245 matches the samples drawn from $p_{\text{data}}(\mathbf{x})$ (green).

246 We also observe in Appendix B.2 that the Concrete score on $p_{\text{data}}(\mathbf{x})$ can recover the Stein score of a
247 data distribution perturbed with triangular noise. Even though the Concrete score model is trained on
248 discrete data (green), this connection allows us to sample with Langevin dynamics using the recovered
249 Stein score. On the right side of Figure 2, we show how the samples generated using Langevin
250 dynamics (smoothed orange) closely match the triangular noise-perturbed data distribution (gray).
251 Then, we leverage a closed-form denoising formula for the perturbed distribution (Appendix B.2) to
252 recover the clean data distribution (green) from samples obtained via Langevin dynamics (smoothed
253 orange). The resulting denoised samples (orange) are labeled as `Denoised` in Figure 2. We provide
254 more details and discussion in Appendix B.2.

Figure 2: Sampling results from a toy 1-D discrete dataset. CSM recovers the true data distribution
$p_{\text{data}}(\mathbf{x})$ using Metropolis-Hastings (left). The Concrete score can also be used to recover the
Stein score of the triangular noise-perturbed data distribution, allowing for sampling with Langevin
dynamics. Such samples can be denoised to recover the original (clean) data distribution (right).

5.3   Sampling with Toy 2-D Multi-Class Datasets

256 Next, we consider three 2-D toy benchmark datasets with multiple modes and discontinuities as
257 commonly used in the density estimation literature [32, 33]. We quantize the data into 91×91 bins
258 to obtain the discrete training data for the experiment (see Figure 3). We compare our method against
259 the two baselines: (1) ratio matching [34]; and (2) discrete marginalization [28]. In particular, we
260 found that the original equations in [28] were incorrect, and provide results using the correct training
261 objectives (denoted as `Ratio-fixed` and `Marginal-fixed`) in Figure 3. We provide a step-by-step
262 derivation addressing this issue with the correct expressions for the training objectives in Appendix D.

263 For a fair comparison, we use the same model architecture and training configurations across all
264 methods. We use the grid neighborhood structure for training CSM. As shown in Figure 3, the
265 samples from CSM best capture the shape of the underlying data distributions across all three datasets
266 (leftmost column). Baselines implemented using the original equations in [28] indeed demonstrate
267 poor performance on the density estimation task (`Ratio` and `Marginal` columns) in Figure 3.

5.4   Likelihood Evaluation on Discrete Tabular Data

269 We then evaluate the performance of CSM on density estimation tasks for a wide range of tabular
270 (discrete) datasets drawn from both the Twenty Datasets [35] and the Amazon Baby Registries
271 benchmarks [36]. In order to evaluate likelihoods, we directly parameterize the density with a
272 discrete autoregressive model (MADE [37]), but train the model using the baseline approaches and
273 CSM. For a fair comparison, we use the same model architecture and experimental configurations
274 across all methods. Similar to our previous experiments, we use the grid neighborhood structure
275 for training CSM. As shown in Table 1, our approach (`CSM`) demonstrates favorable performance
276 relative to the `Ratio Matching` and `Discrete Marginalization` baselines. We provide more
277 experimental details in Appendix C.

| | Data | Ratio | Ratio-fixed | Marginal | Marginal-fixed | CSM (Ours) |

Figure 3: Sampling results on toy 2-D benchmark datasets. We find that CSM produces the highest quality samples across all 3 datasets relative to all baselines.

Datasets	Ratio Matching	Discrete Marginalization	CSM (Ours)
NLTCS	-6.15	-6.21	**-6.13**
Plants	-15.44	-19.03	**-14.02**
Jester	-56.49	-57.06	**-54.91**
Amaz_Diaper	**-10.69**	-42.52	-11.13
Amaz_Feeding	**-12.09**	-35.96	-12.65
Amaz_Gifts	-4.57	-4.28	**-4.22**
Amaz_Media	**-10.22**	-13.77	-10.30
Amaz_Toys	-9.83	-16.34	**-9.30**

Table 1: Log-likelihood comparisons on discrete discrete tabular datasets. Higher is better. We find that CSM demonstrates good performance, almost always outperforming or performing comparably relative to the `Ratio Matching` and `Discrete Marginalization` baselines.

5.5 Generative Modeling with High-dimensional Images

For our final experiment, we demonstrate that we can scale CSM to achieve good performance on complex, high-dimensional binarized image datsets. We experiment with the MNIST [38] dataset, which has 784 dimensions. We directly parameterize the Concrete score function with a U-Net [39], and train the model using the CSM based on a grid neighborhood structure. Similar to [21], we perturb the image with different levels of discrete (Categorical) noise, and train the models at different noise levels with annealing. After the Concrete score model is trained, we sample from the model using Metropolis-Hasting as discussed in Section 3.3 and follow a similar sample initialization process as [21]. We provide more details in Appendix C. We present the samples from our model in Figure 4b. We observe that our CSM approach with Metropolis-Hastings is able to generate samples that look similar to the digit examples in the training set (Figure 4a).

6 Related Work

Score Matching. Our work builds on the body of literature on score matching [18, 19] and score-based generative modeling [20, 21, 13]. Notably, we build upon the generalization of score matching to discrete data [34, 40, 28]. Our score function can be viewed through the lens of generalized score matching as in [28], where the Concrete score serves as a particular instantiation of the linear operator in their framework. However, we provide a novel perspective in terms of constructing the Concrete score via surrogate gradient information over a structured discrete space, and provide efficient training objectives for CSM. Our work is also closely related to score matching with finite difference [27].

(a) Binary training images   (b) MNIST samples (MH)

Figure 4: Image samples from CSM on the binarized MNIST dataset. We observe that CSM is able generate high-quality samples on MNIST using Metropolis-Hastings.

However, rather than approximating the gradient with finite differences for continuous data, we leverage the first-order forward difference to construct our Concrete score function in discrete domains.

Generative Modeling for Discrete Data. CSM also provides another way to train generative models for discrete data. A related work is [41], which trains a score-based model on distributions over graphs. However, they perturb the adjacency matrices with Gaussian noise and use the continuous variant of DSM. Although there exist several model families for learning binary and Categorical probability distributions such as normalizing flows [42, 43, 44], Sum-Product Networks (SPNs) [45, 46], and Generative Flow Networks (GFNs) [47], there does not yet exist a discrete score-based model that can scale to high-dimensional discrete datasets. Finally, our approach bears similarities with Gibbs with Gradients (GWG) [48]. In particular, GWG augments existing MCMC samplers with gradient information by leveraging local structure to estimate likelihood ratios for transitioning to the next state. However, GWG utilizes gradients from the probability mass functions of the underlying discrete distributions, in contrast to the way in which we construct the Concrete score function.

7 Conclusion

We introduced Concrete Score Matching (CSM), a novel framework for learning discrete probability distributions via score matching. We proposed to leverage particular kinds of structural information in the data to construct *surrogate gradient information* about the discrete space, and used this to define a valid score function. We also introduced several modifications to the original training objective that allowed CSM to scale gracefully to high-dimensional datasets, and demonstrated that CSM performs well on a variety of sampling and density estimation tasks.

However, this work is not without limitations. Since CSM depends on the neighborhood structure, certain types of graphs may work better for score matching in practice than others. Additionally, our efficient training objectives may suffer from high variance when scaling to high dimensions for particular kinds of neighborhood-induced graphs, such as the Star graph. For future work, although we fixed the number of neighbors for each $\mathbf{x}$ in our experiments, it would be interesting to adaptively determine the optimal number of neighbors to use for each $\mathbf{x}$ during training. We also believe that CSM can be generalized to leverage more complex neighborhood structures than those we explored in the paper. Additionally, empirically investigating the performance of D-CSM with Langevin dynamics relative to CSM would be interesting future work.

Broader Impact. This work introduces a novel score function—the Concrete score—that is defined over discrete spaces, as well as a corresponding score matching (CSM) framework that can scale to high-dimensional discrete datasets. This leads to empirical performance improvements over a range of density estimation and sampling tasks, and does not have a direct consequence on societal issues. However, we note that CSM could serve as the basis for developing more powerful generative models of structured, discrete data. Although this could lead to tangible benefits (e.g. improved generative modeling of text data), we should be mindful to take the usual precautions required for generative modeling research (e.g. against the development of deepfakes).

References

[1] Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[2] Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International conference on machine learning*, pages 1278–1286. PMLR, 2014.

[3] Irina Higgins, Loic Matthey, Arka Pal, Christopher Burgess, Xavier Glorot, Matthew Botvinick, Shakir Mohamed, and Alexander Lerchner. beta-vae: Learning basic visual concepts with a constrained variational framework. 2016.

[4] Aaron Van Den Oord, Oriol Vinyals, et al. Neural discrete representation learning. *Advances in neural information processing systems*, 30, 2017.

[5] Danilo Rezende and Shakir Mohamed. Variational inference with normalizing flows. In *International conference on machine learning*, pages 1530–1538. PMLR, 2015.

[6] Aaron Van den Oord, Nal Kalchbrenner, Lasse Espeholt, Oriol Vinyals, Alex Graves, et al. Conditional image generation with pixelcnn decoders. *Advances in neural information processing systems*, 29, 2016.

[7] Durk P Kingma, Tim Salimans, Rafal Jozefowicz, Xi Chen, Ilya Sutskever, and Max Welling. Improved variational inference with inverse autoregressive flow. *Advances in neural information processing systems*, 29, 2016.

[8] George Papamakarios, Theo Pavlakou, and Iain Murray. Masked autoregressive flow for density estimation. *Advances in neural information processing systems*, 30, 2017.

[9] Durk P Kingma and Prafulla Dhariwal. Glow: Generative flow with invertible 1x1 convolutions. *Advances in neural information processing systems*, 31, 2018.

[10] Jonathan Ho, Xi Chen, Aravind Srinivas, Yan Duan, and Pieter Abbeel. Flow++: Improving flow-based generative models with variational dequantization and architecture design. In *International Conference on Machine Learning*, pages 2722–2730. PMLR, 2019.

[11] Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, pages 2256–2265. PMLR, 2015.

[12] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

[13] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. *arXiv preprint arXiv:2011.13456*, 2020.

[14] Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. *Advances in neural information processing systems*, 27, 2014.

[15] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *International conference on machine learning*, pages 214–223. PMLR, 2017.

[16] Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. *Advances in neural information processing systems*, 30, 2017.

[17] Tero Karras, Samuli Laine, and Timo Aila. A style-based generator architecture for generative adversarial networks. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 4401–4410, 2019.

[18] Aapo Hyvärinen and Peter Dayan. Estimation of non-normalized statistical models by score matching. *Journal of Machine Learning Research*, 6(4), 2005.

[19] Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural computation*, 23(7):1661–1674, 2011.

[20] Yang Song, Sahaj Garg, Jiaxin Shi, and Stefano Ermon. Sliced score matching: A scalable approach to density and score estimation. In *Uncertainty in Artificial Intelligence*, pages 574–584. PMLR, 2020.

[21] Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. *Advances in Neural Information Processing Systems*, 32, 2019.

[22] Nanxin Chen, Yu Zhang, Heiga Zen, Ron J Weiss, Mohammad Norouzi, and William Chan. Wavegrad: Estimating gradients for waveform generation. *arXiv preprint arXiv:2009.00713*, 2020.

[23] Zhifeng Kong, Wei Ping, Jiaji Huang, Kexin Zhao, and Bryan Catanzaro. Diffwave: A versatile diffusion model for audio synthesis. *arXiv preprint arXiv:2009.09761*, 2020.

[24] Ronald L Graham, Donald E Knuth, Oren Patashnik, and Stanley Liu. Concrete mathematics: a foundation for computer science. *Computers in Physics*, 3(5):106–107, 1989.

[25] John Skilling. The eigenvalues of mega-dimensional matrices. In *Maximum Entropy and Bayesian Methods*, pages 455–466. Springer, 1989.

[26] Michael F Hutchinson. A stochastic estimator of the trace of the influence matrix for laplacian smoothing splines. *Communications in Statistics-Simulation and Computation*, 18(3):1059–1076, 1989.

[27] Tianyu Pang, Kun Xu, Chongxuan Li, Yang Song, Stefano Ermon, and Jun Zhu. Efficient learning of generative models via finite-difference score matching. *Advances in Neural Information Processing Systems*, 33:19175–19188, 2020.

[28] Siwei Lyu. Interpretation and generalization of score matching. *arXiv preprint arXiv:1205.2629*, 2012.

[29] Nicholas Metropolis, Arianna W Rosenbluth, Marshall N Rosenbluth, Augusta H Teller, and Edward Teller. Equation of state calculations by fast computing machines. *The journal of chemical physics*, 21(6):1087–1092, 1953.

[30] W Keith Hastings. Monte carlo sampling methods using markov chains and their applications. 1970.

[31] Siddhartha Chib and Edward Greenberg. Understanding the metropolis-hastings algorithm. *The american statistician*, 49(4):327–335, 1995.

[32] Will Grathwohl, Ricky TQ Chen, Jesse Bettencourt, Ilya Sutskever, and David Duvenaud. Ffjord: Free-form continuous dynamics for scalable reversible generative models. *arXiv preprint arXiv:1810.01367*, 2018.

[33] Nicola De Cao, Wilker Aziz, and Ivan Titov. Block neural autoregressive flow. In *Uncertainty in artificial intelligence*, pages 1263–1273. PMLR, 2020.

[34] Aapo Hyvarinen. Connections between score matching, contrastive divergence, and pseudolikelihood for continuous-valued variables. *IEEE Transactions on neural networks*, 18(5):1529–1531, 2007.

[35] Jan Van Haaren and Jesse Davis. Markov network structure learning: A randomized feature generation approach. In *Twenty-Sixth AAAI Conference on Artificial Intelligence*, 2012.

[36] Jennifer A Gillenwater, Alex Kulesza, Emily Fox, and Ben Taskar. Expectation-maximization for learning determinantal point processes. *Advances in Neural Information Processing Systems*, 27, 2014.

[37] Mathieu Germain, Karol Gregor, Iain Murray, and Hugo Larochelle. Made: Masked autoencoder for distribution estimation. In *International Conference on Machine Learning*, pages 881–889. PMLR, 2015.

[38] Yann LeCun. The mnist database of handwritten digits. *http://yann. lecun. com/exdb/mnist/*, 1998.

[39] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pages 234–241. Springer, 2015.

[40] Aapo Hyvärinen. Some extensions of score matching. *Computational statistics & data analysis*, 51(5):2499–2512, 2007.

[41] Chenhao Niu, Yang Song, Jiaming Song, Shengjia Zhao, Aditya Grover, and Stefano Ermon. Permutation invariant graph generation via score-based generative modeling. In *International Conference on Artificial Intelligence and Statistics*, pages 4474–4484. PMLR, 2020.

[42] Zachary Ziegler and Alexander Rush. Latent normalizing flows for discrete sequences. In *International Conference on Machine Learning*, pages 7673–7682. PMLR, 2019.

[43] Dustin Tran, Keyon Vafa, Kumar Agrawal, Laurent Dinh, and Ben Poole. Discrete flows: Invertible generative models of discrete data. *Advances in Neural Information Processing Systems*, 32, 2019.

[44] Emiel Hoogeboom, Didrik Nielsen, Priyank Jaini, Patrick Forré, and Max Welling. Argmax flows and multinomial diffusion: Learning categorical distributions. *Advances in Neural Information Processing Systems*, 34, 2021.

[45] Hoifung Poon and Pedro Domingos. Sum-product networks: A new deep architecture. In *2011 IEEE International Conference on Computer Vision Workshops (ICCV Workshops)*, pages 689–690. IEEE, 2011.

[46] Alejandro Molina, Antonio Vergari, Karl Stelzner, Robert Peharz, Pranav Subramani, Nicola Di Mauro, Pascal Poupart, and Kristian Kersting. Spflow: An easy and extensible library for deep probabilistic learning using sum-product networks, 2019.

[47] Dinghuai Zhang, Nikolay Malkin, Zhen Liu, Alexandra Volokhova, Aaron Courville, and Yoshua Bengio. Generative flow networks for discrete probabilistic modeling. *arXiv preprint arXiv:2202.01361*, 2022.

[48] Will Grathwohl, Kevin Swersky, Milad Hashemi, David Duvenaud, and Chris Maddison. Oops i took a gradient: Scalable sampling for discrete distributions. In *International Conference on Machine Learning*, pages 3831–3841. PMLR, 2021.