# TNASP: A Transformer-based NAS Predictor with a Self-evolution Framework

## Abstract

Predictor-based Neural Architecture Search (NAS) continues to be an important topic because it aims to mitigate the time-consuming search procedure of traditional NAS methods. A promising performance predictor determines the quality of final searched models in predictor-based NAS methods. Most existing predictor-based methodologies train model-based predictors under a proxy dataset setting, which may suffer from the accuracy decline and the generalization problem, mainly due to their poor abilities to represent spatial topology information of the graph structure data. Besides the poor encoding for spatial topology information, these works did not take advantage of the temporal information such as historical evaluations during training. Thus, we propose a transformer-based NAS performance predictor, associated with a Laplacian matrix based positional encoding strategy, which better represents topology information and achieves better performance than previous state-of-the-art methods on NAS-Bench-101, NAS-Bench-201, and DARTS search space. Furthermore, we also propose a self-evolution framework that can fully utilize temporal information as guidance. This framework iteratively involves the evaluations of previously predicted results as constraints into current optimization iteration, thus further improve the performance of our predictor. Such framework is model-agnostic, thus improving performance on various backbone structures for the prediction task. Our proposed method ranked 2nd among all teams in one recent international NAS challenge. [1]

## 1 Introduction

Neural Architecture Search (NAS) aims to automatically find out superb architectures in a pre-defined search space. The NAS models have outperformed human-designed models in many domains [30, 17, 12, 4, 14]. However, traditional NAS methods like Reinforcement learning and Evolutionary learning require enormous computation resources, i.e., hundreds or thousands of GPU hours, to train sub-models to obtain their performance estimation. The intensive computation prohibits NAS models from deployments to real applications. Although differentiable NAS methods [23] have less search time than traditional methods, they usually suffer from performance collapse due to several problems such as optimization gap [7], discretization discrepancy and the unfair advantage [9], trapping into sharp minimum and the dominant eigenvalue [37, 6].

To reduce the search cost in NAS, predictor-based NAS methods [26, 21, 32, 25, 35, 8, 34, 5, 1] use performance predictors to predict the accuracy of architectures quickly instead of training all architectures to get the accuracy. Simple training-free predictors have been shown promising in some applications, however, those performances are usually not good enough in practice. Many

---

[1]To comply with the double-blind principle, we will add all the details with relevant information once the paper is accepted.

works focus on how to design effective training-based predictors [32, 25, 35, 8, 34]. A training-based predictor usually consists of an encoder module and a regressor module, and only needs to learn from a few architecture-accuracy sampled pairs, thus leading to a fast learning procedure. After the performance predictor learns the relationship between the architecture and its corresponding accuracy, it is able to predict the performance of other unseen architectures in the search space, which greatly accelerates the search process of NAS.

One of the key components of a performance predictor is to encode discrete architectures into continuous feature representations. Neural predictor[32] and CTNAS[8] applied GCN [19] to capture the feature representation of input model structures. Both SemiNAS [25] and GATES [35] learned an embedding matrix for the candidate operations in the search space, and represented architectures as a combination of different embeddings. ReNAS[34] calculated the types matrix, flops matrix, and parameters matrix, and then concatenated them together to form a feature tensor to represent a specific architecture. Unlike previous methods, we propose a **T**ransformer-based **NAS** performance **P**redictor (**TNASP**) and use the linear transformation output over the Laplacian matrix of the model structure graph to be the positional encoding. There are several advantages of the transformer that can be used to train a good performance predictor. First, the self-attention module can help explore better feature representations from the graph structure data. Second, the multi-head mechanism can further help model the different perspective information from the input graph structure. Third, the Laplacian matrix based positional encoding method also fits well to find topology position information on the graph. In summary, we demonstrate that transformer is an effective method to extract feature representation from discrete architecture graphs, and also has superb generalization abilities for processing unseen data, as shown in our experiments. Since the predictors are trained on a small size proxy dataset but the test dataset is much larger, training-based NAS predictors usually have poor generalization abilities. The powerful transformer encoder in our performance predictor can mitigate this problem to a certain degree, due to its good ability to encode the spatial topology information. To further improve our predictor, we introduce a self-evolution framework, which makes full use of temporal information to guide the training. The framework iteratively involves each evaluation score of the previously predicted results on a validation dataset into current ADMM [3] optimization iteration as constraints, to push the predictions close to ground truths gradually. We demonstrate the framework can make our predictor have better generalization, and also achieve better performance than previous predictors.

Our proposed framework is fruitful and practical in several scenarios, for example, all of the machine learning competitions. In competition, the test set that the host provided to users is exactly the validation role in our setting. And the temporal information, such as the feedback of each submission, is able to gradually improve original training iteratively with our framework. Generally speaking, our contributions can be summarized as follows:

- We propose a transformer-based NAS performance predictor (TNASP) to better encoding the spatial topology information, utilizing the multi-head self-attention mechanism to map the discrete architectures to a meaningful feature representation and applying the linear transformation of the Laplacian matrix as the positional encoding.

- By leveraging each evaluation score information in history as constraints in training, and applying ADMM [3] method to iteratively solve the constrained optimization problem, we introduce a generic self-evolution framework to further improve the performance of the proposed predictor, making full use of temporal information.

- Our proposed method surpasses the previous state-of-the-art methods under the same proxy training dataset and achieves state-of-the-art results on NAS-Bench-101 [36], NAS-Bench-201[13], and DARTS [23] search space.

## 2 Related Work

Due to the enormous search cost of traditional NAS methods such as reinforcement learning based methods [39, 2] and evolutionary methods [29, 24], network performance predictor based NAS methods have become a pretty active topic recently. Most works only require a few architecture-accuracy data pairs to train a predictor and estimate the performance of unseen architectures, which can be categorized as training-based network performance predictors. Other works propose to

calculate some kinds of metrics over network structure to represent network performance without training, which are denoted as training-free network performance predictors.

**Training-based network performance predictors** Training-based predictors follow a unified paradigm to learn the correlation from the network architecture and its corresponding accuracy. GP-NAS[21] introduced a Gaussian process based method and modeled the correlation between network architecture and its corresponding accuracy from a Bayesian perspective. Neural Predictor[32] utilized GCN [19] to encode the discrete network structures and defined a general framework for network performance predictors. GCN can depict the topology of a network to a certain degree, but there is still some space for improvements. Our transformer-based design can model such network structure better. ReNAS[34] and CTNAS[8] followed this paradigm and proposed to apply a contrastive loss for predictors to learn the comparative relationship between architectures to get a better ranking. The contrastive training methods usually do not target accuracy but ranking. However, our predictors still outperform their ranking results, although we trained our model using normal MSE loss. GATES [35] and SemiNAS [25] modeled candidate operations as transformation matrices, while the former tried to mimic the actual data processing and the latter raised to employ generated pairs to augment the training data. Similar to these methods, our transformer-based predictor also belongs to training-based network performance predictors category, and we propose to leverage the multi-head self-attention mechanism from the transformer to encode network architectures to excavate more representative features.

**Training-free network performance predictors** In recent years, several works proposed to predict the network performance by designing some metrics, without training a model to perform prediction. [27] scored networks at initialization by computing correspondence between binary codes in the whole mini-batch. TE-NAS[5] analyzed trainability and expressivity to evaluate each network performance. Zero-Cost NAS[1] compared six proxies to predict network performance, such as grasp, fisher, synflow, and so on, but failed to rank architectures in NAS-Bench-101. Zen-NAS measured the expressivity of a network by expected Gaussian complexity to represent its performance. Although these training-free network performance predictors are efficient and have achieved satisfying results on several datasets, their robustness can not be guaranteed and the performance fluctuated dramatically among different tasks. Compared to these efficient methods, our training-based predictor is more time-consuming, but our predictor's performance is dramatically better.

# 3 Methods

In this section, we first briefly review the common paradigm for the training-based NAS predictors as preliminary. Following the same paradigm, we then introduce the details of our transformer-based predictor. Furthermore, we introduce a general framework to utilize the information in evaluation histories over a validation dataset as constraints in ADMM optimization to advance the predictor by a self-evolution framework.

## 3.1 Training-based network performance predictors

Previous works [26, 32, 34, 8] proposed to first apply an encoder $f_E$ to encode the discrete architectures into continuous feature representations, which can be formulated as:

$$e = f_E(A, \kappa) \tag{1}$$

where $A \in \mathbb{R}^{N \times N}$ denotes the adjacency matrix and stands for the directed acrylic connections between nodes, $N$ denotes the number of the connections. $\kappa \in \mathbb{R}^{N \times F}$ stands for the feature matrix and represents the characteristics of the nodes, $F$ denotes the output dimension of the embedding extractor. For NAS predictors, the adjacency matrix $A$ shows the topology information of an architecture and $\kappa$ usually indicates the representation of operations for nodes or edges. Among previous works, the encoder $f_E$ can be a GCN or LSTM or simply an embedding matrix, and the embedding vector $e$ can be interpreted as a latent representation of a specific architecture.

After encoding the discrete architecture into a continuous representation using an encoder, it is easier and more accurate to estimate the network accuracy $\hat{y}$ by a simple regressor $f_R$ once the embedding vector $e$ meaningfully represents the architecture in the latent space.

$$\hat{y} = f_R(e) \tag{2}$$

Figure 1: Our transformer-based NAS predictor mainly consists of an encoder and a regressor. We first encode the information of operations and connections into continuous representation, followed by 4 transformer encoder layers, and the regressor uses the output feature of transformer encoder layers to derive the final prediction. Color grey in features denotes integral form and other colors denote float form. $N$, $F$ and $M$ denote the number of the nodes, the number of candidate operations for each node and the latent dimension of the continuous feature, respectively.

Generally, we apply the MSE loss to supervise the training of the encoder and the regressor, and we use $\theta$ to denote the parameters of both encoder $f_E$ and regressor $f_R$. The optimal parameters $\theta^\star$ can be optimized by stochastic gradient descent method:

$$\theta^\star = \arg\min_\theta \frac{1}{n} \sum_{i=1}^{n} (\hat{y}_i - y_i)^2 \tag{3}$$

where $n$ represents the total number of the training data, $y_i$ denotes the ground truth of the $i$-th sample.

## 3.2 Transformer-based predictor

Recently, the transformer architecture [31] has attracted much attention and outperformed many state-of-the-art models due to its powerful representation ability, which motivates us to borrow the decent encoder structure to be our predictor backbone.

As shown in Fig.1, we first get the operation feature $e_1 \in \mathbb{R}^{N \times M}$ by transforming the operation vector $\kappa$ with an embedding matrix $E \in \mathbb{R}^{F \times M}$.

$$e_1 = E(\kappa) \tag{4}$$

And we propose to encode the positional information by utilizing the Laplacian matrix ($L \in \mathbb{R}^{N \times N}$), computed from the adjacency matrix ($A \in \mathbb{R}^{N \times N}$) and the degree matrix ($D \in \mathbb{R}^{N \times N}$):

$$L = D - A \tag{5}$$

We did not choose the normalized Laplacian matrix, because we find it does not perform well in our experiments.

Then we use a linear layer to map the the Laplacian matrix ($L$) to a continuous feature vector $e_2$, whose dimension is same as the embedding vector $e_1$:

$$e_2 = \text{MLP}(L) \tag{6}$$

Finally, we get the the continuous representation from the transformer encoder with multi-head self-attention module:

$$e = E_{\text{transformer}}(e_1 + e_2) \tag{7}$$

As the continuous representation $e$ contains richer information about the architecture (including the operations and the connections) in the latent space, it's easier to learn the relationship between this representation and its corresponding accuracy. Therefore, we only choose a simple regressor, specifically 2 Multi-Layer Perceptions (MLP), to estimate the final accuracy. The experiments demonstrate the promising performance of our whole designs.

Figure 2: The left sub-figure illustrates the optimization process of self-evolution framework, the blue arrow denotes the input of the validation dataset and the yellow arrow stands for the input of the training dataset. The right sub-figure shows the status transition of the validation predictions and the trainable validation label parameters, both are approaching to ground truth gradually. All the symbols can be found in equations in Section 3.3.

## 3.3 Self-evolution framework

Besides our predictor design that has good encoding ability for spatial topology information, we also propose a framework that can further improve performance by fully utilizing temporal information during training. This framework iteratively involving the evaluation information in the previous iteration over a validation dataset into the current iteration of optimization as constraints, as shown in Fig. 2. Our training strategy is useful and practical in several scenarios, for example, all of the machine learning competitions. In competition, the test set that the host provided to users is exactly the validation role in our framework. And the system feedback of each submission can gradually improve the original training iteratively by adding more and more historical evaluations as constraints. Specifically, our objective function can be formulated as below:

$$
\min_{\theta,\bar{y}} \sum_{i=1}^{n}\|f_{\theta}(x_i) - y_i\|^2 + \alpha \sum_{j=1}^{V}\|f_{\theta}(v_j) - \bar{y}_j\|^2
$$

$$
\text{s.t.} \quad \frac{1}{V}\sum_{j=1}^{V}\|\hat{y}_j^{(t)} - \bar{y}_j\|^2 = e^{(t)}, t = 1, 2, 3, ..., T
$$

(8)

where, $x$ is training data with size $n$. And we call $v$ as help data or validation data with size $V$ in this paper. We denote the number of evaluation on validation dataset $v$ with $t$. And $\alpha$ is the weight to balance train loss and validation loss. We choose different value for $\alpha$ in different experiments. $\bar{y}_j$ is auxilary variable that serves as the proxy variable of ground truth accuracy in validation dataset.

For $e^{(t)}$, it should be computed in system back-end, for example, in the competition situation, users can only get the final evaluation score instead of the ground truth label of every validation sample. For simplicity, we choose MSE as evaluation metric between the prediction $\hat{y}_j^{(t)}$ and the user-unknown

ground truth $y_j^{true}$. In practical situation, the metric can be more complicated.

$$e^{(t)} = \frac{1}{V} \sum_{j=1}^{V} \|\hat{y}_j^{(t)} - y_j^{true}\|^2, t = 1, 2, 3, ..., T \tag{9}$$

We formulate above Eq. 8 as a Minimax optimization problem using Lagrangian Multiplier:

$$L(\theta, \bar{y}, \lambda) = \min_{\theta, \bar{y}} \max_{\lambda \geq 0} \sum_{i=1}^{n} \|f_\theta(x_i) - y_i\|^2 + \alpha \sum_{j=1}^{V} \|f_\theta(v_j) - \bar{y}_j\|^2$$
$$+ \frac{1}{T} \sum_{t=1}^{T} \lambda^{(t)} \left( \frac{1}{V} \sum_{j=1}^{V} \|\hat{y}_j^{(t)} - \bar{y}_j\|^2 - e^{(t)} \right) \tag{10}$$

At each training step, we adopt the Alternating Direction Method of Multipliers (ADMM) to update the variables. And the whole framework is summarized in algorithm 1.

$$\theta^{k+1} = \theta^k - \eta_\theta \frac{\partial L(\theta, \bar{y}^k, \lambda^k)}{\partial \theta} \tag{11}$$

$$\bar{y}^{k+1} = \bar{y}^k - \eta_{\bar{y}} \frac{\partial L(\theta^k, \bar{y}, \lambda^k)}{\partial \bar{y}} \tag{12}$$

$$\lambda^{k+1} = \lambda^k + \eta_\lambda \frac{\partial L(\theta^k, \bar{y}^k, \lambda)}{\partial \lambda} \tag{13}$$

---

**Algorithm 1** Self-evolution Optimization Algorithm

---

**Input:** Input training data $x$, input validation data $v$, input training target $y$, neural network $f$.
**Output:** Network parameters $\theta$, estimated target $\bar{y}$.

 1: Optimize the network parameters $\theta$ until convergence using normal training performed on the training dataset only.
 2: **for** $t = 1$ **to** $T$ **do**
 3:     Compute $e^{(t)}$ according to Eq. (9) using predictor's prediction results on validation dataset.
 4:     Add a new constraint: $\frac{1}{V} \sum_{j=1}^{V} \|\hat{y}_j^{(t)} - \bar{y}_j\|^2 = e^{(t)}$ into Eq. (10)
 5:     **while** not converged **do**
 6:         Update $\theta$ according to the Eq. (11)
 7:         Update $\bar{y}$ according to the Eq. (12)
 8:         Update $\lambda$ according to the Eq. (13)
 9:     **end while**
10: **end for**
11: **return** Network parameters $\theta$ and estimated targets $\bar{y}$

---

# 4 Experiments

We employ our TNASP on three different search spaces, specifically NAS-Bench-101[36], NAS-Bench-201[13] and DARTS[23]. Moreover, we put ranking results over only good architectures; several experimental results performed on ImageNet [20]; a comprehensive comparison with Semi-NAS [25] and the implementation details in supplementary materials.

## 4.1 Experiments on NAS-Bench-101

**NAS-Bench-101** There are 423,624 different architectures in NAS-Bench-101[36]. Each architecture is stacked by 9 repeated cells. The maximum number of nodes and edges for each cell are 7 and 9, respectively. Nodes represent different candidate operations and edges show the connection between nodes. NAS-Bench-101[36] provides the validation accuracy and the test accuracy for three different runs. Following Neural Predictor [32], we utilize the validation accuracy from a single run as the training target and apply the mean test accuracy over three runs as the ground truth accuracy for evaluating the performance of our predictions. We train all models for 300 epochs with batch size 10 using Adam optimizer and the learning rate is 1e-4 with a cosine decay strategy.

**Comparison with SOTA methods**  Following the settings in [32, 8, 34], we choose 0.02%, 0.04%, 0.1% and 1% of the whole data as our training set to train our predictor. And we use all the data as a test set to calculate the Kendall's Tau to evaluate the performance of different predictors. The results are shown in Tab.1. We can see that when the training data is extremely deficient (only 0.02% and 0.04%), our predictor achieves obviously higher Kendall's Tau than Neural Predictor [32] and NAO [26], which illustrates the stronger representation capability of our method in few-shot training scenarios. When using 0.1% of the whole data as the training set, our method still outperforms theirs. When the training data size becomes larger(1%), the performance of all predictors has been improved obviously, due to more information gained. However, our method still beats them.

Although our TNASP has got the best results in all kinds of data splits, we demonstrate that the performance can be further improved with our proposed self-evolution(SE) framework. We use another 200 data as the validation set and only apply the MSE loss over these validation data as the constraints to guide the training optimization of our predictor. As shown in Tab.1, when applied with our SE framework, TNASP can get higher Kendall's Tau under a variety of different data splits. Furthermore, our framework is generic and easy to combine with other methods. When applied to Neural Predictor [32] and NAO [26], both methods achieve higher Kendall's Tau as shown in Tab.1, fully demonstrating the effectiveness of our proposed self-evolution framework.

| Training Samples | 100 (0.02%) | 172 (0.04%) | 424 (0.1%) | 424 (0.1%) | 4236 (1%) |
|---|---|---|---|---|---|
| Validation Samples | 200 | 200 | 200 | 200 | 200 |
| Test Samples | all | all | 100 | all | all |
| Neural Predictor[†] [32] | 0.391 | 0.545 | 0.710 | 0.679 | 0.769 |
| SPOS [15] | - | - | 0.196⋆ | - | - |
| FairNAS [9] | - | - | -0.232⋆ | - | - |
| NAO[‡] [26] | 0.501 | 0.566 | 0.704 | 0.666 | 0.775 |
| ReNAS [34] | - | - | 0.634⋆ | 0.657 | 0.816 |
| RegressionNAS | - | - | 0.430⋆ | - | - |
| CTNAS [8] | - | - | 0.751⋆ | - | - |
| TNASP | **0.600** | **0.669** | **0.752** | **0.705** | **0.820** |
| Neural Predictor[†] + SE | 0.458 | 0.577 | 0.713 | 0.684 | 0.773 |
| NAO[‡] + SE | 0.564 | 0.624 | 0.732 | 0.680 | 0.787 |
| TNASP + SE | **0.613** | **0.671** | **0.754** | **0.722** | **0.820** |

Table 1: Comparison with other methods on NAS-Bench-101. We calculate the Kendall's Tau by predicting accuracy of all architectures in NAS-Bench-101. [†]: re-implemented by ourselves. [‡]: implemented based on their released model. ⋆: reported by CTNAS[8].

## 4.2  Experiments on NAS-Bench-201

**NAS-Bench-201**  Architectures in NAS-Bench-201 [13] are constructed with repeated cells. All cells are composed of 4 nodes and 6 edges, and every cell inside an architecture shares the same structure. Each edge represents an operation, and there are 5 candidate operations in total, resulting in 15,625 different cell candidates. NAS-Bench-201 [13] provides three different results of each architecture on three different datasets and we choose CIFAR-10 results as our targets.

**Comparison with SOTA methods**  Similar to the experimental setup on NAS-Bench-101 [36], we directly train predictors ranging from 0.05% to 10% of the whole dataset and also evaluate the performance on the whole dataset. As shown in Tab.2, TNASP consistently achieves the highest Kendall's Tau and has a large improvement compared to other models regardless of the amount of training data. When applied with the self-evolution framework, TNASP+SE obtains further higher Kendall's Tau at each proportion of the data. Neural Predictor [32] and NAO [26] have the maximum Kendall's Tau improvement of 0.034 and 0.044, respectively, indicating the self-evolution framework is effective for various predictors and different search spaces.

| Training Samples | 78(0.05%) | 156(1%) | 469(3%) | 781(5%) | 1563(10%) |
|---|---|---|---|---|---|
| Validation Samples | 200 | 200 | 200 | 200 | 200 |
| Test Samples | all | all | all | all | all |
| Neural Predictor[†] [32] | 0.343 | 0.413 | 0.584 | 0.634 | 0.646 |
| NAO[‡] [15] | 0.467 | 0.493 | 0.470 | 0.522 | 0.526 |
| TNASP | **0.539** | **0.589** | **0.640** | **0.689** | **0.724** |
| Neural Predictor[†] + SE | 0.377 | 0.433 | 0.602 | 0.652 | 0.649 |
| NAO[‡] + SE | 0.511 | 0.511 | 0.514 | 0.529 | 0.528 |
| TNASP + SE | **0.565** | **0.594** | **0.642** | **0.690** | **0.726** |

Table 2: Comparison with other methods on NAS-Bench-201. We calculate the Kendall's Tau by predicting the accuracy of all architectures in NAS-Bench-201 and comparing them with ground truths. [†]: re-implemented by ourselves. [‡]: implemented based on their released model.

### 4.3 Experiments on DARTS

**DARTS** Architectures in DARTS search space are built by normal cells and reductions cells. Each cell consists of 7 nodes and 14 edges. Every edge is a selection from the 7 candidate operations (we omit the Zero operation in our experiments). Following CTNAS [8], we first train a supernet on CIFAR-10 with a uniform sampling strategy as in [15] for 120 epochs, to get proxy labels for architectures. After the supernet training, we randomly sample 1000 architectures in this search space and query their test accuracy by inheriting the supernet weights to construct the architecture-accuracy pair. Finally, we utilize the generated data pairs to train our TNASP model and apply it in an evolutionary algorithm [10] to search for good architectures in the search space.

**Comparison with SOTA methods** To avoid randomness, we select the top-3 searched architectures to re-train and report the average metrics in the Tab.3. We can notice that our searched cells achieve higher average test accuracy than all the other methods, and the best searched cells get the highest test accuracy 97.48, which implies that our predictor learns the effective correspondence between architectures and accuracy. We visualize the best searched architecture in Fig.3 and append the other searched cells in our supplementary material. Noticeably, several convolution operations appear in the reduction cell and the normal cell contains $max\_pool\_3 \times 3$, which rarely appears in other methods searched normal cells. Our searched cells have a novel structure and achieve higher test accuracy, showing that our method obtains a better local minimum than other methods. It's interesting to explore the essential differences between the cells of different methods in the future.

(a) Normal Cell                    (b) Reduction Cell

Figure 3: Our best searched normal cell and reduction cell.

### 4.4 Ablation studies

**Different positional encoding strategies** We compare different positional encoding schemes in Tab.4 on NAS-Bench-101 [36]. Adjacency option gets the highest score when training data size is 100, Laplacian option obtains highest Kendall's Tau in all other cases. Thus we choose the Laplacian matrix as the positional encoding in our experiments. It is interesting that Normalized Adjacency option's performance is worse than Laplacian option.

| Architecture | Test Accuracy(%) | #Params. (M) | Search Cost(GPU days) |
|---|---|---|---|
| DenseNet-BC [18] | 96.54 | 25.6 | - |
| PyramidNet-BC [16] | 96.69 | 26.0 | - |
| Random search baseline | 96.71 ± 0.15 | 3.2 | - |
| NASNet-A [40] + cutout | 97.35 | 3.3 | 1,800 |
| NASNet-B [40] | 96.27 | 2.6 | 1,800 |
| NASNet-C [40] | 96.41 | 3.1 | 1,800 |
| AmoebaNet-A [29] + cutout | 96.66 ± 0.06 | 3.2 | 3,150 |
| AmoebaNet-B [29] + cutout | 96.63 ± 0.04 | 2.8 | 3,150 |
| SNAS [33] | 97.02 | 2.9 | 1.5 |
| ENAS [28] + cutout | 97.11 | 4.6 | 0.5 |
| NAONet [26] | 97.02 | 28.6 | 200 |
| GHN [38] | 97.16 ± 0.07 | 5.7 | 0.8 |
| PNAS [22] + cutout | 97.17 ± 0.07 | 3.2 | - |
| DARTS [23] + cutout | 97.24 ± 0.09 | 3.4 | 4 |
| CTNAS [8] + cutout | 97.41 ± 0.04 | 3.6 | 0.3 |
| TNASP + cutout(avg) | **97.43 ± 0.04** | 3.6 ± 0.1 | 0.3 |
| TNASP + cutout(best) | **97.48** | 3.7 | 0.3 |

Table 3: Comparison with other methods in DARTS [23] search space on CIFAR-10. "cutout": evaluate the searched cells using cutout [11] data augmentation.

| Training Samples | 100 (0.02%) | 172 (0.04%) | 424 (0.1%) | 424 (0.1%) | 4236 (1%) |
| Test Samples | all | all | 100 | all | all |
|---|---|---|---|---|---|
| Normalized Adjacency | 0.549 | 0.645 | 0.685 | 0.671 | 0.786 |
| Adjacency | **0.620** | 0.643 | 0.725 | 0.693 | 0.802 |
| Normalized Laplacian | 0.592 | 0.642 | 0.740 | 0.697 | 0.813 |
| Laplacian | 0.600 | **0.669** | **0.752** | **0.705** | **0.820** |

Table 4: Comparison with different positional encoding strategies. We calculate the Kendall's Tau by predicting accuracy of all architectures in NAS-Bench-101 and comparing them with ground truths.

**Different evaluation numbers** We investigate the relationship between the number of evaluations performing on the validation dataset and the final Kendall's Tau. As shown in Fig.4, when the number of evaluations increases from 1 to 10, we can see a noticeable increase of the Kendall's Tau. However, when the number of evaluations continues to grow, the increase of the Kendall's Tau seems to be trivial but the training time increases a lot. Hence, we choose to evaluate on validation dataset 10 times in our self-evolution framework for all experiments.

## 5 Conclusion

In this paper, we propose a transformer-based NAS performance predictor and utilize the linear transformation of

Figure 4: Kendall's Tau versus The number of evaluations performing on validation dataset.

the Laplacian matrix as the positional encoding. Our predictor has better encoding ability for spatial topology information, leading to the state-of-the-art performance on several benchmarks. Moreover, we devise a general enough self-evolution framework to further improve our NAS predictor by fully utilizing the temporal information like historical evaluations during training. Unfortunately, we didn't explore how to involve complicated metrics, for example, non-differentiable metrics, as constraints in our framework. In the future, we will further explore how to choose more reasonable and effective constraints to make the NAS predictors converge to a better region stably and efficiently.

# References

[1] Mohamed S Abdelfattah, Abhinav Mehrotra, Łukasz Dudziak, and Nicholas D Lane. Zero-cost proxies for lightweight nas. In *ICLR*, 2021.

[2] Bowen Baker, Otkrist Gupta, Nikhil Naik, and Ramesh Raskar. Designing neural network architectures using reinforcement learning. In *ICLR*, 2017.

[3] Stephen Boyd, Neal Parikh, and Eric Chu. *Distributed optimization and statistical learning via the alternating direction method of multipliers*. Now Publishers Inc, 2011.

[4] Wuyang Chen, Xinyu Gong, Xianming Liu, Qian Zhang, Yuan Li, and Zhangyang Wang. Fasterseg: Searching for faster real-time semantic segmentation. In *ICLR*, 2020.

[5] Wuyang Chen, Xinyu Gong, and Zhangyang Wang. Neural architecture search on imagenet in four gpu hours: A theoretically inspired perspective. In *ICLR*, 2021.

[6] Xiangning Chen and Cho-Jui Hsieh. Stabilizing differentiable architecture search via perturbation-based regularization. In *ICML*, 2020.

[7] Xin Chen, Lingxi Xie, Jun Wu, and Qi Tian. Progressive differentiable architecture search: Bridging the depth gap between search and evaluation. In *ICCV*, 2019.

[8] Yaofo Chen, Yong Guo, Qi Chen, Minli Li, Yaowei Wang, Wei Zeng, and Mingkui Tan. Contrastive neural architecture search with neural architecture comparators. In *CVPR*, 2021.

[9] Xiangxiang Chu, Tianbao Zhou, Bo Zhang, and Jixiang Li. Fair DARTS: eliminating unfair advantages in differentiable architecture search. In *ECCV*, 2020.

[10] Kalyanmoy Deb, Amrit Pratap, Sameer Agarwal, and TAMT Meyarivan. A fast and elitist multiobjective genetic algorithm: Nsga-ii. *IEEE transactions on evolutionary computation*, 6(2):182–197, 2002.

[11] Terrance DeVries and Graham W Taylor. Improved regularization of convolutional neural networks with cutout. *arXiv preprint arXiv:1708.04552*, 2017.

[12] Shaojin Ding, Tianlong Chen, Xinyu Gong, Weiwei Zha, and Zhangyang Wang. Autospeech: Neural architecture search for speaker recognition. In *InterSpeech*, 2020.

[13] Xuanyi Dong and Yi Yang. Nas-bench-201: Extending the scope of reproducible neural architecture search. In *ICLR*, 2020.

[14] Jiemin Fang, Yuzhu Sun, Kangjian Peng, Qian Zhang, Yuan Li, Wenyu Liu, and Xinggang Wang. Fast neural network adaptation via parameter remapping and architecture search. In *ICLR*, 2020.

[15] Zichao Guo, Xiangyu Zhang, Haoyuan Mu, Wen Heng, Zechun Liu, Yichen Wei, and Jian Sun. Single path one-shot neural architecture search with uniform sampling. In *ECCV*, 2020.

[16] Dongyoon Han, Jiwhan Kim, and Junmo Kim. Deep pyramidal residual networks. In *ICCV*, 2017.

[17] Andrew Howard, Mark Sandler, Grace Chu, Liang-Chieh Chen, Bo Chen, Mingxing Tan, Weijun Wang, Yukun Zhu, Ruoming Pang, Vijay Vasudevan, et al. Searching for mobilenetv3. In *ICCV*, 2019.

[18] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. Densely connected convolutional networks. In *CVPR*, 2017.

[19] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017.

[20] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Communications of the ACM*, 60(6):84–90, 2017.

[21] Zhihang Li, Teng Xi, Jiankang Deng, Gang Zhang, Shengzhao Wen, and Ran He. Gp-nas: Gaussian process based neural architecture search. In *CVPR*, 2020.

[22] Chenxi Liu, Barret Zoph, Maxim Neumann, Jonathon Shlens, Wei Hua, Li-Jia Li, Li Fei-Fei, Alan Yuille, Jonathan Huang, and Kevin Murphy. Progressive neural architecture search. In *ECCV*, 2018.

[23] Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: Differentiable architecture search. In *ICLR*, 2019.

[24] Zhichao Lu, Ian Whalen, Vishnu Boddeti, Yashesh Dhebar, Kalyanmoy Deb, Erik Goodman, and Wolfgang Banzhaf. Nsga-net: neural architecture search using multi-objective genetic algorithm. In *GECCO*, 2019.

[25] Renqian Luo, Xu Tan, Rui Wang, Tao Qin, Enhong Chen, and Tie-Yan Liu. Semi-supervised neural architecture search. In *NeurIPS*, 2020.

[26] Renqian Luo, Fei Tian, Tao Qin, Enhong Chen, and Tie-Yan Liu. Neural architecture optimization. In *NeurIPS*, 2018.

[27] Joseph Mellor, Jack Turner, Amos J. Storkey, and Elliot J. Crowley. Neural architecture search without training. *arXiv preprint arXiv:2006.04647*, 2020.

[28] Hieu Pham, Melody Y. Guan, Barret Zoph, Quoc V. Le, and Jeff Dean. Efficient neural architecture search via parameter sharing. In *ICML*, 2020.

[29] Esteban Real, Alok Aggarwal, Yanping Huang, and Quoc V Le. Regularized evolution for image classifier architecture search. In *AAAI*, 2019.

[30] Mingxing Tan and Quoc Le. Efficientnet: Rethinking model scaling for convolutional neural networks. In *ICML*, 2019.

[31] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NeurIPS*, 2017.

[32] Wei Wen, Hanxiao Liu, Yiran Chen, Hai Helen Li, Gabriel Bender, and Pieter-Jan Kindermans. Neural predictor for neural architecture search. In *ECCV*, 2020.

[33] Sirui Xie, Hehui Zheng, Chunxiao Liu, and Liang Lin. SNAS: Stochastic neural architecture search. In *ICLR*, 2019.

[34] Yixing Xu, Yunhe Wang, Kai Han, Shangling Jui, Chunjing Xu, Qi Tian, and Chang Xu. Renas: Relativistic evaluation of neural architecture search. In *CVPR*, 2021.

[35] Huazhong Yang. A generic graph-based neural architecture encoding scheme for predictor-based nas. In *ECCV*, 2020.

[36] Chris Ying, Aaron Klein, Eric Christiansen, Esteban Real, Kevin Murphy, and Frank Hutter. Nas-bench-101: Towards reproducible neural architecture search. In *ICML*, 2019.

[37] Arber Zela, Thomas Elsken, Tonmoy Saikia, Yassine Marrakchi, Thomas Brox, and Frank Hutter. Understanding and robustifying differentiable architecture search. In *ICLR*, 2020.

[38] Chris Zhang, Mengye Ren, and Raquel Urtasun. Graph hypernetworks for neural architecture search. In *ICLR*, 2018.

[39] Barret Zoph and Quoc V. Le. Neural architecture search with reinforcement learning. In *ICLR*, 2017.

[40] Barret Zoph, Vijay Vasudevan, Jonathon Shlens, and Quoc V Le. Learning transferable architectures for scalable image recognition. In *CVPR*, 2018.