RELEVANCE ATTACK ON DETECTORS

ABSTRACT

This paper focuses on high-transferable adversarial attacks on detectors, which are crucial for life-concerning systems such as autonomous driving and security surveillance. Detectors are hard to attack in a black-box manner, because of their multiple-output property and the diversity across architectures. To pursue a high attack transferability, one needs to find a common property shared by different models. We are the first to propose that the relevance map for detectors is such a property. Based on it, we design Relevance Attack on Detectors (RAD). By attacking detectors' common properties, RAD achieves a state-of-the-art transferability, exceeding current methods by above 20%. On MS COCO, the detection mAPs for all 7 black-box architectures are more than halved and the performance of instance segmentation is greatly influenced. Given the great transferability of RAD, we generate Adversarial Objects in COntext (AOCO), the first adversarial dataset on detectors, which helps designers to quickly evaluate and improve their robustness.

1 INTRODUCTION

Adversarial attacks Szegedy et al. (2014); Goodfellow et al. (2015); Carlini & Wagner (2017); Mądry et al. (2017); Baluja & Fischer (2017); Su et al. (2019) have revealed the fragility of Deep Neural Networks (DNNs) by fooling them with elaborately-crafted imperceptible perturbation. Among them, the black-box attack, i.e., attacking without knowledge of the inner structure and weights, is much harder and more aggressive because it is closer to real-world attacking scenarios. For classifiers, there exist some promising black-box attacks Papernot et al. (2016); Brendel et al. (2018); Dong et al. (2018); Xie et al. (2019); Lin et al. (2020); Chen et al. (2020), which greatly influence the black-box performance. Also severe is to attack object detection Zhang & Wang (2019) in a black-box manner, e.g., hiding certain objects from detectors Thys et al. (2019). By that, life-concerning systems based on detection such as autonomous driving and security surveillance would be greatly influence.

To the best of our knowledge, no existing attack is specifically designed for black-box transferability in detectors, because detectors possess multiple-output property and a high diversity across architectures. Adversarial samples do not transfer well in such situations Su et al. (2018), and most attacks only decrease mAP of black-box detectors for 5 to 10% Xie et al. (2017); Li et al. (2018c;b). To overcome that, one reasonable way is to find common properties across detectors. Based on common properties, common weaknesses are dig out, and based on them, the designed attack can threaten variable victims.

In this paper, we adopt the relevance map as a common property, on which different detectors have similar interpretable relevance maps as shown in Fig. 1. Based on relevance maps, we design a Relevance Attack on Detectors (RAD). RAD focuses on suppressing the relevance rather than directly attacking the prediction as in existing works Xie et al. (2017); Li et al. (2018c;a). Since the relevance maps are quite similar across models, those of black-box models are influenced as well in attack, leading to the black-box transferability. Although some works have adopted the relevance map as an indicator or reference of success attacks Dong et al. (2019); Zhang & Zhu (2019); Chen et al. (2020); Wu et al. (2020), we are the first to directly attack the relevance maps of detectors.

In our comprehensive evaluation, RAD achieves the state-of-the-art transferability on 7 black-box models for COCO Lin et al. (2014) dataset, nearly halving the detection mAP. Interestingly, the adversarial samples of RAD also greatly influence the performance of instance segmentation, even only detectors are attacked. Given the high transferability of RAD, we create Adversarial Objects in COntext (AOCO), the first adversarial dataset for object detection. AOCO contains 10K samples that significantly decrease the performance of black-box models for detection and segmentation. AOCO may serve as a benchmark to test the robustness of a DNN or improve it by adversarial training.

| Prediction | YOLOv3 | RetinaNet | Mask R-CNN |

Figure 1: Relevance maps for models with different architectures. Three models not only predict the "stop sign" right, but also share similar relevance maps.

CONTRIBUTIONS

- We propose a novel attack framework on relevance maps for detectors. We extend network visualization methods to detectors, find out the most suitable nodes to attack by relevance maps, and explore on the best update techniques to increase the transferability.

- We evaluate RAD comprehensively and find its state-of-the-art transferability across models and tasks, exceeding current methods by above 20%. Detection mAPs are more than halved, invalidating the state-of-the-art detectors to a certain extent.

- By RAD, we create AOCO, the first adversarial dataset for detectors. AOCO is generated from COCO and contains 10K high-transferable samples as a potential benchmark. AOCO helps designers to quickly evaluate and improve the robustness of detectors.

2 RELATED WORK

Since Szegedy et al. (2014), there have been lots of promising adversarial attacks Goodfellow et al. (2015); Carlini & Wagner (2017); Mądry et al. (2017); Su et al. (2019); Baluja & Fischer (2017); Chen et al. (2020). Generally, they fix the network weights and change the input slightly to optimize the attack loss. The network then predicts incorrectly on adversarial samples with a high confidence. Papernot et al. (2016; 2017) find that adversarial samples crafted by attacking a white-box surrogate model may transfer to other black-box models as well. Input modification Xie et al. (2019); Lin et al. (2020); Dong et al. (2019) or other optimization ways Dong et al. (2018); Lin et al. (2020) can increase the transferability.

Xie et al. (2017) extends adversarial attacks to detectors. It proposes to attack on densely generated bounding boxes. After that, losses about localization and classification are designed Li et al. (2018c) for attack. Li et al. (2018a); Lu et al. (2017) propose to attack detectors in a restricted area. Existing works achieve good results in white-box scenarios, but are not specifically designed for transferability. The adversarial impact on black-box models is quite limited, i.e., a 5 to 10% decrease from the original mAP, even when two models only differ in backbone Xie et al. (2017); Li et al. (2018c;b). Wang et al. (2020) discusses black-box attacks based on queries rather than the transferability as we do. The performance is satisfactory, but it requires over 30K queries, which is easy to be discovered by the model owner.

For the great transferability, we propose to attack on relevance maps, which are calculated by network visualization methods Zeiler & Fergus (2014); Selvaraju et al. (2017); Shrikumar et al. (2017). They are originally developed to interpret how DNNs predict and help users gain trust on them. Specifically, they display how the input contributes to a certain node output in a pixel-wise manner. Typical works include Layer-wise Relevance Propagation (LRP) Bach et al. (2015), Contrastive LRP Gu et al. (2018) and Softmax Gradient LRP (SGLRP) Iwana et al. (2019). These methods encourage the reference of relevance maps in attack Dong et al. (2019); Zhang & Zhu (2019); Chen et al. (2020); Wu et al. (2020), and also inspire us. However, we are the first to attack on relevance maps for detectors.

3 RELEVANCE ATTACK ON DETECTORS

We propose an attack specifically designed for black-box transferability, named Relevance Attack on Detectors (RAD). RAD suppresses multi-node relevance maps for several bounding boxes. Since the relevance map is commonly shared by different detectors as shown in Fig. 1, attacking on it in the white-box surrogate model achieves a high transferability towards black-box models. In this section, we first provide a high-level overview of RAD, and analyze the origin of its transferability. Then we thoroughly discuss three crucial issues in RAD.

- In Section 3.3, we specify the calculation of relevance maps for detectors, where current visualization methods are not applicable.
- In Section 3.4, we introduce the proper nodes to attack by RAD.
- In Section 3.5, we explore the suitable techniques to update samples in RAD.

3.1 WHO IS RAD

We present the framework of RAD in Fig. 2. Initialized by the original sample x_0, the adversarial sample x_k in the k^{th} iteration forward propagates in the surrogate model and gets the prediction $f(x_k)$. Current attacks generally suppress the prediction values of all attacked output nodes in T. In contrast, RAD suppresses the relevance map $h(x_k, T)$ for T. To restrain that, gradients of $h(x_k, T)$ back propagate to x_k, which is then modified to x_{k+1}.

Figure 2: Framework of RAD. x_k is the sample in iteration k and $f(x_k)$ is the network prediction for it. $h(x_k, T)$ stands for the relevance map for all attacked nodes in T. RAD works by repeating processes denoted by "black", "red" and "blud" arrows in turn.

It is notable that RAD is a complete design to attack detectors rather than a simple modification. Heuristically extending single-node relevance maps to multi-node ones or extending classification attacks to detection attacks does not work. We analyze in Section 3.4 that brute attacking on multi-node relevance maps leads to unsatisfactory performance. We also validate in Section 4.3 that classification attacks do not transfer well to detectors in most cases.

3.2 WHY RAD TRANSFERS

RAD's transferability comes from the attack goal: changing the common properties, i.e., the relevance maps. As shown in Fig. 3, the relevance maps are clear and structured for the original sample in both RetinaNet and Mask R-CNN. After RAD, the relevance maps are induced to be meaningless without a correct focus, leading to wrong predictions, i.e., no or false detection. Because relevance maps transfer well across models, those for black-box detectors are also greatly influenced, causing a great performance drop, which is illustrated visually in Section 4.2.

RetinaNet   Mask R-CNN

original   adversarial   original   adversarial

Figure 3: RAD's transferability origins from the change of relevanc maps. The image contains a person and a skateboard. By attacking on relevance maps, both surrogate models make extremely confusing predictions.

RAD also attacks quite "precisely", i.e., the perturbation pattern is quite focused on distinct areas and has a clear structure as shown in Fig. 4. That is to say, RAD accurately locates the most discriminating parts of a sample and concentrates the perturbation on them, leading to a great transferability when the perturbations is equally bounded.

Figure 4: Original image and the adversarial perturbation ($\times 5$ in magnitude for demonstration) generated by Dfool Lu et al. (2017), DAG Xie et al. (2017), and RAD (from left to right)

3.3 WHAT IS THE RELEVANCE MAPS FOR DETECTORS

We analyze the potential of RAD above, below we make it feasible by addressing three crucial issues. First, we need to know the relevance maps for detectors.

Currently, there have been lots of methods to calculate the relevance maps for classifiers as described in Section 2, but none of them are suitable for detectors. We take SGLRP Iwana et al. (2019) as an example to explain this and then to modify, because it excels in discriminating ability against irrelevant regions of a certain target node.

SGLRP visualizes how the input contributes to one output node in a pixel-wise way by back-propagating the relevance from the output to the input. R is the initial relevance in the output layer and its n^{th} component is calculated as

$$R_n = \begin{cases} y_n\left(1 - y_n\right) & n = t \\ -y_n y_t & n \neq t, \end{cases} \tag{1}$$

where y_n is the predicted probability of class n, and y_t is that for the single-node target t. The pixel-wise relevance map $h(x, t)$ for the single-node target t is calculated by back propagating the relevance R from the final layer to the input variable following the rules specified in Iwana et al. (2019).

In detectors, we need the pixel-wise contributions from the input to m bounding boxes. This multi-node relevance map could not be directly calculated by (1), so we naturally modify SGLRP as

$$R_n = \begin{cases} y_n\left(1 - y_n\right) & n \in T \\ -\frac{1}{m} y_n \sum_{i=1}^{m} y_{t_i} & n \notin T, \end{cases} \tag{2}$$

where y_{t_i} is the predicted probabilities for one target node t_i. T is the set containing all target nodes $\{t_1, t_2, ..., t_m\}$. We illustrate the difference between SGLRP and our Multi-Node SGLRP in Fig. 5. SGLRP only displays the relevance map for one bounding box, e.g., "TV", "chair" and "bottle". Multi- Node SGLRP, in contrast, visualizes the overall relevance.

Prediction   Multi Node SGLRP   SGLRP on TV   SGLRP on chair   SGLRP on bottle

Figure 5: Difference between relevance maps from SGLRP and Multi-Node SGLRP. The relevance maps are for YOLOv3 Redmon & Farhadi (2018).

3.4 WHERE TO ATTACK

Besides the calculation of relevance maps, it is also important to choose a proper node set T to attack. Specifically, we need to select certain bounding boxes and the corresponding output nodes for RAD.

Heuristically, the most "obvious" bounding boxes are desired to be eliminated, so we select the bounding boxes with the highest confidence, following Xie et al. (2017). Concretely, it is feasible to *statically* choose m bounding boxes to attack in each iteration, or *dynamically* attack all bounding boxes whose confidence exceeds a threshold. In our evaluation, the two strategies differ a little in performance and are not sensitive to hyper-parameter as demonstrated in Appendix B. This shows that RAD does not require a sophisticated tuning of parameters, which is user-friendly. In our following experiments, we statically attack $m = 20$ nodes.

After selecting bounding boxes, we could attack their size, leading them to shrink; or their localization, leading them to shift; or their confidence, leading them to be misclassified. To adopt the best strategy, we conduct a toy experiment by attacking YOLOv3 Redmon & Farhadi (2018), denoted as M2 and other models are specified in Appendix A. Given the results in Table 1, the classification loss induces a better black-box transferability, which corresponds to the analysis in Zhang & Wang (2019). This may because detectors generally include a pre-trained classification as the feature extractor.

Table 1: Detection mAP in RAD with different attacked nodes

Strategy	M1	M2	M3	M4	M5	M6	M7	M8
No Attack	29.3	33.4	38.1	40.7	42.1	42.5	45.7	46.9
Size	26.0	14.7	31.9	32.5	35.6	35.4	38.6	40.0
Localization	22.8	6.4	27.4	28.1	31.7	30.8	34.4	35.9
Classification	**18.1**	**1.2**	**19.9**	**20.5**	**24.3**	**22.6**	**26.4**	**28.2**

3.5 HOW TO UPDATE

By the relevance map $h(x, T)$ for the attacked nodes T, we are able to attack, i.e., update the original sample to become adversarial with the guidance of the attack gradients $g(x)$ as

$$g(x) = \frac{\partial L_{\text{RAD}}(x)}{\partial x} = \frac{\partial h(x, T)}{\partial x}. \tag{3}$$

Some update techniques are validated to be effective for enhancing the transferability in classification. For example, Scale-Invariant (SI) Lin et al. (2020) proposes to average the attack gradients by scale copies of the samples as

$$g_{\text{si}}(x) = \frac{1}{k} \sum_{i=0}^{k} g(x/2^i). \tag{4}$$

Besides SI, Diverse Input (DI) Xie et al. (2019), Translation-Invariant (TI) Dong et al. (2019) are also promising in classification. We are curious about whether they also work well in object detection. To explore this, we adopt these techniques in RAD as the setting suggested by their designers (see Appendix C). From the results in Table 2, we discover that SI is quite effective, further decreasing the mAP from the baseline to a large extent. Accordingly, we adopt (4) to update the sample in RAD.

Table 2: Detection mAP in RAD with different update techniques

Technique	M1	M2	M3	M4	M5	M6	M7	M8
None	18.1	1.2	19.9	20.5	24.3	22.6	26.4	28.2
DI	18.1	1.0	19.9	20.5	23.9	22.4	26.3	27.9
TI	17.0	2.4	20.8	20.8	25.2	23.0	27.9	29.7
SI	**14.6**	**0.7**	**16.3**	**17.0**	**20.4**	**19.1**	**22.3**	**23.8**

With the calculated gradient, we update the sample as

$$x_{k+1} = \text{clip}_\varepsilon \left(x_k - \alpha \frac{g_{\text{si}}(x_k)}{||g_{\text{si}}(x_k)||_1/N} \right),$$ (5)

where α stands for the step length. x is ℓ_∞-norm bounded by ε from the original sample in each iteration as in Xie et al. (2019); Dong et al. (2019); Lin et al. (2020). Gradient $g(x)$ is normalized by its average ℓ_1-norm,i.e., $||g(x)||_1/N$ to prevent numerical errors and control the degree of perturbation. N is the dimension of the image, i.e., $N = height \times width \times channel$. Division by N is necessary because ℓ_1-norm sums all components of the tensor x, which is too large as a normalization factor. We do not adopt the mainstream *sign* method because it is not suitable to generate small perturbations as shown in other attacks in detectors Xie et al. (2017).

4 EXPERIMENTS

In this section, we evaluate the performance of RAD, especially its transferability. The results are presented numerically and visually. In comprehensive evaluation, RAD achieves a great transferability in across models and even across tasks.

4.1 SETUP

Our experiments are conducted on Keras Chollet et al. (2015), Tensorflow Abadi et al. (2015) and PyTorch Paszke et al. (2019) in 4 NVIDIA GeForce RTX 2080Ti GPUs. Library iNNvestigate Alber et al. (2019) is used to implement Multi-Node SGLRP.

We conduct experiments on MS COCO 2017 dataset Lin et al. (2014), which is a large-scale benchmark for object detection, instance segmentation and captioning. For a fair evaluation, we generate adversarial samples from all 5K samples in its validation set and test several black-box models on their mAP, a standard criteria in many works Ren et al. (2015); He et al. (2017); Chen et al. (2019a).

To validate that the mAP drop comes from the attack instead of resizing or perturbation, we add large Gaussian noises ($\sigma = 9$) to the resized images, and report it as "Ablation". All attacks are conducted with the step length $\alpha = 2$ for 10 iterations and the perturbation is ℓ_∞-bounded in $\varepsilon = 16$ to guarantee the imperceptibility as in Dong et al. (2019).

To attack and test, we choose 8 typical detectors ranging from the first end-to-end detector to recent ones. The variety of model guarantees the validity of results. We specify their information in Appendix A and the corresponding pre-processing in Appendix C.

4.2 VISUAL RESULTS OF RAD

To intuitively illustrate the transferability of RAD, we visualize several predictions on the same adversarial sample by black-box models in Fig. 6. The objects in the image, e.g., the laptop and keyboard, are quite large and obvious to detect. However, with a small perturbation from RAD, 5 black-box models all fail to detect the laptop, keyboard and mouse. Surprisingly, 4 of them even detect a non-existent "bed", which is neither relevant nor similar in the image. The attack process of RAD is analyzed in Appendix D.

| Mask R-CNN (white box) | Faster R-CNN | RetinaNet |
| Cascade R-CNN | Cascade Mask R-CNN | Hybrid Task Cascade |

Figure 6: RAD has a great transferability. The same adversarial sample generated by attacking Mask R-CNN fools all 5 black-box detectors.

4.3 RAD's Transferability in Object Detection

To evaluate the in-domain transferability of detection attacks and cross-domain transferability of classification attacks, we test the detection mAP of 8 models in COCO adversarial samples generated in the same setting.

For classification attacks, we use the model output on the clean sample as the label. By several state-of-the-art attacks on surrogate classifiers (InceptionV3 Szegedy et al. (2016) here as in Xie et al. (2019); Dong et al. (2019)), the adversarial samples are generated and tested the mAP as the transferability towards detectors. For detection attacks, adversarial samples are crafted by attacking surrogate model M2 (YOLOv3 Redmon & Farhadi (2018)). Details of implementation are described in Appendix C.

We present the results in Table 3. It is interesting that detector attacks have similar performance compared to most classifier attacks. Cross-domain attack Naseer et al. (2019) is effective, but RAD is more aggressive. RAD enjoys a state-of-the-art transferability towards most black-box models, outperforming other methods for above 20%. The detection mAPs are more than halved, making state-of-the-art detectors worse than the early single-shot detector (SSD Liu et al. (2016), M1).

Table 3: Detection mAP in different attacks

	Method	M1	M2	M3	M4	M5	M6	M7	M8
Reference	No Attack	29.3	33.4	38.1	40.7	42.1	42.5	45.7	46.9
	Ablation	24.9	31.4	31.2	31.6	35.0	34.3	37.5	38.8
Classification Attack	PGD	26.4	30.4	34.4	35.4	38.4	38.3	41.7	43.1
	SI-PGD	27.5	31.6	36.1	37.1	40.0	40.1	43.5	44.8
	MI-DI-PGD	22.9	26.2	29.3	30.0	33.2	32.1	36.0	37.5
	MI-TI-PGD	20.1	23.7	24.9	25.4	30.1	27.4	32.8	34.5
	CD-painting	16.4	20.8	21.3	22.8	26.6	24.5	28.9	29.5
	CD-comics	16.6	21.6	21.7	22.7	26.8	24.3	29.1	29.8
Detection Attack	Dfool	23.3	2.5	29.2	29.8	33.3	32.9	36.5	38.0
	Loc	21.9	**0.2**	25.8	26.6	29.8	29.4	33.2	33.2
	DAG	20.8	0.6	22.8	23.4	26.8	25.6	28.9	31.0
Ours	RAD	**14.6**	0.7	**16.3**	**17.0**	**20.4**	**19.1**	**22.3**	**23.8**

4.4 RAD'S TRANSFERABILITY TO INSTANCE SEGMENTATION

Detection and segmentation are similar in some aspects, so they could be implemented in one network He et al. (2017); Cai & Vasconcelos (2018); Chen et al. (2019a). Also, adversarial samples for object detection tend to transfer to instance segmentation Xie et al. (2017). Accordingly, we evaluate this cross-task transferability by RAD on surrogate detectors YOLOv3 Redmon & Farhadi (2018) (M2), RetinaNet Lin et al. (2017) (M3) and Mask R-CNN He et al. (2017) (M5). From the results in Table 4, we find that RAD also greatly hurts the performance of instance segmentation, leading to a drop on mAP of over 70%. This might inspire the segmentation attackers to indirectly attack object detection.

Table 4: Segmentation mAP of RAD

Surrogate	mAP			mAP50			mAP75		
	M5	M7	M8	M5	M7	M8	M5	M7	M8
None	38.0	39.4	40.8	60.6	61.3	63.3	40.9	42.9	44.1
Ablation	31.0	31.9	33.5	51.2	51.0	53.7	32.4	34.3	35.4
M2	17.9	18.6	20.3	31.6	31.7	34.5	18.0	18.9	20.7
M3	11.6	11.9	12.9	19.2	19.1	20.7	12.1	12.6	13.7
M5	1.2	11.1	11.8	2.4	17.9	18.9	1.0	11.9	12.6

5 ADVERSARIAL OBJECTS IN CONTEXT

Given the great transferability of RAD, we create Adversarial Objects in COntext (AOCO), the first adversarial dataset for object detection. AOCO is generated from the full COCO 2017 validation set Lin et al. (2014) with 5k samples. It contains 5K adversarial samples for evaluating object detection (AOCO detection) and 5K for instance segmentation (AOCO segmentation).

All 10K samples in AOCO are crafted by RAD. The surrogate model we attack is YOLOv3 for AOCO detection and Mask R-CNN for AOCO segmentation given the results in Table 3 and Table 4. We measure the perturbation Δx in AOCO by Root Mean Squared Error (RMSE) as in Xie et al. (2017); Liu et al. (2017). It is calculated as $\sqrt{\sum_i (\Delta x_i)^2 / N}$ in a pixel-wise way, and N is the size of the image. Performance of AOCO is reported in Table 5. The RMSE in AOCO is lower than that in Wu et al. (2019), and the perturbation is quite imperceptible. Details and samples of AOCO are presented in Appendix E.

Table 5: Detection mAP and segmentation mAP on COCO and AOCO

	RMSE	M1	M2	M3	M4	M5	M6	M7	M8
COCO detection	0.000	29.3	33.4	38.1	40.7	42.1	42.5	45.7	46.9
AOCO detection	6.469	14.6	0.7	16.3	17	20.4	19.1	22.3	23.8
COCO segmentation	0.000	\	\	\	\	38.0	\	39.4	40.8
AOCO segmentation	6.606	\	\	\	\	1.2	\	11.1	11.8

6 CONCLUSION

To pursue a high attack transferability, this paper proposes RAD, which attacks by suppressing the multi-node relevance, a common property across detectors calculated by our Multi-Node SGLRP. We also thoroughly discuss where to attack and the update techniques in attacking relevance maps. RAD achieves a state-of-the-art transferability towards 7 diverse black-box models, exceeding current methods by above 20% and also hurt the instance segmentation. Given the great transferability of RAD, we generate Adversarial Objects in COntext (AOCO), the first adversarial dataset on object detectors, which could help network designers to quickly evaluate and improve the robustness of detectors. Also, attacking other common properties is promising to achieve a good performance.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dandelion Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL `https://www.tensorflow.org/`. Software available from tensorflow.org.

Maximilian Alber, Sebastian Lapuschkin, Philipp Seegerer, Miriam Hägele, Kristof T Schütt, Grégoire Montavon, Wojciech Samek, Klaus-Robert Müller, Sven Dähne, and Pieter-Jan Kindermans. innvestigate neural networks. *Journal of Machine Learning Research*, 20(93):1–8, 2019.

Sebastian Bach, Alexander Binder, Grégoire Montavon, Frederick Klauschen, Klaus-Robert Müller, and Wojciech Samek. On pixel-wise explanations for non-linear classifier decisions by layer-wise relevance propagation. *PloS one*, 10(7), 2015.

Shumeet Baluja and Ian Fischer. Adversarial transformation networks: Learning to generate adversarial examples. *arXiv preprint arXiv:1703.09387*, 2017.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. In *6th International Conference on Learning Representations, ICLR 2018, Vancouver, BC, Canada, April 30 - May 3, 2018, Conference Track Proceedings*, 2018.

Zhaowei Cai and Nuno Vasconcelos. Cascade r-cnn: Delving into high quality object detection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 6154–6162, 2018.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *2017 IEEE Symposium on Security and Privacy (SP)*, pp. 39–57. IEEE, 2017.

Kai Chen, Jiangmiao Pang, Jiaqi Wang, Yu Xiong, Xiaoxiao Li, Shuyang Sun, Wansen Feng, Ziwei Liu, Jianping Shi, Wanli Ouyang, et al. Hybrid task cascade for instance segmentation. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4974–4983, 2019a.

Kai Chen, Jiaqi Wang, Jiangmiao Pang, Yuhang Cao, Yu Xiong, Xiaoxiao Li, Shuyang Sun, Wansen Feng, Ziwei Liu, Jiarui Xu, et al. Mmdetection: Open mmlab detection toolbox and benchmark. *arXiv preprint arXiv:1906.07155*, 2019b.

Sizhe Chen, Zhengbao He, Chengjin Sun, and Xiaolin Huang. Universal adversarial attack on attention and the resulting dataset damagenet. *arXiv preprint arXiv:2001.06325*, 2020.

François Chollet et al. Keras. `https://keras.io`, 2015.

Yinpeng Dong, Fangzhou Liao, Tianyu Pang, Hang Su, Jun Zhu, Xiaolin Hu, and Jianguo Li. Boosting adversarial attacks with momentum. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 9185–9193, 2018.

Yinpeng Dong, Tianyu Pang, Hang Su, and Jun Zhu. Evading defenses to transferable adversarial examples by translation-invariant attacks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4312–4321, 2019.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *STAT*, 1050:20, 2015.

Jindong Gu, Yinchong Yang, and Volker Tresp. Understanding individual decisions of cnns via contrastive backpropagation. In *Asian Conference on Computer Vision*, pp. 119–134. Springer, 2018.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pp. 2961–2969, 2017.

Brian Kenji Iwana, Ryohei Kuroki, and Seiichi Uchida. Explaining convolutional neural networks using softmax gradient layer-wise relevance propagation. In *2019 IEEE/CVF International Conference on Computer Vision Workshops, ICCV Workshops 2019, Seoul, Korea (South), October 27-28, 2019*, 2019.

Yuezun Li, Xian Bian, and Siwei Lyu. Attacking object detectors via imperceptible patches on background. *CoRR, abs/1809.05966*, 2018a.

Yuezun Li, Xiao Bian, Ming-Ching Chang, and Siwei Lyu. Exploring the vulnerability of single shot module in object detectors via imperceptible background patches. 2018b.

Yuezun Li, Daniel Tian, Xiao Bian, Siwei Lyu, et al. Robust adversarial perturbation on deep proposal-based models. 2018c.

Jiadong Lin, Chuanbiao Song, Kun He, Liwei Wang, and John E Hopcroft. Nesterov accelerated gradient and scale invariance for adversarial attacks. In *8th International Conference on Learning Representations, ICLR*, 2020.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European Conference on Computer Vision*, pp. 740–755. Springer, 2014.

Tsung-Yi Lin, Priya Goyal, Ross Girshick, Kaiming He, and Piotr Dollár. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pp. 2980–2988, 2017.

Wei Liu, Dragomir Anguelov, Dumitru Erhan, Christian Szegedy, Scott Reed, Cheng-Yang Fu, and Alexander C Berg. Ssd: Single shot multibox detector. In *European Conference on Computer Vision*, pp. 21–37. Springer, 2016.

Yanpei Liu, Xinyun Chen, Chang Liu, and Dawn Song. Delving into transferable adversarial examples and black-box attacks. In *Proceedings of 5th International Conference on Learning Representations*, 2017.

Jiajun Lu, Hussein Sibai, and Evan Fabry. Adversarial examples that fool detectors. *arXiv preprint arXiv:1712.02494*, 2017.

Aleksander Mądry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *STAT*, 1050:9, 2017.

Muhammad Muzammal Naseer, Salman H Khan, Muhammad Haris Khan, Fahad Shahbaz Khan, and Fatih Porikli. Cross-domain transferability of adversarial perturbations. In *Advances in Neural Information Processing Systems*, pp. 12905–12915, 2019.

Nicolas Papernot, Patrick McDaniel, and Ian Goodfellow. Transferability in machine learning: from phenomena to black-box attacks using adversarial samples. *arXiv preprint arXiv:1605.07277*, 2016.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia Conference on Computer and Communications Security*, pp. 506–519. ACM, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, pp. 8024–8035, 2019.

Joseph Redmon and Ali Farhadi. Yolov3: An incremental improvement. *arXiv preprint arXiv:1804.02767*, 2018.

Shaoqing Ren, Kaiming He, Ross Girshick, and Jian Sun. Faster r-cnn: Towards real-time object detection with region proposal networks. In *Advances in Neural Information Processing Systems*, pp. 91–99, 2015.

Ramprasaath R Selvaraju, Michael Cogswell, Abhishek Das, Ramakrishna Vedantam, Devi Parikh, and Dhruv Batra. Grad-cam: Visual explanations from deep networks via gradient-based localization. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 618–626, 2017.

Avanti Shrikumar, Peyton Greenside, and Anshul Kundaje. Learning important features through propagating activation differences. In *Proceedings of the 34th International Conference on Machine Learning-Volume 70*, pp. 3145–3153. JMLR. org, 2017.

Dong Su, Huan Zhang, Hongge Chen, Jinfeng Yi, Pin-Yu Chen, and Yupeng Gao. Is robustness the cost of accuracy?–a comprehensive study on the robustness of 18 deep image classification models. In *Proceedings of the European Conference on Computer Vision (ECCV)*, 2018.

Jiawei Su, Danilo Vasconcellos Vargas, and Kouichi Sakurai. One pixel attack for fooling deep neural networks. *IEEE Transactions on Evolutionary Computation*, 2019.

Ross Girshick Kaiming He sung Yi Lin, Priya Goyal and Piotr Dollár. Keras implementation of retinanet object detection. https://github.com/fizyr/keras-retinanet, 2017.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian J. Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *2nd International Conference on Learning Representations, ICLR 2014, Banff, AB, Canada, April 14-16, 2014, Conference Track Proceedings*, 2014.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2818–2826, 2016.

Simen Thys, Wiebe Van Ranst, and Toon Goedemé. Fooling automated surveillance cameras: adversarial patches to attack person detection. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, 2019.

Yajie Wang, Yu-an Tan, Wenjiao Zhang, Yuhang Zhao, and Xiaohui Kuang. An adversarial attack on dnn-based black-box object detectors. *Journal of Network and Computer Applications*, pp. 102634, 2020.

Dongxian Wu, Yisen Wang, Shutao Xia, James Bailey, and Xingjun Ma. Skip connections matter: On the transferability of adversarial examples generated with resnets. In *Proceedings of the International Conference on Learning Representations*, 2019.

Weibin Wu, Yuxin Su, Xixian Chen, Shenglin Zhao, Irwin King, Michael R Lyu, and Yu-Wing Tai. Boosting the transferability of adversarial samples via attention. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 1161–1170, 2020.

Cihang Xie, Jianyu Wang, Zhishuai Zhang, Yuyin Zhou, Lingxi Xie, and Alan Yuille. Adversarial examples for semantic segmentation and object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1369–1378, 2017.

Cihang Xie, Zhishuai Zhang, Yuyin Zhou, Song Bai, Jianyu Wang, Zhou Ren, and Alan L Yuille. Improving transferability of adversarial examples with input diversity. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 2730–2739, 2019.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European Conference on Computer Vision*, pp. 818–833. Springer, 2014.

Haichao Zhang and Jianyu Wang. Towards adversarially robust object detection. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 421–430, 2019.

Tianyuan Zhang and Zhanxing Zhu. Interpreting adversarially trained convolutional neural networks. In *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, pp. 7502–7511, 2019.

A   MODEL INFORMATION

Table 6 presents the models' information from our evaluation and MMdetection Chen et al. (2019b).

Table 6: Model backbone and mAPs

ID	Model	Backbone	mAP
M1	SSD512 Liu et al. (2016)	VGG16	29.3
M2	YOLOv3 Redmon & Farhadi (2018)	Darknet	33.4
M3	RetinaNet sung Yi Lin & Dollár (2017)	ResNet-101	38.1
M4	Faster R-CNN Ren et al. (2015)	ResNeXt-101-64*4d	40.7
M5	Mask R-CNN He et al. (2017)	ResNeXt-101-64*4d	42.1
M6	Cascade RCNN Cai & Vasconcelos (2018)	ResNet-101	42.5
M7	Cascade Mask R-CNN Cai & Vasconcelos (2018)	ResNeXt-101-64*4d	45.7
M8	Hyrbrid Task Cascade Chen et al. (2019a)	ResNeXt-101-64*4d	46.9

B   INFLUENCE OF HYPER-PARAMETERS IN NODE SELECTION

Performance of RAD is not sensitive to hyper-parameter, no matter the strategy to select bounding boxes is dynamic or static. Attackers are not bothered to tune them carefully.

Table 7: Detection mAP in different hyper-parameters in RAD

Strategy	Parameter	M1	M2	M3	M4	M5	M6	M7	M8
	-1	18.3	1.2	20.0	20.6	24.3	22.8	26.7	38.3
Dynamic	-2	18.2	1.2	20.1	20.7	24.2	22.8	26.6	28
	-3	18.4	1.3	20.3	20.8	24.3	22.9	26.7	28.5
	10	18.2	1.1	19.9	20.5	24.2	22.8	26.2	28.0
Static	20	18.1	1.2	19.9	20.5	24.3	22.6	26.4	28.2
	30	18.2	1.3	20.1	20.7	24.3	22.8	26.0	27.9

C   IMPLEMENTATION DETAILS

C.1   PRE-PROCESSING

To pre-process, we resize the image with its long side as 416 for YOLOv3 or RetinaNet and 448 for Mask R-CNN, and then zero-pad it to a square. The resolution is kept relatively the same for a fair evaluation. Images are normalized to [0,1] in YOLOv3 or subtracted by the mean of COCO training set in RetinaNet and Mask R-CNN. Accordingly, samples in AOCO detection have the long side 416 and that for AOCO segmentation is 448.

C.2   TRANSFER-ENHANCING TECHNIQUES

DI Xie et al. (2019) transforms the image for 4 times with probability p ($p = 1$ for better transferability as suggested) and averaging the gradients. The transformation is to resize the image to 0.9 of its size and randomly padding the outer areas with white pixels. SI Lin et al. (2020) divides the sample numerically by the power 2 for 4 times and averages 4 calculated gradients. TI Dong et al. (2019) translates the image to calculate the augmented gradients. To implement it efficiently, it adopts a kernel to simulate the averaging of gradients. We choose the kernal size of 15 as suggested. MI Dong et al. (2018) uses momentum optimization (parameter $\mu = 1$ as suggested) for a better transferability and a faster attack. Cross-domain attack Naseer et al. (2019) uses extra datasets (paintings, denoted as CD-paintings, and comics, denoted as CD-comics) to train a perturbation generator with the relative loss. The surrogate model used is also InceptionV3 for consistency. All perturbations are resized to fit the sample size.

C.3 DETECTION ATTACKS

For DAG Xie et al. (2017), we follow the setting of generating dense proposals. The classification probabilities of 3000 bounding boxes with highest confidence are attacked. But we alter its optimization to (5) because its original update produces quite small perturbation, leading to a poor transferability, which is unfair for comparison. Dfool Lu et al. (2017) suppresses the classification confidence for the original bounding boxes, which is the same in our experiment. Localization loss is shown to be useful in Zhang & Wang (2019), and here we suppress the width and height of the original bounding boxes. In RAD, there are rare cases (less than 5% iterations) when the relevance is too small to calculate the gradient. In these cases, we resort to DAG loss, and the gradient would recover after one iteration.

D VISUAL RESULTS OF RAD PROCESS

By RAD, the relevance map is attacked to be meaningless and loss its focus. In Fig. 7, the initial prediction is correct and the relevance map is clear. RAD constantly misleads the relevance map to be unstructured without outline of objects. Finally, all bounding boxes vanish.

Figure 7: Transition of prediction and relevance map in RAD (from top to bottom and left to right).

E MORE ABOUT AOCO

We report the mAP50 and mAP75 of AOCO in Table 8 and Table 9. We show in Fig. 8 the visual comparative results.

Table 8: Detection mAP50 and segmentation mAP50 on COCO and AOCO

	M1	M2	M3	M4	M5	M6	M7	M8
COCO detection	49.2	56.4	58.1	62.0	63.8	60.7	64.1	66.0
AOCO detection	26.7	1.6	27.6	29.1	34.5	29.9	34.3	37.4
COCO segmentation	/	/	/	/	60.6	/	61.3	63.3
AOCO segmentation	/	/	/	/	2.4	/	17.9	18.9

Table 9: Detection mAP75 and segmentation mAP75 on COCO and AOCO

	M1	M2	M3	M4	M5	M6	M7	M8
COCO detection	30.8	35.8	40.6	44.6	46.3	46.3	50.0	51.2
AOCO detection	14.2	0.6	16.5	17.1	20.8	19.9	23.3	24.6
COCO segmentation	/	/	/	/	40.9	/	42.9	44.1
AOCO segmentation	/	/	/	/	1.0	/	11.9	12.6

| COCO detection | AOCO detection | COCO segmentation | AOCO segmentation |

Figure 8: Detection and segmentation results in COCO and AOCO by YOLOv3 and Mask R-CNN. For COCO, both networks predict correctly. For AOCO segmentation results, the top image contains two big masks for "chair" and "potted plan"; the second image contains one false mask for "sports ball"; the bottom image contains "dog" in green, "car" in purple and "elephant" in red.