ROBUST TEMPORAL ENSEMBLING

ABSTRACT

Successful training of deep neural networks with noisy labels is an essential capability as most real-world datasets contain some amount of mislabeled data. Left unmitigated, label noise can sharply degrade typical supervised learning approaches. In this paper, we present *robust temporal ensembling* (RTE), a simple supervised learning approach which combines robust task loss, temporal pseudo-labeling, and a new ensemble consistency regularization term to achieve noise-robust learning. We demonstrate that RTE achieves state-of-the-art performance across the CIFAR-10, CIFAR-100, and ImageNet datasets, without any label filtering or label fixing. In particular, RTE achieves 93.64% accuracy on CIFAR-10 and 66.43% accuracy on CIFAR-100 under 80% label corruption, and achieves 76.72% accuracy on ImageNet under 40% corruption. These are substantial gains over previous state-of-the-art accuracies of 86.6%, 60.2%, and 71.31%, respectively, achieved using three distinct methods. Finally, we show that RTE retains competitive corruption robustness to unforeseen *input* noise using CIFAR-10-C, obtaining a mean corruption error (mCE) of 13.50% even in the presence of an 80% noise ratio, versus 26.9% mCE with standard methods on clean data.

1 INTRODUCTION

Deep neural networks have enjoyed considerable success across a variety of domains, and in particular computer vision, where the common theme is that more labeled training data yields improved model performance (Hestness et al., 2017; Mahajan et al., 2018; Xie et al., 2019b; Kolesnikov et al., 2019). Given the over-parameterized nature of deep networks, deep neural networks naturally overfit noisy labels (Zhang et al., 2016). While noisy labels are perhaps rare in highly curated datasets, most real-world datasets inevitably contain some degree of label error. Moreover, the process of large-scale expert human annotation is time consuming, expensive, and despite best efforts, imperfect. It is therefore essential that learning algorithms in production workflows leverage noise robust methods.

Noise robust learning has a long history and takes many forms (Natarajan et al., 2013; Frenay & Verleysen, 2014; Song et al., 2020). Common strategies include loss correction and reweighting (Patrini et al., 2016; Zhang & Sabuncu, 2018; Menon et al., 2020), label refurbishment (Reed et al., 2014; Song et al., 2019), sample selection and filtering (Nguyen et al., 2020), semi-supervised learning (Zhang et al., 2020; Li et al., 2020), and relying on carefully constructed *trusted* subsets of human-verified labeled data (Li et al., 2017; Hendrycks et al., 2018; Zhang et al., 2020). In this work, we focus on the more challenging setting of robust learning without trusted data, and we focus on methods which forgo the added complexity of identifying and filtering or fixing incorrect labels.

We combine task loss correction and a new form of *ensemble consistency regularization* to achieve robust learning even in the presence of extreme label noise. The main contributions of the paper are as follows:

- To our knowledge, we are the first to combine robust loss correction techniques with semi-supervised consistency methods for noise-robust learning.

- We introduce a new ensemble-based form of consistency regularization which leverages *multiple augmentations of the same images* during each gradient computation.

- We demonstrate that our approach advances state-of-the-art performance across CIFAR-10, CIFAR-100, and ImageNet, even without label filtering or refurbishment.

- We further demonstrate that our approach maintains corruption robustness to unforeseen data shifts which can occur during deployment.

2 RELATED WORK

Prior work on noise-robust learning spans many diverse approaches. These include estimation and correction of the underlying noise transition matrix (Patrini et al., 2016) or a more general corruption process (Goldberger & Ben-Reuven, 2016); outlier detection in feature space (Wang et al., 2018); identifying incorrect labels and fixing them (Song et al., 2019) or filtering them out (Nguyen et al., 2020); and many more. Further, some approaches assume that additional information is available, such as a trusted subset of human-verified data (Li et al., 2017; Hendrycks et al., 2018; Zhang et al., 2020). In this section, we focus on prior work that is closely related to our approach. Additional information on numerous prior works can be found in Section B of the appendix.

In the context of noise-robust learning, the most relevant prior work is (Zhang & Sabuncu, 2018), which introduced generalized cross entropy (GCE). This robust task loss is capable of smoothly transitioning between cross entropy and mean absolute error, which is beneficial since each exhibits distinct properties concerning learning signal and robustness to label noise. In the context of semi-supervised learning, the most relevant prior works are Sajjadi et al. (2016), (Laine & Alia, 2017) and (Tarvainen & Valpola, 2017). (Sajjadi et al., 2016) and (Laine & Alia, 2017) introduced the ideas of label consistency and temporal pseudo-labeling. In particular, (Laine & Alia, 2017) enforced label consistency over time by retaining an ensemble of past predictions for every training example. Later, (Tarvainen & Valpola, 2017) improved upon this idea by instead maintaining consistency with a teacher model that is averaged over time. In this work, we introduce a form of consistency loss for noise-robust learning that builds upon these ideas from semi-supervised learning, and we demonstrate that the combination of GCE with this consistency loss leads to significant improvements in robustness to label noise.

3 ROBUST TEMPORAL ENSEMBLING

3.1 PRELIMINARIES

Adopting the notation of Zhang & Sabuncu (2018), we consider the problem of classification where $\mathcal{X} \subset \mathbb{R}^d$ is the feature space and $\mathcal{Y} = \{1, \ldots, c\}$ is the label space where the classifier function is a deep neural network with a softmax output layer that maps input features to distributions over labels $f : \mathcal{X} \to \mathbb{R}^c$. The dataset of training examples containing *in-sample* noise is defined as $D = \{(x_i, \tilde{y}_i)\}_{i=1}^n$ where $(x_i, \tilde{y}_i) \in (\mathcal{X} \times \mathcal{Y})$ and $\tilde{y}_i$ is the noisy version of the true label y_i such that $p(\tilde{y}_i = k | y_i = j, x_i) \equiv \eta_{ijk}$. We do not consider *open-set* noise (Wang et al., 2018), in which there is a particular type of noise that occurs on inputs, $\tilde{x}$, rather than labels. Following most prior work, we make the simplifying assumption that the noise is conditionally independent of the input, x_i, given the true labels. In this setting, we can write $\eta_{ijk} = p(\tilde{y}_i = k | y_i = j) \equiv \eta_{jk}$ which is, in general, considered to be *class dependent* noise[1,2].

To aid in a simple and precise corruption procedure, we now depart from traditional notation and further decompose η_{jk} as $p_j \cdot c_{jk}$, where $p_j \in [0, 1]$ is the probability of corruption of the j-th class and $c_{jk} \in [0, 1]$ is the relative probability that corrupted samples of class j are labeled as class k, with $c_{i \neq j} \geq 0$, $c_{jj} = 0$ and $\sum_k c_{jk} = 1$. A noisy dataset with m classes can then be described as transition probabilities specified by

$$F = \text{diag}(P) \cdot C + \text{diag}(1 - P) \cdot \mathcal{I} \tag{1}$$

where $C \in \mathbb{R}^{m \times m}$ defines the system confusion or noise structure, $P \in \mathbb{R}^m$ defines the noise intensity or ratio for each class, and $\mathcal{I}$ is the identity matrix. When $c_{jk} = c_{kj}$ the noise is said to be *symmetric* and is considered *asymmetric* otherwise. If ratio of noise is the same for all classes then $p_j = p$ and the dataset is said to exhibit *uniform* noise. For the case of uniform noise, equation (1) interestingly takes the familiar form of the Google matrix equation as

$$F_p = p \cdot C + (1 - p) \cdot \mathcal{I} \tag{2}$$

---

[1]See Lee et al. (2019) for treatment of conditionally dependent *semantic* noise such that $\eta_{ijk} \neq \eta_{jk}$.

[2]Note that Patrini et al. (2016) define the noise transition matrix T such that $T_{jk} \equiv \eta_{jk}$.

Note that, by this definition, $\eta_{jj} = p \cdot c_{jj} = 0$ which prohibits $\tilde{y}_i = y_i$. This ensures a true effective noise ratio of p. For example, suppose there are $m = 10$ classes and we wish to corrupt labels with 80% probability. Then if corrupted labels are sampled from $\mathcal{Y}$ rather than $\mathcal{Y} \setminus \{y\}$, $\frac{1}{10} \cdot 0.8 = 8\%$ of the corrupted samples will not actually be corrupted, leading to a *true* corruption rate of 72%. Therefore, despite prescribing $p = 0.8$, the true effective noise ratio would be 0.72, which in turn yields a $\frac{0.08}{1-0.8} = 40\%$ increase in clean labels, and this is indeed the case in many studies (Zhang & Sabuncu, 2018; Nguyen et al., 2020; Li et al., 2020; Zhang et al., 2020).

3.2 METHODS

At a high level, RTE is the combination of a noise-robust task loss, augmentation, pseudo-labeling, and consistency regularization. We leverage generalized cross entropy (Zhang & Sabuncu, 2018), AugMix stochastic augmentation strategy (Hendrycks* et al., 2020), an exponential moving average of model weights for generating pseudo-labels (Tarvainen & Valpola, 2017), and a mean squared error consistency loss (Laine & Alia, 2017) between pseudo-labels on un-augmented input versus model predictions on augmented input.

3.2.1 NOISE-ROBUST TASK LOSS

Generalized cross entropy (GCE) (Zhang & Sabuncu, 2018) is a theoretically grounded noise-robust loss function that can be seen as a generalization of mean absolute error (MAE) and categorical cross entropy (CCE). The main idea is that CCE learns quickly, but more emphasis is put on difficult samples which is prone to overfit noisy labels, while MAE treats all samples equally, providing noise-robustness but learning slowly. To exploit the benefits of both MAE and CCE, a negative Box-Cox transformation (Box & Cox, 1964) is used as the loss function

$$\mathcal{L}_q(f(x_i), y_i = j) = \frac{(1 - f_j(x_i)^q)}{q} \tag{3}$$

where $q \in (0, 1]$, and f_j denotes the j-th element of f. GCE becomes CCE for $\lim_{q \to 0} \mathcal{L}_q$ and becomes MAE/unhinged loss when $q = 1$, and the optimization of (3) can be seen as a generalization of maximum likelihood (Ferrari & Yang, 2010).

3.2.2 AUGMENTATION

AugMix (Hendrycks* et al., 2020) is a data augmentation technique which utilizes stochasticity, diverse augmentations, a Jensen-Shannon divergence consistency loss, and a formulation to mix multiple augmented inputs. The motivation behind AugMix is to improve model robustness under data shift as small corruptions are enough to subvert existing classifiers which depend on the ability of the training data to faithfully represent the distribution of data encountered during deployment. In other augmentation strategies such as RandAug (Cubuk et al., 2020), augmentations are applied sequentially with fixed intensity which can degrade input quickly. In AugMix, to mitigate input degradation but retain augmentation diversity, several stochastically sampled augmentation chains are layered together in a convex combination to generate highly diverse transformations. These mixing coefficients are randomly sampled from a Dirichlet distribution with shared concentration parameters, and the resulting augmented version of the input is combined with the original input through a second random convex combination sampled from a beta distribution, again with shared parameters. Finally, AugMix minimizes the Jensen-Shannon divergence (JSD) across the softmax-formed distributions p_{orig}, p_{aug1}, and p_{aug2} of the original sample x_{orig} and its augmented variants x_{aug1} and x_{aug2}. This JSD term is computed with $M = (p_{\text{orig}} + p_{\text{aug1}} + p_{\text{aug2}})/3$ and is then

$$\text{JSD} = \frac{1}{3}\Big(\text{KL}(p_{\text{orig}} \parallel M) + \text{KL}(p_{\text{aug1}} \parallel M) + \text{KL}(p_{\text{aug2}} \parallel M)\Big) \tag{4}$$

where $\text{KL}(p \parallel q)$ is Kullback–Leibler divergence from q to p. This drives the model to be stable and consistent across a diverse range of inputs (Zheng et al., 2016; Xie et al., 2019a).

3.2.3 ENSEMBLE CONSISTENCY REGULARIZATION

Consistency regularization works under the assumption that a model should output similar predictions given augmented versions of the same input. This regularization strategy is a common component of semi-supervised learning algorithms with the general form (Sajjadi et al., 2016; Laine &

Alia, 2017) of $\|p_\theta(y|x_{\text{aug1}}) - p_\theta(y|x_{\text{aug2}})\|$ where $p_\theta(y|x)$ is the predicted class distribution produced by the model having parameters θ for input x. We build upon (Tarvainen & Valpola, 2017) and introduce an ensemble consistency regularization (ECR) strategy as

$$\text{ECR} = \frac{1}{N^*} \sum_{i=1}^{N^*} \|p_{\theta'}(y|x) - p_\theta(y|\mathcal{A}(x))\| \tag{5}$$

where x is the unperturbed input, $\mathcal{A}$ is stochastic augmentation function reevaluated for each term, and $\theta'_t = \alpha\theta'_{t-1} + (1-\alpha)\theta_t$. In practice, N^* can be varied during training to mimic a curriculum learning strategy (Bengio et al., 2009), and generally using AugMix for $\mathcal{A}(\cdot)$ performs best while the use of RandAug (Cubuk et al., 2020) can lead to unstable training. In semi-supervised learning techniques it is typical to leverage a larger unsupervised batch-size for consistency regularization. However, as shown in section (4.3), modulating N^* (rather than naively increasing the batch size of the consistency term) is important to achieve good performance. That is, RTE learns using repeated perturbations of the same samples rather than single variations of additional samples.

3.3 FINAL LOSS

We bring the various components defined in sections 3.2 together under a single parsimonious loss function at training defined as

$$L_{\text{RTE}} = \mathcal{L}_q + \lambda_{\text{JSD}} \cdot \text{JSD} + \lambda_{\text{ECR}} \cdot \text{ECR} \tag{6}$$

which is essentially composed of robust task loss and consistency regularization. Here the JSD term is synchronized with ECR by computing the clean distribution using $p_{\theta'}$. Final performance is reported using θ'.

4 EXPERIMENTS

In this section we analyze the performance of RTE against various uniform noise configurations for both symmetric and asymmetric settings. For asymmetric noise, we test both the traditional configuration (Patrini et al., 2016), typically reported by related works, and an additional configuration defined by (7) which is in the spirit of (Lee et al., 2019), where we define the asymmetric noise structure using the confusion matrix of a trained shallow network. In all of these experiments, RTE outperforms existing methods. Finally, we perform additional ablation studies to better understand the contribution and synergy of the terms in equation (6) as well as to probe the efficacy of ECR.

In our experiments we consider the standard CIFAR-10, CIFAR-100, and ImageNet datasets (Krizhevsky, 2009; Deng et al., 2009). CIFAR-10 and CIFAR-100 each contain 50,000 training and 10,000 test images of 10 and 100 classes, respectively; and ImageNet contains approximately 1,000,000 training images and 50,000 validation images of 1000 classes. Additionally, we test networks trained with noisy labels against unforeseen input corruptions using CIFAR-10-C (Hendrycks & Dietterich, 2019) which was constructed by corrupting the original CIFAR-10 test set with a total of 15 noise, blur, weather, and digital corruptions under different severity levels and intensities. Classifier performance is averaged across these corruption types and severity levels to yield *mean corruption error* (mCE). Since CIFAR-10-C is used to measure network behavior under data shift, these 15 corruptions are not included during the training procedure. Here, CIFAR-10-C helps to establish a rigorous benchmark for image classifier robustness to better understand how models trained with noisy data might perform in safety-critical applications.

To mitigate the sensitivity of experimental results to empirical, and perhaps arbitrary, choices of hyperparameters, we present additional results that leverage Population Based Training (PBT) (Jaderberg et al., 2017; Li et al., 2019) which is a simple asynchronous optimisation algorithm that jointly optimize a population of models and their hyperparameters. In particular, PBT discovers a per-epoch *schedule* of hyperparameter settings rather than a static fixed configuration used over the entirety of training. These PBT schedules, for example, allow task loss $\mathcal{L}_q$ to vary between CE and MAE loss dynamically during training and similarly the number of ECR terms N^* can be modulated to realize a form of curriculum learning. Moreover, for our purposes, PBT schedules also provide a form of quasi-ablation study, as optimization of the task-loss parameter q, the number of ECR terms N^*, and the ECR weight λ_{ECR} allows for the realization of a simplified loss which forgos these components

if determined maximally beneficial. We find, as in other studies, that this joint optimization of hyper-parameter schedules typically results in faster wall-clock convergence and higher final performance. (Ho et al., 2019; Li et al., 2019).

4.1 UNIFORM SYMMETRIC NOISE

Training Setup. For CIFAR-10, we leverage equation (2) with $C_{i\neq j}^{10} = \frac{1}{9}$ and we employ a 28-layer residual network (He et al., 2015) with a widening factor of 6 (WNR 28x6) (Zagoruyko & Komodakis, 2016), a dropout rate of 0.01 (Srivastava et al., 2014), $\alpha = 0.99$, AugMix with a mixture width and severity of 3, a batch size of 128, and 300 epochs of training. We optimize using SGD with Nesterov momentum of 0.9 (Sutskever et al., 2013), a weight decay of 0.001, and a cosine learning rate (Loshchilov & Hutter, 2017) of $0.03 \cdot \cos(7\pi k/16K)$, where k is the current training step and K is the total number of training steps. The RTE loss function (6) is configured with static λ_{JSD}, λ_{ECR} and N^* of 12, 1, and 10 respectively while q is prescribed an ad-hoc schedule of $0.6 \cdot \sin(13\pi k/16K)$ which assigns small q-values in early training epochs, reaches a maximum of $q = 0.6$ after 180 epochs, and decreases to $q = 0.33$ over the remaining 120 epochs. For CIFAR-100, the setup is similar, but different hyperparameters are used; details are included in the Appendix in Table 7. In addition to manual configurations, we consider PBT with a population size of 35 to optimize learning rate, weight decay, q, λ_{JSD}, λ_{ECR} and N^*. Fastidious readers will find the complete PBT configuration defined in Appendix C. For ImageNet, ResNet50 is used and trained with SGD for 120 epochs with a stepped learning rate of 0.1, 0.01 and 0.001 which begin at epochs 0, 40 and 80 respectively. ImageNet hyperparameters are also included in the Appendix in Table 7.

Baselines. To best interpret the effectiveness of RTE, we compare our results to many techniques for learning with noise (Table 1). A description of each baseline method can be found in Appendix B. Only two of these references provide ImageNet results trained with label noise (Table 2).

Results. Experimental results with uniform symmetric noise for both CIFAR-10 and CIFAR-100 are presented in Table 1 with comparisons to related work, including current state-of-the-art methods. RTE establishes new state-of-the-art performance at all noise levels and exhibits especially large performance gaps at high noise levels. At 80% noise, previous state-of-the-art was achieved by (Arazo et al., 2019) in the case of CIFAR-10 and by Li et al. (2020) in the case of CIFAR-100. RTE improves performance over these methods by 7.0 absolute percentage points and 6.2 absolute percentage points, respectively. Of all of these works, only two report results on ImageNet training with noisy labels. These are included alongside RTE results in Table 2, where once again we see that RTE performs favorably, improving state-of-the-art performance in terms of both top-1 accuracy and top-5 accuracy. Moreover, Table 5 shows that RTE retains strong corruption robustness with an mCE of 12.05% and 13.50% at noise ratios of 40% and 80% respectively, as measured using CIFAR-10-C. Put in context, experiments summarized in Table 5 indicate that even with extreme levels of mislabeled training data, RTE trained models have lower corruption error than models trained using standard methods using clean data.

4.2 UNIFORM ASYMMETRIC NOISE

Training Setup. For consistency, uniform asymmetric noise experiments use the same hyperparameter configurations outlined in Section 4.1. Here we test RTE performance using both the traditional asymmetric noise configuration (Patrini et al., 2016) typically reported by related works defined by equation (8) as well as an additional configuration in the spirit of (Lee et al., 2019) where we define the asymmetric noise structure using the confusion matrix of a trained shallow network defined by

$$C = \begin{pmatrix} .0000 & .0396 & .2475 & .0594 & .0594 & .0396 & .0495 & .0693 & .2772 & .1584 \\ .1765 & .0000 & .0294 & .0000 & .0000 & .0000 & .0294 & .0000 & .1765 & .5882 \\ .1745 & .0000 & .0000 & .1544 & .1879 & .1074 & .2617 & .0872 & .0268 & .0000 \\ .0388 & .0116 & .1473 & .0000 & .1240 & .3682 & .1899 & .0853 & .0155 & .0194 \\ .0303 & .0000 & .2197 & .1667 & .0000 & .0606 & .2879 & .2121 & .0227 & .0000 \\ .0324 & .0000 & .1435 & .4676 & .1019 & .0000 & .1204 & .1157 & .0093 & .0093 \\ .0536 & .0179 & .3571 & .3036 & .1071 & .0714 & .0000 & .0536 & .0179 & .0179 \\ .0704 & .0000 & .0986 & .1268 & .3803 & .1831 & .0986 & .0000 & .0000 & .0423 \\ .4603 & .0952 & .0794 & .0476 & .0317 & .0000 & .0476 & .0317 & .0000 & .2063 \\ .1711 & .5132 & .0263 & .0526 & .0263 & .0132 & .0658 & .0395 & .0921 & .0000 \end{pmatrix} \quad (7)$$

Table 1: Test accuracy on CIFAR-10 and CIFAR-100 under uniform symmetric label noise. Results in parentheses are upper bounds since they were computed using lower noise levels. The results for Reed-Hard, S-Model, Forward T and Co-Teaching are from Nguyen et al. (2020) and the results for MixUp and Meta-Learning are from Li et al. (2020). RTE provides better robustness to label noise than all other methods. Higher is better.

Method	CIFAR-10		CIFAR-100	
	Noise Ratio		Noise Ratio	
	40%	80%	40%	80%
(Prior Work)				
Reed-Hard (Reed et al., 2014)	69.66	–	51.34	–
S-Model (Goldberger & Ben-Reuven, 2016)	70.64	–	49.10	–
MentorNet PD (Jiang et al., 2018)	77	33	56	14
Forward T (Patrini et al., 2016)	83.25	54.64	31.05	8.90
Open Set (Wang et al., 2018)	78.15	–	–	–
Rand Weights (Ren et al., 2018)	86.06	–	58.01	–
Bi-Level (Jenni & Favaro, 2018)	89	–	61.6	–
GCE (Zhang & Sabuncu, 2018)	(87.12)	(64.07)	(61.77)	(29.16)
Co-Teaching (Han et al., 2018)	81.85	29.22	55.95	23.22
MixUp (Zhang et al., 2018)	–	(71.6)	–	(30.8)
SELFIE (Song et al., 2019)	86.5	–	62.9	–
RoG (Lee et al., 2019)	81.83	–	55.68	–
M-DYR-H (Arazo et al., 2019)	–	86.6	–	48.2
PENCIL (Yi & Wu, 2019)	–	–	69.12	"fail"
Meta-Learning (Li et al., 2019)	–	(77.4)	–	(42.4)
SELF (Nguyen et al., 2020)	93.70	69.91	71.98	42.09
DivideMix (Li et al., 2020)	94.9	79.8	75.2	60.2
(Our Work)				
RTE (Manual)	94.84	93.09	76.70	64.02
RTE (PBT)	**95.52**	**93.64**	**77.44**	**66.43**

Table 2: Validation accuracy on ImageNet with 40% uniform symmetric label noise.

	MentorNet	SELF	RTE
Top-1 Acc	65.1	71.31	**76.72**
Top-5 Acc	85.9	89.92	**93.19**

The asymmetric noise defined by Patrini et al. (2016) in equation (8) does not corrupt all classes but rather attempts to capture a noise process whereby labelers confuse specific pairs of classes which by some is argued to be more realistic in practice (Han et al., 2018; Ren et al., 2018). We additionally consider a rich noise structure by training a shallow classifier (ResNet-10) on clean CIFAR-10 and use the resulting confusion matrix of this model to define the noise structure in equation (7). For example, this asymmetric noise process readily captures the phenomenon that objects on blue backgrounds are often confused (e.g. birds, ships, and airplanes) and its natural asymmetry where $p(\tilde{y}_i = \text{SHIP}|y_i = \text{AIRPLANE}) = 0.2772$ while $p(\tilde{y}_i = \text{AIRPLANE}|y_i = \text{SHIP}) = 0.4603$ (locations $[1, 9]$ and $[9, 1]$ in Eq. 7). Dataset statistics are provided for an instance of CIFAR-10 with

Table 3: Test accuracy on CIFAR-10 with asymmetric noise as defined in Patrini et al. (2016) by equation (8). Higher is better.

| | Noise Ratio: 40% | | | | |
	GCE	SELF	PENCIL	DivideMix	RTE
Test Acc	64.79	89.07	91.16	93.4	**94.49**

Table 4: RTE test performance on CIFAR-10 for different ratios of uniform asymmetric noise defined according to equation (7). Sharp declines in accuracy begin to occur at 65% noise due to more AUTOMOBILE images labeled as TRUCK, than actual TRUCK images labeled as TRUCK, and so on.

| | Noise Ratio | | | | | |
	20%	40%	60%	65%	70%	72%
↑ Test Acc	95.34	94.82	93.99	80.55	72.12	59.70
↓ mCE	11.22	11.89	13.73	25.44	33.61	44.87

asymmetric label noise prescribed according to equation (7) with a uniform noise ratio of 60% in Table 9 of Appendix D .

Baselines. In the case of asymmetric noise as defined in Patrini et al. (2016), by equation (8), we compare the performance of RTE against existing work. A brief description of each baseline method can be found in Appendix B. In the case of asymmetric noise structure as defined in equation (7), to our knowledge, prior work does not exist, and we report RTE performance at varied noise levels.

Results. The results for asymmetric noise as presented in related works defined in Patrini et al. (2016) by equation (8) with a uniform noise ratio of 40% are shown in Table 3 along side the performance of related methods. Again, RTE improves the state-of-the-art performance in this category, with a 1.1 absolute percentage point increase over (Li et al., 2020).

Test accuracy for different level of asymmetric noise using C defined by (7) are shown in Table 4. Even with 60% noise ratio, RTE achieves 93.99% test accuracy. The first significant decline in accuracy occurs around a 65% asymmetric noise ratio, when the majority labels in a class are corrupted labels from another class. That is, for $F_{p=0.65}$ with C defined by (7), there are more AUTOMOBILE images labeled as TRUCKs, than actual TRUCK images labeled as TRUCK.

4.3 ABLATION STUDIES

In this section we present results across two additional ablation studies which help to better understand the contribution of each term in equation (6), as well as to probe the efficacy of ECR. For both ablation studies we use the training configurations defined in section 4.1. Component analysis results of equation 6 are summarized in Table 6 where indeed the removal of any term degrades test accuracy. Figure 1 summarizes the results of two complementary experiments (see Appendix E, Tables 10 and 11). First, we fix the batch size at 128 and vary the number of ECR terms N^*. Second, we use a single consistency loss term and vary the batch size of the ECR component, which is analogous to a more traditional semi-supervised approach where a larger batch size is used for

Table 5: RTE mean corruption error on CIFAR-10-C for models trained at various uniform symmetric noise ratios. Baseline reference values for 'Standard' and 'AugMix' mCE are reported from Hendrycks* et al. (2020) using WRN 40x2 on clean data. Lower is better.

| | | | Noise Ratio | | |
	Standard	AugMix	0%	40%	80%
↓ mCE	26.9	11.2	11.5	12.05	13.50

Table 6: Leave-one-out component ablation study. Here we report CIFAR-10 test accuracy with an 80% uniform symmetric noise ratio across three experiments where individual components of RTE are removed to better understand the contribution of each term in equation (6). That is, in each experiment, 1 of 3 terms is deactivated while the other two terms remain active. In the case of the *no GCE* experiment, standard cross entropy loss was used. Higher is better.

		Test Acc
RTE		93.09
$\lambda_{\mathrm{ECR}} = 0$	no ECR	61.91
$q = 0$	no GCE	76.08
$\lambda_{\mathrm{JSD}} = 0$	no JSD	90.37

Figure 1: RTE ablation study using CIFAR-10 with uniform symmetric noise ratio of 80%. On the left, the ECR batch entries are shared with the task loss and the batch size is fixed at 128, while the number of ECR terms (N^*) is varied. On the right, 1 ECR term is used with varying ECR batch size, using batch entries that are distinct from the task loss (analogous to a more traditional semi-supervised approach). The dashed red line on the right is the ECR baseline established using $N^* = 8$.

unsupervised loss terms. The results of the experiments shown in Figure 1 indicate improved noisy learning performance with smaller batch size and repeated augmentation, in comparison to a larger batch size with a single augmentation per image, supporting the effectiveness of ECR.

5 CONCLUSION

In this paper, we introduced robust temporal ensembling (RTE), a simple and performant method for achieving robustness to label noise. RTE combines a new ensemble consistency regularization term with robust task loss and temporal pseudo-labeling. We demonstrated that RTE performs extremely well in practice, advancing state-of-the-art performance across the CIFAR-10, CIFAR-100, and ImageNet datasets by 7.0, 6.2, and 5.4 absolute percentage points, respectively. These results, alongside comparisons with numerous prior works, can be found in Tables 1, 2, 3, and 4. Moreover, experiments summarized in Tables 4 and 5 show that despite significant label noise, RTE trained models retain lower corruption error on unforeseen data shifts than models trained using standard methods on clean data. Finally, the results of ablation studies, summarized in Table 6 and Figure 1, support the importance of each RTE component as well as the key role played by ECR. Applications of RTE and ECR to different modalities such as natural language processing and speech are important avenues of future work.

REFERENCES

Eric Arazo, Diego Ortego, Paul Albert, Noel E O'Connor, and Kevin McGuinness. Unsupervised label noise modeling and loss correction. *arXiv preprint arXiv:1904.11238*, 2019.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th Annual International Conference on Machine Learning*, ICML '09, pp. 41–48, New York, NY, USA, 2009. Association for Computing Machinery. ISBN 9781605585161. doi: 10.1145/1553374.1553380.

G. E. P. Box and D. R. Cox. An analysis of transformations. *Journal of the Royal Statistical Society. Series B (Methodological)*, 26(2):211–252, 1964. ISSN 00359246.

Ekin D. Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V. Le. Randaugment: Practical automated data augmentation with a reduced search space. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR Workshops 2020, Seattle, WA, USA, June 14-19, 2020*, pp. 3008–3017. IEEE, 2020. doi: 10.1109/CVPRW50498.2020.00359.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255, 2009.

Davide Ferrari and Yuhong Yang. Maximum l q -likelihood estimation. *Ann. Statist.*, 38(2):753–783, 04 2010. doi: 10.1214/09- AOS687.

B. Frenay and M. Verleysen. Classification in the presence of label noise: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, 25(5):845–869, 2014.

Jacob Goldberger and Ehud Ben-Reuven. Training deep neural-networks using a noise adaptation layer. 2016.

Bo Han, Quanming Yao, Xingrui Yu, Gang Niu, Miao Xu, Weihua Hu, Ivor Tsang, and Masashi Sugiyama. Co-teaching: Robust training of deep neural networks with extremely noisy labels. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 8527–8537. Curran Associates, Inc., 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep Residual Learning for Image Recognition. *arXiv e-prints*, art. arXiv:1512.03385, December 2015.

Dan Hendrycks and Thomas Dietterich. Benchmarking neural network robustness to common corruptions and perturbations. *Proceedings of the International Conference on Learning Representations*, 2019.

Dan Hendrycks, Mantas Mazeika, Duncan Wilson, and Kevin Gimpel. Using trusted data to train deep networks on labels corrupted by severe noise. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 10456–10465. Curran Associates, Inc., 2018.

Dan Hendrycks*, Norman Mu*, Ekin Dogus Cubuk, Barret Zoph, Justin Gilmer, and Balaji Lakshminarayanan. Augmix: A simple method to improve robustness and uncertainty under data shift. In *International Conference on Learning Representations*, 2020.

Joel Hestness, Sharan Narang, Newsha Ardalani, Gregory Diamos, Heewoo Jun, Hassan Kianinejad, Md. Mostofa Ali Patwary, Yang Yang, and Yanqi Zhou. Deep Learning Scaling is Predictable, Empirically. *arXiv e-prints*, art. arXiv:1712.00409, December 2017.

Daniel Ho, Eric Liang, Ion Stoica, Pieter Abbeel, and Xi Chen. Population Based Augmentation: Efficient Learning of Augmentation Policy Schedules. *arXiv e-prints*, art. arXiv:1905.05393, May 2019.

Max Jaderberg, Valentin Dalibard, Simon Osindero, Wojciech M. Czarnecki, Jeff Donahue, Ali Razavi, Oriol Vinyals, Tim Green, Iain Dunning, Karen Simonyan, Chrisantha Fernando, and Koray Kavukcuoglu. Population Based Training of Neural Networks. *arXiv e-prints*, art. arXiv:1711.09846, November 2017.

Simon Jenni and Paolo Favaro. Deep bilevel learning. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 618–633, 2018.

Lu Jiang, Zhengyuan Zhou, Thomas Leung, Li-Jia Li, and Li Fei-Fei. Mentornet: Learning data-driven curriculum for very deep neural networks on corrupted labels. In *International Conference on Machine Learning*, pp. 2304–2313, 2018.

Alexander Kolesnikov, Lucas Beyer, Xiaohua Zhai, Joan Puigcerver, Jessica Yung, Sylvain Gelly, and Neil Houlsby. Big Transfer (BiT): General Visual Representation Learning. *arXiv e-prints*, art. arXiv:1912.11370, December 2019.

A. Krizhevsky. Learning multiple layers of features from tiny images. 2009.

Samuli Laine and Timo Alia. Temporal ensembling for semi-supervised learning. In *International Conference on Learning Representations*, 2017.

Kimin Lee, Sukmin Yun, Kibok Lee, Honglak Lee, Bo Li, and Jinwoo Shin. Robust inference via generative classifiers for handling noisy labels. volume 97 of *Proceedings of Machine Learning Research*, pp. 3763–3772, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

Ang Li, Ola Spyra, Sagi Perel, Valentin Dalibard, Max Jaderberg, Chenjie Gu, David Budden, Tim Harley, and Pramod Gupta. A Generalized Framework for Population Based Training. *arXiv e-prints*, art. arXiv:1902.01894, February 2019.

Junnan Li, Yongkang Wong, Qi Zhao, and Mohan S Kankanhalli. Learning to learn from noisy labeled data. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 5051–5059, 2019.

Junnan Li, Richard Socher, and Steven C.H. Hoi. Dividemix: Learning with noisy labels as semi-supervised learning. In *International Conference on Learning Representations*, 2020.

Yuncheng Li, Jianchao Yang, Yale Song, Liangliang Cao, Jiebo Luo, and Li-Jia Li. Learning from noisy labels with distillation. pp. 1928–1936, 10 2017. doi: 10.1109/ICCV.2017.211.

Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. In *International Conference on Learning Representations*, 2017.

Dhruv Mahajan, Ross Girshick, Vignesh Ramanathan, Kaiming He, Manohar Paluri, Yixuan Li, Ashwin Bharambe, and Laurens van der Maaten. Exploring the Limits of Weakly Supervised Pretraining. *arXiv e-prints*, art. arXiv:1805.00932, May 2018.

Aditya Krishna Menon, Ankit Singh Rawat, Sashank J. Reddi, and Sanjiv Kumar. Can gradient clipping mitigate label noise? In *International Conference on Learning Representations*, 2020.

Nagarajan Natarajan, Inderjit S Dhillon, Pradeep K Ravikumar, and Ambuj Tewari. Learning with noisy labels. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger (eds.), *Advances in Neural Information Processing Systems 26*, pp. 1196–1204. Curran Associates, Inc., 2013.

Duc Tam Nguyen, Chaithanya Kumar Mummadi, Thi Phuong Nhung Ngo, Thi Hoai Phuong Nguyen, Laura Beggel, and Thomas Brox. Self: Learning to filter noisy labels with self-ensembling. In *International Conference on Learning Representations*, 2020.

Giorgio Patrini, Alessandro Rozza, Aditya Menon, Richard Nock, and Lizhen Qu. Making Deep Neural Networks Robust to Label Noise: a Loss Correction Approach. *arXiv e-prints*, art. arXiv:1609.03683, September 2016.

Scott Reed, Honglak Lee, Dragomir Anguelov, Christian Szegedy, Dumitru Erhan, and Andrew Rabinovich. Training Deep Neural Networks on Noisy Labels with Bootstrapping. *arXiv e-prints*, art. arXiv:1412.6596, December 2014.

Mengye Ren, Wenyuan Zeng, Bin Yang, and Raquel Urtasun. Learning to reweight examples for robust deep learning. *arXiv preprint arXiv:1803.09050*, 2018.

Mehdi Sajjadi, Mehran Javanmardi, and Tolga Tasdizen. Regularization with stochastic transformations and perturbations for deep semi-supervised learning. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 29*, pp. 1163–1171. Curran Associates, Inc., 2016.

Hwanjun Song, Minseok Kim, and Jae-Gil Lee. SELFIE: Refurbishing unclean samples for robust deep learning. In Kamalika Chaudhuri and Ruslan Salakhutdinov (eds.), *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pp. 5907–5915, Long Beach, California, USA, 09–15 Jun 2019. PMLR.

Hwanjun Song, Minseok Kim, Dongmin Park, and Jae-Gil Lee. Learning from Noisy Labels with Deep Neural Networks: A Survey. *arXiv e-prints*, art. arXiv:2007.08199, July 2020.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: A simple way to prevent neural networks from overfitting. *Journal of Machine Learning Research*, 15(56):1929–1958, 2014.

I. Sutskever, J. Martens, G. Dahl, and G. Hinton. On the importance of initialization and momentum in deep learning. *30th International Conference on Machine Learning, ICML 2013*, pp. 1139–1147, 01 2013.

Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 1195–1204. Curran Associates, Inc., 2017.

Yisen Wang, Weiyang Liu, Xingjun Ma, James Bailey, Hongyuan Zha, Le Song, and Shu-Tao Xia. Iterative learning with open-set noisy labels. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.

Qizhe Xie, Zihang Dai, Eduard Hovy, Minh-Thang Luong, and Quoc V. Le. Unsupervised Data Augmentation for Consistency Training. *arXiv e-prints*, art. arXiv:1904.12848, April 2019a.

Qizhe Xie, Minh-Thang Luong, Eduard Hovy, and Quoc V. Le. Self-training with Noisy Student improves ImageNet classification. *arXiv e-prints*, art. arXiv:1911.04252, November 2019b.

Kun Yi and Jianxin Wu. Probabilistic end-to-end noise correction for learning with noisy labels. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7017–7025, 2019.

Sergey Zagoruyko and Nikos Komodakis. Wide Residual Networks. *arXiv e-prints*, art. arXiv:1605.07146, May 2016.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. *arXiv e-prints*, art. arXiv:1611.03530, November 2016.

Hongyi Zhang, Moustapha Cisse, Yann N. Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018.

Zhilu Zhang and Mert Sabuncu. Generalized cross entropy loss for training deep neural networks with noisy labels. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 8778–8788. Curran Associates, Inc., 2018.

Zizhao Zhang, Han Zhang, Sercan O. Arik, Honglak Lee, and Tomas Pfister. Distilling effective supervision from severe label noise. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

S. Zheng, Y. Song, T. Leung, and I. Goodfellow. Improving the robustness of deep neural networks via stability training. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 4480–4488, 2016.

A APPENDIX: HYPERPARAMETERS

Table 7: Manual hyperparameter configurations for uniform symmetric noise experiments. The two λ values are λ_{JSD} and λ_{ECR}.

	Wt. Decay	β	Dropout	BS	LR	λ	q	N^*	α
CIFAR-10	.001	.9	.01	128	$\cos(\frac{7\pi k}{16K})$	12, 1	$\sin(\frac{13\pi k}{16K})$	10	.99
CIFAR-100	.0005	.9	.01	128	0.04	5, 3	0.3	8	.99
ImageNet	.001	.9	.00	256	.1, .01, .001	12, 1	0.1	3	.99

B APPENDIX: BASELINES FOR TABLE 1

In this section we provide a brief summary of the baseline methods in the main text:

Reed et al. (2014) introduce two methods for achieving prediction consistency, one based on reconstruction and one based on bootstrapping, and demonstrated empirically that bootstrapping leads to better robustness to label noise. **Goldberger & Ben-Reuven (2016)** model the correct label as latent and having gone through a parameterized corruption process. Expectation maximization is used to estimate both the parameters of the corruption process and the underlying latent label. **Jiang et al. (2018)** introduce the idea of *learning* a curriculum-learning strategy with a *mentor* model to train a *student* model to be robust to label noise. **Patrini et al. (2016)** estimate the noise transition matrix (under the assumption of feature independent noise) and show that, given the *true* noise transition matrix, optimizing for the true underlying labels is possible. **Wang et al. (2018)** introduce an iterative scheme that combines 1. outlier detection in feature space (acting as a proxy to noisy-label detection), 2. a Siamese network (taking either a clean, clean pair or a clean, noisy pair) to encourage separation, and 3. sample reweighting based on clean vs. noisy confidence levels in order to effectively filter out noisy labels during training. They focus primarily on *open-set* noise, but they also report performance of their system when used in the *closed-set* setting. **Ren et al. (2018)** use a meta-learning approach to dynamically weight examples to minimize loss *using a set of validation examples with clean labels*, however they also report a competitive baseline using a randomized weighting scheme which requires no clean validation set. **Jenni & Favaro (2018)** formulate example weighting as a bilevel-optimization problem, in which performance on a validation set is maximized with respect to example weights, subject to the constraint that the model maximizes performance on the training set; and they argue that this approach should lead to better generalization when label noise is present. **Zhang & Sabuncu (2018)** introduce a loss function that is a generalization of cross-entropy loss and mean absolute error, which is beneficial since each exhibits distinct desirable properties: cross-entropy exhibits better gradient properties for learning, while mean absolute error exhibits better theoretically-grounded robustness to noisy labels. **Han et al. (2018)** leverage co-teaching such that two networks are trained together, in which each network 1. identifies high-confidence examples, 2. passes this information in a message to its peer, and 3. leverages the incoming message to optimize using the examples selected by its peer. **Zhang et al. (2018)** train using convex combinations of both input images and their labels, arguing that this approach makes it more difficult for the network to memorize corrupt labels. **Song et al. (2019)** measure label consistency throughout training in order to determine which samples are 'refurbishable', and these samples are then 'corrected' by replacing their ground-truth label with the most frequently-predicted label. **Lee et al. (2019)** do not modify the training process of the underlying neural network but instead form a generative model over the final (pre-softmax) features of the neural network, and this generative distribution along with Bayes rule is then used to estimate a more robust conditional distribution over the label. **Arazo et al. (2019)** fit a beta mixture model over the *loss* using two mixture components, representing *clean* and *noisy* labels, and each sample's underlying component probabilities are used to weight each sample's contribution during training. They combine this approach with MixUp (Zhang et al., 2018). **Yi & Wu (2019)** maintain a direct estimate of a distribution over true underlying labels during training, and train the parameters of a neural network by minimizing reverse KL divergence (from the model's predicted distribution to these true-label estimates). Mean-

while a 'compatibility loss' is introduced to ensure that the estimated label distribution stays close to the noisy labels provided with the training set. **Li et al. (2019)** subject a student model to artificial label noise during training and take alternating gradient steps and maintain a teacher model that is not subjected to such noise. Here, alternating gradient steps are taken to 1. minimize classification loss and 2. minimize the KL divergence from the student's predicted distributions to the teacher's predicted distributions. **Nguyen et al. (2020)** use discrepancy between an ensemble-based teacher model and labels to identify and filter out incorrect labels, and continue to leverage these samples without the labels. This is done in a semi-supervised fashion by maintaining consistency between the teacher's predictions and the student's predictions. **Li et al. (2020)** maintain two networks and for each network models *loss* using a mixture of Gaussians with two components (*clean* and *noisy*). Each network estimates which samples belong to each component, and the *other* network then uses the *clean* samples in a supervised manner along with the *noisy* labels in a semi-supervised manner.

C APPENDIX: PBT EXPERIMENTS

Table 8: PBT sampling configuration for CIFAR-10 and CIFAR-100. We used a population size of 35, and permutation interval of 2 epochs. In the case a member inherits another checkpoint, each hyperparameter is resampled from its distribution with $p = 0.25$ or is multiplied with $w \sim \text{Uniform}(0.8, 1.2)$ within its parameter range with $p = 0.75$. In the case of N^*, the previous/next hyperparameter from the ordered list is selected.

Parameter	Sample distribution
Batch size	128
Dropout	0.01
β	0.9
α	0.99
LR	Uniform(0.00001, 0.1)
weight decay	Uniform(0.00005, 0.002)
q	Uniform(0.0, 1.0)
λ_{JSD}	Uniform(0.0, 20.0)
λ_{ECR}	Uniform(0.0, 5.0)
N^*	Uniform$\{3, ..., 10\}$

D APPENDIX: UNIFORM ASYMMETRIC NOISE ON CIFAR-10

The matrix C defines the noise structure for uniform asymmetric noise on CIFAR-10 with following labels: AIRPLANE, AUTOMOBILE, BIRD, CAT, DEER, DOG, FROG, HORSE, SHIP, TRUCK.

$$C = \begin{pmatrix} 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{pmatrix} \tag{8}$$

E APPENDIX: ABLATION STUDIES EXTENDED DATA

Figure 2: Parameter schedules for lr, weight decay, JSD weight λ_{JSD}, ECR weight λ_{ECR}, q and N^* for CIFAR-10 and CIFAR-100 with 40% and 80% uniform symmetric noise rates.

Table 9: Overview of class distribution of total and correct labels after sampling noisy CIFAR-10 training labels with asymmetric noise defined by equation (7) with a uniform 60% noise ratio.

	# samples	% samples	# correct labels	% correct labels
AIRPLANE	5578	11%	1958	35%
AUTOMOBILE	4069	8%	2003	49%
BIRD	6023	12%	2017	33%
CAT	6205	12%	2038	33%
DEER	5056	10%	1986	39%
DOG	4480	9%	1977	44%
FROG	5476	11%	2019	37%
HORSE	4130	8%	2028	49%
SHIP	3896	8%	2024	52%
TRUCK	5087	10%	1950	38%
TOTAL	50000	100%	20000	40%

Table 10: RTE test accuracy and mean corruption error (mCE) on CIFAR-10 and CIFAR-10-C, respectively. In this experiment, fixed batch size of $bs = 128$ is used and the number of ECR terms, N^* is varied. Training configuration of these data is described in section 4.1. Test accuracy is presented in Figure 1 (left).

CIFAR-10							
Fixed batch-size: 128							
Uniform Symmetric Noise: 80%							
Vary the number of ECR terms: N^*							
1	2	3	4	5	6	7	8
↑ Test Acc	91.51	91.90	92.57	92.65	92.77	93.14	93.09	93.21
↓ mCE	15.32	14.87	13.74	13.90	13.84	13.48	13.67	13.66

Table 11: RTE test accuracy and mean corruption error (mCE) on CIFAR-10 and CIFAR-10-C, respectively. In this experiment a single consistency loss term is used and vary the batch size of that term. This experiment with varying batch size is analogous to a more traditional semi-supervised approach where large batch size is used for unsupervised loss terms. Training configuration for these data is described in section 4.1. Test accuracy is presented in Figure 1 (right).

CIFAR-10					
Fixed ECR terms: $N^* = 1$					
Uniform Symmetric Noise: 80%					
Vary the batch size:					
32	64	128	256	512	1024
↑ Test Acc	86.54	88.95	90.32	88.46	85.87	78.13
↓ mCE	19.77	17.78	16.41	18.20	20.42	28.57