SINGLE-LEVEL ADVERSARIAL DATA SYNTHESIS BASED ON NEURAL TANGENT KERNELS

ABSTRACT

Generative adversarial networks (GANs) have achieved impressive performance in data synthesis and have driven the development of many applications. However, GANs are known to be hard to train due to their bilevel objective, which leads to the problems of convergence, mode collapse, and gradient vanishing. In this paper, we propose a new generative model called the generative adversarial NTK (GA-NTK) that has a single-level objective. The GA-NTK keeps the spirit of adversarial learning (which helps generate plausible data) while avoiding the training difficulties of GANs. This is done by modeling the discriminator as a Gaussian process with a neural tangent kernel (NTK-GP) whose training dynamics can be completely described by a closed-form formula. We analyze the convergence behavior of GA-NTK trained by gradient descent and give some sufficient conditions for convergence. We also conduct extensive experiments to study the advantages and limitations of GA-NTK and propose some techniques that make GA-NTK more practical.[1]

1 INTRODUCTION

Generative adversarial networks (GANs) Goodfellow et al. (2014); Radford et al. (2016), a branch of deep generative models based on adversarial learning, have received much attention due to their novel problem formulation and impressive performance in data synthesis. Variants of GANs have also driven recent developments of many applications, such as super-resolution Ledig et al. (2017), image inpainting Xu et al. (2014), and video generation Vondrick et al. (2016).

A GANs framework consists of a discriminator network $\mathcal{D}$ and a generator network $\mathcal{G}$ parametrized by $\boldsymbol{\theta}_{\mathcal{D}}$ and $\boldsymbol{\theta}_{\mathcal{G}}$, respectively. Given a d-dimensional data distribution $\mathcal{P}_{\text{data}}$ and a c-dimensional noise distribution $\mathcal{P}_{\text{noise}}$, the generator $\mathcal{G}$ maps a random noise $\boldsymbol{z} \in \mathbb{R}^c$ to a point $\mathcal{G}(\boldsymbol{z}) \in \mathbb{R}^d$ in the data space, while the discriminator $\mathcal{D}$ takes a point $\boldsymbol{x}' \in \mathbb{R}^d$ as the input and tells whether $\boldsymbol{x}'$ is real or fake, i.e., $\mathcal{D}(\boldsymbol{x}') = 1$ if $\boldsymbol{x}' \sim \mathcal{P}_{\text{data}}$ and $\mathcal{D}(\boldsymbol{x}') = 0$ if $\boldsymbol{x}' \sim \mathcal{P}_{\text{gen}}$, where $\mathcal{P}_{\text{gen}}$ is the distribution of $\mathcal{G}(\boldsymbol{z})$ and $\boldsymbol{z} \sim \mathcal{P}_{\text{noise}}$. The objective of GANs is typically formulated as a bilevel optimization problem:

$$\arg\min_{\boldsymbol{\theta}_{\mathcal{G}}} \max_{\boldsymbol{\theta}_{\mathcal{D}}} \mathbb{E}_{\boldsymbol{x} \sim \mathcal{P}_{\text{data}}}[\log \mathcal{D}(\boldsymbol{x})] + \mathbb{E}_{\boldsymbol{z} \sim \mathcal{P}_{\text{noise}}}[\log(1 - \mathcal{D}(\mathcal{G}(\boldsymbol{z})))]. \tag{1}$$

The discriminator $\mathcal{D}$ and generator $\mathcal{G}$ aim to break each other through the inner $\max$ and outer $\min$ objectives, respectively. The studies Goodfellow et al. (2014); Radford et al. (2016) show that this adversarial formulation can lead to a better generator that produces plausible data points/images.

However, GANs are known to be hard to train due to the following issues Goodfellow (2016). **Failure to converge.** In practice, Eq. (1) is usually only approximately solved by an alternating first-order method such as the alternating stochastic gradient descent (SGD). The alternating updates for $\boldsymbol{\theta}_{\mathcal{D}}$ and $\boldsymbol{\theta}_{\mathcal{G}}$ may cancel each other's progress. During each alternating training step, it is also tricky to balance the number of SGD updates for $\boldsymbol{\theta}_{\mathcal{D}}$ and that for $\boldsymbol{\theta}_{\mathcal{G}}$, as a too small or large number for $\boldsymbol{\theta}_{\mathcal{D}}$ leads to low-quality gradients for $\boldsymbol{\theta}_{\mathcal{G}}$. **Mode collapse.** The alternating SGD is attracted by stationary points and therefore is not good at distinguishing between a $\min_{\boldsymbol{\theta}_{\mathcal{G}}} \max_{\boldsymbol{\theta}_{\mathcal{D}}}$ problem and a $\max_{\boldsymbol{\theta}_{\mathcal{D}}} \min_{\boldsymbol{\theta}_{\mathcal{G}}}$ problem. When the solution to the latter is returned, the generator tends to always produce the points at modes that best deceive the discriminator, making $\mathcal{P}_{\text{gen}}$ of low diversity.

---

[1]Our code is available on GitHub at `https://github.com/ga-ntk/ga-ntk`.

Vanishing gradients. At the beginning of a training process, the finite real and fake training data may not overlap with each other in the data space, and thus the discriminator may be able to perfectly separate the real from fake data. Given the cross-entropy loss (or more generally, any f-divergence measure between $\mathcal{P}_{\text{data}}$ and $\mathcal{P}_{\text{gen}}$), the value of the discriminator becomes saturated on both sides of the decision boundary, resulting in zero gradients for $\boldsymbol{\theta}_{\mathcal{G}}$.

In this paper, we argue that the above issues are rooted in the modeling of $\mathcal{D}$. In most existing variants of GANs, the discriminator is a deep neural network with explicit weights $\boldsymbol{\theta}_{\mathcal{D}}$. Under gradient descent, the gradients of $\boldsymbol{\theta}_{\mathcal{G}}$ in Eq. (1) cannot be back-propagated through the inner $\max_{\boldsymbol{\theta}_{\mathcal{D}}}$ problem because otherwise it requires the computation of high-order derivatives of $\boldsymbol{\theta}_{\mathcal{D}}$. This motivates the use of alternating SGD, which in turn causes the convergence issues and mode collapse. Furthermore, the $\mathcal{D}$ is a single network whose particularity may cause a catastrophic effect, such as the vanishing gradients, during training.

We instead model the discriminator $\mathcal{D}$ as a Gaussian process whose mean and covariance are governed by a kernel function called the neural tangent kernel (NTK-GP) Jacot et al. (2018); Lee et al. (2019); Chizat et al. (2019). The $\mathcal{D}$ approximates an infinite ensemble of infinitely wide neural networks in a nonparametric manner and has no explicit weights. In particular, its training dynamics can be completely described by a closed-form formula. This allows us to simplify adversarial data synthesis into a single-level optimization problem, which we call the generative adversarial NTK (GA-NTK). Moreover, since $\mathcal{D}$ is an infinite ensemble of networks, the particularity of a single element network does not drastically change the training process. This makes GA-NTK less prone to vanishing gradients and stabilizes training even when an f-divergence measure between $\mathcal{P}_{\text{data}}$ and $\mathcal{P}_{\text{gen}}$ is used as the loss of $\mathcal{D}$. The following summarizes our contributions:

- We propose a single-level optimization method, named GA-NTK, for adversarial data synthesis. It can be solved by ordinary gradient descent, avoiding the difficulties of bi-level optimization in GANs.

- We prove the convergence of GA-NTK training under mild conditions. We also show that $\mathcal{D}$ being an infinite ensemble of networks can provide smooth gradients for $\mathcal{G}$, which stabilizes GA-NTK training and helps fight vanishing gradients.

- We propose some practical techniques to reduce the memory consumption of GA-NTK during training and improve the quality of images synthesized by GA-NTK.

- We conduct extensive experiments on real-world datasets to study the advantages and limitations of GA-NTK. In particular, we find that GA-NTK has much lower sample complexity as compared to GANs, and the presence of a generator is not necessary to generate images under the adversarial setting.

Note that the goal of this paper is not to replace existing GANs nor advance the state-of-the-art performance, but to show that adversarial data synthesis can be done via a single-level modeling. Our work has implications for future research. In particular, the low sample complexity makes GA-NTK suitable for applications, such as medical imaging, where data are personalized or not easily collectible. In addition, GA-NTK bridges the gap between kernel methods and adversarial data/image synthesis and thus enables future studies on the relationship between kernels and generated data.

2 RELATED WORK

2.1 GANS AND IMPROVEMENTS

The study Goodfellow et al. (2014) proposes GANs and gives a theoretical convergence guarantee in the function space. However, in practice, one can only optimize the generator and discriminator in Eq. (1) in the parameter/weight space. Many techniques have been proposed to make the bilevel optimization easier. **Failure to convergence.** To solve this problem, studies devise new training algorithms for GANs Nagarajan & Kolter (2017); Daskalakis et al. (2018) or more general minimax problems Thekumparampil et al. (2019); Mokhtari et al. (2020). But recent works Mescheder et al. (2018); Farnia & Ozdaglar (2020) show that there may not be a Nash equilibrium solution in GANs. **Mode collapse.** The study Metz et al. (2017) alleviates this issue by back-propagating the computation of $\boldsymbol{\theta}_{\mathcal{G}}$ through the discriminators trained with several steps to strengthen the $\min_{\boldsymbol{\theta}_{\mathcal{G}}} \max_{\boldsymbol{\theta}_{\mathcal{D}}}$

property. Other works mitigate mode collapse by diversifying the modes of $\mathcal{D}$ through regularization Salimans et al. (2016); Srivastava et al. (2017); Che et al. (2017) or modeling $\mathcal{D}$ as an ensemble of multiple neural networks Durugkar et al. (2017); Ghosh et al. (2018). **Vanishing gradients.** The study Mao et al. (2017) tries to solve this problem by using the Pearson χ^2-divergence between $\mathcal{P}_{\text{data}}$ and $\mathcal{P}_{\text{gen}}$ as the loss to penalize data points that are far away from the decision boundary. However, it still suffers from vanishing gradients as any f-divergence measure, including the cross-entropy loss and Pearson χ^2-divergence, cannot measure the difference between disjoint distributions Sajjadi et al. (2018). Later studies replace the loss with either the Wasserstein distance Arjovsky et al. (2017); Gulrajani et al. (2017) or maximum mean discrepancy Gretton et al. (2012); Li et al. (2015; 2017) that can measure the divergence of disjoint $\mathcal{P}_{\text{data}}$ and $\mathcal{P}_{\text{gen}}$. In addition, the works Miyato et al. (2018); Qi (2020) aim to constrain the Lipschitz continuity of the discriminator to prevent its value from being saturated.

Despite that many efforts have been made to improve the training of GANs, most existing approaches address only one or two issues at a time with different assumptions, and in the meanwhile, they introduce new hyperparameters or side effects. For example, in the Wasserstein GANs Arjovsky et al. (2017); Gulrajani et al. (2017) mentioned above, efficient computation of Wasserstein distance requires the discriminator to be Lipschitz continuous. However, realizing Lipschitz continuity introduces new hyperparameters and could limit the expressiveness of the discriminator Anil et al. (2019). Until now, training GANs is still not an easy task because one has to 1) tune many hyperparameters and 2) strike a balance between the benefits and costs of different training techniques to generate satisfactory data points/images.

2.2 GAUSSIAN PROCESSES AND NEURAL TANGENT KERNELS

Consider an infinite ensemble of infinitely wide networks that use the mean square error (MSE) as the loss and are trained by gradient descent. Recent developments in deep learning theory show that the prediction of the ensemble can be approximated by a special instance of Gaussian process called NTK-GP Jacot et al. (2018); Lee et al. (2019); Chizat et al. (2019). The NTK-GP is a Bayesian method, so it outputs a distribution of possible values for an input point. The mean and covariance of the NTK-GP prediction are governed by a kernel function $k(\cdot, \cdot)$ called the neural tangent kernel (NTK). Given two data points $\boldsymbol{x}^i$ and $\boldsymbol{x}^j$, the $k(\boldsymbol{x}^i, \boldsymbol{x}^j)$ represents the similarity score of the two points in a kernel space, which is fixed once the hyperparameters of the initial weights, activation function, and architecture of the networks in the target ensemble are determined.

Here, we focus on the mean prediction of NTK-GP as it is relevant to our study. Consider a supervised learning task given $\mathbb{D}^n = (\boldsymbol{X}^n \in \mathbb{R}^{n \times d}, \boldsymbol{Y}^n \in \mathbb{R}^{n \times c})$ as the training set, where there are n examples and each example consists of a pair of d-dimensional input and c-dimensional output. Let $\boldsymbol{K}^{n,n} \in \mathbb{R}^{n \times n}$ be the kernel matrix for $\boldsymbol{X}^n$, i.e., $K_{i,j}^{n,n} = k(\boldsymbol{X}_{i,:}^n, \boldsymbol{X}_{j,:}^n)$. Then, at time step t during gradient descent, the mean prediction of NTK-GP for $\boldsymbol{X}^n$ evolve as

$$(\boldsymbol{I}^n - e^{-\eta \boldsymbol{K}^{n,n} t}) \boldsymbol{Y}^n \in \mathbb{R}^{n \times c}, \tag{2}$$

where $\boldsymbol{I}^n \in \mathbb{R}^{n \times n}$ is an identity matrix and η is a sufficiently small learning rate Jacot et al. (2018); Lee et al. (2019).

The NTK used in Eq. (2) can be extended to support different network architectures, including convolutional neural networks (CNNs) Arora et al. (2019); Novak et al. (2019b); Garriga-Alonso et al. (2019); Yang (2019a), recurrent neural networks (RNNs) Alemohammad et al. (2021); Yang (2019b), networks with the attention mechanism Hron et al. (2020), and other architectures Yang (2019b); Arora et al. (2019).

A recent study by Franceschi et al. Franceschi et al. (2021) analyzes the behavior of GANs from the NTK perspective by taking into account the alternating optimization. It shows that, in theory, the discriminator can provide a well-defined gradient flow for the generator, which is opposite to previous theoretical interpretations Arjovsky & Bottou (2017). Our work, on the other hand, focuses on adversarial data synthesis *without* alternating optimization.[2] We make contributions in this direction by (1) formally proving the convergence of the proposed single-level optimization, (2) showing that

---

[2]From GAN perspective, our work can be regarded as a special case of the framework proposed by Franceschi et al. Franceschi et al. (2021), where the discriminator neglects the effect of historical generator updates and only distinguish between the true and currently generated data at each alternating step.

a generator network is not necessary to generate plausible images (although it my be desirable), and (3) proposing the batch-wise and multi-resolutional extensions that respectively improves the memory efficiency of training and global coherency of generated image patterns, respectively.

3 GA-NTK

We present a new adversarial data synthesis method, called the generative adversarial NTK (GA-NTK), based on the NTK theory Jacot et al. (2018); Lee et al. (2019); Chizat et al. (2019). For simplicity of presentation, we let $\mathcal{G}(\boldsymbol{z}) = \boldsymbol{z} \in \mathbb{R}^d$ and focus on the discriminator for now. We will discuss the case where $\mathcal{G}(\cdot)$ is a generator network in Section 3.2. Given an unlabeled, d-dimensional dataset $\boldsymbol{X}^n \in \mathbb{R}^{n \times d}$ of n points, we first augment $\boldsymbol{X}^n$ to obtain a labeled training set $\mathbb{D}^{2n} = (\boldsymbol{X}^n \oplus \boldsymbol{Z}^n \in \mathbb{R}^{2n \times d}, \boldsymbol{1}^n \oplus \boldsymbol{0}^n \in \mathbb{R}^{2n})$, where $\boldsymbol{Z}^n \in \mathbb{R}^{n \times d}$ contains n generated points, $\boldsymbol{1}^n \in \mathbb{R}^n$ and $\boldsymbol{0}^n \in \mathbb{R}^n$ are label vectors of ones and zeros, respectively, and $\oplus$ is the vertical stack operator. Then, we model a discriminator trained on $\mathbb{D}^{2n}$ as an NTK-GP. Let $\boldsymbol{K}^{2n,2n} \in \mathbb{R}^{2n \times 2n}$ be the kernel matrix for $\boldsymbol{X}^n \oplus \boldsymbol{Z}^n$, where the value each element $K_{i,j}^{2n,2n} = k((\boldsymbol{X}^n \oplus \boldsymbol{Z}^n)_{i,:}, (\boldsymbol{X}^n \oplus \boldsymbol{Z}^n)_{j,:})$ can be computed once we decide the initialization, activation function, and architecture of the element networks in the target infinite ensemble, i.e., the discriminator. By Eq. (2) and let $\lambda = \eta \cdot t$, the mean predictions of the discriminator can be written as

$$\mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n; k, \lambda) = (\boldsymbol{I}^{2n} - e^{-\lambda \boldsymbol{K}^{2n,2n}})(\boldsymbol{1}^n \oplus \boldsymbol{0}^n) \in \mathbb{R}^{2n}, \qquad (3)$$

where $\boldsymbol{I}^{2n} \in \mathbb{R}^{2n \times 2n}$ is an identity matrix. We formulate the objective of GA-NTK as follows:

$$\arg \min_{\boldsymbol{Z}^n} \mathcal{L}(\boldsymbol{Z}^n) = \arg \min_{\boldsymbol{Z}^n} \|\boldsymbol{1}^{2n} - \mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n; k, \lambda)\|_2, \qquad (4)$$

where $\mathcal{L}(\cdot)$ is the loss function and $\boldsymbol{1}^{2n} \in \mathbb{R}^{2n}$ is a vector of ones. GA-NTK aims to find points $\boldsymbol{Z}^n$ that best deceive the discriminator such that it outputs wrong labels $\boldsymbol{1}^{2n}$ for these points. On the other hand, the discriminator is trained on $\mathbb{D}^{2n}$ with the correct labels $\boldsymbol{1}^n \oplus \boldsymbol{0}^n$ and therefore has the opposite goal of distinguishing between the real and generated points.

GA-NTK formulates an adversarial data synthesis task as a single-level optimization problem. This is achievable because the training dynamics of the discriminator $\mathcal{D}$ by gradient descent can be completely described by a closed-form formula in Eq. (3). Any change of $\boldsymbol{Z}^n$ causes $\mathcal{D}$ to be "retrained" instantly. Therefore, one can easily solve Eq. (4) by 1) randomly initiating $\boldsymbol{Z}^n$, and 2) updating $\boldsymbol{Z}^n$ using the ordinary gradient descent steps. With different initial values, the resulting points in $\boldsymbol{Z}^n$ may be different, giving creativity.

3.1 MERITS

As compared to GANs, GA-NTK offers the following advantages: **Convergence.** The GA-NTK can be trained by ordinary gradient descent. This gives much nicer convergence properties:

Theorem 3.1 *Let s be the number of the gradient descent iterations solving Eq. (4), and let $\boldsymbol{Z}^{n,(j)}$ be the solution at the j-th iteration. Suppose the following values are bounded: (a) $\boldsymbol{X}_{i,j}^n$ and $\boldsymbol{Z}_{i,j}^{n,(0)}$, $\forall i, j$, (b) t and η, and (c) σ and L. Also, assume that (d) $\boldsymbol{X}^n$ contains finite, non-identical, normalized rows. Then, for a sufficiently large t, we have*

$$\min_{j \in s} \|\nabla_{\boldsymbol{Z}^n} \mathcal{L}(\boldsymbol{Z}^{n,(j)})\|^2 \leq O(\frac{1}{s-1}).$$

We prove the above theorem by showing that, with a large enough λ, $\nabla_{\boldsymbol{Z}^n} \mathcal{L}(\boldsymbol{Z}^{n,(j)})$ is smooth enough to lead to the convergence of gradient descent. For more details, please see Section 6 in Appendix. **Diversity.** GA-NTK is not subject to mode collapse because there is no confusion between the min-max and max-min problems in Eq. (4). Given different initial values, the generated points in $\boldsymbol{Z}^n$ can be very different from each other. **No vanishing gradients, no side effects.** The hyperparameter λ controls how much $\mathcal{D}$ should learn from the true and fake data during each iteration. Figure 5 shows the gradients of $\mathcal{D}$ with a finite λ, which do not saturate. This avoids the necessity of using a loss that imposes side effects, such as the Wasserstein distance Arjovsky et al. (2017); Gulrajani et al. (2017) whose efficient evaluation requires Lipschitz continuity of $\mathcal{D}$.

Note that the above merits hold only when the hyperparameter λ is large enough but finite. We show that it can be tuned *before* training by using a simple line search. Please see Section 7.3 in Appendix for details.

3.2 GA-NTK in Practice

Scalability. To generate a large number of points, we can parallelly solve multiple $\boldsymbol{Z}^n$'s in Eq. (4) on different machines. On a single machine, the gradients of $\boldsymbol{Z}^n$ need to be back-propagated through the computation of $\boldsymbol{K}^{2n,2n}$, which has $O(n^2)$ space complexity. This may incur scalability issues for large datasets. Although recent efforts Arora et al. (2019); Bietti & Mairal (2019); Han et al. (2021) have been made to reduce the time and space complexity of the evaluation of NTK and its variants, they are still at an early stage of development and the consumed space in practice may still be too large. To alleviate this problem, we propose the batch-wise GA-NTK with the objective

$$\arg\min_{\boldsymbol{Z}^n} \mathbb{E}_{\boldsymbol{X}^{b/2} \subset \boldsymbol{X}^n, \boldsymbol{Z}^{b/2} \subset \boldsymbol{Z}^n} \| \mathbf{1}^b - \mathcal{D}(\boldsymbol{X}^{b/2}, \boldsymbol{Z}^{b/2}; k, \lambda) \|, \tag{5}$$

that can be solved using mini-batches: during each gradient descent iteration, we 1) randomly sample a batch of b rows in $\boldsymbol{X}^n \oplus \boldsymbol{Z}^n$ and their corresponding labels, and 2) update $\boldsymbol{Z}^n$ based on $\boldsymbol{K}^{b,b}$. Although the batch-wise GA-NTK is cosmetically similar to the original GA-NTK, it solves a different problem. In the original GA-NTK, the $\boldsymbol{Z}^n$ aims to fool a single discriminator $\mathcal{D}$ trained on $2n$ examples, while in the batch-wise GA-NTK, the $\boldsymbol{Z}^n$'s goal is to deceive *many* discriminators, each trained on b examples only. Fortunately, studies Shankar et al. (2020); Arora et al. (2020) have shown that NTK-based methods perform well on small datasets. We will conduct experiments to verify this later.

Generator Network. So far, we let $\mathcal{G}(\boldsymbol{z}) = \boldsymbol{z}$ and show that a generator is *not* necessary in adversarial data synthesis.[3] Nevertheless, the presence of a generator network may be favorable in some applications to save time and memory at inference time. This can be done by extending the batch-wise GA-NTK as follows:

$$\arg\min_{\boldsymbol{\theta}_{\mathcal{G}}} \mathbb{E}_{\boldsymbol{X}^{b/2} \subset \boldsymbol{X}^n, \boldsymbol{Z}^{b/2} \sim \mathcal{N}(\mathbf{0},\mathbf{I})} \| \mathbf{1}^b - \mathcal{D}(\boldsymbol{X}^{b/2}, \mathcal{G}(\boldsymbol{Z}^{b/2}; \boldsymbol{\theta}_{\mathcal{G}}); k, \lambda) \|, \tag{6}$$

where $\mathcal{G}(\cdot; \boldsymbol{\theta}_{\mathcal{G}})$ is a generator network parametrized by $\boldsymbol{\theta}_{\mathcal{G}}$, and $\boldsymbol{Z} \in \mathbb{R}^l$ where $l \leq d$. Note that this is still a single-level objective, and $\boldsymbol{\theta}_{\mathcal{G}}$ can be solved by gradient descent. We denote this variant GA-NTKg.

Image Quality. To generate images, one can pair up GA-NTK with a convolutional neural tangent kernel (CNTK) Arora et al. (2019); Novak et al. (2019b); Garriga-Alonso et al. (2019); Yang (2019a) that approximates a CNN with infinite channels. This allows the NTK-GP (discriminator) to distinguish between real and fake points based on local patterns in the pixel space. However, the images synthesized by this GA-NTK variant may lack global coherency, just like the images generated by the CNN-based GANs Radford et al. (2016); Salimans et al. (2016). Many efforts have been made to improve the image quality of CNN-based GANs, and this paper opens up opportunities for them to be adapted to the kernel regime. In particular, we propose the multi-resolutional GA-CNTK based on the work Wang et al. (2018), whose objective is formulated as:

$$\arg\min_{\boldsymbol{Z}^n} \sum_m \| \mathbf{1}^{2n} - \mathcal{D}^m(\text{pool}^m(\boldsymbol{X}^n), \text{pool}^m(\boldsymbol{Z}^n); k^m, \lambda^m) \|, \tag{7}$$

where $\mathcal{D}^m$ is an NTK-GP taking input at a particular pixel resolution and $\text{pool}^m(\cdot)$ is a downsample operation (average pooling) applied to each row of $\boldsymbol{X}^n$ and $\boldsymbol{Z}^n$. The generated points in $\boldsymbol{Z}^n$ aim to simultaneously fool multiple NTK-GPs (discriminators), each classifying real and fake images at a distinct pixel resolution. The NTK-GPs working at low and high resolutions encourage global coherency and details, respectively, and together they lead to more plausible points in $\boldsymbol{Z}^n$.

4 Experiments

We conduct experiments to study how GA-NTK works in image generation.

---

[3]In GANs, solving $\boldsymbol{Z}$ directly against a finite-width discriminator is infeasible because it amounts to finding adversarial examples Goodfellow et al. (2015) whose gradients are known to be very noisy Ilyas et al. (2019).

Datasets. We consider the unsupervised/unconditional image synthesis tasks over real-world datasets, including MNIST LeCun et al. (2010), CIFAR-10 Krizhevsky (2009), CelebA Liu et al. (2015), CelebA-HQ Liu et al. (2015), and ImageNet Deng et al. (2009). To improve training efficiency, we resize CelebA images to 64×64 and ImageNet images to 128×128 pixels, respectively. We also create a 2D toy dataset consisting of 25-modal Gaussian mixtures of points to visualize the behavior of different image synthesis methods. **GA-NTK implementations.** GA-NTK works with different NTK-GPs. For the image synthesis tasks, we consider the NTK-GPs that model the ensembles of fully-connected networks Jacot et al. (2018); Lee et al. (2019); Chizat et al. (2019) and convolutional networks Arora et al. (2019); Novak et al. (2019b); Garriga-Alonso et al. (2019); Yang (2019a), respectively. We implement GA-NTK using the Neural Tangents library Novak et al. (2019a) and call the variants based on the former and latter NTK-GPs the GA-FNTK and GA-CNTK, respectively. In GA-FNTK, an element network of the discriminator has 3 infinitely wide, fully-connected layers with ReLU non-linearity, while in GA-CNTK, an element network follows the architecture of InfoGAN Chen et al. (2016) except having infinite filters at each layer. We tune the hyperparameters of GA-FNTK and GA-CNTK following the method proposed in Poole et al. (2016); Schoenholz et al. (2017); Raghu et al. (2017). We also implement their batch-wise, generator, and multi-resolutional variants described in Section 3.2. See Section 7 in Appendix for more details. **Baselines.** We compare GA-NTK with some popular variants of GANs, including vanilla GANs Goodfellow et al. (2014), DCGAN Radford et al. (2016), LSGAN Mao et al. (2017), WGAN Arjovsky et al. (2017), WGAN-GP Gulrajani et al. (2017), SNGAN Miyato et al. (2018) and StyleGAN2 Karras et al. (2020). To give a fair comparison, we let the discriminator of each baseline follow the architecture of InfoGAN Chen et al. (2016) and tune the hyperparameters using grid search. **Metrics.** We evaluate the quality of a set of generated images using the Fréchet Inception Distance (FID) Heusel et al. (2017). The lower the FID score the better. We find that an image synthesis method may produce downgrade images that look almost identical to some images in the training set. Therefore, we also use a metric called the average max-SSIM (AM-SSIM) that calculates the average of the maximum SSIM score Wang et al. (2004) between $\mathcal{P}_{\text{gen}}$ and $\mathcal{P}_{\text{data}}$:

$$\text{AM-SSIM}(\mathcal{P}_{\text{gen}}, \mathcal{P}_{\text{data}}) = \mathbb{E}_{\boldsymbol{x}' \sim \mathcal{P}_{\text{gen}}} \big[\max_{\boldsymbol{x} \sim \mathcal{P}_{\text{data}}} \text{SSIM}(\boldsymbol{x}', \boldsymbol{x}) \big].$$

A generated image set will have a higher AM-SSIM score if it contains downgrade images. **Environment and limitations.** We conduct all experiments on a cluster of machines having 80 NVIDIA Tesla V100 GPUs. As discussed in 3.2, GA-NTK consumes a significant amount of memory on each machine due to the computations involved in the kernel matrix $\boldsymbol{K}^{2n,2n}$. With the current version of Neural Tangents library Novak et al. (2019a) and a V100 GPU of 32GB RAM, the maximum sizes of the training set from MNIST, CIFAR-10, CelebA, and ImageNet are 1024, 512, 256, and 128, respectively (where the computation graph and backprop operations of $\boldsymbol{K}^{2n,2n}$ consume about 27.5 GB RAM excluding other necessary operations). Since our goal is not to achieve state-of-the-art performance but to compare different image synthesis methods, we train all the methods using up to 256 images randomly sampled from all classes of MNIST, the "horse" class CIFAR-10, the "male with straight hair" class of CelebA, and the "daisy" class of ImageNet, respectively. We will conduct larger-scale experiments in Section 8.2. For more details about our experiment settings, please see Section 7 in Appendix.

4.1 Image Quality

We first study the quality of the images synthesized by different methods. Table 1 summarizes the FID and AM-SSIM scores of the generated images. LSGAN and DCGAN using f-divergence as the loss function give high FID and fail to generate recognizable images on CIFAR-10 and CelebA datasets due to the various training issues mentioned previously. StyleGAN, although being able to generate impressive images with sufficient training data, gives high FID here due to the high sample complexity of the style-based generator. Other baselines, including WGAN, WGAN-GP, and SN-GAN, can successfully generate recognizable images on all datasets, as shown in Figure 1. In particular, WGAN-GP performs the best among the GAN variants. However, WGAN-GP limits the Lipschitz continuity of the discriminator and gives higher FID scores than GA-CNTK. Also, it gives higher AM-SSIM values as the size of the training set decreases, implying there are many downgrade images that look identical to some training images. This is because the Wasserstein distance, which is also called the earth mover's distance, allows fewer ways of moving when there are less available "earth" (i.e., the density values of $\mathcal{P}_{\text{data}}$ and $\mathcal{P}_{\text{gen}}$) due to a small n, and thus the $\mathcal{P}_{\text{gen}}$

Table 1: The FID and AM-SSIM scores of the images generated by different methods.

	n	Metric	DCGAN	LSGAN	WGAN	WGANGP	SNGAN	StyleGAN	GACNTK	GACNTKg
MNIST	64	FID	27.43	69.76	50.69	32.49	57.89	91.82	31.10	32.43
		AMSSIM	0.84	0.79	0.77	0.83	0.67	0.69	0.49	0.71
	128	FID	31.89	38.52	49.28	30.20	38.33	88.31	21.14	36.50
		AMSSIM	0.85	0.80	0.74	0.76	0.67	0.66	0.52	0.72
	256	FID	69.76	35.33	50.33	24.37	29.49	84.7	14.96	51.21
		AMSSIM	0.69	0.78	0.72	0.73	0.70	0.65	0.54	0.73
CIFAR-10	64	FID	312.21	258.41	117.85	49.29	118.16	406.02	55.54	106.44
		AMSSIM	0.22	0.25	0.29	0.74	0.28	0.64	0.41	0.44
	128	FID	229.94	339.27	101.90	68.53	128.65	484.36	39.98	61.19
		AMSSIM	0.36	0.10	0.26	0.60	0.21	0.39	0.41	0.44
	256	FID	181.15	255.19	111.92	85.34	107.29	426.58	28.40	55.46
		AMSSIM	0.27	0.22	0.22	0.46	0.20	0.26	0.42	0.44
CelebA	64	FID	489.82	83.71	122.36	83.71	169.04	323.37	30.83	95.91
		AMSSIM	0.02	0.05	0.29	0.56	0.29	0.23	0.60	0.21
	128	FID	55.01	450.81	125.82	92.73	168.11	337.58	33.51	58.39
		AMSSIM	0.03	0.11	0.28	0.54	0.28	0.21	0.51	0.38
	256	FID	461.95	403.79	108.07	79.36	161.20	333.16	63.15	78.46
		AMSSIM	0.04	0.09	0.31	0.39	0.27	0.30	0.38	0.40

Figure 1: The images generated by different methods on MNIST, CIFAR-10, and CelebA datasets given only 256 training images.

(a) GA-CNTK   (b) GA-CNTKg

Figure 2: The images generated by GA-CNTK (a) without and (b) with a generator given 256 CelebA-HQ training images.

(a) MNIST   (b) CIFAR-10   (c) CelebA

Figure 3: The learning curve and image quality at different stages of a training process.

needs to be exactly the same as $\mathcal{P}_{\text{data}}$ to minimize the distance.[4] The GA-NTK variants, including GA-CNTK and GA-CNTKg ("g" means "with generator") perform relatively well due to their lower sample complexity, which aligns with the previous observations Shankar et al. (2020); Arora et al. (2020) in different context.

Next, we compare the images generated by the multi-resolutional GA-CNTK and GA-CNTKg (see Section 3.2) on the CelebA-HQ dataset. The multi-resolutional GA-CNTK employs 3 discriminators working at 256×256, 64×64, and 16×16 pixel resolutions, respectively. Figure 2 shows the results. We can see that the multi-resolutional GA-CNTK (without a generator) gives better-looking images than GA-CNTKg (with a generator) because learning a generator is essentially a harder problem than finding a set of plausible $\boldsymbol{z}$'s. This shows that a generator may not be necessary to generate high-quality images under the adversarial setting.

4.2 TRAINING STABILITY

Convergence. Figure 3 shows the learning curve and the relationship between the image quality and the number of gradient descent iterations during a training process of GA-CNTK. We find that GA-CNTK easily converges under various conditions, which is supported by Theorem 3.1. Furthermore, we can see a correlation between the image quality and the loss value—as

---

[4]The problem of Lipschitz continuity may be alleviated when n becomes larger.

(a) Truth   (b) Vanilla GAN   (c) LSGAN   (d) WGAN   (e) WGAN-GP   (f) SN-GAN   (g) GA-FNTK

Figure 4: Visualization of distribution alignment and mode collapse on a 2D toy dataset.

the loss becomes smaller, the quality of the synthesized images improves. This correlation can save human labor from monitoring the training processes, which is common when training GANs.

Mode collapse. To study how different methods align $\mathcal{P}_{\text{gen}}$ with $\mathcal{P}_{\text{data}}$, we train them using a 2D toy training set where $\mathcal{P}_{\text{data}}$ is a 25-modal Gaussian mixture. We use two 3-layer FNNs as the generator and discriminator for each baseline and an ensemble of 3-layer, infinitely wide FNN as the discriminator in GA-FNTK. For GANs, we stop the alternating SGD training when the generator receives 1000 updates, and for GA-FNTK, we terminate the GD training after 1000 iterations. Figure 4 shows the resultant $\mathcal{P}_{\text{gen}}$ of different methods. By avoiding the use of alternating SGD, GA-FNTK is free from mode collapse. **Gradient vanishing.** To verify that GA-NTK gives no vanishing gradients with a finite λ, we conduct an experiment using another toy dataset consisting of 256 MNIST images and 256 random noises. We replace the discriminator of GA-CNTK with a single parametric network of the same architecture but finite width. We train the finite-width network on the toy dataset by minimizing the MSE loss using gradient descent. We set the training iteration to a large value (65536) to simulate the situation where the network value becomes saturated on both sides of the decision boundary. Figure 5 compares the gradients of a generated image $\boldsymbol{Z}_{i,:}^{n}$ in Eq. (4) obtained from 1) the finite-width network and 2) the corresponding GA-CNTK with a large t. As $\boldsymbol{Z}_{i,:}^{n}$ evolves through gradient descent iterations, the norm of its gradients obtained from the finite-width discriminator quickly shrinks to zero. On the other hand, the gradient norm obtained from the discriminator of GA-CNTK is always positive thanks to the infinite ensembling.

(a)

(b)

Figure 5: Comparison between the gradients of a $\boldsymbol{Z}_{i,:}$ in Eq. (4) obtained from $\mathcal{D}$ as a (a) CNN and (b) NTK-GP (infinite ensemble of networks).

4.3 SCALABILITY

Unlike GA-CNTK, the GA-CNTKg is batch-wise and thus can be trained by more examples. Here, we scale up WGAN-GP and GA-CNTKg by training them on CelebA dataset consisting of 2048 images. The batch size is 256. Table 2 summarizes the FID and AM-SSIM scores of the generated images. On MNIST, WGAN-GP slightly outperforms GA-CNTKg. The training of WGAN-GP on MNIST is easy, so GA-CNTKg does not offer much advantage. However, in a more complex task like CIFAR-10 or CelebA, GA-CNTKg outperforms WGAN-GP, suggesting that our single-level modeling is indeed beneficial.

We have conducted more experiments. Please see Appendix for their results.

Table 2: The FID and AM-SSIM scores of the images output by WGAN-GP and GA-CNTKg trained on 2048 CelebA images with batch size 256.

n=2048	Metric	WGANGP	GACNTKg
MNIST	FID	23.47	56.73
	ASSIM	0.786	0.787
CIFAR-10	FID	110.70	78.85
	ASSIM	0.404	0.432
CelebA	FID	67.29	59.91
	ASSIM	0.337	0.411

5 CONCLUSION

We proposed GA-NTK and showed that adversarial data synthesis can be done via a single-level modeling. It can be solved by ordinary gradient descent, avoiding the difficulties of bi-level training of GANs. We analyzed the convergence behavior of GA-NTK and gave sufficient conditions for convergence. Extensive experiments were conducted to study the advantages and limitations of GA-NTK. We proposed the batch-wise and multi-resolutional variants to improve memory efficiency and image quality, and showed that GA-NTK works either with or without a generator network. GA-NTK works well with small data, making it suitable for applications where data are hard to collect. GA-NTK also opens up opportunities for one to adapt various GAN enhancements into the kernel regime. These are matters of our future inquiry.

REFERENCES

Sina Alemohammad, Zichao Wang, Randall Balestriero, and Richard G. Baraniuk. The recurrent neural tangent kernel. In *Proc. of ICLR*, 2021.

Cem Anil, James Lucas, and Roger Grosse. Sorting out lipschitz function approximation. In *Proc. of ICML*, 2019.

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. In *Proc. of ICLR*, 2017.

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *Proc. of ICML*, 2017.

Sanjeev Arora, Simon S. Du, Wei Hu, Zhiyuan Li, Ruslan Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. In *Proc. of NeurIPS*, 2019.

Sanjeev Arora, Simon S. Du, Zhiyuan Li, Ruslan Salakhutdinov, Ruosong Wang, and Dingli Yu. Harnessing the power of infinitely wide deep nets on small-data tasks. In *Proc. of ICLR*, 2020.

Paul Bergmann, Sindy Löwe, Michael Fauser, David Sattlegger, and Carsten Steger. Improving unsupervised defect segmentation by applying structural similarity to autoencoders. In *VISIGRAPP*, 2019.

Alberto Bietti and Julien Mairal. On the inductive bias of neural tangent kernels. In *Proc. of NeurIPS*, 2019.

Tong Che, Yanran Li, Athul Paul Jacob, Yoshua Bengio, and Wenjie Li. Mode regularized generative adversarial networks. In *Proc. of ICLR*, 2017.

Xi Chen, Yan Duan, Rein Houthooft, John Schulman, Ilya Sutskever, and Pieter Abbeel. Infogan: Interpretable representation learning by information maximizing generative adversarial nets. In *Proc. of NeurIPS*, 2016.

Lenaic Chizat, Edouard Oyallon, and Francis Bach. On lazy training in differentiable programming. In *Proc. of NeurIPS*, 2019.

Constantinos Daskalakis, Andrew Ilyas, Vasilis Syrgkanis, and Haoyang Zeng. Training gans with optimism. In *Proc. of ICLR*, 2018.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proc. of CVPR*, 2009.

Ishan P. Durugkar, Ian Gemp, and Sridhar Mahadevan. Generative multi-adversarial networks. In *Proc. of ICLR*, 2017.

Farzan Farnia and Asuman E. Ozdaglar. Do gans always have nash equilibria? In *Proc. of ICML*, 2020.

Jean-Yves Franceschi, Emmanuel de Bézenac, Ibrahim Ayed, Mickaël Chen, Sylvain Lamprier, and Patrick Gallinari. A neural tangent kernel perspective of gans. *CoRR*, abs/2106.05566, 2021.

Adrià Garriga-Alonso, Carl Edward Rasmussen, and Laurence Aitchison. Deep convolutional networks as shallow gaussian processes. In *Proc. of ICLR*, 2019.

Arnab Ghosh, Viveka Kulharia, Vinay P. Namboodiri, Philip H. S. Torr, and Puneet Kumar Dokania. Multi-agent diverse generative adversarial networks. In *Proc. of CVPR*, 2018.

Ian Goodfellow. Nips 2016 tutorial: Generative adversarial networks. *arXiv preprint arXiv:1701.00160*, 2016.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Proc. of NeurIPS*, 2014.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *Proc. of ICLR*, 2015.

Robert M Gower. Convergence theorems for gradient descent, May 2022. `https://gowerrobert.github.io/pdf/M2_statistique_optimisation/grad_conv.pdf`.

Arthur Gretton, Karsten M. Borgwardt, Malte J. Rasch, Bernhard Schölkopf, and Alexander J. Smola. A kernel two-sample test. *J. Mach. Learn. Res.*, 2012.

Ishaan Gulrajani, Faruk Ahmed, Martín Arjovsky, Vincent Dumoulin, and Aaron C. Courville. Improved training of wasserstein gans. In *Proc. of NeurIPS*, 2017.

Insu Han, Haim Avron, Neta Shoham, Chaewon Kim, and Jinwoo Shin. Random features for the neural tangent kernel. *CoRR*, abs/2104.01351, 2021.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. In *Proc. of NeurIPS*, 2017.

Jiri Hron, Yasaman Bahri, Jascha Sohl-Dickstein, and Roman Novak. Infinite attention: NNGP and NTK for deep attention networks. In *Proc. of ICML*, 2020.

Andrew Ilyas, Shibani Santurkar, Dimitris Tsipras, Logan Engstrom, Brandon Tran, and Aleksander Madry. Adversarial examples are not bugs, they are features. In *Proc. of NeurIPS*, 2019.

Arthur Jacot, Franck Gabriel, and Clement Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Proc. of NeurIPS*, 2018.

Tero Karras, Samuli Laine, Miika Aittala, Janne Hellsten, Jaakko Lehtinen, and Timo Aila. Analyzing and improving the image quality of stylegan. In *Proc. of CVPR*, 2020.

Alex Krizhevsky. Learning multiple layers of features from tiny images. Technical report, 2009.

Yann LeCun, Corinna Cortes, and CJ Burges. Mnist handwritten digit database. *ATT Labs [Online]. Available: http://yann.lecun.com/exdb/mnist*, 2, 2010.

Christian Ledig, Lucas Theis, Ferenc Huszar, Jose Caballero, Andrew Cunningham, Alejandro Acosta, Andrew P. Aitken, Alykhan Tejani, Johannes Totz, Zehan Wang, and Wenzhe Shi. Photo-realistic single image super-resolution using a generative adversarial network. In *Proc. of CVPR*, 2017.

Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as gaussian processes. In *Proc. of ICLR*, 2018.

Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. In *Proc. of NeurIPS*, 2019.

Chun-Liang Li, Wei-Cheng Chang, Yu Cheng, Yiming Yang, and Barnabás Póczos. MMD GAN: towards deeper understanding of moment matching network. In *Proc. of NeurIPS*, 2017.

Yujia Li, Kevin Swersky, and Richard S. Zemel. Generative moment matching networks. In *Proc. of ICML*, 2015.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proc. of ICCV*, December 2015.

Mario Lucic, Karol Kurach, Marcin Michalski, Sylvain Gelly, and Olivier Bousquet. Are gans created equal? A large-scale study. In *Proc. of NeurIPS*, 2018.

Xudong Mao, Qing Li, Haoran Xie, Raymond Y. K. Lau, Zhen Wang, and Stephen Paul Smolley. Least squares generative adversarial networks. In *Proc. of ICCV*, 2017.

Alexander G de G Matthews, Jiri Hron, Mark Rowland, Richard E Turner, and Zoubin Ghahramani. Gaussian process behaviour in wide deep neural networks. In *Proc. of ICLR*, 2018.

Lars M. Mescheder, Andreas Geiger, and Sebastian Nowozin. Which training methods for gans do actually converge? In *Proc. of ICML*, 2018.

Luke Metz, Ben Poole, David Pfau, and Jascha Sohl-Dickstein. Unrolled generative adversarial networks. In *Proc. of ICLR*, 2017.

Takeru Miyato, Toshiki Kataoka, Masanori Koyama, and Yuichi Yoshida. Spectral normalization for generative adversarial networks. In *Proc. of ICLR*, 2018.

Aryan Mokhtari, Asuman E. Ozdaglar, and Sarath Pattathil. A unified analysis of extra-gradient and optimistic gradient methods for saddle point problems: Proximal point approach. In *Proc. of AISTATS*, 2020.

Vaishnavh Nagarajan and J. Zico Kolter. Gradient descent GAN optimization is locally stable. In *Proc. of NeurIPS*, 2017.

Roman Novak, Lechao Xiao, Jiri Hron, Jaehoon Lee, Alexander A Alemi, Jascha Sohl-Dickstein, and Samuel S Schoenholz. Neural tangents: Fast and easy infinite neural networks in python. In *Proc. of ICLR*, 2019a.

Roman Novak, Lechao Xiao, Jaehoon Lee, Yasaman Bahri, Greg Yang, Jiri Hron, Daniel A. Abolafia, Jeffrey Pennington, and Jascha Sohl-Dickstein. Bayesian deep convolutional networks with many channels are gaussian processes. In *Proc. of ICLR*, 2019b.

Ben Poole, Subhaneil Lahiri, Maithra Raghu, Jascha Sohl-Dickstein, and Surya Ganguli. Exponential expressivity in deep neural networks through transient chaos. In *Proc. of NeurIPS*, 2016.

Guo-Jun Qi. Loss-sensitive generative adversarial networks on lipschitz densities. *Int. J. Comput. Vis.*, 2020.

Alec Radford, Luke Metz, and Soumith Chintala. Unsupervised representation learning with deep convolutional generative adversarial networks. In *Proc. of ICLR*, 2016.

Maithra Raghu, Ben Poole, Jon M. Kleinberg, Surya Ganguli, and Jascha Sohl-Dickstein. On the expressive power of deep neural networks. In *Proc. of ICML*, 2017.

Mehdi S. M. Sajjadi, Giambattista Parascandolo, Arash Mehrjou, and Bernhard Schölkopf. Tempered adversarial networks. In *Proc. of ICML*, 2018.

Tim Salimans, Ian J. Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. In *Proc. of NeurIPS*, 2016.

Samuel S. Schoenholz, Justin Gilmer, Surya Ganguli, and Jascha Sohl-Dickstein. Deep information propagation. In *Proc. of ICLR*, 2017.

Vaishaal Shankar, Alex Fang, Wenshuo Guo, Sara Fridovich-Keil, Jonathan Ragan-Kelley, Ludwig Schmidt, and Benjamin Recht. Neural kernels without tangents. In *Proc. of ICML*, 2020.

Akash Srivastava, Lazar Valkov, Chris Russell, Michael U. Gutmann, and Charles Sutton. VEE-GAN: reducing mode collapse in gans using implicit variational learning. In *Proc. of NeurIPS*, 2017.

Kiran Koshy Thekumparampil, Prateek Jain, Praneeth Netrapalli, and Sewoong Oh. Efficient algorithms for smooth minimax optimization. In *Proc. of NeurIPS*, 2019.

Carl Vondrick, Hamed Pirsiavash, and Antonio Torralba. Generating videos with scene dynamics. In *Proc. of NeurIPS*, 2016.

Ting-Chun Wang, Ming-Yu Liu, Jun-Yan Zhu, Andrew Tao, Jan Kautz, and Bryan Catanzaro. High-resolution image synthesis and semantic manipulation with conditional gans. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 8798–8807, 2018.

Zhou Wang, Alan C Bovik, Hamid R Sheikh, and Eero P Simoncelli. Image quality assessment: from error visibility to structural similarity. *IEEE transactions on image processing*, 2004.

Li Xu, Jimmy S. J. Ren, Ce Liu, and Jiaya Jia. Deep convolutional neural network for image deconvolution. In *Proc. of NeurIPS*, 2014.

Greg Yang. Scaling limits of wide neural networks with weight sharing: Gaussian process behavior, gradient independence, and neural tangent kernel derivation. *CoRR*, abs/1902.04760, 2019a.

Greg Yang. Tensor programs I: wide feedforward or recurrent neural networks of any architecture are gaussian processes. *CoRR*, abs/1910.12478, 2019b.

6 PROOF OF THEOREM 3.1

In this section, we prove the convergence of an GA-NTK whose discriminator $\mathcal{D}$ approximates an infinite ensemble of infinitely-wide, fully-connected, feedforward neural networks. The proof can be easily extended to other network architectures such as the convolutional neural networks.

6.1 BACKGROUND AND NOTATION

Consider a fully-connected, feedforward neural network $f : \mathbb{R}^d \to \mathbb{R}$,

$$f(\boldsymbol{x};\boldsymbol{\theta}) = \frac{\sigma_w}{\sqrt{d^{L-1}}}\boldsymbol{w}^L\phi\left(\frac{\sigma_w}{\sqrt{d^{L-2}}}\boldsymbol{W}^{L-1}\phi\left(\cdots\phi\left(\frac{\sigma_w}{\sqrt{d}}\boldsymbol{W}^1\boldsymbol{x}+\sigma_b\boldsymbol{b}^1\right)\cdots\right)+\sigma_b\boldsymbol{b}^{L-1}\right)+\sigma_b\boldsymbol{b}^L, \tag{8}$$

where $\phi(\cdot)$ is the activation function (applied element-wisely), L is the number of hidden layers, $\{d^1,\cdots,d^{L-1}\}$ are the dimensions (widths) of hidden layers, $\boldsymbol{\theta} = \cup_{l=1}^{L}\boldsymbol{\theta}^l = \cup_{l=1}^{L}(\boldsymbol{W}^l \in \mathbb{R}^{d^l\times d^{l-1}}, \boldsymbol{b}^l \in \mathbb{R}^{d^l})$ are trainable weights and biases whose initial values are i.i.d. Gaussian random variables $\mathcal{N}(0,1)$, and σ_w^2 and σ_b^2 are scaling factors that control the variances of weights and biases, respectively. Suppose f is trained on a labeled dataset $\mathbb{D}^{2n} = (\boldsymbol{X}^n\oplus\boldsymbol{Z}^n \in \mathbb{R}^{2n\times d}, \mathbf{1}^n\oplus\mathbf{0}^n \in \mathbb{R}^{2n})$ by minimizing the MSE loss using t gradient-descent iterations with the learning rate η. Let $\boldsymbol{\theta}^{(0)}$ and $\boldsymbol{\theta}^{(t)}$ be the initial and trained parameters, respectively. As $d^1,\cdots,d^L\to\infty$, we can approximate the distribution of $f(\boldsymbol{x};\boldsymbol{\theta}^{(t)})$ as a Gaussian process (NTK-GP) Jacot et al. (2018); Lee et al. (2019); Chizat et al. (2019) whose behavior is controlled by a kernel matrix

$$\boldsymbol{K}^{2n,2n} = \nabla_{\boldsymbol{\theta}}f(\boldsymbol{X}^n\oplus\boldsymbol{Z}^n;\boldsymbol{\theta}^{(0)})^\top\nabla_{\boldsymbol{\theta}}f(\boldsymbol{X}^n\oplus\boldsymbol{Z}^n;\boldsymbol{\theta}^{(0)}) \in \mathbb{R}^{2n\times 2n}, \tag{9}$$

where $f(\boldsymbol{X}^n\oplus\boldsymbol{Z}^n;\boldsymbol{\theta}^{(0)}) \in \mathbb{R}^{2n}$ is the vector of in-sample predictions made by the initial f. The value of each element $K_{i,j}^{2n,2n} = k^L((\boldsymbol{X}^n\oplus\boldsymbol{Z}^n)_{i,:},(\boldsymbol{X}^n\oplus\boldsymbol{Z}^n)_{j,:})$ presents the similarity score of two rows (points) of $\boldsymbol{X}^n\oplus\boldsymbol{Z}^n$ in a kernel space, and it can be expressed by a kernel function $k^L : \mathbb{R}^d\times\mathbb{R}^d \to \mathbb{R}$, called the neural tangent kernel (NTK). The NTK is deterministic as it depends only on $\phi(\cdot)$, σ_w, σ_b, and L rather than the specific values in $\boldsymbol{\theta}^{(0)}$. Furthermore, it can be evaluated layer-wisely. Let $h_j^l(\boldsymbol{x}) \in \mathbb{R}^{d^l}$ be the pre-activation of the j-th neuron at the l-th layer of $f(\boldsymbol{x};\boldsymbol{\theta}^{(t)})$. The distribution of $h_j^l(\boldsymbol{x})$ is still an NTK-GP, and its associated NTK is defined as $k^l : \mathbb{R}^d\times\mathbb{R}^d \to \mathbb{R}$,

$$k^l(\boldsymbol{x},\boldsymbol{x}') = \nabla_{\boldsymbol{\theta}^{\leq l}}h_j^l(\boldsymbol{x})^\top\nabla_{\boldsymbol{\theta}^{\leq l}}h_j^l(\boldsymbol{x}'),$$

where $\boldsymbol{\theta}^{\leq l} = \cup_{i=1}^{l}\boldsymbol{\theta}^i$. Note that all $h_j^l(\boldsymbol{x})$'s, $\forall j$, are i.i.d. and thus share the same kernel. It can be shown that

$$\begin{aligned} k^l(\boldsymbol{x},\boldsymbol{x}') &= \nabla_{\boldsymbol{\theta}^l}h_j^l(\boldsymbol{x})^\top\nabla_{\boldsymbol{\theta}^l}h_j^l(\boldsymbol{x}') + \nabla_{\boldsymbol{\theta}^{\leq l-1}}h_j^l(\boldsymbol{x})^\top\nabla_{\boldsymbol{\theta}^{\leq l-1}}h_j^l(\boldsymbol{x}') \\ &= \tilde{k}^l(\boldsymbol{x},\boldsymbol{x}') + \sigma_w^2 k^{l-1}(\boldsymbol{x},\boldsymbol{x}')\mathbb{E}_{(h_j^{(l-1)}(\boldsymbol{x}),h_j^{(l-1)}(\boldsymbol{x}'))\sim\mathcal{N}(\mathbf{0}^2,\tilde{\boldsymbol{K}}^{l-1})}\left[\phi'(h_j^{(l-1)}(\boldsymbol{x}))\phi'(h_j^{(l-1)}(\boldsymbol{x}'))\right] \end{aligned} \tag{10}$$

and

$$k^1(\boldsymbol{x},\boldsymbol{x}') = \frac{\sigma_w^2}{d}\boldsymbol{x}^\top\boldsymbol{x}' + \sigma_b^2 \tag{11}$$

where $\tilde{k}^l : \mathbb{R}^d\times\mathbb{R}^d \to \mathbb{R}$ is the NNGP kernel Lee et al. (2018); Matthews et al. (2018) that controls the behavior of another Gaussian process, called NNGP, approximating the distribution of $f(\boldsymbol{x};\boldsymbol{\theta}^{(0)})$, and

$$\tilde{\boldsymbol{K}}^{l-1} = \begin{bmatrix} \tilde{k}^{l-1}(\boldsymbol{x},\boldsymbol{x}) & \tilde{k}^{l-1}(\boldsymbol{x},\boldsymbol{x}') \\ \tilde{k}^{l-1}(\boldsymbol{x},\boldsymbol{x}') & \tilde{k}^{l-1}(\boldsymbol{x}',\boldsymbol{x}') \end{bmatrix} \in \mathbb{R}^{2\times 2}.$$

6.2 CONVERGENCE

The GA-NTK employs the above NTK-GP as the discriminator $\mathcal{D}$. So, the in-sample mean predictions of $\mathcal{D}$ can be written as a closed-form formula:

$$\mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n) = (\boldsymbol{I}^{2n} - e^{-\eta t \boldsymbol{K}^{2n,2n}})\boldsymbol{y}^{2n} \in \mathbb{R}^{2n}, \tag{12}$$

where $\boldsymbol{I}^{2n}$ is an identity matrix and $\boldsymbol{y}^{2n} = \boldsymbol{1}^n \oplus \boldsymbol{0}^n \in \mathbb{R}^{2n}$ is the "correct" label vector for training $\mathcal{D}$. We formulate the objective of GA-NTK as:

$$\arg\min_{\boldsymbol{Z}^n} \mathcal{L}(\boldsymbol{Z}^n) = \arg\min_{\boldsymbol{Z}^n} \frac{1}{2}\|\boldsymbol{1}^{2n} - \mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n)\|^2, \tag{13}$$

where $\boldsymbol{1}^{2n} \in \mathbb{R}^{2n}$ in the loss $\mathcal{L}(\cdot)$ is the "wrong" label vector that guides us to find the points $(\boldsymbol{Z}^n)$ that best deceive the discriminator. We show that

Theorem 6.1 *Let s be the number of the gradient descent iterations solving Eq. (13), and let $\boldsymbol{Z}^{n,(j)}$ be the solution at the j-th iteration. Suppose the following values are bounded: (a) $\boldsymbol{X}_{i,j}^n$ and $\boldsymbol{Z}_{i,j}^{n,(0)}$, $\forall i, j$, (b) t and η, and (c) σ and L. Also, assume that (d) $\boldsymbol{X}^n$ contains finite, non-identical, normalized rows. Then, for a sufficiently large t, we have*

$$\min_{j \in s} \|\nabla_{\boldsymbol{Z}^n} \mathcal{L}(\boldsymbol{Z}^{n,(j)})\|^2 \le O(\frac{1}{s-1}).$$

6.3 PROOF

To prove Theorem 6.1, we first introduce the notion of β smoothness:

Definition 6.1 *A continuously differentiable function $g : \mathbb{R}^d \to \mathbb{R}$ is β-smooth if there exits $\beta \in \mathbb{R}$ such that*

$$\|\nabla_{\boldsymbol{a}} g(\boldsymbol{a}) - \nabla_{\boldsymbol{b}} g(\boldsymbol{b})\| \le \beta \|\boldsymbol{a} - \boldsymbol{b}\|$$

for any $\boldsymbol{a}, \boldsymbol{b} \in \mathbb{R}^d$.

It can be shown Gower (2022) that gradient descent finds a stationary point of a β-smooth function efficiently.

Lemma 6.1 *Let $\boldsymbol{a}^{(s)}$ be the input of a function $g : \mathbb{R}^d \to \mathbb{R}$ after applying s gradient descent iterations to an initial input $\boldsymbol{a}^{(0)}$. If g is β-smooth, then $g(\boldsymbol{a}^{(s)})$ converges to a stationary point at rate*

$$\min_{j \in s} \|\nabla_{\boldsymbol{a}} g(\boldsymbol{a}^{(j)})\|^2 \le O(\frac{1}{s-1}).$$

So, our goal is to show that the loss $\mathcal{L}(\boldsymbol{Z}^n)$ in Eq. (13) is β-smooth w.r.t. any generated point $\boldsymbol{z} \in \mathbb{R}^d$.

Corollary 6.1 *If all the conditions (a)-(d) in Theorem 6.1 hold, there exits a constant $c_1 \in \mathbb{R}^+$ such that $\|\nabla_{\boldsymbol{z}} \mathcal{L}(\boldsymbol{Z}^n)\| \le c_1$ for each row $\boldsymbol{z} \in \mathbb{R}^d$ of $\boldsymbol{Z}^n$. This makes $\mathcal{L}(\boldsymbol{Z}^n)$ β-smooth.*

To prove Corollary 6.1, consider $\mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n)$ and $\nabla_{z_j} \mathcal{L}(\boldsymbol{Z}^n)$, the i-th and j-th elements of $\mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n) \in \mathbb{R}^{2n}$ and $\nabla_{\boldsymbol{z}} \mathcal{L}(\boldsymbol{Z}^n) \in \mathbb{R}^d$, respectively. We have

$$\begin{aligned}
\nabla_{z_j} \mathcal{L}(\boldsymbol{Z}^n) &= \nabla_{z_j} \frac{1}{2}\|\boldsymbol{1}^{2n} - \mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n)\|^2 \\
&= \sum_{i=1}^{2n} (\mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n) - 1) \cdot \nabla_{z_j} \mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n)
\end{aligned} \tag{14}$$

Given a sufficiently large t, the $\mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n)$ can be arbitrarily close to $y_i \in \{0, 1\}$ because $\boldsymbol{K}^{2n,2n}$ is positive definite Jacot et al. (2018) and therefore $(\boldsymbol{I}^{2n} - e^{-\eta t \boldsymbol{K}^{2n,2n}}) \to \boldsymbol{I}^{2n}$ as $t \to \infty$ in Eq. (12). There exists $\epsilon \in \mathbb{R}^+$ such that

$$\begin{aligned}
\nabla_{z_j} \mathcal{L}(\boldsymbol{Z}^n) &\le \epsilon \sum_{i=1}^{n} \nabla_{z_j} \mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n) + (1+\epsilon) \sum_{i=n+1}^{2n} \nabla_{z_j} \mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n) \\
&\le (1+\epsilon) \sum_{i=1}^{2n} \nabla_{z_j} \mathcal{D}_i(\boldsymbol{X}^n, \boldsymbol{Z}^n) \\
&= (1+\epsilon) \sum_{i=1}^{2n} \nabla_{z_j} \sum_{p=1}^{2n} (I_{i,p}^{2n} - e_{i,p}^{-\eta t \boldsymbol{K}^{2n,2n}}) y_p^{2n} \\
&= (1+\epsilon) \eta t \sum_{i,p,q=1}^{2n} e_{i,q}^{-\eta t \boldsymbol{K}^{2n,2n}} \nabla_{z_j} k^L((\boldsymbol{X}^n \oplus \boldsymbol{Z}^n)_{q,:}, (\boldsymbol{X}^n \oplus \boldsymbol{Z}^n)_{p,:}) y_p^{2n}.
\end{aligned}$$

Note that $e_{i,q}^{-\eta t \boldsymbol{K}^{2n,2n}} \in \mathbb{R}$ can be arbitrarily close to 0 with a sufficiently large t. Hence, Corollary 6.1 holds as long as $\nabla_{z_j} k^L((\boldsymbol{X}^n \oplus \boldsymbol{Z}^n)_{q,:}, (\boldsymbol{X}^n \oplus \boldsymbol{Z}^n)_{p,:})$ is bounded.

Corollary 6.2 *If the conditions (a)-(d) in Theorem 6.1 hold, there exits a constant $c_2 \in \mathbb{R}^+$ such that $\nabla_{z_j} k^L(\boldsymbol{a}, \boldsymbol{b}) \leq c_2$ for any rows $\boldsymbol{a}$ and $\boldsymbol{b}$ of $\boldsymbol{X}^n \oplus \boldsymbol{Z}^n$.*

It is clear that $\nabla_{z_j} k^L(\boldsymbol{a}, \boldsymbol{b}) = 0$ if $\boldsymbol{a}, \boldsymbol{b} \neq \boldsymbol{z}$. So, without loss of generality, we consider $\nabla_{z_j} k^L(\boldsymbol{a}, \boldsymbol{z})$ only. From Eq. (10), we have

$$\frac{\partial k^L(\boldsymbol{a}, \boldsymbol{z})}{\partial z_j} = \frac{\partial k^L(\boldsymbol{a}, \boldsymbol{z})}{\partial k^{L-1}(\boldsymbol{a}, \boldsymbol{z})} \frac{\partial k^{L-1}(\boldsymbol{a}, \boldsymbol{z})}{\partial k^{L-2}(\boldsymbol{a}, \boldsymbol{z})} \cdots \frac{\partial k^1(\boldsymbol{a}, \boldsymbol{z})}{\partial z_j}.$$

For each $l = 2, \cdots, L$, we can bound $\partial k^l(\boldsymbol{a}, \boldsymbol{z}) / \partial k^{l-1}(\boldsymbol{a}, \boldsymbol{z})$ by

$$
\begin{aligned}
\frac{\partial k^l(\boldsymbol{a}, \boldsymbol{z})}{\partial k^{l-1}(\boldsymbol{a}, \boldsymbol{z})} &= \sigma_w^2 \mathbb{E}_{(h_j^{(l-1)}(\boldsymbol{x}), h_j^{(l-1)}(\boldsymbol{x}')) \sim \mathcal{N}(\mathbf{0}^2, \tilde{\boldsymbol{K}}^{l-1})} \left[\phi'(h_j^{(l-1)}(\boldsymbol{x})) \phi'(h_j^{(l-1)}(\boldsymbol{x}')) \right] \\
&\leq (\sigma_w \max_h \phi'(h))^2
\end{aligned}
$$

provided that the maximum slope of ϕ is limited, which is true for many popular activation functions including ReLU and erf. Also, by Eq. (11), the value

$$\frac{\partial k^1(\boldsymbol{a}, \boldsymbol{z})}{\partial z_j} = \frac{\sigma_w^2}{d} a_j$$

is bounded. Therefore, Corollary 6.2 holds, which in turn makes $\mathcal{L}(\boldsymbol{Z}^n)$ β-smooth via Corollary 6.1. By Lemma 6.1, we obtain the proof of Theorem 6.1.

7 EXPERIMENT SETTINGS

This section provides more details about the settings of our experiments.

7.1 MODEL SETTINGS

The network architectures of the baseline GANs used in our experiments are based on InfoGAN Chen et al. (2016). We set the latent dimensions, training iterations, and batch size according to the study Lucic et al. (2018). The latent dimensions for the generator are all 64. The batch size for all baselines is set to 64. The training iterations are 80K, 100K, and 400K for MNIST, CelebA, and CIFAR-10 datasets, respectively. For the optimizers, we follow the setting from the respective original papers. Below we list the network architecture of the baselines for each dataset as well as the optimizer settings.

Table 3: The architectures of the discriminator and generator in the baseline GANs for the MNIST dataset.

Discriminator	Generator
Input 28×28×1 Gray image	Input $\in \mathbb{R}^{64} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{I})$
4×4 conv; 64 leaky ReLU; stride 2	Fully Connected 1024 ReLU; batchnorm
4×4 conv; 128 leaky ReLU; stride 2. batchnorm	Fully Connected $7 \times 7 \times 128$ ReLU; batchnorm
Fully Connected 1024 leaky ReLU; batchnorm	4×4 deconv; 64 ReLU. stride 2; batchnorm
Fully Connected 1 output	4×4 deconv; 1 sigmoid

Table 4: The architectures of the discriminator and generator in the baseline GANs for the CIFAR-10 dataset.

discriminator	generator
Input 32×32×3 Image	Input$\in \mathbb{R}^{64} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{I})$
4×4 conv; 64 leaky ReLU; stride 2	Fully Connected $2 \times 2 \times 448$ ReLU; batchnorm
4×4 conv; 128 leaky ReLU; stride 2; batchnorm	4×4 deconv; 256 ReLU; stride 2; batchnorm
4×4 conv; 256 leaky ReLU; stride 2; batchnorm	4×4 deconv; 128 ReLU; stride 2
Fully Connected 1 output	4×4 deconv; 64 ReLU; stride 2
	4×4 deconv; 3 Tanh; stride 2.

Table 5: The architectures of the discriminator and generator in the baseline GANs for the CelebA dataset.

discriminator	generator
Input 64×64×3 Image	Input$\in \mathbb{R}^{64} \sim \mathcal{N}(\mathbf{0}, \boldsymbol{I})$
4×4 conv; 64 leaky ReLU; stride 2	Fully Connected $2 \times 2 \times 448$ ReLU; batchnorm
4×4 conv; 128 leaky ReLU; stride 2; batchnorm	4×4 deconv; 256 ReLU; stride 2; batchnorm
4×4 conv; 256 leaky ReLU; stride 2; batchnorm	4×4 deconv; 128 ReLU; stride 2
4×4 conv; 256 leaky ReLU; stride 2; batchnorm	4×4 deconv; 64 ReLU; stride 2
Fully Connected 1 output	4×4 deconv; 32 ReLU; stride 2
	4×4 deconv; 3 Tanh; stride 2.

Table 6: The optimizer settings for each GAN baseline. n_{dis} denotes the training steps for discriminators in the alternative training process.

	Optimizer type	Learning Rate	β_1	β_2	n_{dis}
DCGAN	Adam	0.0002	0.5	0.999	1
LSGAN	Adam	0.0002	0.5	0.999	1
WGAN	RMSProp	0.00005	None	None	5
WGAN-GP	Adam	0.0001	0.5	0.9	5
SN-GAN	Adam	0.0001	0.9	0.999	5

Note that we remove all the batchnorm layers for the discriminators in WGAN-GP. We architect the element network of the discriminator in our GA-NTK following InfoGAN Chen et al. (2016), except that the width (or number of filters) of the network is infinite at each layer and has no batchnorm layers.

The generator of GA-NCTKg consumes memory. To reduce memory consumption, we let $\mathcal{D}$ discriminates true and fake images in the code space of a pretrained autoencoder $\mathcal{A}$ Bergmann et al. (2019). After training, a code output by $\mathcal{G}$ is feed into the decoder of $\mathcal{A}$ to obtain an image. The architectures of the pretrained $\mathcal{A}$ for different datasets are summarized as follows:

Table 7: The architectures of $\mathcal{A}$ for different datasets.

MNIST	CIFAR-10
Input 28×28×1 Image	Input 32×32×3 Image
3×3 conv; 16 SeLU; stride 2	3×3 conv; 32 SeLU; stride 2
3×3 conv; 32 SeLU; stride 2	3×3 conv; 64 SeLU; stride 2
3×3 conv; 64 SeLU; stride 2	3×3 conv; 128 SeLU; stride 2
Fully Connected; 128 tanh	Fully Connected; 1024 tanh
3×3 transposeconv; 64 SeLU; stride 2	3×3 transposeconv; 128 SeLU; stride 2
3×3 transposeconv; 32 SeLU; stride 2	3×3 transposeconv; 64 SeLU; stride 2
3×3 transposeconv; 16 SeLU; stride 2	3×3 transposeconv; 32 SeLU; stride 2
output	output

CelebA	CelebA-HQ
Input 64×64×3 Image	Input 256×256×3 Image
3×(3×3 conv; 32 SeLU; stride 1)	3×(3×3 conv; 64 SeLU; stride 1)
3×3 conv; 32 SeLU; stride 2	3×3 conv; 64 SeLU; stride 2
3×(3×3 conv; 64 SeLU; stride 1)	3×(3×3 conv; 128 SeLU; stride 1)
3×3 conv; 64 SeLU; stride 2	3×3 conv; 128 SeLU; stride 2
3×(3×3 conv; 128 SeLU; stride 1)	3×(3×3 conv; 256 SeLU; stride 1)
3×3 conv; 128 SeLU; stride 2	3×3 conv; 256 SeLU; stride 2
Fully Connected; 2048 tanh	3×(3×3 conv; 512 SeLU; stride 1)
3×(3×3 transposeconv; 128 SeLU; stride 1)	3×3 conv; 512 SeLU; stride 2
3×3 transposeconv; 128 SeLU; stride 2	Fully Connected; 2048 tanh
3×(3×3 transposeconv; 64 SeLU; stride 1)	3×(3×3 transposeconv; 512 SeLU; stride 1)
3×3 transposeconv; 64 SeLU; stride 2	3×3 transposeconv; 512 SeLU; stride 2
3×(3×3 transposeconv; 32 SeLU; stride 1)	3×(3×3 transposeconv; 256 SeLU; stride 1)
3×3 transposeconv; 32 SeLU; stride 2	3×3 transposeconv; 256 SeLU; stride 2
output	3×(3×3 transposeconv; 128 SeLU; stride 1)
	3×3 transposeconv; 128 SeLU; stride 2
	3×3(3×3 transposeconv; 64 SeLU; stride 1)
	3×3 transposeconv; 64 SeLU; stride 2
	output

7.2 METRICS

The FID scores are computed using the code from the original paper Heusel et al. (2017). We sample 2048 images to compute the FID scores. We calculate the AM-SSIM scores using the SSIM settings: filter size 4, filter sigma 1.5, k_1 0.01, and k_2 0.03 Wang et al. (2004).

Algorithm 1 Searching λ for GA-NTK.

Input: Data $\boldsymbol{X}^n$, kernel k, and separation tolerance ϵ
Output: λ for GA-NTK

Randomly initiate $\boldsymbol{Z}^n \in \mathbb{R}^{n \times d}$
$\lambda \leftarrow 1$
while $\frac{1}{2n}\|\mathcal{D}(\boldsymbol{X}^n, \boldsymbol{Z}^n; k, \lambda) - (\boldsymbol{1}^n \oplus \boldsymbol{0}^n)\|_2^2 \leq \epsilon$ **do**
$\quad |\quad \lambda \leftarrow \lambda \cdot 2$
end
return λ

7.3 HYPERPARAMETER TUNING

For each data synthesis method, we tune its hyperparameter using grid search. **GA-NTK.** The computation of $\boldsymbol{K}^{2n,2n}$ requires one to determine the initialization and architecture of the element networks in the ensemble discriminator. Studies Poole et al. (2016); Schoenholz et al. (2017); Raghu et al. (2017) have proposed a principled method to tune the hyperparameters for the initialization. From our empirical results, we also find that the quality of the images generated by GA-NTK is not significantly impacted by the choice of the architecture—a fully connected network with rectified linear unit (ReLU) activation suffices to generate recognizable image patterns. Once $\boldsymbol{K}^{2n,2n}$ is decided, there is only one hyperparameter $\lambda = \eta t$ to tune in Eq. (13). The λ controls how well the discriminator is trained on $\mathbb{D}$, so either a too small or large value can lead to poor gradients for $\boldsymbol{Z}^n$ and final generated points. But since there is no alternating updates as in GANs, we can decide an appropriate value of λ without worrying about canceling the learning progress of $\boldsymbol{Z}^n$. We propose a simple algorithm for tuning λ, as shown in Algorithm 1. Basically, we search for a value that makes the discriminator nearly separate the real data from pure noises in an auxiliary learning task, and then use this value to solve Eq. (13). In practice, a small positive ϵ ranging from 10^{-3} to 10^{-2} suffices to give an appropriate λ. **Multi-resolutional GA-NTK.** We use 3 NTK-GP's as the discriminators, whose architectures are listed in Table 8.

Table 8: The architectures of the discriminators for multi-resolution GA-NTK.

Discriminator small	Discriminator medium	Discriminator large
Input 16×16×3 Image	Input 64×64×3 Image	Input 256×256×3 Image
4×4 conv; ReLU; stride 2	4×4 conv; ReLU; stride 2	4×4 conv; ReLU; stride 2
4×4 conv; ReLU; stride 2	4×4 conv; ReLU; stride 2	4×4 conv; ReLU; stride 2
Fully Connected 1 output	4×4 conv; ReLU; stride 2	4×4 conv; ReLU; stride 2
	4×4 conv; ReLU; stride 2	4×4 conv; ReLU; stride 2
	Fully Connected 1 output	4×4 conv; ReLU; stride 2
		4×4 conv; ReLU; stride 2
		Fully Connected 1 output

8 MORE EXPERIMENTS

8.1 GA-FNTK VS. GA-CNTK

Next, we compare the images generated by GA-FNTK, GA-CNTK, and the multi-resolutional GA-CNTK described in Section 3.2 on the CelebA and CelebA-HQ datasets. The multi-resolutional GA-CNTK employs 3 discriminators working at 256×256, 64×64, and 16×16 pixel resolutions, respectively. Figure 2 shows the results. To our surprise, GA-NTK (which models the discriminator as an ensemble of fully connected networks) suffices to generate recognizable faces. The images synthesized by GA-FNTK and GA-CNTK lacks details and global coherence, respectively, due to

(a) GA-FNTK on CelebA   (b) GA-CNTK on CelebA

Figure 6: The images generated by (a) GA-FNTK and (b) GA-CNTK given 256 CelebA training images.

(a)   (b)

Figure 7: The images generated by batch-wise GA-CNTK on (a) CelebA dataset of 2048 randomly sampled images and (b) ImageNet dataset of 1300 randomly sampled images.

the characteristics of FNNs and CNNs. On the other hand, the multi-resolutional GA-CNTK gives both the details and global coherence thanks to the multiple discriminators working at different pixel resolutions. The results also demonstrate the potential of GA-NTK variants to generate high-quality data as there are many other techniques for GANs that could be adapted into GA-NTK.

8.2 BATCH-WISE GA-NTK

To work with a larger training set, we modify GA-CNTK by following the instructions in Section 3.2 to obtain the batch-wise GA-CNTK, which computes the gradients of Z^n in Eq. (4) from 256 randomly sampled training images during each gradient descent iteration. We train the batch-wise GA-CNTK on two larger datasets consisting of 2048 images from CelebA and 1300 images from ImageNet, respectively. Figure 7 shows the results, and the batch-wise GA-CNTK can successfully generate the "daisy" images on ImageNet.

Note that the batch-wise GA-CNTK solves a different problem than the original GA-CNTK—the former finds Z^n that deceives *multiple* discriminators, each trained on 256 examples, while the latter searches for Z^n that fools a single discriminator trained on 256 examples. Comparing the images in Figure 1(f) with those in Figure 7(a), we can see that the batch-wise GA-CNTK gives a little more blurry images but the patterns in each synthesized image are more globally coherent, both due to the effect of multiple discriminators.

| (a) | (b) |

Figure 8: The distribution of Wasserstein distance between $\mathcal{P}_{\text{gen}}$ and $\mathcal{P}_{\text{data}}$ (used to measure the quality of the generated points) over the searched hyper-parameters on training sets of (a) 8- and (b) 25-modal Gaussian mixtures.

8.3 SENSITIVITY TO HYPERPARAMETERS

Here, we study how sensitive is the performance of WGAN, WGAN-GP, and GA-FNTK to their hyperparameters. We adjust the hyperparameters of different approaches using the grid search under a time budget of 3 hours, and then evaluate the quality of 2048 generated data points by the Wasserstein distance between $\mathcal{P}_{\text{gen}}$ and $\mathcal{P}_{\text{data}}$. We train different methods on two toy datasets consisting of 8- and 25-modal Gaussian mixtures following the settings described in Section 4.2. Figure 8 shows the results, and we can see that GA-FNTK achieves the lowest average Wasserstein distance in both cases. Moreover, its variances are smaller than the two other baselines, too. This shows that the performance of GA-FNTK is less sensitive to the hyperparameters and could be easier to tune in practice.

Note that, with 3-hour time budget, the hyperparameters we obtained through the grid search are good enough for reproducing the experiments conducted by the study Mao et al. (2017) on mode collapse. In the experiments, the $\mathcal{P}_{\text{gen}}$ of different methods aim to align a 2D 8-modal Gaussian mixtures in the ground truth. Our results are shown in Figure 9.

| (a) Ground truth | (b) WGAN | (c) WGAN-GP | (d) GA-FNTK |

Figure 9: Visualization of distribution alignment and mode collapse on a 2D 8-modal Gaussian mixtures dataset.

8.4 TRAINING OF GA-CNTKG

Figure 10 shows the learning curve of the generator in $\mathcal{G}$ in GA-CNTKg and the relationship between the quality of images output by $\mathcal{G}$ and the number of gradient descent iterations. The results show that, the loss can be minimized even it is an f-divergence, and a lower loss score implies higher image quality. This is consistent with the results of GA-CNTK (without a generator) shown in Figure 3.

(a) MNIST   (b) CIFAR-10   (c) CelebA

Figure 10: The learning curve of $\mathcal{G}$ in GA-CNTKg and the image quality at different stages of training.

9 MORE GENERATED IMAGES FROM GA-NTK

In the following, we show more sample images synthesized by GA-CNTK. All these images are obtained using the settings described in the main paper and the above.

Figure 11: Sample images generated by GA-CNTK on the MNIST dataset (a) without and (b) with generator.

(a)

(b)

Figure 12: Sample images generated by GA-CNTK on the CIFAR-10 (a)without generator(b)with generator

(a)

(b)

Figure 13: Sample images generated by GA-CNTK on the CelebA dataset (a) without and (b) with generator.

Figure 14: Sample images generated by multi-resolutional GA-CNTK on the CelebA-HQ dataset.

Figure 15: Sample images generated by GA-CNTKg on the CelebA-HQ dataset.

10 DOWNGRADE IMAGES

As discussed in the main paper, we find that, when the size of training set is small, an image synthesis method may produce downgrade images that look almost identical to some images in the training set. We investigate this problem by showing the images from the training set that are the nearest to a generated image. We use the SSIM Wang et al. (2004) as the distance measure. Figures 16, 17, and **??** show the results for some randomly sampled synthesized images. As compared to GANs, both GA-CNTK and batch-wise GA-CNTK can generate images that look less similar to the ground-truth images.

Figure 16: Comparison between the images generated by WGAN-GP and the nearest neighbors (measured by SSIM) from the training set. Images with red bounding boxes are generated images.

Figure 17: Comparison between the images generated by GA-CNTK and the nearest neighbors (measured by SSIM) from the training set. Images with red bounding boxes are generated images.

Figure 18: Comparison between the images generated by GA-CNTKg and the nearest neighbors (measured by SSIM) from the training set. Images with red bounding boxes are generated images.