Practical Large-Scale Linear Programming using Primal-Dual Hybrid Gradient

Abstract

We present PDLP, a practical first-order method for linear programming (LP) that can solve to the high levels of accuracy that are expected in traditional LP applications. In addition, it can scale to very large problems because its core operation is matrix-vector multiplications. PDLP is derived by applying the primal-dual hybrid gradient (PDHG) method, popularized by Chambolle and Pock (2011), to a saddle-point formulation of LP. PDLP enhances PDHG for LP by combining several new techniques with older tricks from the literature; the enhancements include diagonal preconditioning, presolving, adaptive step sizes, and adaptive restarting. PDLP improves the state of the art for first-order methods applied to LP. We compare PDLP with SCS, an ADMM-based solver, on a set of 383 LP instances derived from MIPLIB 2017. With a target of 10^{-8} relative accuracy and 1 hour time limit, PDLP achieves a 6.3x reduction in the geometric mean of solve times and a 4.6x reduction in the number of instances unsolved (from 227 to 49). Furthermore, we highlight standard benchmark instances and a large-scale application (PageRank) where our open-source prototype of PDLP, written in Julia, outperforms a commercial LP solver.

1 Introduction

First-order methods (FOMs), which use gradient and not Hessian information, are now standard practice in many areas of optimization [10]. A known weakness of FOMs is the *tailing-off* effect, where FOMs quickly find moderately accurate solutions, but progress towards an optimal solution slows down over time. While moderately accurate solutions are often sufficient for large data science and machine learning applications, other applications traditionally demand higher precision. One such area is Linear Programming (LP), the focus of this work.

LP is a fundamental class of optimization problems in applied mathematics and operations research (OR) with a huge range of applications, including mixed-integer programming, scheduling, network flow, chip design, budget allocation, and many others [15, 19, 59, 62]. Software for solving LP problems, called *LP solvers*, originated in the earliest days of computing, predating the invention of operating systems [49]. The state-of-the-art methods for LP, namely Dantzig's simplex method [19,20] and interior-point (or barrier) methods [45], are quite mature and reliable at delivering highly accurate solutions. These widely successful methods have left little room for FOMs to make inroads. Furthermore, practitioners who use LP solvers are not accustomed to reasoning about the trade-off between accuracy and computing times typically intrinsic to FOMs.

In this paper, we provide evidence that, if properly enhanced, FOMs can obtain high quality solutions to LP problems quickly. Indeed, there's reason to expect this, as authors have developed FOMs for LP with linear rates of convergence (i.e., without a tailing-off effect) [21, 28, 41, 63, 64]. However, to our knowledge, ours is the first work to combine both theoretical enhancements with practical heuristics, demonstrating their combined effectiveness with extensive computational experiments

on standard benchmark instances. In fact, our experiments will expose a substantial gap between algorithms presented in the literature and what's needed to obtain good performance.

Starting from a baseline primal-dual hybrid gradient (PDHG) method [16] applied to a saddle point formulation of LP, we develop a series of algorithmic improvements. These enhancements include adaptive restarting [5], dynamic primal-dual step size selection [32, 33], presolving techniques [1], and diagonal preconditioning (data equilibration) [29]. We name our collection of enhancements *PDLP* (PDHG for LP).

The impact of these improvements is substantial. For example, on 383 LP instances derived from the MIPLIB 2017 collection [30], our implementation of a baseline version of PDHG solved only 50 problems to 10^{-8} relative accuracy given a limit of approximately 100,000 iterations per problem. By contrast, PDLP solves 283 of the 383 problems under the same conditions. We demonstrate that PDLP outperforms FOM baselines and, in a small number of cases, obtains performance competitive with a commercial LP solver.

Although not the focus of this paper, we believe that our results open the door to a new set of possibilities and computational trade-offs when solving LPs. PDLP has the potential to solve extremely large scale problems where the simplex method and interior-point methods are unable to run because of their reliance on matrix factorization. Since PDLP uses matrix-vector operations at its core, it can effectively run on multi-threaded CPUs, GPUs [61], or distributed clusters [23]. Furthermore, a GPU implementation of PDLP could efficiently solve batches of similar problems, a setup that has already been successfully applied with other optimization algorithms in applications like strong branching [40] and training neural networks that contain optimization layers [3].

Outline. The remainder of this section focuses on related work. Section 2 introduces LP and PDHG. Section 3 describes the set of enhancements that define PDLP. Section 4 presents numerical experiments, and Section 5 concludes and outlines future directions.

1.1 Literature review

PDHG PDHG was first developed in [65] and later analyzed and extended in [16, 18, 24, 34, 54]. PDHG is closely related to the Arrow-Hurwicz method [6]. PDHG is a form of operator-splitting [9, 58] and can be interpreted as a variant of the alternating directions method of multipliers (ADMM) and Douglas-Rachford splitting (DRS) [14, 22, 50], which themselves are both instantiations of the proximal point method [22, 52, 56]. As opposed to ADMM or DRS, PDHG is 'matrix-free' in that the data matrix is only used for matrix-vector multiplications. This allows PDHG to scale to problems even larger than those tackled by these other techniques, and to make better use of parallel and distributed computation.

FOM-based solvers Recent interest in large-scale cone programming has sparked the development several first-order solvers based on competing methods. Solvers based on Nesterov's accelerated gradients [43] include TFOCS [12], and FOM which is a suite of solvers employing both gradient and proximal algorithms [11]. Solvers based on operator splitting techniques like ADMM include SCS [46–48], OSQP [60], POGS [25], and COSMO [27]. Of these both SCS and POGS offer a matrix-free implementation where the linear system, that arises from the proximal operator used in ADMM, is solved using the conjugate gradient method. However, we shall show experimentally that our method can be significantly faster and more robust than this approach.

FOMs for LP [36] and [55] develop FOMs for LP as a special case of semidefinite programming, with sublinear convergence rates. The FOM-based solvers above, all apply to more general problem classes like cone programming or quadratic programming. In contrast, some of the enhancements that constitute PDLP are specialized, either in theory or practice, for LP (namely restarts [5] and presolving). A number of authors [21, 28, 41, 63, 64] have proposed linearly convergent FOMs for LP; to our knowledge, none have been subject of a comprehensive computational study. [53] apply PDHG with diagonal preconditioning to a limited set of test LP problems. [4] show how to extract infeasibility certificates when applying PDHG to LP. ECLIPSE [8] solves huge-scale industrial LP problems by accelerated gradient descent, without presenting comparisons on standard test problems.

2 Preliminaries

In this section, we introduce the notation we use throughout the paper, summarize the LP formulations we solve, and introduce the baseline PDHG algorithm.

Notation. Let $\mathbb{R}$ denote the set of real numbers, $\mathbb{R}^+$ the set of nonnegative real numbers, and $\mathbb{R}^-$ the set of nonpositive real numbers. Let $\mathbb{N}$ denote the set of natural numbers (starting from one). Let $\|\cdot\|_p$ denote the ℓ_p norm for a vector, and let $\|\cdot\|_2$ denote the spectral norm for a matrix. For a vector $v \in \mathbb{R}^n$, we use v^+ and v^- for their positive and negative parts, i.e., $v_i^+ = \max\{0, v_i\}$ and $v_i^- = \min\{0, v_i\}$. The symbol $v_{1:m}$ denotes the vector with the first m components of v. The symbol $K_{i,\cdot}$ and $K_{\cdot,j}$ corresponds to the ith column and jth row of the matrix K. The symbol $\mathbf{1}$ denotes the vector of all ones. Given a convex set X, we use $\mathbf{proj}_X$ to denote the map that projects onto X.

Linear Programming. We solve primal-dual LP problems of the form:

$$
\begin{array}{ll}
\begin{aligned}
&\underset{x \in \mathbb{R}^n}{\text{minimize}} \quad c^\top x \\
&\text{subject to:} \quad Gx \geq h \\
&\qquad\qquad\quad\; Ax = b \\
&\qquad\qquad\quad\; l \leq x \leq u
\end{aligned}
&
\begin{aligned}
&\underset{y \in \mathbb{R}^{m_1+m_2}, \lambda \in \mathbb{R}^n}{\text{maximize}} \quad q^\top y + l^\top \lambda^+ - u^\top \lambda^- \\
&\text{subject to:} \quad c - K^\top y = \lambda \\
&\qquad\qquad\quad\; y_{1:m_1} \geq 0 \\
&\qquad\qquad\quad\; \lambda \in \Lambda \,,
\end{aligned}
\end{array}
\tag{1}
$$

where $G \in \mathbb{R}^{m_1 \times n}, A \in \mathbb{R}^{m_2 \times n}, c \in \mathbb{R}^n, h \in \mathbb{R}^{m_1}, b \in \mathbb{R}^{m_2}, l \in (\mathbb{R} \cup \{-\infty\})^n, u \in (\mathbb{R} \cup \{\infty\})^n,$
$K^\top = (G^\top, A^\top), q^\top := (h^\top, b^\top)$, and

$$
\Lambda = \Lambda_1 \times \cdots \times \Lambda_n \quad \Lambda_i := \begin{cases} \{0\} & l_i = -\infty, \ u_i = \infty, \\ \mathbb{R}^- & l_i = -\infty, \ u_i \in \mathbb{R} \\ \mathbb{R}^+ & l_i \in \mathbb{R}, \ u_i = \infty \\ \mathbb{R} & \text{otherwise} \end{cases}
$$

is the set of variables λ such that the dual objective is finite. This pair of primal-dual problems is equivalent to the saddle-point problem:

$$
\min_{x \in X} \max_{y \in Y} \mathcal{L}(x, y) := c^\top x - y^\top K x + q^\top y
\tag{2}
$$

with $X := \{x \in \mathbb{R}^n : l \leq x \leq u\}$, and $Y := \{y \in \mathbb{R}^{m_1+m_2} : y_{1:m_1} \geq 0\}$.

PDHG. When specialized to (2), the PDHG algorithm takes the form:

$$
\begin{aligned}
x^{k+1} &= \mathbf{proj}_X(x^k - \tau(c - K^\top y^k)) \\
y^{k+1} &= \mathbf{proj}_Y(y^k + \sigma(q - K(2x^{k+1} - x^k)))
\end{aligned}
\tag{3}
$$

where $\tau, \sigma > 0$ are primal and dual stepsizes, respectively. PDHG is known to converge to an optimal solution when $\tau\sigma\|K\|_2^2 < 1$ [16]. We reparameterize the stepsizes by

$$
\tau = \eta/\omega \quad \text{and} \quad \sigma = \omega\eta \qquad \text{with } \eta \in (0, \infty) \quad \text{and} \quad \omega \in (0, \infty).
\tag{4}
$$

We call $\omega \in (0, \infty)$ the *primal weight*, and $\eta \in (0, \infty)$ the *stepsize*. Under this reparameterization PDHG converges for all $\eta < 1/\|K\|_2$. This allows us to control the scaling between the primal and dual iterates with a single parameter ω. We use the term *primal weight* to describe ω because it weights the primal variables in the following norm:

$$
\|z\|_\omega := \sqrt{\omega\|x\|_2^2 + \frac{\|y\|_2^2}{\omega}}.
$$

This norm plays a role in the theory for PDHG [17] and later algorithmic discussions.

For the *baseline PDHG algorithm* that we use for comparisons, we consider two simple choices for η and ω. For the step size, set $\eta = 0.9/\|K\|_2$ where $\|K\|_2$ is estimated via power iteration, and for the primal weight we set $\omega = 1$; compare with the default parameters in the standard PDHG implementation in ODL [2].

3 Practical algorithmic improvements

In this section, we detail these enhancements, and defer further experimental testing of them to Section 4 and ablation studies to the supplemental materials. While our enhancements are inspired by theory, our focus is on practical performance; the algorithm has no convergence guarantee.

Algorithm 1 presents pseudo-code for PDLP after preprocessing steps. We modify the step sizes (Section 3.1), add restarts (Section 3.2), and dynamically update the primal weights (Section 3.3). Before running Algorithm 1 we apply presolve (Section 3.4) and diagonal preconditioning (Section 3.5). There are some minor differences between the pseudo-code and the actual code. In particular, we only evaluate the restart or termination criteria (Line 10) every 40 iterations. This reduces the associated overheads with minimal impact on the total number of iterations. We also check the termination criteria before beginning the algorithm or if we detect a numerical error.

Algorithm 1: PDLP (after preconditioning and presolve)

1 **Input:** An initial solution $z^{0,0}$;
2 Initialize outer loop counter $n \leftarrow 0$, total iterations $k \leftarrow 0$, step size $\hat{\eta}^{0,0} \leftarrow 1/\|K\|_\infty$, primal weight $\omega^0 \leftarrow \texttt{InitializePrimalWeight}(c, q)$;
3 **repeat**
4      $t \leftarrow 0$;
5   **repeat**
6          $z^{n,t+1}, \eta^{n,t+1}, \hat{\eta}^{n,t+1} \leftarrow \texttt{AdaptiveStepOfPDHG}(z^{n,t}, \omega^n, \hat{\eta}^{n,t}, k)$;
7          $\bar{z}^{n,t+1} \leftarrow \frac{1}{\sum_{i=1}^{t+1} \eta^{n,i}} \sum_{i=1}^{t+1} \eta^{n,i} z^{n,i}$;
8          $z_c^{n,t+1} \leftarrow \texttt{GetRestartCandidate}(z^{n,t+1}, \bar{z}^{n,t+1}, z^{n,0})$;
9          $t \leftarrow t+1, k \leftarrow k+1$;
10   **until** *restart or termination criteria holds*;
11   **restart the outer loop.** $z^{n+1,0} \leftarrow z_c^{n,t}, n \leftarrow n+1$;
12     $\omega^n \leftarrow \texttt{PrimalWeightUpdate}(z^{n,0}, z^{n-1,0}, \omega^{n-1})$;
13 **until** *termination criteria holds*;
14 **Output:** $z^{n,0}$.

3.1 Step size choice

Algorithm 2: Step size heuristic

1 **Function** $\texttt{AdaptiveStepOfPDHG}$ $(z^{n,t}, \omega^n, \hat{\eta}^{n,t}, k)$**:**
2      $(x, y) \leftarrow z^{n,t}, \eta \leftarrow \hat{\eta}^{n,t}$;
3   **for** $i = 1, \dots, \infty$ **do**
4          $x' \leftarrow \mathbf{proj}_X(x - \frac{\eta}{\omega^n}(c - K^\top y))$;
5          $y' \leftarrow \mathbf{proj}_Y(y + \eta\omega^n(q - K(2x' - x)))$;
6          $\bar{\eta} \leftarrow \frac{\|(x'-x, y'-y)\|_{\omega^n}^2}{2(y'-y)^\top K(x'-x)}$;
7          $\eta' \leftarrow \min\left((1-(k+1)^{-0.3})\bar{\eta}, (1+(k+1)^{-0.6})\eta\right)$;
8   **if** $\eta \leq \bar{\eta}$ **then**
9   **return** (x', y'), η, η'
10   **end**
11         $\eta \leftarrow \eta'$;
12   **end**

The convergence analysis [17, Equation (15)] of PDHG (equation (3)) relies on a small constant stepsize

$$\eta \leq \frac{\|z^{k+1} - z^k\|_\omega^2}{2(y^{k+1} - y^k)^\top K(x^{k+1} - x^k)} \tag{5}$$

where $z^k = (x^k, y^k)$. Classically one would ensure (5) by picking $\eta = \frac{1}{\|K\|_2}$. This is overly pessimistic and requires estimation of $\|K\|_2$. Instead our $\texttt{AdaptiveStepOfPDHG}$ adjusts η dynamically to ensure that (5) is satisfied. If (5) isn't satisfied, we abort the step; i.e., we reduce η, and try again. If (5) is satisfied we accept the step. This is described in Algorithm 2. Note that in Algorithm 2 $\bar{\eta} \geq \frac{1}{\|K\|_2}$ holds always, and from this one can show the resulting step size $\eta \geq \frac{1-o(1)}{\|K\|_2}$ holds as $k \to \infty$.

131 Our step size routine compares favorably in practice with the line search by Malitsky and Pock [37]
132 (See Appendix C.1).

3.2 Adaptive restarts

In PDLP, we adaptively restart the PDHG algorithm in each outer iteration. The key to our restarts at
the n-th outer iteration is the normalized duality gap at z with radius r

$$\rho_r^n(z) := \frac{1}{r} \operatorname*{maximize}_{(\hat{x},\hat{y}) \in \{\hat{z} \in Z : \|\hat{z}-z\|_{\omega^n} \leq r\}} \{\mathcal{L}(x,\hat{y}) - \mathcal{L}(\hat{x},y)\},$$

introduced by [5]. Unlike the standard duality gap

$$\operatorname*{maximize}_{(\hat{x},\hat{y}) \in Z} \{\mathcal{L}(x,\hat{y}) - \mathcal{L}(\hat{x},y)\},$$

the normalized duality gap is always a finite quantity. Furthermore, the normalized duality gap $\rho_r^n(z)$
is 0 for any $r > 0$ and ω^n if and only if the solution z is an optimal solution to (2) [5], thus it provides
a valid metric for measuring progress towards the optimal solution. The normalized duality gap is
computable in linear time [5]. For brevity, define $\mu_n(z, z_{\text{ref}})$ as the normalized duality gap at z with
radius $\|z - z_{\text{ref}}\|_{\omega^n}$, i.e.,

$$\mu_n(z, z_{\text{ref}}) := \rho_{\|z-z_{\text{ref}}\|_{\omega^n}}^n(z),$$

134 where z_{ref} is a user-chosen reference point.

Choosing the restart candidate.   To choose the restart candidate $z_{\text{c}}^{n,t+1}$ we call

$$\texttt{GetRestartCandidate}(z^{n,t+1}, \bar{z}^{n,t+1}, z^{n,0}) := \begin{cases} z^{n,t+1} & \mu_n(z^{n,t+1}, z^{n,0}) < \mu_n(\bar{z}^{n,t+1}, z^{n,0}) \\ \bar{z}^{n,t+1} & \text{otherwise} . \end{cases}$$

135 This choice is justified in Remark 5 of [5].

136 **Restart criteria.**   We define three parameters: $\beta_{\text{sufficient}} \in (0,1)$, $\beta_{\text{necessary}} \in (0, \beta_{\text{sufficient}})$ and
137 $\beta_{\text{artificial}} \in (0,1)$. The algorithm restarts if one of three conditions holds:

138 (i) (**Sufficient decay in normalized duality gap**) $\mu_n(z_{\text{c}}^{n,t+1}, z^{n,0}) \leq \beta_{\text{sufficient}} \mu_n(z^{n,0}, z^{n-1,0})$,

139 (ii) (**Necessary decay + no local progress in normalized duality gap**)

$$\mu_n(z_{\text{c}}^{n,t+1}, z^{n,0}) \leq \beta_{\text{necessary}} \mu_n(z^{n,0}, z^{n-1,0}) \quad \text{and} \quad \mu_n(z_{\text{c}}^{n,t+1}, z^{n,0}) > \mu_n(z_{\text{c}}^{n,t}, z^{n,0}) ,$$

140 (iii) (**Long inner loop**) $t \geq \beta_{\text{artificial}} k$.

141 The motivation for (i) is presented in [5]; it guarantees the linear convergence of restarted PDHG
142 on LP problems. The second condition in (ii) is inspired by adaptive restart schemes for accelerated
143 gradient descent where restarts are triggered if the function value increases [51]. The first inequality in
144 (ii) provides a safeguard for the second one, preventing the algorithm restarting every inner iteration
145 or never restarting. The motivation for (iii) relates to the primal weights (Section 3.3). In particular,
146 primal weight updates only occur after a restart, and condition (iii) ensures that the primal weight will
147 be updated infinitely often. This prevents a bad choice of primal weight in earlier iterations causing a
148 long delay in when the restart criteria is satisfied and the primal weights updated.

3.3 Primal weight updates

150 The primal weight is initialized using

$$\texttt{InitializePrimalWeight}(c, q) := \begin{cases} \frac{\|c\|_2}{\|q\|_2} & \|c\|_2, \|q\|_2 > \epsilon_{\text{zero}} \\ 1 & \text{otherwise} \end{cases}$$

151 where ϵ_{zero} is a small nonzero tolerance. This primal weight update scheme guarantees scale in-
152 variance. In particular, in Appendix A we consider PDHG with $\epsilon_{\text{zero}} = 0$, $\eta = 0.9/\|K\|_2$ and
153 $\omega = \texttt{InitializePrimalWeight}(c, q)$. In this simplified setting, we prove that if we multiply the
154 objective, constraints, or the right hand side and variable bounds by a scalar then the iterate behaviour
155 remain identical (up to a scaling factor).

Algorithm 3 aims to choose the primal weight ω^n such that distance to optimality in the primal and
dual is the same, i.e., $\|(x^{n,t} - x^\star, \mathbf{0})\|_{\omega^n} \approx \|(\mathbf{0}, y^{n,t} - y^\star)\|_{\omega^n}$. By definition of $\|\cdot\|_\omega$,

$$\|(x^{n,t} - x^\star, \mathbf{0})\|_{\omega^n} = \omega^n \|x^{n,t} - x^\star\|_2, \quad \|(\mathbf{0}, y^{n,t} - y^\star)\|_{\omega^n} = \frac{1}{\omega^n} \|y^{n,t} - y^\star\|_2.$$

Algorithm 3: Primal weight update

1 Function PrimalWeightUpdate($z^{n,0}, z^{n-1,0}, \omega^{n-1}$)**:**

2 $\quad \Delta_x^n = \|x^{n,0} - x^{n-1,0}\|_2, \quad \Delta_y^n = \|y^{n,0} - y^{n-1,0}\|_2$;

3 $\quad$ **if** $\Delta_x^n > \epsilon_{zero}$ *and* $\Delta_y^n > \epsilon_{zero}$ **then**

4 $\qquad$ **return** $\exp\left(\theta \log\left(\frac{\Delta_y^n}{\Delta_x^n}\right) + (1-\theta)\log\left(\omega^{n-1}\right)\right)$

5 $\quad$ **else**

6 $\qquad$ **return** ω^{n-1} ;

7 $\quad$ **end**

Setting these two terms equal yields $\omega^n = \frac{\|y^{n,t}-y^\star\|_2}{\|x^{n,t}-x^\star\|_2}$. Of course the quantity $\frac{\|y^{n,t}-y^\star\|_2}{\|x^{n,t}-x^\star\|_2}$ is unknown beforehand but we attempt to estimate it using Δ_y^n / Δ_x^n. However, the quantity Δ_y^n / Δ_x^n can change wildly from one restart to another, causing ω^n to oscillate. To smooth ω^n out we first move to a log-scale where the primal weight is symmetric, i.e., $\log(1/\omega^n) = -\log(\omega^n)$, and perform a exponential smoothing with parameter $\theta \in [0,1]$. Compared with the procedure of [33] for choosing the primal weight, which limits modifications with an exponential decay, our method is more aggressive.

3.4 Presolve

Presolving refers to transformation steps that simplify the input problem before starting the optimization solver. These steps span from relatively easy transformations such as detecting inconsistent bounds, removing empty rows and columns of K, and removing variables whose lower and upper bounds are equal, to more complex operations such as detecting duplicate rows in K and tightening bounds. Presolve is a standard component of traditional LP solvers [38]. We are not aware of presolve being combined with PDHG or other FOMs for LP.

As an experiment to measure the impact of presolve, we used PaPILO [26], an open-source presolving library. For technical reasons, it was easier to use PaPILO as a standalone executable than as a library. We simulate its effect by simply solving the preprocessed instances. Convergence criteria are evaluated with respect to the presolved instance, not the original problem.

3.5 Diagonal Preconditioning

Preconditioning is a popular heuristic in optimization for improving the convergence of FOMs. To avoid factorizations, we only consider diagonal preconditioners. Our goal is to rescale the constraint matrix $K = (G, A)$ to $\tilde{K} = (\tilde{G}, \tilde{A}) = D_1 K D_2$ with positive diagonal matrices D_1 and D_2, so that the resulting matrix $\tilde{K}$ is "well balanced". Such preconditioning creates a new LP instance that replaces $A, G, c, b, h, u,$ and l in (1) with $\tilde{G}, \tilde{A}, \hat{x} = D_2^{-1}x, \tilde{c} = D_2 c, (\tilde{b}, \tilde{h}) = D_1(b, h), \tilde{u} = D_2^{-1}u$ and $\tilde{l} = D_2^{-1}l$. Common choices for D_1 and D_2 include:

- **No scaling:** Solve the original LP instance (1) without additional scaling, namely $D_1 = D_2 = I$.

- **Pock-Chambolle [53]:** Pock and Chambolle proposed a family of diagonal preconditioners[1] for PDHG parameterized by α, where the diagonal matrices are defined by $(D_1)_{jj} = \sqrt{\|K_{j,\cdot}\|_{2-\alpha}}$ for $j = 1, ..., m_1 + m_2$ and $(D_2)_{ii} = \sqrt{\|K_{\cdot,i}\|_\alpha}$ for $i = 1, ..., n$. We test $\alpha = 0, 1, 2$ in our ablation studies and choose to use $\alpha = 1$ in PDLP. This is the baseline diagonal preconditioner in the PDHG literature.

- **Ruiz [57]:** Ruiz scaling is a popular algorithm in numerical linear algebra to equilibrate matrices. In an iteration of Ruiz scaling, the diagonal matrices are defined as $(D_1)_{jj} = \sqrt{\|K_{j,\cdot}\|_\infty}$ for $j = 1, ..., m_1 + m_2$ and $(D_2)_{ii} = \sqrt{\|K_{\cdot,i}\|_\infty}$ for $i = 1, ..., n$. Ruiz [57] shows that if this rescaling is applied iteratively, the infinity norm of each row and each column converge to 1.

For the default PDLP settings, we apply a combination of Ruiz rescaling [57] and the preconditioning technique proposed by Pock and Chambolle [53]. In particular, we apply 10 iterations of Ruiz scaling

---

[1]Diagonal preconditioning is equivalent to changing to a weighted ℓ_2 norm in the proximal step of PDHG (weight defined by D_2 and D_1 for the primal and dual respectively). Pock and Chambolle use this weighted norm perspective.

and then apply the Pock-Chambolle scaling. To illustrate the effectiveness of our proposed scaling technique, we compare it against these three common techniques in Appendix C.5.

4 Numerical experiments

Our numerical experiments study the effectiveness of PDLP primarily with respect to traditional LP applications and benchmark sets. Section 4.1 describes the setup for the experiments. Section 4.2 demonstrates PDLP's improvements over baseline PDHG. Section 4.3 compares PDLP with other FOMs. Section 4.4 highlights benchmark instances where PDLP outperforms a commercial LP solver. Finally, Section 4.5 illustrates the ability of PDLP to scale to a large application where barrier and simplex-based solvers run out of memory. The supplemental materials contain extensive ablation studies.

4.1 Experimental setup

Optimality termination criteria. PDLP terminates with an approximately optimal solution when the primal-dual iterates $x \in X, y \in Y, \lambda \in \Lambda$, satisfy:

$$\left| b^\top y + l^\top \lambda^+ - u^\top \lambda^- - c^\top x \right| \leq \epsilon (1 + \left| b^\top y + l^\top \lambda^+ - u^\top \lambda^- \right| + \left| c^\top x \right|) \tag{6a}$$

$$\left\| \begin{pmatrix} Ax - b \\ (h - Gx)^+ \end{pmatrix} \right\|_2 \leq \epsilon (1 + \|q\|_2) \tag{6b}$$

$$\| c - K^\top y - \lambda \|_2 \leq \epsilon (1 + \|c\|_2) \tag{6c}$$

where $\epsilon \in (0, \infty)$ is the termination tolerance. Note that if (6) is satisfied with $\epsilon = 0$, then by LP duality we have found an optimal solution [31]. Indeed, (6a) is the duality gap, (6b) is primal feasibility, and (6c) is dual feasibility. We use these criteria to be consistent with those of SCS [48]. The PDHG algorithm does not explicitly include a reduced costs variable λ. Therefore, to evaluate the optimality termination criteria we compute $\lambda = \mathbf{proj}_\Lambda (c - K^\top y)$. All instances considered have an optimal primal-dual solution. We use $\epsilon = 10^{-8}$ as a benchmark for high-quality solutions and $\epsilon = 10^{-4}$ for moderately accurate solutions.

Benchmark datasets. We use two datasets to compare algorithmic performance. One is the `LP benchmark` dataset of 56 problems, formed by merging the instances from "Benchmark of Simplex LP Solvers", "Benchmark of Barrier LP solvers", and "Large Network-LP Benchmark" from [39]. We also created a larger benchmark of 383 instances curated from LP relaxations of mixed-integer programming problems from the MIPLIB2017 collection [30] (see Appendix B) that we label `MIP Relaxations`. `MIP Relaxations` was used extensively during algorithmic development, e.g., for hyperparameter choices; we held out `LP benchmark` as a test set.

Software. PDLP is implemented in an open-source Julia [13] module. The module also contains a baseline implementation of the extragradient method with many of the same enhancements as PDLP (labeled 'Enh. Extragradient'). We compare with two external packages: SCS [48] version 2.1.3, an open-source generic cone solver based on ADMM, and Gurobi version 9.0.1, a state-of-the-art commercial LP solver. SCS supports two modes for solving the linear system that arises at each iteration, a direct method based on a cached LDL factorization (which is the default 'SCS') and an indirect method based on the conjugate gradient method (which we label 'SCS (matrix-free)'). All solvers are run single-threaded. SCS and Gurobi are provided the same presolved instances as PDLP.

Computing environment. We used two computing environments for our experiments: 1) `e2-highmem-2` virtual machines (VMs) on Google Cloud Platform (GCP). Each VM provides two virtual CPUs and 16GB RAM. 2) A dedicated workstation with an Intel Xeon E5-2669 v3 processor and 128 GB RAM. This workstation has a license for Gurobi that permits at most one concurrent solve. Total compute time on GCP for all preliminary and final experiments was approximately $72,000$ virtual CPU hours.

Initialization. All first-order methods use all-zero vectors as the initial starting points.

Metrics. We use the term *KKT passes* to refer to the number of matrix multiplications by both K and $K^\top$. As the most expensive operation in our algorithm is matrix-vector multiplication, this metric is less noisy than runtime for comparing performance between matrix-free solvers. SGM10 stands for shifted geometric mean with shift 10, which is computed by adding 10 to all data points

(a) `MIP Relaxations` improvements   (b) `LP benchmark` improvements

Figure 1: Summary of relative impact of PDLP's improvements

Figure 2: Number of problems solved for `MIP Relaxations` (top) and `LP benchmark` (bottom) datasets.

and then taking the geometric mean. Unsolved instances are assigned values corresponding to the limits specified in the next paragraph.

Time and KKT pass limits. For Section 4.2 we impose a limit on the KKT passes of $100,000$. For Section 4.3 we impose a time limit of 1 hour.

4.2 Impact of PDLP's improvements

Section 3 details our algorithmic improvements. The y-axis of Figure 1a and 1b displays the SGM10 of the KKT passes normalized by the value for baseline PDHG. We can see, with the exception of presolve for LP benchmark at tolerance 10^{-4}, each of our modifications improves the performance of PDHG.

4.3 Comparison with other first-order baselines

We compared PDLP with several other first-order baselines: SCS [48], in both direct (default) mode and matrix-free mode, and our enhanced implementation of the extragradient method [35, 42]. For SCS in matrix-free mode, we include the KKT passes from the conjugate gradient solves; for SCS in direct mode there is no reasonable measure of KKT passes for the factorization and direct solve, so we only measure running time. The comparisons are summarized in Figure 2.

4.4 PDLP versus simplex and barrier

In this section, we test the performance of PDLP against Gurobi. We used default termination for Gurobi and set $\epsilon = 10^{-8}$ for PDLP. Gurobi runs three methods concurrently: barrier, primal simplex, and dual simplex; it terminates when the first method completes. We ran experiments with instances from the `MIP Relaxations` and `LP benchmark`. Although, for most instances, Gurobi outperforms PDLP, we found problems for which PDLP exhibits moderate to significant gains. Table 1 gives examples of instances where our prototype implementation is within a factor of two of the best of the three Gurobi methods. While further improvements are needed for PDLP to truly compete with the

Table 1: Instances from `MIP Relaxations` (top) and `LP benchmark` (bottom) where PDLP is within a factor of 2 of the best of all Gurobi methods. Time to solve in seconds.

Instance	PDLP	Gurobi Barrier	Gurobi Primal Simp.	Gurobi Dual Simp.
ex9	1.6	102.6	181.3	47.6
genus-sym-g62-2	2.1	10.7	6.7	33.2
highschool1-aigio	72.6	243.8	>3600	>3600
neos-578379	1.4	0.7	1.7	1.8
rwth-timetable	1870.3	>3600	>3600	>3600
ex10	4.9	63.1	16.8	7.9
nug08-3rd	2.2	3.2	2219.2	24.1
savsched1	35.9	25.9	56.0	261.3

Table 2: Solve time for PageRank instances. Gurobi barrier has crossover disabled, 1 thread. PDLP and SCS solve to 10^{-8} relative accuracy. SCS is matrix-free. Baseline PDHG is unable to solve any instances. Presolve not applied. OOM = Out of Memory. The number of nonzero coefficients per instance is $8 \times (\text{\# nodes}) - 18$.

# nodes	PDLP	SCS	Gurobi Barrier	Gurobi Primal Simp.	Gurobi Dual Simp.
10^4	7.4 sec.	1.3 sec.	36 sec.	37 sec.	114 sec.
10^5	35 sec.	38 sec.	7.8 hr.	9.3 hr.	>24 hr.
10^6	11 min.	25 min.	OOM	>24 hr.	-
10^7	5.4 hr.	3.8 hr.	-	-	-

portfolio of methods that Gurobi offers, we interpret these results as evidence that PDLP itself could be of value in this portfolio.

4.5 Large-scale application: PageRank

Nesterov [44, equation (7.3)] gives an LP formulation of the standard "PageRank" problem. Although the LP formulation is not the best approach to computing PageRank, it is a source of very large instances. For a random scalable collection of PageRank instances, we used Barabási-Albert [7] preferential attachment graphs with approximately three edges per node; see Appendix D for details. The results are summarized in Table 2.

5 Future work

In the introduction we outline new implementation possibilities that we intend to pursue. In addition, we would like to develop a stronger theoretical foundation for PDLP's primal weight updates and step size choices. Finally, we hope the community will use the benchmarks and baselines released with this work as a starting point for further investigating new FOMs for LP.

References

[1] T. Achterberg, R. E. Bixby, Z. Gu, E. Rothberg, and D. Weninger. Presolve reductions in mixed integer programming. *INFORMS Journal on Computing*, 32(2):473–506, 2020.

[2] J. Adler, H. Kohr, and O. Öktem. Operator discretization library (odl), Jan. 2017.

[3] B. Amos and J. Z. Kolter. OptNet: Differentiable optimization as a layer in neural networks. In D. Precup and Y. W. Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 136–145. PMLR, 06–11 Aug 2017.

[4] D. Applegate, M. Díaz, H. Lu, and M. Lubin. Infeasibility detection with primal-dual hybrid gradient for large-scale linear programming. *arXiv preprint arXiv:2102.04592*, 2021.

[5] D. Applegate, O. Hinder, H. Lu, and M. Lubin. Faster First-Order Primal-Dual Methods for Linear Programming using Restarts and Sharpness. *arXiv preprint arXiv:2105.12715*, 2021.

[6] K. J. Arrow, L. Hurwicz, and H. Uzawa. *Studies in linear and non-linear programming*. Stanford University Press, 1958.

[7] A.-L. Barabási and R. Albert. Emergence of scaling in random networks. *Science*, 286(5439):509–512, 1999.

[8] K. Basu, A. Ghoting, R. Mazumder, and Y. Pan. ECLIPSE: An extreme-scale linear program solver for web-applications. In H. D. III and A. Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 704–714, Virtual, 13–18 Jul 2020. PMLR.

[9] H. H. Bauschke and P. L. Combettes. *Convex analysis and monotone operator theory in Hilbert spaces*, volume 408. Springer, 2 edition, 2017.

[10] A. Beck. *First-Order Methods in Optimization*. Society for Industrial and Applied Mathematics, Philadelphia, PA, 2017.

[11] A. Beck and N. Guttmann-Beck. FOM–a MATLAB toolbox of first-order methods for solving convex optimization problems. *Optimization Methods and Software*, 34(1):172–193, 2019.

[12] S. R. Becker, E. J. Candès, and M. C. Grant. Templates for convex cone problems with applications to sparse signal recovery. *Mathematical programming computation*, 3(3):165, 2011.

[13] J. Bezanson, A. Edelman, S. Karpinski, and V. B. Shah. Julia: A fresh approach to numerical computing. *SIAM Review*, 59(1):65–98, 2017.

[14] S. Boyd, N. Parikh, E. Chu, B. Peleato, and J. Eckstein. Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends® in Machine learning*, 3(1):1–122, 2011.

[15] S. Boyd and L. Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

[16] A. Chambolle and T. Pock. A first-order primal-dual algorithm for convex problems with applications to imaging. *Journal of mathematical imaging and vision*, 40(1):120–145, 2011.

[17] A. Chambolle and T. Pock. On the ergodic convergence rates of a first-order primal–dual algorithm. *Mathematical Programming*, 159(1):253–287, 2016.

[18] L. Condat. A primal–dual splitting method for convex optimization involving Lipschitzian, proximable and linear composite terms. *Journal of Optimization Theory and Applications*, 158(2):460–479, 2013.

[19] G. Dantzig. *Linear programming and extensions*. Princeton university press, 2016.

[20] G. B. Dantzig. Origins of the simplex method. In *A history of scientific computing*, pages 141–151. Association for Computing Machinery, New York, NY, USA, 1990.

[21] J. Eckstein and D. P. Bertsekas. An alternating direction method for linear programming. Technical Report LIDS-P-1967, Laboratory for Information and Decision Systems, Massachusetts Institute of Technology, 1990.

[22] J. Eckstein and D. P. Bertsekas. On the Douglas–Rachford splitting method and the proximal point algorithm for maximal monotone operators. *Mathematical Programming*, 55(1-3):293–318, 1992.

[23] J. Eckstein and G. Matyasfalvi. Efficient distributed-memory parallel matrix-vector multiplication with wide or tall unstructured sparse matrices. *arXiv preprint arXiv:1812.00904*, 2018.

[24] E. Esser, X. Zhang, and T. F. Chan. A general framework for a class of first order primal-dual algorithms for convex optimization in imaging science. *SIAM Journal on Imaging Sciences*, 3(4):1015–1046, 2010.

[25] C. Fougner and S. Boyd. Parameter selection and preconditioning for a graph form solver. In *Emerging Applications of Control and Systems Theory*, pages 41–61. Springer, 2018.

[26] G. Gamrath, D. Anderson, K. Bestuzheva, W.-K. Chen, L. Eifler, M. Gasse, P. Gemander, A. Gleixner, L. Gottwald, K. Halbig, et al. The SCIP optimization suite 7.0. ZIB-Report 20-10, Zuse Institut Berlin, 2020.

[27] M. Garstka, M. Cannon, and P. Goulart. COSMO: A conic operator splitting method for large convex problems. In *European Control Conference*, 2019.

[28] A. Gilpin, J. Pena, and T. Sandholm. First-order algorithm with $\mathcal{O}(\ln(1/\epsilon))$ convergence for ϵ-equilibrium in two-person zero-sum games. *Mathematical programming*, 133(1):279–298, 2012.

[29] P. Giselsson and S. Boyd. Linear convergence and metric selection for Douglas-Rachford splitting and ADMM. *IEEE Transactions on Automatic Control*, 62(2):532–544, 2016.

[30] A. Gleixner, G. Hendel, G. Gamrath, T. Achterberg, M. Bastubbe, T. Berthold, P. M. Christophel, K. Jarck, T. Koch, J. Linderoth, M. Lübbecke, H. D. Mittelmann, D. Ozyurt, T. K. Ralphs, D. Salvagnin, and Y. Shinano. MIPLIB 2017: Data-Driven Compilation of the 6th Mixed-Integer Programming Library. *Mathematical Programming Computation*, 2021.

[31] A. J. Goldman and A. W. Tucker. Theory of linear programming. *Linear inequalities and related systems*, 38:53–97, 1956.

[32] T. Goldstein, M. Li, and X. Yuan. Adaptive primal-dual splitting methods for statistical learning and image processing. In *Advances in Neural Information Processing Systems*, pages 2089–2097, 2015.

[33] T. Goldstein, M. Li, X. Yuan, E. Esser, and R. Baraniuk. Adaptive primal-dual hybrid gradient methods for saddle-point problems. *arXiv preprint arXiv:1305.0546*, 2013.

[34] B. He and X. Yuan. Convergence analysis of primal-dual algorithms for a saddle-point problem: from contraction perspective. *SIAM Journal on Imaging Sciences*, 5(1):119–149, 2012.

[35] G. M. Korpelevich. The extragradient method for finding saddle points and other problems. *Matecon*, 12:747–756, 1976.

[36] G. Lan, Z. Lu, and R. D. C. Monteiro. Primal-dual first-order methods with $\mathcal{O}(1/\epsilon)$ iteration-complexity for cone programming. *Mathematical Programming*, 126(1):1–29, Jan 2011.

[37] Y. Malitsky and T. Pock. A first-order primal-dual algorithm with linesearch. *SIAM Journal on Optimization*, 28(1):411–432, 2018.

[38] I. Maros. *Computational Techniques of the Simplex Method*. International Series in Operations Research & Management Science. Springer US, 2002.

[39] H. Mittelmann. Decision tree for optimization software. `http://plato.asu.edu/guide.html`, 2021.

[40] V. Nair, S. Bartunov, F. Gimeno, I. von Glehn, P. Lichocki, I. Lobov, B. O'Donoghue, N. Sonnerat, C. Tjandraatmadja, P. Wang, R. Addanki, T. Hapuarachchi, T. Keck, J. Keeling, P. Kohli, I. Ktena, Y. Li, O. Vinyals, and Y. Zwols. Solving Mixed Integer Programs Using Neural Networks. *arXiv preprint arXiv:2012.13349*, Dec. 2020.

[41] I. Necoara, Y. Nesterov, and F. Glineur. Linear convergence of first order methods for non-strongly convex optimization. *Mathematical Programming*, 175(1):69–107, May 2019.

[42] A. Nemirovski. Prox-method with rate of convergence O(1/t) for variational inequalities with lipschitz continuous monotone operators and smooth convex-concave saddle point problems. *SIAM Journal on Optimization*, 15(1):229–251, 2004.

[43] Y. Nesterov. A method of solving a convex programming problem with convergence rate $o(1/k^2)$. *Soviet Mathematics Doklady*, 27(2):372–376, 1983.

[44] Y. Nesterov. Subgradient methods for huge-scale optimization problems. *Mathematical Programming*, 146:275–297, 2014.

[45] Y. Nesterov and A. Nemirovskii. *Interior-point polynomial algorithms in convex programming*, volume 13. SIAM, 1994.

[46] B. O'Donoghue. Operator splitting for a homogeneous embedding of the monotone linear complementarity problem. *arXiv preprint arXiv:2004.02177*, 2020.

[47] B. O'Donoghue, E. Chu, N. Parikh, and S. Boyd. Conic optimization via operator splitting and homogeneous self-dual embedding. *Journal of Optimization Theory and Applications*, 169(3):1042–1068, June 2016.

[48] B. O'Donoghue, E. Chu, N. Parikh, and S. Boyd. SCS: Splitting conic solver, version 2.1.0. https://github.com/cvxgrp/scs, Nov. 2017.

[49] W. Orchard-Hays. History of mathematical programming systems. *IEEE Annals of the History of Computing*, 6(3):296–312, 1984.

[50] D. O'Connor and L. Vandenberghe. On the equivalence of the primal-dual hybrid gradient method and Douglas–Rachford splitting. *Mathematical Programming*, 179(1):85–108, 2020.

[51] B. O'Donoghue and E. Candes. Adaptive restart for accelerated gradient schemes. *Foundations of computational mathematics*, 15(3):715–732, 2015.

[52] N. Parikh and S. Boyd. Proximal algorithms. *Foundations and Trends® in Optimization*, 1(3):127–239, 2014.

[53] T. Pock and A. Chambolle. Diagonal preconditioning for first order primal-dual algorithms in convex optimization. In *2011 International Conference on Computer Vision*, pages 1762–1769. IEEE, 2011.

[54] T. Pock, D. Cremers, H. Bischof, and A. Chambolle. An algorithm for minimizing the mumford-shah functional. In *2009 IEEE 12th International Conference on Computer Vision*, pages 1133–1140. IEEE, 2009.

[55] J. Renegar. Accelerated first-order methods for hyperbolic programming. *Mathematical Programming*, 173(1):1–35, Jan 2019.

[56] R. T. Rockafellar. Monotone operators and the proximal point algorithm. *SIAM journal on control and optimization*, 14(5):877–898, 1976.

[57] D. Ruiz. A scaling algorithm to equilibrate both rows and columns norms in matrices. Technical report, CM-P00040415, 2001.

[58] E. K. Ryu and S. Boyd. Primer on monotone operator methods. *Appl. Comput. Math*, 15(1):3–43, 2016.

[59] A. Schrijver. *Theory of linear and integer programming*. John Wiley & Sons, 1998.

[60] B. Stellato, G. Banjac, P. Goulart, A. Bemporad, and S. Boyd. OSQP: an operator splitting solver for quadratic programs. *Mathematical Programming Computation*, 12(4):637–672, 2020.

[61] Y. M. Tsai, T. Cojean, and H. Anzt. Sparse linear algebra on AMD and NVIDIA GPUs – the race is on. In P. Sadayappan, B. L. Chamberlain, G. Juckeland, and H. Ltaief, editors, *High Performance Computing*, pages 309–327, Cham, 2020. Springer International Publishing.

[62] R. J. Vanderbei et al. *Linear programming*, volume 3. Springer, 2015.

[63] S. Wang and N. Shroff. A new alternating direction method for linear programming. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017.

[64] T. Yang and Q. Lin. Rsg: Beating subgradient method without smoothness and strong convexity. *The Journal of Machine Learning Research*, 19(1):236–268, 2018.

[65] M. Zhu and T. Chan. An efficient primal-dual hybrid gradient algorithm for total variation image restoration. *UCLA CAM Report*, 34:8–34, 2008.