MIXED-PRECISION INFERENCE QUANTIZATION: RADICALLY TOWARDS FASTER INFERENCE SPEED, LOWER STORAGE REQUIREMENT, AND LOWER LOSS

ABSTRACT

Model quantization is important for compressing models and improving computing speed. However, current researchers think that the loss function of the quantized model is usually higher than the full-precision model. This study provides a methodology for acquiring a mixed-precise quantization model with a lower loss without "fine-tuning" than the full-precision model. We also prove that small networks will be more sensitive to quantization technology. Using our algorithm in ResNet 8/14 and VGG 11/16, we gain better quantizated models than full-precision models.

1 INTRODUCTION

Neural network storage, inference, and training are computationally intensive due to the massive parameter size of neural networks. Therefore, developing a compression algorithm for machine learning models is necessary. Model quantization, based on the robustness of computational noise, is one of the most important compression techniques. The computational noise robustness measures the algorithm's performance when noise is added during the computation process. The primary sources of noise are truncation and data type conversion mistakes. In the quantization process, the initial high-precision data type used for a model's parameters is replaced with a lower-precision data type during model quantization. It is typical to replace FP32 with FP16, and both PyTorch and TensorFlow have quantization techniques that translate floats to integers. Various quantization techniques share the same theoretical foundation, which is the substitution of approximation data for the original data in the storage and inference processes. A lower-precision data format requires less memory, and using lower-precision data requires fewer computer resources and less time. In quantization, the precision loss in different quantization level conversions and data type conversions is the source of the noise.

There is a question of whether quantization technology always leads to the model's performance loss or loss function's increase. Actually, we always find the results in different papers that the performance of the quantized model is better than the full precision model. Thus, we want to give an algorithm that can find the quantization model that is better than the full precision model. Besides the performance advantages, quantized model also enjoy the computation advantage like fast computation speed and lower storage cost.

In our view, utilizing mixed-precision quantization is one possible way to approach a better performance quantization model. A precisely controlling and different noise adding scheme can have the chance of improving the performance of the model. However, the search space for a mixed-precision layout strategy is expansive.

In current results, the better performance model is gained by "fine-tuning" skill. The consensus of academics is that quantization technology without "fine-tuning" is detrimental to the performance of the model. No study examines how to increase the performance of a model using quantization technology or which types of models are stable in the quantization process and why.

This research provides a basic analysis of the computational noise robustness of neural networks. The model quantization problem setting for inference processes will be established. Moreover, by focusing on layerwise post-training static model quantization, we present a method for acquiring

a quantized model with a lower loss than the model with full precision. In addition, based on our analysis, we also prove that it is the nature of the computational noise robustness to be strong for neural networks that mainly consist of massive identity mapping, like ResNet or DenseNet.

2 RELATED WORK

Model compression methods include pruning methodsHan et al. (2015); Li et al. (2016); Mao et al. (2017) , knowledge distillationHinton et al. (2015), weight sharingUllrich et al. (2017) and quantization methods. From the perspective of the precision layout, post-training quantization methods can be mainly divided into channelwise Li et al. (2019); Qian et al. (2020), groupwise Dong et al. (2019b) and layerwise Dong et al. (2019a) methods. Layerwise mixed-precision layout schemes are more friendly to hardware. Parameters of the same precision are organized together, making full of a program's temporal and spatial locality. A common problem definition for quantizationDong et al. (2019a); Morgan et al. (1991); Courbariaux et al. (2015); Yao et al. (2020) is as follows Gholami et al. (2021).

Problem 1 *The objective of quantization is to solve the following optimization problem:*

$$\min_{q \in \mathbf{Q}} \|q(w) - w\|^2$$

where q is the quantization scheme, $q(w)$ is the quantized model with quantization q, and w represents the weights, i.e., parameters, in the neural network.

Although problem 1 gives researchers a target to aim for when performing quantization, the current problem definition has two shortcomings: 1. The search space of all possible mixed-precision layout schemes is a discrete space that is exponentially large in the number of layers. There is no effective method to solve the corresponding search problem. 2. There is a gap between the problem target and the final task target. As we can see, no terms related to the final task target, such as the loss function or accuracy, appear in the current problem definition.

3 BACKGROUND ANALYSIS

3.1 MODEL COMPUTATION, NOISE GENERATION AND QUANTIZATION

Compressed models for the inference process are computed using different methods depending on the hardware, programming methods and deep learning framework. All of these methods introduce noise into the computing process. One reason for this noise problem is that although it is common practice to store and compute model parameters directly using different data types, only data of the same precision can support precise computations in a computer framework.

Therefore, before performing computations on nonuniform data, a computer will convert them into the same data type. Usually, a lower-precision data type in a standard computing environment will be converted into a higher-precision data type; this ensures that the results are correct but require more computational resources and time. However, to accelerate the computing speed, some works on artificial intelligence (AI) computations propose converting higher-precision data types into lower-precision data types based on the premise that AI models are not sensitive to compression noise. The commonly used quantization technology is converting data directly and using a lower-precision data type to map to a higher-precision data type linearly.

We use the following example to illustrate quantization method, which is presented in Yao et al. (2020). Suppose that there are two data objects $input_1$ and $input_2$ are to be subjected to a computing operation, such as multiplication. After the quantization process, we have $Q_1 = \text{int}(\frac{input_1}{scale_1})$ and $Q_2 = \text{int}(\frac{input_2}{scale_2})$, and we can write

$$Q_{output} = \text{int}(\frac{input_1 * input_2}{scale_{output}}) \approx \text{int}(Q_1 Q_2 \frac{scale_1 * scale_2}{scale_{output}})$$

$scale_{output}$, $scale_1$ and $scale_2$ are precalculated scale factors that depend on the distributions of $input_1$, $input_2$ and the output; Q_i is stored as a lower-precision data type, such as an integer. All $scale$ terms can be precalculated and established ahead of time. Then, throughout the whole inference

process, only computations on the Q_i values are needed, which are fast. In this method, the noise is introduced in the $\text{int}(\cdot)$ process. This basic idea gives rise to several variants, such as (non)uniform quantization and (non)symmetrical quantization.

When we focus on quantization strategy, i.e. $round$ function in quantization framework like Micronet, we can have at least three strategy: round up, i.e., $ceil$ function in python, round down, i.e., $floor$ function in python and rounding, i.e., $round$ function in python. usually, rounding is the most common method to deal with quantization. But, in this paper, we will show that how to mixed use round up/round down to gain a mixed precision quantized model which is better than full precision model.

3.2 Neural Networks

In this paper, we mainly use the mathematical properties of extreme points to analyze quantization methods. This approach is universal to all cases, not only neural networks. However, there is a myth in the community that it is the neural network properties that guarantee the success of quantization methodsWang et al. (2019); Morgan et al. (1991); Demidovskij & Smirnov (2020). To show that the properties of the extreme points, not the properties of the neural network, are what determine the ability to quantize, i.e. the ability to handle noise, we must first define what a neural network is.

The traditional definition of a neural network Denilson & Barbosa (2016) as a human brain simulation is ambiguous; it is not a rigorous mathematical concept and cannot offer any analyzable information. The traditional descriptions of neural networks Denilson & Barbosa (2016) focus on the inner products of the network weights and inputs, the activation functions and directed acyclic graphs. However, with the development of deep learning, although most neural networks still consist of weighted connections and activation layers, many neural networks no longer obey these rules, such as the network architectures for position embedding and layer norm operations in Transformers. Moreover, current deep learning frameworks, such as PyTorch and TensorFlow, offer application programming interfaces (APIs) to implement any function in a layer. Therefore, we propose that the definition of a neural network adheres to the engineering concept indicated by the definition 1 rather than a precise mathematical definition; that is, a neural network is a way for implementing a function.

Definition 1 *The neural network is the function which is implemented in composite function form.*

A neural network can be described in the following Eq. 1 form.
$$model(x) = h_1(h_{2,1}(h_{3,1}(...), ..., h_{3,k}, w_{2,1}),$$
$$h_{2,2}(h_{3,k+1}(...), ..., w_3), ..., w_{2,2}), ..., w_1) \tag{1}$$
where $h_{i,j}$, $i \in [2, ..., n]$, are the $(n - i + 1)$th layers in the neural network; $w_{i,j}$ is the parameter in $h_{i,j}(\cdot)$.

Definition 1 means that a neural network, without training, can be any function. With definition 1, a neural network is no longer a mathematical concept, but this idea is widely used in practice Roesch et al. (2019). We can see from definition 1 that the requirement that a neural network is in composite function form is the only mathematical property of a neural network that can be used for analysis.

In practice, the loss function is one method to evaluate a neural network. A lower loss on a dataset means a better performance neural network. For example, the training process optimises the model's loss, i.e., following Eq. 2.
$$\min_w f(w) = \mathbf{E}_{sample}\ell(w, sample) = \frac{1}{m} \sum_{(x_i, y_i) \in \mathbb{D}} \ell(w, x_i, y_i) \tag{2}$$

where $f(\cdot)$ is the loss for model on a dataset, w represents the model parameters, $\mathbb{D}$ is the dataset, m is the size of the dataset, $\ell(\cdot)$ is the loss function for a sample and (x_i, y_i) represents a sample in the dataset and its label.

In this paper, we mainly use the sequential neural network to describe the conclusion for the sequential neural network is easily described, and the whole conclusion is non-related to the structure of the neural network. For a sequential n-layer neural network, $\ell(\cdot)$ can be described in the following Eq.3 form.
$$\ell(w, x_i, y_i) = L(model_n(x_i, w), y_i)$$
$$model_n = h_1(h_2(h_3(h_4(\cdots h_n(h_{n+1}, w_n) \cdots, w_4), w_3), w_2), w_1) \tag{3}$$

where $L(\cdot)$ is the loss function, such as the cross-entropy function; h_i, $i \in [1, ..., n]$, is the $(n-i+1)$th layer in the neural network; $w = (w_n^T, w_{n-1}^T, \cdots, w_1^T)^T$, w_i is the parameter in $h_i(\cdot)$; and for a unified format, h_{n+1} stands for the sample x.

4 ANALYSIS OF COMPUTATIONAL NOISE ROBUSTNESS AND QUANTIZATION FOR INFERENCE

4.1 START POINT

4.1.1 ANALYSIS BASE

Quantization methods for inference are complex. Different algorithms use different assumption to solve the problem. Most of them pay much attention to the noise on parameters in NNDong et al. (2019a); Yao et al. (2020); Gholami et al. (2021); Nagel et al. (2020). However, in addition to the noise added to the parameters directly, noise is also introduced between different layers in the inference process because different quantization levels or data types of different precisions are used in different layers.

After quantization, the quantized loss for a sample, i.e. $\bar{\ell}(\cdot)$, in the inference process is as follows.

$$\bar{\ell}(w, x_i, y_i) = L(h_1(h_2(\cdots h_n(h_{n+1} + \epsilon_n, w_n + \delta_n) + \epsilon_{n-1} \cdots, w_2 + \delta_2) + \epsilon_1, w_1 + \delta_1), y_i)$$

where δ_i, $i \in 1, \cdots, n$, and ϵ_i, $i \in [1, ..., n]$, are the minor errors that are introduced in model parameter quantization and in data type conversion in the mixed-precision layout scheme, respectively.

Thus, we obtain the following expression based on the basic total differential calculation.

$$\bar{\ell}(w, x_i, y_i) - \ell(w, x_i, y_i) = \sum_{i=1}^{n} \frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon_i + \frac{\partial \ell}{\partial w_i} \cdot \delta_i \quad (4)$$

where $\cdot$ is inner product and $*$ is the scalar product in following parts. For the loss on whole dataset, we can gain

$$\min_{\epsilon \in E} \bar{f}(w) - f(w) = \frac{1}{m} \sum_{(x_j, y_j) \in \mathbb{D}} \sum_{i=1}^{n} \frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon_i + \frac{\partial \ell}{\partial w_i} \cdot \delta_i \quad (5)$$

$$= \frac{1}{m} \sum_{i=1}^{n} \sum_{(x_j, y_j) \in \mathbb{D}} \frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon_i \quad (6)$$

where $\bar{f}(w) = \frac{1}{m} \sum \bar{\ell}(\cdot)$. The reason for second equation in Eq. 6 is for a well-trained model, the expectation of $\ell(\cdot)$'s gradient for parameters is zero, i.e., for the $\sum_{(x_j, y_j) \in \mathbb{D}} \frac{\partial \ell}{\partial w}$ components, $\frac{\partial \ell}{\partial w_i} = 0$.

As we can see, current works mixed discussed the quantization for storage and inference Dong et al. (2019a); Yao et al. (2020); Dong et al. (2019b); Nahshan et al. (2021). Consequently, these works must add a "fine-tuning" process, and they still fail in some cases. Moreover, this is why channel-wise quantization methods are booming. In a channel that uses the same data type at all times, the precision loss of the corresponding layer input is usually zero.

4.1.2 TARGET AND ALGORITHM GUARANTEE

The key is to choose the appropriate ϵ vector to gain a lower loss model. When the loss of the inner product, i.e., $\sum_{(x_i, y_i) \in \mathbb{D}} \frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon$, is negative, the loss for the quantized model, i.e., $\bar{f}$, is lower than for the full precision model. An appropriate ϵ to produce a negative $\sum_{(x_i, y_i) \in \mathbb{D}} \frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon$ is our algorithm target.

A frequently asked question is why $\sum_{(x_j,y_j)\in\mathbb{D}} \frac{\partial\ell}{\partial w}$ is zero but $\sum_{(x_i,y_i)\in\mathbb{D}} \frac{\partial\ell}{\partial h_{i+1}}$ is non-zero. The optimization algorithm is to optimize w in the training process. Thus, $\sum_{(x_i,y_i)\in\mathbb{D}} \frac{\partial\ell}{\partial h_{i+1}}$ is random in the final model except for the layers with bias terms like the batch norm layer. The bias term will absorb the gradient and train them in the optimization process. What is more, in the model, which mainly consists of identity mapping, $\sum_{(x_i,y_i)\in\mathbb{D}} \frac{\partial\ell}{\partial h_{i+1}}$ is close to zero vector, and we will show this in the next chapter.

Our problem setting for quantization is different from previous work like HAWQDong et al. (2019a); Yao et al. (2020); Dong et al. (2019b); Nagel et al. (2020) because these methods do not take the error in the layer's input into consideration, which prevents their work and analysis in the mixed-precision computing area. As a result, these works can only be used to store a compressed neural network on a disk. When the compressed model is stored in memory for inference, these compressed models have to be recovered into the full precision model.

4.2 The Map from Mathematical Analysis to Real Engineering

In the above analysis, the whole process is under the condition that ϵ vector is small enough, which can be used in the total differential method. However, in practice, the scope of ϵ may be within [-0.1,0.1], which would escape the concept of neighbourhood. What is more, mapping ϵ vector into round operation should be fully discussed. This part will show how to deal with the above gap between analysis and engineering.

4.2.1 Round function choice

We use the convenient language of probability theory to describe $\frac{\partial\ell}{\partial h_{i+1}} \cdot \epsilon$ for ϵ is a stochastic vector naturally. We set $\epsilon = [e_1, e_2, .., e_k]$ and e_i is i.i.d. random variable. We also set that $\frac{\partial\ell}{\partial h_{i+1}} = [p_1, p_2, ..., p_k]$ and p_i is i.i.d. random variable [1]. e and p are independence to each other.

Then, we have $\frac{\partial\ell}{\partial h_{i+1}} \cdot \epsilon = \sum_{i=1}^{k} e_i * p_i = kep$ and following Eq. 7.

$$\mathbf{E}\frac{\partial\ell}{\partial h_{i+1}} \cdot \epsilon = \mathbf{E}\sum_{i=1}^{k} e_i * p_i = \mathbf{E}kep = k\mathbf{E}e\mathbf{E}p \tag{7}$$

For a trained model, the $\mathbf{E}p$ can be computed as $\mathbf{E}p = \frac{1}{k} * \frac{\partial\ell}{\partial h_{i+1}} \cdot \vec{1}$. Then to gain a negative $\mathbf{E}\frac{\partial\ell}{\partial h_{i+1}} \cdot \epsilon$, the $\mathbf{E}e$ should be different signs with $\mathbf{E}p$.

To gain the suitable ϵ vector, we use the different round functions to ensure the sign of $\mathbf{E}e$. The roundup function, i.e., the $ceil$ function in python, will produce an error vector whose all elements are positive. The round down function, i.e., the $floor$ function, will produce an error vector whose all elements are negative. Thus, we are sure that the $\mathbf{E}e$ is positive and negative by round methods. Although the parameters in layers have strong noise robustness, we still try to add less noise to them. Thus, in the parameters quantization process, we use the rounding method, i.e., the $round$ function in python, to quantize parameters for the rounding method exerts less noise on original data.

4.2.2 Replace gradient with secant line slope

.

Although the elements in the ϵ vector are not small enough to use the total differential directly, the elements in the ϵ vector are still small. For example, when using int8 to quantize the res14 model without identity mapping, the element in the ϵ vector is less than 0.01. The above fact shows that $\|\epsilon_i\| * \|\epsilon_i\|$ is small, which has a tiny influence on the final loss function. Thus, we can use the slope of the secant line to replace the gradient in the total differential, which is shown in figure 1.

Because in different direction, the secant line is different, which is shown in figure 2, so we have to define the following $secant^+(h_i, \Delta), \Delta \in \mathbb{R}^1+$ and $secant^-(h_i, \Delta), \Delta \in \mathbb{R}^1+$. Δ is the

---

[1]We also can treat p_i as the random variable with different distributions or directly use $\mathbf{E}\frac{\partial\ell}{\partial h_{i+1}}$ vector in following analyses. The conclusions are the same or close with current analysis.

Figure 1: When the predicted point(x_p) is out of the neighborhood range but not pretty far from x_0, secant lines between the x_0 and x_1 perform significantly better than tangent lines. The choice of x_1 is the maximum quantization noise in practice.

Figure 2: Different directions have different secant line in prediction process.

maximum error which is introduced by quantization. For example, the *scale* parameter in Section 3.1's example is the max error introduced by quantization.

$$\ell_j^{\bar{\mp}\pm}(w, x_i, y_i) = L(h_1(h_2(\cdots h_j(h_{j+1}(\cdots) \pm \Delta * \vec{1}, w_n) \cdots, w_2), w_1), y_i), \Delta > 0$$

$$\bar{f}_j^{\pm}(w) = \frac{1}{m} \sum_{x_i, y_i \in Dataset} \ell_j^{\bar{\mp}\pm}(\cdot), secant(h_i, \Delta)^{\pm} = \frac{f^{\pm} - f}{\pm \Delta}$$

In the algorithm, we will use $scant^{\pm}(\cdot)$ to replace $\frac{\partial \ell}{\partial h_{i+1}}^{\pm} \cdot \vec{1}$. We use this definition because 1. Compared to computing by the definition of secant, the *secant* function is easy to be computed. 2. If slope of secant line is $[sec_1, sec_2 ..., sec_k]$, $secant(h_i, \Delta)^{\pm} = \mathbf{E}sec$.

Although we know the element in ϵ vector is less than 0.01 empirically, we still have to set a mechanism in real algorithm design to keep the analysis map into algorithm practice. Thus, we have to set a value $error_{max}$, which ϵ is small enough for the final loss function. When $\Delta > error_{max}$, we can choose more bits quantization level or full precision in this layer.

When ϵ is close to zero, i.e., we use more bits quantization level. For $\|\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon_i\| \leq \|\frac{\partial \ell}{\partial h_{i+1}}\|\|\epsilon_i\|$, the performance loss or improvement is small on this layer. So, we directly quantize these parameters and layer's input with this quantization level to reduce computation resources. In algorithm design, we can use $error_{min}$ to control this case.

4.2.3 THE PROBABILITY OF GETTING A BETTER MODEL

To show the probability of getting positive $\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon$, we use chebyshev's theorem, we have following Eq. 8.

$$P(\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon \geq 0) < P(\|\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon - \mathbf{E}kep\| \geq \|\mathbf{E}kep\|)$$

$$\leq \frac{Var(kep)}{\|\mathbf{E}kep\|^2} = \frac{Var(e)Var(p)}{\|\mathbf{E}e\mathbf{E}p\|^2} + \frac{Var(e)}{\|\mathbf{E}e\|^2} + \frac{Var(p)}{\|\mathbf{E}p\|^2} \tag{8}$$

Based on Eq.8, we know that to gain a better model performance, for the layer whose $\|\frac{\partial \ell}{\partial h_{i+1}} \cdot \vec{1}\|$ is large and $Var(p)$ is small, we can use high quantization level to gain a model which is better than full precision model with high probability. To guarantee the success probability is high, we can set a algorithm parameter μ and σ. Algorithm quantize $Layer_i$ only when $\|\mathbf{E}p\| > \mu$ and $Var(p) < \sigma$.

4.3 ALGORITHM DESCRIPTION

Based on the above map between analysis and engineering, we can get algorithm 1. Algorithm 1 is a radical probability algorithm. In algorithm 1, we use a high quantization level as a priority to gain a

---

Algorithm 1: Radical Mixed-Precision Inference Layout Scheme

Input: Neural network M, different quantization levels $[q_1, q_2, ..., q_n]$,
     $error_{min}, error_{max}, \mu$, calibration dataset D
Output: Quantized neural network $\bar{M}$
Arrange $Q = [q_1, q_2, ..., q_n]$ in ascending order $Q = [q_{i_1}, q_{i_2}, ..., q_{i_n}]$ based on the the size of
  parameters under q_i;//For example Q=[int8,int4,int16] into Q=[int4,int8,int16]
for q_i *in* Q **do**
    for $Layer_i$ *in* M **do**
        if $Layer_i$ *is quantized* **then**
           | continue
        end
        Compute the error Δ of h_{i+1} under q_i quantization level on D
        if $\Delta < error_{min}$ **then**
           | quantize $Layer_i$'s parameters and input by rounding method on q_i quantization level.
        end
        if $\Delta > error_{max}$ **then**
           | continue
        end
        Compute $secant^+(h_i, \Delta)$ and $secant^-(h_i, \Delta)$
        if $\|secant^\pm(\cdot)\| < \mu$ **then**
           | continue
        end
        $Choice = \max(\| \max(secant^-(h_i, \Delta), 0)\|, \| \min(secant^+(h_i, \Delta)\|, 0))$
        if $Choice == secant^-(h_i, \Delta)$ **then**
           | quantize $Layer_i$'s input by round down method on q_i quantization level.
        end
        if $Choice == secant^+(h_i, \Delta)$ **then**
           | quantize $Layer_i$'s input by round up method on q_i quantization level.
        end
        if $Choice\ != 0$ **then**
           | quantize $Layer_i$'s parameters by rounding method on q_i quantization level.
        end
    end
end
return $\bar{M}$

---

small quantized model. Under the appropriate μ setting, algorithm 1 would give a better model with a high probability. Algorithm 1 does not use the σ value to guarantee success because the cost of computing the variance is high.

5   IDENTITY MAPPING AND QUANTIZATION

Although we give a method to gain a better model, we find that ResNets are hard to gain a significant effect. What is more, we find that for most of the quantization algorithms, the performance of ResNets is pretty stable. In this part, we will give theoretical proof of the above phenomena.

The neural network is under the description of the probably approximately correct (PAC) learning framework Denilson & Barbosa (2016). A neural network hypothesis class $\mathscr{H}$ consists of the neural networks which share the same structure. The learning algorithms, $\mathscr{A}$, are SGD and SGD's variants for the neural network hypothesis class. Identity mapping is when the input to some layer is passed directly or as a shortcut to some other layer. The neural networks, which mainly consist of identity mappings, like ResNet or DenseNet, succeed in the CV area. Then, we can gain the following propositions.

Proposition 1 *There is a set of function $\mathscr{G}$. For any random variable vector x and any random variable vector y, $\exists g \in \mathscr{G}$ which satisfies $\mathbf{E}g(x) \cdot \mathbf{E}y \leq 0$ and $g(x)$ belongs to $\vec{0}$'s neighborhood.*

For a well-trained neural network $model_n^* \in \mathscr{H}_n$ by learning algorithm $\mathscr{A}$, there exists a $model_{n+1} \in \mathscr{H}_{n+1}$ which is slightly better than $model_n^*$. The difference between $\mathscr{H}_n$ and $\mathscr{H}_{n+1}$ is the $model_{n+1} \in \mathscr{H}_{n+1}$ have one more residual block than $model_{n+1} \in \mathscr{H}_n$ and the function in residual block is in $\mathscr{G}$.

Brief proof: From the analysis in algorithm 1, we can find an appropriate $\mathbf{E}\epsilon$ that $\mathbf{E}\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon \le 0$. We can use $g \in \mathscr{G}$ to replace ϵ. Then, proposition 1 is proved, which is also shown in figure 3.

The set, which consists of $Relu(Conv(\cdot))$, satisfies the requirements of $\mathscr{G}$. Proposition 1 tells us how to structure a deep residual network. Repeatedly using proposition 1 and retraining the new model would show that for the neural networks consisting of residual blocks like ResNet, the deeper, the better. It is shown in figure 4. Using proposition 1 in a different place, we can get different networks, shown in figure 5.

Based on the proposition 1's structure process, we can prove the following proposition 2.

Proposition 2 *For a dataset's SOTA or close to SOTA residual network, all $\mathbf{E}\frac{\partial \ell}{\partial h_{i+1}}$ are close to zero.*

Brief proof: The SOTA model implies that adding new layers will not improve model performance, i.e., for well-trained $model_n^* \in \mathscr{H}_n$ and well-trained $model_{n+1}^* \in \mathscr{H}_{n+1}$, $\mathbf{E}_{sample}L(model_n^*, sample) - \mathbf{E}_{sample}L(model_{n+1}^*, sample) = 0$. So for any i and any appropriate $\mathbf{E}\epsilon$, we have the following Eq 9.

$$\mathbf{E}\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon = \mathbf{E}_{sample}L(model_n^*, sample) - \mathbf{E}_{sample}L(model_{n+1}, sample)$$
$$< \mathbf{E}_{sample}L(model_n^*, sample) - \mathbf{E}_{sample}L(model_{n+1}^*, sample) = 0 \qquad (9)$$

Because i and $\mathbf{E}\epsilon$ can be chosen at random, we can tell that $\mathbf{E}\frac{\partial \ell}{\partial h_{i+1}}$ is zero or very close to zero.

Proposition 2 shows one of the residual network's SOTA criterion. Then, we can prove the following theorem 1.

Theorem 1 *The SOTA or near to SOTA residual networks in a dataset exhibit high noise robustness.*

Brief proof: Based on Eq.6 and proposition 2, we know

$$\|\bar{f}(w) - f(w)\| = \|\sum_{i=1}^{n} \mathbf{E}\frac{\partial \ell}{\partial h_{i+1}} \cdot \epsilon_i\| \le \sum_{i=1}^{n} \|\mathbf{E}\frac{\partial \ell}{\partial h_{i+1}}\|\|\mathbf{E}\epsilon_i\| = 0 \qquad (10)$$

Theorem 1 shows that any quantization algorithm can quantize a SOTA or close SOTA residual model with less loss. Furthermore, Theorem 1 also shows that algorithm 1 cannot improve model performance too much.

6 EXPERIMENT

In this section, we evaluate the performance of algorithm 1. Our objective is to show that the quantized model gained by algorithm 1 is better than the full precision model without "fine-tuning" technology. The improvements are significant, especially for some neural networks that are not SOTA residual networks.

We use CIFAR 10 datasets. The training dataset is split into calibration and training datasets. Furthermore, the size of the calibration dataset is equal to the test dataset.

As discussed in Section 5, the model with many identity mapping structures has strong noise robustness. Thus we have to choose the model which is far from the SOTA model. For CIFAR 10, ResNet 20 is close to the SOTA ResNet model(ResNet 110). In experiments, the performance of ResNet 20 is only higher by 1% to 2% in the error rate than ResNet 110. Thus, we choose ResNet 8 and ResNet 14 as our quantization models. Furtherly, to enlarge the $\mathbf{E}\frac{\partial \ell}{\partial h_{i+1}}$, we delete the identity mapping structure in our experimental models. VGG models also are pretty suit for this experiments

Figure 3: Proof of proposition 1

Figure 4: The deeper the neural network is, the better.

Figure 5: Using the Proof of proposition 1 in position 1 repeatedly, we can get ResNet. Using the Proof of proposition 1 in position 1 and 2 repeatedly, we can get DenseNet.

for the structure of VGG is sequential. However, SOTA VGG model, VGG19, shows the same properties with ResNets–the gradients for middle-output is close to zero. Thus, we use VGG11 and 16 in experiments.

In quantization practice, quantizing data into INT8 is the most frequently used and ripe choice because current computation devices, like V100GPU, only support INT8, INT16 and INT32 computing in hardware. Thus, we use mixed-precision INT8 and full-precision(FP32) in our experiments. In Cifar 10 experiment, the min and max value for a quantization vector is decided by whole calibration dataset. Before quantization process, we will process whole calibration dataset in full precise and find the min and max value and compute Δ. We use this setting because we want to enlarge the noise and get a obvious experimental results. However, in VGG experiments, under this setting, we cannot find an appropriate layer to quantize because all Δs are large or $Choice$s variable are zero. Thus, we use the min/max on current quantization vector like HAWQ's experiments to compute Δ. Δ, which is the error caused by the INT8 quantization level for layers' input, is under 0.01 for most of the elements, but a few of them are above this range. So, we use 0.01 in all $secant(\cdot)$ functions. To gain a high performance model as radically as possible, we set $error_{min} = 0$, $\mu = 0$ and $error_{max} = 0.1$.

The loss for ResNet8 with the full precision is 0.3896, and the loss for the quantization model is 0.3782 with all layers quantized. The loss for ResNet14 with full precision is 0.3634, and the loss for the quantization model is 0.3576 with ten layers quantized. Only ten layers are quantized because the $choice$ variable in algorithm 1 is zero for most of the layers. To quantize ResNet14 further, we have to use another quantization level to gain a better performance model, like the INT16 level. However, the current low precision computation toolchains are uncompleted. For example, CUDNN only supports FP32, FP16, INT32 and INT8 input. Further ResNet14 experiments on different fabricated quantization settings are nonsense. The loss for VGG11 with the full precision is 0.0019, and the loss for the quantization model is 0.0017. The loss for VGG16 with full precision is 0.00908., and the loss for the quantization model is 0.0086.

7   CONCLUSION

This paper shows that quantization technology can improve the model's performance, i.e., gain a lower loss. Moreover, based on our analysis, we propose a Radical Mixed-Precision Inference Layout Scheme, which could produce a quantized model which is better than the full-precision model. We also show that residual networks are very resistant to noise. This means that the performance of a SOTA residual network is stable for any quantization algorithms.

In this paper, we also want to show the idea that the neural networks or algorithms should be categorized based on mathematical properties instead of the field like CV/NLP and so on. The same algorithm shows great different performance on different models and datasets which is described by math instead of end to end field.

REFERENCES

Matthieu Courbariaux, Yoshua Bengio, and Jean-Pierre David. Binaryconnect: Training deep neural networks with binary weights during propagations. In *Advances in neural information processing systems*, pp. 3123–3131, 2015.

A. Demidovskij and E. Smirnov. Effective post-training quantization of neural networks for inference on low power neural accelerator. In *2020 International Joint Conference on Neural Networks (IJCNN)*, 2020.

Denilson and Barbosa. Understanding machine learning: from theory to algorithms. *Computing reviews*, 57(4):238–238, 2016.

Z. Dong, Z. Yao, A. Gholami, M. Mahoney, and K. Keutzer. Hawq: Hessian aware quantization of neural networks with mixed-precision. *IEEE*, 2019a.

Zhen Dong, Zhewei Yao, Yaohui Cai, Daiyaan Arfeen, Amir Gholami, Michael W Mahoney, and Kurt Keutzer. Hawq-v2: Hessian aware trace-weighted quantization of neural networks. *arXiv preprint arXiv:1911.03852*, 2019b.

Amir Gholami, Sehoon Kim, Zhen Dong, Zhewei Yao, Michael W Mahoney, and Kurt Keutzer. A survey of quantization methods for efficient neural network inference. *arXiv preprint arXiv:2103.13630*, 2021.

Song Han, Jeff Pool, John Tran, and William J Dally. Learning both weights and connections for efficient neural networks. *arXiv preprint arXiv:1506.02626*, 2015.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient convnets. *arXiv preprint arXiv:1608.08710*, 2016.

R. Li, Y. Wang, F. Liang, H. Qin, and R. Fan. Fully quantized network for object detection. In *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2019.

Huizi Mao, Song Han, Jeff Pool, Wenshuo Li, Xingyu Liu, Yu Wang, and William J Dally. Exploring the regularity of sparse structure in convolutional neural networks. *arXiv preprint arXiv:1705.08922*, 2017.

Nelson Morgan et al. Experimental determination of precision requirements for back-propagation training of artificial neural networks. In *Proc. Second Int'l. Conf. Microelectronics for Neural Networks*, pp. 9–16. Citeseer, 1991.

Markus Nagel, Rana Ali Amjad, Mart Van Baalen, Christos Louizos, and Tijmen Blankevoort. Up or down? adaptive rounding for post-training quantization. In *International Conference on Machine Learning*, pp. 7197–7206. PMLR, 2020.

Yury Nahshan, Brian Chmiel, Chaim Baskin, Evgenii Zheltonozhskii, Ron Banner, Alex M Bronstein, and Avi Mendelson. Loss aware post-training quantization. *Machine Learning*, 110(11):3245–3262, 2021.

X. Qian, V. Li, and C. Darren. Channel-wise hessian aware trace-weighted quantization of neural networks. 2020.

J. Roesch, S. Lyubomirsky, M. Kirisame, J. Pollock, and Z. Tatlock. Relay: A high-level ir for deep learning. 2019.

Karen Ullrich, Edward Meeds, and Max Welling. Soft weight-sharing for neural network compression. *arXiv preprint arXiv:1702.04008*, 2017.

Kuan Wang, Zhijian Liu, Yujun Lin, Ji Lin, and Song Han. Haq: Hardware-aware automated quantization with mixed precision. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 8612–8620, 2019.

Bichen Wu, Yanghan Wang, Peizhao Zhang, Yuandong Tian, Peter Vajda, and Kurt Keutzer. Mixed precision quantization of convnets via differentiable neural architecture search. *arXiv preprint arXiv:1812.00090*, 2018.

Z. Yao, Z. Dong, Z. Zheng, A. Gholami, and K. Keutzer. Hawqv3: Dyadic neural network quantization. 2020.

Haibao Yu, Qi Han, Jianbo Li, Jianping Shi, Guangliang Cheng, and Bin Fan. Search what you want: Barrier panelty nas for mixed precision quantization. In *European Conference on Computer Vision*, pp. 1–16. Springer, 2020.