Towards Understanding the Condensation of Neural Networks at Initial Training

Abstract

Implicit regularization is important for understanding the learning of neural networks (NNs). Empirical works show that input weights of hidden neurons (the input weight of a hidden neuron consists of the weight from its input layer to the hidden neuron and its bias term) condense on isolated orientations with a small initialization. The condensation dynamics implies that the training implicitly regularizes a NN towards one with much smaller effective size. In this work, we utilize multilayer networks to show that the maximal number of condensed orientations in the initial training stage is twice the multiplicity of the activation function, where "multiplicity" is multiple roots of activation function at origin. Our theoretical analysis confirms experiments for two cases, one is for the activation function of multiplicity one, which contains many common activation functions, and the other is for the layer with one-dimensional input. This work makes a step towards understanding how small initialization implicitly leads NNs to condensation at initial training stage, which lays a foundation for the future study of the nonlinear dynamics of NNs and its implicit regularization effect at a later stage of training.

1 Introduction

Over-parameterized neural networks often show good generalization performance on real-world problems by minimizing loss functions without explicit regularization (Breiman, 1995; Zhang et al., 2017). For over-parameterized NNs, there are infinite possible sets of training parameters that can reach a satisfying training loss. However, their generalization performances can be very different. It is important to study what implicit regularization is imposed aside to the loss function during the training that leads the NN to a specific type of solutions.

Empirical works suggest that NNs may learn the data from simple to complex patterns (Arpit et al., 2017; Xu et al., 2019; Rahaman et al., 2019; Xu et al., 2020; Jin et al., 2020; Kalimeris et al., 2019). For example, an implicit bias of frequency principle is widely observed that NNs often learn the target function from low to high frequency (Xu et al., 2019; Rahaman et al., 2019; Xu et al., 2020). Frequency principle inspires a series of algorithms for fast learning high frequency (Xu et al., 2020; Jagtap et al., 2020; Biland et al., 2019; Cai et al., 2020; Peng et al., 2020; Cai & Xu, 2019; Liu et al., 2020; Li et al., 2020; Wang, 2020; Tancik et al., 2020; Mildenhall et al., 2020; Agarwal et al., 2020; Campo et al., 2020; Jiang et al., 2020; Xi et al., 2020) and has been utilized to understand various phenomena emerging in applications of deep learning (Ma et al., 2020; Sharma & Ross, 2020; Zhu et al., 2019; Chakrabarty & Maji, 2019; Xu & Zhou, 2021) The NN output, either simple or complex, is a collective result of all neurons. The study of how neuron weights evolve during the training is central to understanding the collective behavior, including the complexity, of the NN output.

Luo et al. (2021) establish a phase diagram to study the effect of initialization on weight evolution for two-layer ReLU NNs at the infinite-width limit and find that the neural tangent kernel (NTK) initialization and the mean-field initialization are special cases of the linear regime and the critical regime, respectively. Aside from the linear and the critical regime in the phase diagram is a largely unexplored non-linear regime. This non-linear regime is named as condensed regime because the input weights of hidden neurons (the input weight or the feature of a hidden neuron consists of the weight from its input layer to the hidden neuron and its bias term) condense on isolated orientations

Table 1: Comparison of common (Glorot & Bengio, 2010) and condensed Gaussian initializations on resnet18. $\bar{m} = (m_{\text{in}} + m_{\text{out}})/2$. m_{in}: in-layer width. m_{out}: out-layer width.

	common			condensed		
	Glorot_uniform	Glorot_normal	$N(0, \frac{1}{\bar{m}})$	$N(0, \frac{1}{m_{\text{out}}^4})$	$N(0, \frac{1}{m_{\text{out}}^3})$	$N(0, (\frac{1}{\bar{m}})^2)$
Test 1	0.8807	0.8777	0.8816	0.8847	0.8824	0.8826
Test 2	0.8857	0.8849	0.8806	0.8785	0.8813	0.8807
Test 3	0.8809	0.8860	0.8761	0.8824	**0.8861**	0.8800

during the training (Luo et al., 2021). The three regimes in the phase diagram, i.e., linear regime, critical regime and condensed regime, are identified based on the relative change of input weights as the width approaches infinity, which tends to 0, $O(1)$ and $+\infty$, respectively.

The condensation is a feature learning process, which is important to the learning of DNNs. Note that in the following, **condensation is accompanied by a default assumption of small initialization or large relative change of input weights during training**. For practical networks, such as resnet18-like (He et al., 2016) in learning CIFAR10, as shown in Fig. 1(a) and Table 1, we find that the performance of networks with initialization in the condensed regime is very similar to the common initialization methods. However, the condensation phenomenon provides an intuitive explanation of the good performance as follows, which may lead to a quantitatively theory explanation in future work. The condensation transforms a large network to a network of only a few effective neurons, leading to an output function with low complexity. Since the complexity bounds the generalization error (Bartlett & Mendelson, 2002), the study of condensation could provide insight to how NNs are implicitly regularized to achieve good generalization performance in practice.

For two-layer ReLU NN, Maennel et al. (2018) prove that, as the initialization of parameters goes to zero, the features of hidden neurons condense at finite number of orientations depending on the input data; when performing a linearly separable classification task with infinite data, Pellegrini & Biroli (2020) show that at mean-field limit, a two-layer infinite-width ReLU NN is effectively equal to a NN of one hidden neuron, i.e., condensation on a single orientation. Both works (Maennel et al., 2018; Pellegrini & Biroli, 2020) study the condensation behavior for ReLU-NNs at an initial training stage in which the magnitudes of NN parameters are far smaller from well-fitting an $O(1)$ target function. However, it still remains unclear that **for NNs of more general activation functions, how the condensation emerges at the initial training stage.**

In this work, we show that the condensation at the initial stage is closely related to the multiplicity p at $x = 0$, which means the derivative of activation at $x = 0$ is zero up to the $(p-1)th$-order and is non-zero for the p-th order. To verify their relation, we use the common activation function $\text{sigmoid}(x)$, $\text{softplus}(x)$, $\tanh(x)$, which are multiplicity one, and variants of $\tanh(x)$ for our experiments. The most simple way to increase the multiplicity of a function is to multiply the function with x. Therefore, the variants we use are $x \tanh(x)$ and $x^2 \tanh(x)$. For comparison, we also show the initial condensation of $\text{ReLU}(x)$, which is studied previously (Maennel et al., 2018) and has totally different properties at origin compared with $\tanh(x)$. Our experiments suggest that the maximal number of condensed orientations is twice the multiplicity of the activation function used in general NNs. For finite-width two-layer NNs with small initialization at the initial training stage, each hidden neuron's output in a finite domain around 0 can be approximated by a p-th order polynomial and so is the NN output function. Based on the p-th order approximation, we show a preliminary theoretical support for condensation by a theoretical analysis for two cases, one is for the activation function of multiplicity one, which contains many common activation functions, and the other is for the layer with one-dimensional input. Therefore, small initialization imposes an implicit regularization that restricts the NN to be effectively much narrower neural network at the initial training stage. As commonly used activation functions, such as $\tanh(x)$, $\text{sigmoid}(x)$, $\text{softplus}(x)$, etc., are all multiplicity one, our study of initial training behavior lays an important basis for the further study of implicit regularization throughout the training.

(a) test accuracy   (b) ReLU, epoch 8   (c) $x\tanh(x)$, epoch 61

Figure 1: The test accuracy in (a) and condensation in (b, c) of networks on CIFAR10. Each network consists of the convolution part of resnet18 and fully-connected (FC) layers with size 1024-1024-10 and softmax. The color in (b, c) indicates the inner product of normalized input weights of two neurons in the first FC layer, whose indexes are indicated by the abscissa and the ordinate, respectively. We discard the hidden neurons, in which the L_2-norm of each input weight is smaller than 0.001, while remaining ones bigger than 0.05 in (b). The convolution part is equipped with ReLU activation and initialized by Glorot normal distribution (Glorot & Bengio, 2010). For FC layers in (a), the activation is ReLU and they are initialized by three common methods (red) and three condensed ones (green) as indicated in Table 1. The learning rate is 10^{-3} for epoch 1-60 and 10^{-4} for epoch 61-100. For (b, c), the learning rate is 5×10^{-6} for visualization and FC layers are initialized by $N(0, \frac{1}{m_{\text{out}}^3})$ and equipped with ReLU in (b) and $x\tanh(x)$ in (c) as activation functions. Adam optimizer with cross-entropy loss and batch size 128 are used for all experiments.

2 RELATED WORKS

A research line studies how initialization affects the weight evolution of NNs with a sufficiently large or infinite width. For example, with an initialization in the neural tangent kernel (NTK) regime or lazy training regime (weights change slightly during the training), the gradient flow of infinite-width NN, can be approximated by a linear dynamics of random feature model (Jacot et al., 2018; Arora et al., 2019; Zhang et al., 2020; E et al., 2020; Chizat & Bach, 2019), whereas for the initialization in the mean-field regime (weights change significantly during the training), the gradient flow of infinite-width NN exhibits highly nonlinear dynamics (Mei et al., 2019; Rotskoff & Vanden-Eijnden, 2018; Chizat & Bach, 2018; Sirignano & Spiliopoulos, 2020). Pellegrini & Biroli (2020) analyze how the dynamics of each parameter transforms from a lazy regime (NTK initialization) to a rich regime (mean-field initialization) for an two-layer infinite-width ReLU NN to perform a linearly separable classification task with infinite data. Luo et al. (2021) systematically study the effect of initialization for two-layer ReLU NN with infinite width by establishing a phase diagram, which shows three distinct regimes, i.e., linear regime (similar to the lazy regime), critical regime and condensed regime (similar to the rich regime), based on the relative change of input weights as the width approaches infinity, which tends to 0, $O(1)$ and $+\infty$, respectively. NTK initialization is a specific example of the linear regime, while the mean-field initialization is a specific example of the critical regime, which serves as the boundary between the other two regimes. Luo et al. (2021) also empirically find that, in the condensed regime, the features of hidden neurons (orientation of the input weight) condense in several isolated orientations, which is a strong feature learning behavior, an important characteristic of deep learning.

3 PRELIMINARY: NEURAL NETWORKS

A two-layer NN is

$$f_{\boldsymbol{\theta}}(\boldsymbol{x}) = \sum_{j=1}^{m} a_j \sigma(\boldsymbol{w}_j \cdot \boldsymbol{x}), \tag{1}$$

where $\sigma(\cdot)$ is the activation function, $\boldsymbol{w}_j = (\bar{\boldsymbol{w}}_j, \boldsymbol{b}_j) \in \mathbb{R}^{d+1}$ is the neuron feature including the input weight and bias terms, and $\boldsymbol{x} = (\bar{\boldsymbol{x}}, 1) \in \mathbb{R}^{d+1}$ is combination of the input sample and scalar

1, $\boldsymbol{\theta}$ is the set of all parameters, i.e., $\{a_j, \boldsymbol{w}_j\}_{j=1}^m$. For simplicity, **we call $\boldsymbol{w}_j$ as input weight or weight** and $\boldsymbol{x}$ as input sample.

A L-layer NN can be recursively defined by feeding the output of the previous layer as the input to the current hidden layer i.e.,

$$\boldsymbol{x}^{[0]} = (\boldsymbol{x}, 1), \quad \boldsymbol{x}^{[1]} = (\sigma(\boldsymbol{W}^{[1]}\boldsymbol{x}^{[0]}), 1), \quad \boldsymbol{x}^{[l]} = (\sigma(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]}), 1), \text{ for } l \in \{2, 3, ..., L\}$$

$$f(\boldsymbol{\theta}, \boldsymbol{x}) = \frac{1}{\alpha}\mathbf{a}^\mathsf{T}\boldsymbol{x}^{[L]} \triangleq f_{\boldsymbol{\theta}}(\boldsymbol{x}),$$

(2)

where $\boldsymbol{W}^{[l]} = (\bar{\boldsymbol{W}}^{[l]}, \boldsymbol{b}^{[l]}) \in \mathbb{R}^{m_l \times (m_{l-1}+1)}$, and m_l represents the dimension of the l-th hidden layer. For simplicity, **we also call each row of $\boldsymbol{W}^{[l]}$ as input weight or weight** and $\boldsymbol{x}^{[l-1]}$ as input neurons. The target function is denoted as $f^*(\boldsymbol{x})$. The training loss function is mean squared error

$$R_S(\boldsymbol{\theta}) = \frac{1}{2n} \sum_{i=1}^n (f_{\boldsymbol{\theta}}(\boldsymbol{x}_i) - f^*(\boldsymbol{x}_i))^2.$$

(3)

We consider the gradient flow training

$$\dot{\boldsymbol{\theta}} = -\nabla_{\boldsymbol{\theta}} R_S(\boldsymbol{\theta}).$$

(4)

For convenience, we characterize the activation function by the following definition.

Definition 1 (multiplicity p). *Suppose that $\sigma(x)$ satisfies the following condition, there exists a $p \in \mathbb{N}$ and $p \geq 1$, such that the k-th order derivative $\sigma^{(k)}(0) = 0$ for $k = 1, 2, \cdots, p-1$, and $\sigma^{(p)}(0) \neq 0$, then we say σ has multiplicity p.*

4 INITIAL CONDENSATION OF INPUT WEIGHTS

It is intuitively believed that NNs are powerful at learning data features, which should be an important reason behind the success of deep learning. A simple way to define a learned feature of a neuron is by the orientation of its input weights. Previous work in Luo et al. (2021) show that there is a condensed regime, where the neuron features condense on isolated orientations during the training for two-layer ReLU NNs. The condensation implies that although there are many more neurons than samples, the number of effective neurons, i.e., the number of different used features in fitting, is often much smaller than the number of samples. Therefore, the condensation provides a potential mechanism that helps over-parameterized NNs avoid overfitting. However, it is still unclear how the condensation, for general NNs with small initialization, emerges during the training. In this section, we would empirically show how the condensation differs among NNs with activation functions of different multiplicities, followed by theoretical analysis in the next section.

4.1 EXPERIMENTAL SETUP

Throughout this work, we use fully-connected neural network with size, d-m-$\cdots$-m-d_{out}. The input dimension d is determined by the training data. The output dimension is $d_{out} = 1$ for all experiments. The number of hidden neurons m is specified in each experiment. All parameters are initialized by a Gaussian distribution $N(0, var)$. The total data size is n. The training method is Adam with full batch expect for the Resnet18-like NN, learning rate lr and MSE loss. For synthetic data, we sample the training data uniformly from a sub-domain of $\mathbb{R}^d$. The real datasets are MNIST and CIFAR10.

4.2 MULTIDIMENSIONAL DATA

We first show the condensation at initial training stage in fitting multidimensional dataset. Since the input is a multidimensional vector, the direction is also multidimensional. To characterize the condensation, we use $D(\boldsymbol{u}, \boldsymbol{v})$ to denote the inner product of the normalized vectors of two input weights, i.e., $D(\boldsymbol{u}, \boldsymbol{v}) = \boldsymbol{u}^\mathsf{T}\boldsymbol{v}$.

(a) $\tanh(x)$ (b) $x\tanh(x)$ (c) $x^2\tanh(x)$

(d) $\mathrm{ReLU}(x)$ (e) $\mathrm{sigmoid}(x)$ (f) $\mathrm{softplus}(x)$

Figure 2: Condensation of two-layer NNs. The color indicates $D(u,v)$ of two hidden neurons' input weights at epoch 100, whose indexes are indicated by the abscissa and the ordinate, respectively. If neurons are in the same beige block, $D(u,v) \sim 1$ (navy-blue block, $D(u,v) \sim -1$), their input weights have the same (opposite) direction. The activation functions are indicated by the sub-captions. The training data is 80 points sampled from $\sum_{k=1}^{5} 3.5\sin(5x_k + 1)$, where each x_k is uniformly sampled from $[-4, 2]$. $n = 80$, $d = 5$, $m = 50$, $d_{out} = 1$, $var = 0.005^2$. $lr = 10^{-3}, 8 \times 10^{-4}, 2.5 \times 10^{-4}$ for (a-d), (e) and (f), respectively.

We use a two-layer fully-connected NN with size 5-50-1 to fit $n = 80$ training data sampled from a 5-dimensional function $\sum_{k=1}^{5} 3.5\sin(5x_k + 1)$, where $\boldsymbol{x} = (x_1, x_2, \cdots, x_5)^\mathsf{T} \in \mathbb{R}^5$ and each x_k is uniformly sampled from $[-4, 2]$. As shown in Fig. 2(a), for activation function $\tanh(x)$, the color indicates $D(u,v)$ of two hidden neurons' weights at epoch 100, whose indexes are indicated by the abscissa and the ordinate, respectively. If the neurons are in the same beige block, $D(u,v) \sim 1$ (navy-blue block, $D(u,v) \sim -1$), their input weights have the same (opposite) direction. Obviously, input weights of hidden neurons condense at two opposite directions, i.e., one line. As the multiplicity increasing, NNs with $x\tanh(x)$ (Fig. 2(b)) and $x^2\tanh x$ (Fig. 2(c)) condense at two and three different lines, respectively. For activation function $\mathrm{sigmoid}(x)$ in Fig. 2(d) and $\mathrm{softplus}(x)$ in Fig. 2(e), which are frequently used and have multiplicity one, NNs also condense at two opposite directions. For ReLU in Fig. 2(f), for which the multiplicity definition cannot apply, the NN condenses at three directions, in which two are opposite. Through these experiments, we conjecture that the maximal number of condensed orientations is twice the multiplicity of the activation function used at initial training.

For multilayer NNs with different activation functions, we show that the condensation for all hidden layers is similar to the two-layer NNs. In deep networks, residual connection is often introduced to overcome the vanishing of gradient. To show the generality of condensation, we perform an experiment of six-layer NNs with residual connections. To show the difference of various activation functions, we set the activation functions for hidden layer 1 to hidden layer 5 as $x^2\tanh(x)$, $x\tanh(x)$, $\mathrm{sigmoid}(x)$, $\tanh(x)$ and $\mathrm{softplus}(x)$ respectively. The structure of the residual is $\boldsymbol{h}_{l+1}(\boldsymbol{x}) = \sigma(\boldsymbol{W}_l\boldsymbol{h}_l(\boldsymbol{x}) + b_l) + \boldsymbol{h}_l(\boldsymbol{x})$, where $\boldsymbol{h}_l(\boldsymbol{x})$ is the output of the l-th layer. As shown in Fig. 3, input weights condense at three, two, one, one and one lines for hidden layer 1 to hidden layer 5, respectively, which is consistent with the condensation of two-layer NNs. Note that residual connections are not necessary. We show an experiment of the same structure as in Fig. 7 but without residual connections in Appendix. To show the universality of condensation, we train resnet18-like neural networks to learn CIFAR10. We study the condensation of the first fully connected layer of the network, using ReLU and $x\tanh(x)$ as the activation functions and initialization distribution $N(0, (\frac{1}{m^{1.5}})^2)$. As shown in Fig. 1 (b) and (c), the condensations for activation $\mathrm{ReLU}(x)$ and $x\tanh(x)$ are consistent with Fig. 2 and our conjecture.

We also find that when the training data is less oscillated, the NN may condense at fewer directions. For example, as shown in Fig. 4(a), compared with the high frequency function in Fig. 2, we only

| (a) layer 1 | (b) layer 2 | (c) layer 3 | (d) layer 4 | (e) layer 5 |

Figure 3: Condensation of six-layer NNs with residual connections. The activation functions for hidden layer 1 to hidden layer 5 are $x^2 \tanh(x)$, $x \tanh(x)$, $\mathrm{sigmoid}(x)$, $\tanh(x)$ and $\mathrm{softplus}(x)$, respectively. The numbers of steps selected in the sub-pictures are epoch 1000, epoch 900, epoch 900, epoch 1400 and epoch 1400, respectively, while the NN is only trained once. The color indicates $D(u,v)$ of two hidden neurons' input weights, whose indexes are indicated by the abscissa and the ordinate, respectively. The training data is 80 points sampled from a 3-dimensional function $\sum_{k=1}^{3} 4\sin(12x_k + 1)$, where each x_k is uniformly sampled from $[-4, 2]$. $n = 80$, $d = 3$, $m = 18$, $d_{out} = 1$, $var = 0.01^2$, $lr = 4 \times 10^{-5}$.

change the target function to be a lower-frequency function, i.e., $\sum_{k=1}^{5} 3.5\sin(2x_k + 1)$. In this case, the NN with $x^2 \tanh(x)$ only condenses at three directions, in which two are opposite. For MNIST data in Fig. 4(b), we find that, the NN with $x^2 \tanh(x)$ condenses at one line, which may suggest that the function for fitting MNIST dataset is a low-frequency function.

| (a) $\sum_{k=1}^{5} 3.5\sin(2x_k + 1)$ | (b) MNIST |

Figure 4: Condensation of low-frequency functions with two-layer NNs. The color indicates $D(u,v)$ of two hidden neurons' input weights, whose indexes are indicated by the abscissa and the ordinate, respectively. Two-layer NN at epoch: 100. Activation function: $x^2 \tanh(x)$. For (a), we discard hidden neurons, in which the L_2-norm of each input weight is smaller than 0.04, while remaining those bigger than 0.4. All settings in (a) are the same as Fig. 2, except for the lower frequency target function. Parameters for (b) are $n = 60000$, $d = 784$, $m = 30$, $d_{out} = 1$, $var = 0.001^2$. $lr = 5 \times 10^{-5}$.

To understand the mechanism of the initial condensation, we turn to experiments of 1-d input and two-layer NN, which can be clearly visualized in the next subsection.

4.3 1-D INPUT AND TWO-LAYER NN

For 1-d data, we visualize the evolution of the two-layer NN output and each weight, which confirms the connection between the condensation and the multiplicity of the activation function.

We display the outputs at initial training, epoch 1000, in Fig. 5. Due to the small magnitude of parameters, an activation function with multiplicity p can be well approximated by a p-th order polynominal, thus, the NN output can also be approximated by a p-th order polynominal. As shown in Fig. 5(a-c), the NN outputs with activation functions $\tanh(x)$, $x \tanh(x)$ and $x^2 \tanh(x)$ overlap well with the auxiliary of a linear, a quadratic and a cubic polynominal curve, respectively. In Fig. 5(d), the NN output with ReLU activation function deviates from a linear function (red auxiliary line). Particularly, the NN output has several sharp turning points. This experiment, although simple,

(a) $\tanh(x)$ (b) $x\tanh(x)$ (c) $x^2\tanh(x)$ (d) $\mathrm{ReLU}(x)$

Figure 5: The outputs of two-layer NNs at epoch 1000 with activation functions $\tanh(x)$, $x\tanh(x)$, $x^2\tanh(x)$, and $\mathrm{ReLU}(x)$ are displayed, respectively. The training data is 40 points uniformly sampled from $\sin(3x) + \sin(6x)/2$ with $x \in [-1, 1.5]$, illustrated by green dots. The blue solid lines are the NN outputs at test points, while the red dashed auxiliary lines are the first, second, third and first order polynomial fittings of the test points for (a, b, c, d), respectively. Parameters are $n = 40, d = 1, m = 100, d_{out} = 1, var = 0.005^2, lr = 5 \times 10^{-4}$.

but convincingly shows that NN does not always learn a linear function at the initial training stage and the complexity of such learning depends on the activation function.

(a) $\tanh(x)$ (b) $x\tanh(x)$ (c) $x^2\tanh(x)$ (d) $\mathrm{ReLU}(x)$

Figure 6: The direction field for input weight $\boldsymbol{w} := (w, b)$ of the dynamics in (4.3) at epoch 200. All settings are the same as Fig. 5. Around the original point, the field has one, two, three stables lines, on which an input weight would keep its direction, for $\tanh(x)$, $x\tanh(x)$, and $x^2\tanh(x)$, respectively. We also display the value of each weight by the green dots and the corresponding directions by the orange arrows.

We visualize the direction field for input weight $\boldsymbol{w}_j := (w_j, b_j)$, following the gradient flow,

$$\dot{\boldsymbol{w}}_j = -\frac{a_j}{n}\sum_{i=1}^{n} e_i \sigma'(\boldsymbol{w}_j \cdot \boldsymbol{x}_i)\boldsymbol{x}_i,$$

where $e_i := f_{\boldsymbol{\theta}}(\boldsymbol{x}_i) - f^*(\boldsymbol{x}_i)$. Since we only care about the direction of $\boldsymbol{w}_j$ and a_j is a scalar at each epoch, we can visualize $\dot{\boldsymbol{w}}_j$ by $\dot{\boldsymbol{w}}_j/a_j$. For simplicity, we do not distinguish $\dot{\boldsymbol{w}}_j/a_j$ and $\dot{\boldsymbol{w}}_j$ if there is no ambiguity. When we compute $\dot{\boldsymbol{w}}_j$ for different j's, $e_i\boldsymbol{x}_i$ for $(i = 1, \cdots, n)$ is independent with j. Then, at each epoch, for a set of $\{e_i, \boldsymbol{x}_i\}_{i=1}^{n}$, we can consider the following direction field

$$\dot{\boldsymbol{\omega}} = -\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i \sigma'(\boldsymbol{\omega} \cdot \boldsymbol{x}_i).$$

When $\boldsymbol{\omega}$ is set as $\boldsymbol{w}_j$, we can obtain $\dot{\boldsymbol{w}}_j$. As shown in Fig. 6, around the original point, the field has one, two, three stables lines, on which a neuron would keep its direction, for $\tanh(x)$, $x\tanh(x)$, and $x^2\tanh(x)$, respectively. We also display the input weight of each neuron on the field by the green dots and their corresponding velocity directions by the orange arrows. Similarly to the high-dimensional cases, NNs with multiplicity p activation functions condense at p different lines for $p = 1, 2, 3$. Therefore, It is reasonable to conjecture that the maximal number of condensed orientations is twice the multiplicity of the activation function used. As shown in Fig. 6(d), the field and the condensation for the NN with $\mathrm{ReLU}(x)$ is much more complex.

Taken together, we have empirically shown that the multiplicity of the activation function is a key factor that determines the complexity of the initial output and initial condensation.

5 ANALYSIS OF THE INITIAL CONDENSATION OF INPUT WEIGHTS

In this section, we would present a preliminary analysis to understand how the multiplicity of the activation function affects the initial condensation. At each training step, we consider the velocity field of weights in each hidden layer of a neural networks.

Considering a network with L hidden layers, we use row vector $\boldsymbol{W}_j^{[k]}$ to represent the weight from the $(k$-1$)$-th layer to the j-th neuron in the k-th layer. For each k and j, $\boldsymbol{W}_j^{[k]}$ satisfies the following dynamics, (see Appendix)

$$\dot{r} = \boldsymbol{u} \cdot \dot{\boldsymbol{w}}, \quad \dot{\boldsymbol{u}} = \frac{\dot{\boldsymbol{w}} - (\dot{\boldsymbol{w}} \cdot \boldsymbol{u})\boldsymbol{u}}{r}. \tag{5}$$

where $\boldsymbol{w}$ can be $\boldsymbol{W}_j^{[k]\mathsf{T}}$ for all k's and j's, $r = \|\boldsymbol{w}\|_2$ is the amplitude, and $\boldsymbol{u} = \boldsymbol{w}/r$.

Suppose the activation function has multiplicity p, i.e., $\sigma^{(k)}(0) = 0$ for $k = 1, 2, \cdots, p-1$, and $\sigma^{(p)}(0) \neq 0$. For convenience, we define an operator $\mathcal{P}$ satisfying $\mathcal{P}\boldsymbol{w} := \dot{\boldsymbol{w}} - \boldsymbol{u}(\dot{\boldsymbol{w}} \cdot \boldsymbol{u})$. Condensation refers to that the weight evolves towards a direction that will not change in the direction field and is defined as follows,

$$\dot{\boldsymbol{u}} = 0 \iff \mathcal{P}\boldsymbol{w} := \dot{\boldsymbol{w}} - \boldsymbol{u}(\dot{\boldsymbol{w}} \cdot \boldsymbol{u}) = 0.$$

Since $\dot{\boldsymbol{w}} \cdot \boldsymbol{u}$ is a scalar, $\dot{\boldsymbol{w}}$ is parallel with $\boldsymbol{u}$. $\boldsymbol{u}$ is a unit vector, therefore, we have $\boldsymbol{u} = \dot{\boldsymbol{w}}/\|\dot{\boldsymbol{w}}\|_2$. In this work, we consider NNs with sufficiently small parameters. For example, suppose $r = \|\boldsymbol{w}\|_2 \sim O(\epsilon)$, ϵ is a small quantity. Dynamics (5) shows that $O(\dot{r}) \sim O(\dot{\boldsymbol{w}})$ and $O(\dot{\boldsymbol{u}}) \sim O(\dot{r})/O(\epsilon)$. Therefore, the orientation $\boldsymbol{u}$ would moves much more quickly than the amplitude r. In the following, we study the case of (i) $p = 1$ and (ii) $m_l = 1$.

5.1 CASE 1: $p = 1$

Since we have (see Appendix),

$$\boldsymbol{w}^\mathsf{T} = \dot{\boldsymbol{W}}_j^{[k]} = -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta}, \boldsymbol{x}_i) - y_i)\left[\mathrm{diag}\{\sigma'(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})\}(E^{[k+1:L]}\mathbf{a})\right]_j \boldsymbol{x}_i^{[k-1]\mathsf{T}},$$

where we use $E^l = \boldsymbol{W}^{[l]\mathsf{T}} \mathrm{diag}\{\sigma'(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]})\}$, for $l \in \{2, 3, ..., L\}$, $E^{[q:p]} = E^q E^{q+1}...E^p$.

For a fixed step, we only consider the gradient w.r.t. $\dot{\boldsymbol{W}}_j^{[k]}$. Suppose $\sigma'(0) \neq 0$ and parameters are small. Denote $e_i := (f(\boldsymbol{\theta}, \boldsymbol{x}_i) - y_i)$. By Taylor expansion,

$$\mathcal{P}\boldsymbol{w} \overset{\text{leading order}}{\approx} \mathcal{Q}\boldsymbol{w} := -\frac{1}{n}(\mathrm{diag}\{\sigma'(\mathbf{0})\}(E^{[k+1:L]}\mathbf{a}))_j \sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}$$

$$+ \left(\frac{1}{n}(\mathrm{diag}\{\sigma'(\mathbf{0})\}(E^{[k+1:L]}\mathbf{a}))_j \sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]} \cdot \boldsymbol{u}\right)\boldsymbol{u} = 0,$$

where operator $\mathcal{Q}$ is the leading-order approximation of operator $\mathcal{P}$, and here $E^{[k+1:L]}$ is independent with i because $\mathrm{diag}\{\sigma'(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]})\} \approx \mathrm{diag}\{\sigma'(0)\}$. Since $\mathrm{diag}\{\sigma'(\mathbf{0})\} = \boldsymbol{I}$, and, WLOG, we assume $a \neq 0$, then

$$\mathcal{Q}\boldsymbol{w} = 0 \iff \sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]} = \left(\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]} \cdot \boldsymbol{u}\right)\boldsymbol{u}.$$

We have

$$\boldsymbol{u} = \frac{\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}}{\|\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}\|_2} \quad or \quad \boldsymbol{u} = -\frac{\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}}{\|\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}\|_2}.$$

This calculation shows that for layer k, the input weights for any hidden neuron j have the same two stable directions. Therefore, when parameters are sufficiently small, which implies that the orientation $\boldsymbol{u}$ would moves much more quickly than the amplitude r, all input weights towards converging to the same direction or the opposite direction, i.e., condensation on a line.

5.2 CASE 2: $m_l = 1$

By the definition of the multiplicity p, we have

$$\sigma'(\boldsymbol{w} \cdot \boldsymbol{x}_i) = \frac{\sigma^{(p)}(0)}{(p-1)!}(\boldsymbol{w} \cdot \boldsymbol{x}_i)^{p-1} + o((\boldsymbol{w} \cdot \boldsymbol{x}_i)^{p-1}).$$

where $(\cdot)^{p-1}$ and $\sigma^p(\cdot)$ operate on component here. Then up to the leading order in terms of the magnitude of $\boldsymbol{\theta}$, we have (see Appendix)

$$\mathcal{P}\boldsymbol{w} \overset{\text{leading order}}{\approx} \mathcal{Q}\boldsymbol{w} := -(\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}(\boldsymbol{w}^{\mathsf{T}}\boldsymbol{x}_i^{[k-1]})^{p-1})[\text{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})]_j$$

$$+((\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}(\boldsymbol{w}^{\mathsf{T}}\boldsymbol{x}_i^{[k-1]})^{p-1})[\text{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})]_j \cdot \boldsymbol{u})\boldsymbol{u}.$$

WLOG, we also assume $a \neq 0$. And by definition, $\boldsymbol{w} = r\boldsymbol{u}$, we have

$$\mathcal{Q}\boldsymbol{w} = 0 \Leftrightarrow \boldsymbol{u} = \frac{\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}(\boldsymbol{u}^{\mathsf{T}}\boldsymbol{x}_i^{[k-1]})^{p-1}}{\|\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}(\boldsymbol{u}^{\mathsf{T}}\boldsymbol{x}_i^{[k-1]})^{p-1}\|_2}$$

$$or \ \boldsymbol{u} = -\frac{\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}(\boldsymbol{u}^{\mathsf{T}}\boldsymbol{x}_i^{[k-1]})^{p-1}}{\|\frac{1}{n}\sum_{i=1}^{n} e_i \boldsymbol{x}_i^{[k-1]}(\boldsymbol{u}^{\mathsf{T}}\boldsymbol{x}_i^{[k-1]})^{p-1}\|_2}.$$

Since $d+1 = 2$, we denote $\boldsymbol{u} = (u_1, u_2)^{\mathsf{T}} \in \mathbb{R}^2$ and $\boldsymbol{x}_i^{[k-1]} = ((\boldsymbol{x}_i^{[k-1]})_1, (\boldsymbol{x}_i^{[k-1]})_2)^{\mathsf{T}} \in \mathbb{R}^2$, then,

$$\frac{\sum_{i=1}^{n}(u_1(\boldsymbol{x}_i^{[k-1]})_1 + u_2(\boldsymbol{x}_i^{[k-1]})_2)^{p-1} e_i(\boldsymbol{x}_i^{[k-1]})_1}{\sum_{i=1}^{n}(u_1(\boldsymbol{x}_i^{[k-1]})_1 + u_2(\boldsymbol{x}_i^{[k-1]})_2)^{p-1} e_i(\boldsymbol{x}_i^{[k-1]})_2} = \frac{u_1}{u_2} \triangleq \hat{u}.$$

We obtain the equation for $\hat{u}$,

$$\sum_{i=1}^{n}(\hat{u}(\boldsymbol{x}_i^{[k-1]})_1 + (\boldsymbol{x}_i^{[k-1]})_2)^{p-1} e_i(\boldsymbol{x}_i^{[k-1]})_1 = \hat{u}\sum_{i=1}^{n}(\hat{u}(\boldsymbol{x}_i^{[k-1]})_1 + (\boldsymbol{x}_i^{[k-1]})_2)^{p-1} e_i(\boldsymbol{x}_i^{[k-1]})_2.$$

Since it is an univariate p-th order equation, $\hat{u} = \frac{u_1}{u_2}$ has at most p complex roots. Because $\boldsymbol{u}$ is a unit vector, $\boldsymbol{u}$ at most has p pairs of values, in which each pair are opposite.

Taken together, our theoretical analysis is consistent with our experiments, that is, the maximal number of condensed orientations is twice the multiplicity of the activation function used when parameters are small. In addition, because our commonly used activation functions, such as $\tanh(x)$, $\text{sigmoid}(x)$, $\text{softplus}(x)$, etc., are all multiplicity one, the theoretical analysis sheds light on practical training.

6 DISCUSSION

In this work, we have shown that the characteristic of the activation function, i.e., multiplicity, is a key factor to understanding the complexity of NN output and the weight condensation at initial training. The condensation restricts the NN to be effectively low-capacity at the initial training stage, even for finite-width NNs. During the training, the NN increases its capacity to better fit the data, leading to a potential explanation for their good generalization in practical problems. This work also serves as a starting point for further studying the condensation for multiple-layer neural networks throughout the training process.

How small the initialization should be in order to see a clear condensation is studied in Luo et al. (2021) for two-layer ReLU NNs with infinite width. For general activation functions, the regime of the initialization for condensation depends on the NN width. A further study of the phase diagram for finite width NNs would be important.

For general multiplicity with high-dimensional input data, the theoretical analysis for the initial condensation is a very difficult problem, which is equivalent to count the number of the roots of a high-order high-dimensional polynomial with a special structure originated from NNs.

REFERENCES

Rishabh Agarwal, Nicholas Frosst, Xuezhou Zhang, Rich Caruana, and Geoffrey E Hinton. Neural additive models: Interpretable machine learning with neural nets. arXiv preprint arXiv:2004.13912, 2020.

Sanjeev Arora, Simon S. Du, Wei Hu, Zhiyuan Li, Ruslan Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada, pp. 8139–8148, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/dbc4d84bfcfe2284ba11beffb853a8c4-Abstract.html.

Devansh Arpit, Stanislaw Jastrzebski, Nicolas Ballas, David Krueger, Emmanuel Bengio, Maxinder S. Kanwal, Tegan Maharaj, Asja Fischer, Aaron C. Courville, Yoshua Bengio, and Simon Lacoste-Julien. A closer look at memorization in deep networks. In Doina Precup and Yee Whye Teh (eds.), Proceedings of the 34th International Conference on Machine Learning, ICML 2017, Sydney, NSW, Australia, 6-11 August 2017, volume 70 of Proceedings of Machine Learning Research, pp. 233–242. PMLR, 2017. URL http://proceedings.mlr.press/v70/arpit17a.html.

Peter L Bartlett and Shahar Mendelson. Rademacher and gaussian complexities: Risk bounds and structural results. Journal of Machine Learning Research, 3(Nov):463–482, 2002.

Simon Biland, Vinicius C Azevedo, Byungsoo Kim, and Barbara Solenthaler. Frequency-aware reconstruction of fluid simulations with generative networks. arXiv preprint arXiv:1912.08776, 2019.

Leo Breiman. Reflections after refereeing papers for nips. The Mathematics of Generalization, XX: 11–15, 1995.

Wei Cai and Zhi-Qin John Xu. Multi-scale deep neural networks for solving high dimensional pdes. arXiv preprint arXiv:1910.11710, 2019.

Wei Cai, Xiaoguang Li, and Lizuo Liu. A phase shift deep neural network for high frequency approximation and wave problems. SIAM Journal on Scientific Computing, 42(5):A3285–A3312, 2020.

Miguel Campo, Zhengxing Chen, Luke Kung, Kittipat Virochsiri, and Jianyu Wang. Band-limited soft actor critic model. arXiv preprint arXiv:2006.11431, 2020.

Prithvijit Chakrabarty and Subhransu Maji. The spectral bias of the deep image prior. arXiv preprint arXiv:1912.08905, 2019.

Lénaïc Chizat and Francis Bach. On the global convergence of gradient descent for over-parameterized models using optimal transport. In Proceedings of the 32nd International Conference on Neural Information Processing Systems, pp. 3040–3050, 2018.

Lenaic Chizat and Francis Bach. A note on lazy training in supervised differentiable programming. In 32nd Conf. Neural Information Processing Systems (NeurIPS 2018), 2019.

Weinan E, Chao Ma, and Lei Wu. A comparative analysis of optimization and generalization properties of two-layer neural network and random feature models under gradient descent dynamics. Science China Mathematics, pp. 1–24, 2020.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In Proceedings of the thirteenth international conference on artificial intelligence and statistics, pp. 249–256, 2010.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE conference on computer vision and pattern recognition, pp. 770–778, 2016.

Arthur Jacot, Clément Hongler, and Franck Gabriel. Neural tangent kernel: Convergence and generalization in neural networks. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett (eds.), Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada, pp. 8580–8589, 2018. URL https://proceedings.neurips.cc/paper/2018/hash/5a4be1fa34e62bb8a6ec6b91d2462f5a-Abstract.html.

Ameya D Jagtap, Kenji Kawaguchi, and George Em Karniadakis. Adaptive activation functions accelerate convergence in deep and physics-informed neural networks. Journal of Computational Physics, 404:109136, 2020.

Liming Jiang, Bo Dai, Wayne Wu, and Chen Change Loy. Focal frequency loss for generative models. arXiv preprint arXiv:2012.12821, 2020.

Pengzhan Jin, Lu Lu, Yifa Tang, and George Em Karniadakis. Quantifying the generalization error in deep learning in terms of data distribution and neural network smoothness. Neural Networks, 130:85–99, 2020.

Dimitris Kalimeris, Gal Kaplun, Preetum Nakkiran, Benjamin L. Edelman, Tristan Yang, Boaz Barak, and Haofeng Zhang. SGD on neural networks learns functions of increasing complexity. In Hanna M. Wallach, Hugo Larochelle, Alina Beygelzimer, Florence d'Alché-Buc, Emily B. Fox, and Roman Garnett (eds.), Advances in Neural Information Processing Systems 32: Annual Conference on Neural Information Processing Systems 2019, NeurIPS 2019, December 8-14, 2019, Vancouver, BC, Canada, pp. 3491–3501, 2019. URL https://proceedings.neurips.cc/paper/2019/hash/b432f34c5a997c8e7c806a895ecc5e25-Abstract.html.

Xi-An Li, Zhi-Qin John Xu, and Lei Zhang. A multi-scale dnn algorithm for nonlinear elliptic equations with multiple scales. Communications in Computational Physics, 28(5):1886–1906, 2020.

Ziqi Liu, Wei Cai, and Zhi-Qin John Xu. Multi-scale deep neural network (mscalednn) for solving poisson-boltzmann equation in complex domains. Communications in Computational Physics, 28(5):1970–2001, 2020.

Tao Luo, Zhi-Qin John Xu, Zheng Ma, and Yaoyu Zhang. Phase diagram for two-layer relu neural networks at infinite-width limit. Journal of Machine Learning Research, 22(71):1–47, 2021.

Chao Ma, Lei Wu, and E Weinan. The slow deterioration of the generalization error of the random feature model. In Mathematical and Scientific Machine Learning, pp. 373–389. PMLR, 2020.

Hartmut Maennel, Olivier Bousquet, and Sylvain Gelly. Gradient descent quantizes relu network features. arXiv preprint arXiv:1803.08367, 2018.

Song Mei, Theodor Misiakiewicz, and Andrea Montanari. Mean-field theory of two-layers neural networks: dimension-free bounds and kernel limit. In Alina Beygelzimer and Daniel Hsu (eds.), Conference on Learning Theory, COLT 2019, 25-28 June 2019, Phoenix, AZ, USA, volume 99 of Proceedings of Machine Learning Research, pp. 2388–2464. PMLR, 2019. URL http://proceedings.mlr.press/v99/mei19a.html.

Ben Mildenhall, Pratul P Srinivasan, Matthew Tancik, Jonathan T Barron, Ravi Ramamoorthi, and Ren Ng. Nerf: Representing scenes as neural radiance fields for view synthesis. In European Conference on Computer Vision, pp. 405–421. Springer, 2020.

Franco Pellegrini and Giulio Biroli. An analytic theory of shallow networks dynamics for hinge loss classification. Advances in Neural Information Processing Systems, 33, 2020.

Wei Peng, Weien Zhou, Jun Zhang, and Wen Yao. Accelerating physics-informed neural network training with prior dictionaries. arXiv preprint arXiv:2004.08151, 2020.

Nasim Rahaman, Devansh Arpit, Aristide Baratin, Felix Draxler, Min Lin, Fred A Hamprecht, Yoshua Bengio, and Aaron Courville. On the spectral bias of deep neural networks. International Conference on Machine Learning, 2019.

Grant M. Rotskoff and Eric Vanden-Eijnden. Parameters as interacting particles: long time convergence and asymptotic error scaling of neural networks. In Samy Bengio, Hanna M. Wallach, Hugo Larochelle, Kristen Grauman, Nicolò Cesa-Bianchi, and Roman Garnett (eds.), Advances in Neural Information Processing Systems 31: Annual Conference on Neural Information Processing Systems 2018, NeurIPS 2018, December 3-8, 2018, Montréal, Canada, pp. 7146–7155, 2018. URL https://proceedings.neurips.cc/paper/2018/hash/196f5641aa9dc87067da4ff90fd81e7b-Abstract.html.

Renu Sharma and Arun Ross. D-netpad: An explainable and interpretable iris presentation attack detector. In 2020 IEEE International Joint Conference on Biometrics (IJCB), pp. 1–10. IEEE, 2020.

Justin Sirignano and Konstantinos Spiliopoulos. Mean field analysis of neural networks: A central limit theorem. Stochastic Processes and their Applications, 130(3):1820–1852, 2020.

Matthew Tancik, Pratul P Srinivasan, Ben Mildenhall, Sara Fridovich-Keil, Nithin Raghavan, Utkarsh Singhal, Ravi Ramamoorthi, Jonathan T Barron, and Ren Ng. Fourier features let networks learn high frequency functions in low dimensional domains. arXiv preprint arXiv:2006.10739, 2020.

Bo Wang. Multi-scale deep neural network (mscalednn) methods for oscillatory stokes flows in complex domains. Communications in Computational Physics, 28(5):2139–2157, 2020.

Yue Xi, Wenjing Jia, Jiangbin Zheng, Xiaochen Fan, Yefan Xie, Jinchang Ren, and Xiangjian He. Drl-gan: Dual-stream representation learning gan for low-resolution image classification in uav applications. IEEE Journal of selected topics in applied earth observations and remote sensing, 2020.

Zhi-Qin J Xu, Yaoyu Zhang, and Yanyang Xiao. Training behavior of deep neural network in frequency domain. International Conference on Neural Information Processing, pp. 264–274, 2019.

Zhi-Qin John Xu and Hanxu Zhou. Deep frequency principle towards understanding why deeper learning is faster. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 35, 2021.

Zhi-Qin John Xu, Yaoyu Zhang, Tao Luo, Yanyang Xiao, and Zheng Ma. Frequency principle: Fourier analysis sheds light on deep neural networks. Communications in Computational Physics, 28(5):1746–1767, 2020.

Chiyuan Zhang, Samy Bengio, Moritz Hardt, Benjamin Recht, and Oriol Vinyals. Understanding deep learning requires rethinking generalization. In 5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings. OpenReview.net, 2017. URL https://openreview.net/forum?id=Sy8gdB9xx.

Yaoyu Zhang, Zhi-Qin John Xu, Tao Luo, and Zheng Ma. A type of generalization error induced by initialization in deep neural networks. In Mathematical and Scientific Machine Learning, pp. 144–164. PMLR, 2020.

Hu Zhu, Yiming Qiao, Guoxia Xu, Lizhen Deng, and Yu Yu-Feng. Dspnet: A lightweight dilated convolution neural networks for spectral deconvolution with self-paced learning. IEEE Transactions on Industrial Informatics, 2019.

A   APPENDIX

A.1   BASIC DEFINITIONS

In this study, we consider the neural network with l hidden layers,

$$\boldsymbol{x}^{[0]} = (\boldsymbol{x}, 1), \quad \boldsymbol{x}^{[1]} = (\sigma(\boldsymbol{W}^{[1]}\boldsymbol{x}^{[0]}), 1), \quad \boldsymbol{x}^{[l]} = (\sigma(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]}), 1), \text{ for } l \in \{2, 3, ..., L\}$$

$$f(\boldsymbol{\theta}, \boldsymbol{x}) = \frac{1}{\alpha}\mathbf{a}^{\mathsf{T}}\boldsymbol{x}^{[L]} \triangleq f_{\boldsymbol{\theta}}(\boldsymbol{x}),$$

(6)

where $\boldsymbol{W}^{[l]} = (\bar{\boldsymbol{W}}^{[l]}, \boldsymbol{b}^{[l]}) \in \mathbb{R}^{(m_l \times m_{l-1})}$, and m_l represents the dimension of the l-th hidden layer. The initialization of $\boldsymbol{W}^{[l]}_{k,k'}, l \in \{1, 2, 3, ..., L\}$ and $\mathbf{a}_k$ obey normal distribution $\boldsymbol{W}^{[l]}_{k,k'} \sim \mathcal{N}(0, \beta_l^2)$ for $l \in \{1, 2, 3, ..., L\}$ and $\mathbf{a}_k \sim \mathcal{N}(0, \beta_{L+1}^2)$.

The loss function is mean squared error given below,

$$R_s(\boldsymbol{\theta}) = \frac{1}{2n}\sum_{i=1}^{n}(f_{\boldsymbol{\theta}}(\boldsymbol{x}_i) - y_i)^2.$$

(7)

For simplification, we denote $f_{\boldsymbol{\theta}}(\boldsymbol{x})$ as f in following.

A.2   DERIVATIONS FOR CONCERNED QUANTITIES

A.2.1   NEURAL NETWORKS WITH THREE HIDDEN LAYERS

In order to better understand the gradient of the parameter matrix of the multi-layer neural network, we first consider the case of the three-layer neural network,

$$f_{\boldsymbol{\theta}}(\boldsymbol{x}) := \boldsymbol{a}^{\mathsf{T}}\sigma(\boldsymbol{W}^{[2]}\sigma(\boldsymbol{W}^{[1]}\boldsymbol{x})),$$

(8)

with the mean squared error as the loss function,

$$R_s(\boldsymbol{\theta}) = \frac{1}{2n}\sum_{i=1}^{n}(f_{\boldsymbol{\theta}}(\boldsymbol{x}_i) - y_i)^2.$$

(9)

We calculate $\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[2]}}$ and $\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[1]}}$ respectively, using differential form,

$$\mathrm{d}f = \mathrm{tr}((\frac{\partial f}{\partial \boldsymbol{x}})^{\mathsf{T}}\mathrm{d}f).$$

(10)

We consider $\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[2]}}$ first,

$$\begin{aligned}
\mathrm{d}f &= \mathrm{tr}\{\mathrm{d}(\boldsymbol{a}^{\mathsf{T}}\sigma(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))\} \\
&= \mathrm{tr}\{\boldsymbol{a}^{\mathsf{T}}\mathrm{d}(\sigma(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))\} \\
&= \mathrm{tr}\{\boldsymbol{a}^{\mathsf{T}}\sigma'(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}) \odot \mathrm{d}\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}\} \\
&= \mathrm{tr}\{(\boldsymbol{a} \odot \sigma'(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]})^{\mathsf{T}}\mathrm{d}\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}\} \\
&= \mathrm{tr}\{\boldsymbol{x}^{[1]}(\boldsymbol{a} \odot \sigma'(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]})^{\mathsf{T}}\mathrm{d}\boldsymbol{W}^{[2]}\} \\
&= \mathrm{tr}\{((\boldsymbol{a} \odot \sigma'(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))\boldsymbol{x}^{[1]\mathsf{T}})^{\mathsf{T}}\mathrm{d}\boldsymbol{W}^{[2]}\},
\end{aligned}$$

(11)

where $\odot$ is Hadamard Product, and it is the multiplication of matrix elements of the same position. Hence,

$$\begin{aligned}
\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[2]}} &= (\boldsymbol{a} \odot \sigma'(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))\boldsymbol{x}^{[1]\mathsf{T}} \\
&= \mathrm{diag}\{\sigma'(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]})\}\boldsymbol{a}\boldsymbol{x}^{[1]\mathsf{T}}.
\end{aligned}$$

(12)

Then, we consider $\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[1]}}$,

$$
\begin{aligned}
\mathrm{d}f &= \mathrm{tr}\{(\boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))^{\intercal}\boldsymbol{W}^{[2]}\mathrm{d}\sigma(\boldsymbol{W}^{[1]}\boldsymbol{x})\} \\
&= \mathrm{tr}\{(\boldsymbol{W}^{[2]\intercal}(\boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]})))^{\intercal}\sigma^{'}(\boldsymbol{W}^{[1]}\boldsymbol{x})\odot\mathrm{d}(\boldsymbol{W}^{[1]}\boldsymbol{x})\} \\
&= \mathrm{tr}\{((\boldsymbol{W}^{[2]\intercal}(\boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))\odot\sigma^{'}(\boldsymbol{W}^{[1]}\boldsymbol{x}))^{\intercal}\mathrm{d}(\boldsymbol{W}^{[1]}\boldsymbol{x})\} \\
&= \mathrm{tr}\{[(((\boldsymbol{W}^{[2]\intercal}(\boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]}))\odot\sigma^{'}(\boldsymbol{W}^{[1]}\boldsymbol{x}))\boldsymbol{x}^{\intercal}]^{\intercal}\mathrm{d}(\boldsymbol{W}^{[1]})\}.
\end{aligned}
\tag{13}
$$

Hence, we have,

$$
\begin{aligned}
\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[1]}} &= ((\boldsymbol{W}^{[2]\intercal}(\boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]})))\odot\sigma^{'}(\boldsymbol{W}^{[1]}\boldsymbol{x}))\boldsymbol{x}^{\intercal} \\
&= \mathrm{diag}\{\sigma^{'}(\boldsymbol{W}^{[1]}\boldsymbol{x})\}\boldsymbol{W}^{[2]\intercal}\mathrm{diag}\{\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}^{[1]})\}\boldsymbol{a}\boldsymbol{x}^{\intercal}.
\end{aligned}
\tag{14}
$$

Through the chain rule, we can get the evolution equation of $\boldsymbol{W}^{[1]}$ and $\boldsymbol{W}^{[2]}$,

$$
\begin{aligned}
\frac{\mathrm{d}\boldsymbol{W}^{[1]}}{\mathrm{d}t} &= -\frac{\mathrm{d}R_s(\boldsymbol{\theta})}{\mathrm{d}\boldsymbol{W}^{[1]}} \\
&= -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i)\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[1]}} \\
&= -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i)\mathrm{diag}\{\sigma^{'}(\boldsymbol{W}^{[1]}\boldsymbol{x}_i)\}\boldsymbol{W}^{[2]\intercal}\mathrm{diag}\{\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}_i^{[1]})\}\boldsymbol{a}\boldsymbol{x}_i^{\intercal},
\end{aligned}
\tag{15}
$$

and

$$
\begin{aligned}
\frac{\mathrm{d}\boldsymbol{W}^{[2]}}{\mathrm{d}t} &= -\frac{\mathrm{d}R_s(\boldsymbol{\theta})}{\mathrm{d}\boldsymbol{W}^{[2]}} \\
&= -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i)\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[1]}} \\
&= -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i)\mathrm{diag}\{\sigma^{'}(\boldsymbol{W}^{[2]}\boldsymbol{x}_i^{[1]})\}\boldsymbol{a}\boldsymbol{x}_i^{[1]\intercal}.
\end{aligned}
\tag{16}
$$

A.2.2 L HIDDEN LAYERS CONDITION

And, we consider the neural network with L hidden layers,

$$
\begin{aligned}
\mathrm{d}f &= \mathrm{tr}\{\mathrm{d}\boldsymbol{a}^{\intercal}\mathrm{d}\sigma(\boldsymbol{W}^{[L]}\boldsymbol{x}^{[L-1]})\} \\
&= \mathrm{tr}\{(\boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[L]}\boldsymbol{x}^{[L-1]}))^{\intercal}\mathrm{d}\boldsymbol{W}^{[L]}\sigma(\boldsymbol{W}^{[L-1]}\boldsymbol{x}^{[L-2]})\} \\
&= \mathrm{tr}\{(\boldsymbol{W}^{[L]\intercal}\Lambda_L)^{\intercal}\sigma^{'}(\boldsymbol{W}^{[L-1]}\boldsymbol{x}^{[L-2]})\odot\mathrm{d}\boldsymbol{W}^{[L-1]}\sigma(\boldsymbol{W}^{[L-2]}\boldsymbol{x}^{[L-3]})\} \\
&= \mathrm{tr}\{((\boldsymbol{W}^{[L]\intercal}\Lambda_L)\odot\sigma^{'}(\boldsymbol{W}^{[L-1]}\boldsymbol{x}^{[L-2]}))^{\intercal}\boldsymbol{W}^{[L-1]}\mathrm{d}\sigma(\boldsymbol{W}^{[L-2]}\boldsymbol{x}^{[L-3]})\} \\
&= (\boldsymbol{W}^{[L-1]\intercal}\Lambda_{L-1})^{\intercal}\mathrm{d}\sigma(\boldsymbol{W}^{[L-2]}\boldsymbol{x}^{[L-3]}) \\
&= \ldots \\
&= \mathrm{tr}\{\Lambda_k^{\intercal}\mathrm{d}\boldsymbol{W}^{[k]}\boldsymbol{x}^{[k-1]}\} \\
&= \mathrm{tr}\{(\Lambda_k\boldsymbol{x}^{[k-1]\intercal})^{\intercal}\mathrm{d}\boldsymbol{W}^{[k]}\},
\end{aligned}
\tag{17}
$$

where $\Lambda_l \triangleq (\boldsymbol{W}^{[l+1]\intercal}\Lambda_{l+1})\odot\sigma^{'}(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]})$ for $l = k, k+1\ldots L-1$ and $\Lambda_L \triangleq \boldsymbol{a}\odot\sigma^{'}(\boldsymbol{W}^{[L]}\boldsymbol{x}^{[L-1]})$.

Hence, we get,

$$
\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[k]}} = \Lambda_k\boldsymbol{x}^{[k-1]\intercal}.
\tag{18}
$$

Through the chain rule, we can get the evolution equation of $\boldsymbol{W}^{[k]}$,

$$\begin{aligned}
\frac{\mathrm{d}\boldsymbol{W}^{[k]}}{\mathrm{d}t} &= -\frac{\mathrm{d}R_s(\boldsymbol{\theta})}{\mathrm{d}\boldsymbol{W}^{[k]}} \\
&= -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i)\frac{\mathrm{d}f}{\mathrm{d}\boldsymbol{W}^{[k]}} \\
&= -\frac{1}{n}\sum_{i=1}^{n}(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i)\Lambda_k \boldsymbol{x}_i^{[k-1]^{\mathsf{T}}}.
\end{aligned} \tag{19}$$

Through $\boldsymbol{a}\odot\sigma'(\boldsymbol{W}\boldsymbol{x})=\mathrm{diag}\{\sigma^{'}(\boldsymbol{W}\boldsymbol{x})\}\boldsymbol{a}$,

Finally, the dynamic system can be obtained:

$$\begin{aligned}
\dot{\boldsymbol{a}} = \frac{\mathrm{d}\mathbf{a}}{\mathrm{d}t} &= -\frac{1}{n}\sum_{i=1}^{n}\boldsymbol{x}_i^{[L]}\left(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i\right), \\
\dot{\boldsymbol{W}}^{[L]} = \frac{\mathrm{d}\boldsymbol{W}^{[L]}}{\mathrm{d}t} &= -\frac{1}{n}\sum_{i=1}^{n}\mathrm{diag}\{\sigma'(\boldsymbol{W}^{[L]}\boldsymbol{x}_i^{[L-1]})\}\mathbf{a}\boldsymbol{x}_i^{[L-1]^{\mathsf{T}}}\left(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i\right), \\
\dot{\boldsymbol{W}}^{[k]} = \frac{\mathrm{d}\boldsymbol{W}^{[k]}}{\mathrm{d}t} &= -\frac{1}{n}\sum_{i=1}^{n}\mathrm{diag}\{\sigma'(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})\}E^{[k+1:L]}\mathbf{a}\boldsymbol{x}_i^{[k-1]^{\mathsf{T}}}\left(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i\right)\ \forall i\in[1:L-1],
\end{aligned} \tag{20}$$

where we use $E^l(\boldsymbol{x})=\boldsymbol{W}^{[l]^{\mathsf{T}}}\mathrm{diag}\{\sigma'(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]})\}$. And $E^{[q:p]}=E^qE^{q+1}...E^p$.

Let $r_{k,j}=\|\boldsymbol{W}_j^{[k]}\|_2$. We have

$$\frac{\mathrm{d}}{\mathrm{d}t}|r_{k,j}|^2 = \frac{\mathrm{d}}{\mathrm{d}t}\|\boldsymbol{W}_j^{[k]}\|^2. \tag{21}$$

Then we obtain

$$\dot{r}_{k,j}r_{k,j} = \dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{W}_j^{[k]}. \tag{22}$$

Finally, we get

$$\begin{aligned}
\dot{r}_{k,j} = \frac{\mathrm{d}r_{k,j}}{\mathrm{d}t} &= \dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{W}_j^{[k]}/r_{k,j} \\
&= \dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{u}_{k,j},
\end{aligned} \tag{23}$$

where $\boldsymbol{u}_{k,j}=\frac{\boldsymbol{W}_j^{[k]}}{r_{k,j}}$ is a unit vector. Then we have,

$$\begin{aligned}
\dot{\boldsymbol{u}}_{k,j} = \frac{\mathrm{d}\boldsymbol{u}_{k,j}}{\mathrm{d}t} = \frac{\mathrm{d}}{\mathrm{d}t}\left(\frac{\boldsymbol{W}_j^{[k]}}{r_{k,j}}\right) \\
&= \frac{\dot{\boldsymbol{W}}_j^{[k]}r_{k,j}-\boldsymbol{W}_j^{[k]}\dot{r}_{k,j}}{r_{k,j}^2} \\
&= \frac{\dot{\boldsymbol{W}}_j^{[k]}r_{k,j}-\boldsymbol{W}_j^{[k]}(\dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{u}_{k,j})}{r_{k,j}^2} \\
&= \frac{\dot{\boldsymbol{W}}_j^{[k]}-\boldsymbol{u}_{k,j}(\dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{u}_{k,j})}{r_{k,j}}.
\end{aligned} \tag{24}$$

To conclude, the quantities we concern are summarized as follows,

$$\begin{cases} \dot{\boldsymbol{a}} = -\frac{1}{n}\sum_{i=1}^{n}\boldsymbol{x}_i^{[L]}\left(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i\right) & (25) \\[2mm] \dot{\boldsymbol{W}}^{[L]} = -\frac{1}{n}\sum_{i=1}^{n}\operatorname{diag}\{\sigma'(\boldsymbol{W}^{[L]}\boldsymbol{x}_i^{[L-1]})\}\mathbf{a}\boldsymbol{x}_i^{[L-1]\mathsf{T}}\left(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i\right), & (26) \\[2mm] \dot{\boldsymbol{W}}^{[k]} = -\frac{1}{n}\sum_{i=1}^{n}\operatorname{diag}\{\sigma'(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})\}E^{[k+1:L]}\mathbf{a}\boldsymbol{x}_i^{[k-1]\mathsf{T}}\left(f(\boldsymbol{\theta},\boldsymbol{x}_i)-y_i\right)\ \forall i\in[1:L-1] & (27) \\[2mm] \dot{r}_{k,j} = \dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{u}_{k,j} & (28) \\[2mm] \dot{\boldsymbol{u}}_{k,j} = \dfrac{\dot{\boldsymbol{W}}_j^{[k]}-\boldsymbol{u}_{k,j}(\dot{\boldsymbol{W}}_j^{[k]}\cdot\boldsymbol{u}_{k,j})}{r_{k,j}}, & (29) \end{cases}$$

where we use $E^l(\boldsymbol{x}) = \boldsymbol{W}^{[l]\mathsf{T}}\operatorname{diag}\{\sigma'(\boldsymbol{W}^{[l]}\boldsymbol{x}^{[l-1]})\}$. And $E^{[q:p]} = E^q E^{q+1}...E^p$.

A.2.3 PROVE FOR $\mathcal{P}w$ IN 5.2

We calculate $\mathcal{P}w \overset{\text{leading order}}{\approx} \mathcal{Q}w$ as following,

$$\begin{aligned}
\mathcal{P}w \approx \mathcal{Q}w := & -\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{\sigma'(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})\}(E^{[k+1:L]}\mathbf{a})]_j \\
& + (\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{\sigma'(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})\}(E^{[k+1:L]}\mathbf{a})]_j \cdot \boldsymbol{u})\boldsymbol{u} \\
= & -\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\odot(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1}\}(E^{[k+1:L]}\mathbf{a})]_j \\
& + (\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\odot(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1}\}(E^{[k+1:L]}\mathbf{a})]_j \cdot \boldsymbol{u})\boldsymbol{u} \\
= & -\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1}\}\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})]_j \\
& + (\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1}\}\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})]_j \cdot \boldsymbol{u})\boldsymbol{u} \\
= & -\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1}\}]_j\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a}) \\
& + (\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}[\operatorname{diag}\{(\boldsymbol{W}^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1}\}]_j\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})\cdot\boldsymbol{u})\boldsymbol{u} \\
= & -(\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}(\boldsymbol{W}_j^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1})[\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})]_j \\
& + ((\frac{1}{n}\sum_{i=1}^{n}e_i\boldsymbol{x}_i^{[k-1]}(\boldsymbol{W}_j^{[k]}\boldsymbol{x}_i^{[k-1]})^{p-1})[\operatorname{diag}\{\frac{\sigma^{(p)}(\mathbf{0})}{(p-1)!}\}(E^{[k+1:L]}\mathbf{a})]_j \cdot \boldsymbol{u})\boldsymbol{u},
\end{aligned}$$

$$(30)$$

where $(\cdot)^{p-1}$ and $\sigma^p(\cdot)$ operate on component here.

A.3 MULTILAYER EXPERIMENTAL

The condensation of the six layer without residual connections is shown in 7, whose activation functions for hidden layer 1 to hidden layer 5 are $x^2 \tanh(x)$, $x \tanh(x)$, $\mathrm{sigmoid}(x)$, $\tanh(x)$ and $\mathrm{softplus}(x)$, respectively.

The condensation of the three layer without residual connections is shown in 8, whose activation functions are same for each layer indicated by the corresponding sub-captions.

The condensation of the five layer without residual connections is shown in 9, whose activation functions are same for each layer indicated by the corresponding sub-captions.

The condensation of the five layer with residual connections is shown in 10, whose activation functions are same for each layer indicated by the corresponding sub-captions.

(a) layer 1   (b) layer 2   (c) layer 3   (d) layer 4   (e) layer 5

Figure 7: Condensation of six-layer NNs without residual connections. The activation functions for hidden layer 1 to hidden layer 5 are $x^2 \tanh(x)$, $x \tanh(x)$, $\mathrm{sigmoid}(x)$, $\tanh(x)$ and $\mathrm{softplus}(x)$, respectively.The numbers of steps selected in the sub-pictures are epoch 6800, epoch 6800, epoch 6800, epoch 6800 and epoch 6300, respectively, while the NN is only trained once. The color indicates $D(u, v)$ of two hidden neurons' input weights, whose indexes are indicated by the abscissa and the ordinate, respectively. The training data is 80 points sampled from a 3-dimensional function $\sum_{k=1}^{3} 4 \sin(12x_k + 1)$, where each x_k is uniformly sampled from $[-4, 2]$. $n = 80$, $d = 3$, $m = 18$, $d_{out} = 1$, $var = 0.008^2$, $lr = 5 \times 10^{-5}$.

(a) $\tanh(x)$ (b) $x \tanh(x)$ (c) $x^2 \tanh(x)$ (d) ReLU(x) (e) sigmoid(x) (f) softplus(x)

(g) $\tanh(x)$ (h) $x \tanh(x)$ (i) $x^2 \tanh(x)$ (j) ReLU(x) (k) sigmoid(x) (l) softplus(x)

Figure 8: Three-layer NN at epoch 700. (a-f) are for the input weights of the first hidden layer and (g-l) are for the input weights of the second hidden layer. The color indicates $D(u, v)$ of two hidden neurons' input weights, whose indexes are indicated by the abscissa and the ordinate, respectively. The training data is 80 points sampled from a 5-dimensional function $\sum_{k=1}^{5} 3 \sin(8x_k + 1)$, where each x_k is uniformly sampled from $[-4, 2]$. $n = 80$, $d = 5$, $m = 50$, $d_{out} = 1$, $var = 0.005^2$. $lr = 10^{-4}, 2 \times 10^{-5}, 1.4 \times 10^{-5}$ for (a-d), (e) and (f), respectively. For (d) and (j), we discard hidden neurons, whose L_2-norm of its input weight is smaller than 0.1.

Figure 9: Five-layer NN. The first to fourth columns of each row are for the input weights of neurons from the first to the fourth hidden layers, respectively. The color indicates $D(u, v)$ of two hidden neurons' input weights, whose indexes are indicated by the abscissa and the ordinate, respectively. The training data is 80 points sampled from a 5-dimensional function $\sum_{k=1}^{3} 3\sin(10x_k + 1)$, where each x_k is uniformly sampled from $[-4, 2]$. $n = 80$, $d = 5$, $m = 18$, $d_{out} = 1$, $var = 0.008^2$. $lr = 1.5 \times 10^{-5}$, 1.5×10^{-5}, 1.5×10^{-5}, 1.5×10^{-5}, 1.5×10^{-6} and epoch is 10000, 10000, 26000, 10000, 20000 for $tanh(x)$, $xtanh(x)$, $x^2tanh(x)$, $sigmoid(x)$, $softplus(x)$, respectively.

Figure 10: Five-layer NN. The first to fourth columns of each row are for the input weights of neurons from the first to the fourth hidden layers, respectively. The color indicates $D(u, v)$ of two hidden neurons' input weights, whose indexes are indicated by the abscissa and the ordinate, respectively. The training data is 80 points sampled from a 5-dimensional function $\sum_{k=1}^{3} 3\sin(10x_k + 1)$, where each x_k is uniformly sampled from $[-4, 2]$. $n = 80, d = 5, m = 18, d_{out} = 1, var = 0.008^2$. $lr = 1\times10^{-4}, 1\times10^{-4}, 1\times10^{-4}, 5\times10^{-5}, 5\times10^{-5}$ and epoch is $400, 400, 400, 3000, 360, 400$ for $tanh(x), xtanh(x), x^2tanh(x), x^2tanh(x), sigmoid(x), softplus(x)$, respectively.