WHAT WOULD THE EXPERT $do(\cdot)$?: CAUSAL IMITATION LEARNING

ABSTRACT

We develop algorithms for imitation learning from policy data that was corrupted by unobserved confounders. Sources of such confounding include (a) persistent perturbations to actions or (b) the expert responding to a part of the state that the learner does not have access to. When a confounder affects multiple timesteps of recorded data, it can manifest as spurious correlations between states and actions that a learner might latch on to, leading to poor policy performance. By utilizing the effect of past states on current states, we are able to break up these spurious correlations, an application of the econometric technique of instrumental variable regression. This insight leads to two novel algorithms, one of a generative-modeling flavor (`DoubIL`) that can utilize access to a simulator and one of a game-theoretic flavor (`ResiduIL`) that can be run offline. Both approaches are able to find policies that match the result of a query to an unconfounded expert. We find both algorithms compare favorably to non-causal approaches on simulated control problems.

1 INTRODUCTION

Much of the theory of imitation learning (IL) indicates that with enough demonstrations, we should be able to accurately recover the expert's policy. When we apply IL algorithms in practice however, we sometimes see them produce manifestly incorrect estimates of the expert's policy (Muller et al., 2006; Codevilla et al., 2019; de Haan et al., 2019; Bansal et al., 2018; Kuefler et al., 2017). One possible reason for this phenomenon is that empirically, we only have access to *noisy* recordings of what the expert did. This critical detail has been thus far neglected by most prior theoretical work in imitation learning. We focus in this paper on how best to learn from two kinds of noisy data:

- *Exogenous noise*: When we observe expert actions corrupted by a persistent noise (e.g. a faulty joystick that persistently perturbs actions before they are executed in the game).

- *Endogenous noise*: When we do not observe the full state an expert used to pick an action (e.g. the learner not knowing there's an enemy behind a door).

The net effect of either kind of persistent noise (more formally, an *unobserved confounder*) is to introduce temporal correlations in the recorded actions that do not have their true cause in the recorded state. For example, consider recordings of an expert driver slowing down at a stop sign. If all we present the learner with as state input is whether the expert was slowing down at the last timestep, they will likely learn to simply repeat the expert's past action. Thus, once the car begins to slow down, it continues to slow down, *regardless of whether there is a stop sign present*. At a more abstract level, these sorts of *inertia problems* can result from temporal correlations between pairs of actions (e.g. the effect of the stop sign) being reflected in the state (e.g. the past action variable), leading to spurious correlations between state and action that the learner might unfortunately latch onto (e.g. repeating the past action).

What should we hope to learn then in these confounded settings? Given we do not have access to the unobserved confounder, a reasonable choice is to ensure that we match the behavior of an expert that has access to the same information we do. That is, if we could *query* the expert for an action with only the information we have available, we should strive to produce an action that matches this queried action. While applying an interactive imitation learning algorithm (Ross et al., 2011)

Figure 1: We focus in imitation learning in the presence of temporally correlated perturbations (exogenous noise, *(a)*) or not having access to the full state (endogenous noise, *(b)*). We formalize both in a graphical model *(c)* that allows us to leverage a technique known as *instrumental variable regression* to find a policy that isn't corrupted by spurious correlations introduced by the confounder.

would allow us to collect a dataset uncorrupted by confounding, a queryable expert is not a realistic assumption for many domains. We therefore focus on approaches for the off-policy setting. We base our algorithms on a technique from econometrics for dealing with confounding in recorded data known an *instrumental variable regression* (IVR) (Angrist et al., 1996). The high-level idea of IVR is to leverage an *instrument*, a source of random variation independent of the confounder, to deconfound inputs to a learning procedure. In dynamical systems, history may act as this source of variation, as it is unaffected by future confounding (Hefny et al., 2015). Our key insight is that *we can leverage the influence of the past on the present to break the spurious correlation between states and actions caused by an unobserved confounder*.

Our work provides the following contributions:

1. We formalize confounding in imitation learning. We provide a structural causal model that captures inertia affects that result from temporally correlated exogenous or endogenous noise. We also derive a test to detect whether this sort of confounding is present in a dataset.

2. We present a unified derivation of modern instrumental variable regression techniques. We show how two recent extensions of the classical IVR technique share a previously undiscovered structure. We also extend the theoretical analysis of previous work by deriving accuracy bounds.

3. We provide two novel algorithms to deal with confounding in imitation learning. We derive two novel IVR-based algorithms:

- `DoubIL` is a generative modeling approach that and can utilize access to a simulator for reduced sample complexity.
- `ResiduIL` is a simulator-free, game-theoretic approach.

We derive performance bounds for policies produced by these algorithms under exogenous noise. Finally, we empirically investigate the effect of the persistence of the confounder on our bound.

2 RELATED WORK

Imitation Learning. Broadly speaking, imitation learning approaches can be grouped into three classes: offline, online, and interactive. Our work is most similar to offline imitation learning algorithms (e.g. Behavioral Cloning (Pomerleau, 1989), ValueDice (Kostrikov et al., 2019), AdVIL (Swamy et al., 2021)) that operate purely on collected data. Unlike previous work however, we consider the effect of unobserved confounding. Our work shares the goal of interactive imitation learning algorithms (e.g. DAgger (Ross et al., 2011), AggreVaTe (Ross & Bagnell, 2014)), in that we seek to match the output of a query to the expert. However, we focus on matching the output of a query on recorded data, rather than on *learner* rollouts, as is standard for interactive approaches. This is because the confounder decouples the actions recorded in the data and queried actions. Zhang et al. (2020) consider imitation learning through the lens of causal inference but focus on the one-step setting, while we consider multiple timesteps. In contrast to imitation learning methods that seeks to match moments of the expert's behavior (Swamy et al., 2021), we focus only on matching average expert actions. We leave matching arbitrary moments to future work.

PROBLEM	CORRELATED STATE	ACTION	CONFOUNDER
Gridlock	Distance to intersection	Crossing	Cars on other side of intersection (*endog.*)
Stationary	Previously Braking	Braking	Traffic light (*endog.*)
Faulty Brakes	Speed	Braking	Brakes not responding to presses (*exog.*)

Table 1: Concrete examples of confounding from the driving domain. The stationary problem was observed empirically by Codevilla et al. (2019).

Inertia Effects in Imitation Learning. Several authors have empirically observed a latching effect in policies trained via imitation learning: (Muller et al., 2006; Codevilla et al., 2019; de Haan et al., 2019; Bansal et al., 2018; Kuefler et al., 2017), where learned policies tend to inappropriately repeat the same action. We seek to provide a plausible explanation and correction for the phenomenon reported in these works, and list several examples in Table 1. We note that when attempting to explain inertia effects, de Haan et al. (2019) propose causal confounding as the root cause of the error. However, as previously pointed out by Spencer et al. (2021), there is no actual confound in the theoretical or empirical examples in the work of de Haan et al. (2019). This is because the learner observes all of the variables the expert was using to make decisions, eliminating the possibility of an unobserved causal confounder. Instead, Spencer et al. (2021) connect the observed phenomenon to covariate shift, a well-explored topic in the imitation learning literature (Ross et al., 2011). Intuitively, because the learner observes states from *expert rollouts* during training but is tested on states from its *own rollouts*, this distribution shift can lead to spurious correlations being sufficient for good train-time error but not for strong test-time performance. We focus here on a setting with actual unobserved confounders that can explain "inertia"-like effects and the related poor test-time performance that isn't solvable by simply collecting a larger set of demonstrations.

Instrumental Variable Regression. The classical approach to instrumental variable regression (Wright, 1928) is a two-stage least squares procedure (e.g. in Angrist et al. (1996)'s textbook). We focus on the more general nonlinear setting and instead base our approaches on the more recent DEEPIV (Hartford et al., 2017) and AGMM (Dikkala et al., 2020). We present extensions to the work in these papers, including a unified derivation of both methods and error analysis for DEEPIV.

3 A BRIEF REVIEW OF INSTRUMENTS IN CAUSAL MODELING

We begin by discussing the concept of an instrument before deriving our algorithmic approaches in a simplified, non-sequential setting. Let X, Y, and Z be random variables on (potentially infinite) sample spaces $\mathcal{X}$, $\mathcal{Y}$, and $\mathcal{Z}$. Assume that X, Y, and Z have the causal, rather than statistical, dependency structure in Fig. 2. Given a dataset of (x, y, z) tuples, we are interested in determining the causal relationship between X and Y, $\mathbb{E}[Y|do(x)]$, where $do(\cdot)$ is the interventional operator of Pearl et al. (2016). Intuitively, $\mathbb{E}[Y|do(x)]$ is the expected value of Y when we *intervene* and set $X = x$, rather than observe such an X. In the SCM to the right, $h(x) = \mathbb{E}[Y|do(x)]$. Because of the presence of an unobserved confounder, U, that affects both X and Y, standard regression (e.g. Ordinary Least Squares or OLS) generically produces inconsistent estimates. Coarsely, this can occur because OLS will over-estimate the influence of the parts of X that are influenced by the confounder. If we only have observational data and are unable to perform randomized control trials, a canonical technique to recover h is IVR (Winship & Morgan, 1999). Formally, an *instrument* Z must satisfy three structural conditions:

Figure 2: The structural causal model (SCM) we consider. We are interested in finding h, the causal relationship from X to Y, even though there is an unobserved confounder, U. To do so, we leverage the effect of Z, which provides independent randomness from U.

1. *Unconfounded Instrument*: $Z \perp\!\!\!\perp U$ – i.e. independent randomization from confounder.

2. *Exclusion*: $Z \perp\!\!\!\perp Y|X, U$ – i.e. no extraneous paths.

3. *Relevance*: $Z \not\perp\!\!\!\perp X$ – i.e. conditioning has an effect.

Z satisifes these three conditions in the SCM of Fig. 2. [1] Without loss of generality, we assume that $\mathbb{E}[U] = 0$. This allows us to concisely derive a set of *conditional moment restrictions* (CMR):

$$0 = \mathbb{E}[U] = \mathbb{E}[U|z] = \mathbb{E}[Y - h(X)|z] \tag{1}$$

$$\Rightarrow \forall z \in \mathcal{Z}, \; \mathbb{E}[Y|z] = \mathbb{E}[h(X)|z]. \tag{2}$$

In words, these constraints are saying that a necessary condition for recovery of $h(x)$ is that for all values of the instrument, the actual and predicted expected values of $Y|Z$ are equal.

How can we find an $\hat{h}$ that satisifes the CMR? Let us first consider the setting with linear relationships between all variables. Then, one can recover $h(x) = \beta x$ with $\beta = \mathbb{E}[ZY]/\mathbb{E}[ZX]$. This is equivalent to the Two-Stage Ordinary Least Squares (2SLS) procedure, in which one first regresses from Z to X and then regresses from the predicted $\hat{X}$ to Y, returning the latter coefficients. Intuitively, the first stage of this procedure is aggregating Xs based on Z so that the particular instantiation of U that was correlating X and Y has its effect "washed out" in the $\hat{X}$s.

We now turn our attention to the general, nonlinear problem, which can still be formulated in terms of the CMR. We assume that noise U enters additively to Y,[2] and write out the following equations:

$$X = g(Z, U, V), \quad Y = h(X) + U. \tag{3}$$

We now derive an appropriate loss function for finding an $\hat{h}$ that approximately satisfies the CMR. If we only have finite samples and can therefore only estimate conditional expectations up to some tolerance, it is natural to relax the CMR to

$$\begin{aligned} \min_{\hat{h} \in \mathcal{H}, \boldsymbol{\delta}} \quad & J(\boldsymbol{\delta}) \\ \text{s.t.} \quad & |\mathbb{E}[Y - \hat{h}(X)|z]| \leq \delta_z \quad \forall z \in \mathcal{Z}, \end{aligned} \tag{4}$$

where the δ_z are slack variables and J is some convex function of $\boldsymbol{\delta}$ that discourages slacks from getting overly large. We proceed by setting $J(\boldsymbol{\delta}) = \frac{1}{2}\mathbb{E}_z[\delta_z^2]$ for easy computation of a closed-form expression for $\boldsymbol{\delta}$. Then, the Lagrangian (with the natural $P(z)$-weighted inner product that captures how often each we expect each z to occur) is

$$L(\hat{h}, \boldsymbol{\delta}, \boldsymbol{\lambda}) = \sum_{z \in \mathcal{Z}} P(z)\lambda_z(\mathbb{E}[Y - \hat{h}(X)|z] - \delta_z) + P(z)\frac{1}{2}\delta_z^2, \tag{5}$$

where $\boldsymbol{\lambda}$ is the vector of Lagrange multipliers. By the stationarity component of the KKT conditions,

$$\nabla_{\delta_z} L(\hat{h}, \boldsymbol{\delta}, \boldsymbol{\lambda}) = -P(z)\lambda_z + P(z)\delta_z = 0, \tag{6}$$

implying that $\delta_z = \lambda_z$. Plugging this back into the Lagrangian, we can simplify our function to

$$L(\hat{h}, \boldsymbol{\lambda}) = \sum_{z \in \mathcal{Z}} P(z)\lambda_z\mathbb{E}[Y - \hat{h}(X)|z] - P(z)\frac{1}{2}\lambda_z^2. \tag{7}$$

We refer to (7) as the *Regularized Lagrangian* or ReLa for short. Now, solving for the optimal Lagrange multipliers via stationarity, we arrive at

$$\nabla_{\lambda_z} L(\hat{h}, \boldsymbol{\lambda}) = P(z)\mathbb{E}[Y - \hat{h}(X)|z] - P(z)\lambda_z = 0, \tag{8}$$

which implies the optimal λ_z is equal to $\mathbb{E}[Y - \hat{h}(X)|z]$. Plugging this back into (7) recovers the loss function,

$$L(\hat{h}) = \sum_{z \in \mathcal{Z}} P(z)\mathbb{E}[Y - \hat{h}(X)|z]^2 = \text{PRMSE}^2(\hat{h}). \tag{9}$$

This expression is the square of the *Projected Root Mean Squared Error* (PRMSE) of Chen & Pouzo (2012). At first glance, one might think that minimizing Equation (9) over $\hat{h} \in \mathcal{H}$ is equivalent to minimizing the MSE, $\min_{\hat{h} \in \mathcal{H}} \mathbb{E}[(Y - \hat{h}(X))^2]$. Unfortunately, doing the latter only gives us a function that matches unconditional moments (i.e. $\mathbb{E}[Y] = \mathbb{E}[\hat{h}(X)]$). This would give us the inconsistent, OLS-like estimates of h we are explicitly trying to avoid. Instead, by minimizing Eq. 9, we are attempting to find an $\hat{h}$ that satisfies the CMR. We note that minimizing PRMSE does not guarantee recovery of $\mathbb{E}[Y|do(X)]$. However, given that $\mathbb{E}[Y|do(X)]$ always minimizes PRMSE, a low PRMSE is indicative of being close to $\mathbb{E}[Y|do(X)]$.

---

[1] The inclusion of V makes our model a generalization of the standard IVR model, so we confirm the validity of the instrument in Appendix A.

[2] Without this assumption, one can only upper/lower bound $h(x)$ (Balke & Pearl, 2013).

3.1 Generative Modeling Approach

How should we minimize the PRMSE then? One option is learning the distribution $P(X|z) = g(z)$ and passing samples from it to a candidate $\widehat{h}$. Thus, one is matching the conditional moments. This is a generalization of the 2SLS procedure to nonlinear functions. The nonlinearity of the second stage means that one cannot simply compute the first moment of the $P(X|z)$ distribution, which is recovered by linearly regressing from X to Z in the 2SLS procedure. This sort of approach was first proposed for the IVR setting by Hartford et al. (2017) and amounts to first learning a $g(z)$ (e.g. via maximum likelihood estimation) and then solving

$$\min_{\widehat{h} \in \mathcal{H}} \mathbb{E}_Z \left[(\mathbb{E}[Y|z] - \mathbb{E}_{\hat{X} \sim g(z)}[\widehat{h}(\hat{X})])^2 \right]. \tag{10}$$

We note that this approach suffers from a "double-sample" issue (Baird, 1995) where multiple independent samples of $g(z)$ are required to compute gradients of $\widehat{h}$. To see this, note that the gradient with respect to h of (10) is

$$\mathbb{E}_Z \left[(\mathbb{E}[Y|z] - \mathbb{E}_{\hat{x} \sim \hat{g}(z)}[\widehat{h}(\hat{x})])(-\mathbb{E}_{\hat{x} \sim \hat{g}(z)}[\frac{\partial}{\partial \widehat{h}} \widehat{h}(\hat{x})]) \right] \tag{11}$$

Notice that $\hat{x}$ appears under two *separate* expectations that are then multiplied together. To get an unbiased estimate of this product, two samples of $\hat{x}$ are required, one for each expectation. Therefore, it is most correct to use multiple samples from $g(z)$ for each update. The work of Hartford et al. (2017) did not have theoretical analysis regarding the effect of errors in $g(z)$ upon attempts to learn $h(x)$. We prove the following in Appendix A:

Theorem 1. *Assume we learn a $g(z)$ s.t. $\max_{\widehat{h} \in \mathcal{H}} \mathbb{E}_Z[(\mathbb{E}_{x \sim g(z)}[\widehat{h}(x)] - \mathbb{E}_{x \sim P(X|z)}[\widehat{h}(x)])^2] \leq \delta$. Then, optimizing (10) to value ϵ corresponds to recovering a $\widehat{h}(x)$ s.t. PRMSE$(\widehat{h}) \leq \sqrt{\delta} + \sqrt{\epsilon}$.*

3.2 Game-Theoretic Approach

One can also proceed by instead solving the two-player zero-sum game with the ReLa (7) as the payoff. Denoting by $f \in \mathcal{F} = \{\mathcal{Z} \to \mathbb{R}\}$ the function that maps z's to their Lagrange multipliers, we can write this game as

$$\min_{\widehat{h} \in \mathcal{H}} \max_{f \in \mathcal{F}} \mathbb{E}[2(Y - \widehat{h}(X))f(Z) - f(Z)^2]. \tag{12}$$

This game is the core objective of the AGMM method of Dikkala et al. (2020). Importantly, one does not need to learn a generative model of $P(X|z)$ for these sorts of game-theoretic approaches. We prove the following theorem in Appendix A:

Theorem 2. *Assume that $\mathcal{H}$ and $\mathcal{F}$ are bounded, closed under negation, convex, compact, and that $h \in \mathcal{H}$ and $\forall \widehat{h} \in \mathcal{H}$, $f(z) = \mathbb{E}[Y - \widehat{h}(X)|z] \in \mathcal{F}$. Then, an ϵ-approximate Nash equilibrium of (12) corresponds to recovering a $\widehat{h}(x)$ s.t. PRMSE$(\widehat{h}) \leq \sqrt{\epsilon}$.*

One can find such an equilibrium via a standard reduction to no-regret online learning (Freund & Schapire, 1997). In summary, one can frame nonlinear IVR as a generative modeling or game-theoretic problem, leading to different error characteristics. We now turn our attention to applying these methods to imitation learning with unobserved confounders.

4 Causal Confounding in Imitation Learning

We begin with a brief sketch to illustrate the challenges of confounding for IL: consider an expert trying to fly a quadcopter straight but their actions being perturbed by wind (i.e. a form of exogenous noise). Because it attempts to reproduce expert actions, behavioral cloning would reproduce these deviations, producing trajectories that deviate *even further* from a straight path in a windy

Figure 3: Behavioral cloning amplifies the effect of exogenous noise, unlike IV.

environment. In contrast, by filtering out the effects of the confounder, a policy trained via IVR would only be affected by the wind present at test time and therefore produce trajectories similar to those of the expert.

We now formalize this sort of confounding and how one can use IVR to mitigate its effects. We use $\Delta(S)$ to mean the set of distributions over S and focus on a Markov Decision Process (MDP) parameterized by $\langle S, A, \mathcal{T}, r, T \rangle$, where S is the state space, A is the action space, $\mathcal{T} : S \times A \rightarrow \Delta(S)$ is the transition operator, $r : S \times A \rightarrow [-1, 1]$ is the reward function, and T is the horizon of the problem. Let $J(\pi) = \mathbb{E}_{\tau \sim \pi}[\sum_{t=1}^{T} r(s_t, a_t)]$, $\Pi \subseteq \{S \rightarrow \Delta(A)\}$ be the policy class we optimize over and d_π be the visitation distribution of policy π. In the presence of unobserved confounding, the trajectories generated by the expert can be captured by the structural causal model (SCM) in Fig. 4. [3] Fig. 4 captures both the exogenous and endogenous noise settings. In the exogenous noise setting, the confounder u_{t-1} could be a persistent noise that affects pairs of actions, while in the endogenous noise setting, u_{t-1} can be thought of as a response to a part of the state that the learner does not have access to. See Table 1 for several examples that could fit into both noise models. In either setting, the confounding travels through the dynamics to influence the next state, leading to spurious correlations between the recorded states and actions. We can also see this correlative effect by writing out the structural equations:

Figure 4: The SCM for imitation learning with unobserved confounders. The confounding is mediated via the dynamics into the state, introducing spurious correlations between states ($X = s_t$) and actions ($Y = a_t$). To break the confounding, we can utilize the past state as an instrument ($Z = s_{t-1}$).

$$X = s_t = \mathcal{T}(s_{t-1}, a_{t-1}) = \mathcal{T}(s_{t-1}, \pi_E(s_{t-1}) + u_{t-1} + u_{t-2}) \tag{13}$$
$$Y = a_t = \pi_E(s_t) + u_t + u_{t-1}. \tag{14}$$

Fig. 4 also tells us that $Z = s_{t-1}$ satisfies the three conditions to make it a valid instrument for countering the effects of $U = u_{t-1}$. Intuitively, this is because the past state is independent of the current confounder, allowing it to function as an independent source of randomness. One can imagine longer time-scale correlations induced between actions than just one step confounding – our approaches naturally extend to this setting by using a state further back in the past as the instrument.

Unlike standard imitation learning approaches like behavior cloning which attempt to recover $\mathbb{E}[a|s]$, an approach based on IVR enables us to instead recover the interventional effect of the policy $\mathbb{E}[\pi_E(s)|s] = \mathbb{E}[a|do(s)]$. Conceptually, $\mathbb{E}[a|do(s)]$ is asking what the expert would do on average if they were placed in state s, *i.e.* the kind of answer we would get from a queryable expert in DAgger (Ross et al., 2011) or DAeQuIL (Swamy et al., 2021). However, as we are only interested in the result of queries on states from expert demonstrations, we are able to get a similar effect via IVR to an interactive approach without requiring access to a queryable expert. We now build upon this intuition to derive two practical algorithms.

5 ALGORITHMS FOR CAUSAL IMITATION LEARNING

We now present two approaches for causal imitation learning that can be seen as applications of the generative modeling and game-theoretic approaches of Sec. 3. At their core, both algorithms are attempting to minimize a PRMSE objective,

$$\min_{\pi \in \Pi} \mathbb{E}_{(s,s',a') \sim d_{\pi_E}}[(\mathbb{E}[a' - \pi(s')|s])^2], \tag{15}$$

instead of the usual IL objective,

$$\min_{\pi \in \Pi} \mathbb{E}_{(s,a) \sim d_{\pi_E}}[(a - \pi(s))^2]. \tag{16}$$

---

[3] One technically needs to add another input to π_E (i.e. $\pi_E(s, R)$, where R is a random input) to allow for a non-deterministic expert. In this work, we focus on techniques for minimizing the PRMSE, for which matching average expert actions is sufficient. Thus, we suppress the dependence on the other input.

Under exogenous noise, minimizing (16) to 0 would not recover the expert's policy while minimizing Equation (15) would. First, let a distribution $P(U)$ be c-Total Variation stable (Bassily et al., 2021) if:

$$\|a - b\|_2 \leq \delta \Rightarrow d_{TV}(a + U, b + U) \leq c\delta. \tag{17}$$

This property is satisfied by a wide variety of distributions. For example, for standard normal random variables, $c = 1/2$. Next, in our setting, the measure of ill-posedness (Dikkala et al., 2020; Chen & Pouzo, 2012) is

$$\kappa(\Pi) = \sup_{\pi \in \Pi} \frac{\sqrt{\mathbb{E}_{s \sim d_{\pi_E}}[(\pi_E(s) - \pi(s))^2]}}{\sqrt{\mathbb{E}_{s,s',a' \sim d_{\pi_E}}[\mathbb{E}[a' - \pi(s')|s]]^2}} = \sup_{\pi \in \Pi} \frac{\text{RMSE}(\pi)}{\text{PRMSE}(\pi)}. \tag{18}$$

We prove the following bound on policy performance in Appendix B:

Theorem 3. *Assume $P(U)$ is c-TV Stable exog. noise, π_E is deterministic, and let $\kappa(\Pi)$ be the measure of the ill-posedness of the problem. Then, PRMSE$(\pi) \leq \epsilon \Rightarrow J(\pi_E) - J(\pi) \leq c\kappa(\Pi)\epsilon T^2$.*

Intuitively, $\kappa(\Pi)$ measures the strength of the strength of the instrument. Consider the extreme case where $s' = s$. Then, $\kappa(\Pi) = 1$. As the past state becomes a weaker instrument, $\kappa(\Pi) > 1$. Thus, if the confounding affects multiple timesteps, we would expect $\kappa(\Pi)$ to grow as one needs to reach further back in time to find a valid instrument, leading to a looser performance bound. We investigate the effect of the length of confounding on the ill-posedness of the problem empirically in Sec. 6.

One might be curious as to why we only provide a performance bound for the exogenous setting. This is because in general, endogenous noise can make it impossible to effectively imitate an expert. Consider, for example, an expert driver that stops at an intersection when a traffic light is red. If the learner does not see this light, there is no way for them to ensure they match the behavior of such an expert. While for closeness in distribution, the learner could hallucinate a traffic light and stop when it is "red," this is clearly not desirable. However, there are some works that have shown empirically that a learner knowing less than an expert can, for some problems, not be much of a hindrance to learning a performant policy (Choudhury et al., 2017). It is an open problem to delineate what kinds of persistent endogenous noise make it impossible to imitate an expert – Zhang et al. (2020) take some steps towards this goal. We note that our approaches are still capable of recovering $\mathbb{E}[a|do(s)]$ in the endogenous setting but that the information asymmetry between the learner and expert makes it difficult to ensure doing so corresponds to learning a policy of equivalent quality to the expert's.

5.1 WITH A SIMULATOR: DoubIL

Algorithm 1 DoubIL

Input: Dataset $\mathcal{D}_E$ of expert trajectories, Policy class Π, Simulator $\widehat{\mathcal{T}}$
Output: Trained policy π_2
$\pi_1 = \arg\min_{\pi \in \Pi} \mathbb{E}_{s,a \sim \mathcal{D}_E}[-\log \pi(a|s)]$ {Train preliminary policy via moment-matching.}
$\mathcal{D}_{IV} = \{(\widehat{\mathcal{T}}(s, \pi_1(s)), a')|\forall(s, a') \in \mathcal{D}_E\}$ {Pass π_1's actions through simulator.}
$\pi_2 = \arg\min_{\pi \in \Pi} \mathbb{E}_{s,a \sim \mathcal{D}_{IV}}[(a - \pi(s))^2]$ {Train final policy on new dataset and output.}

Algorithm 1 can be seen as a variation of generative modeling approach of Sec. 3 and Hartford et al. (2017) where one leverages knowledge of one factor of the $P(X|z)$ distribution and just learns the other factor. Via the Markov assumption, we can factorize $P(X|z) = P(S'|s) = \sum_{a \in \mathcal{A}} P(a|s)\mathcal{T}(s, a)$. Assuming access to a simulator $\widehat{\mathcal{T}}$ that closely approximates the true transition dynamics, we can instead focus on learning the $P(a|s)$ component: the standard imitation learning task. Notably, this first-stage policy is biased as it includes the effect of the confounder: $P(a|s) = P(U + \pi_E(s)|s)$. However, when we use it to simulate transitions, the next states that are produced no longer have the particular instantiation of the confounder present in the recorded dataset's next actions. Using

Figure 5: DoubIL deconfounds inputs to the second stage by re-simulating state transitions.

a tilde to denote a fresh draw from a distribution, simulated states are drawn from

$$\widetilde{s}_t \sim \widehat{\mathcal{T}}(s_{t-1}, \pi_1(s_{t-1})) \tag{19}$$

while the observed next actions are drawn from

$$a_t \sim \pi_E(\mathcal{T}(s_{t-1}, \pi_E(s_{t-1}) + u_{t-1} + u_{t-2})) + u_{t-1} + u_t. \tag{20}$$

Notice that there are no shared noise terms. This allows us to apply standard imitation learning to this new dataset of $(\widetilde{s}_t, a_t)$ to learn a causally consistent policy. The two applications of imitation learning lead us to term this algorithm `DoubIL`. We can translate the guarantee of Theorem 1 to our factored context:

Lemma 1. *Assume we learn a $\pi_1(s)$ s.t.*

$$\max_{\pi \in \Pi} \mathbb{E}_{s_{t-1}} \left[(\mathbb{E}_{s_t \sim \widehat{\mathcal{T}}(s_{t-1}, \pi_1(s_{t-1}))}[\pi(s_t)] - \mathbb{E}_{s_t \sim P(s_t | s_{t-1})}[\pi(s_t)])^2 \right] \leq \delta$$

Then, optimizing the second-stage MSE to ϵ corresponds to recovering a π_2 s.t.

$$PRMSE(\pi_2) = \sqrt{\mathbb{E}_{s \sim d_{\pi_E}}[\mathbb{E}[\pi_2(s') - \pi_E(s') | s]^2]} \leq \sqrt{\delta} + \sqrt{\epsilon}.$$

We prove this lemma in Appendix A. Combining this lemma with Theorem 3 allows one to derive a performance bound of $J(\pi_E) - J(\pi) \leq c\kappa(\Pi)(\sqrt{\delta} + \sqrt{\epsilon})T^2$. We note that one could simply learn the mapping $P(s'|s)$ but this can be far less sample efficient than merely learning a policy when $|\mathcal{A}| \leq |\mathcal{S}|$, as is often true in practice.

5.2 WITHOUT STATE RE-SAMPLING: RESIDUIL

Algorithm 2 `ResiduIL`

Input: Dataset $\mathcal{D}_E$ of expert trajectories, Policy class Π, Discriminator class $\mathcal{F}$, Learning rate η
Output: Trained policy π
Set $\pi \in \Pi, f \in \mathcal{F}, \widetilde{g}_\pi = 0, \widetilde{g}_f = 0$
while π not satisfactory **do**
    $L(\pi, f) = \mathbb{E}_{(s,s',a') \sim \mathcal{D}_E}[2(a' - \pi(s'))f(s) - f(s)^2]$ {Payoff of zero-sum game.}
    $g_\pi = \nabla_\pi L(\pi, f), g_f = \nabla_f L(\pi, f)$ {Perform Optimistic Mirror Descent.}
    $\pi \leftarrow \pi - \eta(2g_\pi - \widetilde{g}_\pi)$
    $f \leftarrow f + \eta(2g_f - \widetilde{g}_f)$
    $\widetilde{g}_\pi \leftarrow g_\pi, \widetilde{g}_f \leftarrow g_f$
end while

Algorithm 2 is the straightforward application of the game-theoretic approach of Sec. 3 and Dikkala et al. (2020) to imitation learning. We term it `ResiduIL` because the adversary attempts to predict the residual between the learner and the expert's actions while the learner attempts to minimize this residual. Notably, this algorithm can be run completely offline (i.e. without access to a simulator). We use the Optimistic Mirror Descent approach of Syrgkanis et al. (2015) to find approximate Nash equilibria in our experiments. Once again, we can extend our past results to the IL setting:

Lemma 2. *An ϵ-approximate equilibrium for the policy player corresponds to recovering a policy π s.t $PRMSE(\pi) \leq \sqrt{\epsilon}$.*

This lemma dovetails with Theorem 3 to prove that $J(\pi_E) - J(\pi) \leq c\kappa(\Pi)\sqrt{\epsilon}T^2$ (Appendix A).

6 EXPERIMENTS

We test `DoubIL` and `ResiduIL` on a slightly modified version of the OpenAI Gym (Brockman et al., 2016) LunarLander-v2 environment against a behavioral cloning baseline. We generate demonstrations by simulating rollouts of an expert policy trained via PPO (Schulman et al., 2017), adding fresh Gaussian noise to the expert's action as well as cached noise from the last timestep.

Figure 6: We train behavioral cloning, `DoubIL`, and `ResiduIL` on trajectories from a modified LunarLander environment, computing standard errors across 5 runs. The left plot shows that `DoubIL` and `ResiduIL` are better able to match the desired $\mathbb{E}[a|do(s)]$ on states from expert rollouts, while the middle plot shows they are able to generalize better to the state dist. of an expert w/o noise. The right plot shows how we can compare the results of behavioral cloning and causal IL procedures to identify areas of the state space where the effect of confounding is strong (the red dots).

The latter noise is the confounder. See Appendix B for full parameters. We judge policy quality by computing the MSE between the output of a noiseless expert query and a learner's proposed actions on states from expert rollouts. We see that both of our methods are able to more closely match $\mathbb{E}[a|do(s)]$ than behavioral cloning, especially in the low-data regime (Fig. 6, left). We also measure the MSE on states from noiseless expert rollouts – while there are no clear guarantees on this state distribution, we see that our methods generalize better than BC empirically (Fig. 6, middle).

A natural question at this point might be given a dataset of expert demonstrations, how does one detect whether there is unobserved confounding in the data. We can answer this question by comparing the results of behavioral cloning and either of our above algorithms. We prove the following lemma in Appendix A:

Lemma 3. *Assume $\pi_{BC}(s) = \mathbb{E}[a|s]$ and $\pi_{IV}(s) = \mathbb{E}[a|do(s)]$. Then, $\mathbb{E}[u|s] = \pi_{BC}(s) - \pi_{IV}(s)$.*

The implication of this lemma is that comparing the outputs of IVR-based procedures to behavioral cloning can help us detect causal confounding – if they greatly differ with a sufficiently sized dataset, there is likely an unobserved confounding effect in our data. Moreover, the states where they differ represent the parts of the state space where the influence of the confounder is highest. Fig. 6 right is an empirical example of how the test of Lemma 3 can be used to identify areas of the state space where the effect of the confounder is especially strong (e.g. the center).

For linear problems, we can bound $\kappa(\Pi)$ (the measure of ill-posedness) (Dikkala et al., 2020). Extending our previous model to include the effect of the last H confounders ($a_t = \pi_E(s_t) + \sum_{j=t-H}^{t} u_j.$), we arrive at the bound

$$\kappa(\Pi; H) \leq \sqrt{\frac{\lambda_{max}(\mathbb{E}[s_t s_t^T])}{\lambda_{min}(\mathbb{E}[\mathbb{E}[s_t|s_{t-H}]\mathbb{E}[s_t|s_{t-H}]^T])}}. \quad (21)$$

We compute this quantity empirically for a linear-quadratic problem with Gaussian confounding and plot results in Fig. 7. As expected, we see that increasing the length of confounding leads to weaker instruments as one has to use states further back in time. Theorem 3 tells us that under exogenous noise, we should expect a weaker instrument to lead to a larger performance gap between the learner and expert. See Appendix B for full experimental setup details.

Figure 7: We compute $\kappa(\Pi)$ for an LQG problem where we vary the number of steps a confounder sticks around for.

7 CONCLUSION

We present a model that captures confounding in imitation learning and derive two algorithms, `DoubIL` and `ResiduIL`, that are able to utilize history as an instrument to mitigate the effects of unobserved confounders. We then verify their efficacy empirically.

8 REPRODUCIBILITY STATEMENT

On the empirical side, we submit the source code we used to run all experiments as supplementary material. We provide a Jupyter Notebook (`CausIL.ipynb`) that calls the right functions from the source code, making re-running experiments just a matter of running the cells of the notebook. Similarly, the results figures in the paper can be re-created by running the cells of `vis.ipynb`. We also provide the training sets, test sets, and raw performance data files that were used for all experiments in the `data` folder of the supplementary material, as well as our trained expert model and the code we used to train said expert in the `src/experts` folder. All of the hyperparameters we used for experiments are set accurately in the code as well as being in Appendix B, where we also detail how we implemented the loss function for `DoubIL` as it required a non-standard operator. For all results figures, we include the number of runs used to compute standard errors. On the theoretical side, we provide the self-contained proofs of all of our lemmas and theorems in Appendix A.

REFERENCES

Joshua D Angrist, Guido W Imbens, and Donald B Rubin. Identification of causal effects using instrumental variables. *Journal of the American statistical Association*, 91(434):444–455, 1996.

Leemon Baird. Residual algorithms: Reinforcement learning with function approximation. In *Machine Learning Proceedings 1995*, pp. 30–37. Elsevier, 1995.

Alexander Balke and Judea Pearl. Counterfactual probabilities: Computational methods, bounds and applications, 2013.

Mayank Bansal, Alex Krizhevsky, and Abhijit S. Ogale. Chauffeurnet: Learning to drive by imitating the best and synthesizing the worst. *CoRR*, abs/1812.03079, 2018. URL http://arxiv.org/abs/1812.03079.

Raef Bassily, Kobbi Nissim, Adam Smith, Thomas Steinke, Uri Stemmer, and Jonathan Ullman. Algorithmic stability for adaptive data analysis. *SIAM Journal on Computing*, (0):STOC16–377, 2021.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym, 2016.

Xiaohong Chen and Demian Pouzo. Estimation of nonparametric conditional moment models with possibly nonsmooth generalized residuals. *Econometrica*, 80(1):277–321, 2012.

Sanjiban Choudhury, Mohak Bhardwaj, Sankalp Arora, Ashish Kapoor, Gireeja Ranade, Sebastian Scherer, and Debadeepta Dey. Data-driven planning via imitation learning, 2017.

Felipe Codevilla, Eder Santana, Antonio M. López, and Adrien Gaidon. Exploring the limitations of behavior cloning for autonomous driving. *CoRR*, abs/1904.08980, 2019. URL http://arxiv.org/abs/1904.08980.

Pim de Haan, Dinesh Jayaraman, and Sergey Levine. Causal confusion in imitation learning. *Advances in Neural Information Processing Systems*, 32:11698–11709, 2019.

Nishanth Dikkala, Greg Lewis, Lester Mackey, and Vasilis Syrgkanis. Minimax estimation of conditional moment models, 2020.

Yoav Freund and Robert E Schapire. A decision-theoretic generalization of on-line learning and an application to boosting. *Journal of computer and system sciences*, 55(1):119–139, 1997.

Jason Hartford, Greg Lewis, Kevin Leyton-Brown, and Matt Taddy. Deep iv: A flexible approach for counterfactual prediction. In *International Conference on Machine Learning*, pp. 1414–1423. PMLR, 2017.

Ahmed Hefny, Carlton Downey, and Geoffrey J Gordon. Supervised learning for dynamical system learning. *Advances in neural information processing systems*, 28:1963–1971, 2015.

Sham Kakade and John Langford. Approximately optimal approximate reinforcement learning. In *IN PROC. 19TH INTERNATIONAL CONFERENCE ON MACHINE LEARNING*, pp. 267–274, 2002.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Ilya Kostrikov, Ofir Nachum, and Jonathan Tompson. Imitation learning via off-policy distribution matching, 2019.

Alex Kuefler, Jeremy Morton, Tim Wheeler, and Mykel Kochenderfer. Imitating driver behavior with generative adversarial networks. In *2017 IEEE Intelligent Vehicles Symposium (IV)*, pp. 204–211. IEEE, 2017.

Urs Muller, Jan Ben, Eric Cosatto, Beat Flepp, and Yann L Cun. Off-road obstacle avoidance through end-to-end learning. In *Advances in neural information processing systems*, pp. 739–746. Citeseer, 2006.

Judea Pearl, Madelyn Glymour, and Nicholas P Jewell. *Causal inference in statistics: A primer*. John Wiley & Sons, 2016.

Dean A Pomerleau. Alvinn: An autonomous land vehicle in a neural network. 1989.

Stephane Ross and J. Andrew Bagnell. Reinforcement and imitation learning via interactive no-regret learning, 2014.

Stephane Ross, Geoffrey J. Gordon, and J. Andrew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning, 2011.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms, 2017.

Jonathan Spencer, Sanjiban Choudhury, Arun Venkatraman, Brian Ziebart, and J. Andrew Bagnell. Feedback in imitation learning: The three regimes of covariate shift, 2021.

Gokul Swamy, Sanjiban Choudhury, J. Andrew Bagnell, and Zhiwei Steven Wu. Of moments and matching: A game-theoretic framework for closing the imitation gap, 2021.

Vasilis Syrgkanis, Alekh Agarwal, Haipeng Luo, and Robert E Schapire. Fast convergence of regularized learning in games. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015. URL `https://proceedings.neurips.cc/paper/2015/file/7fea637fd6d02b8f0adf6f7dc36aed93-Paper.pdf`.

Christopher Winship and Stephen L Morgan. The estimation of causal effects from observational data. *Annual review of sociology*, 25(1):659–706, 1999.

Philip G Wright. *Tariff on animal and vegetable oils*. Macmillan Company, New York, 1928.

Junzhe Zhang, Daniel Kumor, and Elias Bareinboim. Causal imitation learning with unobserved confounders. *Advances in Neural Information Processing Systems*, 33, 2020.

A PROOFS

A.1 PROOF OF VALIDITY OF INSTRUMENT

Proof. We check the instrument conditions in order:

1. *Unconfounded Instrument*: $Z \perp\!\!\!\perp U$: The $Z \to X \leftarrow U$, $V \to X \leftarrow U$, and $X \to Y \leftarrow U$ triples are blocked by standard d-separation rules (Pearl et al., 2016). All paths from Z to U must pass through one of these triples so $Z \perp\!\!\!\perp U$.

2. *Exclusion*: $Z \perp\!\!\!\perp Y|X,U$: The $Z \to X \to Y$, $X \leftarrow U \to Y$, and $V \to X \to Y$ triples are blocked by standard d-separation rules. All paths from Z to Y must pass through one of these triples so $Z \perp\!\!\!\perp Y|X,U$.

3. *Relevance*: $Z \not\perp\!\!\!\perp X$: There is a $Z \to X$ edge, which is assumed to be non-degenerate.

Thus, Z is a valid instrument for determining the causal relationship between X and Y. $\qquad\square$

A.2 PROOF OF THEOREM 1

Proof. We simplify notation for clarity in our proof. Consider two vectors of the same dimension, $\mathbf{a}$ and $\mathbf{b}$. Assume that $\sum_i^N a_i^2 \leq \epsilon$ and $\sum_i^N b_i^2 \leq \delta$. This implies that $\|\mathbf{a}\|_2 \leq \sqrt{\epsilon}$ and $\|\mathbf{b}\|_2 \leq \sqrt{\delta}$. Then, by the triangle inequality, $\|\mathbf{a} - \mathbf{b}\|_2 \leq \|\mathbf{a}\|_2 + \|\mathbf{b}\|_2 \leq \sqrt{\epsilon} + \sqrt{\delta}$. Setting $a_i = \sqrt{P(z)}(\mathbb{E}[Y|z] - \mathbb{E}_{\hat{x}\sim g(z)}[\widehat{h}(\hat{x})])$ and $b_i = \sqrt{P(z)}(\mathbb{E}_{\hat{x}\sim g(z)}[\widehat{h}(\hat{x})] - \mathbb{E}[\widehat{h}(x)|z])$ proves that

$$\max_{\widehat{h}\in\mathcal{H}} \mathbb{E}_Z[(\mathbb{E}_{x\sim g(z)}[\widehat{h}(x)] - \mathbb{E}_{x\sim P(X|z)}[\widehat{h}(x)])^2] \leq \delta, \tag{22}$$

$$\mathbb{E}_z[(\mathbb{E}[Y|z] - \mathbb{E}_{\hat{x}\sim g(z)}[\widehat{h}(\hat{x})])^2] \leq \epsilon \tag{23}$$

$$\Rightarrow PRMSE(\widehat{h}) = \sqrt{\mathbb{E}_z[(\mathbb{E}[Y|z] - \mathbb{E}_{x\sim P(X|z)}[\widehat{h}(x)])^2]} \leq \sqrt{\epsilon} + \sqrt{\delta} \tag{24}$$

$$\square$$

A.3 PROOF OF THEOREM 2

Proof. The population version of (12) is

$$\min_{h\in\mathcal{H}} \max_{f\in\mathcal{F}} \mathbb{E}[2(Y - h(X))f(Z) - f^2(Z)] \tag{25}$$

An ϵ-approximate equilibrium is an $(\widehat{h}, \widehat{f})$ pair such that:

$$\max_{f\in\mathcal{F}} \mathbb{E}[2(Y - \widehat{h}(X))f(Z) - f^2(Z)] - \frac{\epsilon}{2} \tag{26}$$

$$\leq \mathbb{E}[2(Y - \widehat{f}(X))\widehat{f}(Z) - \widehat{f}^2(Z)] \tag{27}$$

$$\leq \min_{h\in\mathcal{H}} \mathbb{E}[2(Y - h(X))\widehat{f}(Z) - \widehat{f}^2(Z)] + \frac{\epsilon}{2} \tag{28}$$

Taking the derivative w.r.t $f(z)$ of the payoff and setting it equal to 0, we arrive at

$$2P(z)\mathbb{E}[Y - \widehat{h}(X)|z] - 2P(z)f(z) = 0 \Rightarrow f(z) = \mathbb{E}[Y - \widehat{h}(X)|z]. \tag{29}$$

Plugging this back into (35) gives us the inequality

$$\mathbb{E}_Z[\mathbb{E}[Y - \widehat{h}(X)|z]^2] - \frac{\epsilon}{2} \leq \min_{h\in\mathcal{H}} \mathbb{E}[2(Y - h(X))\widehat{f}(Z) - \widehat{f}^2(Z)] + \frac{\epsilon}{2}. \tag{30}$$

Assuming we are in the realizable setting (e.g. $h(x) = \mathbb{E}[Y|do(x)] \in \mathcal{H}$), $\min_{h\in\mathcal{H}} \mathbb{E}[2(Y - h(X))\widehat{f}(Z) - \widehat{f}^2(Z)] \leq 0$. Thus, we can write that:

$$\mathbb{E}_Z[\mathbb{E}[Y - \widehat{h}(X)|z]^2] - \frac{\epsilon}{2} \leq \frac{\epsilon}{2} \Rightarrow \text{PRMSE}(\widehat{h}) \leq \sqrt{\epsilon}. \tag{31}$$

$$\square$$

We note that Theorem 2 follows somewhat directly from the main theorems of Dikkala et al. (2020) but that it was not stated in this precise form in their work.

A.4 PROOF OF LEMMA 1

Proof. Notice that

$$\max_{\pi \in \Pi} \mathbb{E}_{s_{t-1}}[(\mathbb{E}_{s_t \sim \widehat{\mathcal{T}}(s_{t-1}, \pi_1(s_{t-1}))}[\pi(s_t)] - \mathbb{E}_{s_t \sim P(s_t|s_{t-1})}[\pi(s_t)])^2] \leq \delta \tag{32}$$

can be re-written as

$$\max_{\pi \in \Pi} \mathbb{E}_Z[(\mathbb{E}_{x \sim g(z)}[\pi(x)] - \mathbb{E}_{x \sim P(X|z)}[\pi(x)])^2] \leq \delta. \tag{33}$$

Thus, the proof of Theorem 1 holds as written. $\qquad\square$

A.5 PROOF OF LEMMA 2

An ϵ-approximate equilibrium for the policy player is a π such that

$$\max_{f \in \mathcal{F}} \mathbb{E}[2(a_t - \pi(s_t))f(s_{t-1}) - f^2(s_{t-1})] - \frac{\epsilon}{2} \leq \min_{\pi \in \Pi} \mathbb{E}[2(a_t - h(s_t))\widehat{f}(s_{t-1}) - \widehat{f}^2(s_{t-1})] + \frac{\epsilon}{2}. \tag{34}$$

With a change of notation, we can re-write this as:

$$\max_{f \in \mathcal{F}} \mathbb{E}[2(Y - \pi(X))f(Z) - f^2(Z)] - \frac{\epsilon}{2} \leq \min_{\pi \in \Pi} \mathbb{E}[2(Y - h(X))\widehat{f}(Z) - \widehat{f}^2(Z)] + \frac{\epsilon}{2}. \tag{35}$$

Thus, the proof of Theorem 2 holds as written.

A.6 PROOF OF THEOREM 3

Proof. By definition,

$$\text{PRMSE}(\pi) = \sqrt{\mathbb{E}_{s \sim d_{\pi_E}}[\mathbb{E}[a' - \pi(s')|s]]^2} = \epsilon. \tag{36}$$

Recall that the measure of ill-posedness of the problem (Dikkala et al., 2020; Chen & Pouzo, 2012) can be defined as

$$\kappa(\Pi) = \sup_{\pi \in \Pi} \frac{\sqrt{\mathbb{E}_{s \sim d_{\pi_E}}[(\pi_E(s) - \pi(s))^2]}}{\sqrt{\mathbb{E}_{s,s',a' \sim d_{\pi_E}}[\mathbb{E}[a' - \pi(s')|s]]^2}} = \sup_{\pi \in \Pi} \frac{\text{RMSE}(\pi)}{\text{PRMSE}(\pi)} \tag{37}$$

Directly,

$$\text{RMSE}(\pi) \leq \epsilon \kappa(\Pi) \tag{38}$$

We repeat the definition of total variation stability of a distribution $P(U)$:

$$\|a - b\|_2 \leq \delta \Rightarrow d_{TV}(a + U, b + U) \leq c\delta. \tag{39}$$

We proceed by noting that TV-stability implies that $\forall s \in \mathcal{S}$,

$$d_{TV}(\pi(s) + U, \pi_E(s) + U) \leq c \|\pi(s) - \pi_E(s)\| \tag{40}$$

$$\Rightarrow d_{TV}(\pi(s) + U, \pi_E(s) + U)^2 \leq c^2 \|\pi(s) - \pi_E(s)\|^2 \tag{41}$$

$$\Rightarrow \mathbb{E}_{s \sim d_{\pi_E}}[d_{TV}(\pi(s) + U, \pi_E(s) + U)^2] \leq c^2 \mathbb{E}_{s \sim d_{\pi_E}}[\|\pi(s) - \pi_E(s)\|^2] = c^2 \text{MSE}(\pi). \tag{42}$$

By Jensen's inequality,

$$\mathbb{E}_{s \sim d_{\pi_E}}[d_{TV}(\pi(s) + U, \pi_E(s) + U)]^2 \leq \mathbb{E}_{s \sim d_{\pi_E}}[d_{TV}(\pi(s) + U, \pi_E(s) + U)^2] \leq c^2 \text{MSE}(\pi). \tag{43}$$

Taking the square root of both sides, we arrive at

$$\mathbb{E}_{s \sim d_{\pi_E}}[d_{TV}(\pi(s) + U, \pi_E(s) + U)] \leq c\,\text{RMSE}(\pi) \leq c\kappa(\Pi)\epsilon. \tag{44}$$

Lastly, we apply the Performance Difference Lemma of Kakade & Langford (2002) as follows:

$$J(\pi_E) - J(\pi) = T\mathbb{E}_{s,a \sim d_{\pi_E}}[Q^\pi(s,a) - \mathbb{E}_{a' \sim \pi(s)}[Q^\pi(s,a')]] \tag{45}$$

$$= T\mathbb{E}_{s,a \sim d_{\pi_E}}[Q^\pi(s, \pi_E(s) + u + \widetilde{u}_1) - \mathbb{E}[Q^\pi(s, \pi(s) + u + \widetilde{u}_2)]] \tag{46}$$

$$\leq T^2 \mathbb{E}_{s \sim d_{\pi_E}}[d_{TV}(\pi(s) + U, \pi_E(s) + U)] \tag{47}$$

$$\leq c\kappa(\Pi)\epsilon T^2. \tag{48}$$

We use the fact that the same u would be added to both the learner and the expert's actions and that rewards are in the range $[-1, 1]$ in the third step.

$\qquad\square$

A.7   PROOF OF LEMMA 3

Proof.

$$\mathbb{E}[a_t|do(s_t)] = \mathbb{E}[\pi_E(s_t) + u_t + u_{t-1}|do(s_t)] = \pi_E(s_t) + \mathbb{E}[u_t] + \mathbb{E}[u_{t-1}] = \pi_E(s_t) \quad (49)$$

$$\mathbb{E}[a_t|s_t] = \mathbb{E}[\pi_E(s_t) + u_t + u_{t-1}|s_t] = \pi_E(s_t) + \mathbb{E}[u_t] + \mathbb{E}[u_{t-1}|s_t] = \pi_E(s) + \mathbb{E}[u_{t-1}|s_t] \quad (50)$$

$$\pi_{BC}(s) - \pi_E(s) = \mathbb{E}[a_t|s_t] - \mathbb{E}[a_t|do(s_t)] = \mathbb{E}[u_{t-1}|s_t] = \mathbb{E}[u|s] \quad (51)$$

$$\square$$

B   EXPERIMENT DETAILS

B.1   LUNARLANDER EXPERIMENTS

For ease of simulation, we remove the legs from the LunarLander vehicle (the joints connecting them to the main body have a state that is not recorded in the observed state), remove the dispersion noise, and generate trajectories with a fixed ground layout.

For all learned functions, we use two-layer ReLu MLPs with 64 hidden units. We use the Adam optimizer (Kingma & Ba, 2014) for behavioral cloning and `DoubIL` and use the optimistic variant for `ResiduIL`. We apply a weight decay of 1e-3 to all. We train all methods for 50k steps.

PARAMETER	VALUE
LEARNING RATE	3E-4
BATCH SIZE	128

Table 2: Parameters for behavioral cloning.

For computational ease, we only learn the mean of $P(a|s)$ for `DoubIL` and add fresh standard normal noise on-top of it to simulate drawing actions. For more complex noise models, one would need to use a moment matching algorithm (Swamy et al., 2021) in the first stage.

PARAMETER	VALUE
LEARNING RATE	3E-4
BATCH SIZE	128
NUM. SAMPLES FOR $\mathbb{E}$	8

Table 3: Parameters for `DoubIL`.

For implementing the "double samples" for the gradient, we compute $\mathbb{E}_1[a' - \pi(s')|s]$ and $\mathbb{E}_2[a' - \pi(s')|s]$ using independent samples. Then, we apply a stop-gradient operator to the former expectation before taking a product between the expectations and averaging over s:

$$L(\pi) = \mathbb{E}_s[\bullet(\mathbb{E}_1[a' - \pi(s')|s])\mathbb{E}_2[a' - \pi(s')|s]]. \quad (52)$$

This loss function has the correct gradient as it uses independent samples for computing the two expectations.

PARAMETER	VALUE
LEARNING RATE	5E-5
BATCH SIZE	128
BC REGULARIZER WEIGHT	5E-2
f NORM PENALTY	1E-3
ADAM βS	0, 1E-2

Table 4: Parameters for `ResiduIL`.

B.2 LQG EXPERIMENTS

We compute the optimal policy for the following canonical linear system via solving a Discrete-Time Algebraic Ricatti Equation via the standard iterative method:

$$x_t = Ax_{t-1} + Bu_{t-1} \tag{53}$$

$$J(K) = \sum_t^T x_t^T Q x_t + (Kx_t)^T RK x_t \tag{54}$$

$$A = \begin{bmatrix} 1 & \Delta T \\ 0 & 1 \end{bmatrix}, B = \begin{bmatrix} 0.5(\Delta T)^2 \\ \Delta T \end{bmatrix}, Q = \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, R = [0.1], \Delta T = 0.1$$

This is the dynamics of a "sliding brick on a frozen lake." We then simulate rollouts of 200 timesteps with u_t being drawn i.i.d. from the standard normal distribution. We confound actions with the sum of confounders going H steps back:

$$a_t = K^* s_t + \sum_{j=t-H}^t u_j. \tag{55}$$

We simulate 1000 such rollouts to compute (21) empirically. We calculate $\mathbb{E}[X|z] = \mathbb{E}[s_t|s_{t-H}] = (A + BK^*)^H s_{t-H}$ analytically instead of via samples due to the small value of the quantity in comparison to the variance of the noise.