Meta-Query-Net: Resolving Purity-Informativeness Dilemma in Open-set Active Learning

Abstract

Unlabeled examples awaiting annotations contain open-set noise inevitably. A few active learning studies have attempted to deal with this open-set noise in active learning by filtering out the noisy examples. However, because focusing on the purity of examples in a query set leads to overlooking the informativeness of the examples, the best balancing of purity and informativeness remains as an important question. In this paper, to solve this *purity-informativeness dilemma* in open set active learning, we propose a novel *Meta-Query-Net (MQ-Net)* that adaptively finds the best balancing between the two factors. Specifically, by leveraging the multi-round property of active learning, we train MQ-Net using a query set without an additional validation set. Furthermore, a clear dominance relationship between unlabeled examples is effectively captured by MQ-Net through a novel *skyline* regularization. Extensive experiments on multiple open-set active learning scenarios demonstrate that the proposed MQ-Net achieves 20.14% improvement in terms of accuracy, compared with the state-of-the-art methods.

1 Introduction

The success of deep learning in many complex tasks highly depends on the availability of massive data with well-annotated labels, which are often very costly to obtain in practice [1]. *Active learning (AL)* is one of the popular learning frameworks to reduce the high human-labeling cost, where a small number of maximally-informative examples are selected by a query strategy and labeled by an oracle repeatedly [2]. Numerous query (*i.e.*, sample selection) strategies, mainly categorized into *uncertainty*-based sampling [3, 4, 5] and *diversity*-based sampling [6, 7, 8], have succeeded in effectively reducing the labeling cost while achieving high performance.

Despite their success, most standard AL approaches rely on a strict assumption that all unlabeled examples should be cleanly collected from a pre-defined domain called *in-distribution (IN)*, even before being labeled [9]. This assumption is *unrealistic* in practice since the unlabeled examples are mostly collected from a rather *casual* data curation processes such as web-crawling. Notably, in Google search engine, the precision of image retrieval is reported to be 82% on average, and it is worsened to 48% for unpopular entities [10, 11]. That is, such collected unlabeled data naturally involves *open-set noise*, which is defined as a set of the examples collected from different domains called *out-of-distribution (OOD)* [12].

In general, standard AL approaches favor the examples either highly uncertain in predictions or highly diverse in representations as a query for labeling. However, the addition of open-set noise makes these two measures fail to identify informative examples; the OOD examples also exhibit high uncertainty and diversity because they share neither class-distinctive features nor other inductive biases with IN examples [14, 15]. As a result, an active learner is confused and likely to query the OOD examples to a human-annotator for labeling. Human annotators would disregard the OOD examples because they

(a) Purity-informativeness Dilemma.   (b) 10% Open-set Noise.   (c) 20% Open-set Noise.

Figure 1: Motivation of MQ-Net: (a) shows the purity-informativeness dilemma for query selection in open-set AL; (b) shows the AL performances of a standard AL method (HI-focused), LL [5], and an open-set AL method (HP-focused), CCAL [13], along with our proposed MQ-Net for ImageNet dataset with a noise ratio of 10%; (c) shows the trends with a noise ratio of 20%.

are unnecessary for the target task, thereby wasting the labeling budget. Therefore, the problem of active learning with open-set noise, which we call *open-set active learning*, has emerged as a new important challenge for real-world applications.

Recently, a few studies have attempted to deal with the open-set noise for active learning [13, 16]. They commonly try to increase the purity of examples in a query set, which is defined as the proportion of IN examples, by effectively filtering out the OOD examples. However, whether focusing on the purity is needed *throughout* the entire training period remains a question. In Figure 1(a), let's consider the examples of high purity and low informativeness (HP-LI) and those of low purity and high informativeness (LP-HI). The dominance between these two groups of examples in usefulness for open-set AL is not clear but is determined by the learning stage as well as the ratio of OOD examples. Thus, we coin a new term "purity-informativeness dilemma" to call attention to the best balancing of purity and informativeness.

Figures 1(b) and 1(c) illustrate the purity-informativeness dilemma. The standard AL approach, LL[5], puts more weight on the examples of high informativeness (denoted as HI-focused), while the existing open-set AL approach, CCAL [13], puts more weight on those of high purity (denoted as HP-focused). The HP-focused approach improves the test accuracy more significantly than the HP-focused one at earlier AL rounds, meaning that pure as well as easy examples are more beneficial. In contrast, the HI-focused approach outperforms the HP-focused one at later AL rounds, meaning that highly informative examples should be selected even at the expense of purity. Furthermore, comparing a low OOD (noise) ratio in Figure 1(b) and a high OOD ratio in Figure 1(c), the shift from HP-dominance to HI-dominance tends to occur later at a higher OOD ratio, which renders this dilemma more difficult.

In this paper, to solve the purity-informativeness dilemma in open-set AL, we propose a novel meta-model *Meta-Query-Net (MQ-Net)* that adaptively finds the best balancing between the two factors. A key challenge is the best balancing is unknown in advance. The meta-model is trained to assign higher priority for in-distribution examples over OOD examples as well as for more informative examples among in-distribution ones. The input to the meta-model, which includes the target and OOD labels, is obtained for free from each AL round's query set by leveraging the multi-round property of AL. Moreover, the meta-model is optimized more stably through a novel regularization inspired by the *skyline* query [17, 18] popularly used in multi-objective optimization. As a result, MQ-Net can guide the learning of the target model by providing the best balancing between purity and informativeness throughout the entire training period.

Overall, our main contributions are summarized as follows:

1. We formulate the *purity-informativeness dilemma*, which hinders the usability of open-set AL in real-world applications.

2. As our answer to the dilemma, we propose a novel AL framework, MQ-Net, which keeps finding the best trade-off between purity and informativeness.

3. Extensive experiments on CIFAR10, CIFAR100, and ImageNet show that MQ-Net improves the classification accuracy consistently when the OOD ratio changes from 10% to 60% by up to 20.14%.

2 Related Work

2.1 Active Learning and Open-set Recognition

Active Learning is a learning framework to reduce the human labeling cost by finding the most informative examples given unlabeled data [9]. One representative directions is uncertainty-based sampling. Conventional approaches have been developed based on the prediction probability, *e.g.*, soft-max confidence [19, 3], margin [20], and entropy [21]. Another approaches have exploited the components of DNNs for estimating uncertainty. Some of them obtain uncertainty by using Monte Carlo Dropout throughout multiple forward passes [22, 23, 24]. LL [5] predicts the loss of unlabeled examples by jointly learning a small loss prediction module with target model. Meanwhile, diversity-based sampling has been widely studied. To incorporate diversity, most approaches use a clustering algorithm [6, 25] or core-set selection algorithm [7]. Notably, CoreSet [7] finds the set of examples having the highest distance coverage on the entire unlabeled data. BADGE [8] is a hybrid of uncertainty-and diversity-based sampling which uses k-MEANS clustering in the gradient embedding space. However, this family of approaches is not appropriate for open-set AL since they do not consider how to handle the OOD examples for query selection.

Open-set Recognition (OSR) is a detection task to recognize the examples outside of the target domain [12]. Closely related to this purpose, OOD detection has been actively studied [26]. Recent work can be categorized as: classifier-dependent, density-based, and self-supervised approaches. The classifier-dependent approach leverages a pre-trained classifier and introduces several scoring functions, such as Uncertainty [27], ODIN [28], mahalanobis distance (MD) [29], and Energy [30]. Recently, ReAct [31] shows that rectifying penultimate activations can enhance most of the aforementioned classifier-dependent OOD scores. The density-based approach learns an auxiliary generative model like variational auto-encoder to compute likelihood-based OOD scores [32, 33, 34]. In contrast, most self-supervised approaches leverage contrastive learning [35, 36, 37]. CSI shows that contrasting with distributionally-shifted augmentations can considerably enhance the OSR performance [35].

The OSR performance of classifier-dependent approaches degrades significantly if the classifier performs poorly [38]. Similarly, the performance of density-based and self-supervised approaches heavily resorts to the amount of clean IN data [34, 35]. Therefore, open-set active learning is a challenging problem to be resolved by simply applying OSR approaches since it is difficult to obtain high-quality classifiers and sufficient IN data at early AL rounds.

2.2 Open-set Active learning

Two recent approaches have attempted to deal with the open-set noise for active learning [13, 16]. Both approaches attempt to increase purity in query selection by effectively filtering out the OOD examples. CCAL [13] learns two contrastive coding models where each is for calculating informativeness or OODness of an example, and then it combines two scores into one using a heuristic balancing rule. SIMILAR [16] selects a pure and core set of examples that maximize the distance coverage on the entire unlabeled data while minimizing the distance coverage to the already identified OOD data. However, CCAL and SIMILAR are often worse than standard AL methods because they always put more higher weights on purity, although informativeness should be emphasized when the open-set noise ratio is small or in later AL rounds. This calls for the development of a new solution to carefully find the best trade-off between purity and informativeness in open-set AL.

3 Purity-Informativeness Dilemma in Open-set Active Learning

In this section, we define the problem of open-set active learning and then introduce the purity-informativeness delimma in query selection.

3.1 Problem Statement

Let $\mathcal{D}_{IN}$ and $\mathcal{D}_{OOD}$ be the IN and OOD data, where the example's label of $\mathcal{D}_{OOD}$ does not belong to any of the k known (pre-defined) labels $Y = \{y_i\}_{i=1}^{k}$. Thus, an unlabeled set is a mixture of IN and OOD examples, $U = \{X_{IN}, X_{OOD}\}$, *i.e.*, $X_{IN} \sim \mathcal{D}_{IN}$ and $X_{OOD} \sim \mathcal{D}_{OOD}$. In the open-set AL, a human oracle is requested to assign a known label y to an IN example $x \in X_{IN}$ with a labeling cost c_{IN}, while an OOD example $x \in X_{OOD}$ is marked as open-set noise with a labeling cost c_{OOD}.

127 AL imposes restrictions on the labeling budget b every round. It starts with a small labeled set S_L,
128 consisting of both labeled IN and OOD examples. The initial labeled set S_L improves by adding
129 a small but maximally-informative labeled query set S_Q per round, i.e., $S_L \leftarrow S_L \cup S_Q$, where the
130 labeling cost for S_Q by the oracle does not exceed the labeling budget b. Hence, the goal of open-set
131 AL is defined to construct the optimal query set S_Q^*, minimizing the loss for the unseen target IN
132 data $T_{IN} \sim \mathcal{D}_{IN}$, where $T_{IN} \cap X_{IN} = \emptyset$. The difference from standard AL is that the labeling cost
133 for OOD examples is introduced, where the labeling budget is wasted when OOD examples are
134 misclassified as informative ones.

135 Formally, let $C(\cdot)$ be the labeling cost function for a given unlabeled set; then, each round of open-set
136 AL is formulated to find the best query set S_Q^* as

$$S_Q^* = \underset{S_Q: \, C(S_Q) \leq b}{\operatorname{argmin}} \; \mathbb{E}_{(x,y) \in T_{IN}} \Big[\ell_{cls} \big(f(x; \Theta_{S_L \cup S_Q}), y \big) \Big],$$
$$\text{where } C(S_Q) = \sum_{x \in S_Q} \big(\mathbb{1}_{[x \in X_{IN}]} c_{IN} + \mathbb{1}_{[x \in X_{OOD}]} c_{OOD} \big). \tag{1}$$

137 Here, $f(\cdot; \Theta_{S_L \cup S_Q})$ denotes the target model trained for only IN examples in $S_L \cup S_Q$, and ℓ_{cls} is a
138 certain loss function for classification. For each AL round, all the examples in S_Q^* are removed from
139 the unlabeled set U and then added to the accumulated labeled set S_L along with their labels. This
140 procedure repeats for the total number r of rounds.

3.2 Purity-Informativeness Dilemma

142 An ideal approach for open-set AL would be to increase both purity and informativeness of a
143 query set by completely suppressing selection of OOD examples and accurately querying the most
144 informative examples among the remaining IN ones. However, the ideal approach is infeasible
145 because overly emphasizing purity in query selection does not promote example informativeness and
146 *vice versa*. Specifically, OOD examples with low purity scores mostly exhibit high informativeness
147 scores because they share neither class-distinctive features nor other inductive biases with the IN
148 examples [14, 15]. We call this trade-off in query selection as the *purity-informativeness dilemma*,
149 which is our new finding expected to trigger a lot of subsequent work.

150 To address this dilemma, we need to consider the proper weights of a purity score and an informative
151 score when they are combined. Let $\mathcal{P}(x)$ be a purity score of an example x which can be measured
152 by any existing OOD scores, e.g., negative energy [30], and $\mathcal{I}(x)$ be an informativeness score of an
153 example x from any standard AL strategies, e.g., uncertainty [3] and diversity [25]. Next, supposing
154 $z_x = \langle \mathcal{P}(x), \mathcal{I}(x) \rangle$ is a tuple[1] of available purity and informativeness scores for an example x. Then,
155 a score combination function $\Phi(z_x)$, where $z_x = \langle \mathcal{P}(x), \mathcal{I}(x) \rangle$, is defined to return an overall score
156 that indicates the necessity of x being included in the query set.

157 Given two unlabeled examples x_i and x_j, if $\mathcal{P}(x_i) > \mathcal{P}(x_j)$ and $\mathcal{I}(x_i) > \mathcal{I}(x_j)$, it is clear to favor
158 x_i over x_j based on $\Phi(z_{x_i}) > \Phi(z_{x_j})$. However, due to the purity-informativeness dilemma, if
159 $\mathcal{P}(x_i) > \mathcal{P}(x_j)$ and $\mathcal{I}(x_i) < \mathcal{I}(x_j)$ or $\mathcal{P}(x_i) < \mathcal{P}(x_j)$ and $\mathcal{I}(x_i) > \mathcal{I}(x_j)$, it is very challenging
160 to determine the dominance between $\Phi(z_{x_i})$ and $\Phi(z_{x_j})$. In order to model $\Phi(\cdot)$, we mainly focus
161 on leveraging *meta-learning*, which is a more agnostic approach to resolve the dilemma other than
162 several heuristic approaches, such as linear combination and multiplication.

4 Meta-Query-Net

164 We incorporates a meta-model, named *Meta-Query-Net (MQ-Net)*, which aims to learn a meta-score
165 function for the purpose of identifying the query set. In the presence of open-set noise, MQ-Net
166 outputs the meta-score for unlabeled examples to achieve the best balance between purity and
167 informativeness in the selected query set. In this section, we introduce the notion of a self-validation
168 set to guide the meta-model in a supervised manner and then demonstrate the meta-objective of
169 MQ-Net for training. Then, we propose a novel skyline constraint used in optimization, which helps
170 MQ-Net capture the obvious preference among unlabeled examples when a clear dominance exists.
171 Next, we present a way of converting the purity and informativeness scores estimated by existing
172 methods for use in MQ-Net. The overview of MQ-Net is illustrated in Figure 2.

---
[1]It is not necessarily to be a tuple since the number of available scores could be more than two, but we only
use one purity and one informativeness scores for simplicity. We leave the extension as future work.

4.1 Training Objective with Self-validation Set

The parameters $\mathbf{w}$ contained in MQ-Net $\Phi(\cdot; \mathbf{w})$ is optimized in a supervised manner. For a clean supervision, a validation data is required for training. Without assuming a hard-to-obtain clean validation set, we propose to use a *self-validation* set, which is instantaneously generated every AL round. In detail, we obtain a labeled query set S_Q by the oracle, consisting of a labeled IN set and an identified OOD set in every round. As the query set S_Q is unseen for the

Figure 2: Overview of MQ-Net.

target Θ and meta models $\mathbf{w}$ at the current round, we can exploit it as a self-validation set to train MQ-Net. This self-validation set eliminates the need for a clean validation set in meta-learning.

Given the ground-truth labels in the self-validation set, it is feasible to guide MQ-Net to be trained to resolve the purity-informativeness dilemma by designing an appropriate meta-objective. It is based on a cross-entropy loss for classification because a loss value of training examples has been proven to be effective in identifying high informativeness examples [5]. The conventional loss value by a target model Θ is masked to be *zero* if $x \in X_{OOD}$ since OOD examples are useless for AL,

$$\ell_{mce}(x) = \mathbb{1}_{[l_x=1]} \ell_{ce}\big(f(x; \Theta), y\big), \tag{2}$$

where l is a true binary IN label, *i.e.*, 1 for IN examples and 0 for OOD examples, which can be reliably obtained from the self-validation set. This *masked* loss, ℓ_{mce}, preserves the informativeness of IN examples while excluding OOD examples. Given a self-validation data S_Q, the meta-objective is defined such that MQ-Net parameterized by $\mathbf{w}$ outputs a high (or low) meta-score $\Phi(z_x; \mathbf{w})$ if an example x's masked loss value is large (or small),

$$\mathcal{L}(S_Q) = \sum_{i \in S_Q} \sum_{j \in S_Q} \max\Big(0, -\text{Sign}\big(\ell_{mce}(x_i), \ell_{mce}(x_j)\big) \cdot \big(\Phi(z_{x_i}; \mathbf{w}) - \Phi(z_{x_j}; \mathbf{w}) + \eta\big)\Big)$$

$$s.t. \quad \forall x_i, x_j, \text{ if } \mathcal{P}(x_i) > \mathcal{P}(x_j) \text{ and } \mathcal{I}(x_i) > \mathcal{I}(x_j), \text{ then } \Phi(z_{x_i}; \mathbf{w}) > \Phi(z_{x_j}; \mathbf{w}), \tag{3}$$

where $\eta > 0$ is a constant margin for the ranking loss, and $\text{Sign}(a, b)$ is an indicator function that returns $+1$ if $a > b$, 0 if $a = b$, and -1 otherwise. Hence, $\Phi(z_{x_i}; \mathbf{w})$ is forced to be higher than $\Phi(z_{x_j}; \mathbf{w})$ if $\ell_{mce}(x_i) > \ell_{mce}(x_j)$; in contrast, $\Phi(z_{x_i}; \mathbf{w})$ is forced to be lower than $\Phi(z_{x_j}; \mathbf{w})$ if $\ell_{mce}(x_i) < \ell_{mce}(x_j)$. Two OOD examples do not affect the optimization because they do not have any priority between them, *i.e.*, $\ell_{mce}(x_i) = \ell_{mce}(x_j)$.

In addition to the ranking loss, we add a regularization term named the *skyline* constraint (*i.e.*, the second line) in the meta-objective Eq. (3), which is inspired by the skyline query which aims to narrow down a search space in a large-scale database by keeping only those items that are not worse than any other [17, 18]. Specifically, in the case of $\mathcal{P}(x_i) > \mathcal{P}(x_j)$ and $\mathcal{I}(x_i) > \mathcal{I}(x_j)$, the condition $\Phi(z_{x_i}; \mathbf{w}) > \Phi(z_{x_j}; \mathbf{w})$ must always hold in our objective, and hence we make this proposition as the skyline constraint. This simple yet intuitive regularization is very helpful for achieving a meta-model that better judges the importance of purity or informativeness. We provide an ablation study on the skyline constraint in Section 5.4.

4.2 Architecture of MQ-Net

MQ-Net is parameterized by a multi-layer perceptron (MLP), a widely-used deep learning architecture for meta-learning [39]. A challenge here is that the proposed skyline constraint in Eq. (3) does not hold with a standard MLP model. To satisfy the skyline constraint, the meta-score function $\Phi(\cdot; \mathbf{w})$ should be a monotonic non-decreasing function because the output (meta-score) of MQ-Net for an example x_i must be higher than that for another example x_j if the two factors (purity and informativeness) of x_i are both higher than those of x_j. The MLP model consists of multiple matrix multiplications with non-linear activation functions such as ReLU and Sigmoid. In order for the MLP model to be monotonically non-decreasing, all the parameters in $\mathbf{w}$ for $\Phi(\cdot; \mathbf{w})$ should be *non-negative*, as proven by Theorem 4.1.

Theorem 4.1. *For any MLP meta-model $\mathbf{w}$ with a meta-score function $\Phi(z; \mathbf{w}) \colon \mathbb{R}^d \to \mathbb{R}$, the skyline constraints holds if $\mathbf{w} \succeq 0$ and $z(\in \mathbb{R}^d) \succeq 0$, where $\succeq$ is the component-wise inequality.*

Proof. An MLP model is involved with matrix multiplication and composition with activation functions, which are characterized by three basic operators: *(1) addition*: $h(z) = f(z) + g(z)$, *(2) multiplication*: $h(z) = f(z) \times g(z)$, and *(3) composition*: $h(z) = f \circ g(z)$. These three operators are guaranteed to be non-decreasing functions if the parameters of the MLP model are all non-negative, because the non-negative weights guarantee all decomposed scalar operations in MLP to be non-decreasing functions. Combining the three operators, the MLP model $\Phi(z; \mathbf{w})$, where $\mathbf{w} \succeq 0$, naturally becomes a monotonic non-decreasing function for each input dimension. Refer to Appendix A for the complete proof. □

In implementation, non-negative weights are guaranteed by applying a ReLU function to meta-model parameters. Since the ReLU function is differentiable, MQ-Net can be trained with the proposed objective in an end-to-end manner. Putting this simple modification, the skyline constraint is preserved successfully without introducing any complex loss-based regularization term. The only remaining condition is that each input of MQ-Net must be a vector of non-negative entries.

4.3 Active Learning with MQ-Net

4.3.1 Meta-input Conversion

MQ-Net receives $z_x = \langle \mathcal{P}(x), \mathcal{I}(x) \rangle$ and then returns a meta-score for query selection. All the scores for the input of MQ-Net must be positive to preserve the skyline constraint, *i.e.*, $z \succeq 0$. Existing OOD and AL query scores are converted to the meta-input. The methods used for calculating the scores are orthogonal to our framework. The OOD score $\mathcal{O}(\cdot)$ is conceptually the opposite of purity and varies in its scale; hence, we convert it to a purity score by $\mathcal{P}(x) = \mathrm{Exp}(\mathrm{Normalize}(-\mathcal{O}(x)))$, where $\mathrm{Normalize}(\cdot)$ is the z-score normalization. This conversion guarantees the purity score to be positive. Similarly, for the informativeness score, we convert an existing AL query score $\mathcal{Q}(\cdot)$ to $\mathcal{I}(x) = \mathrm{Exp}(\mathrm{Normalize}(\mathcal{Q}(x)))$.

4.3.2 Overall Procedure

For each AL round, a target model is trained via stochastic gradient descent (SGD) on mini-batches sampled from the IN examples in the current labeled set S_L. Based on the current target model, the purity and informative scores are computed by using certain OOD and AL query scores. The querying phase is then performed by selecting the examples S_Q with the highest meta-scores within the labeling budget b. The query set S_Q is used as the self-validation set for training MQ-Net at the current AL round. The trained MQ-Net is used at the next AL round. The alternating procedure of updating the target model and the meta-model repeats for a given number r of AL rounds. The pseudocode of MQ-Net can be found in Appendix B.

5 Experiments

5.1 Experiment Setting

Datasets. We perform the active learning task on three benchmark datasets; CIFAR10 [40], CIFAR100 [40], and ImageNet [41]. Following the 'split-dataset' setup in open-world learning literature [13, 16, 42], we divide each dataset into two subsets: (1) the target set with IN classes and (2) the noise set with OOD classes. Specifically, CIFAR10 is split into the target set with four classes and the noise set with the rest six classes; CIFAR100 into the two sets with 40 and 60 classes; and ImageNet into the two sets with 50 and 950 classes. The entire target set is used as the unlabeled IN data, while only a part of classes in the noise set is selected as the unlabeled OOD data according to the given noise ratio. In addition, following ODD detection literature [27, 32], we also consider the 'cross-dataset' setup, which mixes a certain dataset with two external OOD datasets collected from different domains, such as LSUN [43] and Places365 [44]. For sake of space, we present all the results on the cross-dataset setup in Appendix D.

Algorithms. We compare MQ-Net with four standard AL and two recent open-set AL approaches.

- *Standard AL*: The four methods perform AL without any processing for open-set noise: (1) CONF [3] queries the most uncertain examples with the lowest softmax confidence in the prediction, (2) CORESET [7] queries the most diverse examples with the highest coverage in the representation space, (3) LL [5] queries the examples having the largest predicted loss by jointly learning a loss prediction module, and (4) BADGE [8] considers both uncertainty and diversity by querying the most representative examples in the gradient via k-means$^+$ clustering [45].

(a) Accuracy comparison over AL rounds on CIFAR10 with open-set noise of 10%, 20%, 40%, and 60%.

(b) Accuracy comparison over AL rounds on CIFAR100 with open-set noise of 10%, 20%, 40%, and 60%.

(c) Accuracy comparison over AL rounds on ImgeNet with open-set noise of 10%, 20%, 40%, and 60%.

Figure 3: Test accuracy over AL rounds for CIFAR10, CIFAR100, and ImageNet with varying open-set noise ratios.

- *Open-set AL*: The two methods tend to put more weight on the examples with high purity: (1) CCAL [13] learns two contrastive coding models for calculating informativeness and OODness, and then it combines the two scores into one using a heuristic balancing rule, and (2) SIMILAR [16] selects a pure and core set of examples that maximize the distance coverage on the entire unlabeled data while minimizing the distance coverage to the already labeled OOD data.

For all the experiments, regarding the two inputs of MQ-Net, we mainly use CSI [35] and LL [5] for calculating the purity and informativeness scores, respectively. For CSI, as in CCAL, we train a contrastive learner on the entire unlabeled set with open-set noise since the clean in-distribution set is not available in open-set AL. The ablation study in Section 5.4 shows that MQ-Net is also effective with other OOD and AL scores as its input.

Implementation Details. We repeat the three steps—training, querying, and labeling—of AL. The total number r of rounds is set to 10. Following the prior open-set AL setup [13, 16], we set the labeling cost $c_{IN} = 1$ for IN examples and $c_{OOD} = 1$ for OOD examples. For the class-split setup, the labeling budget b per round is set to 500 for CIFAR10/100 and 1,000 for ImageNet. Regarding the open-set noise ratio τ, we configure five different levels from light to heavy noise in $\{10\%, 20\%, 40\%, 60\%\}$. In the case of $\tau = 0\%$ (no noise), MQ-Net naturally discard the purity score and only use the informativeness score for query selection, since the self-validation set does not contain any OOD examples. The initial labeled set is randomly selected uniformly at random from the entire unlabeled set within the labeling budget b. We report the average results of five runs with different class splits. See Appendix C for more implementation details with training configurations.

5.2 Open-set Noise Robustness

5.2.1 Results over AL Rounds

Figure 3 illustrates the test accuracy of the target model over AL rounds on the two CIFAR datasets. MQ-Net achieves the highest test accuracy in most AL rounds, thereby reaching the best test accuracy at the final round in every case for various datasets and noise ratios. Compared with the two existing open-set AL methods, CCAL and SIMILAR, MQ-Net shows a steeper improvement in test accuracy over rounds by resolving the purity-informativeness dilemma in query selection. For example, the performance gap between MQ-Net and the two open-set AL methods gets larger after the sixth round, as shown in Figure 3(b), because CCAL and SIMILAR mainly depend on purity in query selection, which conveys less informative information to the classifier. For a better classifier, informative

Table 1: Last test accuracy (%) at the final round for CIFAR10, CIFAR100, and ImageNet. The best results are in bold, and the second best results are underlined.

Datasets		CIFAR10 (4:6 split)				CIFAR100 (40:60 split)				ImageNet (50:950 split)			
Noise Ratio		10%	20%	40%	60%	10%	20%	40%	60%	10%	20%	40%	60%
Standard AL	CONF	92.83	91.72	88.69	85.43	62.84	60.20	53.74	45.38	63.56	62.56	51.08	45.04
	CORESET	91.76	91.06	89.12	86.50	63.79	62.02	56.21	48.33	63.64	62.24	55.32	49.04
	LL	92.09	91.21	89.41	86.95	65.08	64.04	56.27	48.49	63.28	61.56	55.68	47.3
	BADGE	92.80	91.73	89.27	86.83	62.54	61.28	55.07	47.60	64.84	61.48	54.04	47.80
Open-set AL	CCAL	90.55	89.99	88.87	87.49	61.20	61.16	56.70	50.20	61.68	60.70	56.60	51.16
	SIMILAR	89.92	89.19	88.53	87.38	60.07	59.89	56.13	50.61	63.92	61.40	56.48	52.84
Proposed	**MQ-Net**	**93.10**	**92.10**	**91.48**	**89.51**	**66.44**	**64.79**	**58.96**	**52.82**	**65.36**	**63.08**	**56.95**	**54.11**
% improve over 2nd best		0.32	0.40	2.32	2.32	2.09	1.17	3.99	4.37	0.80	1.35	0.62	2.40
% improve over the least		3.53	3.26	3.33	4.78	10.6	8.18	9.71	16.39	5.97	3.92	11.49	20.14

(a) The output of MQ-Net over AL rounds (Round 3, 5, 7, and 9) with 10% noise.

(b) The final round's output of MQ-Net with varying noise ratios (10%, 20%, 40%, and 60%).

Figure 4: Visualization of the query score distribution of MQ-Net on CIFAR100. x- and y-axis indicate the normalized informativeness and purity scores, respectively. Background color represents the query score of MQ-Net; the red is high, and the blue is low. Gray points represent unlabeled data, and blue and red points are the IN and OOD examples in the query set, respectively. The slope of the tangent line on the lowest scored example in the query set is displayed together; the steeper the slope, the more informativeness is emphasized in query selection.

examples should be favored at a later AL round due to the sufficient number of IN examples in the labeled set. In contrast, MQ-Net keeps improving the test accuracy even in a later AL round by finding the best balancing between purity and informativeness in its query set. More analysis of MQ-Net associated with the purity-informativeness dilemma is discussed in Section 5.3.

5.2.2 Results with Varying Noise Ratios

Table 1 summarizes the last test accuracy at the final AL round for three datasets with varying levels of open-set noise. Overall, the last test accuracy of MQ-Net is the best in every case. This superiority concludes that MQ-Net successfully find the best trade-off between purity and informativeness in terms of AL accuracy regardless of the noise ratio. In general, the performance improvement becomes larger with the increase in the noise ratio. On the other hand, the two open-set AL approaches are even worse than the four standard AL approaches when noise ratio is less than 20%. This trend confirms that increasing informativeness is more crucial than increasing purity when the noise ratio is small. In addition, in CIFAR10 relatively easier than others, CCAL and SIMILAR are inferior to the non-robust AL method, LL, even with 40% noise. Highly informative examples are still beneficial when the performance of a classifier is saturated in the presence of open-set noise.

5.3 Answers to the Purity-Informativeness Dilemma

The high robustness of MQ-Net in Table 1 and Figure 3 is mainly attributed to its ability to keep finding the best trade-off between purity and informativeness. Figure 4(a) illustrates the preference change of MQ-Net between purity and informativeness throughout the AL rounds. As the round progresses, MQ-Net automatically raises the importance of informativeness rather than purity; the slope of the tangent line keeps steepening from -0.74 to -1.21. This trend implies that more

Table 2: Effect of the meta inputs to MQ-Net.

Dataset		CIFAR10 (4:6 split)			
Noise Ratio		10%	20%	40%	60%
Standard AL	BADGE	92.80	91.73	89.27	86.83
Open-set AL	CCAL	90.55	89.99	88.87	87.49
MQ-Net	CONF-ReAct	93.21	91.89	89.54	87.99
	CONF-CSI	**93.28**	**92.40**	91.43	89.37
	LL-ReAct	92.34	91.85	90.08	88.41
	LL-CSI	93.10	92.10	**91.48**	**89.51**

Table 3: Efficacy of the self-validation set.

Dataset		CIFAR10 (4:6 split)			
Noise Ratio		10%	20%	40%	60%
MQ-Net	Query set	**93.10**	**92.10**	**91.48**	**89.51**
	Random	92.10	91.75	90.88	87.65

Table 4: Efficacy of the skyline constraint.

	Noise Ratio	10%	20%	40%	60%
MQ-Net	w/ skyline	**93.10**	**92.10**	**91.48**	**89.51**
	w/o skyline	87.25	86.29	83.61	81.67

informative examples are required to be labeled when the target classifier becomes mature. Figure 4(b) describes the preference change of MQ-Net with varying noise ratios. Contrary to the trend over AL rounds, as the noise ratio gets higher, MQ-Net prefers purity more over informativeness.

5.4 Ablation Studies

Various Combination of Meta-input. MQ-Net can design its purity and informativeness scores by leveraging diverse metrics in the existing OOD detection and AL literature. Table 2 shows the final round test accuracy on CIFAR10 for the four variants of score combinations, each of which is constructed by a combination of two purity scores and two informativeness scores; each purity score is induced by the two recent OOD detection methods, ReAct [31] and CSI, while each informativeness score is converted from the two existing AL methods, CONF and LL. "CONF-ReAct" denotes a variant that uses ReAct as the purity score and CONF as the informativeness score.

Overall, all the variants perform better than compared standard and open-set AL baselines in every noise level. Refer to Table 2 for detailed comparison. This result concludes that MQ-Net can be generalized over different types of meta-input owing to the learning flexibility of MLPs. Interestingly, the variant using CSI as the purity score is consistently better than those using ReAct. ReAct, a classifier-dependent OOD score, performs very poorly in earlier AL rounds where the performance of the classifier is not sufficient. A more detailed analysis of the two OOD detectors, ReAct and CSI, over AL rounds, can be found in Appendix E.

Efficacy of Self-validation Set. MQ-Net can be trained with an independent validation set available, instead of using the proposed self-validation set. We generate the independent validation set by randomly sampling examples with their ground-truth labels from the entire data, which is not overlapped with the unlabeled set used for AL, where its size is exactly the same with the self-validation set. As can be seen from Table 3, it is of interest to see that our self-validation set performs better than the random validation set. The two validation sets have a major difference in data distributions; the self-validation set mainly consists of the examples with highest meta-scores among the remaining unlabeled data per round, while the random validation set consists of random examples. We conclude that the meta-score of MQ-Net has the potential for constructing a high-quality validation set in addition to query selection.

Efficacy of Skyline Constraint. Table 4 demonstrates the final round test accuracy of MQ-Net with or without the skyline constraint. For the latter, a standard 2-layer MLP is used as the meta-network architecture without any modification. The performance of MQ-Net degrades significantly without the skyline constraint, meaning that the non-constrained MLP can easily overfit to the small-sized self-validation set, thereby assigning high output scores on less-pure and less-informative examples. Therefore, the violation of the skyline constraint in optimization makes MQ-Net hard to balance between the purity and informativeness scores in query selection.

6 Conclusion

We propose MQ-Net, a novel meta-model for open-set active learning that deals with the purity-informativeness dilemma. MQ-Net finds the best balancing between the two factors, being adaptive to the noise ratio and target model status. A clean validation set for the meta-model is obtained for free by exploiting the procedure of active learning. A ranking loss with the skyline constraint optimizes MQ-Net to make the output a legit meta-score that keeps the obvious order of two examples. MQ-Net is shown to yield the best test accuracy throughout the entire active learning rounds, thereby empirically proving the correctness of our solution to the purity-informativeness dilemma. Overall, we expect that our work will raise the practical usability of active learning with open-set noise.

References

[1] Hwanjun Song, Minseok Kim, Dongmin Park, Yooju Shin, and Jae-Gil Lee. Learning from noisy labels with deep neural networks: A survey. *IEEE Transactions on Neural Networks and Learning Systems*, pages 1–19, 2022.

[2] Burr Settles. Active learning literature survey. Technical Report 1648, University of Wisconsin-Madison, Department of Computer Sciences, 2009.

[3] Dan Wang and Yi Shang. A new active labeling method for deep learning. In *IJCNN*, pages 112–119, 2014.

[4] William H Beluch, Tim Genewein, Andreas Nürnberger, and Jan M Köhler. The power of ensembles for active learning in image classification. In *CVPR*, pages 9368–9377, 2018.

[5] Donggeun Yoo and In So Kweon. Learning loss for active learning. In *CVPR*, pages 93–102, 2019.

[6] Hieu T Nguyen and Arnold Smeulders. Active learning using pre-clustering. In *ICML*, 2004.

[7] Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. In *ICLR*, 2018.

[8] Jordan T. Ash, Chicheng Zhang, Akshay Krishnamurthy, John Langford, and Alekh Agarwal. Deep batch active learning by diverse, uncertain gradient lower bounds. In *ICLR*, 2020.

[9] Pengzhen Ren, Yun Xiao, Xiaojun Chang, Po-Yao Huang, Zhihui Li, Brij B Gupta, Xiaojiang Chen, and Xin Wang. A survey of deep active learning. *ACM Computing Surveys (CSUR)*, 54(9):1–40, 2021.

[10] Ahmet Uyar and Rabia Karapinar. Investigating the precision of web image search engines for popular and less popular entities. *Journal of Information Science*, 43(3):378–392, 2017.

[11] Mehrdad CheshmehSohrabi and Elham Adnani Sadati. Performance evaluation of web search engines in image retrieval: An experimental study. *Information Development*, pages 1–13, 2021.

[12] Chuanxing Geng, Sheng-jun Huang, and Songcan Chen. Recent advances in open set recognition: A survey. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 43(10):3614–3631, 2021.

[13] Pan Du, Suyun Zhao, Hui Chen, Shuwen Chai, Hong Chen, and Cuiping Li. Contrastive coding for active learning under class distribution mismatch. In *ICCV*, pages 8927–8936, 2021.

[14] Hung-Yu Tseng, Hsin-Ying Lee, Jia-Bin Huang, and Ming-Hsuan Yang. Cross-domain few-shot classification via learned feature-wise transformation. In *ICLR*, 2020.

[15] Hongxin Wei, Lue Tao, Renchunzi Xie, and Bo An. Open-set label noise can improve robustness against inherent label noise. In *NeurIPS*, 2021.

[16] Suraj Kothawade, Nathan Beck, Krishnateja Killamsetty, and Rishabh Iyer. Similar: Submodular information measures based active learning in realistic scenarios. In *NeurIPS*, 2021.

[17] Christos Kalyvas and Theodoros Tzouramanis. A survey of skyline query processing. *arXiv preprint arXiv:1704.01788*, 2017.

[18] Ke Deng, Xiaofang Zhou, and Heng Tao Shen. Multi-source skyline query processing in road networks. In *ICDE*, pages 796–805, 2007.

[19] David D Lewis and Jason Catlett. Heterogeneous uncertainty sampling for supervised learning. In *ICML*, pages 148–156. 1994.

[20] Dan Roth and Kevin Small. Margin-based active learning for structured output spaces. In *ECML*, pages 413–424, 2006.

[21] Ajay J Joshi, Fatih Porikli, and Nikolaos Papanikolopoulos. Multi-class active learning for image classification. In *CVPR*, pages 2372–2379, 2009.

[22] Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep bayesian active learning with image data. In *ICML*, pages 1183–1192, 2017.

[23] Andreas Kirsch, Joost Van Amersfoort, and Yarin Gal. Batchbald: Efficient and diverse batch acquisition for deep bayesian active learning. In *NeurIPS*, 2019.

[24] Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *ICML*, pages 1050–1059, 2016.

[25] Gui Citovsky, Giulia DeSalvo, Claudio Gentile, Lazaros Karydas, Anand Rajagopalan, Afshin Rostamizadeh, and Sanjiv Kumar. Batch active learning at scale. In *NeurIPS*, 2021.

[26] Jingkang Yang, Kaiyang Zhou, Yixuan Li, and Ziwei Liu. Generalized out-of-distribution detection: A survey. *arXiv preprint arXiv:2110.11334*, 2021.

[27] Dan Hendrycks and Kevin Gimpel. A baseline for detecting misclassified and out-of-distribution examples in neural networks. In *ICLR*, 2017.

[28] Shiyu Liang, Yixuan Li, and Rayadurgam Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *ICLR*, 2018.

[29] Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. In *ICLR*, 2018.

[30] Weitang Liu, Xiaoyun Wang, John D Owens, and Yixuan Li. Energy-based out-of-distribution detection. In *NeurIPS*, 2020.

[31] Yiyou Sun, Chuan Guo, and Yixuan Li. React: Out-of-distribution detection with rectified activations. In *NeurIPS*, 2021.

[32] Jie Ren, Peter J Liu, Emily Fertig, Jasper Snoek, Ryan Poplin, Mark Depristo, Joshua Dillon, and Balaji Lakshminarayanan. Likelihood ratios for out-of-distribution detection. In *NeurIPS*, 2019.

[33] Joan Serrà, David Álvarez, Vicenç Gómez, Olga Slizovskaia, José F Núñez, and Jordi Luque. Input complexity and out-of-distribution detection with likelihood-based generative models. In *ICLR*, 2019.

[34] Eric Nalisnick, Akihiro Matsukawa, Yee Whye Teh, Dilan Gorur, and Balaji Lakshminarayanan. Do deep generative models know what they don't know? In *ICLR*, 2019.

[35] Jihoon Tack, Sangwoo Mo, Jongheon Jeong, and Jinwoo Shin. Csi: Novelty detection via contrastive learning on distributionally shifted instances. In *NeurIPS*, pages 11839–11852, 2020.

[36] Jim Winkens, Rudy Bunel, Abhijit Guha Roy, Robert Stanforth, Vivek Natarajan, Joseph R Ledsam, Patricia MacWilliams, Pushmeet Kohli, Alan Karthikesalingam, Simon Kohl, et al. Contrastive training for improved out-of-distribution detection. *arXiv preprint arXiv:2007.05566*, 2020.

[37] Vikash Sehwag, Mung Chiang, and Prateek Mittal. Ssd: A unified framework for self-supervised outlier detection. In *ICLR*, 2021.

[38] Sagar Vaze, Kai Han, Andrea Vedaldi, and Andrew Zisserman. Open-set recognition: A good closed-set classifier is all you need. In *ICLR*, 2021.

[39] Jun Shu, Qi Xie, Lixuan Yi, Qian Zhao, Sanping Zhou, Zongben Xu, and Deyu Meng. Metaweight-net: Learning an explicit mapping for sample weighting. In *NeurIPS*, 2019.

[40] Alex Krizhevsky. Learning multiple layers of features from tiny images. Master's thesis, University of Toronto, 2009.

[41] Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. ImageNet: A large-scale hierarchical image database. In *CVPR*, pages 248–255, 2009.

[42] Kuniaki Saito, Donghyun Kim, and Kate Saenko. OpenMatch: Open-set semi-supervised learning with open-set consistency regularization. In *NeurIPS*, 2021.

[43] Fisher Yu, Ari Seff, Yinda Zhang, Shuran Song, Thomas Funkhouser, and Jianxiong Xiao. LSUN: Construction of a large-scale image dataset using deep learning with humans in the loop. *arXiv preprint arXiv:1506.03365*, 2015.

[44] Bolei Zhou, Agata Lapedriza, Aditya Khosla, Aude Oliva, and Antonio Torralba. Places: A 10 million image database for scene recognition. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 40(6):1452–1464, 2017.

[45] David Arthur and Sergei Vassilvitskii. k-means++: The advantages of careful seeding. Technical report, Stanford, 2006.