ADVERSARIALLY GUIDED ACTOR-CRITIC

ABSTRACT

Despite definite success in deep reinforcement learning problems, actor-critic algorithms are still confronted with sample inefficiency in complex environments. These methods consider a policy (the actor) and a value (the critic) whose respective losses are obtained using different motivations and approaches. We introduce a third protagonist, the adversary. While this adversary mimics the actor by minimizing the KL-divergence between their respective action distributions, the actor maximizes the log-probability difference between its action and that of the adversary in combination with maximizing expected rewards. This novel objective stimulates the actor to follow strategies that could not have been correctly predicted from previous trajectories, making its behavior innovative in tasks where the reward is extremely rare. Our experimental analysis shows that the resulting Adversarially Guided Actor-Critic (AGAC) algorithm leads to more exhaustive exploration. Notably, AGAC outperforms current state-of-the-art methods on a set of various hard-exploration and procedurally-generated tasks.

1 INTRODUCTION

Research in deep reinforcement learning (RL) has proven to be successful across a wide range of problems (Silver et al., 2014; Schulman et al., 2016; Lillicrap et al., 2016; Mnih et al., 2016b). Nevertheless, generalization and exploration in RL still represent key challenges that leave most current methods ineffective. First, a battery of recent studies (Farebrother et al., 2018; Zhang et al., 2018a; Song et al., 2019; Cobbe et al., 2019) indicates that current RL methods fail to generalize correctly even when agents have been trained in a diverse set of environments. Second, exploration has been extensively studied in RL; however, most hard-exploration problems use the same training and evaluation environment. Hence, since a well-designed exploration strategy should maximize the information received from a trajectory about an environment, the exploration capabilities may not be appropriately assessed if that information is memorized. In this line of research, we choose to study the exploration capabilities of our method and its ability to generalize to new scenarios. Our evaluation domains will, therefore, be tasks with sparse reward in procedurally-generated environments.

In this work, we propose Adversarially Guided Actor-Critic (AGAC), which reconsiders the actor-critic framework by introducing a third protagonist: the adversary. Its role is to predict the actor's actions correctly. Meanwhile, the actor must not only find the optimal actions to maximize the sum of expected returns, but also counteract the predictions of the adversary. This formulation is lightly inspired by adversarial methods, specifically generative adversarial networks (GANs) (Goodfellow et al., 2014a). Such a link between GANs and actor-critic methods has been formalized by Pfau & Vinyals (2016); however, in the context of a third protagonist, we draw a different analogy. The adversary can be interpreted as playing the role of a discriminator that must predict the actions of the actor and the actor can be considered as playing that of a generator that is led to behave to deceive the predictions of the adversary. This approach has the advantage, as with GANs, that the optimization procedure generates a diversity of meaningful data, corresponding to sequences of actions in AGAC.

This paper analyses and explores how AGAC explicitly drives diversity in the behaviors of the agent while remaining reward-focused, and to which extent this approach allows to adapt to the evolving state space of procedurally-generated environments where the map is constructed differently with each new episode. Moreover, because stability is a legitimate concern since specific instances of adversarial networks were shown to be prone to hyper-parameter sensitivity issues (Arjovsky & Bottou, 2017), we also examine this aspect in our experiments.

The contributions of this work are as follow: (i) we propose a novel actor-critic formulation inspired from adversarial learning (AGAC), (ii) we analyse empirically AGAC on key reinforcement learning aspects such as diversity, exploration and stability, (iii) we demonstrate significant gains in performance on several sparse-reward hard-exploration tasks including procedurally-generated tasks.

2 RELATED WORK

Actor-critic methods (Barto et al., 1983; Sutton, 1984) have been extended to the deep learning setting by Mnih et al. (2016a), who combined deep function approximation and multiple distributed actors to an actor-critic, with strong results on Atari. Since then, many additions have been proposed, be it architectural improvements (Vinyals et al., 2019), better advantage estimation (Schulman et al., 2016), or the incorporation of off-policy elements (Wang et al., 2016; Oh et al., 2018; Flet-Berliac & Preux, 2020). Regularization was shown to improve actor-critic methods, either by enforcing trust regions (Schulman et al., 2015; 2017; Wu et al., 2017), or by correcting for off-policiness (Munos et al., 2016; Gruslys et al., 2017); and recent works analyzed its impact from a theoretical standpoint (Geist et al., 2019; Ahmed et al., 2019; Vieillard et al., 2020). With the exception of Han & Sung (2020), which uses the entropy of the mixture between the policy induced from a replay buffer and the current policy as a regularizer, none of these methods explicitly use regularization to promote exploration.

While introduced in supervised learning, adversarial learning (Goodfellow et al., 2014b; Miyato et al., 2015; Kurakin et al., 2016) was leveraged in several RL works. Ho & Ermon (2016) propose an imitation learning method that uses a discriminator whose task is to distinguish between expert trajectories and those of the agent while the agent tries to match expert behavior to fool the discriminator. Bahdanau et al. (2018) use a discriminator to distinguish goal states from non-goal states based on a textual instruction, and use the resulting model as a reward function. Held et al. (2017) use a GAN to produce sub-goals at the right level of difficulty for the current agent, inducing a form of curriculum. Additionally, Pfau & Vinyals (2016) provide a parallel between GANs and the actor-critic framework.

While exploration is driven in part by the core RL algorithms (Fortunato et al., 2017; Han & Sung, 2020), it is often necessary to resort to exploration-specific techniques. For instance, intrinsic motivation encourages explorative behavior from the agent. Some works use state-visitation counts or pseudo-counts to promote exhaustive exploration (Bellemare et al., 2016a), while others use curiosity rewards, expressed in the magnitude of prediction error from the agent, to push it towards unfamiliar areas of the state space (Burda et al., 2018). Ecoffet et al. (2019) propose a technique akin to tree traversal to explore the environment while learning to come back to promising areas. Eysenbach et al. (2018) show that creating and maintaining diversity in the policy space helps with exploration, even when there is no reward from the environment.

Last but not least, generalization in is a key challenge in RL. Zhang et al. (2018b) showed that, even when the environment is not deterministic, agents can overfit to their training distribution and that it is difficult to distinguish agents likely to generalize to new environments from those that will not. In the same vein, recent work has advocated using procedurally-generated environments, in which a new instance of the environment is sampled when a new episode starts, to assess generalization capabilities better (Justesen et al., 2018; Cobbe et al., 2019). Finally, methods based on network randomization (Igl et al., 2019), noise injection (Lee et al., 2020), and credit assignment (Ferret et al., 2020) have been proposed to reduce the generalization gap for RL agents.

3 BACKGROUND AND NOTATIONS

We place ourselves in the Markov Decision Processes (Puterman, 1994) framework. A Markov Decision Process (MDP) is a tuple $M = \{\mathcal{S}, \mathcal{A}, \mathcal{P}, R, \gamma\}$, where $\mathcal{S}$ is the state space, $\mathcal{A}$ is the action space, $\mathcal{P}$ is the transition kernel, $\mathcal{R}$ is the bounded reward function and $\gamma \in [0, 1)$ is the discount factor. Let $\pi : \mathcal{S} \rightarrow \Delta_{\mathcal{A}})$ denote a stochastic policy. We place ourselves in the infinite-horizon setting, $i.e.$, we seek a policy that optimizes $J(\pi) = \mathbb{E}_\pi[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t)]$. The value of a state is the quantity $V^\pi(s) = \mathbb{E}_\pi[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t)|s_0 = s]$ and the value of a state-action pair $Q^\pi(s, a)$ of performing action a in state s and then following policy π is defined as: $Q^\pi(s, a) = \mathbb{E}_\pi[\sum_{t=0}^{\infty} \gamma^t r(s_t, a_t)|s_0 = s, a_0 = a]$. The advantage function, which quantifies how an action a is better than the average action in state s, is $A^\pi(s, a) = Q^\pi(s, a) - V^\pi(s)$. Finally, the entropy $\mathcal{H}^\pi$ of a policy is calculated as: $\mathcal{H}^\pi(s) = \mathbb{E}_{\pi(\cdot|s)}[-\log \pi(\cdot|s)]$.

Actor-Critic and Deep Policy Gradients. An actor-critic algorithm is composed of two main components: a policy and a value predictor. In deep RL, both the policy and the value function are obtained via parametric estimators; we denote θ and ϕ their respective parameters. The policy is updated via policy gradient, while the value is usually updated via temporal difference or Monte Carlo rollouts. In practice, for a sequence of transitions $\{s_t, a_t, r_t, s_{t+1}\}_{t \in [0,N]}$, we use the following policy gradient loss (including the commonly used entropic penalty):

$$\mathcal{L}_{PG} = \frac{1}{N} \sum_{t'=t}^{t+N} (A_{t'} \log \pi (a_{t'}|s_{t'}, \theta) + \alpha \mathcal{H}^\pi(s_{t'}, \theta)),$$

where α is the entropy coefficient and A_t is the generalized advantage estimator (Schulman et al., 2016) defined as: $A_t = \sum_{t'=t}^{t+N} (\gamma\lambda)^{t'-t}(r_{t'} + \gamma V_{\phi_{\text{old}}}(s_{t'+1}) - V_{\phi_{\text{old}}}(s_{t'}))$, with λ a fixed hyper-parameter and $V_{\phi_{\text{old}}}$ the value function estimator at the previous optimization iteration. To estimate the value function, we solve the non-linear regression problem minimize$_\phi \sum_{t'=t}^{t+N} (V_\phi(s_{t'}) - \hat{V}_{t'})^2$ where $\hat{V}_t = A_t + V_{\phi_{\text{old}}}(s_{t'})$.

4 ADVERSARIALLY GUIDED ACTOR-CRITIC

Our approach promotes more diversified behaviors in the policy gradient, by introducing a third protagonist to the actor-critic framework that should correctly predict the actor's actions. The adversary is therefore optimized to *minimize* the discrepancy between the distributions of the actor policy π and the adversary policy π_{adv}. Meanwhile, the actor must, in addition to finding the optimal actions to *maximize* the sum of expected returns, also counteract the adversary's predictions by *maximizing* the latter discrepancy between π and π_{adv} (see Appendix D for an illustration). This discrepancy, used as a form of exploration bonus, is defined as the difference of log-probabilities (see Eq. (1)), of which the expectation is the Kullback–Leibler divergence

$$D_{\text{KL}}(\pi(\cdot|s) \| \pi_{\text{adv}}(\cdot|s)) = \mathbb{E}_{\pi(\cdot|s)} \left[\log \pi(\cdot|s) - \log \pi_{\text{adv}}(\cdot|s) \right].$$

On the one hand, the adversary is an independent neural network whose weights are updated with a smaller learning rate than that of the target for his predictions (the actor). In this way, the adversary network weights represent a delayed and more stable version of the actor network weights. On the other hand, the actor behaves to satisfy the extrinsic reward function and the log-ratio between the sampled actor and adversary distributions.

Formally, for each state-action pair (s_t, a_t) in a trajectory, a sampled bonus $\log \pi(a_t|s_t) - \log \pi_{\text{adv}}(a_t|s_t)$ is given to the actor. In addition, the critic includes the KL divergence bonus $D_{\text{KL}}(\pi(\cdot|s_t) \| \pi_{\text{adv}}(\cdot|s_t))$ in the value function estimator. Under this formulation, when the policy is not optimal and assuming that the critic has a low estimation error, a positive advantage function drives the agent to larger rewards while exploring other strategies than that of the adversary. We discuss in the next section the implications of a divergence from π_{adv}. In addition to the parameters θ (resp. θ_{old} the parameter of the policy at the previous iteration) and ϕ defined above (resp. ϕ_{old} that of the critic), we denote ψ (resp. ψ_{old}) that of the adversary.

AGAC optimizes the following loss:

$$\mathcal{L}_{\text{AGAC}} = \mathcal{L}_{PG} + \beta_V \mathcal{L}_V + \beta_{\text{adv}} \mathcal{L}_{\text{adv}}.$$

In the new objective $\mathcal{L}_{PG} = \frac{1}{N} \sum_{t=0}^N (A_t^{\text{AGAC}} \log \pi (a_t|s_t, \theta) + \alpha \mathcal{H}^\pi(s_t, \theta))$, AGAC modifies A_t as:

$$A_t^{\text{AGAC}} = A_t + c \left(\log \pi(a_t|s_t, \theta_{\text{old}}) - \log \pi_{\text{adv}}(a_t|s_t, \psi_{\text{old}}) \right), \tag{1}$$

with c a hyper-parameter that controls the dependence on the log-action probability difference. $\mathcal{L}_V$ is the objective function of the critic defined as:

$$\mathcal{L}_V = \frac{1}{N} \sum_{t=0}^N \left(V_\phi(s_t) - \hat{V}_t - c\, D_{\text{KL}}(\pi(\cdot|s_t, \theta_{\text{old}}) \| \pi_{\text{adv}}(\cdot|s_t, \psi_{\text{old}})) \right)^2. \tag{2}$$

Finally, $\mathcal{L}_{\text{adv}}$ is the objective function of the adversary:

$$\mathcal{L}_{\text{adv}} = \frac{1}{N} \sum_{t=0}^{N} D_{\text{KL}}(\pi(\cdot|s_t, \theta_{\text{old}}) \| \pi_{\text{adv}}(\cdot|s_t, \psi)). \tag{3}$$

Eqs. (1), (2) and (3) are the three equations that our method modifies (we color in red the specific parts) in the traditional actor-critic framework. The terms β_V and β_{adv} are fixed hyper-parameters.

4.1 BUILDING MOTIVATION

Under the proposed actor-critic formulation, the actor log-probability of a sample action sequence is reinforced if (i) the corresponding reward is large or (ii) the adversarial bonus is large, which means that the action could not be predicted from the behavior of the actor in previous trajectories. Mechanistically, our method disfavors transitions whose actions were better predicted than the average of all other actions, i.e. $\log \pi(a|s, \theta_{\text{old}}) - \log \pi_{\text{adv}}(a|s, \psi_{\text{old}}) \leq D_{\text{KL}}(\pi(\cdot|s'_t, \theta_{\text{old}}) \| \pi_{\text{adv}}(\cdot|s'_t, \psi_{\text{old}}))$.

In the following we provide an interpretation of the new objective formulation in terms of dynamics of attraction and repulsion between the actor and the adversary. To simplify, we study AGAC in a policy iteration scheme. We ignore advantage functions and instead consider Q-functions (the gradient being unbiased for an additionate state-dependent baseline). The quantity of interest is (for simplicity, π_k is analogous to π with parameter θ_{old} in previous notations):

$$\tilde{Q}_{\pi_k} = Q_{\pi_k} + c(\log \pi_k - \log \pi_{\text{adv}}),$$

with π_k the policy at iteration k. The new policy optimizes for (including the entropic penalty):

$$\mathcal{L}_{\text{PI}}(\pi) = \mathbb{E}_s \mathbb{E}_{a \sim \pi(\cdot|s)}[\tilde{Q}_{\pi_k}(s, a) - \alpha \ln \pi(a|s)].$$

We can rewrite this loss:

$$
\begin{aligned}
\mathcal{L}_{\text{PI}}(\pi) &= \mathbb{E}_s \mathbb{E}_{a \sim \pi(\cdot|s)}[\tilde{Q}_{\pi_k}(s, a) - \alpha \log \pi(a|s)] \\
&= \mathbb{E}_s \mathbb{E}_{a \sim \pi(\cdot|s)}[Q_{\pi_k}(s, a) + c(\log \pi_k(a|s) - \log \pi_{\text{adv}}(a|s)) - \alpha \log \pi(a|s)] \\
&= \mathbb{E}_s \mathbb{E}_{a \sim \pi(\cdot|s)}[Q_{\pi_k}(s, a) + c(\log \pi_k(a|s) - \log \pi(a|s) + \log \pi(a|s) - \log \pi_{\text{adv}}(a|s)) - \alpha \log \pi(a|s)] \\
&= \mathbb{E}_s \Big[\mathbb{E}_{a \sim \pi(\cdot|s)}[Q_{\pi_k}(s, a)] \underbrace{-c D_{\text{KL}}(\pi(\cdot|s) \| \pi_k(\cdot|s))}_{\pi_k \text{ is attractive}} \underbrace{+c D_{\text{KL}}(\pi(\cdot|s) \| \pi_{\text{adv}}(\cdot|s))}_{\pi_{\text{adv}} \text{ is repulsive}} \underbrace{+\alpha \mathcal{H}(\pi(\cdot|s))}_{\text{enforce stochastic policies}} \Big].
\end{aligned}
$$

We describe the behavior of the different parts of this equation. In this simplified formulation, AGAC would compute a greedy policy, maximizing Q-values, while remaining close to the previous policy but far from a form of a mixture of the policies that preceded the previous one (i.e., π_{k-1}, π_{k-2}, …). Notice that we experimentally observe (see Section 5.3) that our method performs better with a smaller learning rate for the adversarial network than that of the other networks, which could imply that stabilizing the repulsor is beneficial.

This optimization problem is strongly concave in π (thanks to the entropy term), and is state-wise a Legendre-Fenchel transform. Its solution is given by:

$$\pi_{k+1} \propto \left(\frac{\pi_k}{\pi_{\text{adv}}} \right)^{\frac{c}{\alpha}} \exp \frac{q_{\pi_k}}{\alpha}.$$

This gives us some insight into the behavior of the objective function. Notably, in our example, if π_{adv} is fixed and $c = \tau$, we recover a KL-regularized policy iteration Geist et al. (2019) with a modified reward $r - c \log \pi_{\text{adv}}$.

4.2 IMPLEMENTATION

In all of the experiments, we use PPO (Schulman et al., 2017) as the base algorithm and build on it to incorporate our method. Hence,

$$\mathcal{L}_{PG} = \frac{1}{N} \sum_{t'=t}^{t+N} \min \left(\frac{\pi(a_{t'}|s_{t'}, \theta)}{\pi(a_{t'}|s_{t'}, \theta_{\text{old}})} A_{t'}^{\text{AGAC}}, \text{clip}\left(\frac{\pi(a_{t'}|s_{t'}, \theta)}{\pi(a_{t'}|s_{t'}, \theta_{\text{old}})}, 1 - \epsilon, 1 + \epsilon \right) A_{t'}^{\text{AGAC}} \right),$$

with $A_{t'}^{\text{AGAC}}$ given in Eq. (1), N the temporal length considered for one update of parameters and ϵ the clipping parameter. Similar to RIDE (Raileanu & Rocktäschel, 2019), we also discount PPO by episodic state visitation counts, except for VizDoom (*cf.* Section 5.1). The actor, critic and adversary use the convolutional architecture of the Nature paper of DQN (Mnih et al., 2015) with different hidden sizes (see Appendix C for architecture details). The three neural networks are optimized using Adam (Kingma & Ba, 2015). Our method does not use RNNs in its architecture; instead, in all our experiments, we use frame stacking. Indeed, Hausknecht & Stone (2015) interestingly demonstrate that although recurrence is a reliable method for processing state observation, it does not confer any systematic advantage over stacking observations in the input layer of a CNN. Note that the parameters are not shared between the policy, the critic and the adversary and that we did not observe any noticeable difference in computational complexity when using AGAC compared to the baseline. We direct the reader to Appendix B for a list of hyper-parameters. In particular, the c coefficient behind the adversarial bonus is linearly annealed.

At each training step, we perform a stochastic optimization step to minimize $\mathcal{L}_{\text{AGAC}}$ using stop-gradient:

$$\theta \leftarrow \text{Adam}\left(\theta, \nabla_\theta \mathcal{L}_{PG}, \eta_1\right), \qquad \phi \leftarrow \text{Adam}\left(\phi, \nabla_\phi \mathcal{L}_V, \eta_1\right), \qquad \psi \leftarrow \text{Adam}\left(\psi, \nabla_\psi \mathcal{L}_{\text{adv}}, \eta_2\right).$$

5 EXPERIMENTS

In this section, we describe our experimental study in which we investigate: (i) whether the adversarial bonus alone is sufficient to outperform other methods in VizDoom, a sparse-reward task with high-dimensional observations, (ii) whether AGAC succeeds in partially-observable and procedurally-generated environments with high sparsity in the rewards, compared to other methods, (iii) how well AGAC is capable of exploring in environments without extrinsic reward, (iv) the training stability of our method. In all of the experiments, lines are average performances and shaded areas represent one standard deviation. We include the code for the method in the Supplementary Material.

Figure 1: (a,b) Frames from the 3-D navigation task VizdoomMyWayHome. (c) MiniGrid-KeyCorridorS6R3. (d) MiniGrid-ObstructedMazeFull.

Environments. To carefully evaluate the performance of our method, its ability to develop robust exploration strategies and its generalization to unseen states, we choose tasks that have been used in prior work, which are tasks with high-dimensional observations, sparse reward and procedurally-generated environments. In **VizDoom** (Kempka et al., 2016), the agent must learn to move along corridors and through rooms without any reward feedback from the 3-D environment. The **MiniGrid** environments (Chevalier-Boisvert et al., 2018) are a set of challenging partially-observable and sparse-reward gridworlds. In this type of procedurally-generated environment, memorization is impossible due to the huge size of the state space, so the agent must learn to generalize across the different layouts of the environment. Each gridworld has different characteristics: in the MultiRoom tasks, the agent is placed in the first room and should reach a goal placed in the most distant room. In the KeyCorridor tasks, the agent must navigate to pick up an object placed in a room locked by a door whose key is in another room. Finally, in the ObstructedMaze tasks, the agent must pick up a box that is placed in a corner of a 3x3 maze in which the doors are also locked, the keys are hidden in boxes and balls obstruct the doors. All considered environments (see Fig. 1 for some examples) are available as part of OpenAI Gym (Brockman et al., 2016).

Baselines. For a fair assessment of our method, we compare to some of the most prominent methods specialized in hard-exploration tasks: **RIDE** (Raileanu & Rocktäschel, 2019), based on an intrinsic

reward associated with the magnitude of change between two consecutive state representations and state visitation, **Count** as Count-Based Exploration (Bellemare et al., 2016b), which we couple with IMPALA (Espeholt et al., 2018), **RND** (Burda et al., 2018) in which an exploration bonus is positively correlated to the error of predicting features from the observations and **ICM** (Pathak et al., 2017), where a module only predicts the changes in the environment that are produced by the actions of the agent. Finally, we compare to most the recent and best performing method at the time of writing in procedurally-generated environments: **AMIGo** (Campero et al., 2020) in which a goal-generating teacher provides count-based intrinsic goals. While avoiding unnecessary use of computational resources, we make the fairest comparison with other methods by using, when available, the scores reported in Raileanu & Rocktäschel (2019) and Campero et al. (2020). In the performance graphs presented below ("Ours" means AGAC): the vertical dotted line corresponds to the moment when the performance of the corresponding method reaches its point of convergence and the continuous horizontal line corresponds to its point of maximum performance in the considered plot. Note that all of the corresponding curves can be consulted in Fig. 3 of Raileanu & Rocktäschel (2019) and Fig. 4 of Campero et al. (2020). For the reader convenience, we include all the original graphs in Appendix E with comprehensive comments.

5.1 Adversarially-based Exploration (No Episodic Count)

In this section, we assess the benefits of using an adversarially-based exploration bonus and examine how AGAC performs without the help of count-based exploration. In order to provide a comparison to state-of-the-art methods, we choose VizDoom, a hard-exploration problem used in prior work. In this game, the map consists of 9 rooms connected by corridors where 270 steps separate the initial position of the agent and the goal under an optimal policy. Episodes are terminated either when the agent finds the goal or if the episode exceeds 2100 timesteps. Importantly, while other algorithms (Raileanu & Rocktäschel, 2019; Campero et al., 2020) benefit from count-based exploration, this study has been conducted

Figure 2: Average return in VizDoom (see Appendix E.1 for additional comparison elements).

with our method not benefiting from episodic count whatsoever. Results in Fig. 2 (see Appendix E.1 for additional comparison elements) indicate that AGAC clearly outperforms other methods in sample efficiency. Then, with nearly 2x more transitions, the graph in only ICM and RIDE match the score of AGAC. Although our results support the capabilities of the adversarial bonus and show that it can, on its own, achieve significant gains in performance, VizDoom is not procedurally-generated; hence we have not evaluated the generalization to new states yet. Next, we use MiniGrid to investigate this.

5.2 Hard-Exploration with Partially-Observable Policy

We now fully evaluate our method on multiple hard-exploration procedurally-generated tasks from MiniGrid. Details about MiniGrid can be found in Appendix B.1. Fig. 3 indicates that AGAC dramatically outperforms the baselines on these tasks (see Appendix E.2 for additional comparison elements). We also successfully outperform the current state-of-the-art method, AMIGo, despite the fact that it uses fully-observable policies. In all the considered tasks, the agent must learn to generalize across a very large state space because the layouts are procedurally-generated. We consider three main arguments to explain why our method is successful: (i) our method relies on partially-observable policies: in this context, the adversary has a harder time predicting the actor's actions; nevertheless, the mistakes of the former benefit the latter in the form of an exploration bonus, which pushes the agent to explore further in order to deceive the adversary, (ii) intrinsic reward does not dissipate compared to most other methods, as observed in Fig. 9 in Appendix A.3, (iii) our method does not make assumptions about the environment dynamics (*e.g.*, changes in the environment produced by an action as in Raileanu & Rocktäschel (2019)) since this can hinder learning when the space of state changes induced by an action is too large (such as the action of moving a block in ObstructedMaze).

In Appendix A.2, we also include experiments in two environments with extremely sparse reward signals: KeyCorridorS8R3 and ObstructedMazeFull. In these environments, the agent still manages to find rewards and can perform well by taking advantage of the diversified behaviour induced by our

Figure 3: Performance evaluation of `AGAC` (see Appendix E.2 for additional comparison elements).

Figure 4: Sensitivity analysis of `AGAC` in KeyCorridorS4R3.

method. To the best of our knowledge, no other method ever succeeded to perform well (> 0 average return) in those tasks. We think that given more computing time, `AGAC`'s score could go higher.

5.3 TRAINING STABILITY

Here we want to analyse the stability of the method when changing hyper-parameters. The most important parameters in `AGAC` are c, the coefficient behind the adversarial bonus, and the learning rates ratio $\nu = \frac{\eta_2}{\eta_1}$. We choose KeyCorridorS4R3 as the evaluation task because among all the tasks considered, its difficulty is at a medium level. Fig. 4 shows the learning curves. For readability, we plot the average return only; the standard deviation is sensibly the same for all curves. We observe that deviating from the hyper-parameter values found using grid-search results in a slower training. Moreover, although reasonable, c appears to have more sensitivity than ν.

5.4 EXPLORATION IN REWARD-FREE ENVIRONMENT

To better understand the effectiveness of our method and inspect how the agent collects rewards that would not otherwise be achievable by simple exploration heuristics or other methods, we analyze the performance of `AGAC` in another (although procedurally-generated) moderately challenging environment, MultiRoomN10S6, when there is no reward signal (no extrinsic reward). Beyond the good performance of our method when extrinsic rewards are given to the agent, Fig. 5 indicates that the exploration induced by our method alone makes the agent succeed in a significant proportion of the episodes. Note that in the

Figure 5: Average return on N10S6 with and without extrinsic reward.

configuration "NoExtrinsicReward", the reward signal is not given. That is, the actor is not optimized for it, confirming that the agent exhaustively covers the environment.

Figure 6: State visitation heatmaps of the last ten episodes of an agent trained in a procedurally-generated environment without extrinsic reward for 10M timesteps. The agent is continuously engaging in new strategies.

5.5 Promoting Diversity

In this section, we study the diversity of the agent's behavior. Fig. 6 presents the state visitation heatmaps (darker areas correspond to more visits) of ten episodes in the same singleton environment. We consider an agent trained in procedurally-generated environments from the MultiRoomN10S6 task without extrinsic reward. The heatmaps correspond to the behavior of the resulting policy and still trained policy. Looking at the figure, we can see that the strategies vary at each update with, for example, back-and-forth and back-to-start behaviors. Although there are no extrinsic rewards, the strategies seem to diversify from one update to the next. Fig. 7 in Appendix A.1 shows the state visitation heatmaps in a different configuration: when the agent has been trained on the same singleton environment from the MultiRoomN10S6 task without extrinsic reward. Looking at the figure, we can make essentially the same observations as previously, with a noteworthy behavior in the fourth heatmap of the bottom row where it appears the agent went to the fourth room to remain inside it. Those episodes indicate that, although the agent sees the same environment repeatedly, the successive adversarial updates force it to continuously adapt its behavior and try new strategies.

6 Discussion

This paper introduced `AGAC`, a modification to the traditional actor-critic framework: an adversary network is added to the policy gradient objective. The mechanics of `AGAC` have been discussed from a policy iteration point of view, and we provided theoretical insight into the inner workings of the proposed algorithm. The adversary forces the agent to remain close to the previous policy while moving away from the previous ones. In turn, the influence of the adversary makes the actor *conservatively diversified*.

In the experimental study, we have evaluated the adversarially-based bonus in VizDoom and empirically demonstrated its effectiveness and superiority compared to other relevant methods (some benefiting from count-based exploration). Then, we have conducted several performance experiments using `AGAC` and have shown a significant performance improvement over some of the most popular exploration methods (Count, ICM, RND, RIDE, AMiGO) on a set of various challenging tasks from MiniGrid. These procedurally-generated environments have served another purpose which is to validate the capacity of our method to generalize to unseen scenarios. In addition, the training stability of our method has been studied, showing a greater but acceptable sensitivity for c, the adversarial bonus coefficient. Finally, we have investigated the exploration capabilities of `AGAC` in a reward-free setting where the agent demonstrated exhaustive exploration through various strategic choices, confirming that the adversary successfully drives diversity in the actor behaviors.

REFERENCES

Zafarali Ahmed, Nicolas Le Roux, Mohammad Norouzi, and Dale Schuurmans. Understanding the impact of entropy on policy optimization. In *International Conference on Machine Learning*, pp. 151–160, 2019.

Martin Arjovsky and Léon Bottou. Towards principled methods for training generative adversarial networks. In *International Conference on Representation Learning*, 2017.

Dzmitry Bahdanau, Felix Hill, Jan Leike, Edward Hughes, Arian Hosseini, Pushmeet Kohli, and Edward Grefenstette. Learning to understand goal specifications by modelling reward. *arXiv preprint arXiv:1806.01946*, 2018.

Andrew G Barto, Richard S Sutton, and Charles W Anderson. Neuronlike adaptive elements that can solve difficult learning control problems. *IEEE transactions on systems, man, and cybernetics*, (5): 834–846, 1983.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in Neural Information Processing Systems*, pp. 1471–1479, 2016a.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in neural information processing systems*, pp. 1471–1479, 2016b.

G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. In *International Conference on Learning Representations*, 2018.

Andres Campero, Roberta Raileanu, Heinrich Küttler, Joshua B. Tenenbaum, Tim Rocktäschel, and Edward Grefenstette. Learning with amigo: Adversarially motivated intrinsic goals. *arXiv preprint arXiv:2006.12122*, 2020.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. https://github.com/maximecb/gym-minigrid, 2018.

Djork-Arné Clevert, Thomas Unterthiner, and Sepp Hochreiter. Fast and accurate deep network learning by exponential linear units (elus). In *International Conference on Representation Learning*, 2016.

Karl Cobbe, Christopher Hesse, Jacob Hilton, and John Schulman. Leveraging procedural generation to benchmark reinforcement learning. *arXiv preprint arXiv:1912.01588*, 2019.

Adrien Ecoffet, Joost Huizinga, Joel Lehman, Kenneth O Stanley, and Jeff Clune. Go-explore: a new approach for hard-exploration problems. *arXiv preprint arXiv:1901.10995*, 2019.

Lasse Espeholt, Hubert Soyer, Remi Munos, Karen Simonyan, Vlad Mnih, Tom Ward, Yotam Doron, Vlad Firoiu, Tim Harley, Iain Dunning, et al. Impala: Scalable distributed deep-rl with importance weighted actor-learner architectures. In *International Conference on Machine Learning*, pp. 1407–1416, 2018.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

Jesse Farebrother, Marlos C Machado, and Michael Bowling. Generalization and regularization in dqn. *arXiv preprint arXiv:1810.00123*, 2018.

Johan Ferret, Raphaël Marinier, Matthieu Geist, and Olivier Pietquin. Self-attentional credit assignment for transfer in reinforcement learning. In *International Joint Conference on Artificial Intelligence*, pp. 2655–2661, 2020.

Yannis Flet-Berliac and Philippe Preux. Only relevant information matters: Filtering out noisy samples to boost rl. In *International Joint Conference on Artificial Intelligence*, pp. 2711–2717, 2020.

Meire Fortunato, Mohammad Gheshlaghi Azar, Bilal Piot, Jacob Menick, Ian Osband, Alex Graves, Vlad Mnih, Remi Munos, Demis Hassabis, Olivier Pietquin, et al. Noisy networks for exploration. *arXiv preprint arXiv:1706.10295*, 2017.

Matthieu Geist, Bruno Scherrer, and Olivier Pietquin. A theory of regularized markov decision processes. *arXiv preprint arXiv:1901.11275*, 2019.

Ian Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial nets. In *Advances in neural information processing systems*, pp. 2672–2680, 2014a.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *arXiv preprint arXiv:1412.6572*, 2014b.

Audrunas Gruslys, Will Dabney, Mohammad Gheshlaghi Azar, Bilal Piot, Marc Bellemare, and Remi Munos. The reactor: A fast and sample-efficient actor-critic agent for reinforcement learning. *arXiv preprint arXiv:1704.04651*, 2017.

Seungyul Han and Youngchul Sung. Diversity actor-critic: Sample-aware entropy regularization for sample-efficient exploration. *arXiv preprint arXiv:2006.01419*, 2020.

Matthew Hausknecht and Peter Stone. Deep recurrent q-learning for partially observable mdps. In *AAAI Fall Symposium on Sequential Decision Making for Intelligent Agents*, 2015.

David Held, Xinyang Geng, Carlos Florensa, and Pieter Abbeel. Automatic goal generation for reinforcement learning agents. *arXiv preprint arXiv:1705.06366*, 2017.

Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In *Advances in Neural Information Processing Systems*, pp. 4565–4573, 2016.

Maximilian Igl, Kamil Ciosek, Yingzhen Li, Sebastian Tschiatschek, Cheng Zhang, Sam Devlin, and Katja Hofmann. Generalization in reinforcement learning with selective noise injection and information bottleneck. *arXiv prepint arXiv:1910.12911*, 2019.

Niels Justesen, Ruben Rodriguez Torrado, Philip Bontrager, Ahmed Khalifa, Julian Togelius, and Sebastian Risi. Illuminating generalization in deep reinforcement learning through procedural level generation. *arXiv preprint arXiv:1806.10729*, 2018.

Michał Kempka, Marek Wydmuch, Grzegorz Runc, Jakub Toczek, and Wojciech Jaśkowski. Vizdoom: A doom-based ai research platform for visual reinforcement learning. In *IEEE Conference on Computational Intelligence and Games*, pp. 1–8. IEEE, 2016.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Representation Learning*, 2015.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale. *arXiv preprint arXiv:1611.01236*, 2016.

Kimin Lee, Kibok Lee, Jinwoo Shin, and Honglak Lee. Network randomization: A simple technique for generalization in deep reinforcement learning. *arXiv preprint arXiv:1910.05396*, 2020.

Timothy P Lillicrap, Jonathan J Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *International Conference on Learning Representations*, 2016.

Takeru Miyato, Shin-ichi Maeda, Masanori Koyama, Ken Nakae, and Shin Ishii. Distributional smoothing with virtual adversarial training. *arXiv preprint arXiv:1507.00677*, 2015.

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, 2015.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International Conference on Machine Learning*, pp. 1928–1937, 2016a.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In *International conference on machine learning*, pp. 1928–1937, 2016b.

Rémi Munos, Tom Stepleton, Anna Harutyunyan, and Marc Bellemare. Safe and efficient off-policy reinforcement learning. In *Advances in Neural Information Processing Systems*, pp. 1054–1062, 2016.

Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. *arXiv preprint arXiv:1806.05635*, 2018.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *International Conference on Machine Learning*, pp. 2778–2787, 2017.

David Pfau and Oriol Vinyals. Connecting generative adversarial networks and actor-critic methods. *arXiv preprint arXiv:1610.01945*, 2016.

Martin L. Puterman. *Markov Decision Processes*. Wiley, 1994. ISBN 978-0471727828.

Roberta Raileanu and Tim Rocktäschel. Ride: Rewarding impact-driven exploration for procedurally-generated environments. In *International Conference on Learning Representations*, 2019.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In *International Conference on Machine Learning*, pp. 1889–1897, 2015.

John Schulman, Philipp Moritz, Sergey Levine, Michael Jordan, and Pieter Abbeel. High-dimensional continuous control using generalized advantage estimation. In *International Conference on Learning Representations*, 2016.

John Schulman, Filip Wolski, Prafulla Dhariwal, Alec Radford, and Oleg Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

David Silver, Guy Lever, Nicolas Heess, Thomas Degris, Daan Wierstra, and Martin Riedmiller. Deterministic policy gradient algorithms. In *International Conference on Machine Learning*, 2014.

Xingyou Song, Yiding Jiang, Yilun Du, and Behnam Neyshabur. Observational overfitting in reinforcement learning. *arXiv preprint arXiv:1912.02975*, 2019.

Richard Stuart Sutton. *Temporal Credit Assignment in Reinforcement Learning*. PhD thesis, University of Massachusetts Amherst, 1984.

Nino Vieillard, Tadashi Kozuno, Bruno Scherrer, Olivier Pietquin, Rémi Munos, and Matthieu Geist. Leverage the average: an analysis of regularization in rl. *arXiv preprint arXiv:2003.14089*, 2020.

Oriol Vinyals, Igor Babuschkin, Wojciech Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David Choi, Richard Powell, Timo Ewalds, Petko Georgiev, Junhyuk Oh, Dan Horgan, Manuel Kroiss, Ivo Danihelka, Aja Huang, Laurent Sifre, Trevor Cai, John Agapiou, Max Jaderberg, and David Silver. Grandmaster level in StarCraft II using multi-agent reinforcement learning. *Nature*, 575, 11 2019.

Ziyu Wang, Victor Bapst, Nicolas Heess, Volodymyr Mnih, Remi Munos, Koray Kavukcuoglu, and Nando de Freitas. Sample efficient actor-critic with experience replay. *arXiv preprint arXiv:1611.01224*, 2016.

Yuhuai Wu, Elman Mansimov, Roger B Grosse, Shun Liao, and Jimmy Ba. Scalable trust-region method for deep reinforcement learning using kronecker-factored approximation. In *Advances in Neural Information Processing Systems*, pp. 5279–5288, 2017.

Amy Zhang, Nicolas Ballas, and Joelle Pineau. A dissection of overfitting and generalization in continuous reinforcement learning. *arXiv preprint arXiv:1806.07937*, 2018a.

Chiyuan Zhang, Oriol Vinyals, Remi Munos, and Samy Bengio. A study on overfitting in deep reinforcement learning. *arXiv preprint arXiv:1804.06893*, 2018b.

A ADDITIONAL EXPERIMENTS

A.1 STATE VISITATION HEATMAPS IN SINGLETON ENVIRONMENT WITH NO EXTRINSIC REWARD

In this section, we provide additional state visitation heatmaps. The agent has been trained on a singleton environment from the MultiRoomN10S6 task without extrinsic reward. These ten episodes suggest that the agent sees the same environment over and over again, the updates force it to change behavior by trying new strategies.

Figure 7: State visitation heatmaps of the last ten episodes of an agent trained in a singleton environment with no extrinsic rewards 10M timesteps. The agent is continuously engaging into new strategies.

A.2 (EXTREMELY) HARD-EXPLORATION WITH PARTIALLY-OBSERVABLE POLICY

In this section, we include additional experiments on one of the hardest tasks available in MiniGrid. The first is KeyCorridorS8R3, where the size of the rooms has been increased. In it, the agent has to pick up an object which is behind a locked door: the key is hidden in another room and the agent has to explore the environment to find it. The second, ObstructedMazeFull, is similar to ObstructedMaze4Q, where the agent has to pick up a box which is placed in one of the four corners of a 3x3 maze: the doors are locked, the keys are hidden in boxes and the doors are obstructed by balls. In those difficult tasks, only our method succeeds in exploring well enough to find rewards.

Figure 8: Performance evaluation of `AGAC` compared to RIDE, AMIGo, Count, RND and ICM on extremely hard-exploration problems.

A.3 MEAN INTRINSIC REWARD

In this section, we report the mean intrinsic reward computed for an agent trained in Multi-RoomN12S10 to conveniently compare our results with that of Raileanu & Rocktäschel (2019).

We observe in Fig. 9 that the intrinsic reward is consistently larger for our method and that, contrary to other methods, does not converge to low values (a comparison to the comparing results published in Raileanu & Rocktäschel (2019) is found in Fig. **??**). Please note that, in all considered experiments, the adversarial bonus coefficient c in Eq. 2 and 3 is linearly annealed throughout the training since it is mainly useful at the beginning of learning when the rewards have not yet been met. In the long run, this coefficient may prevent the agent from solving the task by forcing it to always favour exploration over exploitation.

Figure 9: Average intrinsic reward for different methods trained in MultiRoomN12S10.

B EXPERIMENTAL DETAILS AND HYPER-PARAMETERS

B.1 MINIGRID SETUP

Here, we describe in more details the experimental setup we used in our MiniGrid experiments.

There are several different MiniGrid scenarios that we consider in this paper. MultiRoom corresponds to a set of navigation tasks, where the goal is to go from a starting state to a goal state. The notation MultiRoom-N2S4 means that there are 2 rooms in total, and that each room has a maximal side of 4. In KeyCorridor, the agent also has to pick up a key, since the goal state is behind a door that only lets him in with the key. The notation KeyCorridor-S3R4 means that there are 4 side corridors, leading to rooms that have a maximal side of 3. In ObstructedMaze, keys are hidden in boxes, and doors are obstructed by balls the agent has to get out of its way. The notation ObstructedMaze-1Dl means that there are two connected rooms of maximal side 6 and 1 door (versus a 3x3 matrix and 2 doors if the leading characters are $2D$), adding h as a suffix places keys in boxes, and adding b as a suffix adds balls in front of doors. Using Q as a suffix is equivalent to using lhb (that is, both hiding keys and placing balls to be moved). ObstructedMaze-Full is the hardest configuration for this scenario, since it has the maximal number of keys, balls to move, and doors possible.

In each scenario, the agent has access to a partial view of the environment, a 7x7 square that includes itself and points in the direction of its previous movement.

B.2 HYPERPARAMETERS

In all experiments, we train six different instances of our algorithm with different random seeds. In Table 1, we report the list of hyper-parameters.

Table 1: Hyper-parameters used in `AGAC`.

Parameter	Value
Horizon T	2048
Nb. epochs	4
Nb. minibatches	8
Nb. frames stacked	4
Nonlinearity	ELU (Clevert et al., 2016)
Discount γ	0.99
GAE parameter λ	0.95
PPO clipping parameter ϵ	0.2
β_V	0.5
c	$4 \cdot 10^{-4}$ ($4 \cdot 10^{-5}$ in VizDoom)
c anneal schedule	linear
β_{adv}	$4 \cdot 10^{-5}$
Adam stepsize η_1	$3 \cdot 10^{-4}$
Adam stepsize η_2	$9 \cdot 10^{-5} = 0.3 \cdot \eta_1$

C IMPLEMENTATION DETAILS

In Fig. 10 is depicted the architecture of our method.

Figure 10: Artificial neural architecture of the critic, the actor and the adversary.

D ILLUSTRATION OF AGAC

Figure 11: A simple schematic illustration of our method.

E   EXTERNAL ADDITIONAL EXPERIMENTS

In this section, we attach the screenshots from the experimental results in Fig. 3, 5 and 8 in Raileanu & Rocktäschel (2019) and Fig. 4 in Campero et al. (2020), with which we share the same experimental settings.

E.1   VIZDOOM

In this section, we include the results from Fig. 8 in Raileanu & Rocktäschel (2019). We observe that only RIDE and ICM succeed in performing well, and that those methods reach their maximum performance at around $0.58 \cdot 10^7$ timesteps. In Fig. 2, we report those results using a vertical dotted line at $0.58 \cdot 10^7$ timesteps and a plain horizontal line at 0.95. We also indicate that we found AMIGo to achieve the same performance as Count, RND and IMPALA. We found this result surprising because AMIGo has proven to perform well in the MiniGrid environments. Nevertheless, it appears that concurrent works to ours experienced similar issues with the accompanying implementation[1].

Figure 12: Average return reported in Campero et al. (2020) of RIDE, Count, RND, ICM and IMPALA.

E.2   MINIGRID

In this section, we include the top-right graph from Fig. 3 in Raileanu & Rocktäschel (2019) and the four bottom graphs from Fig. 4 in Campero et al. (2020). For comparison, in Fig. 2, we report those results using a vertical dotted line an plain horizontal line. Note that we find the same poor performance results when training AMIGo in MultiRoom-N10S10, similar to Vizdoom results.

---

[1]AMIGo implementation GitHub Issue.

Figure 13: Average return reported in Campero et al. (2020) and Campero et al. (2020).