BeBold: Exploration Beyond the Boundary of Explored Regions

Abstract

Efficient exploration in sparse reward environments remains a key challenge in deep reinforcement learning. Intrinsic reward (IR) has been used extensively to guide the exploration. There are different ways to define IR, including count-based, curiosity-driven, state-difference, and so on. In this paper, we analyze their pros and cons and propose to use the *regulated difference of inverse visitation counts* as a simple but effective criterion for IR. The criterion helps the agent explore **Be**yond the **Bo**undary of exp**lo**re**d** regions and mitigates common issues in count-based methods, such as *short-sightedness* and *detachment*. The resulting method, **BeBold**, solves 12 most challenging procedurally-generated tasks in MiniGrid within 120M environment steps, without any curriculum learning. In comparison, previous SoTA only solves 50% of the tasks. Furthermore, BeBold also achieves SoTA on multiple tasks in NetHack, a popular roguelike game that contains much more challenging procedurally-generated environments.

1 Introduction

Deep reinforcement learning (RL) has experienced significant progress over the last several years. It shows impressive performance in games like Atari (Mnih et al., 2015; Badia et al., 2020a), Star-Craft (Vinyals et al., 2019) and Chess (Silver et al., 2016; 2017; 2018). However, most of the success either requires a manually designed dense reward (Brockman et al., 2016) or a perfect environment model (Silver et al., 2017; Moravčík et al., 2017). This is far less than satisfactory for the real-world settings, where reward is sparse and there is no expert knowledge on how to design proper dense reward for accomplishing a task. Training agent using random exploration (e.g., ϵ-greedy) in these environments is often insufficient and leads to poor performance (Bellemare et al., 2016).

Recent approaches have proposed to use **intrinsic rewards** (IR) (Schmidhuber, 2010) to motivate agents for exploration before any extrinsic rewards are obtained. Various criteria have been proposed, including *curiosity/surprise*-driven (Pathak et al., 2017), *count*-based (Bellemare et al., 2016; Burda et al., 2018a;b; Ostrovski et al., 2017; Badia et al., 2020b), and *state-diff* approaches (Zhang et al., 2019; Marino et al., 2019).

All these approaches have pros and cons. Curiosity-driven approaches look for prediction errors of the learned dynamical model and might get trapped to the noisy TV problem in which the environment dynamics is inherently stochastic. Count-based approaches favor novel states of the environment, but might suffer from *detachment and derailment* (Ecoffet et al., 2019), in which the agent gets trapped into one (long) corridor and forgets to try other choices. Count-based approaches are also *short-sighted*: the agent tends to move to the next state whose visitation count is slightly lower, trapped into local minima (Burda et al., 2018b). Finally, state-diff approaches give rewards if in a trajectory, representation of consecutive states differs a lot. While it considers the entire trajectory of the agent rather than a local state, it is asymptotically inconsistent: the intrinsic reward remains positive when the visitation counts approach infinity. As a result, the final policy does not quite maximize the cumulative extrinsic reward.

In this paper, we propose a novel exploration criterion that combines count-based with the state-diff approach: instead of using difference of state representations, we use the *regulated difference of inverse visitation counts* of consecutive states in a trajectory. The inverse visitation count is approximated by Random Network Distillation (Burda et al., 2018b). On one hand, this solves the issues of asymptotic inconsistency in the state-diff approaches, since the inverse visitation count vanishes with sufficient explorations. On the other hand, our IR is large at the end of a trajectory and at the *boundary* between the explored and the unexplored regions (Fig. 1). This motivates the

Figure 1: A Hypothetical Demonstration of how exploration is done in BeBold versus Random Network Distillation (Burda et al., 2018b), in terms of distribution of intrinsic rewards (IR). BeBold reaches the goal by continuously pushing the frontier of exploration while RND got trapped. Note that IR is defined differently in RND ($1/c(\mathbf{s}_t)$) versus BeBold ($\max(1/c(\mathbf{s}_{t+1}) - 1/c(\mathbf{s}_t), 0)$, See Eqn. 3), and different color is used.

agent to move **Be**yond the **Bo**undary of the exp**l**ore**d** regions and step into the unknown, mitigating the short-sighted issue in count-based approaches.

Following this simple criterion, we propose a novel algorithm **BeBold** and evaluate it on two very challenging procedurally-generated (PG) environments: MiniGrid (Chevalier-Boisvert et al., 2018) and NetHack (Küttler et al., 2020). MiniGrid is a popular benchmark for evaluating exploration algorithms (Raileanu and Rocktäschel, 2020; Campero et al., 2020; Goyal et al., 2019) and NetHack is a much more realistic environment with complex goals and skills. BeBold manages to solve 12 most challenging environments in MiniGrid within 120M environment steps, without curriculum learning. In contrast, (Campero et al., 2020) solves 50% of the tasks categorized as easy and medium ones, by training a separate goal-generating teacher network, in 500M steps. In NetHack, a more challenging procedurally-generated environment (and an old-fashioned rogue like game in 80's), BeBold also outperforms all baselines with a good margin on various tasks. In addition, we analyze BeBold extensively in MiniGrid. The quantitative results shows that BeBold largely mitigates the *detachment* problem, with a much simpler design than Go-Explore (Ecoffet et al., 2020) which contains multiple hand-tune stages and hyper-parameters.

Most Related Works. RIDE (Raileanu and Rocktäschel, 2020) also combines multiple criteria together. RIDE learns the state representation with curiosity-driven approaches, and then uses the difference of learned representation along a trajectory as the reward, weighted by pseudo counts of the state. However, as a two-stage approach, RIDE heavily relies on the quality of generalization of the learned representation on novel states. As a result, BeBold shows substantially better performance in the same precedurally-generated environments.

Go-Explore (Ecoffet et al., 2020) stores many visited states (including boundaries), reaches these states without exploration and explore from them. BeBold focuses on boundaries and perform exploration without human-designed cell representation (e.g., image downsampling) and is end-to-end.

Frontier-based exploration (Yamauchi, 1997; 1998; Topiwala et al., 2018) is used to help specific robots explore the map by maximizing the information gain. The "frontier" is defined as the 2D spatial regions out of the explored parts. No automatic policy optimization with deep models is used. In contrast, BeBold can be applied to more general partial observable MDPs with deep policies.

2 BACKGROUND

Following single agent Markov Decision Process (MDP), we define a state space S, an action space A and a (non-deterministic) transition function $\mathcal{T}: S \times A \rightarrow P(S)$ where $P(S)$ is the probability of next state given the current state and action. The goal is to maximize the expected reward $R = \mathbb{E}[\sum_{k=0}^{T} \gamma^k r_{t+k=1}]$ where r_t is the reward, γ is the discount factor and the expectation is taken w.r.t. the policy π and MDP transition $P(S)$. In this paper, the total reward received at time step t is given by $r_t = r_t^e + \alpha r_t^i$, where r_t^e is the extrinsic reward given by the environment, r_t^i is the intrinsic reward from the exploration criterion, and α is a scaling hyperparameter.

3 EXPLORATION BEYOND THE BOUNDARY

Our new exploration criterion combines both counting-based and state-diff-based criterion. The new criterion doesn't suffer from short-sighted problem and is asymptomatically consistent. We'll first introduce BeBold and then analyse the advantages of BeBold over existing criteria in Sec. 4.

Exploration Beyond the Boundary. BeBold gives the intrinsic reward (IR) to the agent when it explores beyond the boundary of explored regions, i.e., along a trajectory, the previous state $\mathbf{s}_t$ has been sufficiently explored but $\mathbf{s}_{t+1}$ is new:

$$r^i(\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1}) = \max\left(\frac{1}{N(\mathbf{s}_{t+1})} - \frac{1}{N(\mathbf{s}_t)}, 0\right), \tag{1}$$

Here N is the visitation counts. We clip the IR here because we don't want to give a negative IR to the agent if it transits back from a novel state to a familiar state. From the equation, only crossing the frontier matters to the intrinsic reward; if both $N(\mathbf{s}_t)$ and $N(\mathbf{s}_{t+1})$ is high or low, their difference would be small. As we will show in Sec. 4, for each trajectory going towards the frontier/boundary, BeBold assigns an approximately equal IR, regardless of their length. As a result, the agent will continue pushing the frontier of exploration in a much more uniform manner than RND and won't suffer from short-sighted issue. This motivates the agent to explore different trajectories in an alternate order. Also Eq. 1 is asymptotically consistent as $r^i \to 0$ when $N \to \infty$.

Like RIDE (Raileanu and Rocktäschel, 2020), in our implementation, partial observation $\boldsymbol{o}_t$ is used instead of the real state $\mathbf{s}_t$, when $\mathbf{s}_t$ is not available.

Episodic Restriction on Intrinsic Reward (ERIR). In many environments where the state transition is reversible, simply using intrinsic reward to guide exploration would result in the agent going back and force between novel states $\mathbf{s}_{t+1}$ and their previous states $\mathbf{s}_t$. RIDE (Raileanu and Rocktäschel, 2020) avoids this by scaling the intrinsic reward $\mathbf{r}(\mathbf{s})$ by the inverse of the state visitation counts. BeBold puts a more aggressive restriction: the agent is only rewarded when it visits the state $\mathbf{s}$ for the first time in an episode. Thus, the intrinsic reward of BeBold becomes:

$$r^i(\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1}) = \max\left(\frac{1}{N(\mathbf{s}_{t+1})} - \frac{1}{N(\mathbf{s}_t)}, 0\right) * \mathbb{1}\{N_e(\mathbf{s}_{t+1}) = 1\} \tag{2}$$

N_e here stands for episodic state count and is reset every episode. In contrast, the visitation counts N is a life-long memory counting states visitation across the whole training process.

Inverse visitation counts as prediction difference. We use the difference between a teacher ϕ and a student network ϕ' to approximate the visitation counts: $N(\mathbf{s}_{t+1}) \approx \frac{1}{||\phi(\boldsymbol{o}_{t+1}) - \phi'(\boldsymbol{o}_{t+1})||_2}$, here $\boldsymbol{o}_{t+1}$ is the observation to the agent in state $\mathbf{s}_{t+1}$. This yields the following implementation of BeBold:

$$r^i(\mathbf{s}_t, \mathbf{a}_t, \mathbf{s}_{t+1}) = \max(||\phi(\boldsymbol{o}_{t+1}) - \phi'(\boldsymbol{o}_{t+1})||_2 - ||\phi(\boldsymbol{o}_t) - \phi'(\boldsymbol{o}_t)||_2, 0) * \mathbb{1}\{N_e(\boldsymbol{o}_{t+1}) = 1\}) \tag{3}$$

Shared visitation counts $N(\mathbf{s}_t)$ in the training of Procedurally-Generated (PG) Environments. During training, the environment keeps changing (e.g., blue keys becomes red), while the semantic links of these objects remain the same. We use a shared RND (ϕ, ϕ') across different PG environment, and treat these semantically similar states as new without using domain knowledge (e.g., image down-sampling like in Go-Explore (Ecoffet et al., 2019)). Partial observability and generalization of neural network ϕ naturally handles them and leads to count-sharing. For episodic count $N_e(\boldsymbol{o}_{t+1})$, since it is not shared across episode (and environment), we use a hash table.

4 CONCEPTUAL ADVANTAGES OF BEBOLD OVER EXISTING CRITERIA

Short-sightedness and Detachment. One issue in count-based approach is its short-sightedness. Let's assume in a simple environment, there are M corridors $\{\tau_j\}_{j=1}^M$ starting at $\mathbf{s}_0$ and extends to different part of the environment. The corridor τ_j has a length of T_j. The agent starts at $\mathbf{s}_0$. For each visited state, the agent receives the reward of $\frac{1}{N(\mathbf{s})}$ where $N(\cdot)$ is the visitation count, and learns with Q-learning. Then with some calculation (See Appendix), we could see that the agent has a strong preference on exploring the longest corridor first (say τ_1), and only after very late, it starts to explore the second longest, and so on. This is because the agent initially receives high IR in τ_1 due to its length, which makes the policy π visit τ_1 more often, until it depletes the IR in τ_1.

This behavior of "dedication" could lead to serious issues. If $M \geq 3$ and 2 corridors are long enough (say τ_1 and τ_2 are long), then before the agent is able to explore other corridors, its policy π

has already been trained long enough so that it only remembers how to get into τ_1 and τ_2. When τ_1 has depleted its IR, the agent goes to τ_2 following the policy. After that, the IR in τ_1 *revives* since the visitation counts in τ_1 is now comparable or even smaller than τ_2, which lures the agent to explore τ_1 again following the policy. This leaves other corridors (e.g., τ_3) unexplored for a very long time. Note that using a neural network approximated IR (RND) instead of tabular IR could potentially alleviate this issue, but it is often far less than enough in complex environments.

As mentioned in Go-Explore series (Ecoffet et al., 2019; 2020), count-based approaches also suffer from *detachment*: if the agent by chance starts exploring τ_2 after briefly explored the first few states of τ_1, it won't come back and explore τ_1 further since τ_1 is now "shorter" than τ_2 and has lower IR than τ_2 until very late. Go-Explore tries to resolve this dilemma between "dedication" and "exploration" by using a two-stage approach with many hand-tuned parameters.

In contrast, IR of BeBold depends on the *difference* of the visitation count along the trajectory, and is insensitive to the *length* of the corridor. This leads to *simultaneous* exploration of multiple corridors and yields a diverse policy π (See Sec. 5.2 for empirical evidences). Moreover, the IR focuses on the boundary between explored and unexplored regions, where the two goals (dedication and exploration) align, yielding a much cleaner and one-stage method.

Asymptotic Inconsistency. Approaches that define IR as difference between state representations $\|\psi(\mathbf{s}) - \psi(\mathbf{s}')\|$ (ψ is a learned embedding network) (Zhang et al., 2019; Marino et al., 2019) suffer from asymptotic inconsistency: their IR does not vanish even after sufficient exploration: $r^i \nrightarrow 0$ when $N \rightarrow \infty$. This is because when the embedding network ψ converges after sufficient exploration, the agent can always get a nonzero IR if a major change in state representation occurs (e.g., opening a door or picking up a key in MiniGrid). Therefore, the final learned policy does not maximize the extrinsic reward r^e, deviating from the goal of reinforcement learning. Automatic curriculum approaches (Campero et al., 2020)) have similar issues due to an ever-present IR.

For this, (Zhang et al., 2019) proposes to learn a separate scheduler to switch between intrinsic and extrinsic rewards, and (Raileanu and Rocktäschel, 2020) divides the state representation difference by the square root of visitation counts. In comparison, BeBold does not require extra stage and is a much simpler solution.

5 EXPERIMENTS

We evaluate BeBold on challenging procedurally-generated environments: MiniGrid (Chevalier-Boisvert et al., 2018) and the hard-exploration environment NetHack (Küttler et al., 2020). These environments provide a good testbed for exploration in RL since the observations are symbolic rather than raw sensor input (e.g., visual input), which decouples perception from exploration. In MiniGrid, we compare BeBold with baselines like RND (Burda et al., 2018b), ICM (Pathak et al., 2017), RIDE (Raileanu and Rocktäschel, 2020) and AMIGo (Campero et al., 2020). We only evaluate AMIGo for 120M steps in our experiments, the algorithm gets better results when trained for 500M steps as shown in (Campero et al., 2020). For all the other baselines, we follow the exact training paradigm from (Raileanu and Rocktäschel, 2020). Mean and standard deviation across four runs of different seeds is computed. BeBold successfully solves 12 most challenging environments provided by MiniGrid while all the baselines end up with zero reward on half of the environments we tested. In NetHack, BeBold also achieves SoTA results with a strong margin over baselines.

5.1 MINIGRID ENVIRONMENTS

We mainly use three challenging environments from MiniGird: *Multi-Room* (**MR**), *Key Corridor* (**KC**) and *Obstructed Maze* (**OM**). We use these abbreviations for the remaining of the paper (e.g., `OM2Dlh` stands for ObstructedMaze2Dlh). Fig. 2 shows one example of a rendering on `OMFull` as well as all the environments we tested with their relative difficulty. BeBold is also tested on other easier deterministic environments (except for those with dynamic objects) and solve them all.

In MiniGrid, all the environments are size $N \times N$ (N is environment specific) with each tile contains some of the objects: wall, door, key, ball, chest. The action space is defined as turn left, turn right, move forward, pickup an object, drop an object and toggle an object (e.g., open or close a door). **MR** consists of a series of rooms connected by doors and the agent must open the door to get to the next room. The final success is achieved when the agent reaches the goal. In **KC**, agent has to explore the environment to find the key and open the door along the way to achieve success. **OM** is the hardest: the doors are locked, the keys are hidden in boxes and doors are obstructed by balls.

Figure 2: MiniGrid Environments. **Left:** a procedurally-generated `OMFull` environment. **Right:** BeBold solves challenging tasks which previous approaches cannot solve. Note that we evaluate all methods for 120M steps. AMIGo gets better results when trained for 500M steps as shown in (Campero et al., 2020).

Figure 3: Results for various hard exploration environments from MiniGrid. BeBold successfully solves all the environments while all other baselines only manage to solve two to three relatively easy ones.

Results. We test BeBold on all the challenging environments from MiniGrid. BeBold manages to solve 12 most challenging environments while all other baselines can only solve up to medium level tasks and fail to make any progress on all the other ones. Note that some medium tasks we define here are categorized as hard tasks in RIDE and AMIGo (e.g., `KCS4R3` is labeled as "KCHard" and `KCS5R3` is labeled as "KCHarder"). Fig. 3 shows the results of our experiments. Half of the environments (e.g., `KCS6R3`, `OM1Q`) are extremely hard and all the baselines fail. In contrast, BeBold easily solves all such environments listed above without any curriculum.

Multi Room environments are relatively easy in MiniGrid. However, still all the baselines except RIDE fail. As we increase the room size and number (e.g., `MRN12S10`), BeBold can achieve goal quicker than RIDE. Our method easily solves these environments within 20M environment steps.

On Key Corridor environments, RND, AMIGo, RIDE, IMPALA and BeBold successfully solves `KCS3R3` while ICM makes reasonable progress. However, when we increase the room size (e.g., `KCS5R3`), none of the baseline methods work. BeBold manages to solve these environments in 40M environment steps. The agent demonstrates the ability to explore the room and finds the corresponding key to open the door in a randomized, procedurally-generated environment.

Obstructed Maze environments are also very difficult. As shown in Fig. 3, only RIDE manages to solve the easiest task `OM2Dlh` which doesn't contain any obstructions. In contrast, BeBold not only rapidly solves `OM2Dlh`, but also successfully solves four more challenging environments including `OMFull`. These environments have obstructions blocking the door (as shown in Fig. 2) and are much larger in size than `OM2Dlh`. In these environments, our agent learns to move the obstruction away from the door to open the door and enter the next room. This "skill" is hard to learn since there is no extrinsic reward assigned to moving the obstruction. However, it is critical to the final success.

Figure 4: Normalized visitation counts $N(\mathbf{s}_t)/Z$ (Z is a normalization constant) for the location of agents. BeBold successfully explores all rooms at 4.6M steps while RND gets stuck in the fifth room at 9.8M steps.

Table 1: Visitation counts for the toy corridor environment after 3K episodes. BeBold explores corridors more uniformly than count-based approaches.

	C1	C2	C3	C4	Entropy
Length	40	10	30	10	–
Count-Based	68K	2K	3K	36K	1.23
BeBold Tabular	27K	51K	13K	17K	**1.80**
RND	26K	38K	14K	32K	1.92
BeBold	27K	24K	33K	27K	**1.99**

Table 2: Entropy of th visitation counts of each room. Such state distribution of BeBold is much more uniform than RND.

	0.2M	0.5M	2.0M	5.0M
Room1	3.48 / **3.54**	3.41 / **3.53**	3.51 / **3.56**	3.49 / **3.56**
Room2	**2.87** / −	3.09 / **3.23**	3.51 / **3.53**	3.35 / **3.56**
Room3	− / −	− / −	− / **4.02**	3.42 / **4.01**
Room4	− / −	− / −	− / **2.74**	2.85 / **2.87**

* Results are presented in the order of "RND / BeBold".

5.2 Analysis of Intrinsic Reward using Pure Exploration

We disable the extrinsic reward in this section and only allow IR to guide the exploration.

Shorted-Sighted Problem in Long-Corridor Environment. To verify Sec. 4, we design a toy environment with four disconnected corridors with length 40, 10, 30 and 10 respectively starting from the same state. In this example, There is no extrinsic reward and the exploration of the agent is guided by IR. We combine Q-learning with tabular IR (count-based and BeBold tabular) and neural network approximated IR (RND and BeBold) respectively for this experiment. We remove clipping from BeBold for a fair comparison. Tab. 1 shows the visitation counts w.r.t. each corridor after 3K episodes of training. It is clearly seen that BeBold tabular explores each corridor in a much more uniform manner while count-based approach greatly affected by the short-sighted problem, focuses on two out of four corridors. Using neural network approximated IR could alleviate this problem, but BeBold still outperforms RND. Note that comparing to the analysis in Sec. 4, in practical experiment, we perceive that the preference of the corridors for count-based method can be arbitrary because of the random initialization of the Q-network.

Visitation Counts in MiniGrid. To study how different intrinsic reward can affect the exploration of the agent, we test BeBold and RND in a fixed (instead of procedurally generated for simplicity) `MRN7S8` environment. The environment contains 7 rooms connected by doors. To be a successfully exploration strategy, the agent should explore all the states as much as possible and give all states equal amount of exploration. We define two metrics to measure the effectiveness of an exploration strategy: (1) visitation counts at every state over training $N(\mathbf{s})$, and (2) entropy of visitation counts *in each room*: $\mathcal{H}(\rho'(\mathbf{s}))$ where $\rho'(\mathbf{s}) = \frac{N(\mathbf{s})}{\sum_{\mathbf{s} \in \mathcal{S}_r} N(\mathbf{s})}$. We don't calculate the entropy across all states since the agent always starts in the first room and may not visit the last one that often. As a result, the visitation counts for states in the first room will be several magnitudes larger than the last room.

Fig. 4 shows the heatmap of normalizd visitation counts $N(\mathbf{s}_t)/Z$, where Z is the normalization constant. At first, RND enters the second room faster than BeBold. However, BeBold consistently makes progress by pushing the *frontier* of exploration and discover all the rooms in 5M steps, while RND gets stuck in the fifth room even trained with 10M steps.

In Tab. 2, the entropy of distribution in each room $\mathcal{H}(\rho'(\mathbf{s}))$ for BeBold is larger than that of RND. This suggests that BeBold encourages the agent to explore the state in a much more uniform manner.

Intrinsic Reward Heatmap in MiniGrid. We also plot the heatmap of IR at different training steps. We generate the plot by running the policy from different checkpoints for 2K steps and plot the IR associated with each state in the trajectory. States that do not receive IR from the sampled trajectories are left blank. For BeBold, the IR is computed as the difference of inverse visitation counts (approximated by RND) between consecutive states $\mathbf{s}_t$ and $\mathbf{s}_{t+1}$ in the trajectory. From Fig. 5, we can see that BeBold doesn't suffer from short-sighted problem as we can clearly see that

Figure 5: IR heatmaps for the location of agents. BeBold mitigates the short-sighted problem.

Figure 6: Ablation Study on BeBold comparing with RND with episodic intrinsic reward. BeBold significantly outperforms RND with episodic intrinsic reward on all the environments.

the areas with high IRs are continuously pushed forward from room1 to room7. This is true across the whole training process. On the contrary, the IR heatmap for RND is bouncing between two consecutive rooms. It reveals the problem of short-sightedness because the exhaustive exploration of one room over a period of time will result in the IR of this room significantly lower than the previous one. Thus, the agent will go back and re-explore the previous room.

5.3 ABLATION STUDY

Episodic Restriction on Intrinsic Reward. We analyze the importance of each component in BeBold. To illustrate the importance of exploring beyond the boundary, we compare BeBold with a slightly modified RND: RND with ERIR. We only give RND intrinsic when it visits a new state for the first time in an episode. Results are shown in Fig. 6. We can see that although episodic intrinsic reward helps RND to solve `KCS4R3` and `MRN7S8`, without beyond the boundary exploration, the method still fails on more challenging tasks `KCS5R3` and `MRN12S10`. A symmetric experiment of removing ERIR from BeBold is also conducted.

Clipping in Beyond the Boundary Exploration. We also study the role of clipping $\max(\cdot, 0)$ in our method. Fig. 6 shows the effect of removing clipping from BeBold. It turns out it is very important we don't give the agent a negative reward when it transit from an unfamiliar state to a familiar state.

5.4 THE NETHACK LEARNING ENVIRONMENT

To evaluate BeBold on a more challenging and realistic environment, we choose the NetHack Learning Environment (Küttler et al., 2020). In the game, the player is assigned a role of hero at the beginning of the game. The player needs to descend over 50 procedurally-generated levels to the bottom and find "Amulet of Yendor" in the dungeon The procedure can be described as first retrieve the amulet, then escape the dungeon and finally unlock five challenging levels (the four Elemental Planes and the Astral Plane). We test BeBold on a set of tasks with tractable subgoals in the game: **Staircase**: navigating to a staircase to the next level, **Pet**: reaching a staircase and keeping the pet alive, **Gold**: collecting gold, **Score**: maximizing the score in the game, **Scout**: scouting to explore unseen areas in the environment, and **Oracle**: finding the oracle (an in-game character at level 5-9).

Results in Fig. 7 show that BeBold surpasses RND and IMPALA on all tasks[1]. Especially on **Pet**, BeBold outperforms the other two with a huge margin. This again illustrates the strong performance of BeBold in a environment with huge action spaces and long-horizon reward (several magnitudes longer than StarCraft and Dota2). **Oracle** is the hardest task and no approaches is able to find the oracle and obtain a reward of 1000. BeBold still manages to find a policy with less negative rewards (i.e., penalty of taking actions that do not lead to game advancement, like move towards a wall). For

---

[1]For **Gold** task, there has recently been a small fix introduced to the environment. We benchmark all methods before the fix, and will update the results.

Figure 7: Results for tasks on NetHack. BeBold achieves the SoTA results comparing to RND and IMPALA.

RIDE, we contacted the authors and they haven't get it working on NetHack. We also tune it by ourselves but to no vail. So the performance is not reported.

6 RELATED WORK

In addition to the two criteria (*count*-based and *state-diff* based) mentioned above, another stream of defining IRs is *curiosity*-based. The main idea is to encourage agent to explore areas where the prediction of the next state from the current learned dynamical model is wrong. Dynamic-AE (Stadie et al., 2015) computes the distance between the predicted and the real state on the output of an autoencoder, ICM (Pathak et al., 2017) learns the state representation through a forward and inverse model and EMI (Kim et al., 2018) computes the representation through maximizng mutual information $\mathcal{I}([\mathbf{s}, a]; \mathbf{s}')$ and $\mathcal{I}([\mathbf{s}, \mathbf{s}']; a)$.

Another line of research is using information gain to reward the agent. VIME (Houthooft et al., 2016) uses a Bayesian network to measure the uncertainty of the learned model. Later, to reduce computation, a deterministic approach has been adopted (Achiam and Sastry, 2017). Other works also propose to use ensemble of networks for measuring uncertainty (Pathak et al., 2019; Shyam et al., 2019). We can also reward the agent by Empowerment (Klyubin et al., 2005; Gregor et al., 2016; Salge et al., 2014; Mohamed and Rezende, 2015), prioritizing the states that agent can take control through its actions. It is different from state-diff: if $\mathbf{s}_{t+1}$ differs from $\mathbf{s}_t$ but *not* due to agent's choice of actions, then the empowerment at $\mathbf{s}_t$ is zero. Other criteria exist, e.g., diversity (Eysenbach et al., 2018), feature control (Jaderberg et al., 2016; Dilokthanakul et al., 2019) or the KL divergence between current distribution over states and a target distribution of states (Lee et al., 2019).

Outside of intrinsic reward, researchers have proposed to use randomized value functions to encourage exploration (Osband et al., 2016; Hessel et al., 2017; Osband et al., 2019). Adding noise to the network also shown to be effective (Fortunato et al., 2017; Plappert et al., 2017). There has also been effort putting to either explicitly or implicitly separate exploration and exploitation (Colas et al., 2018; Forestier et al., 2017; Levine et al., 2016). The recently proposed Go-Explore series (Ecoffet et al., 2019; 2020) also fall in this category. We might also set up different goals for exploration (Guo and Brunskill, 2019; Oh et al., 2018; Andrychowicz et al., 2017).

Curriculum learning (Bengio et al., 2009) has also been used to solve hard exploration environments. The curriculum can be explicitly generated by: searching the space (Schmidhuber, 2013), teacher-student setting (Matiisen et al., 2019), increasing distance between starting point and goal (Jabri et al., 2019) or using a density model to generate a task distribution for the meta learner (Florensa et al., 2017). Our work can also be viewed as an implicit curriculum learning as gradually encourages the agent to expand the area of exploration. However, it never explicitly generates curriculum.

7 CONCLUSION

In this work, we propose a new criterion for intrinsic reward (IR) that encourages exploration beyond the boundary of explored regions using regulated difference of inverse visitation count along a trajectory. Based on this criterion, the proposed algorithm BeBold successfully solves 12 most challenging tasks in procedurally-generated MiniGrid environment with a significant improvement over the previous SoTA, overcoming short-sighted problems haunted in count-based exploration. We also evaluate BeBold on NetHack, a much more challenging environment. BeBold outperforms all the baselines with a good margin. In summary, this simple criterion and the algorithm shows effectiveness in solving sparse reward problem in reinforcement learning (RL), opening up new opportunity to many real-world applications.

REFERENCES

Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Belle-mare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

Adrià Puigdomènech Badia, Bilal Piot, Steven Kapturowski, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, and Charles Blundell. Agent57: Outperforming the atari human benchmark. *arXiv preprint arXiv:2003.13350*, 2020a.

Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Juny-oung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko Georgiev, et al. Grandmaster level in starcraft ii using multi-agent reinforcement learning. *Nature*, 575(7782):350–354, 2019.

David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484–489, 2016.

David Silver, Julian Schrittwieser, Karen Simonyan, Ioannis Antonoglou, Aja Huang, Arthur Guez, Thomas Hubert, Lucas Baker, Matthew Lai, Adrian Bolton, et al. Mastering the game of go without human knowledge. *nature*, 550(7676):354–359, 2017.

David Silver, Thomas Hubert, Julian Schrittwieser, Ioannis Antonoglou, Matthew Lai, Arthur Guez, Marc Lanctot, Laurent Sifre, Dharshan Kumaran, Thore Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

Greg Brockman, Vicki Cheung, Ludwig Pettersson, Jonas Schneider, John Schulman, Jie Tang, and Wojciech Zaremba. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

Matej Moravčík, Martin Schmid, Neil Burch, Viliam Lisỳ, Dustin Morrill, Nolan Bard, Trevor Davis, Kevin Waugh, Michael Johanson, and Michael Bowling. Deepstack: Expert-level artificial intelligence in heads-up no-limit poker. *Science*, 356(6337):508–513, 2017.

Marc Bellemare, Sriram Srinivasan, Georg Ostrovski, Tom Schaul, David Saxton, and Remi Munos. Unifying count-based exploration and intrinsic motivation. In *Advances in neural information processing systems*, pages 1471–1479, 2016.

Jürgen Schmidhuber. Formal theory of creativity, fun, and intrinsic motivation (1990–2010). *IEEE Transactions on Autonomous Mental Development*, 2(3):230–247, 2010.

Deepak Pathak, Pulkit Agrawal, Alexei A Efros, and Trevor Darrell. Curiosity-driven exploration by self-supervised prediction. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition Workshops*, pages 16–17, 2017.

Yuri Burda, Harri Edwards, Deepak Pathak, Amos Storkey, Trevor Darrell, and Alexei A Efros. Large-scale study of curiosity-driven learning. *arXiv preprint arXiv:1808.04355*, 2018a.

Yuri Burda, Harrison Edwards, Amos Storkey, and Oleg Klimov. Exploration by random network distillation. *arXiv preprint arXiv:1810.12894*, 2018b.

Georg Ostrovski, Marc G Bellemare, Aaron van den Oord, and Rémi Munos. Count-based explo-ration with neural density models. *arXiv preprint arXiv:1703.01310*, 2017.

Adrià Puigdomènech Badia, Pablo Sprechmann, Alex Vitvitskyi, Daniel Guo, Bilal Piot, Steven Kapturowski, Olivier Tieleman, Martín Arjovsky, Alexander Pritzel, Andew Bolt, et al. Never give up: Learning directed exploration strategies. *arXiv preprint arXiv:2002.06038*, 2020b.

Jingwei Zhang, Niklas Wetzel, Nicolai Dorka, Joschka Boedecker, and Wolfram Burgard. Sched-uled intrinsic drive: A hierarchical take on intrinsically motivated exploration. *arXiv preprint arXiv:1903.07400*, 2019.

Kenneth Marino, Abhinav Gupta, Rob Fergus, and Arthur Szlam. Hierarchical RL using an ensem-ble of proprioceptive periodic policies. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=SJz1x20cFQ.

Adrien Ecoffet, Joost Huizinga, Joel Lehman, Kenneth O Stanley, and Jeff Clune. Go-explore: a new approach for hard-exploration problems. *arXiv preprint arXiv:1901.10995*, 2019.

Maxime Chevalier-Boisvert, Lucas Willems, and Suman Pal. Minimalistic gridworld environment for openai gym. https://github.com/maximecb/gym-minigrid, 2018.

Heinrich Küttler, Nantas Nardelli, Alexander H Miller, Roberta Raileanu, Marco Selvatici, Edward Grefenstette, and Tim Rocktäschel. The nethack learning environment. *arXiv preprint arXiv:2006.13760*, 2020.

Roberta Raileanu and Tim Rocktäschel. Ride: Rewarding impact-driven exploration for procedurally-generated environments. *arXiv preprint arXiv:2002.12292*, 2020.

Andres Campero, Roberta Raileanu, Heinrich Küttler, Joshua B Tenenbaum, Tim Rocktäschel, and Edward Grefenstette. Learning with amigo: Adversarially motivated intrinsic goals. *arXiv preprint arXiv:2006.12122*, 2020.

Anirudh Goyal, Riashat Islam, Daniel Strouse, Zafarali Ahmed, Matthew Botvinick, Hugo Larochelle, Yoshua Bengio, and Sergey Levine. Infobot: Transfer and exploration via the information bottleneck. *arXiv preprint arXiv:1901.10902*, 2019.

Adrien Ecoffet, Joost Huizinga, Joel Lehman, Kenneth O Stanley, and Jeff Clune. First return then explore. *arXiv preprint arXiv:2004.12919*, 2020.

Brian Yamauchi. A frontier-based approach for autonomous exploration. In *Proceedings 1997 IEEE International Symposium on Computational Intelligence in Robotics and Automation CIRA'97.'Towards New Computational Principles for Robotics and Automation'*, pages 146–151. IEEE, 1997.

Brian Yamauchi. Frontier-based exploration using multiple robots. In *Proceedings of the second international conference on Autonomous agents*, pages 47–53, 1998.

Anirudh Topiwala, Pranav Inani, and Abhishek Kathpal. Frontier based exploration for autonomous robot. *arXiv preprint arXiv:1806.03581*, 2018.

Bradly C Stadie, Sergey Levine, and Pieter Abbeel. Incentivizing exploration in reinforcement learning with deep predictive models. *arXiv preprint arXiv:1507.00814*, 2015.

Hyoungseok Kim, Jaekyeom Kim, Yeonwoo Jeong, Sergey Levine, and Hyun Oh Song. Emi: Exploration with mutual information. *arXiv preprint arXiv:1810.01176*, 2018.

Rein Houthooft, Xi Chen, Yan Duan, John Schulman, Filip De Turck, and Pieter Abbeel. Vime: Variational information maximizing exploration. In *Advances in Neural Information Processing Systems*, pages 1109–1117, 2016.

Joshua Achiam and Shankar Sastry. Surprise-based intrinsic motivation for deep reinforcement learning. *arXiv preprint arXiv:1703.01732*, 2017.

Deepak Pathak, Dhiraj Gandhi, and Abhinav Gupta. Self-supervised exploration via disagreement. *arXiv preprint arXiv:1906.04161*, 2019.

Pranav Shyam, Wojciech Jaśkowski, and Faustino Gomez. Model-based active exploration. In *International Conference on Machine Learning*, pages 5779–5788, 2019.

Alexander S Klyubin, Daniel Polani, and Chrystopher L Nehaniv. All else being equal be empowered. In *European Conference on Artificial Life*, pages 744–753. Springer, 2005.

Karol Gregor, Danilo Jimenez Rezende, and Daan Wierstra. Variational intrinsic control. *arXiv preprint arXiv:1611.07507*, 2016.

Christoph Salge, Cornelius Glackin, and Daniel Polani. Empowerment–an introduction. In *Guided Self-Organization: Inception*, pages 67–114. Springer, 2014.

Shakir Mohamed and Danilo Jimenez Rezende. Variational information maximisation for intrinsically motivated reinforcement learning. In *Advances in neural information processing systems*, pages 2125–2133, 2015.

Benjamin Eysenbach, Abhishek Gupta, Julian Ibarz, and Sergey Levine. Diversity is all you need: Learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

Max Jaderberg, Volodymyr Mnih, Wojciech Marian Czarnecki, Tom Schaul, Joel Z Leibo, David Silver, and Koray Kavukcuoglu. Reinforcement learning with unsupervised auxiliary tasks. *arXiv preprint arXiv:1611.05397*, 2016.

Nat Dilokthanakul, Christos Kaplanis, Nick Pawlowski, and Murray Shanahan. Feature control as intrinsic motivation for hierarchical reinforcement learning. *IEEE transactions on neural networks and learning systems*, 30(11):3409–3418, 2019.

Lisa Lee, Benjamin Eysenbach, Emilio Parisotto, Eric Xing, Sergey Levine, and Ruslan Salakhutdinov. Efficient exploration via state marginal matching. *arXiv preprint arXiv:1906.05274*, 2019.

Ian Osband, Charles Blundell, Alexander Pritzel, and Benjamin Van Roy. Deep exploration via bootstrapped dqn. In *Advances in neural information processing systems*, pages 4026–4034, 2016.

Matteo Hessel, Joseph Modayil, Hado Van Hasselt, Tom Schaul, Georg Ostrovski, Will Dabney, Dan Horgan, Bilal Piot, Mohammad Azar, and David Silver. Rainbow: Combining improvements in deep reinforcement learning. *arXiv preprint arXiv:1710.02298*, 2017.

Ian Osband, Benjamin Van Roy, Daniel J Russo, and Zheng Wen. Deep exploration via randomized value functions. *Journal of Machine Learning Research*, 20(124):1–62, 2019.

Meire Fortunato, Mohammad Gheshlaghi Azar, Bilal Piot, Jacob Menick, Ian Osband, Alex Graves, Vlad Mnih, Remi Munos, Demis Hassabis, Olivier Pietquin, et al. Noisy networks for exploration. *arXiv preprint arXiv:1706.10295*, 2017.

Matthias Plappert, Rein Houthooft, Prafulla Dhariwal, Szymon Sidor, Richard Y Chen, Xi Chen, Tamim Asfour, Pieter Abbeel, and Marcin Andrychowicz. Parameter space noise for exploration. *arXiv preprint arXiv:1706.01905*, 2017.

Cédric Colas, Olivier Sigaud, and Pierre-Yves Oudeyer. Gep-pg: Decoupling exploration and exploitation in deep reinforcement learning algorithms. *arXiv preprint arXiv:1802.05054*, 2018.

Sébastien Forestier, Yoan Mollard, and Pierre-Yves Oudeyer. Intrinsically motivated goal exploration processes with automatic curriculum learning. *arXiv preprint arXiv:1708.02190*, 2017.

Sergey Levine, Chelsea Finn, Trevor Darrell, and Pieter Abbeel. End-to-end training of deep visuomotor policies. *The Journal of Machine Learning Research*, 17(1):1334–1373, 2016.

Zhaohan Daniel Guo and Emma Brunskill. Directed exploration for reinforcement learning. *arXiv preprint arXiv:1906.07805*, 2019.

Junhyuk Oh, Yijie Guo, Satinder Singh, and Honglak Lee. Self-imitation learning. *arXiv preprint arXiv:1806.05635*, 2018.

Marcin Andrychowicz, Filip Wolski, Alex Ray, Jonas Schneider, Rachel Fong, Peter Welinder, Bob McGrew, Josh Tobin, OpenAI Pieter Abbeel, and Wojciech Zaremba. Hindsight experience replay. In *Advances in neural information processing systems*, pages 5048–5058, 2017.

Yoshua Bengio, Jérôme Louradour, Ronan Collobert, and Jason Weston. Curriculum learning. In *Proceedings of the 26th annual international conference on machine learning*, pages 41–48, 2009.

Jürgen Schmidhuber. Powerplay: Training an increasingly general problem solver by continually searching for the simplest still unsolvable problem. *Frontiers in psychology*, 4:313, 2013.

Tambet Matiisen, Avital Oliver, Taco Cohen, and John Schulman. Teacher-student curriculum learning. *IEEE transactions on neural networks and learning systems*, 2019.

Allan Jabri, Kyle Hsu, Abhishek Gupta, Ben Eysenbach, Sergey Levine, and Chelsea Finn. Unsupervised curricula for visual meta-reinforcement learning. In *Advances in Neural Information Processing Systems*, pages 10519–10531, 2019.

Carlos Florensa, David Held, Markus Wulfmeier, Michael Zhang, and Pieter Abbeel. Reverse curriculum generation for reinforcement learning. *arXiv preprint arXiv:1707.05300*, 2017.

A   SOME ANALYSIS BETWEEN COUNT-BASED APPROACHES AND OUR APPROACH

Consider two corridors, left and right. The left corridor has length T_l while the right corridor has length T_r. Both starts with an initial state s_0. When the game starts, the agent was always placed at s_0.

For simplicity, we just assume there is only a binary action (left or right) to be chosen at the starting point s_0, after that the agent just moves all the way to the end of the corridor and the game restarts. And we set the discount factor $\gamma = 1$.

Using count-based approach, the accumulated intrinsic reward received by the agent if moving to the left corridor for the i-th time is $R_l := T_l/i$. This is because for each state, the first time the agent visit it, it gets a reward of 1 and the second time it gets a reward of $1/2$, etc. And this is true for every state in this corridor. Similarly, for i-th time moving right, it is $R_r := T_r/i$.

Now let's think how the policy of the agent is trained. In general, the probability to take action left or right is proportional to the accumulated reward. In Q learning it is an exponential moving average of the past reward due to the update rule $Q(s, a) \leftarrow (1 - \alpha)Q(s, a) + \alpha R$ for α typically small (e.g., 0.01). If we think about Q learning starting with $Q(s_0, \text{left}) = Q(s_0, \text{right}) = 0$, and consider the situation when the agent has already done n_l left and n_r right actions, then we have:

$$Q(s_0, \text{left}) = T_l \alpha \sum_{i=1}^{n_l} \frac{(1 - \alpha)^{n_l - i}}{i} \qquad (4)$$

Similarly, we have

$$Q(s_0, \text{right}) = T_r \alpha \sum_{i=1}^{n_r} \frac{(1 - \alpha)^{n_r - i}}{i} \qquad (5)$$

We could define $\phi(n) := \alpha \sum_{i=1}^{n} \frac{(1-\alpha)^{n-i}}{i}$ and thus $Q(s_0, \text{left}) = T_l \phi(n_r)$ and $Q(s_0, \text{right}) = T_r \phi(n_r)$.

If we treat $\phi(\cdot)$ as a function in the real domain, and assign visiting probability $\pi(a|s_0) \propto Q(s_0, a)$, then the visitation counts, now is denoted as x_l and x_r since they are continuous, for left and right satisfies the following differential equations:

$$\dot{x}_l = \frac{T_l \phi(x_l)}{T_l \phi(x_l) + T_r \phi(x_r)}, \quad \dot{x}_r = \frac{T_r \phi(x_r)}{T_l \phi(x_l) + T_r \phi(x_r)} \qquad (6)$$

In the following, we will show that if $T_l \neq T_r$, long corridor will dominate the exploration since it has a lot of rewards until very late. Suppose $x_l(0) = x_r(0) = 1$ and $T_l > T_r$, that is, left side has longer corridor than right side. Then from the equations, very quickly $x_l > x_r$. For α close to 0, we could check that $\phi(x)$ is a monotonously increasing function when x is a small positive number, since the more an agent visits a corridor, the more reward it obtains. So this creates a positive feedback and the growth of x_l dominates, which means that the policy will almost always visit left. This happens until after x_l is large enough and $\phi(x_l)$ starts to decay because of diminishing new rewards and the training discount α. The decay is on the order of like $\frac{1}{x_l}$, then the agent will finally start to visit the right side. Indeed, $\pi(\text{right}|s_0) > 50\%$ if $T_r \alpha > T_l/x_l$, or $x_l > \frac{T_l}{T_r}\frac{1}{\alpha}$. In comparison, if we pick sides in a uniform random manner, when x_l is this big, x_r should also be comparable (while here x_r can be as small as 1 or 2).

If an agent have K corridors to pick with $T_1 > T_2 > \ldots > T_K$, things will be similar.

When $T_l = T_r$, the dynamics is perfectly symmetric and the agent visits both left and right with $1/2$ probability. Since this symmetry is quite rare, count-based exploration is often biased towards one or two corridors (See Tbl. 1), BeBold uses difference of inverse visitation counts as intrinsic rewards, and thus balance the exploration.

B   HYPERPARAMETERS FOR MINIGRID

Following (Campero et al., 2020), we use the same hyperparameters for all the baselines. For ICM, RND, IMPALA, RIDE and BeBold, we use the learning rate 10^{-4}, batch size 32, unroll

Figure 8: On policy state density heatmaps $\rho_\pi(\mathbf{s}_t)$. BeBold continuously pushes the frontier of exploration from Room1 to Room7.

length 100, RMSProp optimizer with $\epsilon = 0.01$ and momentum 0. We also sweep the hyperparameters for BeBold: entropy coefficient $\in \{0.0001, 0.0005, 0.001\}$ and intrinsic reward coefficient $\in \{0.01, 0.05, 0.1\}$. We list the best hyperparameters for each method below.

BeBold. For all the Obstructed Maze series environments, we use the entropy coefficient of 0.0005 and the intrinsic reward coefficient of 0.05. For all the other environments, we use the entropy coefficient of 0.0005 and the intrinsic reward coefficient of 0.1. For the hash table used in ERIR, we take the raw inputs and directly use that as the key for visitation counts.

AMIGo. As mentioned in (Campero et al., 2020), we use batch size of 8 for student agent and batch size of 150 for teacher agent. For learning rate, we use learning rate of 0.001 for student agent and learning rate of 0.001 for teacher agent. We use an unroll length of 100, entropy cost of 0.0005 for student agent and entropy cost of 0.01 for teacher agent. Lastly we use $\alpha = 0.7$ and $\beta = 0.3$ for defining IRs in AMIGo.

RIDE. Following (Raileanu and Rocktäschel, 2020), we use entropy coefficient of 0.0005 and intrinsic reward coefficient of 0.1 for key corridor series of environments. For all other environments, we use entropy coefficient of 0.001 and intrinsic reward coefficient of 0.5.

RND. Following (Campero et al., 2020), we use entropy coefficient of 0.0005 and intrinsic reward coefficient of 0.1 for all the environments.

ICM. Following (Campero et al., 2020), we use entropy coefficient of 0.0005 and intrinsic reward coefficient of 0.1 for all the environments.

IMPALA. We use the hyperparameters introduced in first paragraph of this section for the baseline.

C ANALYSIS FOR MINIGRID

In addition to the analysis provided before, we also conduct some other analysis of BeBold in MiniGrid.

On Policy State Density in MiniGrid We also plot the on policy state density $\rho_\pi(\mathbf{s})$ for different checkpoint of BeBold. We ran the policy for 2K steps and plot the BeBold IR based on the consecutive states in the trajectory. In Fig. 8, we can clearly see that the boundary of explored region is moving forward from Room1 to Room7. It is also worth noting that although the policy focuses on exploring one room (one major direction to the boundary.) at a time, it also put a reasonable amount of effort visiting the previous room (other directions of to the boundary). Thus, BeBold greatly alleviate the short-sighted problem aforementioned.

D HYPERPARAMETER FOR NETHACK

For general hyperparameters, we use optimizer RMSProp with a learning rate of 0.0002. No momentum is used and we use $\epsilon = 0.000001$. The entropy cost is set to 0.0001. For RND and BeBold, we scale the the forward distillation loss by a factor of 0.01 to slow down training. We adopt the intrinsic reward coefficient of 100. For the hash table used in ERIR, we take several related infor-

mation (e.g., the position of the agent and the level the agent is in) provided by (Küttler et al., 2020) and use that as the key for visitation counts.