GEOMETRICALLY REGULARIZED AUTOENCODERS FOR NON-EUCLIDEAN DATA

ABSTRACT

Regularization is almost *de rigueur* when designing autoencoders that are sparse and robust to noise. Given the recent surge of interest in machine learning problems involving non-Euclidean data, in this paper we address the regularization of autoencoders on curved spaces. We show that by ignoring the underlying geometry of the data and applying standard vector space regularization techniques, autoencoder performance can be severely degraded, or worse, training can fail to converge. Assuming that both the data space and latent space can be modeled as Riemannian manifolds, we show how to construct regularization terms in a coordinate-invariant way, and develop geometric generalizations of the denoising autoencoder and reconstruction contractive autoencoder such that the essential properties that enable the estimation of the derivative of the log-probability density are preserved. Drawing upon various non-Euclidean data sets, we show that our geometric autoencoder regularization techniques can have important performance advantages over vector-spaced methods while avoiding other breakdowns that can result from failing to account for the underlying geometry.

1 INTRODUCTION

Regularization is almost *de rigueur* when designing autoencoders that are sparse and robust to noise. With appropriate regularization, autoencoders enable representations useful for downstream applications (Bengio et al., 2013), generate plausible data samples (Kingma & Welling, 2013; Rezende et al., 2014), or even obtain information on the data-generating probability density (Vincent et al., 2010; Rifai et al., 2011b).

Existing work on autoencoder regularization has for the most part been confined to vector spaces, i.e., the data are assumed drawn from a vector space. On the other hand, a significant and growing number of problems in machine learning involve data that is non-Euclidean (in some past cases the fact that the data was non-Euclidean was not recognized or ignored). Bronstein et al. (2017) reviews several deep neural network architectures and modeling principles to explicitly deal with data defined on non-Euclidean domains, e.g., data collected from sensor networks, social networks in computational social sciences, or two-dimensional meshes embedded in the three-dimensional space. Other works have also addressed manifold-valued data including human mass and shape data (Kendall, 1984; Freifeld & Black, 2012), directional data (Mardia, 2014), point cloud data (Lee et al., 2022), and MRI imaging data (Fletcher & Joshi, 2007; Banerjee et al., 2015), with several deep neural network architectures proposed to handle such data in a coordinate-invariant way (Huang & Van Gool, 2017; Chakraborty et al., 2020).

The fundamental idea behind these works is that the geometrical structure of the curved space from which the non-Euclidean data are drawn needs to be accounted for properly, so that the output of any deep learning network applied to such input data should not depend on the particular choice of coordinates used to parametrize the data. Ignoring the underlying geometry of the data and simply applying standard vector space techniques can severely degrade performance, or worse, cause training to fail. Autoencoder training and its regularization are no exception.

For example, consider a set of data points on a sphere as shown in Figure 1. When using spherical coordinate representations as inputs to train an autoencoder with a contractive regularization, the trained reconstruction function fails to learn the correct contractive directions towards regions with dense data, especially near the singularity (in this case, the origin

of the spherical coordinates). On the other hand, an autoencoder that properly accounts for the spherical constraints is able to successfully recover the directions as shown.

In this paper we address the regularization of autoencoders on curved spaces. Any loss function used to train or regularize the autoencoder should be formulated in a coordinate-invariant way, i.e., invariant to the choice of local coordinates used to parametrize the data, and instead depend only on the intrinsic properties of the curved space such as curvature or the choice of metric.

(a) Training data   (b) RCAE   (c) GRCAE

Figure 1: Autoencoder training on spherical data sampled from the von Mises-Fisher (vMF) distribution. We train the reconstruction contractive autoencoder (RCAE) and the geometric RCAE (GRCAE). For (b)-(c), we plot the true score vector fields and the score vector fields estimated from the trained autoencoders (denoted by 'True' and 'Estimate,' respectively). The singularity is depicted as green dots.

Assuming that both the data space and latent space can be modeled as Riemannian manifolds, we show how to construct regularization terms and objective functions in a coordinate-invariant way. We also develop geometric generalizations of the denoising autoencoder and reconstruction contractive autoencoder such that the essential properties that enable the estimation of the score, i.e., the log-derivative of the data-generating density, are preserved. We provide some applications that use this property, such as sampling, clustering, and filtering for non-Euclidean data, and also show that the proposed autoencoders can obtain useful representations for non-Euclidean data, especially when noise exists in data. Drawing upon various non-Euclidean data sets, we show that our geometric autoencoder regularization techniques can have important performance advantages over vector-spaced methods – in some cases by significant margins – while avoiding other breakdowns that can result from failing to account for the underlying geometry.

The paper is organized as follows. We describe regularized autoencoders for Euclidean data in Section 2 and propose their coordinate-invariant generalizations to non-Euclidean data in Section 3. We then provide autoencoder training case studies using non-Euclidean data sets in Section 4.

2   REGULARIZED AUTOENCODERS FOR EUCLIDEAN DATA

Mathematically, an autoencoder can be represented as the composition of two mappings $f : \mathbb{R}^D \to \mathbb{R}^d$ (the encoder) and $g : \mathbb{R}^d \to \mathbb{R}^D$ (the decoder), i.e., $r = g \circ f : \mathbb{R}^D \to \mathbb{R}^D$ with the space of hidden variables $\mathbb{R}^d$. Assume there exists a data-generating probability density $\rho : \mathbb{R}^D \to \mathbb{R}$ from which data points on $\mathbb{R}^D$ are drawn. Autoencoder training in a vector space can then be formulated as minimizing the reconstruction error $\int_{\mathbb{R}^D} \|x - g(f(x; \theta_1); \theta_2)\|^2 \, \rho(x) \, dx$ over $\theta = (\theta_1, \theta_2)$, where $x \in \mathbb{R}^D$ denotes an input variable, θ_1 and θ_2 are respectively the parameter sets of the maps f and g, and $\|\cdot\|^2$ is the squared Euclidean norm. In the typical case when $d < D$, the autoencoder engages in a type of dimensionality reduction. By disregarding the assumption that $d < D$, autoencoders have been modeled in the form of deep artificial neural networks accompanied by certain regularization terms to learn useful representations of the data (Bengio et al., 2007; Vincent et al., 2008; 2010; Ranzato et al., 2007; 2008; Kingma & Welling, 2013; Rezende et al., 2014; Rifai et al., 2011b;a). For a more comprehensive review of autoencoders, we refer the reader to Goodfellow et al. (2016).

In the meantime, the effects of regularization have been investigated in some detail in Alain & Bengio (2014) for the denoising autoencoder (DAE) (Vincent et al., 2010) and the reconstruction contractive autoencoder (RCAE). They point out that these regularization methods reduce the autoencoder's sensitivity to the input, while the reconstruction error increases the autoencoder's sensitivity to variations along the region of the highest density in the data space. Reconstruction and regularization together successfully capture variations in such regions while ignoring variations that are orthogonal to it and obtain information on the data-generating probability density. Our focus throughout will be on these two types of regularized autoencoders, i.e., the DAE and the RCAE, but the methods described in this paper are easily generalizable to other autoencoders.

In the standard vector space formulation of the DAE, an input $x \in \mathbb{R}^D$ is assumed corrupted by some noise density $q(\tilde{x}|x)$ to $\tilde{x} \in \mathbb{R}^D$, i.e., $\tilde{x} \sim q(\tilde{x}|x)$. We then seek the reconstruction function $r = \mathrm{g} \circ \mathrm{f} : \mathbb{R}^D \to \mathbb{R}^D$ that minimizes

$$\min_r \int_{\mathbb{R}^D} E_{q(\tilde{x}|x)} \left[\|r(\tilde{x}) - x\|^2 \right] \rho(x) \, dx, \tag{1}$$

where $E_{q(\tilde{x}|x)} \left[\cdot \right]$ denotes the expectation with respect to the noise density $q(\tilde{x}|x)$. A trivial identity mapping $r(x) = x$ can be avoided due to the injected noise.

For the vector space formulation of the RCAE, the objective function is

$$\min_r \int_{\mathbb{R}^D} \left(\|r(x) - x\|^2 + \sigma^2 \mathrm{Tr} \left(\left(\frac{\partial r}{\partial x} \right)^\top \left(\frac{\partial r}{\partial x} \right) \right) \right) \rho(x) \, dx, \tag{2}$$

where σ^2 is a scalar weighting coefficient. The second term in (2) acts as a regularization term to prevent $r(x)$ from becoming the identity mapping $r(x) = x$. (Note that replacing $\left(\frac{\partial r}{\partial x} \right)$ with $\left(\frac{\partial \mathrm{f}}{\partial x} \right)$ in (2) reduces to the objective function for the contractive autoencoder (CAE) (Rifai et al., 2011b).)

For both the DAE under a Gaussian corruption process $\tilde{x} \sim N(x, \sigma^2 I)$ and the RCAE with σ small, the derivative of the log-probability density, which is also referred to as the score, can be estimated from the optimized $r(x)$ as follows (Alain & Bengio, 2014):

$$\frac{\partial \log \rho(x)}{\partial x} = \frac{1}{\rho} \frac{\partial \rho}{\partial x}(x) \approx \frac{r(x) - x}{\sigma^2}. \tag{3}$$

3 REGULARIZED AUTOENCODERS FOR NON-EUCLIDEAN DATA

In this section, we address the problem of autoencoder training for the case when the data points are drawn from an *a priori* known non-Euclidean space $\mathcal{M}$, possibly with another non-Euclidean latent space $\mathcal{N}$. We formulate the reconstruction error and regularization terms in a coordinate-invariant way using notions from Riemannian geometry.[1] We then show that, as in the Euclidean case, it is possible to estimate the score for non-Euclidean data using the trained autoencoders.

3.1 COORDINATE-INVARIANT GENERALIZATIONS OF THE AUTOENCODER COMPONENTS

Referring to Figure 2, let $\mathcal{M}$ be an m-dimensional manifold with local coordinates $x = (x^1, \ldots, x^m)$ and Riemannian metric $ds^2 = \sum_{i=1}^m \sum_{j=1}^m g_{ij}(x) \, dx^i dx^j$. Throughout we use italics to represent local coordinates, e.g., a point $\mathrm{x} \in \mathcal{M}$ has local coordinates $x \in \mathbb{R}^m$, the mapping $\mathrm{r} : \mathcal{M} \to \mathcal{M}$ can be represented in local coordinates as $r : \mathbb{R}^m \to \mathbb{R}^m$. The metric will also be denoted in matrix form as $G(x) = (g_{ij}(x)) \in \mathbb{R}^{m \times m}$.

Figure 2: Local coordinates for the reconstruction mapping $\mathrm{r} : \mathcal{M} \to \mathcal{M}$. Local coordinates are denoted in italics.

We now provide coordinate-invariant generalizations of each component in autoencoder training, especially in (1) and (2), while simultaneously reflecting any intrinsic properties of the manifold $\mathcal{M}$.

Reconstruction error The reconstruction error on Riemannian manifolds can be defined as $\mathrm{dist}(\mathrm{r}(\mathrm{x}), \mathrm{x})^2$, where $\mathrm{dist}(\mathrm{x}, \mathrm{y})$ denotes the minimal geodesic distance between points $\mathrm{x}, \mathrm{y} \in \mathcal{M}$.

Probability function Assume there exists a data-generating probability function $\mathrm{p}_g : \mathcal{M} \to \mathbb{R}$ from which data points on $\mathcal{M}$ are drawn. Denote by $\rho_g : \mathbb{R}^m \to \mathbb{R}$ its representation in local

---

[1] For further mathematical details on Riemannian geometry, we refer the reader to Boothby (1986) and Dubrovin et al. (1992).

coordinates, satisfying $\rho_g(x) > 0$ for all $x \in \mathbb{R}^m$ and $\int_{\mathcal{M}} \rho_g(x)\sqrt{\det G(x)}dx = 1$ (Pennec, 1999), where $\sqrt{\det G(x)}dx$ is the natural volume element induced from the metric. When formulating regularized autoencoders later, p_g (or ρ_g) is used in the form of a weighted volume element $\rho(x)dx = \rho_g(x)\sqrt{\det G(x)}dx$. In practice, the integrations involving $\rho(x)dx$ is approximated as an equally weighted finite sum of the integrands (with $\rho(x)$ excluded) evaluated at given data points.

Contractive regularization The regularizer of RCAE can be interpreted as the Dirichlet energy of $r : \mathbb{R}^D \to \mathbb{R}^D$, measuring how variable the mapping r is (Belkin & Niyogi, 2003; Solomon et al., 2013). The Dirichlet energy has been generalized to mappings between Riemannian manifolds in the theory of harmonic maps (Eells & Sampson, 1964), based on which we formulate the contractive regularization for non-Euclidean settings.

Let $\mathcal{M}$ be the input manifold, and let $\mathcal{N}$ be an n-dimensional output manifold with local coordinates $y = (y^1, \ldots, y^n)$ and Riemannian metric $dr^2 = \sum_{\alpha=1}^{n} \sum_{\beta=1}^{n} h_{\alpha\beta}(y)\, dy^\alpha dy^\beta$. The metric will also be denoted in matrix form as $H(y) = (h_{\alpha\beta}(y)) \in \mathbb{R}^{n\times n}$. In Eells & Sampson (1964) the Dirichlet energy of a smooth map $\mathrm{f} : \mathcal{M} \to \mathcal{N}$ is defined as

$$\int_{\mathcal{M}} \mathrm{Tr}(J^\top HJG^{-1})\sqrt{\det G}\, dx^1 \cdots dx^m, \tag{4}$$

where $J(x) = \left(\frac{\partial f^i}{\partial x^j}(x)\right) \in \mathbb{R}^{n\times m}$ is the differential $\mathrm{df_x} : T_\mathrm{x}\mathcal{M} \to T_\mathrm{y}\mathcal{N}$ denoted in local coordinates. The energy functional in (4) is an intrinsic quantity, i.e., coordinate-invariant. We discuss the coordinate-invariance of (4) and some physical interpretations of minimizing (4) in Appendix A.1 and refer the reader to the extensive literature on the theory and applications of harmonic maps, e.g., Eells & Lemaire (1978; 1988); Park & Brockett (1994); Gu et al. (2004); Jang et al. (2021); Lee et al. (2021b).

To apply this energy functional to autoencoder regularization, we replace the mapping $\mathrm{f} : \mathcal{M} \to \mathcal{N}$ and the Riemannian metric $H(f(x))$ to the reconstruction mapping $\mathrm{r} : \mathcal{M} \to \mathcal{M}$ and $G(r(x))$, respectively, and use the weighted volume element $\rho(x)\, dx$ instead of $\sqrt{\det G}\, dx$. Also note that for the case of non-Euclidean latent space $\mathcal{N}$, the objective in (4) with the volume element $\rho(x)\, dx$ can serve as a geometric regularizer for the contractive autoencoders.

Data corruption process To corrupt an input $\mathrm{x} \in \mathcal{M}$, we sample a tangent vector $\mathrm{v} \in T_\mathrm{x}\mathcal{M}$ from an isotropic zero-mean multivariate Gaussian, i.e., a linear combination of an orthonormal basis for $T_\mathrm{x}\mathcal{M}$ with coefficients sampled from $N(0, \sigma^2 I)$, and then apply the exponential map $\mathrm{Exp_x} : T_\mathrm{x}\mathcal{M} \to \mathcal{M}$ to v. The point $\tilde{\mathrm{x}} = \mathrm{Exp_x}(\mathrm{v})$ can then be interpreted as a corrupted point from x. We denote by $q(\tilde{\mathrm{x}}|\mathrm{x})$ the noise density that samples $\tilde{\mathrm{x}}$ for given x according to this procedure. A data corruption example for data on a sphere (S^2) is illustrated in Figure 3, and a rationale for adopting this way of corruption is explained in Appendix A.2.

Figure 3: A data corruption example for an input $\mathrm{x} \in \mathrm{S}^2$. Tangent vectors (the yellow triangles) are sampled from a zero-mean Gaussian in $T_\mathrm{x}\mathrm{S}^2$ and mapped via the exponential map to black dots, the corrupted points from x. The red dot $\tilde{\mathrm{x}} = \mathrm{Exp_x}(\mathrm{v})$ for $\mathrm{v} \in T_\mathrm{x}\mathrm{S}^2$.

3.2 GEOMETRICALLY REGULARIZED AUTOENCODERS

We now derive coordinate-invariant formulations of the regularized autoencoders presented in (1) and (2). For the reconstruction contractive autoencoder (2), the contractive regularizer modified from (4) (as explained above) is augmented to the reconstruction error term as follows:

$$\min_r \int_{\mathcal{M}} \left(\mathrm{dist}(\mathrm{r(x)}, \mathrm{x})^2 + \sigma^2 \, \mathrm{Tr}\left(\left(\frac{\partial r}{\partial x}\right)^\top G(r) \left(\frac{\partial r}{\partial x}\right) G^{-1} \right) \right) \rho(x)\, dx, \tag{5}$$

where the reconstruction map $\mathrm{r} : \mathcal{M} \to \mathcal{M}$ is expressed in local coordinates as $r : \mathbb{R}^m \to \mathbb{R}^m$, and $G(r)$ denotes the metric at point $r(x)$. We refer to (5) as the geometric RCAE, or GRCAE.

Similarly, the geometric version of the DAE (1), referred to as GDAE, can be formulated as follows:

$$\min_r \int_{\mathcal{M}} E_{q(\tilde{x}|x)} \left[\text{dist}(r(\tilde{x}), x)^2 \right] \rho(x) \, dx, \tag{6}$$

where $E_{q(\tilde{x}|x)} [\,\cdot\,]$ denotes the expectation with respect to the noise density $q(\tilde{x}|x)$ presented above.

From the geometric formulations (5)-(6), we can obtain the following relations between the reconstruction function r and the log of the probability function $\rho_g(x) = \frac{\rho(x)}{\sqrt{\det G(x)}}$.

Theorem 1. *Provided σ^2 is small, the derivative of the log of the probability function $\rho_g(x) = \frac{\rho(x)}{\sqrt{\det G(x)}}$ can be approximated for both the GRCAE and GDAE as*

$$\frac{\partial \log \rho_g(x)}{\partial x} = \frac{1}{\rho_g} \frac{\partial \rho_g}{\partial x}(x) \approx G(x) \left(\frac{r(x) - x}{\sigma^2} \right). \tag{7}$$

The proof of Theorem 1 is provided in Appendix B. Equation (7) can be thought of as a generalization of (3) for non-Euclidean data, and we will refer to $\frac{\partial \log \rho_g(x)}{\partial x}$ as the *geometric score*.

The reconstruction function $r : \mathcal{M} \to \mathcal{M}$ for proposed autoencoders is modeled as a neural network in later experiments, with implementation details provided in Appendix C.

4 EXPERIMENTS

In the experiments, we first verify the validity of using geometrically regularized autoencoders to estimate the geometric score $\frac{\partial \log \rho_g(x)}{\partial x}$ for non-Euclidean data. We then provide some use-cases of the proposed autoencoders to applications utilizing the geometric scores, such as sampling data based on the Langevin Monte Carlo methods (Girolami & Calderhead, 2011) or mode-seeking applications (Fukunaga & Hostetler, 1975; Cheng, 1995; Comaniciu & Meer, 2002), involving real-world non-Euclidean data sets. We also examine the usefulness of the proposed autoencoders in the representation learning perspective, using noisy point cloud data.

4.1 GEOMETRIC SCORE ESTIMATION

For geometric score estimation, we consider the data sampled from $P(n)$, the space of $n \times n$ symmetric positive-definite matrices, endowed with the affine-invariant Riemannian metric (Fletcher & Joshi, 2007). We train the GDAE and GRCAE using synthetic data sampled from m mixtures of isotropic tangent space Gaussians for which the ground truth geometric score values are obtainable. For purposes of comparison, we also use DAE, RCAE, the least-squares log-density gradient method (LSLDG) presented in Sasaki et al. (2014), and also their extension to data on Riemannian manifolds (R-LSLDG) in Ashizawa et al. (2017). Full experimental details are provided in Appendix D.

For a given data set $\{x_1, \ldots, x_N\}$ represented in local coordinates of $P(n)$, the geometric score estimation error (Est. error) is evaluated as follows:

$$\text{Est. error} = \frac{1}{N} \sum_{i=1}^{N} \left(\frac{\partial \log \rho_g}{\partial x} \bigg|_{\text{est}} (x_i) - \frac{\partial \log \rho_g}{\partial x}(x_i) \right)^{\top} G^{-1}(x_i) \left(\frac{\partial \log \rho_g}{\partial x} \bigg|_{\text{est}} (x_i) - \frac{\partial \log \rho_g}{\partial x}(x_i) \right), \tag{8}$$

where $\frac{\partial \log \rho_g}{\partial x} \big|_{\text{est}} (x_i)$ and $\frac{\partial \log \rho_g}{\partial x}(x_i)$ respectively denote the estimated value and the ground truth value for $\frac{\partial \log \rho_g(x)}{\partial x}$ at x_i. The estimation errors measured on $10,000$ test data points are averaged over five runs in Table 1. Note that the GDAE, GRCAE, and R-LSLDG methods show superior performance over DAE, RCAE, and LSLDG in estimating $\frac{\partial \log \rho_g(x)}{\partial x}$. Notably, GRCAE shows the best performance for higher dimensionality and a higher number of mixtures in terms of the estimation error. We also obtain similar tendency for another synthetic data set on the hypersphere $S^n = \{p \in \mathbb{R}^{n+1} \mid \|p\| = 1\}$, and the results are provided in Appendix D.4.

4.2 SAMPLING ON S^2

We can apply the geometric scores estimated from GDAE and GRCAE to the sampling of non-Euclidean data via Riemannian Langevin Monte Carlo (RLMC) methods. The stochastic process

Table 1: Estimation errors for $\frac{\partial \log \rho_g}{\partial x}$ for m mixtures of tangent space Gaussian data on P(n) with the standard errors in parentheses. Bolds represent the best and comparable methods from the t-test with a significance level of 5%.

n	m	LSLDG	DAE	RCAE	R-LSLDG	GDAE (ours)	GRCAE (ours)
2	2	10.5 (0.87)	8.72 (3.03)	9.04 (2.49)	3.84 (0.19)	3.55 (0.31)	**2.61** (0.20)
3	2	30.0 (0.91)	17.9 (1.23)	18.1 (1.83)	5.64 (0.19)	4.95 (0.27)	**4.33** (0.34)
3	3	37.6 (2.16)	21.0 (0.97)	22.4 (1.18)	**7.07** (0.31)	**6.86** (0.96)	**5.85** (1.07)
4	2	75.5 (0.85)	42.4 (0.69)	43.8 (1.01)	9.67 (0.78)	**7.72** (0.60)	**6.97** (0.39)
4	3	90.8 (1.91)	59.5 (4.41)	63.3 (6.25)	**12.2** (1.45)	**11.8** (0.71)	**10.5** (1.06)
4	4	88.4 (0.82)	73.2 (2.98)	78.1 (4.76)	13.9 (0.82)	16.0 (1.29)	**12.6** (0.28)

for the RLMC methods in Girolami & Calderhead (2011) can be reformulated using the geometric score in (7) as follows:

$$dx = \frac{1}{2}\left(G^{-1}(x)\frac{\partial \log \rho_g(x)}{\partial x} - \frac{1}{\beta}G^{-1}(x)\frac{\partial \beta}{\partial x} + \Psi(x)\right)dt + \sqrt{G^{-1}(x)}dw, \quad (9)$$

where $dw \in \mathbb{R}^m$ is the Brownian motion in an m-dimensional vector space, $\beta(x) = 1/\sqrt{\det G(x)}$, and $\Psi(x) \in \mathbb{R}^m$ is a vector whose i-th component is given by $\sum_{j=1}^{m}\frac{\partial g^{ij}}{\partial x^j}$ with g^{ij} as the (i,j) element of $G^{-1}(x)$. A discretization of the above process gives the RLMC method (Girolami & Calderhead, 2011). Note that in (9), the terms except for $\frac{1}{2}G^{-1}(x)\frac{\partial \log \rho_g(x)}{\partial x}dt$ correspond to the Brownian motion on manifolds (Brockett, 1997).

As an illustrative case study, we consider sampling on a sphere (S^2). After training DAE, RCAE, GDAE, and GRCAE for data points on S^2 shown in Figure 4 (left), we sample new data points that approximately follow the original data distribution by applying the RLMC methods using the geometric scores estimated from GDAE/GRCAE and its Euclidean counterparts using DAE/RCAE. We also report the results obtained from the S-Flow method (a variation of the M-Flow method (Brehmer & Cranmer, 2020) for the case of S^2). The experimental details are provided in Appendix E.

For a quantitative comparison of the sampling performances, the maximum mean discrepancy (MMD) (Gretton et al., 2012) between a test data set and the obtained samples is provided in Table 2. As can be seen from the table and Figure 4, among the considered autoencoders, GDAE shows the best performance both quantitatively and qualitatively. Even though the samples from GDAE do not yield better numerical results than those from the S-Flow method, an algorithm targeted for data sampling, it is observed that plausible samples can be obtained. Also note that the samples obtained from RCAE and GRCAE tend to be inferior to those from DAE and GDAE in this task, possibly due to the algorithmic properties of RCAE/GRCAE that, unlike DAE/GDAE, the inputs to neural networks are strictly confined to the given training data. Thus the reconstruction functions may not be accurately trained on other regions visited during the sampling process compared to DAE/GDAE.

Table 2: The MMD measure (the lower, the better) between the test and the sampled data with standard errors in parentheses.

$\times 10^{-2}$	DAE	RCAE	GDAE (ours)	GRCAE (ours)	S-Flow
four blobs	0.215 (0.015)	0.598 (0.059)	**0.188** (0.018)	0.291 (0.052)	**0.137** (0.038)
two moons	0.147 (0.022)	0.249 (0.020)	**0.144** (0.032)	0.161 (0.020)	**0.100** (0.030)
s-curve	0.300 (0.042)	0.248 (0.048)	**0.242** (0.031)	**0.231** (0.072)	0.326 (0.063)
circles	0.075 (0.021)	0.353 (0.012)	**0.061** (0.005)	0.323 (0.008)	**0.046** (0.093)

4.3 CLUSTERING OF HYPERSPHERICAL DATA

In natural language processing, the similarity between word embeddings, i.e., the vector representations that encode semantic information of the words, is often measured according to the cosine similarity (Mikolov et al., 2013). This can be equated to considering the embeddings as points on a hypersphere and measuring the distance based on the geodesic distance (Straub et al., 2015).

Based on this idea, we group documents in the Newsgroup20 data set (Lang, 1995) using the GDAE trained on the document embeddings. The document embeddings are first represented as the average

Figure 4: Data sampling on S^2.

of the word embeddings in the document and then projected to a hypersphere. For the word embeddings, we utilize pre-trained 50-dimensional GloVe embeddings (Pennington et al., 2014) hence the document embeddings lie on S^{49}. We define four clustering tasks as described in Appendix F.1.

We train DAE, GDAE, LSLDG, and R-LSLDG as explained in Appendix F.2. Here we consider two variations of DAE and LSLDG, respectively; the first ones are trained on the spherical coordinate representations of the data, and the second ones are trained on the representations in the ambient space $\mathbb{R}^{n+1}$. After training the models, the document embeddings are iteratively updated along the gradient of the log-probability (for GDAE, this can be performed by repeatedly applying the reconstruction function on the embedding) for a fixed number of steps and then grouped as done in the mean shift clustering (Comaniciu & Meer, 2002). The adjusted Rand index (ARI) is used as the performance metric for the clustering tasks (Hubert & Arabie, 1985).

Table 3: The adjusted Rand index for the clustering results on the Newsgroup20 data set (S^{49}) with standard errors in parentheses. The higher, the better.

Tasks	LSLDG	LSLDG Ambient	DAE	DAE Ambient	R-LSLDG	GDAE (ours)
crypt	0.174 (0.016)	0.034 (0.025)	0.205 (0.069)	0.071 (0.040)	0.221 (0.109)	**0.465** (0.018)
electronics	0.204 (0.006)	0.036 (0.018)	0.228 (0.082)	0.092 (0.001)	0.192 (0.099)	**0.448** (0.044)
med	0.153 (0.012)	0.021 (0.017)	0.227 (0.120)	0.071 (0.040)	0.246 (0.090)	**0.451** (0.055)
space	0.176 (0.019)	0.025 (0.026)	0.211 (0.066)	0.089 (0.001)	0.241 (0.081)	**0.429** (0.070)

The averaged clustering performance for five runs of each method is presented in Table 3. Note that the vector-spaced methods trained on the ambient representations of the data are hardly successful in grouping the data. The R-LSLDG performs slightly better than LSLDG and DAE on average but with higher variance. The results obtained from GDAE show a much higher ARI than others. Additional case study for the clustering of covariance matrix data is provided in Appendix F.3.

4.4 FILTERING OF DIFFUSION TENSOR IMAGING DATA

For the next case study, we consider data obtained from diffusion tensor imaging (DTI). Mathematically, a DTI datum is a three-dimensional image in which the value assigned to each voxel is an element of P(3). A voxel of DTI data can be treated as in the space of three-dimensional normal distributions N(3), by regarding the voxel location and voxel value as the mean and covariance of a normal distribu-

Table 4: The R-squared score for N(2) data filtering. The higher, the better.

Noise level	DAE	GDAE (ours)	MVKR
0.02	99.80 (0.00)	**99.86** (0.00)	96.31 (0.01)
0.05	99.12 (0.05)	**99.51** (0.03)	96.21 (0.03)
0.1	97.14 (0.16)	**98.51** (0.03)	95.79 (0.04)
0.2	89.44 (0.32)	**93.70** (0.47)	**94.11** (0.10)

tion, respectively. In this section, following Han & Park (2014), we adopt the Fisher information Riemannian metric (FIRM) for DTI data (see Appendix C.3.1 for the definition of the FIRM). We train the GDAE on raw DTI data, and apply the trained GDAE to filter the noise in the data.

Figure 5: N(2) data filtering (noise 0.2). The redder, the higher error.

Consider a data set comprised of N voxels $\{(x_1, P_1), \ldots, (x_N, P_N)\}$ of a raw DTI datum, where $x_i \in \mathbb{R}^3$ and $P_i \in \mathrm{P}(3)$ denote the location and value of the i-th voxel, respectively. For the data set, we train the GDAE with reconstruction function r : N(3) → N(3); the overall training process is explained in Appendix G.1.

By iteratively applying the reconstruction function of the trained GDAE, data points are mapped toward the local modes of the probability function (as can be implied from (7)), and the voxels with added noise, which usually have lower probability, can be automatically filtered (Comaniciu & Meer, 2002). We summarize a DTI filtering algorithm based on the GDAE in Appendix G.2.

We first demonstrate the effectiveness of this algorithm in a simpler setting by using a synthetic data set in two-dimensional normal distributions N(2). We train our GDAE on a noisy input artificially corrupted from clean data in Figure 5 and apply the filtering algorithm. The proposed algorithm can effectively filter out the noises qualitatively better than other filtering methods, such as the DAE-based filtering with more remaining noises and a manifold-valued kernel regression-based filtering approach (MVKR) (Banerjee et al., 2015) which tends to smooth the boundary erroneously. A quantitative comparison in Table 4 also suggests that our GDAE-based filtering can perform well at various noise levels. The experimental details are deferred to Appendix G.3.

We now conduct numerical experiments of DTI filtering by applying our algorithm. Data used in these experiments were obtained from the Alzheimer's Disease Neuroimaging Initiative (ADNI) database (adni.loni. usc.edu). See Appendix G.4 for the data preprocessing details. We also perform filtering based on DAE trained on nine-dimensional vector representations of voxels. Note that, critically, the DAE-based filtering has no guarantee for the filtered voxel values to be positive-definite, while GDAE-based filtering always satisfies the constraint.

(a) Noisy input   (b) DAE   (c) GDAE

Figure 6: DTI filtering results.

The input image and the filtering results from each algorithm are shown in Figure 6. We plot axial slices of the corresponding DTI data in Figures 6 (a)-(c). Voxel values are drawn as ellipsoids with colors representing the direction of the first principal axis.

Since the ground truths of DTI data are not available, only qualitative comparisons between the filtering results can be made. In Figures 6 (a)-(c), it can be seen that the GDAE-based method effectively filters outliers (the abruptly changing colors appearing in Figure 6 (a)) when compared to DAE-based filtering. Using brain anatomical terms, the separation between the cerebrospinal fluid and brain parenchyma became clear after GDAE-based filtering, and as a result specifying the sulci and gyri of the brain is much easier than from the raw input or DAE-based filtering results. Furthermore, noise in the ventricle area also disappeared after GDAE-based filtering, while DAE-based filtering failed to eliminate this noise. We should note here that the DTI filtering results would require further concordance verification procedures with experts such as radiologists to ensure that only spurious artifacts are erased rather than important anatomy.

4.5 ROBUST REPRESENTATION LEARNING OF POINT CLOUD DATA

We now show that we can obtain useful representations for non-Euclidean data from our proposed autoencoders, especially when noise exists in the data. We consider point cloud data in this case study. A point cloud data in $\mathbb{R}^D$ is a set of n points in $\mathbb{R}^D$, represented as $X = \{x_1, \ldots, x_n \mid x_i \in \mathbb{R}^D\}$. Recently, a statistical manifold framework has been suggested for point cloud data in Lee

et al. (2022), and they have observed that reflecting this geometry to train autoencoders can obtain better representations than the vector space counterparts. We explain more about this geometry in Appendix C.4.1.

Based on this choice of geometry, we train GDAE for point cloud data. We reflect the Fisher information metric proposed in Lee et al. (2022) in the data corruption process for GDAE and use the modified Chamfer loss as the reconstruction error for point cloud data. For comparison purposes, we also consider DAE trained on the vector representations of point cloud data. We use the FcNet (Yang et al., 2018) as the structure for the reconstruction functions with a latent space dimension of 512. Further details are provided in Appendix C.4.

To verify the usefulness of the representations obtained from our trained autoencoders, we utilize them as features to train classifiers in the transfer learning setting based on some benchmark data sets following Yang et al. (2018). More specifically, we train autoencoders using the ShapeNet data set (Chang et al., 2015) and obtain representations for the ModelNet data set (Wu et al., 2015). We then train a linear SVM using the representations and measure the transfer classification accuracy. We inject varying noises in the data sets to verify if the obtained representations are robust to noise. More experimental details are explained in Appendix H.

Table 5: Classification accuracy by transfer learning for ModelNet10 and ModelNet40 from ShapeNet under the noise levels of 0.01, 0.05, 0.1, and 0.2.

| Noise level | AE | DAE | ModelNet10 | | | AE | DAE | ModelNet40 | | |
			GDAE (ours)	AE +R.	GDAE (ours) + R.			GDAE (ours)	AE + R.	GDAE (ours) + R.
0.01	93.1	92.7	**93.2**	92.8	**93.2**	87.3	87.0	87.3	**88.6**	**88.8**
0.05	91.3	91.6	92.3	**93.3**	**92.4**	83.2	84.6	85.0	**86.8**	**86.5**
0.1	88.9	90.6	**91.1**	90.2	**91.7**	75.6	79.9	**83.2**	80.5	**82.4**
0.2	79.8	81.2	**88.2**	84.8	**88.0**	64.6	67.3	**77.3**	72.2	**76.1**

The experimental results are in Table 5. The features obtained from GDAE lead to a better transfer classification accuracy than those from the vanilla autoencoder (AE) or DAE; this tendency gets stronger as the noise level increases. Our approach also shows comparable or better performances compared to another regularization method ('AE + R.' in Table 5) considered in Lee et al. (2022), which tries to match the pull-back metric of the Fisher information metric (via the decoder mapping) to the identity. Combining these two regularization methods ('GDAE + R.' in Table 5) shows the best overall transfer classification accuracy, demonstrating the usefulness of our geometric regularization methods in obtaining better representations of non-Euclidean data for downstream tasks.

5 CONCLUSION

This paper has presented geometrically regularized autoencoders for non-Euclidean data. Assuming non-Euclidean input and latent spaces, we have shown how to construct regularization terms in a coordinate-invariant way, and developed the geometric reconstruction contractive autoencoder and the geometric denoising autoencoder for non-Euclidean data. We have shown that it is possible to estimate the derivative of the log of the probability density of non-Euclidean data, i.e., the geometric scores, using these autoencoders and applied the trained autoencoders successfully to data sampling, mode-seeking, and representation learning applications involving real-world non-Euclidean data sets.

Even though our geometric autoencoders have shown superior performance in various tasks considered in the paper, it should be noted that model training can demand heavy computations or solving any numerical issues that may arise when reflecting the geometry of the data, e.g., from the Riemannian metric, exponential maps, or geodesic distances. Even if that is the case, as the experimental results demonstrate, the GDAE-based approach can be a viable option compared to other methods when the non-Euclidean data dimensionality is high, and the data distribution gets complex. In this regard, it would be worth investigating a more efficient and robust way of reflecting the geometry and model training than the current ones. More broadly, we can also consider applying our idea of geometric regularizations to other machine learning regularization problems that involve non-Euclidean data.

REPRODUCIBILITY STATEMENT

We refer the reader to the following pointers for reproducibility:

- Codes to train the proposed autoencoders: Supplementary Material.
- Proof of Theorem 1: Appendix B.
- Implementation details of the proposed autoencoders: Appendix C.
- Experimental settings: Appendix D, E, F, G, and H.

REFERENCES

Guillaume Alain and Yoshua Bengio. What regularized auto-encoders learn from the data-generating distribution. *Journal of Machine Learning Research*, 15(1):3563–3593, 2014.

Mina Ashizawa, Hiroaki Sasaki, Tomoya Sakai, and Masashi Sugiyama. Least-squares log-density gradient clustering for riemannian manifolds. In *Artificial Intelligence and Statistics*, pp. 537–546, 2017.

Monami Banerjee, Rudrasis Chakraborty, Edward Ofori, David Vaillancourt, and Baba C Vemuri. Nonlinear regression on riemannian manifolds and its applications to neuro-image analysis. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 719–727. Springer, 2015.

Mikhail Belkin and Partha Niyogi. Laplacian eigenmaps for dimensionality reduction and data representation. *Neural Computation*, 15(6):1373–1396, 2003.

Yoshua Bengio, Pascal Lamblin, Dan Popovici, and Hugo Larochelle. Greedy layer-wise training of deep networks. In *Advances in neural information processing systems*, pp. 153–160, 2007.

Yoshua Bengio, Aaron Courville, and Pascal Vincent. Representation learning: A review and new perspectives. *IEEE transactions on pattern analysis and machine intelligence*, 35(8):1798–1828, 2013.

William M Boothby. *An introduction to differentiable manifolds and Riemannian geometry*, volume 120. Academic press, 1986.

Johann Brehmer and Kyle Cranmer. Flows for simultaneous manifold learning and density estimation. *Advances in Neural Information Processing Systems*, 33:442–453, 2020.

Roger Brockett. Notes on stochastic processes on manifolds. In *Systems and Control in the twenty-first century*, pp. 75–100. Springer, 1997.

Michael M Bronstein, Joan Bruna, Yann LeCun, Arthur Szlam, and Pierre Vandergheynst. Geometric deep learning: going beyond euclidean data. *IEEE Signal Processing Magazine*, 34(4):18–42, 2017.

Rudrasis Chakraborty, Jose Bouza, Jonathan Manton, and Baba C Vemuri. Manifoldnet: A deep neural network for manifold-valued data with applications. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

Angel X Chang, Thomas Funkhouser, Leonidas Guibas, Pat Hanrahan, Qixing Huang, Zimo Li, Silvio Savarese, Manolis Savva, Shuran Song, Hao Su, et al. Shapenet: An information-rich 3d model repository. *arXiv preprint arXiv:1512.03012*, 2015.

Yizong Cheng. Mean shift, mode seeking, and clustering. *IEEE transactions on pattern analysis and machine intelligence*, 17(8):790–799, 1995.

Dorin Comaniciu and Peter Meer. Mean shift: A robust approach toward feature space analysis. *IEEE Transactions on Pattern Analysis & Machine Intelligence*, (5):603–619, 2002.

Laurent Dinh, Jascha Sohl-Dickstein, and Samy Bengio. Density estimation using real nvp. *arXiv preprint arXiv:1605.08803*, 2016.

Boris A Dubrovin, Anatolij Timofeevič Fomenko, and Sergeĭ Petrovich Novikov. *Modern Geometry—Methods and Applications Part I. The Geometry of Surfaces, Transformation Groups, and Fields*. Springer, 1992.

James Eells and Luc Lemaire. A report on harmonic maps. *Bulletin of the London Mathematical Society*, 10(1):1–68, 1978.

James Eells and Luc Lemaire. Another report on harmonic maps. *Bulletin of the London Mathematical Society*, 20(5):385–524, 1988.

James Eells and Joseph H Sampson. Harmonic mappings of riemannian manifolds. *American Journal of Mathematics*, 86(1):109–160, 1964.

P Thomas Fletcher and Sarang Joshi. Riemannian geometry for the statistical analysis of diffusion tensor data. *Signal Processing*, 87(2):250–262, 2007.

Oren Freifeld and Michael J Black. Lie bodies: A manifold representation of 3d human shape. In *European Conference on Computer Vision*, pp. 1–14. Springer, 2012.

Keinosuke Fukunaga and Larry Hostetler. The estimation of the gradient of a density function, with applications in pattern recognition. *IEEE Transactions on information theory*, 21(1):32–40, 1975.

Mark Girolami and Ben Calderhead. Riemann manifold langevin and hamiltonian monte carlo methods. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 73(2): 123–214, 2011.

Xavier Glorot and Yoshua Bengio. Understanding the difficulty of training deep feedforward neural networks. In *Proceedings of the thirteenth international conference on artificial intelligence and statistics*, pp. 249–256. JMLR Workshop and Conference Proceedings, 2010.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT Press, 2016. http://www.deeplearningbook.org.

Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *The Journal of Machine Learning Research*, 13(1):723–773, 2012.

Xianfeng Gu, Yalin Wang, Tony F Chan, Paul M Thompson, and Shing-Tung Yau. Genus zero surface conformal mapping and its application to brain surface mapping. *IEEE Transactions on Medical Imaging*, 23(8):949–958, 2004.

Minyeon Han and Frank C Park. Dti segmentation and fiber tracking using metrics on multivariate normal distributions. *Journal of mathematical imaging and vision*, 49(2):317–334, 2014.

Zhiwu Huang and Luc Van Gool. A riemannian network for spd matrix learning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 31, 2017.

Lawrence Hubert and Phipps Arabie. Comparing partitions. *Journal of classification*, 2(1):193–218, 1985.

Aapo Hyvärinen. Estimation of non-normalized statistical models by score matching. *Journal of Machine Learning Research*, 6(Apr):695–709, 2005.

Cheongjae Jang, Yung-Kyun Noh, and Frank Chongwoo Park. A riemannian geometric framework for manifold learning of non-euclidean data. *Advances in Data Analysis and Classification*, 15 (3):673–699, 2021.

Sadeep Jayasumana, Richard Hartley, Mathieu Salzmann, Hongdong Li, and Mehrtash Harandi. Kernel methods on riemannian manifolds with gaussian rbf kernels. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 37(12):2464–2477, 2015.

Mark Jenkinson, Christian F. Beckmann, Timothy E.J. Behrens, Mark W. Woolrich, and Stephen M. Smith. Fsl. *NeuroImage*, 62(2):782 – 790, 2012. ISSN 1053-8119. doi: https://doi.org/10. 1016/j.neuroimage.2011.09.015. URL http://www.sciencedirect.com/science/article/pii/S1053811911010603. 20 YEARS OF fMRI.

David G Kendall. Shape manifolds, procrustean metrics, and complex projective spaces. *Bulletin of the London Mathematical Society*, 16(2):81–121, 1984.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015, San Diego, CA, USA, May 7-9, 2015, Conference Track Proceedings*, 2015. URL http://arxiv.org/abs/1412.6980.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Ken Lang. Newsweeder: Learning to filter netnews. In *Machine Learning Proceedings 1995*, pp. 331–339. Elsevier, 1995.

Yonghyeon Lee, Jonghyuk Baek, Young Min Kim, and Frank Chongwoo Park. Imat: The iterative medial axis transform. In *Computer Graphics Forum*, volume 40, pp. 162–181. Wiley Online Library, 2021a.

Yonghyeon Lee, Sangwoong Yoon, MinJun Son, and Frank C Park. Regularized autoencoders for isometric representation learning. In *International Conference on Learning Representations*, 2021b.

Yonghyeon Lee, Seungyeon Kim, Jinwon Choi, and Frank Park. A statistical manifold framework for point cloud data. In *International Conference on Machine Learning*, pp. 12378–12402. PMLR, 2022.

Bastian Leibe and Bernt Schiele. Analyzing appearance and contour based methods for object categorization. In *2003 IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2003. Proceedings.*, volume 2, pp. II–409. IEEE, 2003.

Kantilal Varichand Mardia. *Statistics of directional data*. Academic press, 2014.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg Corrado, and Jeffrey Dean. Distributed representations of words and phrases and their compositionality. *arXiv preprint arXiv:1310.4546*, 2013.

Maher Moakher. A differential geometric approach to the geometric mean of symmetric positive-definite matrices. *SIAM Journal on Matrix Analysis and Applications*, 26(3):735–747, 2005.

Sameer A Nene, Shree K Nayar, and Hiroshi Murase. Columbia object image library (coil-20). *Technical Report CUCS-005-96*, 1996a.

Sameer A Nene, Shree K Nayar, and Hiroshi Murase. Columbia object image library (coil-100). *Technical Report CUCS-006-96*, 1996b.

Frank C Park and Roger W Brockett. Kinematic dexterity of robotic mechanisms. *The International Journal of Robotics Research*, 13(1):1–15, 1994.

Adam Paszke, Sam Gross, Soumith Chintala, Gregory Chanan, Edward Yang, Zachary DeVito, Zeming Lin, Alban Desmaison, Luca Antiga, and Adam Lerer. Automatic differentiation in pytorch. In *NIPS-W*, 2017.

Xavier Pennec. Probabilities and statistics on riemannian manifolds: Basic tools for geometric measurements. In *NSIP*, pp. 194–198. Citeseer, 1999.

Jeffrey Pennington, Richard Socher, and Christopher D. Manning. Glove: Global vectors for word representation. In *Empirical Methods in Natural Language Processing (EMNLP)*, pp. 1532–1543, 2014. URL http://www.aclweb.org/anthology/D14-1162.

Marc'aurelio Ranzato, Christopher Poultney, Sumit Chopra, and Yann L. Cun. Efficient learning of sparse representations with an energy-based model. In *Advances in Neural Information Processing Systems 19*, pp. 1137–1144. MIT Press, 2007.

Marc'aurelio Ranzato, Y lan Boureau, and Yann L. Cun. Sparse feature learning for deep belief networks. In *Advances in Neural Information Processing Systems 20*, pp. 1185–1192. Curran Associates, Inc., 2008.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *Proceedings of the 31st International Conference on Machine Learning*, volume 32, pp. 1278–1286. PMLR, 2014.

Salah Rifai, Grégoire Mesnil, Pascal Vincent, Xavier Muller, Yoshua Bengio, Yann Dauphin, and Xavier Glorot. Higher order contractive auto-encoder. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 645–660. Springer, 2011a.

Salah Rifai, Pascal Vincent, Xavier Muller, Xavier Glorot, and Yoshua Bengio. Contractive auto-encoders: Explicit invariance during feature extraction. In *Proceedings of the 28th International Conference on Machine Learning (ICML-11)*, pp. 833–840, 2011b.

Hiroaki Sasaki, Aapo Hyvärinen, and Masashi Sugiyama. Clustering via mode seeking by direct estimation of the gradient of a log-density. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 19–34. Springer, 2014.

Justin Solomon, Leonidas Guibas, and Adrian Butscher. Dirichlet energy for analysis and synthesis of soft maps. In *Computer Graphics Forum*, volume 32, pp. 197–206. Wiley Online Library, 2013.

Julian Straub, Jason Chang, Oren Freifeld, and John Fisher III. A dirichlet process mixture model for spherical data. In *Artificial Intelligence and Statistics*, pp. 930–938. PMLR, 2015.

Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th International Conference on Machine Learning*, pp. 1096–1103. ACM, 2008.

Pascal Vincent, Hugo Larochelle, Isabelle Lajoie, Yoshua Bengio, and Pierre-Antoine Manzagol. Stacked denoising autoencoders: Learning useful representations in a deep network with a local denoising criterion. *Journal of Machine Learning Research*, 11(Dec):3371–3408, 2010.

Zhirong Wu, Shuran Song, Aditya Khosla, Fisher Yu, Linguang Zhang, Xiaoou Tang, and Jianxiong Xiao. 3d shapenets: A deep representation for volumetric shapes. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1912–1920, 2015.

Yaoqing Yang, Chen Feng, Yiru Shen, and Dong Tian. Foldingnet: Point cloud auto-encoder via deep grid deformation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 206–215, 2018.

APPENDIX

A   FURTHER EXPLANATIONS OF THE GEOMETRIC REGULARIZATION COMPONENTS

A.1   CONTRACTIVE REGULARIZATION

To see why (4) is coordinate-invariant, observe that under a pair of local coordinate transformations $x \mapsto x' = \phi(x)$ and $y \mapsto y' = \psi(y)$, G, H, and J transform according to the following rules: (i) $G \mapsto G' = \Phi^{-\top}G\Phi^{-1}$, where $\Phi = \frac{\partial\phi}{\partial x}$; (ii) $H \mapsto H' = \Psi^{-\top}H\Psi^{-1}$, where $\Psi = \frac{\partial\psi}{\partial y}$; (iii) $J \mapsto J' = \Psi J\Phi^{-1}$, where it can be verified that the matrix $J^\top HJG^{-1}$ remains the same.

Also note that minimizing (4) induces the contraction (shrinking without distortion) of the mapping f. As an extreme case without any boundary conditions or constraints, trivial solutions are obtained as $J = 0$ or equivalently f = constant, which is an extreme contraction. On the other hand, provided the boundary conditions or constraints for f are well-specified, a useful physical analogy for minimizing (4) is to imagine wrapping a curved object made of marble ($\mathcal{N}$) by an elastic sheet ($\mathcal{M}$); harmonic maps, which are extrema of (4), can be viewed as solutions corresponding to elastic equilibria (Eells & Sampson, 1964).

A.2   DATA CORRUPTION PROCESS

The corruption process $\tilde{x} \sim N(x, \sigma^2 I)$ in vector space is equivalent to set $\tilde{x} = x + \epsilon$ for $\epsilon \sim N(0, \sigma^2 I)$, i.e., the endpoint of a line segment starting from x and extended according to the vector ϵ. On the Riemannian manifolds, a similar discussion is possible using the notion of the geodesic.

As shown in Figure 7, consider a geodesic curve x : $[0, 1] \to \mathcal{M}$ emanating from a point x(0) $\in \mathcal{M}$ with an initial velocity vector $\dot{x}(0) = $ v $\in T_{x(0)}\mathcal{M}$. It is known that such a geodesic is unique if it exists (Boothby, 1986), and denote by x(1) $\in \mathcal{M}$ the endpoint of the geodesic that propagates for a unit time. The mapping that maps the initial velocity vector v to the point x(1) is called the exponential map $\text{Exp}_{x(0)} : T_{x(0)}\mathcal{M} \to \mathcal{M}$. Note that the

Figure 7: A geodesic curve x : $[0, 1] \to \mathcal{M}$ emanating from x(0) $\in \mathcal{M}$ along v $\in T_{x(0)}\mathcal{M}$.

distance between x(0) and x(1) is the same as the norm of v. This corresponds to a generalization of propagating a line in vector space from a starting point along a vector.

Also note that, when corrupting an input x $\in \mathcal{M}$, we sample v $\in T_x\mathcal{M}$ by v $= v^1 E_1 + \cdots + v^m E_m$ for an orthonormal basis $E_1, \ldots, E_m$ for $T_x\mathcal{M}$ and an m-dimensional vector $(v^1, \ldots, v^m) \sim N(0, \sigma^2 I)$. By using an isotropic Gaussian, the corruption process $\tilde{x} = \text{Exp}_x(v)$ does not depend on which orthonormal basis $E_1, \ldots, E_m$ is used.

B   PROOF OF THEOREM 1

B.1   THE FIRST-ORDER NECESSARY CONDITIONS FOR GRCAE

Lemma 1. *Provided σ^2 is small, the derivative of the log of the probability function $\rho_g(x) = \frac{\rho(x)}{\sqrt{\det G(x)}}$ can be approximated for the geometric reconstruction contractive autoencoder as*

$$\frac{\partial \log \rho_g(x)}{\partial x} = \frac{1}{\rho_g}\frac{\partial \rho_g}{\partial x}(x) = \frac{1}{\rho}\frac{\partial \rho}{\partial x}(x) - \Gamma(x) \approx G\left(\frac{r(x) - x}{\sigma^2}\right), \tag{10}$$

where $\Gamma(x) \in \mathbb{R}^m$ is a vector whose i-th component is given by $\frac{1}{2}\text{Tr}\left(G^{-1}\frac{\partial G}{\partial x^i}\right)$.

Proof. The first-order necessary conditions for (5) can be obtained from the following Euler-Lagrange equations:

$$\frac{\partial \mathcal{L}}{\partial r^i} - \sum_{j=1}^{m} \frac{\partial}{\partial x^j} \left(\frac{\partial \mathcal{L}}{\partial \left(\frac{\partial r^i}{\partial x^j} \right)} \right) = 0, \qquad i = 1, \dots, m, \tag{11}$$

where $\mathcal{L}$ is the integrand of (5) with an approximation on the squared geodesic distance to $(r(x) - x)^\top G(x)(r(x) - x)$ provided σ^2 small,[2] and r^i denotes the i-th coordinate representation of the reconstruction function r. By applying $\mathcal{L}$ to the Euler-Lagrange equations, (11) results in

$$r^i - x^i = \sigma^2 \, \eta^i(x, r, r', r''), \qquad i = 1, \dots, m, \tag{12}$$

where r' denotes $\frac{\partial r}{\partial x}$, r'' denotes the collection of $\frac{\partial^2 r^j}{\partial x^2}$ for $j = 1, \dots, m$, and η^i denotes a function of x, r, r', r''.[3] Assuming r, G, G^{-1}, ρ are smooth, and their higher-order derivatives are bounded, $r^i - x^i = \sigma^2 \, \eta^i(x, r, r', r'') = \mathcal{O}(\sigma^2)$ holds. By iterating the relation $r^i = x^i + \sigma^2 \, \eta^i(x, r, r', r'') = x^i + \mathcal{O}(\sigma^2)$, i.e., substituting this form of r^i into $\eta^i(x, r, r', r'')$, the i-th component of r is obtained for small σ^2 as follows:

$$r^i - x^i \;\approx\; \sigma^2 \left(\sum_{j=1}^{m} g^{ij} \left(\frac{1}{\rho} \frac{\partial \rho}{\partial x^j} - \frac{1}{2} \text{Tr} \left(G^{-1} \frac{\partial G}{\partial x^j} \right) \right) \right), \tag{13}$$

$$= \;\sigma^2 \left(\sum_{j=1}^{m} g^{ij} \frac{1}{\rho_g} \frac{\partial \rho_g}{\partial x^j} \right), \tag{14}$$

where g^{ij} denotes the (i, j) entry of G^{-1}, $\rho_g = \frac{\rho}{\sqrt{\det G}}$, and the identity $\frac{\partial \log(\det G)}{\partial x^j} = \text{Tr} \left(G^{-1} \frac{\partial G}{\partial x^j} \right)$ is used to derive (14). By gathering (14) for all i, the first-order necessary conditions can be rewritten as

$$\frac{1}{\rho_g} \frac{\partial \rho_g}{\partial x}(x) \approx G \left(\frac{r(x) - x}{\sigma^2} \right). \tag{15}$$

$\square$

B.2 THE FIRST-ORDER NECESSARY CONDITIONS FOR GDAE

To obtain the first-order necessary conditions for GDAE, the integrand of (6) is first represented in local coordinates $x = (x^1, \dots, x^m)$ in Lemma 2.

Lemma 2. *Provided σ^2 is small, $E_{q(\tilde{x}|x)} \left[\text{dist}(r(\tilde{x}), x)^2 \right]$ in (6) can be approximated in local coordinates as*

$$E_{q(\tilde{x}|x)} \left[\text{dist}(r(\tilde{x}), x)^2 \right] \tag{16}$$

$$\approx (r(x) - x)^\top G(x)(r(x) - x) + \sigma^2 \left(\text{Tr} \left(\left(\frac{\partial r}{\partial x} \right)^\top G(r) \left(\frac{\partial r}{\partial x} \right) G^{-1}(x) \right) \right.$$

$$+ \sum_{i=1}^{m} \sum_{j=1}^{m} (r^i - x^i) \, g_{ij} \, \text{Tr} \left(\left(\frac{\partial^2 r^j}{\partial x^2} \right) G^{-1} \right)$$

$$\left. + \sum_{k=1}^{m} \sum_{l=1}^{m} \sum_{n=1}^{m} (r^i - x^i) \left(\Gamma_{i;jk} \frac{\partial r^j}{\partial x^l} \frac{\partial r^k}{\partial x^n} g^{ln} - g_{ij} \frac{\partial r^j}{\partial x^k} \Gamma_{ln}^k g^{ln} \right) \right),$$

where r^i is the i-th component of r, g_{ij} and g^{ij} respectively denote the (i, j) entry of G and G^{-1}. The $\Gamma_{k;ij}$ and Γ_{ij}^k respectively denote the Christoffel symbol of the first and second kind in $\mathcal{M}$.

---

[2]The difference between optimal $r(x)$ and x turns out to be $\mathcal{O}(\sigma^2)$. It can be verified that this approximation does not affect the final results, since the approximation error of the squared geodesic distance becomes $\mathcal{O}(\sigma^6)$.

[3]The explicit form of $\eta^i(x, r, r', r'')$ is obtained as
$\eta^i = \sum_{j,k,l,\alpha} g^{ij} \left(\left(\sum_\beta -\frac{1}{2} \frac{\partial r^\alpha}{\partial x^k} \frac{\partial g(r)_{\alpha\beta}}{\partial r^j} \frac{\partial r^\beta}{\partial x^l} g^{kl} + \frac{\partial g(r)_{j\alpha}}{\partial r^\beta} \frac{\partial r^\beta}{\partial x^k} \frac{\partial r^\alpha}{\partial x^l} g^{kl} \right) + g(r)_{j\alpha} \left(\frac{\partial^2 r^\alpha}{\partial x^k \partial x^l} g^{kl} \right.\right.$
$\left.\left. + \frac{\partial r^\alpha}{\partial x^l} \left(\frac{\partial g^{kl}}{\partial x^k} + g^{kl} \frac{1}{\rho} \frac{\partial \rho}{\partial x^k} \right) \right) \right)$, where g^{ij} and $g(r)_{ij}$ respectively denote the (i, j) entry of G^{-1} and $G(r(x))$.

Proof. We represent $x \in \mathcal{M}$ and $\tilde{x} \in \mathcal{M}$ in local coordinates as $x \in \mathbb{R}^m$ and $\tilde{x} \in \mathbb{R}^m$, respectively. Furthermore, at x, consider a nonlinear function $\phi : \mathbb{R}^m \to \mathbb{R}^m$ that maps the representations in local coordinates of the points near x to those in the normal coordinates; from these settings, $\phi(x) = 0$ holds and let $\tilde{u} = \phi(\tilde{x})$. Denote by $r_u : \mathbb{R}^m \to \mathbb{R}^m$ the reconstruction function represented in the normal coordinates. (The functions r and r_u are then related by $r_u(\tilde{u}) = \phi(r(\tilde{x}))$, and $r_u(0) = \phi(r(x))$ holds.)

Since the distance between $x \in \mathcal{M}$ and $r(\tilde{x}) \in \mathcal{M}$ corresponds to the standard vector norm of the representation of $r(\tilde{x})$ in normal coordinates at x, $\mathrm{dist}(r(\tilde{x}), x)^2 = \|r_u(\tilde{u})\|^2$ holds. Near the origin of the normal coordinates at x, $r_u^i : \mathbb{R}^m \to \mathbb{R}$ (the i-th component of $r_u : \mathbb{R}^m \to \mathbb{R}^m$) admits following Taylor expansion:

$$r_u^i(\tilde{u}) = r_u^i(0) + \frac{\partial r_u^i}{\partial u} \, \tilde{u} + \frac{1}{2!} \, \tilde{u}^\top \left(\frac{\partial^2 r_u^i}{\partial u^2} \right) \tilde{u} + \cdots . \tag{17}$$

Then $\|r_u(\tilde{u})\|^2$ can be expressed as follows:

$$\|r_u(\tilde{u})\|^2 = \sum_{i=1}^m \left(r_u^i(\tilde{u}) \right)^2 \tag{18}$$

$$= \|r_u(0)\|^2 + 2 \, r_u(0)^\top \left(\frac{\partial r_u}{\partial u} \right) \tilde{u} + \tilde{u}^\top \left(\frac{\partial r_u}{\partial u} \right)^\top \left(\frac{\partial r_u}{\partial u} \right) \tilde{u} \tag{19}$$

$$+ \sum_{i=1}^m r_u^i(0) \, \tilde{u}^\top \left(\frac{\partial^2 r_u^i}{\partial u^2} \right) \tilde{u} + \cdots ,$$

where the terms of the order (with respect to $\tilde{u}$) higher than three are omitted in (19). Consider the expectation with respect to $\tilde{u} \sim N(0, \sigma^2 I)$ of (19) (this corresponds to the expectation of $\mathrm{dist}(r(\tilde{x}), x)^2$ with respect to $q(\tilde{x}|x)$). Provided σ^2 is small, we obtain

$$E_{q(\tilde{x}|x)} \left[\mathrm{dist}(r(\tilde{x}), x)^2 \right] = E_{q(\tilde{u})} \left[\|r_u(\tilde{u})\|^2 \right] \tag{20}$$

$$\approx \|r_u(0)\|^2 + \sigma^2 \, \mathrm{Tr} \left(\left(\frac{\partial r_u}{\partial u} \right)^\top \left(\frac{\partial r_u}{\partial u} \right) \right) + \sigma^2 \, \sum_{i=1}^m r_u^i(0) \, \mathrm{Tr} \left(\left(\frac{\partial^2 r_u^i}{\partial u^2} \right) \right),$$

where $q(\tilde{u})$ denotes the noise density for $\tilde{u} \sim N(0, \sigma^2 I)$, and the terms with the order higher than σ^2 are assumed to be negligible.

We now represent (20) in local coordinates. For this purpose, the following equations are useful:

$$r_u^i(0) = \phi^i(r(x)) \approx \frac{\partial \phi^i}{\partial x}(r(x) - x), \tag{21}$$

$$\frac{\partial r_u^i}{\partial u^j} = \frac{\partial \phi^i(r(x))}{\partial u^j} = \sum_{k=1}^m \sum_{l=1}^m \frac{\partial \phi^i}{\partial r^k} \frac{\partial r^k}{\partial x^l} \frac{\partial x^l}{\partial u^j}, \tag{22}$$

$$\frac{\partial^2 r_u^i}{\partial u^j \partial u^k} = \left(\sum_{l=1}^m \sum_{n=1}^m \sum_{p=1}^m \sum_{q=1}^m \frac{\partial^2 \phi^i}{\partial r^l \partial r^n} \frac{\partial r^l}{\partial x^p} \frac{\partial r^n}{\partial x^q} \frac{\partial x^p}{\partial u^j} \frac{\partial x^q}{\partial u^k} \right) \tag{23}$$

$$+ \left(\sum_{l=1}^m \sum_{p=1}^m \sum_{q=1}^m \frac{\partial \phi^i}{\partial r^l} \frac{\partial^2 r^l}{\partial x^p \partial x^q} \frac{\partial x^p}{\partial u^j} \frac{\partial x^q}{\partial u^k} \right) + \left(\sum_{l=1}^m \sum_{n=1}^m \frac{\partial \phi^i}{\partial r^l} \frac{\partial r^l}{\partial x^n} \frac{\partial^2 x^n}{\partial u^j \partial u^k} \right),$$

$$g_{jk} = \sum_{i=1}^m \frac{\partial \phi^i}{\partial x^j} \frac{\partial \phi^i}{\partial x^k}, \tag{24}$$

$$g^{jk} = \sum_{i=1}^m \frac{\partial x^j}{\partial u^i} \frac{\partial x^k}{\partial u^i}, \tag{25}$$

$$\Gamma_{j;kl} = \sum_{i=1}^m \frac{\partial \phi^i}{\partial x^j} \frac{\partial^2 \phi^i}{\partial x^k \partial x^l}, \tag{26}$$

$$\sum_{j=1}^m \sum_{k=1}^m \Gamma_{jk}^i g^{jk} = - \sum_{j=1}^m \sum_{k=1}^m \frac{\partial^2 x^i}{\partial u^j \partial u^k} \delta^{jk}, \tag{27}$$

where $\frac{\partial x^i}{\partial u^j}$ is the (i,j) entry of $\left(\frac{\partial x}{\partial u}\right) = \left(\frac{\partial \phi}{\partial x}\right)^{-1} \in \mathbb{R}^{m \times m}$, and $\delta^{jk} = 1$ for $j = k$ and $\delta^{jk} = 0$ otherwise in (27). Here, the higher-order terms in (21) can be neglected for small σ^2, and (22)-(23) are obtained from the chain rule. We can derive (24)-(27) using the properties of the normal coordinates. By applying (21)-(27) to (20) and rearranging the terms, we obtain the result in (16). $\square$

We now provide the first-order necessary conditions for (6) using Lemma 2.

Lemma 3. *Provided σ^2 is small, the derivative of the log of the probability function $\rho_g(x) = \frac{\rho(x)}{\sqrt{\det G(x)}}$ can be approximated for the geometric denoising autoencoder as*

$$\frac{\partial \log \rho_g(x)}{\partial x} = \frac{1}{\rho_g} \frac{\partial \rho_g}{\partial x}(x) = \frac{1}{\rho} \frac{\partial \rho}{\partial x}(x) - \Gamma(x) \approx G\left(\frac{r(x) - x}{\sigma^2}\right), \tag{28}$$

where $\Gamma(x) \in \mathbb{R}^m$ is a vector whose i-th component is given by $\frac{1}{2}\text{Tr}\left(G^{-1}\frac{\partial G}{\partial x^i}\right)$.

Proof. The first-order necessary conditions for (6) are obtained from the following Euler-Lagrange equations:

$$\frac{\partial \mathcal{L}}{\partial r^i} - \sum_{j=1}^m \frac{\partial}{\partial x^j}\left(\frac{\partial \mathcal{L}}{\partial\left(\frac{\partial r^i}{\partial x^j}\right)}\right) + \sum_{j,k=1}^m \frac{\partial^2}{\partial x^j \partial x^k}\left(\frac{\partial \mathcal{L}}{\partial\left(\frac{\partial^2 r^i}{\partial x^j \partial x^k}\right)}\right) = 0, \qquad i = 1, \ldots, m, \tag{29}$$

where $\mathcal{L}$ denotes (16) approximated according to Lemma 2. Applying $\mathcal{L}$ to (29) results in an equation of the form $r^i - x^i = \sigma^2 \, \varphi^i(x, r, r', r'')$ for $i = 1, \ldots, m$, where φ^i is a function of x, r, r', r''.[4] Assuming r, G, G^{-1}, ρ are smooth and their higher-order derivatives are bounded, we obtain an equation identical to (14) for small σ^2 by iterating $r^i = x^i + \sigma^2 \varphi^i(x, r, r', r'') = x^i + \mathcal{O}(\sigma^2)$. Hence the first-order necessary conditions are obtained as (15). $\square$

B.3 Proof of Theorem 1

Theorem 2. *Provided σ^2 is small, the derivative of the log of the probability function $\rho_g(x) = \frac{\rho(x)}{\sqrt{\det G(x)}}$ can be approximated for both the GRCAE and GDAE as*

$$\frac{\partial \log \rho_g(x)}{\partial x} = \frac{1}{\rho_g} \frac{\partial \rho_g}{\partial x}(x) = \frac{1}{\rho} \frac{\partial \rho}{\partial x}(x) - \Gamma(x) \approx G(x)\left(\frac{r(x) - x}{\sigma^2}\right), \tag{30}$$

where $\Gamma(x) \in \mathbb{R}^m$ is a vector whose i-th component is given by $\frac{1}{2}\text{Tr}\left(G^{-1}\frac{\partial G}{\partial x^i}\right)$.

Proof. Collecting Lemma 1 from Appendix B.1 and Lemma 3 from Appendix B.2 completes the proof. $\square$

C Implementation of geometrically regularized autoencoders

In this section, we provide the implementation details of the geometrically regularized autoencoders for S^n, $P(n)$, $N(3)$, and point cloud data considered in our experiments. Furthermore, we also provide some ideas to model reconstruction functions in local coordinates for the case of manifolds that require multiple coordinate charts.

---

[4]The explicit form of $\varphi^i(x, r, r', r'')$ is obtained as

$\varphi^i = \sum_{j,k,l,\alpha} g^{ij} \left(-\frac{1}{2}\left(\left(\sum_\beta \frac{\partial g(r)_{\alpha\beta}}{\partial r^j}\frac{\partial r^\alpha}{\partial x^k}\frac{\partial r^\beta}{\partial x^l}g^{kl} + \Gamma_{j;\alpha\beta}\frac{\partial r^\alpha}{\partial x^k}\frac{\partial r^\beta}{\partial x^l}g^{kl} - g_{j\alpha}\frac{\partial r^\alpha}{\partial x^\beta}\Gamma_{kl}^\beta g^{kl}\right)\right.$

$\left. + g_{j\alpha}\frac{\partial^2 r^\alpha}{\partial x^k \partial x^l}g^{kl}\right) + \frac{1}{\rho}\left(\frac{\partial}{\partial x^k}\left(g(r)_{j\alpha}\frac{\partial r^\alpha}{\partial x^l}g^{kl}\rho + \left(\sum_\beta(r^\alpha - x^\alpha)\Gamma_{\alpha;j\beta}\frac{\partial r^\beta}{\partial x^l}g^{kl}\rho - \frac{1}{2}(r^\alpha - x^\alpha)g_{j\alpha}\right.\right.\right.$

$\left.\left.\left.\Gamma_{l\beta}^k g^{l\beta}\rho\right)\right) - \frac{1}{2}\frac{\partial^2}{\partial x^k \partial x^l}\left(g_{j\alpha}(r^\alpha - x^\alpha)g^{kl}\rho\right)\right)\right)$, where $g(r)_{ij}$ is the (i,j) entry of $G(r(x))$.

C.1 S^n DATA

C.1.1 DATA CORRUPTION PROCESS

Given an $n + 1$-dimensional vector with the unit norm $x \in S^n \subseteq \mathbb{R}^{n+1}$, we first sample an $n + 1$-dimensional vector $\epsilon \sim N(0, \sigma^2 I)$ and project ϵ onto $T_x S^n$ (with the origin identified to that of the ambient Euclidean space) as $v = (I - xx^\top)\epsilon$. As discussed in Section 3.2, the input x is then corrupted to $\tilde{x} \in S^n$ as follows:

$$\tilde{x} = \mathrm{Exp}_x(v) = \cos\|v\| \cdot x + \frac{\sin\|v\|}{\|v\|} \cdot v, \tag{31}$$

where $\|\cdot\|$ is the Euclidean norm.

C.1.2 THE RECONSTRUCTION ERROR

For a reconstruction function $r : S^n \to S^n$, the reconstruction error is defined as follows:

$$\mathrm{dist}(r(\tilde{x}), x)^2 = \arccos(r(\tilde{x})^\top x)^2. \tag{32}$$

C.1.3 THE RECONSTRUCTION FUNCTION

We implement our regularized autoencoder for S^n as a mapping $r : S^n \to S^n$. The input and output of the mapping are $n + 1$-dimensional vectors with the unit norm. The reconstruction function r is modeled by a neural network with two hidden layers, with the hyperbolic tangent (Tanh) activation function as follows:

$$r(x) = \mathrm{Proj}(x + W_3 h_2 + b_3), \tag{33}$$
$$h_i = \mathrm{Tanh}(W_i h_{i-1} + b_i), \qquad i = 1, 2, \tag{34}$$

where $h_1, h_2 \in \mathbb{R}^{d_h}$ denote the hidden variables, h_0 is set to be $x \in S^n \subseteq \mathbb{R}^{n+1}$, $\mathrm{Proj} : \mathbb{R}^{n+1} \to S^n \subseteq \mathbb{R}^{n+1}$ is the function to project a vector onto a hypersphere by dividing the input vector by its norm, and W_i, b_i for $i = 1, 2, 3$ respectively denote the matrix and vector parameters with sizes defined accordingly as above.

C.1.4 CONTRACTIVE REGULARIZATION

For the case of S^n, the contractive term of (5) (without the $\rho(x)$ term) can be computed using r as $\mathrm{Tr}\left(\left(\frac{dr}{dx}\right)^\top \left(\frac{dr}{dx}\right)(I - xx^\top)\right)$, where $\frac{dr}{dx} \in \mathbb{R}^{n+1 \times n+1}$ and $x \in S^n \subseteq \mathbb{R}^{n+1}$.

C.2 $P(n)$ DATA

C.2.1 DATA CORRUPTION PROCESS

Given an input $P \in P(n)$, we first sample a $\frac{n(n+1)}{2}$-dimensional vector $\epsilon \sim N(0, \sigma^2 I)$. As discussed in Section 3.2, the input P is then corrupted to $\tilde{P} \in P(n)$ as follows:

$$\tilde{P} = P^{\frac{1}{2}} \mathrm{Exp}\left([\epsilon]\right) P^{\frac{1}{2}}, \tag{35}$$

where $P^{\frac{1}{2}} = RS^{\frac{1}{2}}R^\top$ for an eigendecomposition of $P = RSR^\top$, and the bracket operator is defined for $\epsilon = (\epsilon_{11}, \ldots, \epsilon_{1n}, \epsilon_{22}, \ldots, \epsilon_{2n}, \ldots, \epsilon_{nn}) \in \mathbb{R}^{\frac{n(n+1)}{2}}$ as $([\epsilon])_{ij} = a_{ij}\epsilon_{ij}$ for $i \leq j$ and $([\epsilon])_{ij} = ([\epsilon])_{ji}$ for $i > j$, with $a_{ij} = 1$ if $i = j$ and $\frac{1}{\sqrt{2}}$ otherwise.

Provided σ^2 is small, the matrix exponential can be approximated using the Tayor expansion for efficient training. We have considered the expansion up to the second-order, i.e., $\mathrm{Exp}([\epsilon]) \approx I + [\epsilon] + \frac{1}{2}[\epsilon]^2$.

C.2.2 THE RECONSTRUCTION ERROR

For a reconstruction function $r : P(n) \to P(n)$, the reconstruction error is defined from the affine-invariant Riemannian metric as follows (Fletcher & Joshi, 2007):

$$\mathrm{dist}(r(\tilde{P}), P)^2 = \left\|\mathrm{Log}\left(P^{-\frac{1}{2}}r(\tilde{P})P^{-\frac{1}{2}}\right)\right\|_F^2, \tag{36}$$

where $P^{-\frac{1}{2}} = RS^{-\frac{1}{2}}R^\top$ for an eigendecomposition of $P = RSR^\top$, $\mathrm{Log} : \mathrm{P}(n) \to \mathrm{S}(n)$ is the matrix logarithm, and $\| \cdot \|_F$ is the matrix Frobenius norm. Assuming a small reconstruction error (which is usually valid for small σ^2), the matrix logarithm can be approximated using the Taylor expansion up to the second-order as $\mathrm{Log}(M) \approx (M - I) - \frac{1}{2}(M - I)^2$ with $M = P^{-\frac{1}{2}}\mathrm{r}(\tilde{P})P^{-\frac{1}{2}}$.

C.2.3 THE RECONSTRUCTION FUNCTION

The reconstruction functions r : $\mathrm{P}(n) \to \mathrm{P}(n)$ for GDAE and GRCAE should consider the special structure of $\mathrm{P}(n)$. By defining a function v : $\mathrm{P}(n) \to \mathrm{S}(n)$,[5] the reconstruction function at $P \in \mathrm{P}(n)$ is modeled as

$$\mathrm{r}(P) = P^{\frac{1}{2}}\mathrm{Exp}(\mathrm{v}(P))P^{\frac{1}{2}}. \tag{37}$$

Hence training r reduces to training unconstrained v (when considering only the lower- or upper-triangular part), and we denote by $v : \mathrm{P}(n) \to \mathbb{R}^{\frac{n(n+1)}{2}}$ the function that returns the $\frac{n(n+1)}{2}$-dimensional vector representation of the lower- (or upper-) triangular part of the output for v.

We model v by neural networks with two hidden layers, with the hyperbolic tangent (Tanh) activation function as follows:

$$v(P) = W_3 h_2 + b_3, \tag{38}$$
$$h_i = \mathrm{Tanh}(W_i h_{i-1} + b_i), \qquad i = 1, 2, \tag{39}$$

where $h_1, h_2 \in \mathbb{R}^{d_h}$ denote the hidden variables, $h_0 \in \mathbb{R}^{\frac{n(n+1)}{2}}$ is set to the vector representation of the lower- (or upper-) triangular part of $\mathrm{Log}(P)$ with $\mathrm{Log} : \mathrm{P}(n) \to \mathrm{S}(n)$ as the matrix logarithm,[6] and W_i, b_i for $i = 1, 2, 3$ respectively denote the matrix and vector parameters with sizes defined accordingly as above. We set the dimensionality of the hidden variables d_h to 1,000 for both GDAE and GRCAE in all the experiments.

We have used the following approximation $\mathrm{Exp}(\mathrm{v}(P)) \approx I + \mathrm{v}(P) + \frac{1}{2}\mathrm{v}(P)^2$ for (37) for efficient training, assuming a small norm of v.

C.2.4 CONTRACTIVE REGULARIZATION

For the case of $\mathrm{P}(n)$, we can consider the upper- (or lower-) triangular part of the matrix representations as its local coordinates, i.e., $\mathrm{r}(\mathrm{x}) \simeq r(x)$ and $\mathrm{x} \simeq x$, and calculate the contractive term of (5) straight-forwardly.

C.3 N(3) DATA

In training geometric denoising autoencoder for diffusion tensor imaging (DTI) data in Section 4.4, the structure of the manifold N(3) (using the Fisher information Riemannian metric) should be dealt with properly. Here, we provide technical details for the modeling and training of the reconstruction function r : N(3) $\to$ N(3).

C.3.1 THE FISHER INFORMATION RIEMANNIAN METRIC

Denoting by $N(\mu, \Sigma)$ a normal distribution in $\mathbb{R}^n$ with mean μ and covariance Σ, the space of n-dimensional normal distributions N(n) is defined as follows:

$$\mathrm{N}(n) = \{N(\mu, \Sigma) \mid \mu \in \mathbb{R}^n, \Sigma \in \mathrm{P}(n)\}. \tag{40}$$

N(n) becomes a differentiable manifold with dimension $n + \frac{1}{2}n(n + 1)$. By using the Fisher information Riemannian metric with local coordinates (μ, Σ) (for Σ, only the lower- or upper-triangular is needed part), the inner product of two tangent vectors $V = (V_\mu, V_\Sigma)$, $W = (W_\mu, W_\Sigma)$ for $V_\mu, W_\mu \in \mathbb{R}^n$ and $V_\Sigma, W_\Sigma \in \mathrm{S}(n)$ at a point $N = (\mu, \Sigma) \in \mathrm{N}(n)$ is defined as follows:

$$\langle V, W \rangle_N = V_\mu^\top \Sigma^{-1} W_\mu + \frac{1}{2}\mathrm{Tr}(\Sigma^{-1} V_\Sigma \Sigma^{-1} W_\Sigma). \tag{41}$$

---

[5]Here S(n) denotes the space of $n \times n$ symmetric matrices.

[6]It has shown better performance empirically to use the vector representation obtained from $\mathrm{Log}(P)$ rather than P.

It can be easily verified that the Fisher information metric reduces to the affine-invariant metric when the $\mathbb{R}^n$ part of the tangent vectors is zero; the geodesic distance between two normal distributions with identical means is then obtained in closed-form from the affine-invariant distance between the two covariance matrices. However, in general, the distance between two normal distributions cannot be obtained in closed-form; a numerical algorithm to find the minimal geodesic according to this metric is proposed in Han & Park (2014), along with some physical insights of adopting the Fisher information Riemannian metric for DTI analysis.

C.3.2 MATRIX EXPONENTIAL AND MATRIX LOGARITHM

We first provide the closed-form expressions of the matrix exponential on $S(n)$ and matrix logarithm on $P(n)$. Given an eigendecomposition of a symmetric matrix $A = RDR^\top \in S(n)$, with $R \in O(n)$ as the eigenvector matrix and $D = \text{diag}(d_1, \ldots, d_n)$ the matrix of corresponding eigenvalues, the matrix exponential is obtained as

$$\text{Exp}(A) = R \, \text{Exp}(D) \, R^\top, \tag{42}$$

where $\text{Exp}(D) = \text{diag}(\exp(d_1), \ldots, \exp(d_n))$. Given an eigendecomposition of a symmetric positive-definite matrix $A = RDR^\top \in P(n)$ similarly to the above, the matrix logarithm is obtained as

$$\text{Log}(A) = R \, \text{Log}(D) \, R^\top, \tag{43}$$

where $\text{Log}(D) = \text{diag}(\log(d_1), \ldots, \log(d_n))$.

C.3.3 DATA CORRUPTION PROCESS

Given an input voxel data $N = (x, P) \in N(3)$, we first sample $\epsilon_p \sim N(0, \sigma^2 P)$ and a six-dimensional vector $\epsilon_c \sim N(0, \sigma^2 I)$. The input voxel $(x, P) \in N(3)$ is then corrupted to $(\tilde{x}, \tilde{P}) \in N(3)$ as follows:

$$\tilde{x} = x + \epsilon_p, \tag{44}$$

$$\tilde{P} = P^{\frac{1}{2}} \text{Exp}([\epsilon_c]) \, P^{\frac{1}{2}}, \tag{45}$$

where $P^{\frac{1}{2}} = RS^{\frac{1}{2}}R^\top$ for an eigendecomposition of $P = RSR^\top$, and the bracket operator $[\,\cdot\,]$ is defined for $\epsilon = (\epsilon_1, \epsilon_2, \epsilon_3, \epsilon_4, \epsilon_5, \epsilon_6) \in \mathbb{R}^6$ as

$$[\epsilon] = \begin{bmatrix} \sqrt{2}\epsilon_1 & \epsilon_2 & \epsilon_3 \\ \epsilon_2 & \sqrt{2}\epsilon_4 & \epsilon_5 \\ \epsilon_3 & \epsilon_5 & \sqrt{2}\epsilon_6 \end{bmatrix}. \tag{46}$$

Note that this corresponds to an approximation of the data corruption process $q(\tilde{x}|x)$ (for small σ^2) discussed in Section 3.2.

C.3.4 THE RECONSTRUCTION ERROR

Denote the reconstruction function by $r = (r_p, r_c)$, where $r_p : N(3) \to \mathbb{R}^3$ corresponds to the location part and $r_c : N(3) \to P(3)$ the value part of the reconstruction function, respectively (we discuss their exact modeling in the later section). Assuming σ^2 is small, the reconstruction error between $(x, P) \in N(3)$ and $(r_p(\tilde{x}, \tilde{P}), r_c(\tilde{x}, \tilde{P})) \in N(3)$ is approximated according to the inner product of the Fisher information metric defined in (41) as follows:

$$\text{dist}\left((r_p(\tilde{x}, \tilde{P}), r_c(\tilde{x}, \tilde{P})), (x, P)\right)^2 \tag{47}$$

$$\approx (r_p(\tilde{x}, \tilde{P}) - x)^\top P^{-1}(r_p(\tilde{x}, \tilde{P}) - x) + \frac{1}{2}\text{Tr}\left(\left(P^{-\frac{1}{2}}r_c(\tilde{x}, \tilde{P})P^{-\frac{1}{2}} - I\right)^2\right),$$

where $P^{-\frac{1}{2}} = RS^{-\frac{1}{2}}R^\top$ for an eigendecomposition of $P = RSR^\top$.

C.3.5 THE RECONSTRUCTION FUNCTION

Next, we model the reconstruction function $r = (r_p, r_c)$ on N(3). By defining a function $v : N(3) \to S(3)$, the voxel value part r_c of the reconstruction function at $(x, P) \in N(3)$ is modeled as

$$r_c(x, P) = P^{\frac{1}{2}} \text{Exp} \left(v(x, P) \right) P^{\frac{1}{2}}. \tag{48}$$

In this way, training r_c reduces to training unconstrained v (when considering only the lower- or upper-triangular part), and we denote by $v : N(3) \to \mathbb{R}^6$ the function that returns the six-dimensional vector representation of the lower- (or upper-) triangular part of the output for v.

We model r_p and v by neural networks with two hidden layers, with the hyperbolic tangent (Tanh) activation function as follows:

$$
\begin{aligned}
r_p(x, P) &= x + W_3 h_2 + b_3, & (49) \\
v(x, P) &= W_4 h_2 + b_4, & (50) \\
h_i &= \text{Tanh}(W_i h_{i-1} + b_i), \qquad i = 1, 2, & (51)
\end{aligned}
$$

where $h_1, h_2 \in \mathbb{R}^{d_h}$ denote the hidden variables, and h_0 is set to be $(x, p) \in \mathbb{R}^9$ with $p \in \mathbb{R}^6$ as the vector representation of the lower- (or upper-) triangular part of P. Moreover, W_i, b_i for $i = 1, 2, 3, 4$ respectively denote the matrix and vector parameters with sizes defined accordingly as above. We set the dimensionality of the hidden variables d_h to 1,000.

C.4 POINT CLOUD DATA

C.4.1 THE FISHER INFORMATION RIEMANNIAN METRIC FOR POINT CLOUD DATA

A statistical manifold framework has been suggested to deal with point cloud data in Lee et al. (2022). Briefly speaking, they deem each point in a point cloud as a sample from a certain parametric probability density model and identify the data to the density. The Fisher information metric for these density models can then serve as a natural Riemannian metric in the point cloud data space.

For a point cloud data in $\mathbb{R}^D$ represented as $X = \{x_1, \ldots, x_n \mid x_i \in \mathbb{R}^D\}$, by using X itself as the parameter, following parametric probability density model is considered:

$$p(x; X) = \frac{1}{n\sqrt{|\Sigma|}} \sum_{i=1}^{n} K\left(\Sigma^{-\frac{1}{2}}(x - x_i)\right), \tag{52}$$

where $K : \mathbb{R}^D \to \mathbb{R}$ is a kernel function satisfying $\int_{\mathbb{R}^D} K(u)du = 1$, and $\Sigma \in \mathbb{R}^{D \times D}$ is a symmetric positive-definite bandwidth matrix. In the experiments, we choose the Gaussian kernel function $K(u) = 1/\sqrt{(2\pi)^D} \exp(-u^\top u/2)$ with $\Sigma = \sigma_p^2 I$ following Lee et al. (2022).

With such a choice of density model, the Fisher information metric $G \in \mathbb{R}^{nD \times nD}$ is obtained as

$$G_{ijkl} = \int p(x; X) \frac{\partial \log p(x; X)}{\partial X^{ij}} \frac{\partial \log p(x; X)}{\partial X^{kl}} dx \tag{53}$$

for $i, k = 1, \ldots, n$ and $j, l = 1, \ldots, D$, where G_{ijkl} is the $((i-1)D + j, (k-1)D + l)$ entry of G and X^{ij} is the j-th entry of x_i. We approximate the integration in (53) as a finite sum of the integrands (with $p(x; X)$ excluded) over the data points $x_1, \ldots, x_n$. We refer the reader to Lee et al. (2022) for more details.

C.4.2 DATA CORRUPTION PROCESS

Since applying the exponential map based on the Riemannian metric in (53) is computationally very expensive, we resort to an approximation for the data corruption process. Given a vector representation of the point cloud data $x = (x_1^\top, \ldots, x_n^\top) \in \mathbb{R}^{nD}$, we sample a random vector of the same size $\epsilon \sim N(0, \sigma^2 I)$, and corrupt the data as $\tilde{x} \approx x + \sqrt{G^{-1}}\epsilon$, where $G^{-1} \in \mathbb{R}^{nD \times nD}$ is the inverse of the Riemannian metric G in (53). We further approximate G to be a diagonal matrix by considering only the diagonal elements of (53) so that $\sqrt{G^{-1}}$ is computationally tractable.

C.4.3 THE RECONSTRUCTION ERROR

For a reconstruction function $r : \mathbb{R}^{n \times D} \to \mathbb{R}^{n \times D}$, consider a point cloud $X = \{x_1, \ldots, x_n \mid x_i \in \mathbb{R}^D\}$ and its reconstructed version $r(\tilde{X}) = Y = \{y_1, \ldots, y_n \mid y_i \in \mathbb{R}^D\}$. We define the reconstruction error by slightly modifying the Chamfer distance in Yang et al. (2018) as follows (Lee et al., 2022):

$$\text{Reconstruction error} = \frac{1}{|X|} \sum_{x \in X} \min_{y \in Y} \|x - y\|^2 + \frac{1}{|Y|} \sum_{y \in Y} \min_{x \in X} \|x - y\|^2, \quad (54)$$

where $|X|$ denotes the number of elements in the set X.

Note that using the reconstruction error in (54) does not perfectly correspond to our original definition of GDAE in (6), which uses the geodesic distance as the reconstruction error. However, with a slight abuse of notation, we still use the term GDAE for the method minimizing the reconstruction error defined in (54).

C.4.4 THE RECONSTRUCTION FUNCTION

We use the exactly same point cloud autoencoder with the reconstruction function $r : \mathbb{R}^{n \times D} \to \mathbb{R}^{n \times D}$ (i.e., the composition of the encoder $f : \mathbb{R}^{n \times D} \to \mathbb{R}^d$ and the decoder $g : \mathbb{R}^d \to \mathbb{R}^{n \times D}$) adopted from the FcNet in Yang et al. (2018). We set the latent space dimensionality d as 512.

C.5 A REMARK ON IMPLEMENTATION FOR MANIFOLDS THAT REQUIRE MULTIPLE COORDINATE CHARTS

Since the manifolds mainly considered in the experiments, e.g., S^n, $P(n)$, $N(n)$, and the statistical manifold for point cloud data, could be embedded in Euclidean spaces, we have directly used the manifold elements embedded in Euclidean spaces as the form of input and output for $r : \mathcal{M} \to \mathcal{M}$. When this is not the case, e.g., for the abstract manifolds, we can implement the mappings $r : \mathbb{R}^m \to \mathbb{R}^m$ represented in local coordinates. When multiple charts are required, one available approach would be to implement mappings for each chart as separate neural networks and train each mapping by minimizing objective functions weighted by appropriate weight functions. In the case of GDAE, for example, we can solve C optimization problems as follows:

$$\min_{r_i} \int_{\mathcal{M}} E_{q(\tilde{x}|x)}[\text{dist}(r_i(\tilde{x}), x)^2] \rho(x) f_i(x) dx, \quad i = 1, \ldots, C, \quad (55)$$

where C is the number of charts, $r_i : \mathbb{R}^m \to \mathbb{R}^m$ is the mapping for the i-th chart, and $f_i(x)$ is the weight function for the i-th chart, e.g., determined based on partitions of unity (satisfying that, for all $x \in \mathcal{M}$, there is a neighborhood of x where all but a finite number of $f_i(x)$s are zero and $\sum_{i=1}^{C} f_i(x) = 1$). The final reconstruction results for $x \in \mathcal{M}$ can be obtained by geometrically averaging (after appropriate coordinate transforms) the outputs $r_i(x)$ from each mapping with corresponding weights $f_i(x)$.

D DETAILS FOR SECTION 4.1

D.1 SYNTHETIC DATA GENERATION

We use 10,000 data sampled from m mixtures of tangent space Gaussian on $P(n)$ in Section 4.1. For the i-th mixture, we set the mean as $\mu_i = \text{Exp}(\frac{\sqrt{d}}{2}\text{diag}(e_i)) \in P(n)$ and the covariance represented using an orthonormal basis of $T_{\mu_i}P(n)$ as $\Sigma_i = (0.1)^2 I \in \mathbb{R}^{d \times d}$. Here $d = \frac{n(n+1)}{2}$ is the dimension of $P(n)$, $e_i \in \mathbb{R}^n$ is a standard vector whose i-th element is one, and $\text{Exp} : S(n) \to P(n)$ is the matrix exponential.

D.2 DEFINITION OF THE ESTIMATION ERROR

For a given data set $\{x_1, \ldots, x_N\}$ represented in local coordinates of $P(n)$, the log-density gradient estimation error (Est. error) is evaluated as follows:

$$\text{Est. error} = \frac{1}{N} \sum_{i=1}^{N} \left(\frac{\partial \log \rho_g}{\partial x}\Big|_{\text{est}}(x_i) - \frac{\partial \log \rho_g}{\partial x}(x_i) \right)^\top G^{-1}(x_i) \left(\frac{\partial \log \rho_g}{\partial x}\Big|_{\text{est}}(x_i) - \frac{\partial \log \rho_g}{\partial x}(x_i) \right), \quad (56)$$

where $\frac{\partial \log \rho_g}{\partial x}\big|_{\text{est}}(x_i)$ and $\frac{\partial \log \rho_g}{\partial x}(x_i)$ respectively denote the estimated value and the ground truth value for $\frac{\partial \log \rho_g(x)}{\partial x}$ at x_i. Note that it is usually impossible to calculate the estimation performance based on (56) since the ground truth value of $\frac{\partial \log \rho_g(x)}{\partial x}$ is generally not available. Instead, (56) can be reformulated not to require the $\frac{\partial \log \rho_g(x)}{\partial x}$ term by using the integration by parts technique presented in Hyvärinen (2005). Ignoring the constant terms that do not depend on the estimated value, (56) can be rewritten as

$$\frac{1}{N}\sum_{i=1}^N \left(\frac{\partial \log \rho_g}{\partial x}\Big|_{\text{est}}^\top (x_i) G^{-1}(x_i) \left(\frac{\partial \log \rho_g}{\partial x}\Big|_{\text{est}}(x_i) + 2\Gamma(x_i) \right) + 2\sum_{j=1}^m \sum_{k=1}^m \frac{\partial}{\partial x^k}\left(\frac{\partial \log \rho_g}{\partial x^j}\Big|_{\text{est}}(x_i) g^{jk}(x_i) \right) \right), \quad (57)$$

where $\Gamma(x) \in \mathbb{R}^m$ is a vector whose i-th component is given by $\frac{1}{2}\mathrm{Tr}\left(G^{-1}\frac{\partial G}{\partial x^i}\right)$. Note that this formulation turns out to be equivalent to the minimization objective of the R-LSLDG method (Ashizawa et al., 2017). In the case of GDAE and GRCAE, further simplification is available for (57): $\sum_j \sum_k \frac{\partial}{\partial x^k}\left(\frac{\partial \log \rho_g}{\partial x^j}\big|_{\text{est}} g^{jk} \right) = \frac{1}{\sigma^2}\mathrm{Tr}\left(\frac{\partial r}{\partial x} - I\right)$ holds from (7). Equation (57) can be used in hyperparameter tuning to evaluate the performance of the estimation in place of (56).

D.3 Training DAE, RCAE, GDAE, GRCAE, LSLDG, and R-LSLDG

We model the reconstruction functions r : P(n) $\to$ P(n) for GDAE and GRCAE as explained in Appendix C.2. The reconstruction functions $r : \mathbb{R}^d \to \mathbb{R}^d$ ($d = \frac{n(n+1)}{2}$ for P(n)) for DAE and RCAE are modeled by a neural network with two hidden layers, with the hyperbolic tangent (Tanh) activation function as follows:

$$\begin{aligned} r(x) &= x + W_3 h_2 + b_3, & (58) \\ h_i &= \mathrm{Tanh}(W_i h_{i-1} + b_i), & i = 1, 2, & (59) \end{aligned}$$

where $h_1, h_2 \in \mathbb{R}^{d_h}$ denote the hidden variables, h_0 is set to be $x \in \mathbb{R}^d$, and W_i, b_i for $i = 1, 2, 3$ respectively denote the matrix and vector parameters with sizes defined accordingly as above. We set the dimensionality of the hidden variables d_h to 1,000 for both DAE and RCAE.

We optimize the parameters $\theta = \{W_1, b_1, W_2, b_2, W_3, b_3\}$ in (38), (39) for (6) and (5) to respectively train GDAE and GRCAE (or those in (58), (59) for (1) and (2) to respectively train DAE and RCAE). We apply the Adam algorithm (Kingma & Ba, 2015) using the Pytorch library (Paszke et al., 2017) and update the parameters for 500,000 iterations. We use the batch size of 1,000 to train RCAE and GRCAE and the batch size of 10,000 to train DAE and GDAE. The learning rate starts at 2.5e-5 and is divided by ten after 250,000 iterations with a weight decay parameter of 1e-12. We have applied the weight initialization scheme of Glorot & Bengio (2010) in training. Dividing the initial W_1, b_1 by two helped to improve the estimation error for GDAE and GRCAE.

In discretizing (1), (2), (6), and (5), the expectations with respect to the data-generating probability density $\rho(x)$ are approximated by a finite sum over the N training data points with equal weights $\frac{1}{N}$. Given an input x (or x), the expectation with respect to the noise density $q(\tilde{x}|x)$ in (6) for GDAE (or $q(\tilde{x}|x)$ in (1) for DAE) is also approximated by a finite sum over finite samples of $\tilde{x}$ (or $\tilde{x}$) with equal weights.

In training the autoencoders, the noise parameter in the data corruption process or the weighting coefficient for the contractive term (σ^2) should be chosen carefully. In this experiment, σ is selected among $\sigma \in \{0.01, 0.025, 0.05\}$ to reduce the modified estimation error in (57), which does not require the true value of $\frac{\partial \log \rho_g(x)}{\partial x}$, on a randomly selected validation data set of sizes 20,000. Since the estimation results from the autoencoders can vary over iterations due to the stochastic nature of the optimization algorithm, instances with the minimum value of (57) during the training process are taken to be the output for each run of autoencoder training.

In LSLDG, the derivative of the log-probability density, i.e., $\frac{\partial \log \rho(x)}{\partial x}$, is modeled as a weighted sum of some basis functions, with the weights optimized in a least-squares sense. R-LSLDG method estimates the derivative of the log-probability function, i.e., $\sum_j g^{ij}\frac{\partial \log \rho_g(x)}{\partial x^j}$ for $i = 1, \ldots, m$ in local coordinates, similar to LSLDG but using basis functions defined on the Riemannian manifold. For both LSLDG and R-LSLDG, we perform cross-validation for the hyperparameters $\lambda \in \{10^{-3}, 10^{-2}, 10^{-1.5}, 10^{-1}, 10^{-0.5}, 10^0, 10^{0.5}, 10^1\}$ and

$\sigma \in \{10^{-4}, 10^{-3}, 10^{-2.5}, 10^{-2}, 10^{-1.5}, 10^{-1}, 10^{-0.5}, 10^0\}$ as described in Sasaki et al. (2014) and Ashizawa et al. (2017).[7] The number of the basis functions is set to 500.

We have utilized NVIDIA Tesla V100 GPU with Intel Xeon E5-2698 v4 2.2 GHz (20-Core) CPU for most of the experiments. The time spent in training each model is shown in Table 6. The autoencoders (DAE, RCAE, GDAE, and GRCAE) take a much longer time for training when compared to LSLDG and R-LSLDG, which are linear-in-parameter models and have closed-form solutions for the parameters. Furthermore, GRCAE (or RCAE) requires more computations than GDAE (or DAE) due to the contractive terms containing the derivative of the reconstruction functions. Compared to DAE and RCAE, GDAE and GRCAE involve heavier computations such as the eigenvalue decomposition (EVD) to reflect the non-Euclidean geometry of the data. Efficient parallel computation for EVD has been available by using the `torch_batch_svd` repository (MIT License).[8]

Table 6: The time (in seconds) spent in training each model for $P(n)$ data.

n	LSLDG	DAE	RCAE	R-LSLDG	GDAE	GRCAE
2	9	3062	17382	126	20671	43254
3	17	4087	19622	306	22499	67580
4	33	4014	25120	545	33166	116255

D.4 GEOMETRIC SCORE ESTIMATION OF SYNTHETIC HYPERSPHERICAL DATA

This section provides the result of the geometric score estimation for the data on hypersphere $S^n = \{p \in \mathbb{R}^{n+1} \mid \|p\| = 1\}$ endowed with the Riemannian metric induced from the Euclidean metric on $\mathbb{R}^{n+1}$. We use 10,000 data generated by mapping samples from m Gaussian mixtures in $T_p S^n$ via the exponential map $\text{Exp}_p : T_p S^n \to S^n$, where $p = (1, 0, \ldots, 0) \in \mathbb{R}^{n+1}$. For the i-th mixture, we set the mean as $\mu_i = \frac{1}{\sqrt{2}} e_i \in \mathbb{R}^n$ with $e_i \in \mathbb{R}^n$ as a standard vector whose i-th element is one, and the covariance as $\Sigma_i = (0.1)^2 I \in \mathbb{R}^{n \times n}$ so that the ground truth log-probability derivative values are obtainable.

We train the DAE, RCAE, GDAE, GRCAE, LSLDG, and R-LSLDG using the data. For the autoencoder models described in Appendix C.1 (for GDAE and GRCAE) and Appendix D.3 (for DAE and RCAE), we use the Adam optimizer (Kingma & Ba, 2015) of the Pytorch library (Paszke et al., 2017) to update the parameters for 500,000 iterations. We use the batch size of 1,000 to train RCAE and GRCAE and the batch size of 10,000 to train DAE and GDAE. From the initialization scheme of Glorot & Bengio (2010), the initial W_1, b_1 are further divided by 1-5 for the experiments. Other optimization and hyperparameter tuning conditions are kept the same as those explained in Appendix D.3.

For both LSLDG and R-LSLDG, we perform cross-validation for the hyperparameters $\lambda \in \{10^{-3}, 10^{-2}, 10^{-1.5}, 10^{-1}\}$ and $\sigma \in \{10^{-2}, 10^{-1.5}, 10^{-1}, 10^{-0.5}, 10^0\}$ as described in Sasaki et al. (2014) and Ashizawa et al. (2017). The number of the basis functions is set to 500. The time spent in training each model is shown in Table 7.

Table 7: The time (in seconds) spent in training each model for S^n data.

n	LSLDG	DAE	RCAE	R-LSLDG	GDAE	GRCAE
2	33	3002	17165	240	5236	21804
6	111	3472	20369	399	6590	25864
10	203	4112	25019	570	7696	34365

The estimation errors for $\frac{\partial \log \rho_g}{\partial x}$ obtained from each model are reported in Table 8. Similar to the results in Section 4.1, the GDAE and GRCAE perform much better than other methods (especially for higher dimensionality), while GRCAE gives the least estimation error in most cases.

---

[7]The definitions of λ and σ can be found in Sasaki et al. (2014) and Ashizawa et al. (2017).

[8]URL: https://github.com/KinglittleQ/torch-batch-svd.

Table 8: The estimation errors for $\frac{\partial \log \rho_g}{\partial x}$ for tangent space Gaussian mixture data on S^n. Bolds represent the best and comparable methods from the t-test with a significance level of 5%.

n	m	LSLDG	DAE	RCAE	R-LSLDG	GDAE	GRCAE
2	2	**1.44** (0.07)	4.94 (0.25)	6.43 (2.05)	1.77 (0.09)	1.91 (0.18)	1.74 (0.15)
6	2	644 (10.3)	647 (266)	586 (93.9)	5.83 (0.11)	5.16 (0.16)	**4.74** (0.09)
6	6	677 (21.1)	1194 (369)	1175 (259)	22.9 (0.14)	**14.2** (1.05)	**14.1** (1.27)
10	2	782 (6.45)	630 (107)	802 (187)	14.4 (0.35)	8.52 (0.17)	**7.58** (0.07)
10	6	1201 (4.46)	739 (81.1)	1142 (67.4)	42.7 (0.12)	**21.3** (3.90)	20.7 (3.57)
10	10	1700 (133)	1380 (54.8)	1655 (82.2)	50.4 (0.27)	**39.3** (0.95)	38.2 (1.72)

E DETAILS FOR SECTION 4.2

We consider four synthetic data sets on S^2: four blobs, two moons, an s-curve, and circles, which are generated by the following procedure. First, we make two-dimensional data sets by using the python `sklearn.datasets` package with zero noise level, place them on the plane $z = 1$, and project them to the spherical surface S^2. Secondly, we add tangent Gaussian noises with standard deviations of 0.01 for two moons, s-curve, circles, and 0.05 for four blobs, and project those perturbed data to the sphere by Riemannian projections. The number of training data is 800, that of validation data is 200, and that of test data is 1000.

For autoencoder-based models, we use the fully-connected neural network architecture that has 3-512-512-512-512-512-3 layers with ReLU-ReLU-linear-ReLU-ReLU-linear activation functions. For S-Flow that uses the RealNVP model (Dinh et al., 2016), the depth is 8 and the length of the hidden feature is 512. For all cases, the learning rate is 1e-3 and the weight decay parameter is 1e-12.

For autoencoder-based models, we search $\sigma \in \{0.01, 0.025, 0.05\}$. We use the batch gradient descent, and the maximum training epoch is set to 5000. As a validation loss used to determine the best model during the training, we use the modified score estimation error in (57) for autoencoder-based models and negative log-likelihood for S-Flow. In RLMC sampling of the autoencoder-based models, we need to determine the step size. The step size is searched over $\{0.00001, 0.00005, 0.0001, 0.0005, 0.001\}$. We run the experiment five times with different random seeds. In the result table, the averages and standard errors of the best cases are reported, where for each run the best-model-resulting hyperparameters (i.e., σ and step size for autoencoder-based models) are selected by computing the MMD metrics (Gretton et al., 2012) between sampled points and the validation data sets. We compute the MMD metric with the exponential kernel $k(x, y) = \exp(-d_{S^2}^2(x, y)/(2 * \eta^2))$ where $d_{S^2}(x, y)$ is the squared geodesic distance between data $x, y \in S^2$ and the bandwidth parameter η is defined as the mean of the 1,2,3,4,5-nearest neighbor geodesic distances for all training data.

F DETAILS FOR SECTION 4.3

F.1 DEFINITION OF THE CLUSTERING TASKS

We define the clusters by merging relevant topics among 20 groups in the Newsgroup20 data set,[9] resulting in 'religion', 'computers', 'politics', 'automobiles', 'sports', and a topic in 'science' (one among 'crypt','electronics','med', and 'space'). We define four clustering tasks by differing the topic in 'science'.

F.2 TRAINING DAE, GDAE, LSLDG, AND R-LSLDG

The reconstruction function for GDAE is modeled as explained in Appendix C.1, and DAE is modeled in the same way as explained in Appendix D.3.

We then optimize the parameters $\theta = \{W_1, b_1, W_2, b_2, W_3, b_3\}$ for (6) and (1) to train GDAE and DAE, respectively. We use the Adam optimizer (Kingma & Ba, 2015) of the Pytorch library (Paszke

---

[9]URL: http://qwone.com/ jason/20Newsgroups/.

et al., 2017) and update the parameters for 500,000 iterations. The learning rate respectively starts at 2.5e-3 and 1e-3 for GDAE and DAE, and is divided by ten after 250,000 iterations. Other optimization conditions are kept the same as those in Appendix D.3, and the corruption noise standard deviations σ used are selected between $\sigma \in \{0.025, 0.05\}$ to reduce the modified estimation error in (57) on the training data set.

For both LSLDG and R-LSLDG, we perform cross-validation for the hyperparameters $\lambda \in \{10^{-3}, 10^{-2}, 10^{-1.5}, 10^{-1}\}$ and $\sigma \in \{10^{-1.2}, 10^{-1}, 10^{-0.5}, 10^{0}\}$ as described in Sasaki et al. (2014) and Ashizawa et al. (2017). The number of the basis functions is set to 300. The time spent in training each model is shown in Table 9.

Table 9: The time (in seconds) spent in training each model for S^{49} data.

LSLDG	LSLDG Amb	DAE	DAE Amb	R-LSLDG	GDAE
288	166	5006	5015	1435	6108

F.3 CLUSTERING OF COVARIANCE MATRIX DATA

In this section we provide a case study of the clustering of covariance matrix data. Following Jayasumana et al. (2015), we calculate covariance matrices from the features of image data and group the images based on the covariance matrices. For this case study, we consider the ETH-80 data set[10] with 3,240 images from eight categories (Leibe & Schiele, 2003), COIL-20 data set[11] with 1,440 images from twenty categories (Nene et al., 1996a), and COIL-100 data set[12] with 7,200 images from a hundred categories (Nene et al., 1996b). In calculating the covariance matrix for each image, we use the feature (from every pixel of the image) consists of $\{x, y, I, |I_x|, |I_y|\}$, where x, y are the horizontal and vertical pixel locations, I is the intensity of the pixel, and I_x and I_y are the horizontal and vertical gradients of the intensity, respectively.[13] Hence the data in use are in $P(5)$.

We train DAE, GDAE, LSLDG, and R-LSLDG using the covariance matrix data and perform clustering using the trained models similarly as explained in Section 4.3. For the GDAE and DAE models respectively described in Appendix C.2 and Appendix D.3, we use the Adam optimizer (Kingma & Ba, 2015) of the Pytorch library (Paszke et al., 2017) to update the parameters for 400,000 iterations. The learning rate starts at 1e-4 and is divided by ten after 200,000 iterations with a weight decay parameter of 1e-12.

The corruption noise standard deviations σ can significantly affect the clustering performance in DAE and GDAE. To choose σ, we use a (randomly chosen) half of the data as a validation set to train the DAE and GDAE models and measure the clustering performance. The value that gives the best clustering performance among $\sigma \in \{0.025, 0.05, 0.1, 0.2\}$ is chosen, and we use the rest half of the data to train the models and report the clustering performance. Other optimization conditions are kept the same as those explained in Appendix D.3.

For both LSLDG and R-LSLDG, we perform cross-validation for the hyperparameters $\lambda \in \{10^{-3}, 10^{-2}, 10^{-1.5}, 10^{-1}\}$ and $\sigma \in \{10^{-2}, 10^{-1.5}, 10^{-1}, 10^{-0.5}, 10^{0}\}$ as described in Sasaki et al. (2014) and Ashizawa et al. (2017). The number of the basis functions is set to 100. The clustering is performed using the identical data used to report the results from DAE and GDAE. The time spent in training each model is shown in Table 10.

Table 10: The time (in seconds) spent in training each model for $P(5)$ data.

Data set	LSLDG	DAE	R-LSLDG	GDAE
ETH-80	20	1184	63	14227
COIL-20	15	1221	50	13282
COIL-100	23	1178	99	14924

---

[10]URL: https://github.com/Kai-Xuan/ETH-80.

[11]URL: https://www.cs.columbia.edu/CAVE/software/softlib/coil-20.php.

[12]URL: https://www.cs.columbia.edu/CAVE/software/softlib/coil-100.php.

[13]Each dimension of the features has been normalized before calculating the covariance matrices.

The averaged clustering performance for five runs of each method is presented in Table 11. For the ETH-80 data set, R-LSLDG and GDAE show better performance than others on average but without much significance. In the case of the COIL-20 data set, the clustering results from DAE show the best performance. The absence of a significant performance difference between DAE and GDAE in both cases may partially be due to the less peculiarity in the covariance matrices, e.g., having extremely small or large eigenvalues, for the relatively small number of categories. (According to the affine-invariant metric, the geometry of the covariance matrices can become more relevant when the relative eigenvalues of the covariance matrices get bigger or smaller.) When the number of categories gets bigger as in the COIL-100 data set, the results from GDAE show better performance with a large margin compared to DAE. Even though this case study does not show a distinct tendency, clustering using GDAE performs well among the considered methods in terms of the overall adjusted Rand index.

Table 11: The adjusted Rand index for the covariance matrix data on P(5). Bolds represent the best and comparable methods from the t-test with a significance level of 5%.

Data set	LSLDG	DAE	R-LSLDG	GDAE
ETH-80	**0.318** (0.039)	**0.348** (0.016)	**0.362** (0.035)	**0.361** (0.022)
COIL-20	0.170 (0.030)	**0.655** (0.012)	0.483 (0.030)	0.616 (0.016)
COIL-100	1.46e-3 (2.9e-4)	0.204 (0.009)	0.314 (0.036)	**0.380** (0.015)

G   DETAILS FOR SECTION 4.4

G.1   TRAINING OF THE RECONSTRUCTION FUNCTION

We model GDAE for N(3) as explained in Appendix C.3.5. We then optimize the parameters $\theta = \{W_1, b_1, W_2, b_2, W_3, b_3, W_4, b_4\}$ for (6) to train GDAE. We model DAE as explained in Appendix D.3 with $d = 9$, and the parameters in (58), (59) are optimized for (1). We use the Adam optimizer (Kingma & Ba, 2015) of the Pytorch library (Paszke et al., 2017) and update the parameters for 40,000 iterations. The learning rate starts at 1e-4 and is divided by 100 after 20,000 iterations. In discretizing (6), the expectation with respect to the data-generating probability density $\rho(x)$ and the noise density $q(\tilde{x}|x)$ are dealt with in the same way as for the case studies in Section 4.1 (explained in Appendix D.3), and we use the approximated reconstruction error in (47). We use the corruption noise standard deviation $\sigma = 0.05$ in training both DAE and GDAE.

G.2   A GDAE-BASED DTI FILTERING ALGORITHM

Based on the discussions in Section 4.4, we summarize a DTI filtering algorithm based on the GDAE in Algorithm 1. At each iteration, the input points are updated toward the reconstructed points of GDAE along the geodesic with a predefined step size ϵ. Assuming small step sizes, we approximate the update along the geodesic on N(3) by treating the updates of the location (in $\mathbb{R}^3$) and the value (in P(3)) separately. The update of the voxel values then reduces to update along the geodesic according to the affine-invariant Riemannian metric on P(3) (Fletcher & Joshi, 2007), as expressed in line 5 of Algorithm 1. The functions $\text{Exp}_Q : \text{S}(3) \to \text{P}(3)$ and $\text{Log}_Q : \text{P}(3) \to \text{S}(3)$ (for $Q \in \text{P}(3)$) are defined as follows:

$$\text{Exp}_Q(A) = Q^{\frac{1}{2}} \text{Exp}\left(Q^{-\frac{1}{2}} A Q^{-\frac{1}{2}}\right) Q^{\frac{1}{2}}, \tag{60}$$

$$\text{Log}_Q(P) = Q^{\frac{1}{2}} \text{Log}\left(Q^{-\frac{1}{2}} P Q^{-\frac{1}{2}}\right) Q^{\frac{1}{2}}, \tag{61}$$

where $Q^{\frac{1}{2}} = RS^{\frac{1}{2}}R^\top$ and $Q^{-\frac{1}{2}} = RS^{-\frac{1}{2}}R^\top$ for an eigendecomposition of $Q = RSR^\top$, and the functions $\text{Exp}(\cdot)$ and $\text{Log}(\cdot)$ respectively denote the matrix exponential and logarithm of which the closed-forms are provided in Appendix C.3.2. When the iteration is terminated, we assign the final voxel values to their original locations.

G.3   DETAILS FOR N(2) FILTERING EXPERIMENTS

In this experiment, we consider a synthetic N(2) data set obtained by gathering the position (in $\mathbb{R}^2$)-value (in P(2)) pairs at 1,600 grid points (i.e., $N = 1,600$) of a P(2) field on $\mathbb{R}^2$. For the P(2) field

---

Algorithm 1 DTI Filtering Algorithm Using GDAE

Given: Voxels of a DTI datum $(x_i, P_i) \in N(3)$, $i = 1, \ldots, N$.
Input: Reconstruction function r : $N(3) \to N(3)$ of the GDAE trained from the given set of voxels, step size ϵ, the number of iterations N_{iter}.
Initialize: $(y_{i,1}, Q_{i,1}) = (x_i, P_i)$ for $i = 1, \ldots, N$.
Iteration:
1: **for** $j = 1, \ldots, N_{\text{iter}}$, $i = 1, \ldots, N$ **do**
2:     Compute the reconstruction point $(y_i, Q_i) = \text{r}(y_{i,j}, Q_{i,j})$.
3:     Shift the current point according to step size ϵ:
4:     $y_{i,j+1} \leftarrow y_{i,j} + \epsilon(y_i - y_{i,j})$,
5:     $Q_{i,j+1} \leftarrow \text{Exp}_{Q_{i,j}} \left(\epsilon \, \text{Log}_{Q_{i,j}}(Q_i) \right)$ ($Q_{i,j+1} \leftarrow Q_i$ holds when $\epsilon = 1$).
6: **end for**
7: Assign $P_{i,f} = Q_{i,N_{\text{iter}}+1}$ for $i = 1, \ldots, N$.
Output: Filtered voxels $(x_i, P_{i,f}) \in N(3)$, $i = 1, \ldots, N$.

---

for clean data, we gather four distinct smoothly-varying P(2) fields as depicted in Figure 5. For the noisy data, we corrupt each value in P(2) as explained in (35) with noise standard deviations (or noise levels) in $\{0.02, 0.05, 0.1, 0.2\}$.

We model the neural networks for both DAE and GDAE as explained in Appendix D.3 and Appendix C.3.5 with appropriate modifications to deal with data in N(2), respectively, and train the reconstruction functions. We use the Adam optimizer (Kingma & Ba, 2015) and update the parameters for 20,000 iterations. The learning rate starts at 1e-4 and is divided by 100 after 10,000 iterations. The corruption noise standard deviation is chosen among $\sigma \in \{0.01, 0.025, 0.05, 0.1\}$ to show the best modified estimation error in (57). For the trained models, we apply Algorithm 1 (with appropriate modifications to deal with N(2) data) with $N_{\text{iter}} \leq 300$ and the step size $\epsilon \in \{0.01, 0.03, 0.1, 0.3, 1.0\}$ chosen to achieve the minimum averaged square distances (according to the affine-invariant metric) to the clean data.

For the MVKR method in Banerjee et al. (2015), the number of considered nearest neighbors $k \in \{10, 20, 30, 40, 100\}$ and the kernel bandwidth parameter $\sigma \in \{1, 10, 20, 30, 50\}$ are chosen to achieve the minimum averaged square distances (according to the affine-invariant metric) to the clean data.

We report the R-squared score to compare the filtering results from each method in Table 4, and the scores are calculated as follows:

$$\text{R-squared score} = 1 - \frac{\sum_i \text{dist}(P_{i,f}, P_{i,true})^2}{\sum_i \text{dist}(\bar{P}, P_{i,true})^2}, \tag{62}$$

where $\text{dist}(P_1, P_2)$ is the distance between $P_1, P_2 \in P(2)$ obtained according to the affine-invariant metric, $P_{i,f} \in P(2)$ is the i-th filtered value, $P_{i,true} \in P(2)$ is the i-th value of the clean data, and $\bar{P} \in P(2)$ is the intrinsic mean of $\{P_{1,true}, \ldots, P_{N,true}\}$ (Moakher, 2005).

G.4 PREPROCESSING DIFFUSION TENSOR IMAGING (DTI) DATA

Data used in the preparation of the experiments performed in Section 4.4 were obtained from the Alzheimer's Disease Neuroimaging Initiative (ADNI) database (adni.loni.usc.edu).[14] Among the data set, we use the DTI data for a randomly chosen healthy subject.

FSL library (Jenkinson et al., 2012) is utilized to fit diffusion tensors from raw diffusion weighted image data.[15] The brain extraction tool (BET), eddy current correction function (eddy_correct),

---

[14]The ADNI was launched in 2003 as a public-private partnership, led by Principal Investigator Michael W. Weiner, MD. The primary goal of ADNI has been to test whether serial magnetic resonance imaging (MRI), positron emission tomography (PET), other biological markers, and clinical and neuropsychological assessment can be combined to measure the progression of mild cognitive impairment (MCI) and early Alzheimer's disease (AD).

[15]The license information is available at URL: https://fsl.fmrib.ox.ac.uk/fsl/fslwiki/Licence.

a linear transformation tool to match to the brain template (`flirt`), and `dtifit` module are used in the preprocessing of the DTI data. The region of interest (ROI) is chosen as an axial slice that intersects with the corpus callosum region of the brain.

H DETAILS FOR SECTION 4.5

Overall experimental settings have been set similarly to those in Lee et al. (2022). We add noise to each point $x \in \mathbb{R}^3$ in the point cloud of the data sets (ShapeNet, ModelNet10, and ModelNet40) according to $x \to x + m \cdot v$, where $v \in \mathbb{R}^3 \subseteq S^2$ is uniformly sampled on the unit sphere and m is sampled from the Gaussian distribution with zero mean and different levels of standard deviation (0.01, 0.05, 0.1, and 0.2 of the diagonal length of the point cloud bounding box) as done in Lee et al. (2021a).

For the parameters in the kernel functions (52), we use $\Sigma = \sigma_p^2 I$ with $\sigma_p = 0.8 \times$ MED, where MED denotes the median of the distances between the points in the point cloud and their nearest points. The mean values of MEDs of each data set are 0.0320, 0.0364, 0.0442, and 0.579 for the cases of the noise levels 0.01, 0.05, 0.1, and 0.2, respectively.

To train the autoencoders defined in Appendix C.4, we use ADAM (Kingma & Ba, 2015) with a learning rate of 1e-4, betas of [0.9, 0.999], a weight decay of 1e-6, and a batch size of 16; the total number of epochs is 500. The noise parameters σ for DAE and GDAE are set to 0.1 and 1e-4, respectively. The coefficient for the regularization term (defined in (13) of Lee et al. (2022)) is set to $\lambda = 8000$ for both the 'AE + R.' and 'GDAE + R.' methods in Table 5.