Unsupervised Multi-object Segmentation by Predicting Probable Motion Patterns

Abstract

We propose a new approach to learn to segment multiple image objects without manual supervision. The method can extract objects form still images, but uses videos for supervision. While prior works have considered motion for segmentation, a key insight is that, while motion can be used to identify objects, not all objects are necessarily in motion: the absence of motion does not imply the absence of objects. Hence, our model learns to predict image regions that are likely to contain motion patterns characteristic of objects moving rigidly. It does not predict a *specific* motion, which cannot be done from a still image, but a distribution of possible motions, which includes the option that an object does not move at all. We demonstrate the advantage of this approach over a deterministic counterpart, show state-of-the-art unsupervised instance segmentation performance on benchmarks, and performance competitive with methods that use motion at test time.

1 Introduction

Humans have an innate ability to segment individual objects in a picture, but learning this capability with an algorithm usually relies on manual supervision. In this paper, we consider the problem of learning to segment objects from visual data only—without externally provided labels. Algorithms for this task usually assume that objects are seen in different configurations and in front of different backgrounds. They then exploit cues such as the visual consistency and the co-occurrence of characteristic object parts to learn to discover and segment individual object instances.

Most such methods work by using still images as input [14, 19, 32]. They work well on simple synthetic scenes, but they struggle in scenes with more complex visual appearance [23]. This has motivated the development of algorithms that use videos as input [20, 29, 47] and can thus observe the motion of the objects as evidence of their presence. A common way of using motion for unsupervised learning is to seek for a compact representation to *reconstruct* the video itself. Effectively, such methods seek for a compressed representation of appearance, but do not sidestep entirely the difficult task of modeling it. This has motivated authors to look instead at reconstructing the video's *optical flow* [24, 51]. In fact, the optical flow measures the motion of the objects directly and is much simpler to analyse than the objects' appearance.

In this paper, we propose a method that sits in-between these two classes. Our model learns to segment objects in still images, and is thus based on appearance, but learns to do so using video as a learning signal, in an unsupervised manner. The learning process can be summarized as follows. Given an image, each pixel is assigned to a slot that represents a certain object. The quality of the assignments is then measured by the coherence of the (unobserved) optical flow within the extracted regions. Because predicting optical flow from a still image is intrinsically ambiguous, the method models *distributions* of probable flow patterns within each region. The idea is that (rigid) objects generate characteristic flow patterns that can be used to distinguish between them.

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Note that, because the segmentation network is based on a single image, it will learn to partition all objects contained in the scene, not just the ones that actually move in the video, *i.e.* solving the object instance segmentation problem, rather than *motion* segmentation.

We derive closed-form distributions for the flow field generated by rigid objects moving in the scene. We also derive efficient expressions for the calculation of the flow probability under such models. The problem of decomposing the image into a number of regions is cast instead as a standard image segmentation task and an off-the-shelf neural network can be used for it.

As our method uses videos to train an image-based model, we introduce two new datasets which are straightforward video extensions of the existing image datasets CLEVR [21] and CLEVRTEX [23]. These datasets are build by animating the objects with initial velocities and using a physics simulation to generate realistic object movement. Our datasets are constructed with the realistic assumption that not all objects are moving at all times. This means that motion alone cannot be used as the sole cue for objectness and reflects scenarios such a workbench where a person only interacts with a small number of objects at a time.

Empirically, we validate our model against several ablations and baselines. We also compare our approach to existing unsupervised multi-object segmentation methods achieving state-of-the-art performance. We demonstrate particularly strong performance in visually complex scenes even with unseen objects and textures at test time. We also experiment with adding our motion-aware formulation to existing image-based models and see substantial improvements, confirming that motion is an important cue to learn objectness. Finally, we show that our learned segmenter, which operates on still images, produces better segmentation results than current methods that use motion information at test time.

2 Related Work

Multi object decomposition. Learning unsupervised object segmentation for static scenes is a well-researched problem in computer vision [3, 6, 7, 8, 9, 10, 12, 13, 19, 30, 32, 40, 41, 50]. These methods aim to decompose the scene into its constituent parts, *e.g.* the different foreground objects and the background. Glimpse-based methods [6, 10, 19, 30] find input patches (glimpses) that contain the objects in the scene. These methods learn object descriptors that encode their properties (*e.g.* position, number, size of the objects) using variational inference, composing glimpses into the final picture. More related to ours are approaches that learn per-pixel object masks [3, 7, 8, 9, 32]. MoNet [3] and IODINE [14] employ multiple encoding-decoding steps to sequentially explain the scene as a collection of regions. Slot Attention [32] uses a multi-step soft clustering-like scheme to find the regions simultaneously. In all cases, learning is posed as an image reconstruction problem. In order to align learnable slots with semantic objects, models have to make efficient use of a limited representation available for each region, such as learning to only explain visual appearance. This principle, however, is difficult to extend to visually complex data [23], and special network architectures.Instead, here we use any standard segmentation architecture which we train to predict regions that are most likely described by rigid motion patterns.

Video-based multi object decomposition. Another line of work extends the unsupervised object decomposition problem to videos [16, 20, 22, 25, 26, 27, 29, 39, 46, 48, 49, 53]. Many of the methods work mainly with simpler datasets [26, 39, 53]. Most of these approaches require sequential frames for training: *e.g.* SCALOR [20] is a glimpse-based method that discovers and propagates objects across frames to learn intermediate object latents. SIMONe [22] processes the whole video at once, learning both temporal scene representation and time-invariant object representations simultaneously. Slot Attention for Video (SAVi) [24] poses the multi-object problem as optical-flow prediction using sequential frames as input. The internal slot-attention mechanism drives the network to learn regions that move in a simple and consistent manner. Different to our work, it does not assume a specific motion model but relies on directly regressing the flow. It is computationally more expensive and struggles when only one or few frames are available.

Unsupervised video object segmentation. Unsupervised video object segmentation (VOS) is a popular problem in computer vision [11, 17, 28, 33, 38, 43, 45, 51, 52], that focuses on extracting the most salient object in the scene. Many of the approaches treat the problem as a motion segmentation task as the background typically shows a dominant motion independent of the salient object. Motion

Grouping [51] employs the Slot Attention architecture to reconstruct optical flow from itself, avoiding appearance information entirely. Another related line of work [5, 35, 36, 44] employ approximate motion models. These approaches rely on a point estimate of the motion model parameters. In contrast, we adopt a more principled probabilistic approach, placing a prior on the motion parameters and integrating them out. To deal with flow outliers that do not conform to a rigid motion model, Mahendran et al. [35] use a histogram matching-based loss and GWM [5] performs non-linear transformation of the flow with limited success. Instead, we model the noise in our formulation directly. Meunier et al. [36] rely on flow as input, limiting the method to videos only.

3 Method

Let a frame $\mathcal{I} \in \mathbb{R}^{3 \times H \times W}$ of a video and its optical flow $\mathbf{f} \in \mathbb{R}^{2 \times H \times W}$ be defined on the $H \times W$ lattice. The optical flow is a local summary of the motion from one frame to the next. We use it to supervise a network Φ that, given the (single) image $\mathcal{I}$ as input, predicts soft assignments of each pixel to up to K different image regions, outputting an $H \times W$ collection of probability vectors $\Phi(\mathcal{I}) \in \hat{\Delta}_K^{H \times W} \subset [0,1]^{K \times H \times W}$, where $\hat{\Delta}_K$ is the $K-1$-dimensional simplex. The quality of the regions is measured based on how likely they contain *flow patterns* typical of the motion of independent objects.

In more detail, we represent the predicted image regions by a hard K-way pixel assignment (mask) $\mathbf{m} \in \Delta_K^{H \times W} \subset \{0,1\}^{K \times H \times W}$, where Δ_K is the space of K-dimensional one-hot vectors. Each mask is a sample from the categorical distribution output by the network, i.e. $\mathbf{m} \sim p_\Phi(\mathbf{m} \mid \mathcal{I}) = \text{Categorical}[\Phi(\mathcal{I})]$. Note that there is one categorical distribution for each pixel and that these are mutually independent.

We then assume that the flow depends only the regions, in the sense that $p_\Phi(\mathbf{f}, \mathbf{m} \mid \mathcal{I}) = p(\mathbf{f} \mid \mathbf{m}) \, p_\Phi(\mathbf{m} \mid \mathcal{I})$, where $p(\mathbf{f} \mid \mathbf{m})$ is a model of the distribution of the flow field given the regions. The likelihood of the modeled Φ is bounded by:

$$\log p_\Phi(\mathbf{f} \mid \mathcal{I}) = \log \mathop{\mathbb{E}}_{\mathbf{m} \sim p_\Phi(\mathbf{m}|\mathcal{I})} [p(\mathbf{f} \mid \mathbf{m})] \geq \mathop{\mathbb{E}}_{\mathbf{m} \sim p_\Phi(\mathbf{m}|\mathcal{I})} [\log p(\mathbf{f} \mid \mathbf{m})].$$

Furthermore, inspired by ELBO, we regularize the model's prediction $p_\Phi(\mathbf{m} \mid \mathcal{I})$ by taking its KL divergence from a uniform prior $p_0(\mathbf{m})$, obtaining the learning objective

$$\mathcal{L}_\beta = \mathop{\mathbb{E}}_{\mathbf{m} \sim p_\Phi(\mathbf{m}|\mathcal{I})} [-\log p(\mathbf{f} \mid \mathbf{m})] + \beta D_{\text{KL}}(p_\Phi(\mathbf{m} \mid \mathcal{I}) \,\|\, p_0(\mathbf{m})). \tag{1}$$

Next, we introduce the closed-form motion model $p(\mathbf{f} \mid \mathbf{m})$ in Eq. (1) and then explain how the Gumbel-Softmax trick can be used to learn the network.

Approximate motion models for optical flow. We now turn to describing the models of motion used in our work, which play a role in assessing the likelihood of optical flow $p(\mathbf{f} \mid \mathbf{m})$. Optical flow measures the coordinate change of pixels between neighboring frames. This change arises due to the motion of the camera and objects. We consider rigid-body motion of some object k.

Let $\mathbf{x}_k^t, \mathbf{y}_k^t \in \mathbb{R}^{n_k}$ be the spatial locations of the pixels belonging to region/object k at time t, where n_k is the number of pixels in the region. For convenience, we stack the coordinates in a single vector $\Omega_k^t = (\mathbf{x}_k^t, \mathbf{y}_k^t) \in \mathbb{R}^{2n_k}$. The pixels comprising this object undergo coordinate change from Ω_k^t to Ω_k^{t+1}, giving rise to the optical flow for this object as $\mathbf{f}_k = \Omega_k^{t+1} - \Omega_k^t$. We assume this underlying 3D rigid-body motion can be approximated using a linear 2D parametric model Π_θ with parameters θ, so that:

$$\Omega_k^{t+1} = \Pi_\theta(\Omega_k^t) + \epsilon, \qquad \mathbf{f}_k = \Pi_\theta(\Omega_k^t) - \Omega_k^t + \epsilon, \tag{2}$$

where ϵ captures the residual error of the approximation. Several forms of models are available (see, *e.g.*, [1, 2] for an overview). Here, we consider two such models: the translation of an object within the camera plane and an affine motion, given respectively by linear functions:

$$\Pi_\theta^{\text{tr}}(\Omega_k^t) = \Omega_k^t + \underbrace{\begin{bmatrix} \mathbf{1}_{n_k} & 0 \\ 0 & \mathbf{1}_{n_k} \end{bmatrix}}_{P_k^{\text{tr}}} \begin{pmatrix} \theta_1 \\ \theta_2 \end{pmatrix}, \quad \Pi_\theta^{\text{aff}}(\Omega_k^t) = \underbrace{\begin{bmatrix} \mathbf{x}_t & \mathbf{y}_t & \mathbf{1}_{n_k} & 0 & 0 & 0 \\ 0 & 0 & 0 & \mathbf{x}_t & \mathbf{y}_t & \mathbf{1}_{n_k} \end{bmatrix}}_{P_k^{\text{aff}}} \begin{pmatrix} \theta_1 \\ \vdots \\ \theta_6 \end{pmatrix}, \tag{3}$$

131 where we use $\mathbf{1}_{n_k}$ is a vector of n_k ones and matrix P_k contains the coefficients of the model.

132 The affine model supports object rotation, scaling and shearing in addition to translation. It is often a
133 sufficient approximation to real-world optical flow, provided the objects are rigid, convex, and mainly
134 rotating in-plane.

135 We can then use the motion equations (2) to construct the distribution $p(\mathbf{f} \mid \mathbf{m})$ by assuming a prior
136 on the motion parameters and by marginalizing over it. Specifically, denote by $\mathbf{m}_k$ the k-th slice
137 of the tensor $\mathbf{m}$ encoding the regions (*i.e.* the mask of the k-th region). We assume that regions are
138 statistically independent and decompose the log-likelihood $p(\mathbf{f} \mid \mathbf{m})$ as:

$$\log p(\mathbf{f} \mid \mathbf{m}) = \sum_k \log p(\mathbf{f}_k \mid \mathbf{m}_k) = \sum_k \int \log p(\mathbf{f}_k, \theta_k \mid \mathbf{m}_k) d\theta_k. \tag{4}$$

139 Assuming that each object has i.i.d. parameters θ_k with a Gaussian prior $\mathcal{N}(\theta; \mu, \Sigma)$, and assuming ϵ
140 is a zero-mean noise with variance σ^2, Eq. (2) gives marginal optical flow likelihood for segment k:

$$p(\mathbf{f}_k \mid \mathbf{m}_k) = \mathcal{N}(\mathbf{f}_k; \Pi_\mu(\Omega_k) - \Omega_k, P_k \Sigma P_k^\top + \sigma^2 I). \tag{5}$$

141 A practical issue with Eq. (5) is that, if segment k contains $n_k = \sum_i (\mathbf{m}_k)_i$ pixels, then the covariance
142 matrix $P_k \Sigma P_k^\top + \sigma^2 I$ has dimension $2n_k \times 2n_k$. Inverting such a matrix in the evaluation of the
143 Gaussian log-density is very slow except for very small regions. Furthermore, it is not obvious how
144 to relax Eq. (4) to support gradient-based learning, *e.g.* through the Gumbel-Softmax approximation.
145 We solve these problems in the next section.

146 **Expressions for the likelihood.** We now derive expressions for the Eq. (5) which are efficient
147 and that lead to a natural relaxation for use in the Gumbel-Softmax sampling. Given the definitions
148 $\mathbf{F}_k = \mathbf{f}_k - \Pi_\mu(\Omega_k) + \Omega_k^t$ and $\Lambda = \Sigma^{-1}$, we can rewrite Eq. (5) as:

$$p(\mathbf{f}_k \mid \mathbf{m}_k) = (2\pi\sigma^2)^{-n_k} \left(\frac{\det S_k}{\det \Lambda} \right)^{-\frac{1}{2}} e^{-\frac{d^2}{2\sigma^2}}, \quad d^2 = \mathbf{F}_k^\top \mathbf{F}_k - \frac{1}{\sigma^2} \mathbf{F}_k^\top P_k S_k^{-1} P_k^\top \mathbf{F}_k, \tag{6}$$

149 where $S_k = 1/\sigma^2 P_k^\top P_k + \Lambda$. The significant advantage of this form is that it involves the computation
150 of the inverse and determinant of matrix S_k, whose size is only 2×2 (for the translation model) or
151 6×6 (for the affine one), instead of the much larger $2n_k \times 2n_k$.

152 We can more explicitly introduce the dependency on the region assignments $\mathbf{m}$ by defining selector
153 matrices $R_k \in \{0,1\}^{2n_k \times 2n}$ (with $n = \sum_k n_k = HW$) that extract the $\mathbf{x}$ and $\mathbf{y}$ coordinates of
154 the pixels that belong to the corresponding region, in the sense that $\Omega_k = R_k \Omega$. We can write
155 $\mathbf{F}_k = R_k \mathbf{F}$ and $P_k = R_k P$. Furthermore, the product of selectors $L_k = R_k^\top R_k \in \{0,1\}^{2n \times 2n}$ can
156 be written directly as a function of the assignment $\mathbf{m}$ as $L_k(\mathbf{m}) = \operatorname{diag}(\mathbf{m}_k, \mathbf{m}_k)$. Plugging these
157 back in Eq. (6), we obtain expressions involving L_k only:

$$n_k = \frac{1}{2} |L_k|_1, \quad S_k = \frac{1}{\sigma^2} P^\top L_k P + \Lambda, \quad d^2 = \mathbf{F}^\top L_k \mathbf{F} - \frac{1}{\sigma^2} (\mathbf{F}^\top L_k P) S_k^{-1} (P^\top L_k \mathbf{F}). \tag{7}$$

158 **Translation-only model.** Further simplifications are possible for specific models. For instance, for
159 the translation-only model, assuming that $\Lambda = \operatorname{diag}(1/\tau^2, 1/\tau^2)$ then $S_k = \operatorname{diag}(n_k + 1/\tau^2, n_k + 1/\tau^2)$
160 $1/\tau^2)$ and, after some calculations, we obtain the expression:

$$-\log p(\mathbf{f} \mid \mathbf{m}) = n \log 2\pi\sigma^2 + \sum_k \log \frac{n_k + \frac{\sigma^2}{\tau^2}}{\frac{\sigma^2}{\tau^2}} + \frac{1}{2\sigma^2} \mathbf{F}^\top \left(I - \sum_k \frac{1}{n_k + \frac{\sigma^2}{\tau^2}} \begin{bmatrix} \mathbf{m}_k \mathbf{m}_k^\top & \\ & \mathbf{m}_k \mathbf{m}_k^\top \end{bmatrix} \right) \mathbf{F}$$

161 where I is the identity matrix.

162 **Affine model.** For the affine model, the expression for $-\log p(\mathbf{f} \mid \mathbf{m})$ does not simplify as much.
163 Still, by exploiting the structure of matrix P_k^{aff}, we can reduce the calculations to the computation
164 of inverse and determinant of small 3×3 matrices, which can be implemented efficiently in closed
165 form. We leave derivation to the supplementary material. Unless otherwise stated, the mean vector is
166 set to $\mu = (1\ 0\ 0\ 0\ 1\ 0)^\top$ centering the prior on the no-motion point.

Figure 1: Example images and optical flow of MOVINGCLEVR and MOVINGCLEVRTEX datasets, which extend CLEVR and CLEVRTEX respectively to short videos based on physics simulation. Note that only a subset of objects is in motion in each frame.

Gumbel-softmax. In order to learn the network using gradient descent, we need a differentiable version of loss (1). To do so, we use the re-parametrizable Gumbel-softmax relaxation [18, 34]. The Gumbel-softmax relaxation replaces categorical samples $\mathbf{m} \in \Delta_K^{H \times W}$ from the distribution $p_\Phi(\mathbf{m} \mid \mathcal{I}) = \mathrm{Categorical}[\Phi(\mathcal{I})]$ with continuous samples $\hat{\mathbf{m}} \in \hat{\Delta}_K^{H \times W}$ from the distribution $\mathrm{GumbelSoftmax}[\Phi(\mathcal{I})]$. We take $N = 10$ samples from this distribution to evaluate the expected negative log-likelihood, further reducing variance. Note that evaluating Eq. (1) at samples $\hat{\mathbf{m}}$ requires to relax the factor $p(\mathbf{f} \mid \mathbf{m})$. For this, we simply replace $\hat{\mathbf{m}}$ for $\mathbf{m}$ in the the expression found in Eq. (7) for the loss, leading to differentiable quantities.

Post-processing. Our loss (Eq. (5)) naturally encourages the model to form larger regions to explain parts of the scene that move in a consistent (under the assumed prior) manner. However, we find that this can also lead to the model grouping together objects that only coincidentally move together (*e.g.* all objects mostly falling due to gravity in one of the datasets). Furthermore, optical flow is ambiguous around object edges and occlusions. To address both the object grouping and occlusion boundary issue, we use a simple post-processing step. We isolate connected components in the model output, selecting the K largest masks, discarding any that are smaller than 0.1% of image area, and combining the left-over and discarded ones with the largest mask overall.

4 Experiments

Our method sits in between image-based and video-based segmentation approaches, because it uses videos for supervision, but trains an image segmentation network that operates on still images only. We thus evaluate several settings. Firstly, we evaluate how well motion can be used to supervise an object instance segmenter that operates on still images. Secondly, we compare such a segmenter to state-of-the-art object segmentation methods that use motion at test time (and are thus advantaged compared to our model). Finally, we conduct further analysis to validate our modelling assumptions and the model's reliance on the quality of the optical flow used for supervision.

4.1 Experimental setup

Datasets. We evaluate our method on video and still image datasets. For video-based data, we use the Multi-Object Video (MOVi) datasets which have been recently released as part of Kubric [15]. Specifically, we employ MOVi-A and MOVi-C. MOVi-A is similar to CLEVR [21] in terms of visual complexity and features videos of 3–10 falling objects on a simple, gray background. MOVi-C is significantly more challenging, as it features scanned, textured, common objects on top of backgrounds textured using HDR images. We use a resolution of 128×128 pixels and the ground truth optical flow provided with the datasets.

To evaluate our method on still images, we use CLEVR [21] and CLEVRTEX [23] benchmark suites. Both consist of images depicting 3-10 objects. CLEVR images are simpler, featuring colored metallic or rubbery appearances. CLEVRTEX features more diverse objects with complex textures applied. We also use OOD and CAMO testing sets from CLEVRTEX benchmark. OOD contains out-of-distribution shapes and textures. CAMO has camouflaged objects where the same texture is sampled for objects and the background.

Since our method requires optical flow during training, we extend the implementation of [23] to generate video datasets of CLEVR and CLEVRTEX scenes, where a *subset* of objects contained

Table 1: Benchmark results on CLEVR, CLEVRTEX, CAMO, and OOD comparing FG-ARI and mIoU metrics. Results are a mean of 3 seed ($\pm\sigma$). Methods above the line are trained on single images, while methods below train on videos. [†] – indicates post-processing.

Model	CLEVR		CLEVRTEX		OOD		CAMO	
	FG-ARI↑	mIoU↑	FG-ARI↑	mIoU↑	FG-ARI↑	mIoU↑	FG-ARI↑	mIoU↑
SPAIR [6]	77.13± 1.92	65.95± 4.02	0.00± 0.00	0.00±0.00	0.00± 0.00	0.00±0.00	0.00± 0.00	0.00±0.00
SPAIR[†]	77.05± 1.96	66.87± 9.65	0.00± 0.00	0.00±0.00	0.00± 0.00	0.00±0.00	0.00± 0.00	0.00±0.00
SPACE [30]	22.75±14.04	26.31±12.93	17.53± 4.13	9.14±3.46	12.71± 3.44	6.87±3.32	10.55± 2.09	8.67±3.50
SPACE[†]	22.74±14.03	27.00±13.69	17.52± 4.12	9.68±4.10	12.71± 3.44	7.20±3.75	10.54± 2.08	9.25±3.95
GenV2 [9]	57.90±20.38	9.48± 0.55	31.19±12.41	7.93±1.53	29.04±11.23	8.74±1.64	29.60±12.84	7.49±1.67
GenV2[†]	57.78±21.12	10.76± 1.39	30.55±14.27	9.04±0.63	28.41±13.20	9.96±0.70	29.19±14.55	8.40±1.00
MN [40]	72.12± 0.64	56.81±0.40	38.31± 0.70	10.46±0.10	37.29± 1.04	12.13±0.19	31.52± 0.87	8.79±0.15
MN[†]	72.08± 0.62	57.61±0.40	38.34± 0.73	10.34±0.12	37.28± 1.07	11.97±0.21	31.54± 0.87	8.77±0.18
MONet [3]	54.47±11.41	30.66±14.87	36.66± 0.87	19.78±1.02	32.97± 1.00	19.30±0.37	12.44± 0.73	10.52±0.38
MONet[†]	61.36± 7.33	45.61± 4.80	35.64± 1.17	23.59±0.29	31.51± 1.46	23.04±0.52	9.94± 0.50	11.31±0.30
SA [32]	**95.89**± 2.37	36.61±24.83	62.40± 2.23	22.58±2.07	58.45± 1.87	20.98±1.59	57.54± 1.01	19.83±1.41
SA[†]	94.88± 1.67	37.68±26.56	61.60± 2.29	21.96±1.79	57.41± 1.92	20.60±1.45	56.85± 1.12	19.42±1.42
IODINE [14]	93.81± 0.76	45.14±17.85	59.52± 2.20	29.17±0.75	53.20± 2.55	26.28±0.85	36.31± 2.57	17.52±0.75
IODINE[†]	93.68± 0.83	44.20±18.67	60.63± 2.50	29.40±1.10	54.92± 2.24	27.96±0.81	38.29± 1.40	18.87±0.52
eMORL [7]	93.25± 3.24	50.19±22.56	55.62± 2.12	30.17±2.60	49.21± 2.69	25.03±1.99	37.66± 8.41	19.13±4.88
eMORL[†]	93.09± 2.68	49.28±24.28	58.59± 1.96	31.64±2.22	51.97± 2.44	26.91±1.69	43.83± 7.34	22.40±4.35
DTI-S [37]	89.54± 1.44	48.74± 2.17	79.90± 1.37	33.79±1.30	73.67± 0.98	32.55±1.08	**72.90**± 1.89	27.54±1.55
DTI-S[†]	89.86± 1.78	53.38± 3.51	79.86± 1.36	32.20±1.49	73.60± 0.97	30.74±1.22	72.89± 1.88	26.30±1.57
GNM [19]	65.05± 4.19	59.92± 3.72	53.37± 0.67	42.25±0.18	48.43± 0.86	40.84±0.30	15.73± 0.89	17.56±0.74
GNM[†]	65.67± 4.23	63.38± 3.76	53.38± 0.67	44.30±0.19	48.44± 0.86	42.87±0.28	15.72± 0.89	18.53±0.75
SAVi [24]	—	—	49.54	31.88	42.68	30.31	42.67	29.60
Ours	86.84± 2.46	60.14± 3.32	85.05± 0.60	49.49±0.34	73.22± 0.93	43.16±0.64	50.19± 2.02	30.76±0.82
Ours[†]	93.19± 1.56	**80.21**± 4.43	**88.90**± 0.17	**69.29**±1.19	**77.15**± 0.49	**53.53**±0.83	60.44± 1.52	**42.65**±1.33

in each scene are sliding, rolling and colliding based on a physics simulation (Fig. 1). To train our model, we generate 10k sequences for MOVINGCLEVRTEX and 5k for MOVINGCLEVR, where we retain 1000 and 500 sequences, respectively, for validation. Each sequence is 5 frames long. We will publish both datasets, their annotations and the code to generate them. All dataset details can be found in the appendix. The evaluation is performed on the original CLEVR and CLEVRTEX test sets.

Metrics. Following prior work [23, 24], we measure performance using two metrics. FG-ARI is the Adjusted Rand Index measured on foreground pixels only (selected using the ground-truth segmentation). Mean Intersection-over-Union (mIoU), is measured through Hungarian matching and averaged across the number of predicted or ground truth components, whichever is higher. For videos, we calculate the metrics per-frame.

Network architecture. Our method can employ any image segmentation network architecture and train from scratch. Unless otherwise specified, we use Mask2Former [4], using only its semantic segmentation, with Swin-tiny transformer [31] as the backbone. We use 11 transformer queries which become $K = 11$ slots in our experiments. The model takes approximately 48h to train on a single A30 24GB GPU.[1] We specify all training details and hyperparameters in the supplementary material.

4.2 Unsupervised multi-object segmentation in images

We evaluate our method on CLEVR [21] and CLEVRTEX [23] suite of benchmarks and compare with appearance-based image models. Table 1 shows results. Our method shows strong performance on CLEVR achieving highest overall mIoU and competitive FG-ARI. While other methods perform a lot worse in the visually more complex CLEVRTEX setting, our model achieves high mIoU even without our post-processing function, showing the strong inductive bias that motion information during training provides. We additionally note that, despite relying only on discriminative segmentation network, we similarly maintain lead in the OOD and challenging CAMO settings.

As shown in Fig. 2, post-processing by separating connected components helps by suppressing boundary segments that tend to group difficult occlusion boundaries, and by separating objects that might be assigned to the same component. For a fairer comparison, we also test if this post-processing improves the results of other methods but only obtain mixed results.

---

[1]Approx. total compute in this paper: 52 GPU days for our models, 110 GPU days for comparisons.

Figure 2: Example output on CLEVR and CLEVRTEX benchmarks. Our model is able to segment simple and visually complex scenes. Occasional mistakes around object boundaries and assignment of objects to the same component is addressed by post-processing. † – indicates post-processing.

Table 2: Segmentation results on MOVi-A and MOVi-C datasets. Mean $\pm$ standard error (5 seeds). We calculate metric for each frame. All values in %. † – indicates post-processing.

	MOVi-A		MOVi-C	
Model	FG-ARI↑	mIoU↑	FG-ARI↑	mIoU↑
GWM [5]	54.00	42.23	36.35	25.39
SCALOR [20]	59.57	44.41	40.43	22.54
SAVi [24]	**88.30**	62.69	43.26	31.92
Ours	81.19±0.80	55.64±1.17	**59.18**±0.45	33.96±0.14
Ours†	83.15±0.40	**72.82**±0.43	59.17±0.46	**36.06**±0.24

Note that in this setting compared to the other models in Table 1, our model is advantaged as it can observe (through the loss) the optical flow of the training scenes. Due to this, we also train the optical flow-based, unconditional SAVi [24] model. We find that despite having access to motion information during training, SAVi does not surpass appearance-only models, likely due to only having access to single frame during testing. We do find that learning from motion information is especially helpful for CAMO, where the objects are camouflaged.

4.3 Unsupervised multi-object segmentation in video

We now evaluate our approach for video segmentation, where motion is available at test time. We report the performance of our method in Table 2 compared to video-based models: SCALOR [20], *unconditional* SAVi [24], and GWM [5]; the latter two also use optical flow supervision. It is important to note that SAVi and SCALOR make predictions jointly over all frames of a video, that allows them to actually see the objects in motion at test time. Despite the comparison being unfair to our approach, which operates on a single frame at a time, we achieve competitive results. On the visually simpler MOVi-A, our method has more than 10% lead over SAVi in mIoU, however performs worse in terms of FG-ARI. Fig. 3 compares the models qualitatively, showcasing that object boundaries are overall more refined for our model, which explains the higher mIoU. On the more complex MOVi-C, our model shows strong performance, outperforming prior work on both metrics.

Figure 3: Qualitative comparison on MOVi-A and MOVi-C. Our method performs consistently well compared to other methods. GWM suffers from oversegmentation where SCALOR has undersegmentation issue. Among the related methods, SCALOR fails to discover all the objects and SAVi's object boundaries are coarser [†]– indicates post-processing.

Figure 4: Failure cases on MOVi-A and MOVi-C. Our method has difficulty with objects that typically exhibit complex motion. It results in an over-segmentation of the object. Due to inherently imprecise optical flow near the boundaries our method also has a tendency to segment boundary pixels into a separate mask, which we fix with our post-processing step. [†]– indicates post-processing.

4.4 Model ablations

Optical flow. In Table 3a we replace the ground-truth optical flow used so far with the one estimated by SMURF [42]. The additional noise impacts our model's accuracy, as evidenced by the significant drop in mIoU (but comparable FG-ARI scores).

Motion model. In Table 3b we show that using the more complex affine motion model significantly outperforms modeling translations only.

Motion awareness. We investigate the effect of using our objective in combination with existing appearance-based methods. To further evaluate our formulation and its advantages when motion

Table 3: Model ablations. (3a) replacing flow supervision with an unsupervised flow method, (3b) compares a translation-only with the affine flow model, and (3c) adds our motion-based formulation to an appearance-only model. All models with post-processing applied.

(a) Choice of Optical Flow Method

	MOVi-A		MOVi-C	
Optical Flow	**FG-ARI↑**	**mIoU↑**	**FG-ARI↑**	**mIoU↑**
SMURF [42]	80.17	26.3	61.21	28.77
Ground Truth	83.48	72.61	58.59	35.67

(b) Choice of Motion Model

	MOVi-A		MOVi-C	
Motion Mdl.	**FG-ARI↑**	**mIoU↑**	**FG-ARI↑**	**mIoU↑**
Translation	66.03	59.94	39.77	32.23
Affine	83.48	72.61	58.59	35.67

(c) Adding motion awareness to an appearance-only model

	CLEVRTEX		OOD		CAMO	
Model	**FG-ARI↑**	**mIoU↑**	**FG-ARI↑**	**mIoU↑**	**FG-ARI↑**	**mIoU↑**
GNM [19]	53.38	44.30	48.44	42.87	15.72	18.53
GNM+Our Loss	63.84	55.26	59.01	48.65	51.00	47.63

information becomes available during training, and to decouple the performance from the choice of architecture in our experiments, we employ it on top of GNM [19] with no other modifications. As in Table 1, we train GNM with our loss on video data (MOVINGCLEVRTEX) and evaluate on the corresponding image test sets of the CLEVRTEX suite, reporting the comparison to the original method in Table 3c. We find that using our loss further improves performance the appearance method, especially in the challenging CAMO setting.

4.5 Limitations

Sometimes motion is insufficient to distinguish different objects, for instance because they do not move or because they move similarly. In principle, this should not matter if sufficient motion diversity is observed in the training data as a whole; in practice, our model occasionally merges different object at test time, which we address partly in post-processing. Further improvements could be obtained by choosing a more informative prior $p_0(\mathbf{m})$ in Eq. (1), capturing other desirable properties of objects, such as compactness and connectedness.

Figure 4 shows some failure cases where the affine motion model struggles to capture strong perspective effects caused by non-smooth depth changes in the object geometry. This could be addressed by modeling the object geometry (depth) and the ensuing complex flow patterns or, alternatively, by using a hierarchical segmentation model that can account for geometric discontinuities and self-occlusions.

5 Conclusions

We have presented a method that bridges the gap between image-based and video-based scene decomposition, in that it requires only a single image as input, yet exploits motion cues available in videos during training. In comparison to prior work on image-based multi-object segmentation, our approach shows that motion provides useful objectness cues, especially as the visual complexity of a scene increases. Different from video-based approaches, however, our model operates on still images and does not rely on motion to detect or refine objects, which makes it more generally applicable. Finally, we deviate from the common objective of image or flow *reconstruction* and, instead, model the problem by only predicting regions likely to contain affine flow patterns. This does not require a specialized architecture, thus any segmentation network is suitable for this task. Our approach shows strong performance on multiple image and video benchmarks validating the paradigm of training image models using motion.

Broader impact. Our work introduces a method for unsupervised multi-object segmentation by exploiting the law of common fate in a principled way. The work is evaluated on existing and new 3D simulated datasets of simple objects that do not contain people or personal information. We build on top of open source projects, respecting licenses and will release all code, trained models and datasets. Currently, the application of this approach is limited to simulated imagery. Thus, the immediate broader impact of our work in real-world scenarios, beyond the research community, is also limited.

References

[1] Gilad Adiv. Determining three-dimensional motion and structure from optical flow generated by several moving objects. *IEEE transactions on pattern analysis and machine intelligence*, (4):384–401, 1985.

[2] James R Bergen, Patrick Anandan, Keith J Hanna, and Rajesh Hingorani. Hierarchical model-based motion estimation. In *European conference on computer vision*, pages 237–252. Springer, 1992.

[3] Christopher P Burgess, Loic Matthey, Nicholas Watters, Rishabh Kabra, Irina Higgins, Matt Botvinick, and Alexander Lerchner. Monet: Unsupervised scene decomposition and representation. *arXiv preprint arXiv:1901.11390*, 2019.

[4] Bowen Cheng, Ishan Misra, Alexander G. Schwing, Alexander Kirillov, and Rohit Girdhar. Masked-attention mask transformer for universal image segmentation. 2022.

[5] Subhabrata Choudhury, Laurynas Karazija, Iro Laina, Andrea Vedaldi, and Christian Rupprecht. Guess what moves: Unsupervised video and image segmentation by anticipating motion. *arXiv preprint arXiv:2205.07844*, 2022.

[6] Eric Crawford and Joelle Pineau. Spatially invariant unsupervised object detection with convolutional neural networks. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 3412–3420, 2019.

[7] Patrick Emami, Pan He, Sanjay Ranka, and Anand Rangarajan. Efficient iterative amortized inference for learning symmetric and disentangled multi-object representations. In *Proceedings of the 38th International Conference on Machine Learning*, pages 2970–2981. PMLR, 2021.

[8] Martin Engelcke, Adam R Kosiorek, Oiwi Parker Jones, and Ingmar Posner. Genesis: Generative scene inference and sampling with object-centric latent representations. In *International Conference on Learning Representations*, 2020.

[9] Martin Engelcke, Oiwi Parker Jones, and Ingmar Posner. Genesis-v2: Inferring unordered object representations without iterative refinement. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[10] S. M. Ali Eslami, Nicolas Heess, Theophane Weber, Yuval Tassa, David Szepesvari, Koray Kavukcuoglu, and Geoffrey E. Hinton. Attend, infer, repeat: Fast scene understanding with generative models. In *Proceedings of the 30th International Conference on Neural Information Processing Systems*, page 3233–3241, 2016.

[11] Alon Faktor and Michal Irani. Video segmentation by non-local consensus voting. In *Proceedings of the British Machine Vision Conference*. BMVA Press, 2014.

[12] Klaus Greff, Rupesh Kumar Srivastava, and Jürgen Schmidhuber. Binding via reconstruction clustering. *ArXiv*, abs/1511.06418, 2015.

[13] Klaus Greff, Antti Rasmus, Mathias Berglund, Tele Hao, Harri Valpola, and Jürgen Schmidhuber. Tagger: Deep unsupervised perceptual grouping. In *Advances in Neural Information Processing Systems*, pages 4484–4492, 2016.

[14] Klaus Greff, Raphaël Lopez Kaufman, Rishabh Kabra, Nick Watters, Christopher Burgess, Daniel Zoran, Loic Matthey, Matthew Botvinick, and Alexander Lerchner. Multi-object representation learning with iterative variational inference. In *International Conference on Machine Learning*, pages 2424–2433. PMLR, 2019.

[15] Klaus Greff, Francois Belletti, Lucas Beyer, Carl Doersch, Yilun Du, Daniel Duckworth, David J Fleet, Dan Gnanapragasam, Florian Golemo, Charles Herrmann, Thomas Kipf, Abhijit Kundu, Dmitry Lagun, Issam Laradji, Hsueh-Ti (Derek) Liu, Henning Meyer, Yishu Miao, Derek Nowrouzezahrai, Cengiz Oztireli, Etienne Pot, Noha Radwan, Daniel Rebain, Sara Sabour, Mehdi S. M. Sajjadi, Matan Sela, Vincent Sitzmann, Austin Stone, Deqing Sun, Suhani Vora, Ziyu Wang, Tianhao Wu, Kwang Moo Yi, Fangcheng Zhong, and Andrea Tagliasacchi. Kubric: a scalable dataset generator. 2022.

[16] Zhen He, Jian Li, Daxue Liu, Hangen He, and David Barber. Tracking by animation: Unsupervised learning of multi-object attentive trackers. *2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1318–1327, 2019.

[17] Suyog Jain, Bo Xiong, and Kristen Grauman. Fusionseg: Learning to combine motion and appearance for fully automatic segmention of generic objects in videos. *arXiv preprint arXiv:1701.05384*, 2017.

[18] Eric Jang, Shixiang Gu, and Ben Poole. Categorical reparameterization with gumbel-softmax. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017.

[19] Jindong Jiang and Sungjin Ahn. Generative neurosymbolic machines. In *Advances in Neural Information Processing Systems*, volume 33, pages 12572–12582, 2020.

[20] Jindong Jiang, Sepehr Janghorbani, Gerard De Melo, and Sungjin Ahn. Scalor: Generative world models with scalable object representations. In *International Conference on Learning Representations*, 2020.

[21] Justin Johnson, Bharath Hariharan, Laurens Van Der Maaten, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. CLEVR: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 2901–2910, 2017.

[22] Rishabh Kabra, Daniel Zoran, Goker Erdogan, Loïc Matthey, Antonia Creswell, Matthew M. Botvinick, Alexander Lerchner, and Christopher P. Burgess. Simone: View-invariant, temporally-abstracted object representations via unsupervised video decomposition. In *NeurIPS*, 2021.

[23] Laurynas Karazija, Iro Laina, and Christian Rupprecht. Clevrtex: A texture-rich benchmark for unsupervised multi-object segmentation. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 2)*, 2021.

[24] Thomas Kipf, Gamaleldin Fathy Elsayed, Aravindh Mahendran, Austin Stone, Sara Sabour, Georg Heigold, Rico Jonschkowski, Alexey Dosovitskiy, and Klaus Greff. Conditional object-centric learning from video. In *International Conference on Learning Representations*, 2022.

[25] Adam R Kosiorek, Hyunjik Kim, Ingmar Posner, and Yee Whye Teh. Sequential attend, infer, repeat: Generative modelling of moving objects. page 8615–8625, 2018.

[26] Jannik Kossen, Karl Stelzner, Marcel Hussing, Claas Voelcker, and Kristian Kersting. Structured object-aware physics prediction for video modeling and planning. In *Proceedings of the International Conference on Learning Representations*, 2020.

[27] Nanbo Li, Cian Eastwood, and Robert B. Fisher. Learning object-centric representations of multi-object scenes from multiple views. *ArXiv*, abs/2111.07117, 2020.

[28] Siyang Li, Bryan Seybold, Alexey Vorobyov, Alireza Fathi, Qin Huang, and C-C Jay Kuo. Instance embedding transfer to unsupervised video object segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 6526–6535, 2018.

[29] Zhixuan Lin, Yi-Fu Wu, Skand Vishwanath Peri, Bofeng Fu, Jindong Jiang, and Sungjin Ahn. Improving generative imagination in object-centric world models. In *ICML*, 2020.

[30] Zhixuan Lin, Yi-Fu Wu, Skand Vishwanath Peri, Weihao Sun, Gautam Singh, Fei Deng, Jindong Jiang, and Sungjin Ahn. SPACE: Unsupervised object-oriented scene representation via spatial attention and decomposition. In *International Conference on Learning Representations*, 2020.

[31] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10012–10022, 2021.

[32] Francesco Locatello, Dirk Weissenborn, Thomas Unterthiner, Aravindh Mahendran, Georg Heigold, Jakob Uszkoreit, Alexey Dosovitskiy, and Thomas Kipf. Object-centric learning with slot attention. In *Advances in Neural Information Processing Systems*, volume 33, pages 11525–11538, 2020.

[33] Xiankai Lu, Wenguan Wang, Chao Ma, Jianbing Shen, Ling Shao, and Fatih Porikli. See more, know more: Unsupervised video object segmentation with co-attention siamese networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3623–3632, 2019.

[34] Chris J Maddison, Andriy Mnih, and Yee Whye Teh. The concrete distribution: A continuous relaxation of discrete random variables. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017.

[35] Aravindh Mahendran, James Thewlis, and Andrea Vedaldi. Self-supervised segmentation by grouping optical-flow. In *Proceedings of the European Conference on Computer Vision (ECCV) Workshops*, September 2018.

[36] Etienne Meunier, Anaïs Badoual, and Patrick Bouthemy. Em-driven unsupervised learning for efficient motion segmentation. *CoRR*, abs/2201.02074, 2022.

[37] Tom Monnier, Elliot Vincent, Jean Ponce, and Mathieu Aubry. Unsupervised layered image decomposition into object prototypes. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 8640–8650, 2021.

[38] Anestis Papazoglou and Vittorio Ferrari. Fast object segmentation in unconstrained video. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, December 2013.

[39] Gautam Singh, Skand Vishwanath Peri, Junghyun Kim, Hyunseok Kim, and Sungjin Ahn. Structured world belief for reinforcement learning in pomdp. In *ICML*, 2021.

[40] Dmitriy Smirnov, Michael Gharbi, Matthew Fisher, Vitor Guizilini, Alexei A Efros, and Justin Solomon. Marionette: Self-supervised sprite learning. In *Advances in Neural Information Processing Systems*, volume 34, 2021.

[41] Karl Stelzner, Robert Peharz, and Kristian Kersting. Faster attend-infer-repeat with tractable probabilistic models. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 5966–5975. PMLR, 09–15 Jun 2019.

[42] Austin Stone, Daniel Maurer, Alper Ayvaci, Anelia Angelova, and Rico Jonschkowski. Smurf: Self-teaching multi-frame unsupervised raft with full-image warping. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3886–3895, 2021.

[43] Pavel Tokmakov, Cordelia Schmid, and Karteek Alahari. Learning to segment moving objects. *Int. J. Comput. Vision*, 127(3):282–301, mar 2019. ISSN 0920-5691.

[44] Philip H. S. Torr. Geometric motion segmentation and model selection. *Philosophical Transactions of the Royal Society of London. Series A: Mathematical, Physical and Engineering Sciences*, 356:1321 – 1340, 1998.

[45] Yi-Hsuan Tsai, Ming-Hsuan Yang, and Michael J. Black. Video segmentation via object flow. In *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3899–3908, 2016.

[46] Sjoerd Van Steenkiste, Michael Chang, Klaus Greff, and Jürgen Schmidhuber. Relational neural expectation maximization: Unsupervised discovery of objects and their interactions. *arXiv preprint arXiv:1802.10353*, 2018.

[47] Rishi Veerapaneni, John D Co-Reyes, Michael Chang, Michael Janner, Chelsea Finn, Jiajun Wu, Joshua Tenenbaum, and Sergey Levine. Entity abstraction in visual model-based reinforcement learning. In *Conference on Robot Learning*, pages 1439–1456. PMLR, 2020.

[48] Marissa A. Weis, Kashyap Chitta, Yash Sharma, Wieland Brendel, Matthias Bethge, Andreas Geiger, and Alexander S. Ecker. Benchmarking unsupervised object representations for video sequences. *Journal of Machine Learning Research*, 22(183):1–61, 2021.

[49] Yizhe Wu, Oiwi Parker Jones, Martin Engelcke, and Ingmar Posner. Apex: Unsupervised, object-centric scene segmentation and tracking for robot manipulation. *2021 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 3375–3382, 2021.

[50] Kun Xu, Chongxuan Li, Jun Zhu, and Bo Zhang. *Multi-Object Generation with Amortized Structural Regularization*. Curran Associates Inc., Red Hook, NY, USA, 2019.

[51] Charig Yang, Hala Lamdouar, Erika Lu, Andrew Zisserman, and Weidi Xie. Self-supervised video object segmentation by motion grouping. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 7177–7188, 2021.

[52] Yanchao Yang, Antonio Loquercio, Davide Scaramuzza, and Stefano Soatto. Unsupervised moving object detection via contextual information separation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2019.

[53] Polina Zablotskaia, Edoardo A. Dominici, Leonid Sigal, and Andreas M. Lehrmann. Provide: a probabilistic framework for unsupervised video decomposition. In Cassio de Campos and Marloes H. Maathuis, editors, *Proceedings of the Thirty-Seventh Conference on Uncertainty in Artificial Intelligence*, volume 161 of *Proceedings of Machine Learning Research*, pages 2019–2028. PMLR, 27–30 Jul 2021.