Bootstrap Your Own Skills: Learning to Solve New Tasks with Large Language Model Guidance

Abstract: We propose BOSS, an approach that automatically learns to solve new long-horizon, complex, and meaningful tasks by growing a learned skill library with minimal supervision. Prior work in reinforcement learning require expert supervision, in the form of demonstrations or rich reward functions, to learn long-horizon tasks. Instead, our approach BOSS (**BO**ot**S**trapping your own **S**kills) learns to accomplish new tasks by performing "skill bootstrapping," where an agent with a set of primitive skills interacts with the environment to practice new skills without receiving reward feedback for tasks outside of the initial skill set. This bootstrapping phase is guided by large language models (LLMs) that inform the agent of meaningful skills to chain together. Through this process, BOSS builds a wide range of complex and useful behaviors from a basic set of primitive skills. We demonstrate through experiments in realistic household environments that agents trained with our LLM-guided bootstrapping procedure outperform those trained with naïve bootstrapping as well as prior unsupervised skill acquisition methods on zero-shot execution of unseen, long-horizon tasks in new environments. Supplementary videos at https://sites.google.com/view/boss-corl-2023.

1 Introduction

Robot learning aims to equip robots with the capability of learning and adapting to novel scenarios. Popular learning approaches like reinforcement learning (RL) excel at learning short-horizon tasks such as pick-and-place [1, 2, 3], but they require dense supervisions (e.g., demonstrations [4, 5, 6, 7] or frequent reward feedback [8, 9, 10]) to acquire long-horizon skills.

In contrast, humans can learn complex tasks with much less supervision—take, for example, the process of learning to play tennis: we may initially practice individual skills like forehand and backhand returns under close supervision of a coach, analogous to RL agents practicing simple pick-place skills using demonstrations or dense rewards. Yet importantly, in between coaching sessions, tennis players return to the tennis court and *practice* to combine the acquired basic skills into long-horizon gameplay without supervision from the coach. This allows them to develop a rich repertoire of tennis-playing skills independently and perform better during their next match.

Can we enable agents to similarly practice and expand their skills without close human supervision? We introduce BOSS (**BO**ot**S**trapping your own **S**kills), a framework for learning a rich repertoire of long-horizon skills with minimal human supervision. Starting from a base set of acquired primitive skills, BOSS performs a *skill bootstrapping phase* in which it progressively grows its skill repertoire by practicing to chain skills into longer-horizon behaviors. BOSS enables us to train generalist agents, starting from a repertoire of only tens of skills, to perform hundreds of long-horizon tasks without additional human supervision.

A crucial question during practice is which skills are meaningful to chain together: randomly chaining tennis moves does not lead to meaningful gameplay; similarly, random chains of pick-place movements do not solve meaningful household tasks. Thus, in BOSS we proposed to leverage the rich knowledge captured in large language models (LLMs) to guide skill chaining: given the chain

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: BOSS learns to execute a large set of useful, long-horizon skills with minimal supervision by performing LLM-guided *skill bootstrapping*. **(a):** The agent starts with an initial skill library. During bootstrapping, it practices chaining skills into new long-horizon behaviors using guidance from an LLM. The collected experience is used to update the policy. Newly discovered skill chains are summarized into with an LLM and added as new skills into the library for further bootstrapping. Thus, the agent's skill repertoire grows over time. **(b):** After bootstrapping, we condition the policy on novel instructions and show execution in the environment using the bootstrapped skill repertoire.

of executed skills so far, the LLM predicts a distribution over meaningful next skills to sample. Importantly, in contrast to existing approaches that leverage the knowledge captured in LLMs for long-horizon task planning [11, 12, 13, 14], BOSS can use unsupervised environment interactions to *practice* how to chain skills into long-horizon task executions; this practice is crucial especially if the target environment differs from the ones used to train the base skill set. This results in a more robust policy that can compensate for accumulating errors from the initial skill repertoire.

We validate the effectiveness of our proposed approach in simulated household environments from the ALFRED benchmark. Experimental results demonstrate that BOSS can practice effectively with LLM guidance, allowing it to solve long-horizon household tasks in novel household environments which prior LLM-based planning and unsupervised exploration approaches fail at.

2 Preliminaries and Related Work

Reinforcement Learning Reinforcement learning (RL) algorithms aim to learn a policy $\pi(a|s)$ that maximizes the expected discounted return $\mathbb{E}_{a\sim\pi,P}\left[\sum_t \gamma^t R(s_t, a_t, s_{t+1})\right]$ in a Markov Decision Process $\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, \mathcal{R}, \gamma)$, where $\mathcal{S}$ and $\mathcal{A}$ are state and action spaces, $P : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}_+$ represents the transition probability distribution, $\mathcal{R} : \mathcal{S} \times \mathcal{A} \times \mathcal{S} \to \mathbb{R}$ denotes the reward function, and γ is the discount factor. Temporal-difference algorithms are a class of RL algorithms that also learn critic functions, denoted $V^\pi(s)$ or $Q^\pi(s, a)$, which represent future discounted returns when following the policy at state s or after taking action a from state s, respectively [15]. Standard RL algorithms struggle with learning long-horizon tasks and can be prohibitively sample-inefficient.

Skill-based RL To solve long-horizon tasks, prior works have focused on pre-training *skills*, short-horizon behaviors that can be re-combined into long-horizon behaviors [16, 17, 18, 9]. These skills can be represented as learned options [16, 18], sub-goal setting and reaching policies [19, 20], a set of discrete policies [21, 22], or continuous latent spaces that represent behaviors [23, 9, 10]. Yet, most of these approaches need expert supervision (e.g., demonstrations [19, 4, 20, 5, 6, 24, 7], frequent reward feedback [22, 9, 10]). In contrast, BOSS learns to execute long-horizon tasks with minimal human supervision via skill bootstrapping.

Unsupervised RL To learn skills without human supervision, recent works have introduced many unsupervised RL objectives, e.g., based on curiosity [25], contrallability [26, 27], and behavior or state diversification [28, 29, 30, 31, 32]. Because these works learn skills from scratch and explore without supervision, they generally focus on locomotion tasks where most behaviors agents can ex-

plore, such as different running gaits, are already meaningful. Few works demonstrate learning of manipulation tasks, but either require hand-crafted state or action spaces [25] or remain constrained to learning simple, short-horizon skills [33, 34]. BOSS makes two improvements to enable bootstrapping of long-horizon tasks: (1) We start from a base repertoire of language-conditioned skills to enable coherent, long-horizon exploration. (2) We leverage an LLM to guide exploration towards meaningful skill-chains within the exponential number of possible long-horizon behaviors.

Language in RL Prior works have employed language to parameterize rich skill sets to train multi-task RL agents [35, 36, 37]. Recent progress in training LLMs has enabled approaches that combine LLMs with pre-trained language-conditioned policies to perform open-loop planning over pre-trained skills [11, 12, 13, 38, 14]. These works do not perform any policy training or finetuning when planning with the LLMs; but instead use the LLMs as top-down planners whose plans are given to fixed low-level skill policies to execute. In contrast, BOSS *pratices* chaining behaviors in the environment during skill bootstrapping and thus learns a more robust, closed-loop policy that can perform meaningful long-horizon behaviors. We demonstrate that this leads to substantially higher success rate for execution of long-horizon kitchen manipulation tasks (see Section 4).

Closest to our work, ELLM [39] and IMAGINE [40] use language guidance to generate tasks for policy learning. ELLM samples open-ended tasks from an LLM and thus requires an observation captioning model to propose tasks and reward agents. Instead, we expand upon a pre-trained skill repertoire during a skill bootstrapping process, allowing for building skill chains while automatically rewarding the agent based on the completion of the fixed skills in the chain. Meanwhile, IMAGINE uses language guidance to generate goals for exploration. However, IMAGINE requires a "social partner" that modifies the environment according to desired agent goals. In realistic settings, this social partner either needs to be a human or requires extensive human effort to design. BOSS instead utilizes LLMs to propose behaviors to acquire in a target environment automatically.

3 Method

Our method, BOSS (**BO**ot**S**trapping your own **S**kills), automatically learns to solve new long-horizon, complex tasks by growing a learned skill library with minimal supervision. BOSS consists of two phases: (1) it acquires a base repertoire of skills (Section 3.1) and then (2) it practices chaining these skills into long-horizon behaviors in the *skill bootstrapping phase* (Section 3.2). BOSS can then *zero-shot execute* novel natural language instructions describing complex long-horizon tasks.

3.1 Pre-training a Language-Conditioned Skill Policy

We assume access to a dataset $\mathcal{D}^L = \{\tau_{z_1}, \tau_{z_2}, \tau_{z_3}, ...,\}$ where τ_{z_i} denotes a trajectory of (s, a, s', r) tuples and z_i is a freeform language description of the trajectory. We also assume access to a sparse reward function for the primitive skills, e.g., an object detector that can detect if an object is placed in the correct location. For example, if τ_{z_i} describes a demonstration of a robot arm picking up a mug, then $z_i =$ *"pick up the mug."* and $r = 1$ in the final transition in which the mug is picked up and 0 otherwise. To obtain a language-conditioned primitive skill policy, we train a standard offline RL algorithm on $\mathcal{D}^L$. In our experiments, we use Implicit Q-Learning (IQL) [41] as it is performant and amenable to online fine-tuning. We additionally condition the policy and critic networks on the trajectory's natural language annotation z. After training, we obtain a language-conditioned policy $\pi(a|s, z)$ and a critic function $V(s, z)$.

3.2 Skill Bootstrapping

After pre-training the language-conditioned skill policy, we perform skill bootstrapping. During this phase, the agent practices by interacting with the environment, trying new skill chains, then adding them back into its skill repertoire for further bootstrapping. Therefore the agent learns increasingly long-horizon skills without requiring additional supervision beyond the initial set of skills. Now we will describe the details of skill sampling and policy training.

Sampling initial skills At the start of bootstrapping, the skill repertoire $Z = \{z_1, z_2, ...\}$ is initialized to the set of pre-trained base skills. Upon initializing the agent in the environment at state s_1, we must sample an initial skill. Intuitively, the skill we choose should be executable from s_1 i.e.,

have a high chance of success. Therefore, in every bootstrapping episode, we sample the initial skill according to probabilities generated from the pre-trained value function, $V(s_1, z)$. We then try to execute the sampled skill until a timeout threshold is reached.

Guiding Skill Chaining via LLMs   If the first skill execution succeeds, the next step is constructing a longer-horizon behavior by chaining together the first skill with a sampled next skill. Naïvely choosing the next skill by, for example, sampling at random will likely result in a behavior that is not useful for downstream tasks. Even worse, the likelihood of picking a *bad* skill chain via random sampling increases linearly with the size of the skill repertoire and *exponentially* with the length of the skill chain. For a modestly sized repertoire with 20 skills and a chain length of 5 there are $20^5 = 3.2M$ possible skill chains, only few of which are likely meaningful.

Thus, instead of randomly sampling subsequent skills, we propose to use large language models (LLMs) to guide skill selection. Prior work has demonstrated that modern LLMs capture relevant information about meaningful skill chains [11, 12, 14]. Yet, in contrast to prior *top-down* LLM planning methods, we explore a *bottom-up* approach to learning long-horizon tasks: by allowing our agent to iteratively sample skill chains and practice their execution in the environment, we train more robust long-horizon task policies that achieve higher empirical success rates, particularly when generalizing to unseen environments (see Section 4).

LLM Prompt Example

Predict the next skill from the following list: Pick up the mug; Turn on the lamp; Put the mug in the coffee machine; ...

1: Pick up the mug.
2:

Figure 2: A shortened example of the LLM prompt. See the full prompt in Appendix A.2.

To sample next skills in practice, we prompt the LLM with the current skill repertoire and the chain of skills executed so far. For example, if the agent has just completed *"Pick up the mug"*, we prompt the LLM with the list of skill annotations in Z and then the following prompt: 1. PICK UP THE MUG. 2.____ (see Figure 2). The LLM then *proposes* the next skill by generating text following the prompt. We then map this predicted next skill string back to the set of existing skills in Z by finding the nearest neighbor of Z to the proposed skill annotation in the embedding space of a pre-trained sentence embedding model [42]. To encourage diversity in the practiced skill chains, we repeat this process N times and sample the true next skill from the distribution of LLM-assigned token likelihoods. Finally, if the sampled skill is successfully executed, we repeat the same process for sampling the following skill.

Learning new skills   Once an episode concludes, either because a skill times out or because a defined maximum skill chain length is reached, we add the collected data back into the replay buffer with a sparse reward of 1 for every completed skill. For example, if an attempted skill chain contains a total of 3 skills, then the maximum return of the entire trajectory is 3. We then continue policy training via the same offline RL algorithm used to learn the primitive skills—in our case, IQL [41].

Finally, to maximize data efficiency, we relabel the language instructions for the collected episode upon adding it to the replay buffer. Specifically, following prior work [43], we aggregate consecutive skills into *composite* skill instructions using the same LLM as for skill sampling. We then add the composite skill instruction and associated experience to the replay buffer and also add it to our skill repertoire for continued bootstrapping.

In summary, we iterate through these three steps to train a policy during the skill bootstrapping phase: (1) Sampling initial skills using the value function. (2) Sampling next skills by prompting the LLM with skills executed so far. (3) Adding learned skills back to the agent's skill library and training on collected agent experience. For a brief overview, see pseudocode in Algorithm 1. We list further implementation details in Appendix B and the full algorithm in Appendix Algorithm 2.

4   Experimental Evaluation

The goal of our experimental evaluation is to test BOSS's ability to acquire long-horizon, complex, and meaningful behaviors. We compare to multiple unsupervised RL and zero-shot planning meth-

(a) ALFRED benchmark

(b) Real world Jaco arm setup.

Figure 3: Our environments. (a) **The ALFRED environment** is a benchmark for learning agents that can follow natural language instructions to fulfill household tasks. This illustration was drawn from Shridhar et al. [44] with permission. (b) **Real-world Jaco arm** Our real-world kitchen manipulation tabletop environment based on RGB image inputs.

ods in two challenging, image-based control environments: solving household tasks in the ALFRED simulator [44] and kitchen manipulation tasks with a real-world Jaco robot arm. Concretely, we aim to answer the following questions: (1) Can BOSS learn a rich repertoire of useful skills during skill bootstrapping? (2) How do BOSS's acquired skills compare to skills learned by existing unsupervised RL methods? (3) Can our proposed approach directly be applied on real robot hardware?

4.1 Experimental Setup

ALFRED Environment. We test our approach in the ALFRED simulator [44] (see Figure 3a), since its 100+ floorplans with many interactable objects provide a rich environment for learning numberous long-horizon household tasks. We leverage a modified version of the ALFRED simulator [43] that allows for online RL interactions via a gym interface with 300×300 egocentric RGB image observations. The

---

Algorithm 1 BOSS Pseudocode.

1: Train policy π on initial skill repertoire
2: **for** skill bootstrapping episode **do**
3:     Sample initial skill z and execute
4:     **while** not episode timeout **do**
5:         Sample next skill from LLM and execute
6:     **end while**
7:     Construct composite skill and add to repertoire
8:     Update policy π
9: **end for**

---

action space consists of 12 discrete action choices (e.g. turn left, look up, pick up object), along with 82 discrete object types, first proposed by Pashevich et al. [45]. To train the skills in our initial skill library, we leverage the ALFRED dataset of $73k$ primitive skill demonstrations with language instructions. For bootstrapping we use four unseen floorplans. In each floorplan we define 10 evaluation tasks, each of which requires 2 to 8 primitive skills to complete.

Real-Robot Kitchen Manipulation. We evaluate our method with a real-robot manipulation setup in which a Kinova Jaco 2 robot arm needs to solve stylized kitchen tasks in a table-top environment (see Figure 3b). The observations consist of concatenated RGB images from a third-person and a wrist-mounted camera. The robot is controlled with continuous end-effector displacements and discrete gripper open/stay/close commands at a frequency of $10Hz$. To train the initial skills, we collect a dataset of $6k$ language-annotated primitive skill demonstrations via human teleoperation. We perform bootstrapping and evaluate the agents in a table setup with unseen object arrangements.

Training and Evaluation Procedure. We equip the policy with the initial primitive skill library by training it for 150 epochs on the respective pre-collected demonstration datasets using IQL [41] (see Section 3.1). We then perform 500,000 and 15,000 steps ($\sim$17 min of robot interaction time) of online skill bootstrapping in the respective evaluation environments of ALFRED and the real robot setup. Note that for ALFRED we train separate agents for each floorplan, mimicking a scenario in which an agent is dropped into a new household and needs to acquire skills with minimal super-

vision. After bootstrapping is completed, we evaluate the trained agents *zero-shot* on the held-out evaluation tasks by conditioning the policy on the respective language instruction. To perform well in this evaluation setting, an agent needs to acquire a *large* number of *useful* skills during online environment interactions.

Baselines. We compare BOSS to prior works that can learn a wide range of skills with minimal supervision: (1) unsupervised RL approaches that, like BOSS, learn from environment interactions without additional feedback and (2) large-language model based planners, that leverage the knowledge captured in large pre-trained language models to "bootstrap" given skill libraries into long-horizon behaviors. Concretely, we are comparing to the following approaches:

- **CIC** [46]: SoTA method on the unsupervised RL benchmark [47], expands its skill library with a contrastive alignment objective during bootstrapping. For fair comparison, we pre-train CIC's policy on the same primitive skill dataset used in BOSS before unsupervised bootstrapping.

- **SayCan** [12]: Leverages a pre-trained large language model (LLM) to break down a given task into step-by-step instructions, i.e., "primitive skills", by ranking skills from a given library. We implement SayCan using the same primitive skill policy pre-trained via offline RL as in BOSS. We use the same LLM as our method, and adapt SayCan's language model prompt for our environment. Notably, SayCan and similar top-down LLM planning work have no mechanism for fine-tuning to new environments.

- **SayCan+P**: To evaluate the effects of online bootstrapping vs. top-down LLM planning in isolation, we evaluate a SayCan variant that uses *our* LLM-based *skill proposal* mechanism, which leverages the LLM to *generate* step-by-step instructions in place of SayCan's original skill ranking method. Empirically, we found this to perform better than standard SayCan in the tested environments.

Additionally, we evaluate (1) an **Oracle** that finetunes the pre-trained primitive skill policy directly on the target tasks, serving as an upper bound, and (2) a pre-trained primitive skill policy *without any* bootstrapping (**No Bootstrap**), serving as a performance lower bound.

All methods utilize the same base primitive skill policy pre-trained on the same demonstration data. We implement a transformer policy and critic architecture based on Pashevich et al. [45] trained with the IQL algorithm [41]. All results reported are inter-quartile means and standard deviations over 5 seeds [48]. Finally, Saycan, Saycan+P, and BOSS all use the LLaMA-13b open-source, 13-billion parameter LLM [49]. For more baseline implementation and training details, see Section B.

4.2 BOSS Bootstrapping Learns Useful Skills

ALFRED. Overall, BOSS achieves superior performance to all non-oracle baselines, with **1.6-6x** better oracle-normalized return than the best baseline at each task length, and BOSS is the **only** non-oracle method to achieve non-zero success rates across all lengths of tasks. From Table 1, the gap between BOSS and best baselines is largest on the length 4 tasks, indicating the benefit of BOSS' LLM-guided skill bootstrapping in

Table 1: Inter-quartile means (IQMs) and standard deviations of oracle-normalized returns, i.e., number of solved subtasks, broken down by task length, across the ALFRED evaluation tasks in unseen household floorplans. We do not report results for evaluation tasks of length 6 and 8 since not even the oracle was able to learn these.

	Evaluation Task Length			
Method	Length 2	Length 3	Length 4	Average
No Bootstrap	0.03 +- 0.02	0.05 +- 0.07	0.08 +- 0.09	0.08 +- 0.09
CIC [46]	0.02 +- 0.02	0.25 +- 0.08	0.18 +- 0.07	0.05 +- 0.03
SayCan [12]	0.06 +- 0.02	0.14 +- 0.00	0.10 +- 0.12	0.05 +- 0.01
SayCan + P	0.08 +- 0.04	0.28 +- 0.00	0.20 +- 0.15	0.08 +- 0.01
BOSS (ours)	**0.48 +- 0.26**	**0.55 +- 0.07**	**0.71 +- 0.04**	**0.62 +- 0.29**

learning difficult, longer-horizon tasks without task supervision. CIC can make some progress in some length 3 and 4 tasks, but its contrastive objective generally fails to finetune the primitive skills into meaningful long-horizon skills. Saycan+P performs better than Saycan, indicating that our proposal mechanism better extracts a more meaningful distribution of skills from an LLM, but even Saycan+P greatly falls short of BOSS' performance as it is not robust to execution failures incurred from directly using the pre-trained policy in unseen floor plans. Since BOSS learns to finetune in-

Figure 4: Left: The number of subtasks in skills executed *during* skill bootstrapping by BOSS in one of the unseen ALFRED floorplans. BOSS progressively learns longer skill chains throughout the course of training. Right: The number of newly acquired skills by BOSS throughout training, averaged over all ALFRED floorplans.

Figure 5: Example skill chains (light gray) and new skill summaries (dark grey) learned by BOSS during skill bootstrapping. LLM-guidance ensures meaningful skill chains and summaries.

dividual primitive skills and transition *between* skills using a closed-loop policy, it performs much better on complex, long-horizon language-specified tasks in unseen environments.

We display qualitative examples of a length 2 and 3 task in appendix Figure 10, where we can see that BOSS successfully completes the tasks whereas Saycan suffers from execution failures, getting stuck while attempting to manipulate objects, and CIC navigates around performing random behaviors (Figure 10a) or gets stuck navigating around objects (Figure 10b). We show qualitative examples of learned skills in Figure 5.

Real Robot. In our real world experiments, we compare BOSS to **ProgPrompt** [14], a similar LLM planning method to Saycan that has been extensively evaluated on real-world tabletop robot manipulation environments similar to ours. We also augment it with prompt examples similar to ours and our skill proposal mechanism. Here, we evaluate on 5 tasks, 3 of length 2 and 2 of length 4 after performing bootstrapping. Results in Table 2 demonstrate that BOSS outperforms ProgPrompt as it is able to learn to chain together long-horizon skills in the new environment. See Appendix C.1 for more detailed task information.

Table 2: Success rates, split by task length, across the 5 robot eval tasks in an unseen table arrangement.

| Method | Evaluation Task Length | |
	Length 2	Length 4
ProgPrompt [14]	0.33	0.05
BOSS (ours)	0.34	**0.15**

4.2.1 Ablation Studies

To better analyze the effect of our core contribution, the usage of LLM guidance during skill bootstrapping, we compare to the following variants of our approach:

- **BOSS-OPT1**: A BOSS agent that uses a weaker 1-billion parameter LLM, OPT-1 [50] for skill bootstrapping.

- **BOSS-Rand**: An ablation of our approach BOSS that uses *no* LLM guidance during skill bootstrapping and simply selects the next skill at random from the current skill library.

We report results in Table 3. The analysis shows the importance of accurate LLM guidance during skill bootstrapping for learning useful skills. Using an LLM with lower performance (OPT1 vs. LLaMA 13B) results in degraded overall performance. Yet, performing bootstrapping without any LLM guidance performs even worse. Interestingly, the performance gap between BOSS and its variants widens for longer task lengths. Intuitively, the longer the task, the more possible other, less useful tasks of the same length could be learned by the agent during bootstrapping. Thus, particularly for long tasks accurate LLM guidance is helpful.

Table 3: Oracle-normalized returns per task length on the ALFRED evaluation tasks for ablation approaches.

| Method | Evaluation Task Length | | | |
	Length 2	Length 3	Length 4	Average
BOSS(ours)	**0.48 +- 0.26**	**0.55 +- 0.07**	**0.71 +- 0.04**	**0.62 +- 0.29**
BOSS-OPT1	0.39 +- 0.08	0.22 +- 0.08	0.56 +- 0.08	0.41 +- 0.24
BOSS-Rand	0.32 +- 0.03	0.29 +- 0.11	0.61 +- 0.16	0.41 +- 0.21

To further analyze this, we compare the sizes of the learned skill libraries between BOSS bootstrapped with Llama 13B guidance vs. random skill selection (BOSS-Rand) in Figure 6. Perhaps surprisingly, the random skill chaining ablation learns *more* skills than BOSS – its skill library grows faster during bootstrapping. Yet, Table 3 shows that it has lower performance. This indicates, that while BOSS-Rand learns many skills, it learns less *meaningful* skills. A qualitative analysis supports this intuition: many of the learned skills contain repetitions and meaningless skill chains. This underlines the importance of LLM guidance during skill bootstrapping. Furthermore, the positive correlation between the powerfulness of the used guidance LLM (1B → 13B parameters) and the evaluation task performance suggests that future, even more powerful LLMs can lead to even better skill bootstrapping.

Figure 6: Size of the learned skill library during bootstrapping.

5 Discussion

We propose BOSS, an approach that learns a diverse set of long-horizon tasks with minimal supervision via language-guided skill bootstrapping. Starting from an initial library of skills, BOSS acquires new behaviors by practicing to chain skills while using pre-trained large language models to guide skill selection. We demonstrate in a complex household simulator and real robot manipulation tasks that BOSS can learn useful skills during bootstrapping.

Limitations. While BOSS learns a large repertoire of skills with minimal supervision, it still has limitations that prevent it from truly fulfilling the vision of agents autonomously acquiring skills in a new environment. On the one hand, BOSS requires environment resets between episodes during bootstrapping, which are currently performed by a human in our real world experiments. Also, we require reward functions for each of the primitive skills to evaluate skill chaining success during bootstrapping, which is currently provided by a human supervising the experiment. Future research can investigate using advances in reset-free RL [51, 52] and learned reward functions [53, 54] to approach the goal of truly autonomous skill learning. Finally, BOSS is currently limited to skills that are combinations of primitive skills in its initial skill library. Extending our work with unsupervised RL [55, 46] techniques for learning new *low-level* skills are an exciting direction for future work.

References

[1] D. Kalashnikov, A. Irpan, P. Pastor, J. Ibarz, A. Herzog, E. Jang, D. Quillen, E. Holly, M. Kalakrishnan, V. Vanhoucke, and S. Levine. Scalable deep reinforcement learning for vision-based robotic manipulation. In *Conference on Robot Learning*, 2018.

[2] D. Kalashnkov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. Mt-opt: Continuous multi-task robotic reinforcement learning at scale. *arXiv*, 2021.

[3] A. X. Lee, C. Devin, Y. Zhou, T. Lampe, K. Bousmalis, J. T. Springenberg, A. Byravan, A. Abdolmaleki, N. Gileadi, D. Khosid, C. Fantacci, J. E. Chen, A. Raju, R. Jeong, M. Neunert, A. Laurens, S. Saliceti, F. Casarini, M. Riedmiller, R. Hadsell, and F. Nori. Beyond pick-and-place: Tackling robotic stacking of diverse shapes. In *Conference on Robot Learning (CoRL)*, 2021. URL https://openreview.net/forum?id=U0Q8CrtBJxJ.

[4] A. Gupta, V. Kumar, C. Lynch, S. Levine, and K. Hausman. Relay policy learning: Solving long horizon tasks via imitation and reinforcement learning. *Conference on Robot Learning (CoRL)*, 2019.

[5] K. Pertsch, Y. Lee, Y. Wu, and J. J. Lim. Demonstration-guided reinforcement learning with learned skills. *5th Conference on Robot Learning*, 2021.

[6] F. Ebert, Y. Yang, K. Schmeckpeper, B. Bucher, G. Georgakis, K. Daniilidis, C. Finn, and S. Levine. Bridge data: Boosting generalization of robotic skills with cross-domain datasets, 2021.

[7] M. Heo, Y. Lee, D. Lee, and J. J. Lim. Furniturebench: Reproducible real-world benchmark for long-horizon complex manipulation. In *Robotics: Science and Systems*, 2023.

[8] X. B. Peng, M. Chang, G. Zhang, P. Abbeel, and S. Levine. Mcp: Learning composable hierarchical control with multiplicative compositional policies, 2019. URL https://arxiv.org/abs/1905.09808.

[9] K. Pertsch, Y. Lee, and J. J. Lim. Accelerating reinforcement learning with learned skill priors. In *Conference on Robot Learning*, 2020.

[10] A. Ajay, A. Kumar, P. Agrawal, S. Levine, and O. Nachum. Opal: Offline primitive discovery for accelerating offline reinforcement learning, 2021.

[11] W. Huang, P. Abbeel, D. Pathak, and I. Mordatch. Language models as zero-shot planners: Extracting actionable knowledge for embodied agents. *arXiv preprint arXiv:2201.07207*, 2022.

[12] M. Ahn, A. Brohan, N. Brown, Y. Chebotar, O. Cortes, B. David, C. Finn, C. Fu, K. Gopalakrishnan, K. Hausman, A. Herzog, D. Ho, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, E. Jang, R. J. Ruano, K. Jeffrey, S. Jesmonth, N. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, K.-H. Lee, S. Levine, Y. Lu, L. Luu, C. Parada, P. Pastor, J. Quiambao, K. Rao, J. Rettinghouse, D. Reyes, P. Sermanet, N. Sievers, C. Tan, A. Toshev, V. Vanhoucke, F. Xia, T. Xiao, P. Xu, S. Xu, M. Yan, and A. Zeng. Do as i can and not as i say: Grounding language in robotic affordances. In *arXiv preprint arXiv:2204.01691*, 2022.

[13] W. Huang, F. Xia, T. Xiao, H. Chan, J. Liang, P. Florence, A. Zeng, J. Tompson, I. Mordatch, Y. Chebotar, P. Sermanet, N. Brown, T. Jackson, L. Luu, S. Levine, K. Hausman, and B. Ichter. Inner monologue: Embodied reasoning through planning with language models. In *arXiv preprint arXiv:2207.05608*, 2022.

[14] I. Singh, V. Blukis, A. Mousavian, A. Goyal, D. Xu, J. Tremblay, D. Fox, J. Thomason, and A. Garg. ProgPrompt: Generating situated robot task plans using large language models. 2022.

[15] R. S. Sutton and A. G. Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

[16] R. S. Sutton, D. Precup, and S. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 112(1):181–211, 1999. ISSN 0004-3702. doi:https://doi.org/10.1016/S0004-3702(99)00052-1. URL https://www.sciencedirect.com/science/article/pii/S0004370299000521.

[17] M. Pickett and A. G. Barto. Policyblocks: An algorithm for creating useful macro-actions in reinforcement learning. In *Proceedings of the Nineteenth International Conference on Machine Learning*, ICML '02, page 506–513, San Francisco, CA, USA, 2002. Morgan Kaufmann Publishers Inc. ISBN 1558608737.

[18] P.-L. Bacon, J. Harb, and D. Precup. The option-critic architecture. In *Association for the Advancement of Artificial Intelligence*, 2017.

[19] A. Gupta, V. Kumar, C. Lynch, S. Levine, and K. Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning, 2019.

[20] A. Mandlekar, F. Ramos, B. Boots, S. Savarese, L. Fei-Fei, A. Garg, and D. Fox. Iris: Implicit reinforcement without interaction at scale for learning control from offline robot manipulation data, 2020.

[21] S. Schaal. Dynamic movement primitives–a framework for motor control in humans and humanoid robotics. *Adaptive Motion of Animals and Machines*, 01 2006. doi:10.1007/4-431-31381-8_23.

[22] Y. Lee, S.-H. Sun, S. Somasundaram, E. Hu, and J. J. Lim. Composing complex skills by learning transition policies with proximity reward induction. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=rygrBhC5tQ.

[23] K. Hausman, J. T. Springenberg, Z. Wang, N. Heess, and M. Riedmiller. Learning an embedding space for transferable robot skills. In *International Conference on Learning Representations*, 2018.

[24] L. X. Shi, J. J. Lim, and Y. Lee. Skill-based model-based reinforcement learning. In *Conference on Robot Learning*, 2022.

[25] D. Pathak, P. Agrawal, A. A. Efros, and T. Darrell. Curiosity-driven exploration by self-supervised prediction, 2017.

[26] A. Sharma, S. Gu, S. Levine, V. Kumar, and K. Hausman. Dynamics-aware unsupervised discovery of skills. *arXiv*, abs/1907.01657, 2019.

[27] S. Park, K. Lee, Y. Lee, and P. Abbeel. Controllability-aware unsupervised skill discovery, 2023.

[28] J. Achiam, H. Edwards, D. Amodei, and P. Abbeel. Variational option discovery algorithms. *arXiv*, 2018.

[29] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine. Diversity is all you need: Learning skills without a reward function. In *ICLR*, 2019.

[30] D. Warde-Farley, T. V. de Wiele, T. Kulkarni, C. Ionescu, S. Hansen, and V. Mnih. Unsupervised control through non-parametric discriminative rewards. In *ICLR*, 2019.

[31] K. Gregor, D. J. Rezende, and D. Wierstra. Variational intrinsic control. *arXiv*, abs/1611.07507, 2016.

[32] J. Zhang, H. Yu, and W. Xu. Hierarchical reinforcement learning by discovering intrinsic options. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=r-gPPHEjpmw.

[33] R. Sekar, O. Rybkin, K. Daniilidis, P. Abbeel, D. Hafner, and D. Pathak. Planning to explore via self-supervised world models, 2020.

[34] R. Mendonca, O. Rybkin, K. Daniilidis, D. Hafner, and D. Pathak. Discovering and achieving goals via world models, 2021.

[35] C. Lynch and P. Sermanet. Language conditioned imitation learning over unstructured data. *Robotics: Science and Systems*, 2021. URL https://arxiv.org/abs/2005.07648.

[36] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. BC-z: Zero-shot task generalization with robotic imitation learning. In *5th Annual Conference on Robot Learning*, 2021. URL https://openreview.net/forum?id=8kbp23tSGYv.

[37] A. Brohan, N. Brown, J. Carbajal, Y. Chebotar, J. Dabis, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, J. Hsu, J. Ibarz, B. Ichter, A. Irpan, T. Jackson, S. Jesmonth, N. J. Joshi, R. Julian, D. Kalashnikov, Y. Kuang, I. Leal, K.-H. Lee, S. Levine, Y. Lu, U. Malla, D. Manjunath, I. Mordatch, O. Nachum, C. Parada, J. Peralta, E. Perez, K. Pertsch, J. Quiambao, K. Rao, M. Ryoo, G. Salazar, P. Sanketi, K. Sayed, J. Singh, S. Sontakke, A. Stone, C. Tan, H. Tran, V. Vanhoucke, S. Vega, Q. Vuong, F. Xia, T. Xiao, P. Xu, S. Xu, T. Yu, and B. Zitkovich. Rt-1: Robotics transformer for real-world control at scale, 2022.

[38] D. Shah, B. Osinski, B. Ichter, and S. Levine. Robotic Navigation with Large Pre-Trained Models of Language, Vision, and Action. 2022. URL https://arxiv.org/abs/2207.04429.

[39] Y. Du, O. Watkins, Z. Wang, C. Colas, T. Darrell, P. Abbeel, A. Gupta, and J. Andreas. Guiding pretraining in reinforcement learning with large language models, 2023. URL https://arxiv.org/abs/2302.06692.

[40] C. Colas, T. Karch, N. Lair, J.-M. Dussoux, C. Moulin-Frier, F. P. Dominey, and P.-Y. Oudeyer. Language as a cognitive tool to imagine goals in curiosity driven exploration. *NeurIPS 2020*, 2020.

[41] I. Kostrikov, A. Nair, and S. Levine. Offline reinforcement learning with implicit q-learning. In *International Conference on Learning Representations*, 2022. URL https://openreview.net/forum?id=68n2s9ZJWF8.

[42] N. Reimers and I. Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 11 2019. URL https://arxiv.org/abs/1908.10084.

[43] J. Zhang, K. Pertsch, J. Zhang, T. Nam, S. J. Hwang, X. Ren, and J. J. Lim. SPRINT: Scalable semantic policy pre-training via language instruction relabeling. In *Workshop on Language and Robotics at CoRL 2022*, 2022. URL https://openreview.net/forum?id=NC0JYBjl2j.

[44] M. Shridhar, J. Thomason, D. Gordon, Y. Bisk, W. Han, R. Mottaghi, L. Zettlemoyer, and D. Fox. ALFRED: A Benchmark for Interpreting Grounded Instructions for Everyday Tasks. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020. URL https://arxiv.org/abs/1912.01734.

[45] A. Pashevich, C. Schmid, and C. Sun. Episodic Transformer for Vision-and-Language Navigation. In *ICCV*, 2021.

[46] M. Laskin, H. Liu, X. B. Peng, D. Yarats, A. Rajeswaran, and P. Abbeel. Cic: Contrastive intrinsic control for unsupervised skill discovery, 2022.

[47] M. Laskin, D. Yarats, H. Liu, K. Lee, A. Zhan, K. Lu, C. Cang, L. Pinto, and P. Abbeel. Urlb: Unsupervised reinforcement learning benchmark, 2021.

[48] R. Agarwal, M. Schwarzer, P. S. Castro, A. Courville, and M. G. Bellemare. Deep reinforcement learning at the edge of the statistical precipice. *Advances in Neural Information Processing Systems*, 2021.

[49] H. Touvron, T. Lavril, G. Izacard, X. Martinet, M.-A. Lachaux, T. Lacroix, B. Rozière, N. Goyal, E. Hambro, F. Azhar, A. Rodriguez, A. Joulin, E. Grave, and G. Lample. Llama: Open and efficient foundation language models, 2023.

[50] S. Zhang, S. Roller, N. Goyal, M. Artetxe, M. Chen, S. Chen, C. Dewan, M. Diab, X. Li, X. V. Lin, T. Mihaylov, M. Ott, S. Shleifer, K. Shuster, D. Simig, P. S. Koura, A. Sridhar, T. Wang, and L. Zettlemoyer. Opt: Open pre-trained transformer language models, 2022. URL https://arxiv.org/abs/2205.01068.

[51] A. Gupta, J. Yu, T. Z. Zhao, V. Kumar, A. Rovinsky, K. Xu, T. Devlin, and S. Levine. Reset-free reinforcement learning via multi-task learning: Learning dexterous manipulation behaviors without human intervention. In *2021 IEEE International Conference on Robotics and Automation (ICRA)*. IEEE, 2021.

[52] A. Sharma, A. Gupta, S. Levine, K. Hausman, and C. Finn. Autonomous reinforcement learning via subgoal curricula. *Advances in Neural Information Processing Systems*, 2021.

[53] J. Fu, K. Luo, and S. Levine. Learning robust rewards with adversarial inverse reinforcement learning. In *ICLR*, 2018.

[54] A. S. Chen, S. Nair, and C. Finn. Learning generalizable robotic reward functions from" in-the-wild" human videos. In *RSS*, 2021.

[55] A. Sharma, S. Gu, S. Levine, V. Kumar, and K. Hausman. Dynamics-aware unsupervised discovery of skills. In *ICLR*, 2020.

[56] X. B. Peng, A. Kumar, G. Zhang, and S. Levine. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning, 2019.

[57] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2016.

[58] J. L. Ba, J. R. Kiros, and G. E. Hinton. Layer normalization, 2016.

[59] P. J. Ball, L. Smith, I. Kostrikov, and S. Levine. Efficient online reinforcement learning with offline data, 2023.

[60] S. Nair, A. Rajeswaran, V. Kumar, C. Finn, and A. Gupta. R3m: A universal visual representation for robot manipulation. In *CoRL*, 2022.

[61] T. Z. Zhao, V. Kumar, S. Levine, and C. Finn. Learning fine-grained bimanual manipulation with low-cost hardware. *arXiv preprint arXiv:2304.13705*, 2023.

Appendix

A Dataset and Environment Details

A.1 ALFRED

A.1.1 Dataset Details

We base our dataset and environment on the ALFRED benchmark [44]. ALFRED originally contains over 6000 full trajectories collected from an expert planner following a set of 7 high-level tasks with randomly sampled objects (e.g., *"pick an object and heat it"*). Each trajectory has three crowd-sourced annotations, resulting in around 20k distinct language-annotated trajectories. We separate these into only the primitive skill trajectories, resulting in about 141k language-annotated trajectories. Following Zhang et al. [43], we merge navigation skills (e.g., *"Walk to the bed"*) with the skill immediately following them as these navigation skills make up about half of the dataset, are always performed before another skill, and are difficult to design online RL reward functions for that work across all house floor plans given only the information in the dataset for these skills. After this processing step, the resulting dataset contains 73k language-annotated primitive skill trajectories.

A.1.2 RL Environment Details

We modified ALFRED similarly to Zhang et al. [43], Pashevich et al. [45] to make it suitable for policy learning by modifying the action space to be fully discrete, with 12 discrete action choices and 82 discrete object types.

Furthermore, we rewrote reward functions for all primitive skill types ("CoolObject", "PickupObject", "PutObject", "HeatObject", "ToggleObject", "SliceObject", "CleanObject") so that rewards can be computed independently of a reference expert trajectory. While our rewards depend on the ground truth primitive skill type, no agents are allowed access to what the underlying true primitive skill type is. All of our reward function are sparse, with 1 for a transition that completes primitive skill and 0 for all other transitions.

A.1.3 Evaluation Tasks

We generate evaluation tasks by randomly sampling 10 tasks each for 4 unseen ALFRED floor plans, resulting in 40 total tasks unseen tasks requiring anywhere from 2-8 primitive skills to complete. The tasks for each floor plan are sampled randomly from the VALID-UNSEEN ALFRED dataset collected in these plans with the specific object arrangements, and we use the high-level task language descriptions collected by humans for ALFRED as our task descriptions for language-conditioned zero-shot evaluation. See Figure 7 for a histogram of task lengths.

Figure 7: Task lengths regarding the number of primitive skills needed to chain together to solve the task.

> Examples of common household tasks and their descriptions:
> Task Steps: 1. Pick up the keys on the center table. 2. Put the keys in the box. 3. Pick up the box with keys. 4. Put the box with keys on the sofa close to the newspaper.
> Task: Put the box with keys on the sofa.
>
> Task Steps: 1. Pick up the knife from in front of the tomato. 2. Cut the lettuce on the counter. 3. Set the knife down on the counter in front of the toaster. 4. Pick up a slice of the lettuce from the counter. 5. Put the lettuce slice in the refrigerator. take the lettuce slice out of the refrigerator. 6. Set the lettuce slice on the counter in front of the toaster.
> Task: Put a cooled slice of lettuce on the counter.
>
> Task Steps: 1. Pick up the book on the table, in front of the chair. 2. Place the book on the left cushion of the couch.
> Task: Put a book on the couch.
>
> Task Steps: 1. Pick up the fork from the table. 2. Put the fork in the sink and fill the sink with water, then empty the water from the sink and remove the fork. 3. Put the fork in the drawer.
> Task: Put the cleaned fork in a drawer.
>
> Task Steps: 1. Take the box of tissues from the makeup vanity. 2. Put the tissues on the barred rack. 3. Take the box of tissues from the top of the toilet. 4. Put the tissues on the barred rack.
> Task: Put the box of tissues on the barred rack.
>
> Task Steps: 1. Pick up the glass from the sink. 2. Heat the glass in the microwave. 3. Put the glass on the wooden rack.
> Task: Put a heated glass on the wooden rack.
>
> Task Steps: 1. Pick up the box from the far side of the bed. 2. Hold the box and turn on the lamp.
> Tasks: Look at the box under the lamp light.
>
> Predict the next skill correctly by choosing from the following skills: [SKILL 1 IN LIBRARY], [SKILL 2 IN LIBRARY], ...
> Task Steps: 1. [SKILL 1 EXECUTED SO FAR] 2. [SKILL 2 EXECUTED SO FAR] ... N. ____

Figure 8: Prompt for the LLM for next skill proposal Section 3.2 Text is generated after listing out all skills completed so far.

A.2 Language Model Prompts

We use two prompts when using the LLM for two different purposes. The main purpose of the LLM is to propose a distribution over next skills to chain with currently executed skills during skill bootstrapping (Section 3.2). Thus, we pass skills in the given skill library Z into the prompt and ask it to predict the next skill. We also include a fixed set of 7 in-context examples from a random sample of different tasks from the ALFRED training dataset. The prompt for bootstrapping is shown in Figure 8.

We also generate summaries (see Section 3.2 and appendix Appendix B.3) for *composite* skill annotations with the LLM. These summaries are used to label newly chained longer-horizon skills before adding them back to the skill library. We show the prompt for this in Figure 9.

B Training Implementation details and Hyperparameters

We implement IQL [41] as the base offline RL algorithm to pre-train on primitive skill data for all methods, baselines, and ablations, due to its strong offline and finetuning performance on a variety of dense and sparse reward environments.

The IQL policy is trained to maximize the following objective:

$$e^{\beta(Q(s,a)-V(s))} \log \pi(a|s),$$

which performs advantage-weighted regression [56] with an inverse temperature term β. Q and V are trained on (s, a, s', r, a') tuples from the dataset rather than sampling a policy for a' to mitigate

Figure 9: Prompt for the LLM to summarize completed skills into high-level *composite* annotations, following Zhang et al. [43].

issues with critic function overestimation common in offline RL. We detail shared training and implementation details below, with method-specific information and hyperparameters in the following subsections.

B.1 ALFRED Environment

We implement the same observation and action space as Zhang et al. [43]. Details are listed below.

Observation space. The observations given to agents are 300×300 RGB images. For all methods, we first preprocess these images by sending them through a frozen ResNet-18 encoder [57] pre-trained on ImageNet, resulting in a $512 \times 7 \times 7$ observation.

Action space. The agent chooses from 12 discrete low-level actions. There are 5 navigation actions: MoveAhead, RotateRight, RotateLeft, LookUp, and LookDown and 7 interaction actions: Pickup, Put, Open, Close, ToggleOn, ToggleOff, and Slice. For interaction actions the agent additionally selects one of 82 object types to interact with, as defined by Pashevich et al. [45]. In total, the action space consists of $5 + 7 * 82 = 579$ discrete action choices. For all methods, due to the large discrete action space, we perform the same action masking as Zhang et al. [43] to prevent agents from taking actions that are not possible. For example, we do not allow the agent to Close objects that aren't closeable or ToggleOn objects that can't be turned on.

Policy and critic networks. We use the transformer architecture (and hyperparameters) used by Episodic Transformers (ET) [45] for our policy and critic networks. We implement all critics (two Q functions and one V) with a shared backbone and separate output heads. Additionally, we use

LayerNorms [58] in the MLP critic output heads as recommended by Ball et al. [59]. All networks condition on tokenized representations of input language annotations.

Hyperparameters. Hyperparameters were generally selected from tuning the Oracle baseline to work as best as possible, then carried over to all other methods. Shared hyperparameters for all methods (where applicable) for pre-training on primitive skills are listed below. Any unlisted hyperparameters or implementation details are carried over from Pashevich et al. [45]:

Param	Value
Batch Size	64
# Training Epochs	150
Learning Rate	1e-4
Optimizer	AdamW
Dropout Rate	0.1
Weight Decay	0.1
Discount γ	0.97
Q Update Polyak Averaging Coefficient	0.005
Policy and Q Update Period	1 per train iter
IQL Advantage Clipping	[0, 100]
IQL Advantage Inverse Temperature β	5
IQL Quantile τ	0.8
Maximum Observation Context Length	21

When fine-tuning policies (for Oracle, CIC, and BOSS), we keep hyperparameters the same. We fine-tune one policy per floor plan (zero-shot evaluating on 10 tasks in each floor plan) in our AL-FRED task set so that the aggregated results are reported over 4 runs per seed. For methods that use a skill library (BOSS, Saycan, Saycan+P), all available primitive skills across all evaluation tasks in each floor plan compose the starting skill library, resulting in anywhere from 15-40 available skills depending on the floor plan.

Additionally, when finetuning the Oracle baseline along with BOSS and its ablations, we sample old data from the offline dataset and newly collected data at equal proportions in the batch, following suggestions from [59]. We do not do this for CIC when finetuning with its unsupervised RL objective because the language embeddings from the old data are not compatible with the online collected data labeled with CIC-learned skill embeddings. Fine-tuning hyperparameters follow:

Param	Value
# Initial Rollouts	50
# Training Steps to Env Rollouts Ratio	15
ϵ in ϵ-greedy action sampling	0.05
Discrete action sampling	True
# Parallel Rollout Samplers	10

B.2 Real Robot Environment

The input observation from the environment includes environment RGB input and robot states. The RGB input consists of the third-person view RGB images from a Logitech Pro Webcam C920 cropped to 224×224×3, and wrist view images from an Intel RealSense D435. We use a pretrained R3M [60] model to get the latent representation for each view. The robot states include the robot's end-effector position, velocity, and gripper state. The end-effector position and velocity are two continuous vectors, and the gripper state is a one-hot vector, which presents OPEN, CLOSE, or NOT MOVE. We concatenate the RGB latent representations and robot states together as environment states.

The policy is language conditioned, and we use a pre-trained sentence encoder to encode the language annotation to a 384-dimensional latent vector. The pretrained sentence encoder we use is `all-MiniLM-L12-v2` from the `SentenceTransformers` package [42].

The total state input dimension is 2048 (third-person R3M) + 2048 (wrist R3M) + 15 (robot state input) + 384 (language latent representation) = 4495.

Action space. The action space of the robot encompasses the difference in the end effector position between each time step, along with discrete open and close signals for the gripper. These actions are transmitted to the robot with 10HZ and interpreted as desired joint poses using PyBullet's inverse kinematics module.

In line with [61], we adopt the Action Chunking method to train an autoregressive policy. Our policy utilizes an LSTM model to predict the next 15 actions, given the initial observation as input, denoted as $\pi(a_{t:t+15}|s_t)$. Both our Q and Value networks are recurrent as well, estimating rewards on a per-timestep basis for each action in the sequence. Similar to the policy, these networks only have access to the observation preceding the action sequence initiation.

Due to the gripper action space is discrete and imbalanced distributed in the dataset, we reweigh gripper loss inversely proportionally to the number of examples in each class.

B.3 Additional BOSS Implementation Details

Here we continue discussion of BOSS in detail. In the main text in Section 3.2 we mention that we add learned skills back to the agent's skill repertoire and then train on collected experience gathered from each rollout. Here, we detail exactly how we do that.

Labeling new composite skills. Finally, after we have finished attempting a composite skill chain, we need a natural language description for it so we can train the language-conditioned policy on this new composite skill. We ask the LLM to generate high-level task descriptions of the annotations of the two skills the agent has just attempted to chain together like proposed by Zhang et al. [43] for offline policy pre-training. Doing so will allow the agent to learn skills at a higher level of text abstraction, allowing the agent to operate on more natural evaluation task specifications. For example, humans are more likely to ask an agent to "Make coffee" than to say "Get a coffee pod. Put the coffee pod in the machine. Fill it up with water..."

We give the LLM a prompt similar to the one for generating next skills. For example, if our agent has just completed two skills: *"Pick up the spoon"*, *"Put the spoon on the counter"*, we ask the LLM to summarize "1. PICK UP THE SPOON. 2. PUT THE SPOON ON THE COUNTER.", and the LLM can generate *"put a spoon on the counter."* We denote the generated language annotation for this combined skill composed of the annotations of z^1 and z^2 as z'. We then add z' as a new composite skill to Z for the agent to possibly sample from again.

Training on new skill data After the agent has finished a rollout in the environment, it trains on the experience gathered. There are five types of data that we add to the agent's replay buffer from its rollout data:

1. The trajectory of the attempted skill chain which is collected only if the entire first skill is successfully executed (regardless if it is a primitive skill or a chain of them) since only then will another skill be used for chaining. The label for this trajectory is produced by the LLM.

2. The trajectory of the composite skill but with a label generated by concatenating the primitive skill annotations as a sequence of sentences of their language annotations. This trajectory ensures that the agent receives a description for the collected composite trajectory that specifies the exact primitive skills that make it up, in order. This is useful because the LLM-generated high-level skill description may not describe certain steps. Those steps are explicitly spelled out in this new label.

3. Trajectories for all lowest-level primitive skills executed during the rollout. These correspond to the original set of skills the policy was equipped with and will help the policy continue to finetune its ability to execute its original primitive skills.

After the rollout, we add these trajectories to the agent's replay buffer.

Other details When performing skill bootstrapping in the ALFRED environment, we set a max time limit (T in Algorithm 2) for 40 timesteps per primitive skill. For simplicity, we restrict M,

the max number of skills to chain, to be 2 during skill bootstrapping rollouts. We also restrict the second skill to be chained to only the set of primitive skills so that the agent can only learn new skill chains that are one primitive skill longer than the first sampled skill. Note that this does not restrict the agent from sampling composite skills it has learned during bootstrapping as first skills upon initialization.

B.4   CIC Implementation

For fairness in our experimental comparison, we implement CIC [46] by using its objective to train a policy pre-trained on the same dataset as BOSS; thus, the CIC agent is first initialized with a set of sensible behaviors. Since CIC operates on a fixed latent space, we modified the critic and policy architectures so that they operate on fixed-length, 768-dimensional embeddings of language inputs from the same sentence embedding model used for skill bootstrapping [42] instead of on variable length tokenized language representations.

CIC-specific hyperparameters follow:

Param	Value
CIC K-means K	12
CIC K-means avg	True
CIC Hidden Dim	1024
CIC Latent Skill Dim	768
CIC Temp	0.5
CIC Skill Projection Layer	True
# Timesteps for each skill rollout before reset	200

B.5   SayCan Implementation

We implement SayCan [12] by combining the prompt from SayCan with ours. We use the same in-context examples except but convert them to a human-robot conversation. All other details are the same, including the LLM that we use in this comparison (LLaMa-13b [49]). The Saycan prompt follows below:

Robot: Hi there, I'm a robot operating in a house. Robot: You can ask me to do various tasks

and I'll tell you the sequence of actions I would do to accomplish your task.

Human: How would you put the box with keys on the sofa?
Robot: 1. Pick up the keys on the center table. 2. Put the keys in the box. 3. Pick up the box with keys. 4. Put the box with keys on the sofa close to the newspaper.

Human: How would you put a cooled slice of lettuce on the counter?
Robot: 1. Pick up the knife from in front of the tomato. 2. Cut the lettuce on the counter. 3. Set the knife down on the counter in front of the toaster. 4. Pick up a slice of the lettuce from the counter. 5. Put the lettuce slice in the refrigerator. take the lettuce slice out of the refrigerator. 6. Set the lettuce slice on the counter in front of the toaster.

Human: How would you put a book on the couch?
Robot: 1. Pick up the book on the table, in front of the chair. 2. Place the book on the left cushion of the couch.

Human: How would you put the cleaned fork in a drawer?
Robot: 1. Pick up the fork from the table. 2. Put the fork in the sink and fill the sink with water, then empty the water from the sink and remove the fork. 3. Put the fork in the drawer.

Human: How would you put the box of tissues on the barred rack?
Robot: 1. Take the box of tissues from the makeup vanity. 2. Put the tissues on the barred rack. 3. Take the box of tissues from the top of the toilet. 4. Put the tissues on the barred rack.

Human: How would you put a heated glass on the wooden rack?
Robot: 1. Pick up the glass from the sink. 2. Heat the glass in the microwave. 3. Put the glass on the wooden rack.

Human: How would you look at the box under the lamp light?
Robot: 1. Pick up the box from the far side of the bed. 2. Hold the box and turn on the lamp.

Predict the next skill correctly by choosing from the following skills: [SKILL 1 IN LIBRARY], [SKILL 2 IN LIBRARY], ...

Human: How would you [HIGH LEVEL TASK DESCRIPTION]?
Robot: 1. [SKILL 1 EXECUTED SO FAR] 2. [SKILL 2 EXECUTED SO FAR] ... N. ____

B.6 ProgPrompt Implementation

ProgPrompt [14] converts natural language queries to code and executes the code on a real robot. After consulting with the authors, we converted the examples in our prompt to one suitable for Progprompt by converting task descriptions into a code representation by converting spaces into underscores, e.g., "Pick up the milk" into "def pick_up_the_milk()". Then, to translate code commands into commands suitable for our pre-trained policy, we prompt ProgPrompt to output 'pick_and_place(object, object)' style code commands that we convert into two separate pick and place natural language commands in the same format as the instructions used for pre-training the policy. We then execute these instructions on the real robot in sequence.

C Additional Results

C.1 Real Robot Results

We evaluate on 5 tasks, detailed below, in the environment setup shown in Figure 11.

1. Clean the black bowl (length 2): (1) Pick up the black bowl, (2) put it in the sink.

2. Put the black bowl to the dish rack (length 2): (1) Pick up the black bowl, (2) put it in the dish rack.

(a) Length 3 Task Example

(b) Length 2 Task Example

Figure 10: Qualitative visualizations of zero-shot evaluation rollouts.

Figure 11: Example of a BOSS rollout after skill bootstrapping on task 5: "Clean the black bowl and put it in the gray plate." BOSS is able to complete all 4 tasks in this rollout after performing skill bootstrapping.

3. Put the black bowl to the gray plate (length 2): (1) Pick up the black bowl, (2) put it in the gray plate.

4. Clean the black bowl and put it in the dish rack (length 4): (1) Pick up the black bowl, (2) put it in the sink, (3) pick up the black bowl, (4) put it in the dish rack.

5. Clean the black bowl and put it in the gray plate (length 4): (2) pick up the black bowl, (2) put it in the sink, (3) pick up the black bowl, (4) put it in the plate.

We report full results in Table 4.

Task	ProgPrompt return	ProgPrompt success rate	BOSS return	BOSS success rate
1	2 ± 0	1	1.6 ± 0.8	0.8
2	0.67 ± 0.47	0	0.8 ± 0.75	0.2
3	0.67 ± 0.47	0	0.6 ± 0.49	0
4	0.9 ± 0.78	0	1.7 ± 1.1	0.1
5	2.0 ± 1.2	0.1	2.2 ± 0.98	0.2

Table 4: Full returns and success rates for real robot evaluation comparisons.

Algorithm 2 BOSS Algorithm

Require: Dataset $\mathcal{D}^L$ w/ language instruction labels, LLM, Skill Library Z, Time limit T, max chain length M
1: Pre-train policy $\pi(a|s)$, value function $V(s, z)$ on $\mathcal{D}^L$ with offline RL. $\triangleright$ Section 3.1
2: **while** not converged **do**
3:     SKILLBOOTSTRAPPING(V, Z, LLM, π, $\mathcal{D}^L$, M, T) $\triangleright$ Section 3.2
4: **end while**
5:
6: **procedure** SKILLBOOTSTRAPPING(V, Z, LLM, π, $\mathcal{D}^L$, M, T)
7:     $s_1 \leftarrow$ Reset environment
8:     RolloutData $\leftarrow$ []
9:     z $\leftarrow$ sample   from   categorical   distribution   with   parameters $\left[V(s, z_1), V(s, z_2), ..., V(s, z_{|Z|}) \right]$.
10:     $i \leftarrow 0$
11:     Success $\leftarrow$ True
12:     **while** $i < M$ and Success **do**
13:         $i \leftarrow i + 1$
14:         (Success, τ) $\leftarrow$ Rollout $\pi(\cdot|s, z)$ in Environment for at most T steps.
15:         RolloutData.append(τ)
16:         **if** Success **then**
17:             $z \leftarrow$ SAMPLENEXTSKILL(LLM, ROLLOUTDATA, Z)
18:         **end if**
19:     **end while**
20:     UPDATEBUFFERANDSKILLREPERTOIRE($\mathcal{D}^L$, ROLLOUTDATA, LLM)
21:     Train π, V on $\mathcal{D}^L$ with offline RL.
22: **end procedure**
23:
24: **procedure** SAMPLENEXTSKILL(LLM, RolloutData, Z)
25:     AllSkills $\leftarrow$ extract all skill annotations from Z.
26:     CompletedSkillChain $\leftarrow$ extract executed primitive skills in current rollout from RolloutData.
27:     Prompt $\leftarrow$ construct prompt from AllSkills, CompletedSkillChain. $\triangleright$ Prompt in Figure 8.
28:     $([\hat{z}_1, ..., \hat{z}_N], [p_1, ..., p_N]) \leftarrow$ Sample N text generations from LLM(Prompt) with average token probabilities $p_1, ..., p_N$.
29:     Find closest match in Z to each of $\hat{z}_1, ..., \hat{z}_N$ in embedding space from a sentence embedding model. $\triangleright$ Embedding model: all-mpnet-base-v2 from the SentenceTransformers package [42].
30:     $z \leftarrow$ sample the matches in Z from categorical distribution with parameters $p_1, ..., p_N$.
31:     **return** z
32: **end procedure**
33:
34: **procedure** UPDATEBUFFERANDSKILLREPERTOIRE($\mathcal{D}^L$, RolloutData, Z, LLM) $\triangleright$ See Appendix B.3 for details.
35:     $\tau_1, ..., \tau_k$ $\leftarrow$ extract   completed   and   attempted   primitive   skill   trajectories   from RolloutData.
36:     **for** τ_i in $\tau_1, ..., \tau_k$ **do**
37:         $\mathcal{D}^L \leftarrow \mathcal{D}^L \cup \{\tau_{i, z_i}\}$ $\triangleright$ Add primitive skill trajectory to $\mathcal{D}^L$ with primitive skill annotation z_i.
38:     **end for**
39:     $\tau_{1:k} \leftarrow$ concatenate all trajectories together
40:     $z_{LLM, 1:k} \leftarrow LLM(\tau_{1:k})$ assign new skill name from LLM by asking it to write a high-level summary of annotations of $\tau_{1:k}$. $\triangleright$ See Appendix A.2 for this prompt.
41:     $z_{concat, 1:k} \leftarrow$ "$\{z_1\}.\{z_2\}...\{z_k\}$.' $\triangleright$ Assign another label for the trajectory by concatenating sentences
42:     $\mathcal{D}^L \leftarrow \mathcal{D}^L \cup \{\tau_{LLM, 1:k}, \tau_{concat, 1:k}\}$ $\triangleright$ Add to $\mathcal{D}^L$ with annotation $z_{LLM, 1:k}$ and $z_{concat, 1:k}$.
43:     Add $z_{LLM, 1:k}$ as a new skill to Z.
44: **end procedure**