Ask or Assume? Uncertainty-Aware Clarification-Seeking in Coding Agents

Abstract

As Large Language Model (LLM) agents are increasingly deployed in open-ended domains like software engineering, they frequently encounter *underspecified* instructions that lack crucial context. While human developers naturally resolve underspecification by asking clarifying questions, current agents are largely optimized for autonomous execution. In this work, we systematically evaluate the clarification-seeking abilities of LLM agents on an underspecified variant of SWE-bench Verified. We propose an uncertainty-aware multi-agent scaffold that explicitly decouples underspecification detection from code execution. Our results demonstrate that this multi-agent system using OpenHands + Claude Sonnet 4.5 achieves a 69.40% task resolve rate, significantly outperforming a standard single-agent setup (61.20%) and closing the performance gap with agents operating on fully specified instructions. Furthermore, we find that the multi-agent system exhibits well-calibrated uncertainty, conserving queries on simple tasks while proactively seeking information on more complex issues. These findings indicate that current models can be turned into proactive collaborators, where agents independently recognize when to ask questions to elicit missing information in real-world, underspecified tasks.

1 Introduction

A core property of a good collaborator is the ability to establish and maintain a shared understanding of a goal. In human communication, this is rarely achieved through a single perfectly specified instruction; instead, interlocutors dynamically infer missing context and explicitly signal uncertainty, such as by asking clarification questions (Clark, 1996; Hawkins et al., 2015).

Such behavior of information gathering under uncertainty has, for example, been modeled using Bayesian Optimal Experimental Design (BOED) (Lindley, 1956, 1972; Grand et al., 2024; Handa et al., 2024; Rainforth et al., 2024). In more applied context in the NLP domain, information-seeking behavior has also been studied in tasks like question answering and conversational search (Rao and Daumé III, 2018; Aliannejadi et al., 2019; Zhang and Choi, 2025). However, these paradigms fail to capture the complexity of open-ended, multi-step environments: BOED becomes computationally intractable within massive hypothesis spaces, while most NLP settings involve static or single-turn interactions over bounded contexts.

In contrast, modern AI agents are increasingly deployed in more naturalistic, open-ended domains such as software engineering. For instance, fixing real-world GitHub issues (Jimenez et al., 2024) requires exploring, understanding, and editing large-scale repositories often containing hundreds of files and thousands of lines of code, while remaining aligned with implicit developer intentions. Existing agents are optimized for autonomous completion rather than interactive collaboration, creating a critical gap between user intent and agent execution (METR, 2025; Shen et al., 2025; Wang et al., 2026).

Given these constraints, we investigate the abilities of LLMs to assess their own uncertainty and determine how and when to seek information. Previous work has shown that LLMs can exhibit basic internal calibration (Kadavath et al., 2022), although this behavior is not always robust out of the box (Kapoor et al., 2024). Furthermore, a true agentic collaborator must not only possess this internal calibration, but be able to continuously monitor its uncertainty and proactively initiate dialogue to elicit missing information.

Existing coding environments to investigate information-seeking behaviors focus on isolated function-level tasks with limited exchanges, typically allowing only a single, predetermined round of clarification (Li et al., 2023; Mu et al., 2024; Wu and Fard, 2025). To address this gap, we systemati-

cally evaluate the clarification-seeking abilities of LLM agents within a dynamic, multi-turn software engineering framework. We conduct our evaluation using an underspecified variant of SWE-bench Verified (Chowdhury et al., 2024; Vijayvargiya et al., 2026), where information is removed from the dataset's original GitHub issues. To assess the capabilities of agents to act as question-asking collaborators, we design agent scaffolds where models must rely on their internal uncertainty to decide when to query a user.

Contributions We investigate the information-seeking abilities of LLM agents on underspecified, multi-step coding tasks in an interactive setup. We develop and test both single- and multi-agent frameworks using a frontier LLM backbone (Claude Sonnet 4.5) to assess how agents use their internal uncertainty to deal with underspecification. We find that interactive agents can successfully identify and retrieve missing information, obtaining a resolve rate comparable to an autonomous agent provided with a fully specified issue. Our results also provide evidence that some models exhibit well-calibrated clarification-seeking behavior, accurately recognizing when an issue is already resolvable and refraining from unnecessary interaction. We will release our agent and evaluation code upon publication.

2 Method

2.1 Dataset and Evaluation Framework

To evaluate our approach, we closely follow and adapt the interactive evaluation setting introduced by Vijayvargiya et al. (2026). We conduct our evaluation on an underspecified variant of SWE-bench Verified (Chowdhury et al., 2024). SWE-bench Verified is a human-annotated subset of 500 GitHub issues derived from the standard SWE-bench dataset (Jimenez et al., 2024), filtered to remove examples with unreliable unit tests or inherent underspecification. To create the interactive setting, the fully specified instructions were summarized into underspecified variants using GPT-4o (Hurst et al., 2024), withholding important details while preserving specific repository terminology. Concrete examples are provided in Appendix C.

2.2 Agent Design

Agent Framework We use the OpenHands (Wang et al., 2025) agent framework for all experiments. This framework enables an LLM to control a range of tools for understanding and modifying

Figure 1: Illustration of the uncertainty-aware multi-agent scaffold. The Intent Agent analyzes the state history at each turn to detect underspecification, halting execution to constrain the Main Agent to query the user if missing information is required.

codebases, including editing files and executing Bash/Python scripts. The agent runs inside a secure sandbox environment, where it can iteratively write, execute, and debug code to solve a given task. In our experiments, all agent setups are provided a maximum of 100 iterations to solve the task.

Agent Backbone We evaluate the proprietary model Claude Sonnet 4.5 as the backbone LLM for the coding agent in all experiments (Anthropic, 2025). As a frontier model which performs competitively in many coding benchmarks, it serves as a representative upper bound for current agentic capabilities in software engineering tasks and provides a strong proxy for how existing models perform out of the box in interactive settings.

User Simulator Following recent interactive environments that utilize "oracle" user simulators with access to complete information (e.g., Yao et al., 2025; Zhou et al., 2025), we employ GPT-5.1 (OpenAI, 2025) as the simulated user for all interactive agent configurations. The simulated user is provided with the original, fully specified issue and is constrained to answer queries from the coding agent using only this withheld context. The user

simulator prompt and all additional agent and task prompts are detailed in Appendices A.1–A.3.

2.3 Task Design

2.3.1 Baselines

Following Vijayvargiya et al. (2026), we evaluate our approach on the SWE-bench Verified dataset against three distinct baseline configurations.

FULL This is the standard SWE-bench setting, where the agent is provided with a fully specified version of the GitHub issue. The agent is prohibited from interacting with a user, representing default fully autonomous agent behavior.

HIDDEN In this configuration, the agent is provided with an underspecified version of the GitHub issue where details are missing. As in the FULL baseline, the agent cannot interact with a user.

INTERACTIVE BASELINE The agent receives an underspecified version of the GitHub issue (as with the HIDDEN baseline) but can interact with a simulated user who possesses the fully specified issue. Importantly, the task prompt is modified to explicitly inform the agent that the issue description is incomplete, making it compulsory to query the user before proceeding with any execution. Consequently, this hardcoded instruction forces a predetermined conversational turn with the user rather than evaluating independent information-seeking behavior.

2.3.2 Uncertainty-Aware Agents

To investigate how agents can leverage internal uncertainty to detect and resolve underspecification, we propose two custom scaffolds. While these agents can query the same simulated user as the INTERACTIVE BASELINE, they do not rely on a hardcoded interaction prompt. Instead, both of our scaffolds operate using the default SWE-bench task prompt. Because they receive no prior warning that the issue is underspecified, they must independently identify missing context and query the simulated user only when they determine it is necessary to solve the task.

UNCERTAINTY-AWARE (SINGLE) In this configuration, a single coding agent is prompted at each turn to check for underspecification and, if detected, to query the user. We refer to the agent hereafter as UA-SINGLE.

Figure 2: Task resolve rates (in %) across evaluation settings. Explicitly separating underspecification detection and code execution allows UA-MULTI (69.40%) to significantly outperform UA-SINGLE (61.20%, $p <$ 0.001), closing the gap with the explicitly prompted INTERACTIVE BASELINE. All reported p-values are computed via non-parametric permutation tests.

UNCERTAINTY-AWARE (MULTI) We investigate whether leveraging a multi-agent scaffold can improve underspecification detection. By assigning specialized roles to multiple LLMs, multi-agent systems tackle complex tasks in a coordinated and modular fashion. These systems have shown promise in domains including software development (Hong et al., 2024; Huang et al., 2024; Qian et al., 2024), story generation (Huot et al., 2025), and social simulation (Park et al., 2023). As illustrated in Figure 1, to decouple code execution from underspecification detection, we design a multi-agent scaffold consisting of two agents: the **Main Agent**, equipped with tools to navigate repositories, edit files, and execute code; and the **Intent Agent** that continuously analyzes the state history at each turn to determine if the user's intent or current repository context contains missing information. Whenever the Intent Agent detects underspecification, the Main Agent's next action is constrained to query the user. As in other settings, both agents use Claude Sonnet 4.5 as the LLM backbone. We refer to the agent hereafter as UA-MULTI.

3 Results and Discussion

Figure 2 presents the overall resolve rates. While UA-SINGLE outperforms the HIDDEN baseline (61.20% vs. 54.80%), it falls short of the prompted INTERACTIVE BASELINE (70.40%). However, separating the roles of underspecification detection and code execution in UA-MULTI substantially improves performance. It achieves a 69.40% resolve rate, yielding a significant improvement over UA-SINGLE ($p < 0.001$) and closing the gap with the INTERACTIVE BASELINE ($p = 0.621$) and FULL

Evaluation Setting	Agent Asked ($N = 344$)		Agent Did Not Ask ($N = 156$)	
	# Resolved	Resolve Rate (%)	# Resolved	Resolve Rate (%)
Uncertainty-Aware (Multi)	227	65.99	120	76.92
Full	**229**	**66.57**	**125**	**80.13**
Hidden	153	44.48	121	77.56
Uncertainty-Aware (Single)	192	55.81	114	73.08
Interactive Baseline	**229**	**66.57**	123	78.85

Table 1: Task resolve rates conditioned on whether the UA-MULTI agent queried the user at least once in a trajectory ($N_{ask} = 344$, $N_{not} = 156$). Best performing settings for each subset are highlighted in bold.

($p = 0.458$) configurations.[1]

Agent Uncertainty is Calibrated to Task Difficulty   The success of UA-MULTI can be largely attributed to its ability to discern *when* to ask questions. As shown in Table 1, while it queried the user at least once in fewer overall tasks than UA-SINGLE (N=344 vs. N=369), its interventions were substantially more effective, resolving 65.99% of queried tasks compared to UA-SINGLE's 55.81% and the HIDDEN baseline's 44.48%, while closely matching the INTERACTIVE BASELINE and FULL settings (both 66.57%). Conversely, for the 156 tasks where UA-MULTI refrained from asking, it still achieved a 76.92% resolve rate, indicating it correctly identified tasks that already contained sufficient information to proceed, closely mirroring the HIDDEN baseline's performance on this identical subset (77.56%). This improved calibration is further validated by analyzing agent query rates across the human-annotated task difficulty levels for SWE-bench Verified (Chowdhury et al., 2024). While it queries in fewer tasks overall, UA-MULTI demonstrates an improved ability to distinguish when to ask based on task complexity, with a 9.28% higher ask rate for medium ("15 min – 1 hour") tasks than easy ("<15 min") tasks, whereas UA-SINGLE exhibits only a 2.43% higher ask rate. Both agents also exhibit similarly high ask rates for the most time-intensive tasks (see Appendix B.2 for the full breakdown).

Proactive Information Seeking   Beyond knowing *when* to ask, explicitly isolating the intent-detection role improved *how* the agent interacted. When UA-MULTI engaged in dialogue, it interrogated the user more iteratively to fully resolve un-

certainty, averaging 3.06 queries per task compared to 1.84 for UA-SINGLE. Furthermore, while UA-SINGLE often asked questions near the end of the trajectory, UA-MULTI distributed its queries across the early and middle stages of execution (see Appendix B.1 for a more detailed analysis). This continuous monitoring enabled the multi-agent system to more robustly identify missing context during the trajectory. We provide a comparative analysis which demonstrates this mid-execution follow-up behavior in Appendix B.4.

4   Conclusion

In this work, we investigated the abilities of LLM agents to act as collaborators by independently identifying missing information and seeking clarification in underspecified software engineering tasks. We introduced an uncertainty-aware multi-agent scaffold that isolates the role of underspecification detection. Evaluated on an underspecified variant of SWE-bench Verified, this system successfully identified and retrieved missing information, achieving a 69.40% resolve rate that effectively closed the performance gap with an autonomous agent operating on a fully specified issue.

Our results show that the multi-agent scaffold exhibits well-calibrated information-seeking behavior, accurately recognizing when an issue was already resolvable and refraining from unnecessary interaction on simpler tasks, while proactively querying the user in the earlier phases of the trajectory. Moreover, we demonstrated that this architectural decoupling is necessary; while frontier models possess basic internal calibration, relying on a single agent to handle both code execution and underspecification detection leads to suboptimal information-seeking behavior. These findings present a promising step towards deploying agents not only as autonomous coding assistants, but as proactive collaborators capable of internalizing and navigating real-world underspecification.

---

[1]Our reported resolve rate for the FULL baseline (70.80%) is slightly lower than the official OpenHands result using Claude Sonnet 4.5 as the backbone LLM (74.20%). This is likely due to a combination of running for a maximum of 100 iterations instead of 500, as well as minor system prompt differences.

Limitations

User Simulator Our evaluation relies on an LLM-based user simulator to provide withheld information. While we implemented strict guardrails to prevent unintended leakage and generally observed reasonable simulator responses, recent studies highlight that LLM-simulated users can be unreliable proxies for human behavior, often being unnaturally cooperative and failing to reflect the nuance and variance of real human users (Naous et al., 2026; Seshadri et al., 2026). Results may therefore vary if real human users interact with the agents that we presented in this work.

Prompting and Training While our most successful approach relies on a multi-agent scaffold with tailored prompts for each agent, it demonstrates that frontier models possess the latent capacity to monitor their own uncertainty and proactively seek clarification out of the box. Rather than relying on prompting specialized agents, future work could explore utilizing these successful interaction trajectories to train single models with standard finetuning or reinforcement learning (RL) techniques to natively exhibit this calibrated, information-seeking behavior (e.g., Andukuri et al., 2024; Bhargava et al., 2024; Sun et al., 2025).

Model Generalization and Cost Our experiments were conducted using Claude Sonnet 4.5, a frontier proprietary model. At the time of conducting our experiments, this was the most capable model available for software engineering tasks, allowing us to establish an upper bound for out-of-the-box information-seeking capabilities. However, by relying on a frontier model, our evaluation incurred a non-trivial financial cost (detailed in Appendix D). Furthermore, previous studies have shown that current open-weight models severely lack the internal calibration required to handle interactive underspecification, even with explicit prompting (Vijayvargiya et al., 2026). The current findings may therefore be limited to frontier models and may not directly translate to smaller open-source models.

Ethical Considerations

Our work investigated the ability of LLM agents to monitor their internal uncertainty and seek clarification on underspecified software engineering tasks. While our results demonstrate that uncertainty-aware scaffolds can effectively resolve underspeci-fied GitHub issues, SWE-bench Verified represents only a subset of software engineering tasks. As such, our empirical findings should not be extrapolated to suggest that agents will reliably detect missing information in other, often high-stakes environments, such as security-critical applications without further experimentation.

We also acknowledge the environmental and financial costs associated with the deployment of multi-agent systems. As detailed in our cost breakdown (Appendix D), the increased inference overhead in multi-agent systems is a trade-off that must be weighed against the gains in developer productivity.

AI Use. We used an AI assistant to assist with experimental code generation, and help improve the clarity and flow of the writing while revising the paper. However, all original writing, research conceptualization, methods, experiments, and analyses were performed by the authors, and any AI outputs were carefully verified.

References

Mohammad Aliannejadi, Hamed Zamani, Fabio Crestani, and W. Bruce Croft. 2019. Asking clarifying questions in open-domain information-seeking conversations. In *Proceedings of the 42nd International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 475–484.

Chinmaya Andukuri, Jan-Philipp Fränken, Tobias Gerstenberg, and Noah Goodman. 2024. STaR-GATE: Teaching language models to ask clarifying questions. In *First Conference on Language Modeling (COLM)*.

Anthropic. 2025. Introducing claude sonnet 4.5. Accessed: 2026-03-15.

Aman Bhargava, Cameron Witkowski, Alexander Detkov, and Matt Thomson. 2024. Prompt baking. *arXiv preprint arXiv:2409.13697*.

Neil Chowdhury, James Aung, Chan Jun Shern, Oliver Jaffe, Dane Sherburn, Giulio Starace, Evan Mays, Rachel Dias, Marwan Aljubeh, Mia Glaese, Carlos E. Jimenez, John Yang, Leyton Ho, Tejal Patwardhan, Kevin Liu, and Aleksander Madry. 2024. Introducing SWE-bench verified. Accessed: 2026-03-15.

Herbert H. Clark. 1996. *Using Language*. Cambridge University Press.

Gabriel Grand, Valerio Pepe, Jacob Andreas, and Joshua B. Tenenbaum. 2024. Loose LIPS sink ships: Asking questions in battleship with language-informed program sampling. In *Proceedings of the 46th Annual Meeting of the Cognitive Science Society*.

Kunal Handa, Yarin Gal, Ellie Pavlick, Noah Goodman, Jacob Andreas, Alex Tamkin, and Belinda Z. Li. 2024. Bayesian preference elicitation with language models. *arXiv preprint arXiv:2403.05534*.

Robert X.D. Hawkins, Andreas Stuhlmuller, Judith Degen, and Noah D. Goodman. 2015. Why do you ask? good questions provoke informative answers. In *Proceedings of the 37th Annual Meeting of the Cognitive Science Society*.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. 2024. MetaGPT: Meta programming for a multi-agent collaborative framework. In *The Twelfth International Conference on Learning Representations*.

Dong Huang, Jie M. Zhang, Michael Luck, Qingwen Bu, Yuhao Qing, and Heming Cui. 2024. Agent-Coder: Multi-agent-based code generation with iterative testing and optimisation. *arXiv preprint arXiv:2312.13010*.

Fantine Huot, Reinald Kim Amplayo, Jennimaria Palomaki, Alice Shoshana Jakobovits, Elizabeth Clark, and Mirella Lapata. 2025. Agents' room: Narrative generation through multi-step collaboration. In *The Thirteenth International Conference on Learning Representations*.

Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Ostrow, Akila Welihinda, Alan Hayes, Alec Radford, and 1 others. 2024. GPT-4o system card. *arXiv preprint arXiv:2410.21276*.

Carlos E. Jimenez, John Yang, Alexander Wettig, Shunyu Yao, Kexin Pei, Ofir Press, and Karthik R. Narasimhan. 2024. SWE-bench: Can language models resolve real-world github issues? In *The Twelfth International Conference on Learning Representations*.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, and 1 others. 2022. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*.

Sanyam Kapoor, Nate Gruver, Manley Roberts, Katie Collins, Arka Pal, Umang Bhatt, Adrian Weller, Samuel Dooley, Micah Goldblum, and Andrew G. Wilson. 2024. Large language models must be taught to know what they don't know. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*.

Haau-Sing (Xiaocheng) Li, Mohsen Mesgar, André Martins, and Iryna Gurevych. 2023. Python code generation by asking clarification questions. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 14287–14306, Toronto, Canada. Association for Computational Linguistics.

Dennis V Lindley. 1956. On a measure of the information provided by an experiment. *The Annals of Mathematical Statistics*, 27(4):986–1005.

Dennis Victor Lindley. 1972. *Bayesian Statistics: A Review*. Society for Industrial and Applied Mathematics.

METR. 2025. Research update: Algorithmic vs. holistic evaluation. Accessed: 2026-03-15.

Fangwen Mu, Lin Shi, Song Wang, Zhuohao Yu, Binquan Zhang, ChenXue Wang, Shichao Liu, and Qing Wang. 2024. ClarifyGPT: A framework for enhancing LLM-based code generation via requirements clarification. *Proceedings of the ACM on Software Engineering*, 1(FSE):2332–2354.

Tarek Naous, Philippe Laban, Wei Xu, and Jennifer Neville. 2026. Flipping the dialogue: Training and evaluating user language models. In *The Fourteenth International Conference on Learning Representations*.

OpenAI. 2025. GPT-5.1: A smarter, more conversational ChatGPT. Accessed: 2026-03-15.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the ACM Conference on Human Factors in Computing Systems (CHI)*, pages 1–22.

Chen Qian, Wei Liu, Hongzhang Liu, Nuo Chen, Yufan Dang, Jiahao Li, Cheng Yang, Weize Chen, Yusheng Su, Xin Cong, Juyuan Xu, Dahai Li, Zhiyuan Liu, and Maosong Sun. 2024. ChatDev: Communicative agents for software development. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 15174–15186, Bangkok, Thailand. Association for Computational Linguistics.

Tom Rainforth, Adam Foster, Desi R Ivanova, and Freddie Bickford Smith. 2024. Modern bayesian experimental design. *Statistical Science*, 39(1):100–114.

Sudha Rao and Hal Daumé III. 2018. Learning to ask good questions: Ranking clarification questions using neural expected value of perfect information. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2737–2746, Melbourne, Australia. Association for Computational Linguistics.

Preethi Seshadri, Samuel Cahyawijaya, Ayomide Odumakinde, Sameer Singh, and Seraphina Goldfarb-Tarrant. 2026. Lost in simulation: LLM-simulated users are unreliable proxies for human users in agentic evaluations. In *Algorithmic Fairness Across Alignment Procedures and Agentic Systems*.

Shannon Zejiang Shen, Valerie Chen, Ken Gu, Alexis Ross, Zixian Ma, Jillian Ross, Alex Gu, Chenglei Si, Wayne Chi, Andi Peng, Jocelyn J. Shen, Ameet Talwalkar, Tongshuang Wu, and David Sontag. 2025. Completion ≠ collaboration: Scaling collaborative effort with agents. In *Socially Responsible and Trustworthy Foundation Models at NeurIPS 2025*.

Weiwei Sun, Xuhui Zhou, Weihua Du, Xingyao Wang, Sean Welleck, Graham Neubig, Maarten Sap, and Yiming Yang. 2025. Training proactive and personalized LLM agents. *arXiv preprint arXiv:2511.02208*.

Sanidhya Vijayvargiya, Xuhui Zhou, Akhila Yerukola, Maarten Sap, and Graham Neubig. 2026. Interactive agents to overcome underspecificity in software engineering. In *The Fourteenth International Conference on Learning Representations*.

Xingyao Wang, Boxuan Li, Yufan Song, Frank F. Xu, Xiangru Tang, Mingchen Zhuge, Jiayi Pan, Yueqi Song, Bowen Li, Jaskirat Singh, and 1 others. 2025. OpenHands: An open platform for AI software developers as generalist agents. In *The Thirteenth International Conference on Learning Representations*.

Zora Zhiruo Wang, John Yang, Kilian Lieret, Alexa Tartaglini, Valerie Chen, Yuxiang Wei, Zijian Wang Lingming Zhang, Karthik Narasimhan, Ludwig Schmidt, Graham Neubig, and 1 others. 2026. Position: Humans are missing from ai coding agent research. Accessed: 2026-03-15.

Jie JW Wu and Fatemeh H. Fard. 2025. HumanEval-Comm: Benchmarking the communication competence of code generation for llms and llm agents. *ACM Transactions on Software Engineering and Methodology*, 34(7):1–42.

Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik R. Narasimhan. 2025. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. In *The Thirteenth International Conference on Learning Representations*.

Michael JQ Zhang and Eunsol Choi. 2025. Clarify when necessary: Resolving ambiguity through interaction with LMs. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 5541–5558, Albuquerque, New Mexico. Association for Computational Linguistics.

Yifei Zhou, Song Jiang, Yuandong Tian, Jason Weston, Sergey Levine, Sainbayar Sukhbaatar, and Xian Li. 2025. SWEET-RL: Training multi-turn LLM agents on collaborative reasoning tasks. *arXiv preprint arXiv:2503.15478*.

A Task and Scaffold Prompts

A.1 Task Prompts

Figure 3 presents the SWE-bench task prompt template. The FULL baseline is provided with this prompt including the original, fully specified issue. The HIDDEN baseline and both UNCERTAINTY-AWARE scaffolds receive it with the underspecified issue. Conversely, only the INTERACTIVE BASELINE receives the augmented variant (highlighted in bold in Figure 3), which explicitly mentions that there is missing information and instructs the agent to first ask questions before proceeding.

A.2 Agent Scaffold Prompts

Figure 4 shows specific prompts required for the uncertainty-aware agents.

For UNCERTAINTY-AWARE (SINGLE), we provide a recurring reminder prompt to the agent at each turn (Figure 4A) to assess for underspecification. If the agent detects underspecification, it is encouraged to use the `clarify` tool to query the user.

For UNCERTAINTY-AWARE (MULTI), we employ a customized system prompt for the Intent Agent (Figure 4B). This prompt instructs the agent to analyze the state history at each turn to detect underspecification. Rather than performing code edits, the Intent Agent is constrained to identifying missing information and determining when the Main Agent must pause execution to seek clarification from the simulated user.

A.3 User Simulator Prompt

Figure 5 shows the prompt provided to the user simulator, adapted from the prompt in Vijayvargiya et al. (2026). Initial experiments revealed that the simulated user occasionally provided misaligned guidance due to a lack of awareness regarding the specific constraints of our evaluation environment (i.e., OpenHands agent in SWE-bench). To prevent the simulator from misleading the agent or leaking unintended information, we augmented the original prompt with the following environment-specific guardrails:

- **Preventing test modifications (Rule 5):** In SWE-bench, test files should not be modified by the agent. Because the original simulated user lacked this context, it failed to correct the agent when it attempted to edit files inside the `/testbed` directory. Rule 5 was added to instruct the simulated user to explicitly remind the agent of this if it asked about changing test files.

- **Resolving directory mismatches (Rule 6):** Agents in OpenHands operate within a designated `/workspace` directory, whereas SWE-bench imports and runs tests in a separate `/testbed` directory. Agents often became confused when changes in `/workspace` were not reflected in the tests run in `/testbed`. Rule 6 was added to instruct the simulated user to explicitly remind the agent of this if it asked why its edits weren't being reflected.

B Question Analyses

B.1 Question Statistics

Table 2 provides a detailed breakdown of clarification-seeking behavior across the three interactive agent configurations.

Regarding the amount of interaction, the INTERACTIVE BASELINE initiates queries in nearly all tasks ($N=496$), but averages slightly more than one single query (1.02). Conversely, the uncertainty-aware agents demonstrate more conservative query initiation but greater query volume. UNCERTAINTY-AWARE (MULTI) initiated queries in 344 tasks, engaging in significantly more iterative dialogue (averaging 3.06 queries per task). UNCERTAINTY-AWARE (SINGLE) initiated queries in 369 tasks, but queried fewer times per task (1.84).

The length of these interactions also varies. The INTERACTIVE BASELINE generates highly verbose queries (averaging 251.33 tokens) and receives correspondingly long answers (averaging 415.53 tokens), reflecting a strategy to ask for all potentially missing information upfront. In contrast, UNCERTAINTY-AWARE (MULTI) utilizes the most concise queries (171.57 tokens) and receives the shortest answers (173.65 tokens). This conciseness supports the observation that the multi-agent scaffold often asks highly targeted, context-specific questions based on intermediate tool observations (e.g., see the mid-trajectory example in Figure 6). UNCERTAINTY-AWARE (SINGLE) falls between the two, with average query and answer lengths of 181.35 and 229.76 tokens, respectively.

Finally, we analyze the temporal distribution of these queries. We categorize the timing of each question based on its event ID position within the agent trajectory, divided into deciles:

SWE-bench Task Prompt

<uploaded_files>
/workspace/{{ workspace_dir_name }}
</uploaded_files>

I've uploaded a python code repository in the directory {{ workspace_dir_name }}. Consider the following issue description:

<issue_description>
{{ instance.problem_statement }}
</issue_description>

Can you help me implement the necessary changes to the repository so that the requirements specified in the <issue_description> are met?

I've already taken care of all changes to any of the test files described in the <issue_description>. This means you DON'T have to modify the testing logic or any of the tests in any way!

Also the development Python environment is already set up for you (i.e., all dependencies already installed), so you don't need to install other packages. Your task is to make the minimal changes to non-test files in the /workspace/{{ workspace_dir_name }} directory to ensure the <issue_description> is satisfied.

I have not provided all the necessary details about the issue and I have some hidden details that are helpful. Please ask me specific questions using non-code commands to gather the relevant information that I have to help you solve the issue. Ensure you have all the details you require to solve the issue.
You have a limited number of turns. Do NOT interact with me more than three times so as to maximize the number of turns you have to work on the solution.

Then, follow these phases to resolve the issue:
[...]

Figure 3: The base SWE-bench task prompt provided to the agents. The highlighted block in bold indicates the explicit clarification instructions added in the interactive variant, provided *only* to the INTERACTIVE BASELINE.

Agent	Interaction Volume			Token Length		Timing Distribution (%)		
	# Queried Tasks	Total Queries	Avg # Q/Task	Avg Q	Avg A	Early	Mid	Late
Uncertainty-Aware (Multi)	344	1053	3.06	171.57	173.65	41.8	43.4	14.8
Uncertainty-Aware (Single)	369	679	1.84	181.35	229.76	25.0	31.1	43.9
Interactive Baseline	496	508	1.02	251.33	415.53	97.6	1.4	1.0

Table 2: Question statistics across evaluation settings. *# Queried Tasks* denotes the number of tasks where the agent initiated at least one query turn. Timing distributions are categorized into Early (1st–3rd decile), Mid (4th–7th decile), and Late (8th–10th decile) based on the question's event ID position within the trajectory. Overall, the data illustrates that the INTERACTIVE BASELINE relies on verbose, upfront queries, whereas UNCERTAINTY-AWARE (MULTI) engages in more concise, iterative, and evenly distributed information-seeking behavior.

"Early" (1st–3rd decile), "Mid" (4th–7th decile), and "Late" (8th–10th decile). The INTERACTIVE BASELINE asks almost all questions early on, with 97.6% of its questions occurring in the Early stage. UNCERTAINTY-AWARE (SINGLE) heavily skews towards asking near the end of the trajectory (43.9% Late), suggesting it often attempts codebase modifications before recognizing an information gap. In contrast, UNCERTAINTY-AWARE (MULTI) exhibits a more balanced and proactive strategy; its queries are distributed smoothly across the Early (41.8%) and Mid (43.4%) stages, suggesting that explicitly decoupling the underspecification detection role allows the agent to continuously monitor for underspecification and seek information throughout the trajectory.

B.2 Query Frequency by Task Difficulty

Difficulty Level	# Tasks	Ask Rate (%)	
		UA-SINGLE	UA-MULTI
<15 min fix	194	71.13	62.37
15 min – 1 hour	261	73.56	71.65
1–4 hours	42	85.71	78.57
>4 hours	3	100.00	100.00

Table 3: Ask rates by SWE-bench Verified difficulty (estimated time-to-fix) for uncertainty-aware (UA) agents.

To evaluate whether the agents appropriately calibrate their uncertainty to the complexity of the task, we mapped their querying behavior to the human-annotated difficulty levels provided by SWE-bench Verified (Chowdhury et al., 2024). Dif-

ficulty is categorized by the estimated time required for a human developer to fix the issue.

Table 3 presents the ask rates for both UNCERTAINTY-AWARE (SINGLE) and UNCERTAINTY-AWARE (MULTI). UNCERTAINTY-AWARE (MULTI) exhibits a greater difference in ask rates than UNCERTAINTY-AWARE (SINGLE), particularly between the "<15 min fix" and "15 min – 1 hour" levels (9.28% vs. 2.43% increase). Notably, both scaffolds exhibit an increased ask rate for the harder tasks with both agents reaching a 100% interaction rate on the most difficult ">4 hours" tasks.

B.3 Conditional Resolve Rates for UNCERTAINTY-AWARE (SINGLE)

Table 4 details the task resolve rates conditioned on whether the UNCERTAINTY-AWARE (SINGLE) agent chose to interact with the user. When UNCERTAINTY-AWARE (SINGLE) chose to ask questions (369 of 500 tasks), it successfully elicited missing information, resolving 216 tasks compared to only 175 for the HIDDEN baseline on the same subset. Conversely, on the 131 tasks where the agent refrained from interaction, its performance closely mirrored the HIDDEN baseline (90 vs. 99 resolved tasks). These results indicate that UNCERTAINTY-AWARE (SINGLE) can effectively detect when missing information is critical for task resolution, although the performance gap with other configurations suggests that its internal calibration remains imperfect compared to UNCERTAINTY-AWARE (MULTI).

B.4 Qualitative Example of Agent Interaction

The transcripts in Figure 6 illustrate the distinct information-seeking strategies employed by the agents for the `pytest-dev__pytest-7324` task, which involves resolving a `pytest`-related Python interpreter crash. As highlighted in bold, while the baseline relies on more generic questions, both uncertainty-aware agents asks more specific, technical questions. In particular, note how the multi-agent scaffold uniquely engages in a mid-trajectory follow-up query after observing a test failure.

C Underspecified Issue Examples

Figure 7 provides a comparison of the original and underspecified issue descriptions for two tasks. In creating the underspecified examples, specific details such as code snippets, file paths/line references and stack traces are removed, while relevant terminology to describe the issue at a high level are preserved.

D Computing Costs

Table 5 details the total inference costs for each evaluation setting. All agent inference calls (using Claude Sonnet 4.5) were executed via the Anthropic API. While the multi-agent scaffold more than doubles the total inference cost compared to the single-agent baselines, the absolute financial cost per task remains negligible. We argue that this increase in compute expenditure is a highly favorable trade-off; by proactively resolving underspecification and significantly increasing the overall task resolve rate, the multi-agent setup ultimately saves substantial human developer time and effort that would otherwise be spent on debugging solutions that are misaligned with the original intent.

	Agent Asked ($N = 369$)		Agent Did Not Ask ($N = 131$)	
Evaluation Setting	**# Resolved**	**Resolve Rate (%)**	**# Resolved**	**Resolve Rate (%)**
Uncertainty-Aware (Single)	216	58.54	90	68.70
Full	249	67.48	**105**	**80.15**
Hidden	175	47.43	99	75.57
Uncertainty-Aware (Multi)	245	66.40	102	77.86
Interactive Baseline	**252**	**68.29**	100	76.34

Table 4: Task resolution rates conditioned on whether the UNCERTAINTY-AWARE (SINGLE) agent queried the user at least once in a trajectory ($N_{ask} = 369$, $N_{not} = 131$). Best performing settings for each subset are highlighted in bold.

Setting	**Total Cost ($)**	**Avg Cost / Task ($)**
Full	817.02	1.63
Hidden	899.43	1.80
Interactive Baseline	697.88	1.40
Uncertainty-Aware (Single)	1017.34	2.03
Uncertainty-Aware (Multi)	1748.08	3.50

Table 5: Anthropic API costs (in USD) across evaluation settings on SWE-bench Verified.

Uncertainty-Aware Agent Scaffold Prompts

A. UNCERTAINTY-AWARE (SINGLE) Reminder Prompt

Before selecting your next tool or drafting a reply, first reason explicitly about whether you have enough information. After stating that reasoning, write a line formatted as `Ambiguity assessment: <clear|ambiguous>`. If the assessment is `ambiguous`, immediately call the `clarify` tool with questions for the user. If it is `clear`, proceed normally.

B. UNCERTAINTY-AWARE (MULTI) Intent Agent Prompt

You are Intent Agent, a specialized OpenHands agent. Your sole purpose is to assess at a given turn whether there exists ambiguity or key missing information which may impact the work of the main agent trying to solve a user's task.

<ROLE>

- Your primary role is to interpret, at any given point, the conversation history so far. This includes user messages, as well as main agent actions and observations.

- Keep in mind these questions when you are performing the analysis:

  1. What is the intended goal?
  2. What is missing, ambiguous, or assumption-heavy?
  3. What must be clarified before any further code or tool executions can happen?

</ROLE>

<WORKFLOW>

1. Carefully read the provided conversation history, including user messages, main agent actions, and observations.

2. Enumerate any ambiguities, missing information, or assumptions that could impact the main agent's ability to successfully complete the user's task.

3. Finally, call the `clarify_decision` tool, producing a structured JSON output only indicating with a boolean whether or not clarification is required ('needs_clarification'), and providing the reasons if necessary. if the main agent attempts to read a file that does not exist, you would output something like:

   ```
   {
     'needs_clarification': true,
     'reasons': 'The main agent attempted to read a file that does not exist,
         indicating possible misunderstanding of the file structure.'
   }
   ```

</WORKFLOW>

<EXTRA_GUIDELINES>

- Be clear and concise in your reasoning, avoiding unnecessary complexity. Keep your reasoning short, only 30-50 words.

- You will be provided with a summary of the conversation history so far, including user messages, main agent actions, and observations. Some of these may be truncated with "...".

- If you ever see a user message of the form "1a, 2b, 3c", this refers to answers for the main agent's previous clarifying questions.

</EXTRA_GUIDELINES>

Figure 4: Prompts required for the custom uncertainty-aware agent scaffolds. Part A shows the reminder prompt for the UNCERTAINTY-AWARE (SINGLE) agent at each turn. Part B shows the system prompt for the specialized Intent Agent in the UNCERTAINTY-AWARE (MULTI) agent scaffold.

User Simulator Prompt

You are a GitHub user reporting an issue. Here are the details of your issue and environment:

Issue: `{issue}`

Files relative to your current directory: `{files}`

Your task is to respond to questions from a coder who is trying to solve your issue. The coder has a summarized version of the issue you have. Follow these rules:

1. If the coder asks a question that is directly related to the information in the issue you have, provide that information.

2. Always stay in character as a user reporting an issue, not as an AI assistant.

3. Keep your responses concise and to the point.

4. The coder has limited turns to solve the issue. Do not interact with the coder beyond 3 turns.

5. If the coder asks about modifying test files, remind them that all changes to any of the test files described in the issue are already handled and should not be further modified.

6. If the coder says that their fixes aren't reflected in tests or asks why the expected test behavior isn't changing, remind them that `/testbed` is where tests are imported and run, but they should make their final edits in `/workspace`.

Respond with "I don't have that information" if the question is unrelated or you're unsure.

Figure 5: The prompt provided to the user simulator, including specific guardrails to prevent unintended test modifications (rule 5) and resolve environment directory mismatches (rule 6).

Figure 6: Comparison of user-agent interactions on the `pytest-dev__pytest-7324` task. Both the INTERACTIVE BASELINE and the UNCERTAINTY-AWARE (SINGLE) agent successfully identify missing information but group all their queries into a single, upfront interaction turn. Bold text highlights INTERACTIVE BASELINE's generic queries versus the more specific, technical queries of UNCERTAINTY-AWARE (SINGLE).

Agent (Turn 1 - Early Stage): I need more specific information to understand and fix the issue properly:

1. Can you provide the specific Python expression that causes the crash? For example, is it something like **assert __debug__ or a specific constant name**?

2. Do you have the **actual error message** or assertion failure from Python's compiler/interpreter that appears on a debug build?

3. Is there a **specific test file or test case** that was added to reproduce this issue?

4. What is the **'known issue'** this is linked to? Is it a Python bug tracker issue or a GitHub issue?

User:

1. The specific expression is just Expression.compile("False"), i.e. the string "False" being compiled by Expression.compile in src/_pytest/mark/expression.py.

2. Yes, on a debug build it crashes with:

```
python: Python/compile.c:3559: compiler_nameop: Assertion
    `!_PyUnicode_EqualToASCIIString(name, "None") &&
     !_PyUnicode_EqualToASCIIString(name, "True") &&
     !_PyUnicode_EqualToASCIIString(name, "False")' failed.
[1] 29440 abort (core dumped) python
```

3. There is a test covering this scenario, but all changes to the test files are already handled and shouldn't be modified further for this task.

4. The linked known issue is a Python bug tracker issue: bpo-40870 (https://bugs.python.org/issue40870).

Agent (Turn 2 - Mid Stage, Execution Phase): The **test still fails after modifying the source code**. This suggests either a caching issue or the module hasn't been reloaded. Let me check if the changes were saved correctly and try reloading.

1. **Should I continue debugging** why the changes aren't taking effect?

User: No, you don't need to keep debugging that part. Remember that the tests are imported and run from /testbed, but your final code changes should be made in /workspace. If your fixes aren't reflected in the tests, it's likely due to that setup rather than a caching issue.

Figure 6: (continued). Unlike the single-agent setups, the multi-agent framework successfully engages in additional late-stage, iterative clarification following a test failure on the pytest-dev__pytest-7324 task.

pytest-dev__pytest-7324

Original:

Pytest crashes the interpreter on debug build for 3.8+.
Short reproducer:

```
>>> Expression.compile("False")
python: Python/compile.c:3559: compiler_nameop: Assertion `!_PyUnicode_EqualToASCIIString(name, "None
    ") &&
!_PyUnicode_EqualToASCIIString(name, "True") &&
!_PyUnicode_EqualToASCIIString(name, "False")' failed.
[1]    29440 abort (core dumped)  python
```

Related issue: https://bugs.python.org/issue40870

- -

Underspecified:

There is an issue where running a specific Python expression using Pytest on a debug build of Python 3.8 or later causes the interpreter to crash. This is due to an assertion failure in the Python compiler related to handling certain constant names. The problem is linked to a known issue aimed at improving this behavior.

scikit-learn__scikit-learn-26194

Original:

Thresholds can exceed 1 in roc_curve while providing probability estimate. While working on https://github.com/scikit-learn/scikit-learn/pull/26120, I found out that something was odd with roc_curve that returns a threshold greater than 1. A non-regression test (that could be part of sklearn/metrics/tests/test_ranking.py) could be as follow:

```python
def test_roc_curve_with_probablity_estimates():
    rng = np.random.RandomState(42)
    y_true = rng.randint(0, 2, size=10)
    y_score = rng.rand(10)
    _, _, thresholds = roc_curve(y_true, y_score)
    assert np.logical_or(thresholds <= 1, thresholds >= 0).all()
```

The reason is due to the following:
(https://github.com/scikit-learn/scikit-learn/blob/e886ce4e1444c61b865e7839c9cff5464ee20ace/sklearn/metrics/_ranking.py#L1086)
Basically, this is to add a point for fpr=0 and tpr=0. However, the + 1 rule does not make sense in the case y_score is a probability estimate.
I am not sure what would be the best fix here. A potential workaround would be to check thresholds.max() <= 1 in which case we should clip thresholds to not be above 1.

- -

Underspecified:

There is an issue with the roc_curve function where thresholds can exceed 1 when using probability estimates. This behavior is unexpected and may be due to the way additional points are added to the curve. A test case demonstrates this anomaly, and a potential workaround involves clipping the thresholds. However, the best solution is still under consideration.

Figure 7: Comparison of original (fully specified) and underspecified issues for two SWE-bench Verified tasks, pytest-dev__pytest-7324 and scikit-learn__scikit-learn-26194.