KNOWLEDGE-IN-CONTEXT: TOWARDS KNOWLEDGEABLE SEMI-PARAMETRIC LANGUAGE MODELS

ABSTRACT

Fully-parametric language models generally require a huge number of model parameters to store the necessary knowledge for solving multiple natural language tasks in zero/few-shot settings. In addition, it is hard to adapt to the evolving world knowledge without the costly model re-training. In this paper, we develop a novel semi-parametric language model architecture, *Knowledge-in-Context (KiC)*, which empowers a parametric text-to-text language model with a knowledge-rich external memory. Specifically, the external memory contains six different types of knowledge: entity, dictionary, commonsense, event, script, and causality knowledge. For each input instance, the KiC model adaptively selects a knowledge type and retrieves the most helpful pieces of knowledge. The input instance along with its knowledge augmentation is fed into a text-to-text model (e.g., T5) to generate the output answer, where both the input and the output are in natural language forms after prompting. Interestingly, we find that KiC can be identified as a special mixture-of-experts (MoE) model, where the knowledge selector plays the role of a router that is used to determine the sequence-to-expert assignment in MoE. This key observation inspires us to develop a novel algorithm for training KiC with an instance-adaptive knowledge selector. As a knowledge-rich semi-parametric language model, KiC only needs a much smaller parametric part to achieve superior zero-shot performance on unseen tasks. By evaluating on 40+ different tasks, we show that KiC_{Large} with 770M parameters easily outperforms large language models (LMs) that are 4-39x larger by a large margin. We also demonstrate that KiC exhibits emergent abilities at a much smaller model scale compared to the fully-parametric models.

1 INTRODUCTION

Recently, large-scale fully-parametric language models have achieved great success in solving natural language processing (NLP) tasks (Radford et al., 2019; Brown et al., 2020; Chowdhery et al., 2022; Kaplan et al., 2020). However, they generally require a huge number of model parameters to store the necessary knowledge for solving multiple NLP tasks in the zero/few-shot setting. Meanwhile, their problem solving capability only emerges after reaching a certain model scale (Wei et al., 2022). In addition, large parametric language models are hard to adapt to the evolving world knowledge without expensive model re-training. To overcome these challenges, there has been an increasing interest in developing semi-parametric language models, where a parametric language model is augmented with an external memory containing a large amount of text chunks (Borgeaud et al., 2022; Izacard et al., 2022; Khandelwal et al., 2019; Zhong et al., 2022). Although these semi-parametric approaches are shown to be more effective than their much larger parametric counterparts, there remain several challenges. The first challenge is that useful knowledge pieces are generally *sparsely* distributed over a large textual corpus. Therefore, it is difficult to locate and retrieve the correct text chunk that contains the right knowledge to complement a particular input instance. Second, it is difficult to determine the proper text chunk granularity to cover the desired knowledge. Thus, people usually use oversized text chunks to build indexing, which makes it even harder to determine whether knowledge is contained. On the other hand, there have been a rich collection of knowledge resources such as diverse knowledge graphs, where different kinds of knowledge are *densely* and *compactly* organized in structured or semi-structured forms. In this paper, we leverage these knowledge resources to

construct a semi-parametric language model, by simply using off-shelf encoders and retrievers to index and search the external memory.

In particular, our primary contribution is developing a novel semi-parametric language model architecture, *Knowledge-in-Context (KiC)*, that is fueled by a large *knowledge-rich* external memory (Section 2). Specifically, the memory covers six broad categories of knowledge types: entity, dictionary, commonsense, event, script and causality (Section 2.2). Our comprehensive analysis reveals that a wide range of natural language tasks (31 out of 35 tasks) benefit from adding knowledge, where different knowledge resources help with different subsets of tasks. Interestingly, some tasks are even improved by 10%+ after adding suitable knowledge. To adaptively utilize knowledge, we exploit KiC to dynamically identify the most useful knowledge pieces for each input instance from a certain task and places them in the current context for answering the question. We adopt a single text-to-text transformer (e.g., T5) to generate the output answer from the input. Specifically, we append the retrieved knowledge pieces to the input instance and convert them into a natural language sequence with prompt templates. It is then fed into the text-to-text model to generate the output answer (also in natural language). The major advantage of such a text-to-text paradigm is that it handles multiple natural language tasks with the same interface and can also generalize to unseen tasks (Sanh et al., 2022; Raffel et al., 2020). Moreover, we find this training paradigm is suitable for our model design as it can teach our KiC model to learn how to select and use knowledge through various seen language tasks and then generalize well to use knowledge for solving unseen tasks. Our experimental analysis further shows that such instance-adaptive (context-dependent) knowledge augmentation is critical to the success of KiC model. However, due to the inherent discrete nature, it is difficult to train KiC in a fully differentiable manner to select the correct knowledge category for each instance. To solve this problem, we find that KiC can be reformulated as a special mixture-of-experts (MoE) model (Jacobs et al., 1991; Jordan & Jacobs, 1994; Shazeer et al., 2017; Fedus et al., 2022), where the knowledge selector is identified as the router that is used to determine the sequence-to-expert assignment in MoE (Section 2.3). Furthermore, the memory partition corresponding to each knowledge category together with the text-to-text model can be recognized as a special semi-parametric expert in MoE. This key observation inspires us to develop a novel learning algorithm to train KiC with instance-adaptive knowledge selection capabilities.

In our experiments (Section 3), we adopt the same setting as T0 (Sanh et al., 2022), where we train KiC models on a collection of tasks and then evaluate on another set of unseen tasks in a zero-shot manner. As a knowledge-rich semi-parametric language model, KiC only needs a much smaller parametric part to achieve superior zero-shot performance on unseen tasks. With only 0.77B parameters, KiC_{Large} outperforms zero-shot baseline models such as GPT-NeoX-20B or OPT-30B that are 25-38x larger. It achieves 39.4% zero-shot performance on MMLU benchmark, very close to the GPT-3's 43.9% that has 175B parameters (227x larger) and uses 5 training examples. Meanwhile, KiC exhibits emergent abilities at a much smaller model scale compared to the fully-parametric models. Finally, we discuss related work in Section 4 and conclude our paper with some future directions in Section 5.

2 KNOLWEDGE-IN-CONTEXT LANGUAGE MODEL

2.1 OVERVIEW

In this section, we introduce our proposed KiC language model, which augments a parametric text-to-text Transformer (backbone) model with a knowledge-rich external memory (Figure 1). Overall, KiC consists of the following modules: (i) a parametric text-to-text backbone, (ii) an external knowledge memory with a retriever, and (iii) a knowledge selector. As shown in Figure 1, for each input instance, the knowledge selector first selects a particular knowledge category based on the input context and then retrieves the most helpful knowledge pieces for solving the current problem. The retrieved knowledge is used to complement the input context via concatenation, which is further converted into a natural language sequence using prompt templates. Then, the prompted textual inputs are fed into the text-to-text backbone model, which generates the output solution in natural language. The text-to-text backbone model can be any encoder-decoder models (e.g., T5, BART) or decoder-only models (e.g., GPT, PaLM). For convenience and without loss of generality, we adopt T5 as our backbone model throughout this paper. In the following subsections, we will explain in detail how to

Figure 1: Overview of the KiC model architecture. It is augmented with a knowledge-rich memory that contains diverse categories of knowledge. For each input instance, KiC first selects a particular knowledge category and retrieves the most helpful knowledge pieces to augment the input. It then feeds the prompted input into a text-to-text backbone module (e.g., T5) to generate the output answer.

construct the knowledge memory along with its retriever (Section 2.2) as well as how to learn the entire KiC model in a fully-differentiable end-to-end manner (Section 2.3).

2.2 EXTERNAL KNOWLEDGE MEMORY AND RETRIEVER

Knowledge-rich external memory A significant advantage of semi-parametric models over fully-parametric ones is that we could flexibly change the knowledge resources. As shown in Table 6, structured knowledge resources can often provide more relevant and accurate knowledge than plain text. In this work, we include the following popular representative knowledge resources. We summarize the number of knowledge instances from each resource in Appendix Table 5.

- **Dictionary:** We consider dictionary (lexical) knowledge, which records definitions and example sentences of English words. In our experiment, we leverage the largest open-source dictionary Wiktionary[1] as the lexical knowledge resource. Specifically, we use the Wiktionary dump dated April.30 2022 that contains 1.3M word senses and 470K example sentences for 1M words/phrases.

- **Commonsense:** Besides the lexical knowledge, we also include commonsense knowledge from ConceptNet (Liu & Singh, 2004), which covers broad knowledge in our daily life. In ConceptNet, all knowledge are in the format of triplets with human-defined relations (e.g., *"bird"*-CAPABLEOF-*"fly"*). We follow previous works (Zhang et al., 2020) to include the core 600K high-quality triplets.

- **Entity:** We cover named entity knowledge in Wikipedia and Wikidata (Vrandečić & Krötzsch, 2014). Given an entity (e.g., *"United States"*), we convert each property of it to be a separate triplet (e.g., *"United States"*-CAPITAL-*"Washington D.C."*) such that the format is same as other knowledge resources. In addition to structured entity knowledge, we also include all Wikipedia sentences related to the entity.

- **Event:** We cover knowledge about daily events with human-constructed (i.e., ATOMIC (Hwang et al., 2021) and GLUCOSE (Mostafazadeh et al., 2020)) or auto-extracted event knowledge graphs (i.e., ASER (Zhang et al., 2022a)). Similar to commonsense knowledge, all event knowledge graphs store knowledge in the triplet format, where relations are human-defined or discourse relations, the head and the tail are events. An ASER example is *"I am hungry"*-BEFORE-*"I eat food"*.

- **Script:** Besides the knowledge covered by pre-defined relations, we also include script knowledge to cover more complex ones. We use the script knowledge from (Sun et al., 2022), which can also be regarded as a special kind of commonsense knowledge. We use 325K pieces of script knowledge, each containing a pair of related verbal and nonverbal information (e.g., *"Of course not. I'm going......to his house."* and *"thinking"*) as well as the context where they situate. Given a query, we retrieve the most relevant scenario as external knowledge.

- **Causality:** The last external knowledge resource we include is the auto-extracted causal knowledge CausalBank Li et al. (2020), which collects large-scale English sentences expressing cause-effect relations. It consists of 133M because mode sentences (i.e., sentences captured by 12 patterns such as *"because"*, *"caused by"*, etc.) and 181M therefore mode sentences (i.e., sentences captured by 19 patterns such as *"therefore"*, *"result in"*, etc.).

---

[1]https://en.wiktionary.org/wiki/Wiktionary:Main_Page

Figure 2: KiC model can be equivalently formulated as a mixture-of-experts (MoE) architecture. The knowledge selector can be identified as a router that is used to determine the sequence-to-expert assignment in MoE. Each expert is made up of the (shared) text-to-text model and the external memory of a particular knowledge category. Therefore, each expert is in itself a stand-alone semi-parametric language model specialized in a certain type of knowledge. To allow the option of not using any knowledge, we also include a "generalist" module, which is the (shared) text-to-text model alone.

Note that although the effectiveness of knowledge such as entity and dictionary knowledge has been demonstrated on a wide range of tasks (e.g., (Zhang et al., 2019b)), other types of knowledge such as commonsense and script knowledge are only used for carefully selected tasks that tend to require these types of knowledge (Ye et al., 2019; Qiu et al., 2019).

Retriever We use the target word as the key and definition as the value for dictionary knowledge and use every utterance as the key and the background context as the value for script knowledge. To effectively retrieve knowledge from the other four knowledge resources, we follow the previous work Borgeaud et al. (2022) to use dense retrieval techniques. Specifically, we convert all knowledge pieces into natural language sentences as values (e.g., *I am hungry before I eat food.*) and then encode all sentences into dense vectors as keys using a SOTA sentence encoder MPNet Song et al. (2020).Given a query, we encode it with the same sentence encoder model and then retrieve the most relevant knowledge with the maximum inner product search (MIPS) search which is able to reduce search complexity from $O(n)$ to $O(\log n)$. In KiC, we employ SCaNN Guo et al. (2020) as the MIPS search algorithm.

2.3 KiC: A Mixture of Semi-Parametric Experts

As we will show in our comprehensive analysis (Table 1), for a particular task, some knowledge categories help the performance while others might hurt. For this reason, it is critical to dynamically select the correct knowledge type in order to facilitate the solution of the problem. In our work, instead of using *task-dependent* knowledge selection, we consider a more fine-grained *instance-dependent* strategy: we adaptively choose the knowledge based on each input instance. We now proceed to explain how KiC learns to make such instance-dependent knowledge selection.

Note that the discrete decision made by the knowledge selector will seep into the overall neural architecture in the form of a discrete latent variable. There could be several alternative methods (such as reinforcement learning (Sutton & Barto, 2018)) for learning the model with discrete latent variables. In this paper, we develop a simple yet effective approach for learning KiC in a fully-differentiable end-to-end manner. The key idea is based on an important observation that KiC can be reformulated as a special one-layer mixture-of-experts architecture, as shown in Figure 2. Note that the knowledge selector can be identified as the router that is used to determine the sequence-to-expert assignment in MoE. This is slightly different from the settings of the recent MoE works (Shazeer et al., 2017; Fedus et al., 2022), where their routers perform token-to-expert assignments. Meanwhile, each expert is made up of the text-to-text module together with a particular category of knowledge memory. Interestingly, each expert is in itself a stand-alone semi-parametric language model, which retrieves a particular kind of knowledge from its own memory to augment its inputs. In other words, each expert can be understood as a specialist with expertise in a specific knowledge category. In addition, we also

include a special expert named *generalist*, which is used to handle situation where we do not need knowledge from our memory. Furthermore, due to the original KiC design, the text-to-text modules in all the experts (and the generalist) share the same model parameters with the only difference being the non-parametric parts (i.e., the knowledge memories).

Inspired by the above KiC-MoE equivalence, we now proceed to develop a fully-differentiable learning strategy for KiC by leveraging existing MoE learning approaches used in (Fedus et al., 2022). More formally, the knowledge selector $S(x)$ is modeled as a $(K + 1)$-way classifier, which outputs a $(K + 1)$-dimensional normalized probability vector. Its k-th element, denoted as $S_k(x)$, represents the probability of choosing the k-th knowledge category for $k = 0, 1, \ldots, K$, where $k = 0$ represents the choice of generalist (i.e., no external knowledge). Let $T(\cdot)$ denote the text-to-text transformer and c_k be the knowledge retrieved from the k-th category. Then, in KiC, we select the top-1 knowledge category according to $S(x)$ and compute the output according to the following expressions:

$$\bar{k} = \arg \max_k S_k(x) \tag{1}$$

$$\hat{y} = T(x \oplus c_{\bar{k}}) \cdot S_{\bar{k}}(x) \tag{2}$$

where $\oplus$ denotes concatenation of the input x and the retrieved knowledge $c_{\bar{k}}$ (both in the form of natural language). Observe that KiC first selects the knowledge category $\bar{k}$ that has the highest probability, and then retrieves the most relevant knowledge $c_{\bar{k}}$ from that category to complement the input x. The knowledge-augmented input is fed into the text-to-text model to generate the logits for the output tokens. Similar to SwitchTransformer (Fedus et al., 2022), we multiply the output logits from $T(\cdot)$ by the probability $S_{\bar{k}}(x)$ from the selector to compute the final logits for the output tokens. This is a simple yet quite effective strategy to enable differentiable learning in MoE, which was successfully used in both Shazeer et al. (2017) and Fedus et al. (2022). We adopt this similar strategy and our experiments in Section 3 will demonstrate its effectiveness in KiC learning as well.[2] Note that we currently only consider the top-1 knowledge selection (routing) for simplicity and leave the generalization to top-n selection as future work. Finally, similar to MoE, we also add an auxiliary load balancing loss together with the standard cross-entropy loss during KiC learning:

$$\mathcal{L}(x, y) = \sum_{t=1}^{T} \texttt{CrossEntropy}(\hat{y}_t, y_t) + \alpha \cdot \texttt{Balancing}(S(x)) \tag{3}$$

where y denotes the target sequence, the subscript t indexes the t-th output token, and α is a positive hyper-parameter that controls the tradeoff between the two loss terms. We find that, without a load balancing term, the knowledge selector tends to select only one knowledge category throughout the entire training process, which was also observed in MoE learning. There could be different choices of the load balancing loss such as the ones used in (Shazeer et al., 2017; Fedus et al., 2022), which encourage the diversity of knowledge selection in different ways based on $S(x)$. Without loss of generality, we use the same load balancing loss as in SwithTransformer (Fedus et al., 2022).

The above KiC-MoE equivalence may also lead to interesting observations that could potentially benefit the studies of both semi-parametric language models and MoEs. For example, in MoE works, the experts are generally designed to be different parametric neural modules (e.g., different MLPs (Fedus et al., 2022; Shazeer et al., 2017)). However, our work shows that this may not be the only option: we can construct different experts by using the same parametric module but with different inputs. By bridging these two active areas, we hope there could be more fruitful future outcomes.

3 EXPERIMENTS

3.1 ANALYSIS OF KNOWLEDGE USEFULNESS

To verify our assumption that external knowledge resources can facilitate LMs in general language understanding and see effects of using different types of knowledge, we conduct single-task fine-tuning experiments on a wide range of downstream tasks (Table 1). We evaluate on 35 tasks in total and classify them into 10 categories following the P3 task categorization framework. For each

---

[2]It might be tempting to use Gumbel-Softmax to handle the discrete latent variable in KiC. However, in order to use the straight-through-estimator during backpropagation, it has to compute the hidden states for all the experts, i.e., executing the text-to-text transformer by $(K + 1)$ times, which is prohibitive when K increases.

Category	Task	Task Reference	None	ENT	DIC	COM	EVT	SCR	CAU
Coreference	WSC	Levesque et al. (2012)	60.3	49.5	62.0	53.1	**64.7**	62.0	63.4
	Wino. debiased	Sakaguchi et al. (2021)	**59.1**	53.5	57.3	56.9	58.3	58.5	54.1
	Wino. xl	Sakaguchi et al. (2021)	63.5	63.0	64.2	**64.5**	64.3	63.8	63.5
NLI	CB	De Marneffe et al. (2019)	87.5	87.5	85.9	87.5	85.9	**90.6**	84.4
	RTE	Wang et al. (2019)	77.1	76.2	79.0	**79.2**	76.6	76.9	71.3
Paraphrase	MRPC	Dolan & Brockett (2005)	82.9	80.5	**87.7**	77.9	84.9	84.4	82.0
	QQP	Wang et al. (2018)	89.4	89.1	**89.5**	89.5	89.2	89.3	89.4
	PAWS	Zhang et al. (2019a)	**94.6**	94.2	94.3	94.4	94.4	94.5	94.2
Close QA	ARC-Easy	Clark et al. (2018)	52.8	52.6	53.1	51.7	56.1	51.7	**64.6**
	ARC-Challenge	Clark et al. (2018)	30.9	36.2	30.9	33.5	34.2	37.2	**39.5**
	WikiQA	Yang et al. (2015)	**96.2**	95.6	95.8	95.9	95.7	95.7	96.2
Extr. QA	ReCoRD	Zhang et al. (2018)	53.9	53.9	53.2	54.0	**54.1**	53.9	53.5
Multi QA	CoS-E v1.11	Rajani et al. (2019)	60.6	**61.2**	59.9	60.8	60.1	59.7	61.1
	CosmosQA	Huang et al. (2019)	69.1	69.0	68.3	**69.7**	67.9	67.7	66.4
	DREAM	Sun et al. (2019)	62.4	63.8	63.5	62.5	63.3	**63.8**	62.7
	OpenBookQA	Mihaylov et al. (2018)	56.2	54.7	54.7	57.4	**58.2**	55.7	57.6
	PIQA	Bisk et al. (2020)	71.7	72.5	71.6	71.5	71.5	70.6	**74.3**
	QASC	Khot et al. (2020)	97.8	**98.1**	98.0	98.0	98.1	97.8	97.6
	QuAIL	Rogers et al. (2020)	68.3	68.3	72.9	**73.5**	72.9	66.6	68.6
	QuaRTz	Tafjord et al. (2019)	**83.1**	81.8	81.1	81.1	81.5	82.2	81.1
	RACE-Middle	Lai et al. (2017)	74.1	73.8	74.1	**74.4**	73.3	73.3	72.7
	RACE-High	Lai et al. (2017)	69.4	69.3	**69.9**	69.7	69.2	68.8	69.7
	SciQ	Welbl et al. (2017)	94.0	95.5	95.0	98.0	96.6	94.1	**98.7**
	SocialIQA	Sap et al. (2019)	63.4	63.5	63.6	**64.2**	63.7	63.9	63.2
	BoolQ	Clark et al. (2019)	81.9	**82.2**	81.7	82.0	80.6	81.5	81.7
	MultiRC	Khashabi et al. (2018)	80.0	79.7	79.5	**80.0**	79.5	79.2	79.0
	WikiHop	Welbl et al. (2018)	58.7	58.7	58.8	**59.4**	59.4	59.1	58.5
	WIQA	Tandon et al. (2019)	74.4	74.4	75.1	**83.9**	83.6	82.4	83.5
Sentiment	IMDB	Maas et al. (2011)	94.8	**94.9**	94.7	94.9	94.7	94.7	94.8
	Rotten Tomatoes	Pang & Lee (2005)	90.2	89.6	**90.3**	89.9	90.0	90.0	89.6
Completion	HellaSwag	Zellers et al. (2019)	49.8	49.3	50.6	51.8	52.0	49.8	**53.7**
	COPA	Roemmele et al. (2011)	58.0	58.5	59.8	54.5	58.9	56.2	**62.0**
Topic Class.	AG News	Del Corso et al. (2005)	93.9	93.6	94.0	**94.3**	94.0	94.1	94.1
	DBpedia14	Lehmann et al. (2015)	**28.4**	28.4	28.4	28.4	28.4	28.4	28.4
WSD	WiC	Pilehvar et al. (2019)	68.8	67.9	69.5	**70.2**	68.2	66.3	69.8

Table 1: Single task fine-tuning results of using no knowledge (None) or adding entity (ENT), dictionary (DIC), commonsense (COM), event (EVT), script (SCR), or causality (CAU) knowledge separately. For each row, we use green and red to indicate performance increase or decrease in comparison with no knowledge (None). The boldface numbers are the best performance for each row. Note that all results in this table are based on T5$_{Base}$. We report accuracy (%) for all tasks.

knowledge type (each column), we append all retrieved knowledge texts in front of the input sentence by adding a special token in between. Next, the augmented input sentences are fed into the standard text-to-text model (T5) to generate the target answer for optimization, where training instances are from each single task. We can see that model performances on 30 out of 35 tasks are improved after adding at least one type of knowledge, which demonstrates the effectiveness of using high-quality external knowledge. Based on these results, we exploit KiC to dynamically identify the most useful knowledge pieces to adaptively utilize knowledge.

3.2 MAIN RESULTS

Our main model KiC is initialized with T5-LM-adapt, an improved version of T5 that continues training T5 for additional 100K steps on the LM objective (Lester et al., 2021) to leverage its ability to generate natural language. Similar to T0, we train our KiC model on a mixture of multiple tasks (39 tasks in total) by combining and shuffling all training instances from different tasks (8.4M in

Models	Params	Coreference		NLI					Completion			WSD
		WSC	Wino. XL	ANLI$_{R1}$	ANLI$_{R2}$	ANLI$_{R3}$	CB	RTE	COPA	H.S.	S.C.	WiC
BERT	0.34B	53.4	49.5	33.8	33.8	33.2	48.2	48.4	49.0	25.5	50.1	50.2
RoBERTa	0.35B	37.0	48.9	33.4	33.4	33.3	42.9	54.1	56.0	22.4	48.5	50.0
GPT-Neo	2.7B	45.2	50.8	33.5	33.3	33.4	48.2	51.1	50.5	25.0	54.6	52.5
GPT-J	6B	40.4	48.5	34.0	33.7	33.6	28.6	50.5	56.0	24.7	53.3	51.0
OPT	30B	63.5	48.4	33.3	33.3	33.4	50.0	47.3	52.0	24.4	55.3	50.0
GPT-NeoX	20B	60.6	48.9	33.4	33.4	33.6	30.4	48.4	44.5	25.0	53.5	49.9
T0$_{Base}$	0.22B	57.7	51.1	30.0	32.6	34.9	50.0	70.2	65.0	26.8	83.8	50.6
T0$_{Large}$	0.77B	59.1	50.5	30.5	32.7	33.8	60.7	62.1	73.5	26.2	84.0	50.2
T0$_{XL}$	3B	64.4	50.5	33.7	33.4	33.3	50.0	64.1	74.9	27.5	85.1	50.4
T0$_{XXL}$	11B	64.4	60.5	44.7	39.4	42.4	78.6	81.2	90.8	33.7	94.7	57.2
KiC$_{Small}$	0.06B	63.5	51.3	33.3	33.4	33.6	44.6	47.3	48.0	26.0	57.3	50.0
KiC$_{Base}$	0.22B	63.5	50.0	28.4	31.1	32.8	58.9	66.8	67.0	27.2	82.2	50.2
KiC$_{Large}$	0.77B	65.4	55.3	36.3	35.0	37.6	67.9	74.0	85.3	31.2	93.6	52.4

Table 2: Zero-shot evaluation results on held-out unseen tasks (H.S.: the HellaSwag task; S.C.: the StoryCloze task). Following previous papers, we report the median accuracy (%) of all prompts used. T0$_{Base}$ and T0$_{Large}$ are reproduced using the same hyper-parameters with KiC models. Baseline models are: BERT(Devlin et al., 2019), RoBERTa(Liu et al., 2019), GPT-Neo(Black et al., 2021), GPT-J(Wang & Komatsuzaki, 2021), GPT-NeoX(Black et al., 2022), OPT(Zhang et al., 2022b). We use the standard autoregressive (log) probabilities to score candidate choices and select the best one as the prediction for all baseline models including mask LMs such as BERT and RoBERTa.

Models	Params	Method	STEM	Hum.	Soc. Sci.	Other	Average
RoBERTa$_{Large}$	0.35B	fine-tune	27.0	27.9	28.8	27.7	27.9
GPT-2	1.5B	fine-tune	30.2	32.8	33.3	33.1	32.4
Gopher	7.1B	5-shot	30.1	28.0	31.0	31.0	29.5
Atlas	11B	5-shot	38.8	46.1	54.6	52.8	47.9
GPT-3	13B	5-shot	24.3	27.1	25.6	26.5	26.0
GPT-NeoX	20B	5-shot	34.9	29.8	33.7	37.7	33.6
GPT-3	175B	5-shot	36.7	40.8	50.4	48.8	43.9
GPT-Neo	2.7B	0-shot	28.2	30.1	21.9	24.4	26.1
T0$_{XL}$	3B	0-shot	29.9	34.2	40.4	38.1	35.7
GPT-J	6B	0-shot	26.9	29.3	29.2	27.4	28.2
T0$_{XXL}$	11B	0-shot	33.3	42.2	48.5	48.9	43.2
Atlas	11B	0-shot	38.0	43.6	54.1	54.4	47.5
GPT-NeoX	20B	0-shot	29.2	29.9	28.5	27.0	28.7
OPT	30B	0-shot	27.7	30.1	27.0	28.6	28.4
KiC$_{Small}$	0.06B	0-shot	26.4	26.6	26.8	27.5	26.8
KiC$_{Base}$	0.22B	0-shot	27.9	30.7	33.4	33.7	31.4
KiC$_{Large}$	0.77B	0-shot	30.7	38.3	43.6	44.8	39.4

Table 3: Comparison to state-of-the-art results on the test set of MMLU tasks. Additional models used for comparison: Gopher (Rae et al., 2021), Atlas (Izacard et al., 2022).

total) and predict on unseen (held-out) tasks to evaluate zero-shot generalization ability. Our final KiC$_{Large}$ model is trained using 128 NVIDIA V100 GPUs for 42 hours.

Zero-shot Generalization We evaluate our KiC model on two groups of zero-shot datasets. 1) Held-out tasks of P3 contain two coreference tasks, three NLI tasks, three sentence completion tasks and one word sense disambiguation (WSD) task. Table 2) shows that our KiC$_{Large}$ model outperforms all zeroshot baseline models (e.g., GPT-NeoX, OPT) that are 25-38x larger. Moreover, KiC$_{Large}$ beats T0$_{XL}$ that has 3B parameters on all 9 tasks by a large margin with our adaptive knowledge selector and only 0.77B parameters. 2) Massive Multitask Language Understanding (MMLU) (Hendrycks et al., 2020) benchmark is designed to measure knowledge acquired in model pretraining. MMLU covers 57 subjects under four categories, i.e., STEM, Humanities, Social Sciences and Other. Comparison with SOTA LMs are shown in Table 3. We can see that KiC$_{Large}$ beats all fine-tuning baseline models

Model	Paraphrase			Close Book QA			Multi-Choice QA	
	MRPC	QQP	PAWS	ARC$_{Easy}$*	ARC$_{Challenge}$*	WikiQA	CoS-E$_{v1.11}$	CosmosQA
T0$_{Large}$	85.3	88.6	94.7	50.9	37.5	95.4	58.1	71.2
KiC$_{Large}$	85.5	89.3	95.3	67.9	46.5	95.7	76.3	81.3

Multi-Choice QA								
DREAM	OpenBookQA*	PIQA*	QASC	QuAIL	QuaRTz	RACE$_{Middle}$*	RACE$_{High}$*	SciQ
72.9	38.8	53.2	97.6	71.4	84.8	61.6	49.6	92.5
82.5	53.4	64.6	99.1	78.9	89.7	74.8	65.8	94.6

Multi-Choice QA				Sentiment Analysis		Topic Classification	
SocialIQA	BoolQ*	WikiHop	WIQA	IMDB	Rotten Tomatoes	AG News	DBpedia14
67.7	62.6	60.9	75.8	95.2	87.8	94.0	28.4
74.2	72.9	61.2	79.1	96.5	91.7	94.2	28.9

Table 4: In-domain evaluation results. KiC$_{Large}$ has the knowledge selector and is trained using multitask learning. We report accuracy (%) for all tasks here. * indicates that this task is not included in KiC multitask training. We regard tasks with * as in-domain evaluation because they are within the task category (such as multi-choice QA tasks) used in multitask training.

RoBERTa$_{Large}$ and GPT-2 without using any training data from MMLU. Surprisingly, KiC$_{Large}$ achieves an average performance of 39.4% using only 0.77B parameters, which is just 4.5% below GPT-3 that has 175B parameters (227x larger) plus 5 training examples.

KiC in Multi-task training To see whether our KiC learning can help with multi-tasking training, we reproduce T0$_{Large}$ with the same collection of tasks and evaluate KiC$_{Large}$ on the validation set of each in-domain task (Table 4). Here, in-domain tasks can be divided into two groups - tasks used in multitask training and tasks not used in multitask training but within the observed task category. Again, KiC$_{Large}$ outperforms T0$_{Large}$, with significant improvement on in-domain unseen tasks (tasks with *) such as Race and BoolQ and knowledge-intensive tasks such as CosmosQA and DREAM. It demonstrates the superiority of our proposed KiC learning in multi-tasking training.

Emerging behavior Wei et al. (2022) discover that language models usually can only perform a near random zero/few-shot performance when they are small but achieves a substantial performance jump when they reach a certain critical threshold of scale (size). A language model is generally considered superior if it can show emerging behavior at a smaller model scale. Therefore, we compare our KiC model with T5 and T0 on held-out tasks to see how performance change with respect to their model sizes. From Figure 3, we can see that T5 is around random guess when the model is below 11B. T0 is better than T5 as it shows emerging behavior when it increases from 3B to 11B. Surprisingly, our KiC model shows emerging behavior when it increases from 0.22B to 0.77B, which demonstrates that our semi-parametric model can achieve the same language understanding capacity using much fewer parameters with the help of adaptive knowledge selector and external knowledge.

3.3 RESULT ANALYSIS

We further analyze the improved instances to investigate which kind of knowledge is more helpful for a certain task after multitask training that leverages multi-source knowledge. We observe that the dominating knowledge type picked by the selector may not be the same as that in the single-task single-knowledge setting. For example, for the RTE dataset, the top-2 frequently selected knowledge types (script and causal) actually hurt the performance in the previous setting (Table 1). Besides, it is also possible that a benchmark originally constructed to mainly test one type of knowledge does not benefit from this type. For example, for a commonsense reasoning benchmark Winogrande, more instances are improved by the entity knowledge than other types of knowledge including commonsense. One possible reason might be that entity knowledge we include in this work also involve other types of knowledge: e.g., for a Winogrande instance *"In the sentence below, does the _ stand for ear or piercing? Mary wanted to get another piercing in her ear, but the _ was much too tiny."*, the selected entity knowledge is a description about *"piercing"* (*"The word "piercing" can refer to the act or practice of body piercing, or to an opening in the body created by this act or practice..."*). The observations show the importance of our instance-adaptive knowledge selector.

Figure 3: Emerging behaviors of T5, T0 and KiC model.

4 RELATED WORK

Knowledge Injection of PLMs Although PLMs can capture knowledge such as linguistic, semantic, commonsense, and world knowledge to some extent, they can only memorize knowledge vaguely in parameters, causing poor performance on knowledge-intensive tasks. Recent studies make a great effort to inject knowledge such as lexical knowledge, entity knowledge graph, or syntactic knowledge into LM pre-training (Yang et al., 2021). For example, besides masked language modeling (MLM) and next sentence prediction (NSP), Lauscher et al. (2020) add synonyms and hyponym-hypernym relation prediction between words and Levine et al. (2020) add supersense prediction of masked words into LM training objectives. To use entity knowledge, ERNIE 2.0 (Sun et al., 2020) introduces named entity masking to learn better embeddings for semantic units, Peters et al. (2019) include entity linking, hypernym linking into pre-training and K-BERT (Liu et al., 2020) uses entity knowledge triples to construct knowledge-rich sentence trees. For syntax knowledge injection, Wang et al. (2021) integrate dependency relation prediction into LM training and Bai et al. (2021) incorporate syntax tree information through a syntax-aware self-attention mechanism.

Semi-parametric language models Most of the existing works on semi-parametric language models (Khandelwal et al., 2019; Zhong et al., 2022; Grave et al., 2017; Merity et al., 2017; de Masson d'Autume et al., 2019; Guu et al., 2020; Fan et al., 2021; Lewis et al., 2020) mainly focus on improving the language modeling capability (e.g., improving perplexities) or a particular category of downstream task (e.g., open-domain question answering). Some recent works (Izacard et al., 2022; Borgeaud et al., 2022; Petroni et al., 2021) seek to improving diverse downstream tasks with an external memory. All these works augment the parametric language model with memories of plain texts. In contrast, we focus on developing semi-parametric language models with a knowledge-rich memory for improving the performance of a wide range of downstream language tasks.

5 CONCLUSIONS AND FUTURE WORK

This work develops a novel semi-parametric language model architecture, *Knowledge-in-Context (KiC)*, which empowers a parametric text-to-text language model with a knowledge-rich external memory containing six different types of knowledge. We also design an instance-adaptive knowledge selector to retrieve the most helpful pieces of knowledge for each input instance. As a knowledge-rich semi-parametric language model, KiC only needs a relatively smaller parametric part to achieve superior zero-shot performance on unseen tasks and exhibits emergent abilities at a much smaller model scale compared to the fully-parametric models. Future work may include future exploiting unstructured plain texts to pre-train KiC.

REFERENCES

Jiangang Bai, Yujing Wang, Yiren Chen, Yaming Yang, Jing Bai, Jing Yu, and Yunhai Tong. Syntax-bert: Improving pre-trained transformers with syntax trees. In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 3011–3020, 2021.

Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 7432–7439, 2020.

Sid Black, Gao Leo, Phil Wang, Connor Leahy, and Stella Biderman. GPT-Neo: Large Scale Autoregressive Language Modeling with Mesh-Tensorflow, March 2021. URL https://doi.org/10.5281/zenodo.5297715. If you use this software, please cite it using these metadata.

Sidney Black, Stella Biderman, Eric Hallahan, Quentin Anthony, Leo Gao, Laurence Golding, Horace He, Connor Leahy, Kyle McDonell, Jason Phang, et al. Gpt-neox-20b: An open-source autoregressive language model. In *Proceedings of BigScience Episode\# 5–Workshop on Challenges & Perspectives in Creating Large Language Models*, pp. 95–136, 2022.

Sebastian Borgeaud, Arthur Mensch, Jordan Hoffmann, Trevor Cai, Eliza Rutherford, Katie Millican, George Bm Van Den Driessche, Jean-Baptiste Lespiau, Bogdan Damoc, Aidan Clark, et al. Improving language models by retrieving from trillions of tokens. In *International Conference on Machine Learning*, pp. 2206–2240. PMLR, 2022.

Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, et al. Palm: Scaling language modeling with pathways. *arXiv preprint arXiv:2204.02311*, 2022.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. BoolQ: Exploring the surprising difficulty of natural yes/no questions. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 2924–2936, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1300. URL https://aclanthology.org/N19-1300.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. *arXiv preprint arXiv:1803.05457*, 2018.

Marie-Catherine De Marneffe, Mandy Simons, and Judith Tonhauser. The commitmentbank: Investigating projection in naturally occurring discourse. In *proceedings of Sinn und Bedeutung*, volume 23, pp. 107–124, 2019.

Cyprien de Masson d'Autume, Sebastian Ruder, Lingpeng Kong, and Dani Yogatama. Episodic memory in lifelong language learning. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/f8d2e80c1458ea2501f98a2cafadb397-Paper.pdf.

Gianna M Del Corso, Antonio Gulli, and Francesco Romani. Ranking a stream of news. In *Proceedings of the 14th international conference on World Wide Web*, pp. 97–106, 2005.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, 2019.

Bill Dolan and Chris Brockett. Automatically constructing a corpus of sentential paraphrases. In *Third International Workshop on Paraphrasing (IWP2005)*, 2005.

Angela Fan, Claire Gardent, ChloÃ© Braud, and Antoine Bordes. Augmenting Transformers with KNN-Based Composite Memory for Dialog. *Transactions of the Association for Computational Linguistics*, 9:82–99, 03 2021. ISSN 2307-387X. doi: 10.1162/tacl_a_00356. URL `https://doi.org/10.1162/tacl_a_00356`.

William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research*, 23(120):1–39, 2022.

Edouard Grave, Armand Joulin, and Nicolas Usunier. Improving neural language models with a continuous cache. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=B184E5qee`.

Ruiqi Guo, Philip Sun, Erik Lindgren, Quan Geng, David Simcha, Felix Chern, and Sanjiv Kumar. Accelerating large-scale inference with anisotropic vector quantization. In *International Conference on Machine Learning*, pp. 3887–3896. PMLR, 2020.

Kelvin Guu, Kenton Lee, Zora Tung, Panupong Pasupat, and Mingwei Chang. Retrieval augmented language model pre-training. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 3929–3938. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/guu20a.html`.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. In *International Conference on Learning Representations*, 2020.

Lifu Huang, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Cosmos qa: Machine reading comprehension with contextual commonsense reasoning. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 2391–2401, 2019.

Jena D. Hwang, Chandra Bhagavatula, Ronan Le Bras, Jeff Da, Keisuke Sakaguchi, Antoine Bosselut, and Yejin Choi. (Comet-) Atomic 2020: On symbolic and neural commonsense knowledge graphs. In *Proceedings of the 25th AAAI Conference on Artificial Intelligence, Virtual Event*, pp. 6384–6392, 2021.

Gautier Izacard, Patrick Lewis, Maria Lomeli, Lucas Hosseini, Fabio Petroni, Timo Schick, Jane Dwivedi-Yu, Armand Joulin, Sebastian Riedel, and Edouard Grave. Few-shot learning with retrieval augmented language models. *arXiv preprint arXiv:2208.03299*, 2022.

Robert A Jacobs, Michael I Jordan, Steven J Nowlan, and Geoffrey E Hinton. Adaptive mixtures of local experts. *Neural computation*, 3(1):79–87, 1991.

Michael I Jordan and Robert A Jacobs. Hierarchical mixtures of experts and the em algorithm. *Neural computation*, 6(2):181–214, 1994.

Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. Scaling laws for neural language models. *arXiv preprint arXiv:2001.08361*, 2020.

Urvashi Khandelwal, Omer Levy, Dan Jurafsky, Luke Zettlemoyer, and Mike Lewis. Generalization through memorization: Nearest neighbor language models. *arXiv preprint arXiv:1911.00172*, 2019.

Daniel Khashabi, Snigdha Chaturvedi, Michael Roth, Shyam Upadhyay, and Dan Roth. Looking beyond the surface: A challenge set for reading comprehension over multiple sentences. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 252–262, 2018.

Tushar Khot, Peter Clark, Michal Guerquin, Peter Jansen, and Ashish Sabharwal. Qasc: A dataset for question answering via sentence composition. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 8082–8090, 2020.

Guokun Lai, Qizhe Xie, Hanxiao Liu, Yiming Yang, and Eduard Hovy. RACE: Large-scale ReAding comprehension dataset from examinations. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 785–794, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/D17-1082. URL `https://aclanthology.org/D17-1082`.

Anne Lauscher, Ivan Vulić, Edoardo Maria Ponti, Anna Korhonen, and Goran Glavaš. Specializing unsupervised pretraining models for word-level semantic similarity. In *Proceedings of the 28th International Conference on Computational Linguistics*, pp. 1371–1383, 2020.

Jens Lehmann, Robert Isele, Max Jakob, Anja Jentzsch, Dimitris Kontokostas, Pablo N Mendes, Sebastian Hellmann, Mohamed Morsey, Patrick Van Kleef, Sören Auer, et al. Dbpedia–a large-scale, multilingual knowledge base extracted from wikipedia. *Semantic web*, 6(2):167–195, 2015.

Brian Lester, Rami Al-Rfou, and Noah Constant. The power of scale for parameter-efficient prompt tuning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 3045–3059, 2021.

Hector Levesque, Ernest Davis, and Leora Morgenstern. The winograd schema challenge. In *Thirteenth international conference on the principles of knowledge representation and reasoning*, 2012.

Yoav Levine, Barak Lenz, Or Dagan, Ori Ram, Dan Padnos, Or Sharir, Shai Shalev-Shwartz, Amnon Shashua, and Yoav Shoham. Sensebert: Driving some sense into bert. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4656–4667, 2020.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, Sebastian Riedel, and Douwe Kiela. Retrieval-augmented generation for knowledge-intensive nlp tasks. In H. Larochelle, M. Ranzato, R. Hadsell, M.F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 9459–9474. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/6b493230205f780e1bc26945df7481e5-Paper.pdf`.

Zhongyang Li, Xiao Ding, Ting Liu, J. Edward Hu, and Benjamin Van Durme. Guided generation of cause and effect. In *Proceedings of the IJCAI*, 2020.

Hugo Liu and Push Singh. Conceptnet—a practical commonsense reasoning tool-kit. *BT technology journal*, 22(4):211–226, 2004.

Weijie Liu, Peng Zhou, Zhe Zhao, Zhiruo Wang, Qi Ju, Haotang Deng, and Ping Wang. K-bert: Enabling language representation with knowledge graph. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 2901–2908, 2020.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

Andrew Maas, Raymond E Daly, Peter T Pham, Dan Huang, Andrew Y Ng, and Christopher Potts. Learning word vectors for sentiment analysis. In *Proceedings of the 49th annual meeting of the association for computational linguistics: Human language technologies*, pp. 142–150, 2011.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *International Conference on Learning Representations*, 2017. URL `https://openreview.net/forum?id=Byj72udxe`.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2381–2391, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1260. URL `https://aclanthology.org/D18-1260`.

Nasrin Mostafazadeh, Aditya Kalyanpur, Lori Moon, David W. Buchanan, Lauren Berkowitz, Or Biran, and Jennifer Chu-Carroll. GLUCOSE: Generalized and contextualized story explanations. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing, Virtual Event*, pp. 4569–4586, 2020.

Bo Pang and Lillian Lee. Seeing stars: Exploiting class relationships for sentiment categorization with respect to rating scales. In *Proceedings of the 43rd Annual Meeting of the Association for Computational Linguistics (ACL'05)*, pp. 115–124, 2005.

Matthew E Peters, Mark Neumann, Robert Logan, Roy Schwartz, Vidur Joshi, Sameer Singh, and Noah A Smith. Knowledge enhanced contextual word representations. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 43–54, 2019.

Fabio Petroni, Aleksandra Piktus, Angela Fan, Patrick S. H. Lewis, Majid Yazdani, Nicola De Cao, James Thorne, Yacine Jernite, Vladimir Karpukhin, Jean Maillard, Vassilis Plachouras, Tim Rocktäschel, and Sebastian Riedel. Kilt: a benchmark for knowledge intensive language tasks. In *NAACL-HLT*, pp. 2523–2544, 2021. URL `https://doi.org/10.18653/v1/2021.naacl-main.200`.

Mohammad Taher Pilehvar, Jose Camacho-Collados, et al. WiC: the word-in-context dataset for evaluating context-sensitive meaning representations. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1267–1273, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1128. URL `https://aclanthology.org/N19-1128`.

Delai Qiu, Yuanzhe Zhang, Xinwei Feng, Xiangwen Liao, Wenbin Jiang, Yajuan Lyu, Kang Liu, and Jun Zhao. Machine reading comprehension using structural knowledge graph-aware network. In *Proceedings of the EMNLP-IJCNLP*, pp. 5896–5901, Hong Kong, China, 2019. URL `https://aclanthology.org/D19-1602`.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Jack W Rae, Sebastian Borgeaud, Trevor Cai, Katie Millican, Jordan Hoffmann, Francis Song, John Aslanides, Sarah Henderson, Roman Ring, Susannah Young, et al. Scaling language models: Methods, analysis & insights from training gopher. *arXiv preprint arXiv:2112.11446*, 2021.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, Peter J Liu, et al. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(140):1–67, 2020.

Nazneen Fatema Rajani, Bryan McCann, Caiming Xiong, and Richard Socher. Explain yourself! leveraging language models for commonsense reasoning. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4932–4942, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1487. URL `https://aclanthology.org/P19-1487`.

Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S Gordon. Choice of plausible alternatives: An evaluation of commonsense causal reasoning. In *AAAI spring symposium: logical formalizations of commonsense reasoning*, pp. 90–95, 2011.

Anna Rogers, Olga Kovaleva, Matthew Downey, and Anna Rumshisky. Getting closer to ai complete question answering: A set of prerequisite real tasks. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 8722–8731, 2020.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021.

Victor Sanh, Albert Webson, Colin Raffel, Stephen Bach, Lintang Sutawika, Zaid Alyafeai, Antoine Chaffin, Arnaud Stiegler, Teven Le Scao, Arun Raja, et al. Multitask prompted training enables zero-shot task generalization. In *The Tenth International Conference on Learning Representations*, 2022.

Maarten Sap, Hannah Rashkin, Derek Chen, Ronan Le Bras, and Yejin Choi. Social IQa: Commonsense reasoning about social interactions. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 4463–4473, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1454. URL `https://aclanthology.org/D19-1454`.

Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *International Conference on Learning Representations*, 2017.

Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. Mpnet: Masked and permuted pre-training for language understanding. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin (eds.), *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, 2020.

Kai Sun, Dian Yu, Jianshu Chen, Dong Yu, Yejin Choi, and Claire Cardie. Dream: A challenge data set and models for dialogue-based reading comprehension. *Transactions of the Association for Computational Linguistics*, 7:217–231, 2019.

Kai Sun, Dian Yu, Jianshu Chen, Dong Yu, and Claire Cardie. Improving machine reading comprehension with contextualized commonsense knowledge. In *Proceedings of the ACL*, pp. 8736–8747, 2022. URL `https://aclanthology.org/2022.acl-long.598`.

Yu Sun, Shuohuan Wang, Yukun Li, Shikun Feng, Hao Tian, Hua Wu, and Haifeng Wang. Ernie 2.0: A continual pre-training framework for language understanding. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pp. 8968–8975, 2020.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Oyvind Tafjord, Matt Gardner, Kevin Lin, and Peter Clark. QuaRTz: An open-domain dataset of qualitative relationship questions. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 5941–5946, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1608. URL `https://aclanthology.org/D19-1608`.

Niket Tandon, Bhavana Dalvi, Keisuke Sakaguchi, Peter Clark, and Antoine Bosselut. WIQA: A dataset for "what if..." reasoning over procedural text. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 6076–6085, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1629. URL `https://aclanthology.org/D19-1629`.

Denny Vrandečić and Markus Krötzsch. Wikidata: a free collaborative knowledgebase. *Communications of the ACM*, 57(10):78–85, 2014.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel Bowman. Superglue: A stickier benchmark for general-purpose language understanding systems. *Advances in neural information processing systems*, 32, 2019.

Ben Wang and Aran Komatsuzaki. GPT-J-6B: A 6 Billion Parameter Autoregressive Language Model. `https://github.com/kingoflolz/mesh-transformer-jax`, May 2021.

Ruize Wang, Duyu Tang, Nan Duan, Zhongyu Wei, Xuan-Jing Huang, Jianshu Ji, Guihong Cao, Daxin Jiang, and Ming Zhou. K-adapter: Infusing knowledge into pre-trained models with adapters. In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 1405–1418, 2021.

Jason Wei, Yi Tay, Rishi Bommasani, Colin Raffel, Barret Zoph, Sebastian Borgeaud, Dani Yogatama, Maarten Bosma, Denny Zhou, Donald Metzler, et al. Emergent abilities of large language models. *Transactions on Machine Learning Research*, August 2022.

Johannes Welbl, Nelson F. Liu, and Matt Gardner. Crowdsourcing multiple choice science questions. In *Proceedings of the 3rd Workshop on Noisy User-generated Text*, pp. 94–106, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4413. URL https://aclanthology.org/W17-4413.

Johannes Welbl, Pontus Stenetorp, and Sebastian Riedel. Constructing datasets for multi-hop reading comprehension across documents. *Transactions of the Association for Computational Linguistics*, 6:287–302, 2018. doi: 10.1162/tacl_a_00021. URL https://aclanthology.org/Q18-1021.

Jian Yang, Gang Xiao, Yulong Shen, Wei Jiang, Xinyu Hu, Ying Zhang, and Jinghui Peng. A survey of knowledge enhanced pre-trained models. *arXiv preprint arXiv:2110.00269*, 2021.

Yi Yang, Wen-tau Yih, and Christopher Meek. WikiQA: A challenge dataset for open-domain question answering. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 2013–2018, Lisbon, Portugal, September 2015. Association for Computational Linguistics. doi: 10.18653/v1/D15-1237. URL https://aclanthology.org/D15-1237.

Zhi-Xiu Ye, Qian Chen, Wen Wang, and Zhen-Hua Ling. Align, mask and select: A simple method for incorporating commonsense knowledge into language representation models. *arXiv preprint*, cs.CL/1908.06725v5, 2019. URL https://arxiv.org/abs/1908.06725v5.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. HellaSwag: Can a machine really finish your sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 4791–4800, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1472. URL https://aclanthology.org/P19-1472.

Hongming Zhang, Daniel Khashabi, Yangqiu Song, and Dan Roth. Transomcs: From linguistic graphs to commonsense knowledge. In Christian Bessiere (ed.), *Proceedings of the Twenty-Ninth International Joint Conference on Artificial Intelligence, IJCAI 2020*, pp. 4004–4010. ijcai.org, 2020. URL https://doi.org/10.24963/ijcai.2020/554.

Hongming Zhang, Xin Liu, Haojie Pan, Haowen Ke, Jiefu Ou, Tianqing Fang, and Yangqiu Song. ASER: towards large-scale commonsense knowledge acquisition via higher-order selectional preference over eventualities. *Artif. Intell.*, 309:103740, 2022a. URL https://doi.org/10.1016/j.artint.2022.103740.

Sheng Zhang, Xiaodong Liu, Jingjing Liu, Jianfeng Gao, Kevin Duh, and Benjamin Van Durme. Record: Bridging the gap between human and machine commonsense reading comprehension. *arXiv preprint arXiv:1810.12885*, 2018.

Susan Zhang, Stephen Roller, Naman Goyal, Mikel Artetxe, Moya Chen, Shuohui Chen, Christopher Dewan, Mona Diab, Xian Li, Xi Victoria Lin, et al. Opt: Open pre-trained transformer language models. *arXiv preprint arXiv:2205.01068*, 2022b.

Yuan Zhang, Jason Baldridge, and Luheng He. Paws: Paraphrase adversaries from word scrambling. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 1298–1308, 2019a.

Zhengyan Zhang, Xu Han, Zhiyuan Liu, Xin Jiang, Maosong Sun, and Qun Liu. ERNIE: Enhanced language representation with informative entities. In *Proceedings of the ACL*, pp. 1441–1451, 2019b. URL https://aclanthology.org/P19-1139.

Zexuan Zhong, Tao Lei, and Danqi Chen. Training language models with memory augmentation. *arXiv preprint arXiv:2205.12674*, 2022.

APPENDIX

A EXPERIMENTAL DETAILS

A.1 KNOWLEDGE STATISTICS

	Dictionary	Commonsense	Entity	Event	Script	Causal
# instances	1.8M	600K	257M	6.4M	248K	314M
type	human	human	human	auto	auto	auto

Table 5: Knowledge Statistics ("K" and "M" stand for thousand and million, respectively; human: knowledge that is collected by crowd-sourcing; auto: knowledge that is automatically extracted).

Question	*High-pressure systems stop air from rising into the colder regions of the atmosphere where water can condense. What will most likely result if a high-pressure system remains in an area for a long period of time?*
Answer	*Drought*
CausalBank (KG)	*Persistent high pressure has a stabilizing effect on the weather, causing subsiding air that dries out the atmosphere.*
Wikipedia (plain text)	*High - pressure systems are alternatively referred to as anticyclones. On English - language weather maps, high - pressure centers are identified by the letter H in English, within the isobar with the highest pressure value. On constant pressure upper level charts, it is located within the highest height line contour.*

Table 6: Examples of retrieved supporting knowledge from different resources (i.e., CausalBank v.s. Wikipedia).

A.2 IMPLEMENTATION DETAILS

	Learning Rate	Max. Input Len.	Max. Output Len.	Batch Size	α	# epoch
KiC$_{Base}$	5e$-$5	512	64	1024	0.05	5
KiC$_{Large}$	5e$-$5	512	64	1024	0.001	5

Table 7: Hyper-parameters for KiC$_{Base}$ and KiC$_{Large}$.

Model	Learning Rate	Max. Input Len.	Max. Output Len.	Batch Size	# epoch
T5-LM-adapt$_{Base}$	2e$-$4	1024	512	16	10

Table 8: Hyper-parameters for single task fine-tuning.

	Hardware	Hours
KiC$_{Base}$	NVIDIA V100 $\times$ 64	33.2
KiC$_{Large}$	NVIDIA V100 $\times$ 128	41.5

Table 9: Hardware and training time for KiC$_{Base}$ and KiC$_{Large}$.

B ADDITIONAL EXPERIMENTAL RESULTS

Models	Params	Coreference		NLI					Completion			WSD
		WSC	Wino. XL	$ANLI_{R1}$	$ANLI_{R2}$	$ANLI_{R3}$	CB	RTE	COPA	HellaSwag	StoryCloze	WiC
BERT	0.34B	53.2/53.4	49.7/49.5	34.1/33.8	33.8/33.8	33.2/33.2	45.0/48.2	48.3/48.4	48.9/49.0	25.5/25.5	50.1/50.1	50.3/50.2
RoBERTa	0.35B	38.5/37.0	49.1/48.9	33.6/33.4	33.6/33.4	33.5/33.3	44.0/42.9	53.8/54.1	56.8/56.0	22.9/22.4	48.5/48.5	50.4/50.0
GPT-Neo	2.7B	49.2/45.2	50.4/50.8	34.0/33.5	33.5/33.3	33.5/33.4	36.4/48.2	51.1/51.1	50.5/50.5	24.8/25.0	54.0/54.6	52.2/52.5
GPT-J	6B	44.6/40.4	48.9/48.5	33.7/34.0	34.0/33.7	33.7/33.6	26.6/28.6	49.6/50.5	54.9/56.0	24.7/24.7	53.1/53.3	52.4/51.0
OPT	30B	53.4/63.5	48.5/48.4	33.2/33.3	33.3/33.3	33.4/33.4	40.6/50.0	47.8/47.3	52.5/52.0	24.5/24.4	55.5/55.3	50.0/50.0
GPT-NeoX	20B	56.0/60.6	49.1/48.9	33.5/33.4	33.6/33.4	33.6/33.6	30.6/30.4	49.3/48.4	45.9/44.5	24.9/25.0	53.1/53.5	50.8/49.9
$T0_{Base}$	0.22B	59.1/57.7	51.1/51.1	30.4/30.0	33.0/32.6	34.8/34.9	49.5/50.0	70.8/70.2	61.3/65.0	38.6/26.8	79.6/83.8	50.7/50.6
$T0_{Large}$	0.77B	57.6/59.1	50.4/50.5	31.3/30.5	32.8/32.7	34.0/33.8	52.0/60.7	62.4/62.1	71.6/73.5	38.1/26.2	79.2/84.0	50.2/50.2
$T0_{XL}$	3B	65.1/64.4	51.0/50.5	33.8/33.7	33.1/33.4	33.3/33.3	45.4/50.0	64.6/64.1	72.4/74.9	27.3/27.5	84.0/85.1	50.7/50.4
$T0_{XXL}$	11B	61.5/64.4	59.9/60.5	43.6/44.7	38.7/39.4	41.3/42.4	70.1/78.6	80.8/81.2	90.0/90.8	33.6/33.7	92.4/94.7	56.6/57.2
KiC_{Small}	0.6B	60.9/63.5	51.2/51.3	33.5/33.3	33.6/33.4	33.6/33.6	40.2/44.6	48.2/47.3	47.9/48.0	38.0/26.0	57.1/57.3	50.0/50.0
KiC_{Base}	0.22B	63.7/63.5	49.9/50.0	29.3/28.4	31.6/31.1	33.0/32.8	52.9/58.9	66.9/66.8	62.6/67.0	38.9/27.2	78.1/82.2	51.1/50.2
KiC_{Large}	0.77B	62.6/65.4	54.1/55.3	36.7/36.3	34.9/35.0	37.6/37.6	57.5/67.9	73.1/74.0	81.7/85.3	41.2/31.2	88.5/93.6	52.1/52.4

Table 10: Full zero-shot evaluation results on holdout unseen tasks. We report mean/median accuracy (%) of all prompts for each task.