# Topologically faithful image segmentation via induced matching of persistence barcodes

## Abstract

Image segmentation is a largely researched field where neural networks find vast applications in many facets of technology. Some of the most popular approaches to train segmentation networks employ loss functions optimizing pixel-overlap, an objective that is insufficient for many segmentation tasks. In recent years, their limitations fueled a growing interest in topology-aware methods, which aim to recover the correct topology of the segmented structures. However, so far, none of the existing approaches achieve a spatially correct matching between the topological features (persistence barcodes) of label (ground truth) and prediction (output of the neural network).

In this work, we propose the first topologically and feature-wise accurate metric and loss function for supervised image segmentation, which we term TopoMatch. We show how induced matchings guarantee the spatially correct matching between barcodes in a segmentation setting. Furthermore, we propose an efficient algorithm to compute TopoMatch for images. We show that TopoMatch is an interpretable metric to evaluate the topological correctness of segmentations. Moreover, we demonstrate how induced matchings can be used to train segmentation networks and improve the topological correctness of the segmentations across all 6 baseline datasets while preserving volumetric segmentation performance.

## 1 Introduction

Topology studies properties of shapes that are related to their connectivity and that remain unchanged under deformations, translations, and twisting. Some topological concepts, such as cubical complexes and homology, form complete and interpretable descriptions of shapes in space that can be efficiently computed. Naturally, the topology of shapes is highly relevant to machine learning tasks that concern two-dimensional (2D) and three-dimensional (3D) structures and objects and that require the preservation of their properties, a prominent example being the task of image segmentation. Recently, a number of methods have been proposed with the aim to improve topology preservation in image segmentation for a wide range of applications.

Figure 1: Motivation. Our TopoMatch (induced matching) and the Wasserstein matching (Hu et al. (2019)) for a CREMI label-prediction pair. The matched cycles are represented in the same color.

In this work, we introduce a rigorous framework for faithfully quantifying the preservation of topological properties in the context of image segmentation. Our method builds on the *induced matchings* of persistence barcodes by Bauer & Lesnick (2015), a recent generalization of the foundational algebraic stability theorem of persistent homology. In simple terms, we propose the first loss function that guarantees to penalize and emphasize the spatially and topologically correct features for segmentation.

## 1.1 RELATED WORK

**Algebraic stability of persistence**   Several proofs for the stability of persistence have been proposed in the literature. In 2005, Cohen-Steiner et al. (2005) established a first stability result for persistent homology of real-valued functions. The result states that the map sending a function to the barcode of its sublevel sets is 1-Lipschitz with respect to suitable metrics. In 2008 this result was generalized by Chazal et al. (2009b) and formulated in purely algebraic terms, in what is now known as the *algebraic stability theorem*. This theorem states that the existence of a $\delta$-interleaving (a sort of approximate isomorphism) between two pointwise finite-dimensional persistence modules $M, N$ implies the existence of a $\delta$-matching between their respective barcodes $\mathcal{B}(M)$ and $\mathcal{B}(N)$. This theorem provides the justification for the use of persistent homology to study noisy data. In Bauer & Lesnick (2015), the authors present a constructive proof of this theorem, which associates to a $\delta$-interleaving between persistence modules a $\delta$-matching between their barcodes in an explicit way. For this purpose, they introduce the notion of induced matchings, which form the foundation of our proposed *TopoMatch* algorithm.

Figure 2: Topological matchings. Illustration of the advantages of our TopoMatch algorithm over the existing *Wasserstein matching* and the *Betti number error* for two exemplary segmentations. On the left side, we depict a prediction-label pair for an image. On the right side, we depict the matched representative cycles in the same color for the Wasserstein matching (bottom row) and *TopoMatch matching* (top row). In all examples, our TopoMatch matching matches the features spatially correct and the *TopoMatch loss* will penalize the correct intervals during training. In a) the Wasserstein matching mismatches the two predicted cycles, leading to irritating gradient updates during training. In b) we show a binarized prediction that is obtained by a wrong segmentation. Our method correctly does not match a single cycle, whereas the Wasserstein matching matches both cycles, leading to an undesired loss of 0. The Betti number error fails to detect the mistake in the segmentation as well, whereas the TopoMatch loss captures the error.

**Topology aware segmentation**   Multiple studies have described the importance of topologically correct segmentations in various computer vision applications. Clough et al. (2020) used the concept of Betti numbers as a prior for the segmentation network. A key publication by Hu et al. (2019) introduced the *Wasserstein loss* as a variation of the *Wasserstein distance* to improve image segmentation with neural networks. The method computes persistence diagrams for the ground truth and the prediction and matches the points in the persistence diagrams of dimension-1 by minimizing the squared distance of matched points. However, this matching algorithm has a fundamental limitation, in that it cannot guarantee that the 0-dim and 1-dim structures matched by the algorithm are spatially related in any sense, see Figure 2. Put succinctly, the matched cycles and connected components are matched irrespective of the location within the image, frequently leading to situations where the

resulting loss will emphasize the wrong features and penalize the correct features. See Figure 2 for two schematic examples and Figures 1,11 for the result of the Wasserstein matching method on the CREMI dataset. Moreover, the method only considers 1-dimensional structures in their implementation and restricts to superlevel filtrations. Persistent homology and distance-based barcode matching have been used in different settings, for example, by Abousamra et al. (2021) for crowd localization, by Wang et al. (2022) for gland segmentation, and by Waibel et al. (2022) for reconstructing 3D cell shapes from 2D images. An alternative approach to persistent homology is employed by Hu & Chen (2021), whose method penalizes different locations of critical points using the warping error metric Jain et al. (2010). Other frequently used methods in topology-aware segmentation focus on overlap-based segmentation, where the overlapped structures are not the entire volume but certain topologically relevant structures. For example, the skeleta of curvilinear structures play this role in the clDice score Shit et al. (2021), which is calculated as the harmonic mean of the overlap of the prediction skeleton with the label volume and the label skeleton with the prediction volume. Another recent method utilizes discrete Morse theory to extract topologically structures such as 1D skeletons Delgado-Friedrichs et al. (2014), and compares them to the likelihood in the prediction Hu et al. (2021). Generally, these overlap-based approaches are computationally efficient but often do not guarantee topology preservation in the sense that a zero loss implies a canonically induced correspondence of topological structures. Zhang & Lui (2022) use diffeomorphic template masks to enforce a specific shape. Other approaches aim at enforcing topologically motivated priors, for example, enforcing connectivity priors on segmentations of line drawings and vessels post-hoc Sasaki et al. (2017); Wang & Jiang (2018). In these approaches, the topological aspects are not actually trained in the neural network. Similarly, Mosinska et al. (2018) applied task-specific pre-trained filters to improve connected components. Further recent work by Cheng et al. (2021) jointly model connectivity and features based on iterative feedback learning, while Oner et al. (2020) implicitly aim to improve the topological performance by enforcing region separation of curvilinear structures.

## 2 TOPOLOGICAL BACKGROUND

### 2.1 GRAYSCALE IMAGES AS FILTERED CUBICAL COMPLEXES

The topology of grayscale images is best captured by *filtered cubical complexes*. See appendix J.1 for the definitions of this section. In order to filter a *cubical complex* $K$ we consider an *order preserving* function $f \colon K \to \mathbb{R}$ (the values on the faces of a cube are less than or equal to the value of the cube itself). Its **sublevel sets** $D(f)_r := f^{-1}((-\infty, r])$ assemble to the **sublevel filtration** $D(f) = \{D(f)_r\}_{r \in \mathbb{R}}$ of $K$. Since $f$ can only take finitely many values $\{f_1 < \ldots < f_l\}$, the filtered cubical complex $K_*$ given by $K_i = D(f)_{f_i}$ for $i = 1, \ldots, l$, already encodes all the information about the filtration.

For a grayscale image matrix $\boldsymbol{I} \in \mathbb{R}^{m \times n}$ we consider the cubical **grid complex** $K(\boldsymbol{I})$ consisting of all cubical cells contained in $[1, m] \times [1, n] \subseteq \mathbb{R}^2$. The **filter function** $f_I$ is defined on the vertices of $K(\boldsymbol{I})$ by the corresponding entry in $\boldsymbol{I}$, and on all higher-dimensional cubes as the maximum value of its vertices. Note that $f_I$ is order preserving, so we can associate the sublevel filtration of $f_I$ and its filtered cubical complex to the image $\boldsymbol{I}$ and denote them by $D(\boldsymbol{I})$ and $K_*(\boldsymbol{I})$, respectively. This construction is called the **V-construction** since pixels are treated as vertices in the cubical complex. An alternative, the **T-construction**, considers pixels as top-dimensional cells of a 2-dimensional cubical complex (see Heiss & Wagner (2017)). We implemented both, V- and T-construction, in our TopoMatch algorithm but employ the V-construction in all of our experiments.

$$\begin{pmatrix} 4 & 1 & 5 \\ 8 & 3 & 6 \\ 7 & 2 & 9 \end{pmatrix}$$

(a) $\boldsymbol{I}$      (b) $f_I \colon K(\boldsymbol{I}) \to \mathbb{R}$

Figure 3: (a) shows an image and (b) visualizes the V-construction.

### 2.2 HOMOLOGY

*Homology* is a powerful concept involving local computations to capture information about the global structure of topological spaces. It assigns a sequence of abelian groups to a space which encode its topological features in all dimensions. A feature in dimension-0 describes a connected component, in dimension-1, it describes a loop, and in dimension-2, it describes a cavity. It also relates these features between spaces by inducing linear maps between their respective homology

groups. We briefly introduce the homology of cubical complexes with coefficients in $\mathbb{F}_2$, where the homology groups are $\mathbb{F}_2$-vector spaces. For more details we refer to Kaczynski et al. (2004) and our appendix J.2 for the basic definitions of this section.

For $d \in \mathbb{Z}$, we denote by $K_d$ the set of $d$-dimensional cells in a cubical complex $K$. The $\mathbb{F}_2$-vector space $C_d(K)$ freely generated by $K_d$ is the **chain group** of $K$ in degree $d$. We can think of the elements in $C_d(K)$ as sets of $d$-dimensional cells and call them **chains**. These chain groups are connected by linear **boundary maps** $\partial_d \colon C_d(K) \to C_{d-1}(K)$, which map a cell to the sum of its faces of codimension 1 and are extended linearly to all of $C_d(K)$. The **cubical chain complex** $C_*(K)$ is given by the pair $(\{C_d(K)\}_{d \in \mathbb{Z}}, \{\partial_d\}_{d \in \mathbb{Z}})$. We denote by $Z_d(K) = \ker \partial_d$ the subspace of **cycles** and by $B_d(K) = \operatorname{im} \partial_{d+1}$ the subspace of **boundaries** in $C_d(K)$. Since $\partial_{d-1} \circ \partial_d = 0$, every boundary is a cycle and the **homology group** of $K$ in degree $d$ is defined by the quotient space $H_d(K) := Z_d(K)/B_d(K)$. In other words, $H_d(K)$ consists of equivalence classes of $d$-cycles and two $d$-cycles

(a) 1-cell      (b) 2-cell

(c) 1-cycle $z_2$    (d) 1-cycle $z_2$

Figure 4: (a) and (b) show cells and their boundary (red). (c) and (d) visualize two homologous 1-cycles (blue) in a cubical complex.

$z_1, z_2$ are equivalent (**homologous**) if their difference is a boundary. For convenience, we define $H_*(K) = \bigoplus_{d \in \mathbb{Z}} H_d(K)$. Note that the homology groups still carry the structure of a $\mathbb{F}_2$-vector space and the dimension $\beta_d(K) = \dim_{\mathbb{F}_2}(H_d(K))$ is the $d$th **Betti number** of $K$.

Homology does not only act on spaces; it also acts on maps between spaces. Therefor, a *cubical map* $f \colon K \to K'$ induces a linear map $C_*(f) \colon C_*(K) \to C_*(K')$, by mapping a cell $c \in K$ with $\dim(f(c)) = \dim(c)$ to $f(c)$ and extending this assignment linearly to all of $C_*(K)$. Then $C_*(f)$ descends to a linear map $H_*(f) \colon H_*(K) \to H_*(K')$ in homology since $\partial_* \circ C_*(f) = C_*(f) \circ \partial_*$.

## 2.3 Persistent Homology as a Persistence Module

*Persistent homology* considers filtrations of spaces and observes the lifetime of topological features within the filtration in form of *persistence modules*. The basic premise is that features that persist for a long time are significant, whereas features with a short lifetime are likely to be caused by noise. We refer to appendix J.3 for the basic definitions in this section.

The **persistent homology** $H_*(f)$ of an order preserving function $f \colon K \to \mathbb{R}$ consists of vector spaces $H_*(f)_r = H_*(D(f)_r)$ and transition maps $H_*(f)_{r,s} \colon H_*(D(f)_r) \to H_*(D(f)_s)$ induced by the inclusions $D(f)_r \hookrightarrow D(f)_s$ for $r \leq s$. Note that $H_*(f)$ is a p.f.d persistence module. By a result of see Crawley-Boevey (2012), any p.f.d. persistence module is isomorphic to a direct sum of interval modules $M \cong \bigoplus_{I \in \mathcal{B}(M)} C(I)$. Here, $\mathcal{B}(M)$ denotes the **barcode** of $M$, which is given by a *multiset* of intervals. For a grayscale image matrix $\boldsymbol{I} \in \mathbb{R}^{m \times n}$ with associated filter function $f_{\boldsymbol{I}} \colon K \to \mathbb{R}$, we will refer to the persistent homology of $f_{\boldsymbol{I}}$ as the persistent homology of the image $\boldsymbol{I}$ and denote it by $H_*(\boldsymbol{I})$. Its associated barcode will be denoted by $\mathcal{B}(\boldsymbol{I})$. Note that the persistent homology is **continuous from above**: all intervals in the barcode are of the form $[s, t)$.

(a) $K_1$    (b) $K_2$    (c) $K_3$

Figure 5: A filtered cubical complex with varying homology in degree 1 at each filtration step. Adding the 1-cell in (b) creates homology and adding the 2-cell in (c) turns homology trivial.

In order to compute the barcode $\mathcal{B}(\boldsymbol{I})$, we make use of the *reduction algorithm* described in Edelsbrunner et al. (2008). It starts by sorting the cells of the associated filtered cubical complex $K_*(\boldsymbol{I})$ to obtain a **compatible** ordering $c_1, \dots, c_l$: the cells in $K_i$ preceed the cells in $K \setminus K_i$, and the faces of a cell preceed the cell. This ordering induces a *cell-wise refinement* $L_*(\boldsymbol{I})$ of $K_*(\boldsymbol{I})$. The algoritm then performs a variant of Gaussian elimination on the *boundary matrix* of $K$, with rows and columns indexed by the cells in the compatible ordering. Adding a $d$-cell $c_k$ to the complex will then either create new homology in degree $d$ or turn homology classes in degree $d - 1$ trivial (see Figure 5). In the latter case, assuming that the class that becomes trivial when adding $c_k$ has been created by cell $c_j$ with $j < k$, we pair the cells $c_j$ and $c_k$. This way we partition the set of cells into **persistence pairs** and singletons. Each pair $(c_j, c_k)$, satisfying $f_{\boldsymbol{I}}(c_j) < f_{\boldsymbol{I}}(c_k)$, gives rise to a **finite interval** $[f_{\boldsymbol{I}}(c_j), f_{\boldsymbol{I}}(c_k))$, and each singleton $c_i$ gives rise to an **essential interval** $[f_{\boldsymbol{I}}(c_i), \infty)$

in the barcode of $I$. Note that a finite interval $[f_I(c_j), f_I(c_k))$ determines a **refined interval** $[j, k)$, and we call the set $\mathcal{B}_{\text{fine}}(I)$ of refined intervals the **refined barcode** of $I$. Alternatively, the refined barcode of $I$ can be seen as barcode of the persistent homology of the refined filtration $L_*(I)$.

## 2.4 INDUCED MATCHINGS AND STABILITY OF BARCODES

In order to give a constructive proof for the algebraic stability theorem of persistent homology, the authors of Bauer & Lesnick (2015) introduced the notion of induced matchings, which play a central role in our TopoMatch matching. For the basic terminology in this section we refer to appendix $J.4$.

The following theorem (paraphrased as a special case of the general Theorem 4.2 in Bauer & Lesnick (2015)) is key to the definition of induced matchings:

**Theorem 1** *Let $\Phi\colon M \to N$ be a morphism of p.f.d., staggered persistence modules that are continuous from above. Then there are unique injective maps $\mathcal{B}(\mathrm{im}\,\Phi) \hookrightarrow \mathcal{B}(M)$ and $\mathcal{B}(\mathrm{im}\,\Phi) \hookrightarrow \mathcal{B}(N)$, which map an interval $[b, c) \in \mathcal{B}(\mathrm{im}\,\Phi)$ to an interval $[b, d) \in \mathcal{B}(M)$ with $c \leq d$, and to an interval $[a, c) \in \mathcal{B}(N)$ with $a \leq b$, respectively.*

Note that $\mathrm{im}\,\Phi$ is a p.f.d. submodule of $N$, and we will refer to its barcode as the **image barcode** of $\Phi$. Obviously, the injections in Theorem 1 determine matchings $\mathcal{B}(M) \xrightarrow{\sigma_M} \mathcal{B}(\mathrm{im}\,\Phi) \xrightarrow{\sigma_N} \mathcal{B}(N)$. The **induced matching** of $\Phi$ is then given by the composition $\sigma(\Phi) = \sigma_N \circ \sigma_M$.

Let $I, J \in \mathbb{R}^{m \times n}$ be matrices describing grayscale images, such that $I \geq J$ (entry-wise). Then the sublevel sets of $I$ form subcomplexes of the sublevel sets of $J$ and the corresponding inclusions $D(I)_r \hookrightarrow D(J)_r$ are cubical maps. Hence, they induce maps $H_*(I)_r \to H_*(J)_r$ in homology, which assemble to a persistence map $\Phi(I, J)\colon H_*(I) \to H_*(J)$. We will denote the image barcode of $\Phi(I, J)$ by $\mathcal{B}(I, J)$. Considering the refined filtrations, we obtain staggered persistence modules resulting in refined barcodes $\mathcal{B}_{\text{fine}}(I), \mathcal{B}_{\text{fine}}(J)$. For the computation of the image barcode, we follow the algorithm described in Bauer & Schmahl (2022). It involves the *reduction* of the boundary matrix of $K(I) = K(J)$ with rows indexed by the ordering $c_1, \ldots, c_l$ in $L_*(I)$ and columns indexed by the ordering $d_1, \ldots, d_l$ in $L_*(J)$. A pair $(c_i, d_j)$ satisfying $f_I(c_i) < f_J(d_j)$, obtained by the means of this reduction, then gives rise to an **image persistence pair** $(c_i, d_j)$, which corresponds to the finite interval $[f_I(c_i), f_J(d_j)) \in \mathcal{B}(I, J)$. By matching refined intervals with the image persistence pairs according to Theorem 1, we obtain a matching $\sigma_{\text{fine}}\colon \mathcal{B}_{\text{fine}}(I) \to \mathcal{B}_{\text{fine}}(J)$ between the refined barcodes, which determines the **induced matching** $\sigma(I, J)\colon \mathcal{B}(I) \to \mathcal{B}(J)$ by replacing refined intervals with the corresponding finite interval.

$$
\begin{pmatrix} 0 & 1 & 2 \\ 7 & 39 & 3 \\ 6 & 5 & 4 \end{pmatrix} \qquad \begin{pmatrix} 20 & 27 & 26 \\ 21 & 49 & 25 \\ 22 & 23 & 24 \end{pmatrix} \qquad \begin{pmatrix} 0 & 1 & 2 \\ 7 & 19 & 3 \\ 6 & 5 & 4 \end{pmatrix}
$$

(a) $J_1$      (b) $\sigma(I, J_1)$      (c) $I$      (d) $\sigma(I, J_2)$      (e) $J_2$

Figure 6: (a), (c) and (e) show images which satisfy $I \geq J_1, J_2$. (b) and (d) visualize the induced matchings. Red bars correspond to the barcode of $I$, green bars to the barcodes of $J_1, J_2$ and grey bars to the image barcodes $\mathcal{B}(I, J_1), \mathcal{B}(I, J_2)$. The shaded gray area highlights matched intervals according to their endpoints.

In this work, we augment this induced matching by additionally considering **reverse persistence pairs**, i.e., pairs $(c_i, d_j)$ obtained by the reduction, with $f_I(c_i) \geq f_J(d_j)$ (see Figure 6d). When this is the case, we also match the corresponding intervals in $\mathcal{B}_{\text{fine}}(I)$ and $\mathcal{B}_{\text{fine}}(J)$. Note that this is a slight variation of the induced matching defined in Bauer & Lesnick (2015). This extension satisfies similar properties and is a natural adaptation to our computational context.

## 3 TOPOMATCH – A TOPOLOGICAL MATCHING OF BARCODES AND ITS ASSOCIATED LOSS FUNCTION

Matchings between barcodes have been used for image segmentation tasks and have proven to be successful in improving their topological correctness (see Hu et al. (2019)). In their work, inter-

vals are matched by minimizing a Wasserstein-type distance ignoring the spatial correspondence of topological features (see Figures 1, 2, 9, 10, 11 and appendix D). In general, the structure of interest is given by the foreground (label 1) in image segmentation tasks. Therefore, we consider *superlevel filtrations* instead of sublevel filtrations in applications. For simplicity, we stick to sublevel filtrations to describe the theoretical background. Throughout this section, we denote by $L \in [0,1]^{m \times n}$ a **likelihood map** predicted by a deep neural network, by $P \in \{0,1\}^{m \times n}$ the binarized **prediction** of $L$, and by $G \in \{0,1\}^{m \times n}$ the **ground truth** segmentation.

### 3.1 TOPOLOGICAL MATCHING OF BARCODES

We compare the topologies of the sublevel filtrations $D(L), D(G)$ by matching intervals in their barcodes $\mathcal{B}(L), \mathcal{B}(G)$ using the concept of induced matchings (see Section 2.4). In general, there is no canonical choice of cubical maps between the sublevel sets $D(L)_r$ and $D(G)_r$ that would allow us to compare their topologies directly. Therefore, we introduce a **comparison image** $C = \min(L, G)$ (entry-wise minimum), that captures the topology of both $L$ and $G$. Note that $D(C)_r = D(L)_r \cup D(G)_r$. By construction, we have $L, G \geq C$ and we obtain two induced matchings $\sigma(L, C) \colon \mathcal{B}(L) \to \mathcal{B}(C)$ and $\sigma(G, C) \colon \mathcal{B}(G) \to \mathcal{B}(C)$. The final **TopoMatch matching** $\tau(L, G) \colon \mathcal{B}(L) \to \mathcal{B}(G)$ is then given by the composition

$$\tau(L, G) = \sigma(G, C)^{-1} \circ \sigma(L, C).$$

Working with superlevel sets yields an analogous construction, which is the one we use in applications. We then choose $C = \max(L, G)$ as comparison image. Roughly, in this case the comparison image consists of the foreground of the ground truth $G$ and the background of the likelihood map $L$. Again, each superlevel set of the comparison image is the union of the corresponding superlevel sets of ground truth and likelihood map.

(a) $L$    (b) $\mathcal{B}(L)$    (c) $G$    (d) $\mathcal{B}(G)$    (e) $C$    (f) $\mathcal{B}(C)$

(g) $\sigma(L, C)$    (h) $\sigma(G, C)$    (i) $\tau(L, G)$

Figure 7: An exemplary construction of the TopoMatch matching. (a)–(f) show a predicted likelihood map $L$, a ground truth $G$, the comparison image $C$, and their barcodes (in unique colors). We consider superlevel filtrations and choose $C = \max(L, G)$. (g) and (h) show the induced matchings (matching in grey), and (i) shows the TopoMatch matching between the barcodes in (b) and (d); i.e., we match a red bar to a blue bar if there is a green bar in between.

### 3.2 TOPOMATCH DEFINES A TOPOLIGCAL LOSS FUNCTION FOR IMAGE SEGMENTATION

We denote by $\overline{\mathbb{R}}$ the **extended real line** $\mathbb{R} \cup \{-\infty, \infty\}$. A barcode $\mathcal{B}$ consisting of intervals $[a, b)$ can then equivalently be seen as a multiset $\text{Dgm}(\mathcal{B})$ of points $(a, b) \in \overline{\mathbb{R}}^2$ which lie above the diagonal $\Delta = \{(x, x) \mid x \in \mathbb{R}\}$. Furthermore, we add all the points on the diagonal $\Delta$ with infinite multiplicity to $\text{Dgm}(\mathcal{B})$ and thus define the **persistence diagram** of $\mathcal{B}$. A matching $\sigma \colon \mathcal{B}_1 \to \mathcal{B}_2$ between barcodes then corresponds to a bijection $\sigma \colon \text{Dgm}(\mathcal{B}_1) \to \text{Dgm}(\mathcal{B}_2)$ between persistence

diagrams, by mapping unmatched points $(a, b)$ to their closest point $((a + b)/2, (a + b)/2)$ on the diagonal. We use the two perspectives interchangeably.

Persistent homology is stable, see Chazal et al. (2009a), i.e., there exist metrics on the set of persistence diagrams for which slight variations in the input result in small variations of the corresponding persistence diagrams. Therefore, it is natural to require $\mathrm{Dgm}(\mathcal{B}(\boldsymbol{L}))$ to be similar to $\mathrm{Dgm}(\mathcal{B}(\boldsymbol{G}))$. The Wasserstein distance is a frequently used metric to measure the difference between persistence diagrams (see Cohen-Steiner et al. (2010)), and has been adapted in Hu et al. (2019) to train segmentation networks. Because of the shortcomings described in Figures 1,2,9, 10, 11 and appenix D, we propose to replace the Wasserstein matching $\gamma_*$ by the TopoMatch matching $\tau(\boldsymbol{L}, \boldsymbol{G})$ and define the **TopoMatch loss**

$$L_{\mathrm{TM}}(\boldsymbol{L}, \boldsymbol{G}) = \sum_{p \in \mathrm{Dgm}(\mathcal{B}(\boldsymbol{L}))} \|p - \tau(\boldsymbol{L}, \boldsymbol{G})(p)\|_2^2.$$

Since the values in $\boldsymbol{L}$ and $\boldsymbol{G}$ are contained in $[0, 1]$, we replace the essential intervals $[a, \infty)$ with the finite interval $[a, 1]$, in order to obtain a well-defined expression. To efficiently train segmentation networks, we combine our TopoMatch loss with a standard volumetric loss function, specifically, the *Dice Loss*, to $L_{train} = \alpha L_{\mathrm{TM}}(\boldsymbol{L}, \boldsymbol{G}) + L_{\mathrm{dice}}(\boldsymbol{L}, \boldsymbol{G})$.

### 3.3 TOPOMATCH LOSS AS TOPOLOGICAL EVALUATION METRIC FOR IMAGE SEGMENTATION

A well-established metric to evaluate the topological performance of a segmentation network is the Betti number error, see appendix I, which compares the topological complexity of $\boldsymbol{P}$ and $\boldsymbol{G}$. However, it is limited as it ignores the spatial correspondence of the topological features within their respective images (see Figure 2(b)). Therefore, we also recommend using the TopoMatch loss $L_{\mathrm{TM}}(\boldsymbol{P}, \boldsymbol{G})$ as a refined evaluation metric in place of the Betti number error. Since the entries of $\boldsymbol{P}$ and $\boldsymbol{G}$ take values in $\{0, 1\}$, the only type of interval appearing in their barcodes is $[0, 1)$ and its multiplicity coincides with the number of features in the respective image. Observe that an unmatched interval contributes with $\frac{1}{2}$ to the loss, and a matched pair contributes with 0. Hence, the TopoMatch loss takes values in $\frac{1}{2}\mathbb{N}_0$ and is given by

$$L_{\mathrm{TM}}(\boldsymbol{P}, \boldsymbol{G}) = \frac{1}{2}\bigg(\#\ker(\tau(\boldsymbol{P}, \boldsymbol{G})) + \#\mathrm{coker}(\tau(\boldsymbol{P}, \boldsymbol{G}))\bigg),$$

i.e., half the number of unmatched features in both $\boldsymbol{P}$ and $\boldsymbol{G}$ (see appendix J.3 and J.4 for the definitions).

## 4 EXPERIMENTATION

**Datasets** We employ a set of 6 datasets with diverse topological features for our validation experimentation. Two datasets, the Massachusetts roads dataset and the CREMI neuron segmentation dataset, exhibit frequently connected curvilinear, network-like structures, which form a large number of cycles (topological dimension-1 features) in the foreground. The C.elegans infection live/dead image dataset (Elegans) from the Broad Bioimage Benchmark Collection Ljosa et al. (2012) and our synthetic, modified MNIST dataset LeCun (1998) (synMnist) consist of a balanced number of dimension-0 and dimension-1 features. And third, the colon cancer cell dataset (Colon) from the Broad Bioimage Benchmark Collection Carpenter et al. (2006); Ljosa et al. (2012) and the Massachusetts buildings dataset (Buildings) Mnih (2013) have "blob-like" foreground structures, which have very few dimension-1 features but every instance of a cell or building forms a dimension-0 feature. By *Alexander duality*, the dimension-0 features of the foreground are described by dimension-1 features in the background. Hence, in these two datasets, the background forms a complex topological structure with a large number of cycles, which our method can match efficiently. We choose such a vastly varying set of training datasets to study the efficiency of *TopoMatch* across segmentation tasks and to study the impact of the oftentimes neglected topology of the background class in image segmentation.

**Training of the segmentation networks** For implementation details, e.g., the training splits, please refer to the supplementary material, appendix H. We train all our models for a fixed, dataset-specific number of epochs and evaluate the final model on an unseen test set. We train all models on

an Nvidia P8000 GPU using Adam optimizer. We run experiments on a range of alpha-parameters for all, the clDice Shit et al. (2021), the distance matching based baseline introduced by Hu et al. (2019), and our method; we choose to present the top performing model in Table 1; extended results are given in tables 2, 3, 4,5, 6 in appendix F. All experiments, including their evaluation and standard deviations, will be available in a public GitHub repository.

Table 1: Main results for our *TopoMatch* method and three baselines on six datasets. Green columns indicate the topology-related metrics. Numbers in bold numbers indicate the best performance for a given dataset. We find that *TopoMatch* improves the segmentations in all topological metrics for all datasets. We further observe a constantly high performance in volumetric metrics on all datasets.

| | Loss | Dice | clDice | Acc. | T.M. | T.M.-0 | T.M.-1 | Betti | Betti-0 | Betti-1 |
|---|---|---|---|---|---|---|---|---|---|---|
| CREMI | Dice | **0.894** | 0.939 | **0.959** | 74.82 | 19.84 | 54.98 | 114.12 | 39.12 | 75.00 |
| | clDice | 0.879 | **0.944** | 0.952 | 73.52 | 17.18 | 56.34 | 103.92 | 33.64 | 70.28 |
| | Hu et al. | 0.888 | 0.935 | 0.957 | 81.24 | 22.12 | 59.12 | 118.16 | 43.68 | 74.48 |
| | Ours | 0.893 | 0.941 | **0.959** | **64.90** | **15.50** | **49.40** | **79.16** | **30.36** | **48.80** |
| Roads | Dice | 0.663 | 0.698 | 0.974 | 58.90 | 43.52 | 15.38 | 113.96 | 86.54 | 27.42 |
| | clDice | 0.668 | 0.704 | **0.975** | 65.50 | 51.04 | 14.46 | 125.83 | 101.67 | 24.17 |
| | Hu et al. | **0.674** | 0.712 | 0.974 | 50.50 | 36.52 | 13.98 | 95.83 | 72.54 | 23.29 |
| | Ours | 0.663 | **0.713** | 0.972 | **41.50** | **28.15** | **13.35** | **75.08** | **55.79** | **19.29** |
| synMnist | Dice | 0.871 | 0.907 | 0.962 | 1.849 | 0.979 | 0.870 | 2.590 | 1.674 | 0.916 |
| | clDice | **0.875** | **0.921** | **0.963** | 1.270 | 0.436 | 0.834 | 1.640 | 0.700 | 0.940 |
| | Hu et al. | 0.866 | 0.915 | 0.960 | 1.425 | 0.502 | 0.923 | 1.802 | 0.764 | 1.038 |
| | Ours | 0.849 | 0.915 | 0.954 | **1.140** | **0.265** | **0.875** | **1.348** | **0.426** | **0.922** |
| Elegans | Dice | **0.922** | 0.959 | **0.984** | 2.05 | 1.30 | 0.750 | 2.60 | 1.40 | 1.20 |
| | clDice | 0.917 | **0.964** | 0.982 | 1.95 | 1.10 | 0.850 | 2.20 | 1.20 | **1.00** |
| | Hu et al. | 0.921 | 0.959 | **0.984** | 2.15 | 1.42 | 0.725 | 2.50 | 1.35 | 1.15 |
| | Ours | 0.919 | 0.960 | 0.983 | **1.70** | **1.05** | **0.650** | **1.90** | **0.80** | 1.10 |
| Colon | Dice | 0.899 | 0.863 | 0.970 | 22.13 | 10.88 | 11.25 | 33.75 | 13.75 | 20.00 |
| | clDice | **0.907** | 0.871 | 0.974 | 23.63 | 9.38 | 14.25 | 37.75 | 11.75 | 26.00 |
| | Hu et al. | 0.902 | **0.876** | 0.972 | 17.25 | 7.75 | 9.50 | 22.00 | 7.00 | 15.00 |
| | Ours | **0.907** | 0.871 | **0.975** | **16.00** | **7.13** | **8.88** | **21.50** | **6.25** | **15.25** |
| Buildings | Dice | 0.623 | 0.672 | 0.934 | 286.22 | 275.50 | 10.73 | 162.95 | 151.70 | 11.25 |
| | clDice | **0.632** | **0.693** | 0.931 | 285.60 | 267.98 | 17.63 | 175.50 | 155.05 | 20.45 |
| | Hu et al. | 0.625 | 0.677 | 0.934 | 278.30 | 268.75 | 9.55 | 181.10 | 169.60 | 11.50 |
| | Ours | 0.625 | 0.685 | **0.937** | **244.58** | **235.63** | **8.95** | **118.45** | **107.75** | **10.70** |

## 4.1 RESULTS

**Main Results** Our proposed TopoMatch loss improves the topological correctness of the segmentations across all datasets (Table 1), irrespective of the choice of the hyper-parameters (Table Ablations) compared to all baselines. We show superior scores for the topology metrics Topo-Match (T.M.) and Betti number error (Betti) in both dimension-1 and dimension-0. Further, the volumetric metrics of the segmentations show equivalent, if not superior quantitative results for our method. Our method can be trained from scratch or used to refine pre-trained networks. Importantly, our method improves the topological correctness of curvilinear segmentation problems (Roads, CREMI), blob-segmentation problems (Buildings, Colon), and mixed problems (SynMnist, Elegans). We confidently attribute this to the theoretical guarantees of induced matchings, which hold for the foreground and the background classes in dim-1 and dim-0. For illustration, please consider the Roads and Buildings dataset; essentially, the topology of the background of the Buildings dataset is very similar to the foreground in Roads. Therefore, it is intuitive that our method can efficiently leverage the topology features of both foreground and background when we apply *sub-and superlevelset*-matching. It is of note that for some datasets, the method by Hu et al. (2019) is the best performing baseline and for some Shit et al. (2021).

**Ablation experiments** In order to study the behavior of our loss, we conduct various ablation experiments. First, we study the effect of the $\alpha$ parameter in our method, see table 2,3. We find that increasing $\alpha$ improves the topological metrics. For some datasets, e.g., synMnist, a too high

Figure 8: Qualitative Results on CREMI dataset. (same models used as in table 1). Topological errors are indicated by red circles. Our method leads to less topological errors in the segmentation.

$\alpha$ can compromise the Dice metric; therefore, we conclude that $\alpha$ is a tunable and dataset-specific parameter if one wants to consider the topological matching and the volumetric scores at the same time. For ablation of the alpha in Hu et al. (2019) and Shit et al. (2021), please refer to appendix table 2. Ostensibly, the effect of the $\alpha$ parameter cannot be compared directly. Nonetheless, it appears that our method is more robust towards variation in $\alpha$. Second, we study the effect of applying *TopoMatch* on both the foreground and background (bothlevel) versus solely on the foreground (superlevel). We find that the bothlevel matching is particularly useful if the background has a complex topology (e.g. in buildings), whereas the superlevel matching is as efficient as the bothlevel when the foreground has a more complex topology than the background, e.g., for Roads and CREMI, see table 5.

Third, we test the effect of pre-training and training from scratch for our method and the method by Hu et al. (2019). We show that our method can efficiently if not superiorly, be trained from scratch, whereas the baseline method struggles in that setting, especially on more complex datasets such as CREMI, see table 6. We attribute this property to the fact that our method learns to emphasize the topologically correctly matched features, whereas the baseline method is likely to emphasize the wrong features and penalize geometrically correct features as described in our theory. These incorrect features will then be emphasized repeatedly when training for more epochs, as in the training-from-scratch-setting leading to worse performance. For CREMI we found that the Wasserstein matching matches cycles incorrectly in more then 99 % of the cases, see appendix D.1. Further, we studied the effect of our loss on the Wasserstein matching; we find that our loss better optimizes the Wasserstein matching loss as well, see appendix D.2. Moreover, we experiment with training on a dataset where we add a boundary around images to close all loops which may cross the image border, similar to Hu et al. (2019). We term this **relative TopoMatch**; we observe a negligible effect on all metrics, see table 3. For additional ablation and more metrics on the ablation studies, please refer to the appendix section E. The computational complexity of our matching is $\mathcal{O}(n^3)$, see appendix G for details.

## 5 DISCUSSION

**Concluding remarks**   In this paper, we propose a rigorous method called *TopoMatch*, which enables the faithful quantification of corresponding topological properties in image segmentation. Herein, our method is the first to guarantee the correct matching of persistence barcodes in image segmentation according to their spatial correspondence. We show that *TopoMatch* is efficient as an interpretable segmentation metric, which can be understood as a sharpened variant of the Betti error. Further, we show how our method can be used to train segmentation networks. Training networks using *TopoMatch* is stable and leads to improvements on all 6 datasets. We foresee vast application potential in challenging tasks such as road network and Neuron instance segmentation. We are thus hopeful that our method's theory and experimentation will stimulate future research in this area.

**Limitations**   In the general setting of persistent homology of functions on arbitrary topological spaces, there are instances where maps of persistence modules cannot be written as matchings. This is somewhat analogous to the fact that in linear algebra, certain linear transformations cannot be diagonalized. We did not observe any such case in our specific segmentation setting. A theoretical investigation of this question will be the subject of future work. Further, we understand application-specific experimental limitations. Our method's computational complexity is beyond widely used loss functions such as BCE (see appendix G); moreover, our current implementation is only available in 2D, whereas the theoretical guarantees trivially generalize to 3D.

## 6 REPRODUCIBILITY STATEMENT

To facilitate understanding of the theory section please refer to the basic definitions in the appendix. The core algorithm (TopoMatch) is available as a python script (with a tox example) in the supplementary material and is printed in pseudocode in the appendix, section C. The training details are also described in the appendix, section F. Furthermore, all of our code and all of our experimentation, including baselines and hyperparameters, will be available in a public repository on GitHub after acceptance.

## 7 ETHICS STATEMENT

We, the authors, declare that we strictly adhere to the ICLR Code of Ethics. Our method and experimentation are carried out on (partly modified) public datasets with no known ethical concern associations. Our studies do not involve human subjects and we do not foresee any conflicts of interest and sponsorship, discrimination/bias/fairness concerns, privacy and security issues, legal compliance, and research integrity issues.

## REFERENCES

Shahira Abousamra, Minh Hoai, Dimitris Samaras, and Chao Chen. Localization in the crowd with topological constraints. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 35, pp. 872–881, 2021.

Ulrich Bauer. Ripser: efficient computation of vietoris–rips persistence barcodes. *Journal of Applied and Computational Topology*, 5(3):391–423, 2021.

Ulrich Bauer and Michael Lesnick. Induced matchings and the algebraic stability of persistence barcodes. *Journal of Computational Geometry*, 6(2):162–191, 2015.

Ulrich Bauer and Maximilian Schmahl. Efficient computation of image persistence. *arXiv preprint arXiv:2201.04170*, 2022.

Anne E Carpenter, Thouis R Jones, Michael R Lamprecht, Colin Clarke, In Han Kang, Ola Friman, David A Guertin, Joo Han Chang, Robert A Lindquist, Jason Moffat, et al. Cellprofiler: image analysis software for identifying and quantifying cell phenotypes. *Genome biology*, 7(10):1–11, 2006.

Frédéric Chazal, David Cohen-Steiner, Marc Glisse, Leonidas J Guibas, and Steve Y Oudot. Proximity of persistence modules and their diagrams. In *Proceedings of the twenty-fifth annual symposium on Computational geometry*, pp. 237–246, 2009a.

Frédéric Chazal, David Cohen-Steiner, Marc Glisse, Leonidas J Guibas, and Steve Y Oudot. Proximity of persistence modules and their diagrams. In *Proceedings of the twenty-fifth annual symposium on Computational geometry*, pp. 237–246, 2009b.

Mingfei Cheng, Kaili Zhao, Xuhong Guo, Yajing Xu, and Jun Guo. Joint topology-preserving and feature-refinement network for curvilinear structure segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 7147–7156, 2021.

James Clough, Nicholas Byrne, Ilkay Oksuz, Veronika A Zimmer, Julia A Schnabel, and Andrew King. A topological loss function for deep-learning based image segmentation using persistent homology. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2020.

David Cohen-Steiner, Herbert Edelsbrunner, and John Harer. Stability of persistence diagrams. In *Proceedings of the twenty-first annual symposium on Computational geometry*, pp. 263–271, 2005.

David Cohen-Steiner, Herbert Edelsbrunner, John Harer, and Yuriy Mileyko. Lipschitz functions have l p-stable persistence. *Foundations of computational mathematics*, 10(2):127–139, 2010.

William Crawley-Boevey. Decomposition of pointwise finite-dimensional persistence modules, 2012. URL https://arxiv.org/abs/1210.0819.

Olaf Delgado-Friedrichs, Vanessa Robins, and Adrian Sheppard. Skeletonization and partitioning of digital images using discrete morse theory. *IEEE transactions on pattern analysis and machine intelligence*, 37(3):654–666, 2014.

Herbert Edelsbrunner, John Harer, et al. Persistent homology-a survey. *Contemporary mathematics*, 453:257–282, 2008.

Jan Funke, Fabian Tschopp, William Grisaitis, Arlo Sheridan, Chandan Singh, Stephan Saalfeld, and Srinivas C. Turaga. Large scale image segmentation with structured loss based deep learning for connectome reconstruction. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 41(7):1669–1680, Jul 2019. ISSN 1939-3539. doi: 10.1109/tpami.2018.2835450. URL http://dx.doi.org/10.1109/TPAMI.2018.2835450.

Adélie Garin, Teresa Heiss, Kelly Maggs, Bea Bleile, and Vanessa Robins. Duality in persistent homology of images. *arXiv preprint arXiv:2005.04597*, 2020.

Teresa Heiss and Hubert Wagner. Streaming algorithm for euler characteristic curves of multidimensional images. *CoRR*, abs/1705.02045, 2017. URL http://arxiv.org/abs/1705.02045.

X Hu, Y Wang, F Li, D Samaras, and C Chen. Topology-aware segmentation using discrete morse theory. In *International Conference on Learning Representations (ICLRR)*, 2021.

Xiaoling Hu and Chao Chen. Image segmentation with homotopy warping. *arXiv preprint arXiv:2112.07812*, 2021.

Xiaoling Hu, Fuxin Li, Dimitris Samaras, and Chao Chen. Topology-preserving deep image segmentation. *Advances in neural information processing systems*, 32, 2019.

Viren Jain, Benjamin Bollmann, Mark Richardson, Daniel R Berger, Moritz N Helmstaedter, Kevin L Briggman, Winfried Denk, Jared B Bowden, John M Mendenhall, Wickliffe C Abraham, et al. Boundary learning by optimization with topological constraints. In *2010 IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, pp. 2488–2495. IEEE, 2010.

Tomasz Kaczynski, Konstantin Mischaikow, and Marian Mrozek. *Cubical Homology*, pp. 39–92. Springer New York, New York, NY, 2004. ISBN 978-0-387-21597-6. doi: 10.1007/0-387-21597-2_2. URL https://doi.org/10.1007/0-387-21597-2_2.

Yann LeCun. The mnist database of handwritten digits. *http://yann. lecun. com/exdb/mnist/*, 1998.

Vebjorn Ljosa, Katherine L Sokolnicki, and Anne E Carpenter. Annotated high-throughput microscopy image sets for validation. *Nature methods*, 9(7):637–637, 2012.

Volodymyr Mnih. *Machine Learning for Aerial Image Labeling*. PhD thesis, University of Toronto, 2013.

Agata Mosinska et al. Beyond the pixel-wise loss for topology-aware delineation. In *CVPR*, pp. 3136–3145, 2018.

Doruk Oner, Mateusz Koziński, Leonardo Citraro, Nathan C Dadap, Alexandra G Konings, and Pascal Fua. Promoting connectivity of network-like structures by enforcing region separation. *arXiv preprint arXiv:2009.07011*, 2020.

Nina Otter, Mason A Porter, Ulrike Tillmann, Peter Grindrod, and Heather A Harrington. A roadmap for the computation of persistent homology. *EPJ Data Science*, 6:1–38, 2017.

Kazuma Sasaki, Satoshi Iizuka, Edgar Simo-Serra, and Hiroshi Ishikawa. Joint gap detection and inpainting of line drawings. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 5725–5733, 2017.

Suprosanna Shit, Johannes C Paetzold, Anjany Sekuboyina, Ivan Ezhov, Alexander Unger, Andrey Zhylka, Josien PW Pluim, Ulrich Bauer, and Bjoern H Menze. cldice-a novel topology-preserving loss function for tubular structure segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 16560–16569, 2021.

Hubert Wagner, Chao Chen, and Erald Vuçini. Efficient computation of persistent homology for cubical data. In *Topological methods in data analysis and visualization II*, pp. 91–106. Springer, 2012.

Dominik JE Waibel, Scott Atwell, Matthias Meier, Carsten Marr, and Bastian Rieck. Capturing shape information with multi-scale topological loss terms for 3d reconstruction. *arXiv preprint arXiv:2203.01703*, 2022.

Haotian Wang, Min Xian, and Aleksandar Vakanski. Ta-net: Topology-aware network for gland segmentation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, pp. 1556–1564, 2022.

Xiaohong Wang and Xudong Jiang. Post-processing for retinal vessel detection. In *Tenth International Conference on Digital Image Processing (ICDIP 2018)*, volume 10806, pp. 1442–1446. SPIE, 2018.

Han Zhang and Lok Ming Lui. Topology-preserving segmentation network: A deep learning segmentation framework for connected component. *arXiv preprint arXiv:2202.13331*, 2022.

## A    ADDITIONAL TOPOLOGICAL MATCHING ILLUSTRATION

Figure 9: Topological matchings. Illustration of the advantages of our TopoMatch algorithm over the existing *Wasserstein matching* and the *Betti number error* for two exemplary segmentations. On the left side, we depict a prediction-label pair for an image. On the right side, we depict the matched representative cycles in the same color for the Wasserstein matching (bottom row) and *TopoMatch matching* (top row). Our **TopoMatch** matches the spatially correct features and will penalize the correct features in the loss. Here, the distance matching mismatches the correctly predicted feature with the erroneously predicted feature, leading to a false loss for the wrongly segmented cycle.

Figure 10: Motivation. Our TopoMatch (induced matching) and the Wasserstein matching (Hu et al. (2019)) for Roads label-prediction pairs. The matched cycles (according to the matching methods) are represented in the same color. We randomly sample 7 matched cycles in each pair. We observe that our method correctly matches the cycles in the first two rows. The third row represents an example early in Training. Here we observe that our method correctly matches some "finished" cycles but also provides a correct matching to the blue and green cycles which still have to be closed. Essentially, one can observe here that our TopoMatch leads to a correct loss.

Figure 11: Motivation. Our TopoMatch (induced matching) and the Wasserstein matching (Hu et al. (2019)) for CREMI label-prediction pairs. The matched cycles (according to the matching methods) are represented in the same color. We randomly sample 7 matched cycles in each pair.

# B ADDITIONAL QUALITATIVE RESULTS

Figure 12: Qualitative Results on Roads and Buildings dataset. Image, Label, and different segmentations (same models as table 1). Topological errors are indicated by red circles. Our method leads to improved topology compared to the baselines.

Figure 13: Qualitative Results on CREMI, Elegans and Colon dataset. Image, Label, and different segmentations (same models as table 1). Topological errors are indicated by red circles. Our method leads to improved topology compared to the baselines.

| Image | Label | Dice | clDice | Hu et al. | Ours |

Figure 14: Qualitative Results on SynMnist. Image, Label, and different segmentations (same models as table 1) on examples of the SynMnist testset. Topological errors are indicated by red circles. Our method always segments the correct topology.

## C   DETAIL ALGORITHM

Below, we provide the pseudocode for an efficient realization of the TopoMatch matching. For the computation of the barcodes in dimension-0 we leveraged the *Union-Find* datastructure, which is very efficient at managing equivalence classes. Alexander duality allows us to use it in dimension-1, as well (see Garin et al. (2020)). Moreover, it can also be used for the computation of the image barcodes in both dimensions. Note that we adapt the Union Find class to manage the birth of equivalence classes. We use *clearing* (as proposed in Bauer (2021)) by keeping track of *critical-edges* and *columns-to-reduce*, in order to reduce the amount of operations during the reductions (see sections 2.3, 2.4).

---

**Algorithm 1:** TopoMatch

---

**Data:** $G, L$
**Option:** $relative = False, filtration = `superlevel'$
**Result:** $\mathcal{L}_0, \mathcal{L}_1, \mathcal{L}$

1 **begin**
2    **if** *filtration=`superlevel'* **then**        `// Construction of comparison image`
3      $\lfloor$   $C \leftarrow max(G, L)$
4    **else**
5      $\lfloor$   $C \leftarrow min(G, L)$
6    **end**
7    $\mathcal{B}(G), \mathbb{D}_G, V_G, X_G \leftarrow CubicalPersistence(G, relative, filtration, True)$;
8    $\mathcal{B}(L), \mathbb{D}_L, V_L, X_L \leftarrow CubicalPersistence(L, relative, filtration, True)$;
9    $\mathcal{B}(C), \mathbb{C}_C, V_C, X_C \leftarrow CubicalPersistence(C, relative, filtration, False)$;
10    $\mathcal{B}(G, C) \leftarrow ImagePersistence(\mathbb{D}_G, X_G, \mathbb{C}_C, X_C)$;
11    $\mathcal{B}(L, C) \leftarrow ImagePersistence(\mathbb{D}_L, X_L, \mathbb{C}_C, X_C)$;
12    $\sigma(G, C) \leftarrow InducedMatching(\mathcal{B}(G, C), \mathcal{B}(G), \mathcal{B}(C))$;
13    $\sigma(L, C) \leftarrow InducedMatching(\mathcal{B}(L, C), \mathcal{B}(L), \mathcal{B}(C))$;
14    $\tau(L, G) = \phi$;        `// Initialize matched refined intervals`
15    $\mathbb{U}_0, \mathbb{U}_1 = \mathcal{B}(G)_0, \mathcal{B}(G)_1$ ;    `// Initialize unmatched refined intervals`
      `for ground truth`
16    $\mathbb{V}_0, \mathbb{V}_1 = \mathcal{B}(L)_0, \mathcal{B}(L)_1$ ;    `// Initialize unmatched refined intervals`
      `for prediction`
17    $\mathcal{L}_0 = \mathcal{L}_1 = 0$ ;        `// Initialize TopoMatch loss`
18    **for** $d \leftarrow 0$ **to** $1$ **by** $1$ **do**        `// Loop over dimension-d`
19      **foreach** $m_0 \in \sigma(G, C)_d$ **do**
20        **foreach** $m_1 \in \sigma(L, C)_d$ **do**
21          **if** $m_0[2] = m_1[2]$ **then**    `// Check for same image persistence`
          `pair`
22           Add $((m_0[0], m_0[2], m_1[0]))$ to $\tau(L, G)_d$;
23           Remove $(m_0[0])$ from $\mathbb{U}_d$;
24           Remove $(m_1[0])$ from $\mathbb{V}_d$;
25           Remove $(m_1)$ from $\sigma(L, C)_d$;
26           $p, q = m_0[0], m_1[0]$;
27           $I_0, I_1 = V_G(Index2Coord(p[0])), V_G(Index2Coord(p[1]))$ ;    `// Map`
          `index to value`
28           $J_0, J_1 = V_L(Index2Coord(q[0])), V_L(Index2Coord(q[1]))$ ;    `// Map`
          `index to value`
29           $\mathcal{L}_d = \mathcal{L}_d + (I_0 - J_0)^2 + (I_1 - J_1)^2$ ;       `// Loss for matched`
          `intervals`
30           **break**
31          **end**
32        **end**
33      **end**
34      **foreach** $p \in \mathbb{U}_d$ **do**
35        $I_0, I_1 = V_G(Index2Coord(p[0])), V_G(Index2Coord(p[1]))$ ;    `// Map index`
       `to value`
36        $\mathcal{L}_d = \mathcal{L}_d + \frac{(I_0 - I_1)^2}{2}$ ; `// Loss for unmatched intervals in ground`
       `truth`
37      **end**
38      **foreach** $p \in \mathbb{V}_d$ **do**
39        $I_0, I_1 = V_L(Index2Coord(p[0])), V_L(Index2Coord(p[1]))$ ;    `// Map index`
       `to value`
40        $\mathcal{L}_d = \mathcal{L}_d + \frac{(I_0 - I_1)^2}{2}$ ;        `// Loss for unmatched intervals in`
       `prediction`
41      **end**
42    **end**
43    $\mathcal{L} \leftarrow \mathcal{L}_0 + \mathcal{L}_1$ ;        `// Total TopoMatch loss`
44 **end**

---

```
45  Procedure CubicalPersistence(I, relative, filtration, critical)
46      if relative=True then
47          I ← AddBoundary(I);                              // Add image boundary
48      end
49      V, X, 𝔼 ← FilterCubeMap(I, filtration); // Valuemap, Indexmap & edges
         are computed using the CubeMap datastructure as in Wagner
         et al. (2012)
50      ℬ(I)₀, ℬ(I)₁ = φ;                       // Initialize refined barcodes
51      ℂ = φ; // Initialize columns-to-reduce for the clearning trick
52      if critical=True then
53          𝔻 = φ;   // Initialize critical-edges for the clearing trick
54      end
55      𝒰 = UnionFind(#cubes + 1);         // Instantiate a Union-Find class
56      foreach e ∈ 𝔼 do          // Compute refined intervals in dimension-1
57          b₀, b₁ ← DualBoundary(X, e);    // Find dual boundary of an edge
58          x, y ← 𝒰.find(b₀), 𝒰.find(b₁);
59          if x = y then
60              Add e to ℂ, continue
61          end
62          b = min(𝒰.getbirth(x), 𝒰.getbirth(y));            // Retrieve birth
63          if critical=True then
64              Add e to 𝔻;
65          end
66          if (e, b) is valid then                  // Check for positive interval
67              Add (e, b) to ℬ(I)₁
68          end
69          𝒰.union(x, y)
70      end
71      𝒰 = UnionFind(#cubes);              // Instantiate a Union-Find class
72      foreach e ∈ ℂ do          // Compute refined intervals in dimension-0
73          b₀, b₁ ← Boundary(X, e);                 // Find boundary of an edge
74          x, y ← 𝒰.find(b₀), 𝒰.find(b₁);
75          if x = y then
76              continue
77          end
78          b = max(𝒰.getbirth(x), 𝒰.getbirth(y));            // Retrieve birth
79          if (e, b) is valid then                  // Check for positive interval
80              Add (e, b) to ℬ(I)₀;
81          end
82          𝒰.union(x, y)
83      end
84      if critical=True then
85          return (ℬ(I)₀, ℬ(I)₁), 𝔻, V, X;          // Return refined barcodes,
             critical-edges, Valuemap & Indexmap
86      else
87          return (ℬ(I)₀, ℬ(I)₁), ℂ, V, X;          // Return refined barcodes,
             columns-to-reduce, Valuemap & Indexmap
88      end
```

```
89  Procedure ImagePersistence(𝔻, 𝑿_I, ℂ, 𝑿_J)
90  │   ℬ(𝑰, 𝑱)_0, ℬ(𝑰, 𝑱)_1 = φ ;              // Initialize image persistence pairs
91  │   𝒰 = UnionFind(#cubes) ;                 // Instantiate a Union-Find class
92  │   foreach e ∈ ℂ do                        // Compute pairs in dimension-0
93  │   │   b_0, b_1 ← Boundary(𝑿_I, e);              // Find boundary of an edge
94  │   │   x, y ← 𝒰.find(b_0), 𝒰.find(b_1);
95  │   │   if x = y then
96  │   │   │   continue
97  │   │   end
98  │   │   b = max(𝒰.getbirth(x), 𝒰.getbirth(y));              // Retrieve birth
99  │   │   Add (e, b) to ℬ(𝑰, 𝑱)_0 ; // All pairs for extended induced matching
    │   │      (see Sec.  2.4)
100 │   │   𝒰.union(x, y)
101 │   end
102 │   𝒰 = UnionFind(#cubes + 1) ;            // Instantiate a Union-Find class
103 │   foreach e ∈ 𝔻 do                        // Compute pairs in dimension-1
104 │   │   b_0, b_1 ← DualBoundary(𝑿_J, e);     // Find dual boundary of an edge
105 │   │   x, y ← 𝒰.find(b_0), 𝒰.find(b_1);
106 │   │   if x = y then
107 │   │   │   continue
108 │   │   end
109 │   │   b = min(𝒰.getbirth(x), 𝒰.getbirth(y));              // Retrieve birth
110 │   │   Add (e, b) to ℬ(𝑰, 𝑱)_1 ;        // All intervals for extended induced
    │   │    matching (see Sec.  2.4)
111 │   │   𝒰.union(x, y)
112 │   end
113 │   return (ℬ(𝑰, 𝑱)_0, ℬ(𝑰, 𝑱)_1) ;          // Return image persistence pairs
114 Procedure InducedMatching(ℬ(𝑰, 𝑱), ℬ(𝑰), ℬ(𝑱))
115 │   σ(𝑰, 𝑱)_0, σ(𝑰, 𝑱)_1 = φ ;       // Initialize matched refined intervals
116 │   for d ← 0 to 1 by 1 do                            // Loop over dimension-d
117 │   │   foreach (a, b) ∈ ℬ(𝑰, 𝑱)_d do      // For each image persistence pair
118 │   │   │   m_i, m_j = None;
119 │   │   │   foreach (c, d) ∈ ℬ(𝑰)_d do                  // Match left endpoints
120 │   │   │   │   if c = a then
121 │   │   │   │   │   m_i = (c, d);
122 │   │   │   │   │   break
123 │   │   │   │   end
124 │   │   │   end
125 │   │   │   if m_i = None then              // Skip search if no match found
126 │   │   │   │   continue
127 │   │   │   end
128 │   │   │   foreach (c, d) ∈ ℬ(𝑱)_d do                 // Match right endpoints
129 │   │   │   │   if d = b then
130 │   │   │   │   │   m_j = (c, d);
131 │   │   │   │   │   break
132 │   │   │   │   end
133 │   │   │   end
134 │   │   │   if m_j = None then              // Skip search if no match found
135 │   │   │   │   continue
136 │   │   │   end
137 │   │   │   Add (m_i, (a, b), m_j) to σ(𝑰, 𝑱)_d;
138 │   │   │   Remove m_i from ℬ(𝑰)_d;
139 │   │   │   Remove m_j from ℬ(𝑱)_d;
140 │   │   end
141 │   end
142 │   return (σ(𝑰, 𝑱)_0, σ(𝑰, 𝑱)_1)
```

## D    WASSERSTEIN MATCHING

The $p$th **Wasserstein distance** is frequently used to measure the difference between barcodes; it is given by

$$d_p(\mathcal{B}_1, \mathcal{B}_2) = \inf_{\gamma} \left( \sum_p \|p - \gamma(p)\|_\infty^p \right)^{1/p}$$

for $p \geq 1$, where $\gamma$ runs over all bijections $\mathrm{Dgm}(\mathcal{B}_1) \to \mathrm{Dgm}(\mathcal{B}_2)$ that respect the dimension, and $p$ runs over all points in $\mathrm{Dgm}(\mathcal{B}_1)$. For a likelihood map $\boldsymbol{L} \in [0,1]^{m \times n}$ and a ground truth $\boldsymbol{G} \in \{0,1\}^{m \times n}$, the authors of Hu et al. (2019) adopt this metric to define the **Wasserstein loss**

$$L_{\mathrm{W}}(\boldsymbol{L}, \boldsymbol{G}) = \min_{\gamma} \sum_p \|p - \gamma(p)\|_2^2,$$

where $\gamma$ runs over all bijections $\mathrm{Dgm}(\mathcal{B}(\boldsymbol{L})) \to \mathrm{Dgm}(\mathcal{B}(\boldsymbol{G}))$ that respect the dimension, and $p$ runs over all points of dimension 1 in $\mathrm{Dgm}(\mathcal{B}_1)$. The bijection $\gamma_*$ achieving the minimum corresponds to the **Wasserstein matching** $\mathcal{B}(\boldsymbol{L}) \to \mathcal{B}(\boldsymbol{G})$ of barcodes, which minimizes the squared distance of matched interval endpoints. So the underlying topological features are matched according their local contrast in the images $\boldsymbol{L}$ and $\boldsymbol{G}$. Furthermore, note that $\mathcal{B}(\boldsymbol{G})$ contains exclusively intervals of the form $[0, 1)$, except for one essential interval $[0, \infty)$ in dimension 0. Hence, $\gamma_*$ matches the features in $\boldsymbol{L}$ with enough local contrast in descending order until $\mathcal{B}(\boldsymbol{G})$ runs out of intervals. This procedure results in a matching of topological features, which potentially exhibit no spatial relation within their respective images (see Figures 1,2,9,11,10), and can have a negative impact on the training of segmentation networks. To see this, we distinguish two cases for a fixed interval $I = [a, b) \in \mathcal{B}(\boldsymbol{L})$:

**case 1:** $I$ is matched but there is no corresponding feature in $\boldsymbol{G}$ (*false positive*):
Since $I$ is matched to the interval $[0, 1)$, the loss $L_{\mathrm{W}}$ will be reduced by decreasing the value $a$ and increasing the value $b$. Hence, the neural network will learn to increase the local contrast of the feature in $\boldsymbol{L}$ described by the interval $[a, b)$, but it should be decreased.

**case 2:** $I$ is unmatched but there is a corresponding feature in $\boldsymbol{G}$ (*false negative*):
Since $I$ is unmatched, the bijection $\gamma_*$ will map its corresponding point $p = (a, b) \in \mathrm{Dgm}(\mathcal{B}(\boldsymbol{L}))$ to $((a+b)/2, (a+b)/2)$ and the loss $L_{\mathrm{W}}$ will be reduced by increasing the value $a$ and decreasing the value $b$. Hence, the neural network will learn to decrease the local contrast of the feature in $\boldsymbol{L}$ described by the interval $[a, b)$, but it should be increased.

Both cases are visualized by Figure 2(a) where the cycle in the bottom right of the prediction is a false positive and the cycle in the top left of the prediction is a false negative with respect to the Wasserstein matching, and highlight the importance of using the topologically induced TopoMatch matching instead of the Wasserstein matching for the training of segmentation networks.

For example on the Cremi dataset, we observed that Wasserstein matching has 9.3% false positives out of all matched intervals and 12.6% false negatives out of all reference intervals.

### D.1    FREQUENCY OF "INCORRECT MATCHING" IN WASSERSTEIN MATCHING

Next, we study how frequently these two cases occur. Assuming that the TopoMatch matching is correct, we evaluate the quality of the Wasserstein matching on the CREMI dataset. Therefor, we choose a segmentation model to obtain label-prediction pairs for every image in the CREMI dataset and compute both matchings. Among the 37243 matched intervals in the barcodes of the predictions by the Wasserstein matching, only 224 have been matched correctly, i.e. they achieve a *precision* of 0.6%.

### D.2    WASSERSTEIN LOSS AS BETTI NUMBER ERROR

Observe that for binarized outputs $\boldsymbol{P}$ and ground truth $\boldsymbol{G}$, the Wasserstein loss $L_{\mathrm{W}}(\boldsymbol{P}, \boldsymbol{G})$ coincides with the Betti number error $\beta_{\mathrm{err}}(\boldsymbol{P}, \boldsymbol{G})$. A lower Betti number error of a model trained with our TopoMatch loss compared to a model trained with Wasserstein loss, asserts that TopoMatch loss produces more *faithful* gradients during the training of segmentation networks. Note that, empirically, TopoMatch consistently outperforms Wasserstein in Betti number error (see Tables 1,2.

# E   ADDITIONAL ABLATION EXPERIMENTS

Table 2: $\alpha$ ablation on the synMnist dataset and the Roads dataset

| | | $\alpha$ | Dice | clDice | Acc. | T.M. | T.M.-0 | T.M.-1 | Betti | Betti-0 | Betti-1 | ARI | VOI |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Roads | Ours | 0.0005 | 0.670 | 0.706 | 0.974 | 53.958 | 39.896 | 14.063 | 103.917 | 79.375 | 24.542 | 0.643 | 0.847 |
| | | 0.005 | 0.670 | 0.708 | 0.974 | 51.250 | 37.271 | 13.979 | 97.583 | 74.042 | 23.542 | 0.647 | 0.839 |
| | | 0.05 | 0.667 | 0.709 | 0.974 | 45.396 | 31.667 | 13.729 | 85.042 | 62.833 | 22.208 | 0.655 | 0.828 |
| | | 0.5 | 0.663 | 0.713 | 0.972 | 41.500 | 28.146 | 13.354 | 75.083 | 55.792 | 19.292 | 0.690 | 0.791 |
| | clDice | 0.05 | 0.664 | 0.701 | 0.975 | 77.292 | 61.688 | 15.604 | 151.250 | 123.125 | 28.125 | 0.588 | 0.895 |
| | | 0.1 | 0.663 | 0.697 | 0.975 | 81.188 | 65.979 | 15.208 | 158.375 | 131.708 | 26.667 | 0.599 | 0.885 |
| | | 0.25 | 0.667 | 0.701 | 0.975 | 79.188 | 64.125 | 15.063 | 154.208 | 127.917 | 26.292 | 0.622 | 0.879 |
| | | 0.75 | 0.668 | 0.704 | 0.975 | 65.500 | 51.042 | 14.458 | 125.833 | 101.667 | 24.167 | 0.615 | 0.873 |
| | | 0.5 | 0.663 | 0.696 | 0.975 | 78.625 | 63.750 | 14.875 | 152.417 | 127.000 | 25.417 | 0.618 | 0.874 |
| | Hu et al. | 0.0005 | 0.669 | 0.706 | 0.974 | 53.750 | 39.521 | 14.229 | 102.500 | 78.542 | 23.958 | 0.651 | 0.838 |
| | | 0.005 | 0.674 | 0.712 | 0.974 | 50.500 | 36.521 | 13.979 | 95.833 | 72.542 | 23.292 | 0.660 | 0.836 |
| | | 0.05 | 0.669 | 0.707 | 0.974 | 52.896 | 39.208 | 13.688 | 99.875 | 77.917 | 21.958 | 0.654 | 0.832 |
| | | 0.5 | 0.656 | 0.699 | 0.970 | 58.583 | 44.604 | 13.979 | 105.417 | 88.708 | 16.708 | 0.709 | 0.787 |
| synMnist | Ours | 0.0005 | 0.866 | 0.907 | 0.962 | 1.687 | 0.843 | 0.844 | 2.302 | 1.370 | 0.932 | 0.844 | 0.537 |
| | | 0.005 | 0.871 | 0.920 | 0.962 | 1.270 | 0.458 | 0.812 | 1.596 | 0.732 | 0.864 | 0.873 | 0.481 |
| | | 0.05 | 0.849 | 0.916 | 0.955 | 1.140 | 0.265 | 0.875 | 1.348 | 0.426 | 0.922 | 0.868 | 0.491 |
| | | 0.5 | 0.796 | 0.888 | 0.939 | 1.150 | 0.291 | 0.859 | 1.428 | 0.466 | 0.962 | 0.805 | 0.612 |
| | clDice | 0.05 | 0.871 | 0.911 | 0.963 | 1.616 | 0.796 | 0.820 | 2.264 | 1.328 | 0.936 | 0.871 | 0.483 |
| | | 0.1 | 0.872 | 0.912 | 0.963 | 1.642 | 0.816 | 0.826 | 2.320 | 1.384 | 0.936 | 0.862 | 0.506 |
| | | 0.25 | 0.874 | 0.917 | 0.963 | 1.342 | 0.519 | 0.823 | 1.764 | 0.826 | 0.938 | 0.877 | 0.461 |
| | | 0.5 | 0.875 | 0.922 | 0.963 | 1.270 | 0.436 | 0.834 | 1.640 | 0.700 | 0.940 | 0.881 | 0.454 |
| | | 0.75 | 0.869 | 0.921 | 0.961 | 1.196 | 0.401 | 0.795 | 1.580 | 0.622 | 0.958 | 0.888 | 0.429 |
| | Hu et al. | 0.0005 | 0.872 | 0.909 | 0.963 | 1.881 | 1.001 | 0.880 | 2.650 | 1.686 | 0.964 | 0.880 | 0.461 |
| | | 0.005 | 0.870 | 0.908 | 0.962 | 1.787 | 0.911 | 0.876 | 2.498 | 1.514 | 0.984 | 0.864 | 0.504 |
| | | 0.05 | 0.867 | 0.916 | 0.960 | 1.425 | 0.502 | 0.923 | 1.802 | 0.764 | 1.038 | 0.893 | 0.425 |
| | | 0.5 | 0.785 | 0.862 | 0.935 | 1.754 | 0.562 | 1.192 | 1.968 | 0.840 | 1.128 | 0.814 | 0.589 |

Table 3: Relative Frame ablation of our method on the Roads dataset

| | $\alpha$ | Dice | clDice | Acc. | T.M. | T.M.-0 | T.M.-1 | Betti | Betti-0 | Betti-1 | ARI | VOI |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| relative | 0.0005 | 0.670 | 0.706 | 0.974 | 53.958 | 39.896 | 14.063 | 103.917 | 79.375 | 24.542 | 0.643 | 0.847 |
| | 0.005 | 0.670 | 0.708 | 0.974 | 51.250 | 37.271 | 13.979 | 97.583 | 74.042 | 23.542 | 0.647 | 0.839 |
| | 0.05 | 0.667 | 0.709 | 0.974 | 45.396 | 31.667 | 13.729 | 85.042 | 62.833 | 22.208 | 0.655 | 0.828 |
| | 0.5 | 0.663 | 0.713 | 0.972 | 41.500 | 28.146 | 13.354 | 75.083 | 55.792 | 19.292 | 0.690 | 0.791 |
| non-relative | 0.0005 | 0.669 | 0.706 | 0.974 | 54.729 | 40.521 | 14.208 | 104.542 | 80.542 | 24.000 | 0.654 | 0.835 |
| | 0.005 | 0.671 | 0.709 | 0.974 | 50.250 | 36.479 | 13.771 | 95.167 | 72.458 | 22.708 | 0.661 | 0.829 |
| | 0.005 | 0.669 | 0.712 | 0.973 | 46.104 | 32.271 | 13.833 | 84.708 | 64.042 | 20.667 | 0.675 | 0.818 |
| | 0.5 | 0.661 | 0.711 | 0.972 | 41.417 | 28.167 | 13.250 | 75.583 | 55.833 | 19.750 | 0.695 | 0.787 |

Table 4: dimension-1 and dimensions-0,1 matching ablation for the Hu et al. method on the Roads dataset

| | $\alpha$ | Dice | clDice | Acc. | T.M. | T.M.-0 | T.M.-1 | Betti | Betti-0 | Betti-1 | ARI | VOI |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| dim-1 | 0.0005 | 0.669 | 0.706 | 0.974 | 53.750 | 39.521 | 14.229 | 102.500 | 78.542 | 23.958 | 0.651 | 0.838 |
| | 0.005 | 0.674 | 0.712 | 0.974 | 50.500 | 36.521 | 13.979 | 95.833 | 72.542 | 23.292 | 0.660 | 0.836 |
| | 0.05 | 0.669 | 0.707 | 0.974 | 52.896 | 39.208 | 13.688 | 99.875 | 77.917 | 21.958 | 0.654 | 0.832 |
| | 0.5 | 0.656 | 0.699 | 0.970 | 58.583 | 44.604 | 13.979 | 105.417 | 88.708 | 16.708 | 0.709 | 0.787 |
| dim-0,1 | 0.0005 | 0.672 | 0.709 | 0.974 | 54.292 | 40.104 | 14.188 | 104.083 | 79.708 | 24.375 | 0.649 | 0.839 |
| | 0.005 | 0.673 | 0.710 | 0.974 | 52.750 | 38.625 | 14.125 | 100.667 | 76.750 | 23.917 | 0.656 | 0.836 |
| | 0.05 | 0.668 | 0.708 | 0.974 | 47.000 | 33.146 | 13.854 | 88.083 | 65.792 | 22.292 | 0.649 | 0.832 |
| | 0.5 | 0.662 | 0.711 | 0.972 | 44.708 | 31.292 | 13.417 | 80.583 | 62.083 | 18.500 | 0.692 | 0.798 |

Table 5: bothlevel versus superlevel matching of our method on the Elegans dataset and the CREMI dataset. The bothlevel matching appears to have a more pronounced contribution in the scenario of topologically complex background

| level | $\alpha$ | Dice | clDice | Acc. | T.M. | T.M.-0 | T.M.-1 | Betti | Betti-0 | Betti-1 | ARI | VOI |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Elegans bothlevel | 0.005 | 0.919 | 0.960 | 0.983 | 1.700 | 1.050 | 0.650 | 1.900 | 0.800 | 1.100 | 0.927 | 0.360 |
| Elegans superlevel | 0.005 | 0.916 | 0.954 | 0.983 | 2.150 | 1.350 | 0.800 | 2.400 | 1.300 | 1.100 | 0.906 | 0.427 |
| CREMI bothlevel | 0.5 | 0.887 | 0.946 | 0.955 | 60.480 | 12.920 | 47.560 | 52.080 | 25.280 | 26.800 | 0.929 | 0.359 |
| CREMI superlevel | 0.5 | 0.888 | 0.945 | 0.955 | 59.200 | 14.400 | 44.800 | 52.240 | 28.160 | 24.080 | 0.931 | 0.352 |

Table 6: Pretraining vs training from scratch of ours and the Hu et al. method on the Elegans dataset

| | Training | $\alpha$ | Dice | clDice | Acc. | T.M. | T.M.-0 | T.M.-1 | Betti | Betti-0 | Betti-1 | ARI | VOI |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| CREMI | Ours f. scratch | 0.05 | 0.882 | 0.938 | 0.953 | 65.06 | 13.94 | 51.12 | 45.72 | 27.16 | 18.56 | 0.919 | 0.393 |
| | Ours pretrained | 0.05 | 0.889 | 0.940 | 0.957 | 65.68 | 14.26 | 51.42 | 64.40 | 27.96 | 36.44 | 0.905 | 0.437 |
| | Hu et al. f. scratch | 0.05 | 0.880 | 0.932 | 0.953 | 82.76 | 27.92 | 54.84 | 55.28 | 30.32 | 0.905 | 0.436 |
| | Hu et al. pretrained | 0.05 | 0.895 | 0.942 | 0.960 | 66.40 | 17.76 | 48.64 | 75.36 | 34.96 | 40.40 | 0.909 | 0.425 |
| Elegans | Ours f. scratch | 0.005 | 0.919 | 0.960 | 0.983 | 1.700 | 1.050 | 0.650 | 1.90 | 0.80 | 1.10 | 0.927 | 0.359 |
| | Ours pretrained | 0.005 | 0.924 | 0.963 | 0.984 | 1.950 | 1.200 | 0.750 | 2.30 | 1.20 | 1.10 | 0.939 | 0.313 |
| | Hu et al. f. scratch | 0.005 | 0.921 | 0.959 | 0.984 | 2.150 | 1.425 | 0.725 | 2.50 | 1.35 | 1.15 | 0.929 | 0.350 |
| | Hu et al. pretrained | 0.005 | 0.921 | 0.962 | 0.984 | 2.075 | 1.250 | 0.825 | 2.55 | 1.30 | 1.25 | 0.929 | 0.349 |

## F    DATASETS AND TRAINING SPLITS

The full training routine with the complete trainingsets and testsets will be available with our github repository [1]. All our trainings are done on patches of $48 \times 48$ pixels. For the buildings dataset Mnih (2013), we downsample the images to $375 \times 375$ pixels and randomly choose 80 samples for training and 20 for testing. For each epoch, we randomly sample 8 patches from each sample. For the Colon dataset Carpenter et al. (2006); Ljosa et al. (2012), we downsample the images to $256 \times 256$ pixels; we randomly choose 20 samples for training and 4 for testing. For each epoch, we randomly sample 12 patches from each sample. For the CREMI dataset Funke et al. (2019), we downsample the images to $312 \times 312$ pixels; we choose 100 samples for training and 25 for testing. For each epoch, we randomly sample 4 patches from each sample. For the Elegans dataset Ljosa et al. (2012), we crop the images to $96 \times 96$ pixels; we randomly choose 80 samples for training and 20 for testing. For each epoch, we randomly sample 1 patch from each sample. For the synMnist dataset LeCun (1998), we synthetically modify the MNIST dataset to an image size of $48 \times 48$ pixels; please see our GitHub repository for details; we train on 4500 full, randomly chosen images and use 1500 for testing. For the Roads dataset Mnih (2013), we downsample the images to $375 \times 375$ pixels; we randomly choose 100 samples for training and 24 for testing. For each epoch, we randomly sample 8 patches from each sample.

## G    COMPUTATIONAL COMPLEXITY

For a grayscale image represented by a matrix $\boldsymbol{I} \in \mathbb{R}^{M,N}$, we have $n = MN$ number of pixels and form a cubical grid complex of dimension $d = 2$. The computation of the filtration and the boundary matrix can be done efficiently using the CubeMap data structure (see Wagner et al. (2012)) with $\mathcal{O}(3^d n + d^2 n)$ time and $\mathcal{O}(d^2 n)$ space complexity. Computing the barcodes, by means of the reduction algorithm, requires cubic complexity in the number of pixels $\mathcal{O}(n^3)$ (see Otter et al. (2017)). Despite our empirical acceleration due to the Union-Find class and clearing tricks (as described in Bauer & Schmahl (2022); Bauer (2021)), the order complexity remains $\mathcal{O}(n^3)$. We need $\mathcal{O}(n^2)$ time complexity for computing the final matching and loss. It is noteworthy that Hu et al. (2019) also needs $\mathcal{O}(n^3)$ time complexity to compute the barcode and $\mathcal{O}(n^2)$ for the matching, whereas Shit et al. (2021) requires relatively lower complexity $\mathcal{O}(n)$ due to overlap based loss formulation.

---

[1] github/anonymous

# H    NETWORK SPECIFICATIONS

We use the following notation:

1. In(*input channels*), Out(*output channels*), BI(*output channels*) present input, output, and bottleneck information (for U-Net);

2. C(*filter size, output channels*) denote a convolutional layer followed by *ReLU* and batch-normalization;

3. U(*filter size, output channels*) denote a trans-posed convolutional layer followed by *ReLU* and batch-normalization;

4. $\downarrow 2$ denotes maxpooling;

5. $\oplus$ indicates concatenation of information from an encoder block.

## H.1    UNET CONFIGURATION-I

We use this configuration for CREMI, synthMNIST, Colon and Elegans dataset. This is a lightweight U-net which has sufficient expressive power for these datasets.

**ConvBlock :**   $C_B(3, out\ size) \equiv C(3, out\ size) \rightarrow C(3, out\ size) \rightarrow\downarrow 2$

**UpConvBlock:**   $U_B(3, out\ size) \equiv U(3, out\ size) \rightarrow \oplus \rightarrow C(3, out\ size)$

**Encoder :**   $IN(1/3\ \text{ch}) \rightarrow C_B(3, 16) \rightarrow C_B(3, 32) \rightarrow C_B(3, 64) \rightarrow C_B(3, 128) \rightarrow C_B(3, 256) \rightarrow B(256)$

**Decoder :**   $B(256) \rightarrow U_B(3, 256) \rightarrow U_B(3, 128) \rightarrow U_B(3, 64) \rightarrow U_B(3, 32) \rightarrow U_B(3, 16) \rightarrow Out(1)$

## H.2    UNET CONFIGURATION-II

We had to choose a different U-Net architecture for the road and building dataset because we realized that a larger model is needed to learn useful features for this complex task.

**ConvBlock :**   $C_B(3, out\ size) \equiv C(3, out\ size) \rightarrow C(3, out\ size) \rightarrow\downarrow 2$

**UpConvBlock:**   $U_B(3, out\ size) \equiv U(3, out\ size) \rightarrow \oplus \rightarrow C(3, out\ size)$

**Encoder :**   $IN(3\ \text{ch}) \rightarrow C_B(3, 64) \rightarrow C_B(3, 128) \rightarrow C_B(3, 256) \rightarrow C_B(3, 512) \rightarrow C_B(3, 1024) \rightarrow B(1024)$

**Decoder :**   $B(1024) \rightarrow U_B(3, 1024) \rightarrow U_B(3, 512) \rightarrow U_B(3, 256) \rightarrow U_B(3, 128) \rightarrow U_B(3, 64) \rightarrow Out(1)$

# I    EVALUATION METRICS

We evaluate our experiments using a set of topological and pixel-based metrics. The metrics are computed with respect to the binarized predictions. Here, TopoMatch constitutes the most meaningful quantification, see section 3.3. We calculate the TopoMatch metric for dimension-0 (T.M.-0) and dimension-1 (T.M.-1) as well as their sum (T.M.). Furthermore, we implement the **Betti number error** for dimension-0 (Betti 0), dimension-1 (Betti 1), and their sum (Betti):

$$\beta_{\text{err}}(\boldsymbol{P}, \boldsymbol{G}) = \sum_{d=0}^{\infty} |\beta_d(D(\boldsymbol{P})_{0.5}) - \beta_d(D(\boldsymbol{G})_{0.5})|,$$

It is important to consider the dimensions separately since they have different relevance on different datasets. E.g., Roads has many 1-cycles, whereas Buildings has many 0-cycles (connected components).

Additionally, we use the traditional Dice metric and Accuracy, which describe the in total correctly classified pixels, as well as the clDice metric from Shit et al. (2021). Here, we calculate the clDice between the volumes and the skeleta, extracted using the *skeletonize* function of the skimage python-library. We compute all metrics on the individual test images of their respective size (without patching) and take the mean across the whole testset.

## J  BASIC DEFINITIONS AND TERMINOLOGY

### J.1  CUBICAL COMPLEXES

A $d$-dimensional **(cubical) cell** in $\mathbb{R}^n$ is the Cartesian product $c = \prod_{j=1}^{n} I_j$ of intervals $I_j = [a_j, b_j]$ with $a_j \in \mathbb{Z}$, $b_j \in \{a_j, a_j + 1\}$ and $d \in \{0, \dots, n\}$ is the number of non-degenerate intervals among $\{I_1, \dots, I_d\}$.

If $c$ and $d$ are cells and $c \subseteq d$, we call $c$ a **face** of $d$ of **codimension** $\dim(d) - \dim(c)$. A face of codimension one is also called a **facet**.

A $d$-dimensional **(cubical) complex** in $\mathbb{R}^n$ is a finite set of cubical cells in $\mathbb{R}^n$ with maximal dimension $d$ that is closed under the face relation, i.e., if $d \in K$ and $c$ is a face of $d$, then $c \in K$. Furthermore we call a cubical complex $K' \subseteq K$ a **subcomplex** of $K$.

A **filtration** of a cubical complex $K$ is given by a family $(K_r)_{r \in \mathbb{R}}$ of subcomplexes of $K$, which satisfies:

(1) $K_r \subseteq K_s$ for all $r \leq s$,

(2) $K = K_r$ for some $r \in \mathbb{R}$.

A **filtered (cubical) complex** $K_*$ is a cubical complex $K$ together with a nested sequence of subcomplexes, i.e., a sequence of complexes

$$\emptyset = K_0 \subseteq K_1 \dots \subseteq K_m = K.$$

A function $f \colon K \to \mathbb{R}$ on a cubical complex is said to be **order preserving** if $f(c) \leq f(d)$ for a face $c$ of a cell $d$.

### J.2  HOMOLOGY

A **chain complex** $C_*$ consists of a family $\{C_d\}_{d \in \mathbb{Z}}$ of vector spaces and a family of linear maps $\{\partial_d \colon C_d \to C_{d-1}\}_{d \in \mathbb{Z}}$ that satisfy $\partial_{d-1} \circ \partial_d = 0$.

A map $f \colon K \to K'$ between cubical complexes is said to be **cubical** if it respects the face relation, i.e., $f(c)$ must be a face of $f(d)$ in $K'$ if $c$ is a face of $d$ in $K$.

### J.3  PERSISTENCE MODULES

A **persistence module** $M$ consists of a family $\{M_r\}_{r \in \mathbb{R}}$ of vector spaces, which are connected by linear **transition maps** maps $M_{r,s} \colon M_r \to M_s$ for all $r \leq s$, such that

(1) $M_{r,r} = \mathrm{id}_{M_r}$ for all $r \in \mathbb{R}$,

(2) $M_{s,t} \circ M_{r,s} = M_{r,t}$ for $r \leq s \leq t$.

$M$ is said to be **pointwise finite-dimensional** (p.f.d.) if $M_r$ is finite-dimensional for every $r \in \mathbb{R}$.

A basic example of a persistence module is an **interval module** $C(I)$ for a given interval $I \subseteq \mathbb{R}$. It consists of vector spaces

$$C(I)_r = \begin{cases} \mathbb{F}_2 & \text{if } r \in I, \\ 0 & \text{otherwise.} \end{cases}$$

and transition maps

$$C(I)_{r,s} = \begin{cases} \mathrm{id}_{\mathbb{F}_2} & \text{if } r, s \in I, \\ 0 & \text{otherwise.} \end{cases}$$

for $r \leq s$.

A **morphism** $\Phi \colon M \to N$ between persistence modules is a family $\{\Phi_r \colon M_r \to N_r\}_{r \in \mathbb{R}}$ of linear maps, such that for all $r \leq s$ the following diagram commutes:

$$
\begin{array}{ccc}
M_r & \xrightarrow{M_{r,s}} & M_s \\
{\scriptstyle \Phi_r} \downarrow & & \downarrow {\scriptstyle \Phi_s} \\
N_r & \xrightarrow[N_{r,s}]{} & N_s
\end{array}
$$

We call $\Phi$ an **isomorphism** (resp. **monomorphism**, **epimorphism**) of persistence modules if $\Phi_r$ is a isomorphism (resp. monomorphism, epimorphism) of vector spaces for all $r \in \mathbb{R}$.

For a family $\{M_i\}_{i \in I}$ of persistence modules, the **direct sum** $\bigoplus_{i \in I} M_i$ is the persistence module consisting of vector spaces $(\bigoplus_{i \in I} M_i)_r = \bigoplus_{i \in I} (M_i)_r$ for all $r \in \mathbb{R}$ and transition maps $(\bigoplus_{i \in I} M_i)_{r,s} = \bigoplus_{i \in I} (M_i)_{r,s}$ for all $r \leq s \in \mathbb{R}$.

A **multiset** $X$ consists of a set $|X|$ together with a **multiplicity function** $\mathrm{mult}_X \colon |X| \to \mathbb{N} \cup \{\infty\}$. Equivalently it can be represented by its **underlying set** $\amalg X = \bigcup_{x \in |X|} \coprod_{i=1}^{\mathrm{mult}_X(x)} \{x\}$. We say $X$ is finite if its underlying set $\amalg X$ is finite and its cardinality $\#X$ is given by the cardinality of its underlying set.

Let $K_*$ be a filtered cubical complex and $L_*$ a cell-wise refinement according to the compatible ordering $c_1, \ldots, c_l$ of the cells in $K$. The **boundary matrix** $\boldsymbol{B} \in \mathbb{F}_2^{l \times l}$ of $L_*$ is given entry-wise by

$$\boldsymbol{B}_{i,j} = \begin{cases} 1 & \text{if } \sigma_i \text{ is a facet of } \sigma_j, \\ 0 & \text{otherwise.} \end{cases}$$

## J.4 MATCHINGS

A **map** $f \colon X \to Y$ between multisets is a map $f \colon \amalg X \to \amalg Y$ between their underlying sets.

A **matching** $\sigma \colon X \to Y$ between multisets is a bijection $\sigma \colon X' \to Y'$ for some multisets $X', Y'$ that satisfy $\amalg X' \subseteq \amalg X$ and $\amalg Y' \subseteq \amalg Y$. We call

- $\mathrm{coim}(\sigma) = X'$ the **coimage** of $\sigma$,
- $\mathrm{im}(\sigma) = Y'$ the **image** of $\sigma$,
- $\ker(\sigma) = X \setminus X'$ the **kernel** and of $\sigma$,
- $\mathrm{coker}(\sigma) = Y \setminus Y'$ the **cokernel** of $\sigma$.

For a morphism $\Phi \colon M \to N$ of persistence modules, the **image** of $\Phi$ is the persistence module $\mathrm{im}(\Phi)$, with $\mathrm{im}(\Phi)_r = \mathrm{im}(\Phi_r)$ and transition maps $\mathrm{im}(\Phi)_{r,s} = N_{r,s}|_{\mathrm{im}(\Phi_r)} \colon \mathrm{im}(\Phi_r) \to \mathrm{im}(\Phi_s)$ for $r, s \in \mathbb{R}$.

Let $M, N$ be persistence modules. We call $M$ a **(persistence) submodule** of $N$ if $M_r$ is a subspace of $N_r$ for every $r \in \mathbb{R}$ and the inclusions $i_r \colon M_r \hookrightarrow N_r$ assemble to a persistence map $i = (i_r)_{r \in \mathbb{R}}$. In this case we write $M \subseteq N$.

The composition of two matchings $X \xrightarrow{\sigma_1} Y \xrightarrow{\sigma_2} Z$ is given by the composition of the bijections

$$\sigma_1^{-1}(Y') \xrightarrow{\sigma_1} Y' \xrightarrow{\sigma_2} \sigma_2(Y'),$$

with $Y' = \amalg \, \mathrm{im}(\sigma_1) \cap \amalg \, \mathrm{coim}(\sigma_2)$.

A persistence module $M$ is said to be **staggered** if every real number $r \in \mathbb{R}$ occurs at most once as endpoint of an interval in $\mathcal{B}(M)$.