DISTRIBUTIONALLY ROBUST MODELS WITH PARAMETRIC LIKELIHOOD RATIOS

ABSTRACT

As machine learning models are deployed ever more broadly, it becomes increasingly important that they are not only able to perform well on their training distribution, but also yield accurate predictions when confronted with distribution shift. The Distributionally Robust Optimization (DRO) framework proposes to address this issue by training models to minimize their expected risk under a collection of distributions, to imitate test-time shifts. This is most commonly achieved by instance-level re-weighting of the training objective to emulate the likelihood ratio with possible test distributions, which allows for estimating their empirical risk via importance sampling. However, re-weighting schemes in the literature are usually limited due to the difficulty of keeping the optimization problem tractable and the complexity of enforcing normalization constraints. In this paper, we show that two simple ideas – mini-batch level normalization and a KL penalty – allow us to train models with DRO using a broader class of parametric likelihood ratios. In a series of experiments on both image and text classification benchmarks, we find that models trained with the resulting parametric adversaries are consistently more robust to distribution shifts when compared to other DRO approaches, and that the method performs reliably well with little hyper-parameter tuning.

1 INTRODUCTION

It is well acknowledged that modern neural-network based machine learning models tend to under-perform when they are evaluated on data distributions that differ from the one they were trained on. For example, machine learning model performance has been observed to degrade under train-test mismatch in topics (Gururangan et al., 2020), demographics (Blodgett et al., 2016; Amodei et al., 2016; Hovy & Søgaard, 2015; Grother et al., 2019), geographic regions (Koh et al., 2020), and even data collection processes (Beery et al., 2018; Zech et al., 2018; Michel & Neubig, 2018). In particular, these models often perform poorly when evaluated on subpopulations, domains that are present but underrepresented in their training data (Sagawa et al., 2020), and they can latch on to spurious correlations (McCoy et al., 2019). This has problematic real-world consequences: when such models are deployed at large, this representation disparity can, for example, unfairly affect minority groups (Buolamwini & Gebru, 2018; Hashimoto et al., 2018).

This behaviour can largely be explained by the empirical risk minimization (ERM) principle which underlies the majority of learning algorithms used in practice. In ERM, models are trained to minimize the expectation of a loss function under a fixed training distribution (Vapnik, 1992). This favors models which perform well *on average* on a fixed training set, as opposed to models which would perform equally well on a variety of subpopulations that better reflects the diverse set of distributions that can be encountered at test time. On the other hand, Distributionally robust optimization (DRO) proposes an appealing alternative to ERM. In DRO, models are trained to minimize their worst case risk under a pre-determined family of distributions $\mathcal{Q}$, called the "uncertainty set":

$$\mathcal{L}_{\text{DRO}}(\theta) = \max_{q \in \mathcal{Q}} \mathbb{E}_{(x,y) \sim q} \, \ell_\theta(x, y). \tag{1}$$

In the absence of explicit information about the sub-populations of interest (which would naturally define $\mathcal{Q}$), it is up to the practitioner to carefully define this uncertainty set. This has been the subject of much work in the literature (see Rahimian & Mehrotra (2019) for a survey). Recently, Michel et al.

(2021) proposed P-DRO, a promising approach where the uncertainty set is defined by a parametric family of generative models, which allows for more flexibility in defining the uncertainty set. P-DRO shows significant improvement over comparable baselines, but it suffers from several drawbacks. First, it presupposes the availability of generative models capable of outputting exact densities, which limits its field of application to modalities where such models are readily available (such as language models in NLP). Second, it is challenging to use in practice due to its reliance on a number of hyperparameters and approximations to the objective function.

In this paper, we propose a new approach for DRO, called R-PDRO, based on a key modification of the P-DRO algorithm: instead of modeling the worst-case distributions directly, we parametrize the likelihood ratio between the training distribution and the worst-case distribution. This removes the dependency on an unwieldy generative model, making the method useful for more applications. While likelihood-ratio formulations of DRO have been tried in prior work (Sagawa et al., 2020), we show that they are particularly effective for parametric, neural-network based adversaries. Our approach relies on two simple ideas: a mini-batch level normalization strategy to enforce likelihood ratio constraints and a penalty-form to the KL divergence uncertainty set. R-PDRO consistently achieves equal or better robust sub-population accuracy compared to P-DRO and other baselines on a variety of standard benchmarks in image and text classification. In addition, we find it is both faster than P-DRO and depends on fewer hyper-parameters. Additional ablation experiments demonstrate that our minibatch normalization strategy is necessary for high performance. Finally, we perform experimental analyses to shed light on the advantages brought by parametric adversaries compared to their non-parametric counterparts.

2 BACKGROUND

In the following, we consider a model parametrized by $\theta \in \mathbb{R}^{d_{\text{model}}}$. Our goal is to find a model which minimizes the loss function $\ell_\theta(x, y)$ on pairs of inputs and outputs $(x, y) \in \mathcal{X} \times \mathcal{Y}$. For instance, x might represent images and y a categorical label. Parameters θ are estimated on a training dataset $\mathcal{D}_{\text{train}} = \{(x_i, y_i)\}_{i=1...N_{\text{train}}}$ which we assume to be drawn from a training distribution p.

The DRO optimization problem with uncertainty set $\mathcal{Q}$ is

$$\min_\theta \max_{q \in \mathcal{Q}} \mathbb{E}_q \, \ell_\theta(x, y). \tag{2}$$

We refer to the solution of the inner maximum as the "adversary".

The DRO loss in Equation 1 provides an upper bound on the expected loss of the model under any distribution in the uncertainty set $\mathcal{Q}$, which motivates the use the minimizer of the min-max game in Equation 2 as a robust model. However this objective is only useful insofar that $\mathcal{Q}$ (1) covers test distributions of interest (corresponding to different domains, demographics, etc.) and (2) is not overly pessimistic. To fulfil this second condition, there should exist some model θ^* that achieves low loss simultaneously on the test distribution as well as $\mathcal{Q}$. This often requires that $\mathcal{Q}$ only contain distributions that are covariate shifts of the test distribution, *i.e.* that are such that the conditional distribution $q(y \mid x)$ coincides with that of training distribution $p(y \mid x)$.

2.1 NON-PARAMETRIC DRO

There is substantial existing work on *non-parametric* formulations of DRO, where $\mathcal{Q}$ is expressed as a divergence ball centered at the training distribution. This includes f-divergences (Ben-Tal et al., 2013; Hu & Hong, 2013; Faury et al., 2020), Wasserstein/IPM (Sinha et al., 2018; Husain, 2020), moment constraints (Delage & Ye, 2010; Nguyen et al., 2020), and CVaR (Fan et al., 2017; Curi et al., 2020; Levy et al., 2020) based uncertainty sets. These nonparametric approaches are appealing as they require very little domain-specific knowledge, have well-understood theory (Duchi & Namkoong, 2018), and optimization procedures (*e.g.* Hu & Hong (2013) for KL constraints and Levy et al. (2020) for χ_2 and CVaR constraints).

Unfortunately, nonparametric DRO algorithms suffer from being overly pessimistic. Their uncertainty sets tend to include distributions that are exceedingly difficult to learn, or not representative of real-world distribution shifts. Furthermore, they often cannot enforce even basic constraints such as covariate shift structures (Duchi et al., 2020; Hu et al., 2018). Group-structured DRO uncertainty sets

(Sagawa et al., 2020) overcome some of these challenges, but require significant domain expertise to pre-specify target subpopulations that a model should be robust to.

2.2 PARAMETRIC DRO

Parametric DRO (Michel et al., 2021) is a method for DRO in which the uncertainty set $\mathcal{Q}$ is defined as a family of parametric generative models, which avoids the extreme pessimism of non-parametric DRO without the explicit specification of subpopulations. Specifically, given a generative model q_ψ parameterized by $\psi \in \mathbb{R}^{d_{\text{adv}}}$, the KL-constrained parametric DRO objective can be written as follows:

$$\min_\theta \max_{\substack{\psi \\ \text{KL}(q_\psi \| p) \leq \kappa}} \mathbb{E}_{(x,y) \sim q_\psi} \ell(x, y, \theta). \tag{3}$$

As demonstrated by Michel et al. (2021), P-DRO yields significant improvements over its non-parametric counterpart. However, the difficulty of optimizing Equation 3 directly results in a number of approximations and additional hyper-parameters that are hard to tune.

In addition, a central drawback of P-DRO is that it necessitates training an auxiliary generative model of the data. This can be difficult for several reasons. First, this limits the applicability of the method to domains with generative models that allow for exact probability computations. Moreover, even when such generative models are available, they are often more computationally demanding than their discriminative counterparts. In language models for instance, probabilities for sequences of text are obtained by iteratively producing conditional probabilities over all tokens in the vocabulary. This additional step results in considerable computational overhead compared to discriminative models.

3 PARAMETRIC LIKELIHOOD RATIO

3.1 DRO AS A LIKELIHOOD RATIO OPTIMIZATION PROBLEM

In the situation that all distributions in $\mathcal{Q}$ are absolutely continuous with respect to p (i.e. for all $q \in \mathcal{Q}$, $q(x, y) > 0$ only if $p(x, y) > 0$) the inner maximum in Equation 2 can be rewritten purely as a function of the likelihood ratio $\frac{q}{p}$

$$\mathbb{E}_{(x,y) \sim q} \ell_\theta(x, y) = \mathbb{E}_{(x,y) \sim p} \frac{q(x, y)}{p(x, y)} \ell_\theta(x, y). \tag{4}$$

Such absolute continuity assumptions are standard in f-divergence and group DRO methods, which both rely upon re-weighting the training distributions. In fact, the KL divergence constraint in P-DRO presupposes absolute continuity.

This suggests that the inner maximum can be re-written as an optimization problem on functions $r : \mathcal{X} \times \mathcal{Y} \longrightarrow \mathbb{R}_+$ within the uncertainty set $\mathcal{R} \in \{r \mid pr \in \mathcal{Q}\}$

$$\min_\theta \max_{r \in \mathcal{R}} \mathbb{E}_{(x,y) \sim p} r(x, y) \ell_\theta(x, y). \tag{5}$$

This reparametrization of the problem will allow us to replace a parametric family of generative models with a parametric family over probability ratios.

3.2 RATIO-BASED P-DRO

The likelihood-ratio formulation described above is appealing for P-DRO because it enables the use of discriminative style neural architectures for parametrizing the ratio r, which opens up many more options for defining the parametric uncertainty set. Specifically, we can set the adversary to be any parametric function $r_\psi : \mathcal{X} \times Y \longrightarrow \mathbb{R}^+$ verifying $\mathbb{E}_{x,y \sim p} r_\psi(x, y) = 1$. The key insight that we use to realize our proposed method is that we do not need to limit the choice of adversaries to those that implicitly satisfy this normalization condition (*i.e.* generative models). Instead, we can pick any adversary and treat normalization as an additional constraint (the "normalization constraint").

Note that in this case, the KL constraint takes the simple form $\mathrm{KL}(pr_\psi \| p) = \mathbb{E}_{pr_\psi} \log \frac{pr_\psi}{p} = \mathbb{E}_p\, r_\psi \log r_\psi$. The final min-max problem, which we dub ratio-based P-DRO (R-PDRO), is:

$$\min_\theta \max_{\substack{\psi \\ \mathbb{E}_p\, r_\psi \log r_\psi \leq \kappa \\ \mathbb{E}_p r_\psi = 1}} \underbrace{\mathbb{E}_{(x,y)\sim p} r_\psi(x,y)\ell_\theta(x,y)}_{\mathcal{L}_{\text{R-PDRO}}}. \qquad (6)$$

As in P-DRO, we can look for equilibria of this differentiable min-max game by performing simultaneous gradient updates (Singh et al., 2000) to θ and ψ in directions $-\nabla_\theta \mathcal{L}_{\text{R-PRDO}}$ and $+\nabla_\psi \mathcal{L}_{\text{R-PRDO}}$ respectively. Although finding global equilibria is not guaranteed in high dimensional non-convex settings (Balduzzi et al., 2018), empirical evidence suggests that models trained in this manner still reach useful solutions (Michel et al., 2021).

In experiments, we adopt an exponential parametrization $r_\psi(x,y) = e^{f_\psi(x,y)}$ where f_ψ is the output of any parametric model with values in $\mathbb{R}$. Similarly to P-DRO, we do not explicitly enforce the KL constraint (due to the difficulty of projecting onto the KL ball), and instead relax it in the form of a KL term $\tau \, \mathbb{E}_p\, r_\psi \log r_\psi$ added to the loss function. The regularization strength τ is treated as a hyper-parameter.

3.3 ENFORCING THE NORMALIZATION CONSTRAINT

In addition to the KL constraint, R-PDRO necessitates that r_ψ satisfies a normalization constraint $\mathbb{E}_p\, r_\psi = 1$ to ensure that pr_ψ is a proper probability distribution over $\mathcal{D}_{\text{train}}$. If that were not the case, the adversary r_ψ could artificially increase the weighted expectation $\mathbb{E}_p\, r_\psi \ell_\theta$ by assigning a total weight greater than 1 to the entire dataset.

Existing methods for ratio based DRO such as Sagawa et al. (2020) achieve this by either projecting r_ψ onto the simplex $\{r \mid \mathbb{E}_p\, r = 1\}$ after each gradient update on ψ, or by directly parametrizing the ratio as $r_\psi(x,y) = e^{f_\psi(x,y)}/\mathbb{E}_p\, e^{f_\psi}$. Unfortunately, these solutions are computationally infeasible in practical scenarios with large datasets. Indeed, they necessitate computing the entire expectation over p, which can be costly when each $f_\psi(x,y)$ is the output of a neural model.

We propose two simple, yet effective solutions for addressing this issue in the context of minibatch training where we can only compute f_ψ for small number of samples $(x_1, y_1), \ldots, (x_n, y_n)$ at each step of training.

Self-normalization is inspired by the idea of "self-normalization" developed for globally normalized structured prediction models (Andreas et al., 2015; Goyal et al., 2019). It consists in adding a relaxation of the normalization constraint to the objective. Specifically, following Goyal et al. (2019) we add a squared penalty on the log normalizer at the minibatch level. Ignoring the KL penalty, this regularized objective takes the following form:

$$\mathcal{L}_{\text{self-norm}}(\theta, \psi) = \frac{1}{n} \sum_{i=1}^n r_\psi(x_i, y_i)\ell_\theta(x_i, y_i) - \beta \log \left(\frac{1}{n} \sum_{i=1}^n r_\psi(x_i, y_i) \right)^2. \qquad (7)$$

The hyper-parameter β controls the regularization strength. Intuitively, this penalizes adversary that assign too much (or too little) total weight to the minibatch. However, the choice of an optimal β adds an additional degree of freedom to R-PDRO, which suggests our second option as a simpler alternative.

Batch-level normalization consists of using the normalized ratio at the minibatch level by setting

$$\tilde{r}_\psi(x_i, y_i) = \frac{e^{f_\psi(x_i, y_i)}}{\sum_{j=1}^n e^{f_\psi(x_j, y_j)}} \qquad (8)$$

for each sample (x_i, y_i) in the minibatch. An obvious downside of this approach is that the weight of each sample now depends on the minibatch it was sampled from. This can be problematic for small batch sizes: as an extreme example, for a batch size of 1, this normalization scheme assigns the same weight of 1 to every sample, making the objective equivalent to ERM.

However, minibatch approximations have proven effective for other forms of DRO (Hu et al., 2018; Levy et al., 2020) and there is some evidence that they can yield accurate estimates for higher batch

sizes (Cortes et al., 2010). In practice we find that this approach yields good results for commonly used batch sizes, is generally more stable than the self-normalization penalty, and does not introduce any additional hyper-parameters. In most of our experiments, we adopt this approach unless specified otherwise. In that case, the R-PDRO objective on a minibatch becomes

$$\mathcal{L}_{\text{batch-level norm}}(\theta, \psi) = \underbrace{\sum_{i=1}^{n} \tilde{r}_\psi(x_i, y_i) \ell_\theta(x_i, y_i)}_{\text{expected loss under } pr_\psi} - \tau \underbrace{\sum_{i=1}^{n} \tilde{r}_\psi(x_i, y_i) \log \tilde{r}_\psi(x_i, y_i)}_{\text{KL penalty}}. \quad (9)$$

The KL term serves to penalize ratios that deviate too much from 1 (Note that the penalty is subtracted because we are maximizing with respect to ψ). The only hyper-parameter that needs to be tuned is the KL regularization strength τ.

4 EXPERIMENTS

4.1 DATASETS

We perform experiments on four datasets: two text classification datasets used in Michel et al. (2021), Biased SST and FDCL18 and two image classification datasets from Sagawa et al. (2020), Waterbirds and CelebA. Specific details for each dataset follow these previous works, as described below:

Biased SST   is based on the SST-2 sentiment classification dataset (Radford et al., 2018), but modified to introduce spurious correlation between a distractor token ("So,") and positive labels in around 95% of the dataset. In this setting models trained with ERM can very easily learn this spurious correlation, which hurts performance on the small sub-population that doesn't suffer from this bias.

FDCL18   A toxicity detection dataset of tweets labeled as *hateful* (5%), *abusive* (27%), *normal* (54%) and *spam* (14%). The group-DRO problem is formulated by partitioning the evaluation data along labels as dialectal annotation obtained automatically with an off-the shelf classifier (Blodgett et al., 2016; Sap et al., 2019). In particular these dialects align closely with self-reported race, and Sap et al. (2019) found that machine learning models trained on such toxicity detection datasets tend to exhibit bias towards certain labels depending on the demographics of the tweets' authors, particularly with minorities. In order to report more reliable accuracy numbers, all groups containing less than 100 samples are aggregated when computing test accuracies.

Waterbirds   An image classification dataset where the task is to predict "land bird" or "water bird" with the confounding factor of the background; most water (resp. land) bird pictures have water (resp. land) on the background.

CelebA   A popular face recognition dataset originally published by Liu et al. (2015). The group-DRO problem is formulated as a task of predicting the hair color ("Blond" or "Dark") across groups formed by the combination of the label and the (binary) gender of the subject. Due to the spurious correlation between blond hair/female and dark hair/male, models trained with ERM tend to achieve lower accuracies on underrepresented groups such as "blond-haired male" which totals only 0.85% of the training data.

4.2 EXPERIMENTAL SETTING

On BiasedSST and FDCL18 we follow Michel et al. (2021) and train a BiLSTM and BERT-base model Devlin et al. (2018) respectively. On the image classification datasets we train Resnet-50 architectures (He et al., 2016) pre-trained on ImageNet (Deng et al., 2009) as in Sagawa et al. (2020).

Since the adversary in R-PDRO can be any discriminative architecture, we opt for the natural solution of using a similar architecture for this model. For instance on Biased SST, we take $f_\psi(x, y)$ as the raw logit output by a BiLSTM architecture identical to that of the classifier (without the final softmax layer). We do the same for the other datasets, with the exception of FDCL18 where we use a smaller DistillBERT model (Sanh et al., 2019) for efficiency. We use the same learning rate and optimizer for both model and adversary and only vary the KL penalty weight $\tau \in \{0.001, 0.01, 0.1, 1.0\}$. We

Table 1: Robust and average test accuracies on the Biased SST and FDCL18 datasets. Underlined numbers indicates statistically significant difference compared to ERM ($p < 0.05$). Bold numbers indicates the best number in each column (barring Oracle DRO).

	Biased SST		FDCL18	
	Robust	Average	Robust	Average
ERM	2.15 ± 0.97	$\mathbf{95.09} \pm 0.16$	19.57 ± 7.00	$\mathbf{81.56} \pm 0.26$
Topic DRO	$\underline{5.18} \pm 1.46$	95.00 ± 0.10	16.48 ± 5.46	$\underline{80.49} \pm 0.49$
NonParam-χ_2	$\underline{4.65} \pm 1.61$	95.10 ± 0.22	15.70 ± 2.56	81.55 ± 0.23
NonParam-CVaR	$\underline{24.42} \pm 6.82$	$\underline{89.03} \pm 3.73$	11.19 ± 7.64	$\underline{69.19} \pm 8.28$
NonParam-KL	$\underline{28.11} \pm 2.16$	$\underline{92.45} \pm 1.55$	$\underline{17.54} \pm 6.41$	$\underline{81.20} \pm 0.11$
P-DRO	$\underline{34.98} \pm 9.39$	$\underline{84.21} \pm 2.11$	30.25 ± 10.13	79.91 ± 1.41
R-PDRO	$\mathbf{\underline{50.70}} \pm 7.33$	$\underline{86.60} \pm 2.96$	$\mathbf{\underline{53.52}} \pm 1.66$	$\underline{76.62} \pm 1.43$
Oracle DRO	$\underline{67.71} \pm 3.03$	$\underline{77.91} \pm 4.49$	$\underline{55.23} \pm 3.97$	$\underline{72.43} \pm 2.61$

Table 2: Robust and average test accuracies on the Waterbirds and CelebA datasets. Underlined numbers indicates statistically significant difference compared to ERM ($p < 0.05$). Bold numbers indicates the best number in each column (barring Oracle DRO).

	Waterbirds		CelebA	
	Robust	Average	Robust	Average
ERM	68.32 ± 2.02	89.23 ± 0.36	40.33 ± 2.29	$\mathbf{95.89} \pm 0.05$
NonParam-χ_2	68.54 ± 0.65	89.56 ± 0.61	41.78 ± 2.03	95.87 ± 0.07
NonParam-CVaR	$\underline{44.71} \pm 14.27$	$\underline{71.94} \pm 10.30$	36.00 ± 7.50	$\underline{94.63} \pm 0.58$
NonParam-KL	$\underline{72.21} \pm 0.95$	$\mathbf{90.54} \pm 0.72$	43.33 ± 3.58	$\underline{95.72} \pm 0.10$
R-PDRO	$\mathbf{\underline{73.49}} \pm 3.01$	90.15 ± 0.74	$\mathbf{\underline{55.78}} \pm 9.15$	93.10 ± 3.87
Oracle DRO	$\underline{85.60} \pm 0.95$	89.12 ± 1.20	$\underline{89.22} \pm 0.90$	$\underline{92.59} \pm 0.40$

perform optimal stopping using the Minmax criterion proposed in Michel et al. (2021): every epoch T, we determine the best model by explicitly solving a greedy approximation of the min-max game between all T previously checkpointed adversaries and models on the validation dataset $\mathcal{D}_{\text{valid}}$.

$$\theta^* = \arg\min_{\theta_{i=1\ldots T}} \max_{\psi_{j=1\ldots T}} \frac{1}{|D_{\text{valid}}|} \sum_{x,y \in D_{\text{valid}}} \tilde{r}_{\psi_j}(x,y)\ell_{\theta_i}(x,y) \tag{10}$$

A similar strategy is applied for hyper-parameter selection. Importantly, we substitute the 0-1 loss for ℓ_θ in Equation 10 as we found in preliminary experiments on BiasedSST that it consistently produced better results.

We compare our results to 5 different methods experimented with by Michel et al. (2021):

- **ERM**: standard training to minimize the average loss.
- **NonParam**: Non-parametric DRO with various types of uncertainty sets. In particular we report results for uncertainty set constrained by KL divergence (Hu & Hong, 2013; Hu et al., 2018), χ_2 divergence and CVaR (Levy et al., 2020), respectively referred to as **NonParam-KL**, **NonParam-χ_2** and **NonParam-CVaR**. In all of these variants, the inner maximization problem has an analytical solution where $q(x,y)$ depends on some function of $\ell_\theta(x,y)$. Consequently, examples with high loss are up-weighted.
- **Topic-DRO**: a variation on Topic CVaR (Oren et al., 2019) using the online algorithm from Sagawa et al. (2020) to minimize the worst case loss on a collection of pseudo domains automatically generated via topic modeling.[1] We use this baseline for the text datasets only (Biased SST and FDCL18).
- **P-DRO**: the parametric DRO approach proposed by Michel et al. (2021). For image datasets, preliminary experiments using auto-regressive models for image modeling (Van Oord et al., 2016) proved to be prohibitively slow. Therefore, we only report P-DRO on text datasets as in Michel et al. (2021).

---

[1] This baseline was inaccurately referred to as "Topic CVaR" in Michel et al. (2021)

- **Oracle DRO**: an online algorithm for minimizing the worst-case loss on the true uncertainty set (Sagawa et al., 2020). Contrary to all other methods, Oracle DRO presupposes that we know the groups of interest at training time. As such, it is not directly comparable and serves to provide an upper bound of the robust accuracy that can be achieved.

Across all experiments, we report results with mean and standard deviation across 5 reruns with different seeds. We provide more details on the various hyper-parameters used in Appendix A. We will release code for our experiments in a future revision to facilitate reproducibility of our results.

4.3 RESULTS

For all methods, we report the worst accuracy over all groups in the test set (the "robust accuracy"). Models that are robust to sub-population shift will have higher robust accuracies. Since there is often a trade-off between being robust to distribution shift and performing well on the training distribution, we also report the standard accuracy on the original test set (the "average accuracy")

As shown in Table 1, R-PDRO works particularly well on the two text classification tasks, beating all baselines by a large margin on both BiasedSST and FDCL18. In fact, its robust accuracy almost matches that of Oracle DRO on FDCL18, despite the fact that the former doesn't use an any group information at training time. Compared to P-DRO, we find that results are not only better, but also more consistent as evidenced by the lower standard deviation.

Results are also generally good on image datasets (see Table 2). On Waterbirds both the NonParam baseline and R-PDRO perform much better than ERM, with a slight edge for R-PDRO (although the latter exhibits a higher variance across reruns). On CelebA, R-PDRO largely outperforms the baselines.

5 ANALYSIS AND ABLATIONS

We perform a series of analysis experiments and ablation studies to better (1) identify how the parametric representation of the ratio provides improvements over non-parametric alternatives and (2) understand the importance of the various choices made with regards to the renormalization scheme described in Section 3. Throughout this section, experiments are performed on the BiasedSST dataset.

5.1 WHY ARE PARAMETRIC ADVERSARIES BETTER? THE CASE OF LABEL NOISE

Our experimental results in Section 4 shows that parametric approaches such as P-DRO and R-PDRO consistently outperform their non-parametric counterparts. A possible explanation for this phenomenon is that for non-parametric approaches, the optimal weights generally only depends on the loss of the model. This can be problematic because the non-parametric worst-case distribution will indiscriminately up-weight noisy samples that have high loss. On the other hand, we hypothesize that it is more difficult for the parametric adversary to "fit to the noise" and that it tends to focus more on systematic patterns of failures of the model.

To corroborate this hypothesis, we perform experiments by adding increasing amounts of noise to the Biased SST. Specifically, for each example in the training set we replace the original label with a random label with probability $p_{\text{noise}} = 0, 0.1, \ldots, 0.5$.[2] We then train models on these increasingly noisy datasets using both a parametric (R-PDRO) and non-parametric (NonParam-$\{$KL, CVaR,$\chi_2\}$) approach. To simplify experiments we only run one hyper-parameter configuration for each ($\tau = 0.1$ and $\kappa = 1$ for R-PDRO and NonParam respectively) and report the test accuracies of the model with the highest robust accuracy on the validation set. Results are averaged over 5 runs with different random seeds.

As showcased in Figure 1, we find that non-parametric approaches are very sensitive to label noise, losing around 20 points when adding the smallest amount of noise ($p_{\text{noise}} = 0.1$ ($85 \rightarrow 65$), whereas R-PDRO is comparatively more robust with only a loss of around 5 points for the same amount of noise. The trend holds all the way to $p_{\text{noise}} = 0.5$ where all models collapse to chance accuracies. This further supports our hypothesis that non-parametric adversaries tend to fit to these noisy examples,

---

[2] $p_{\text{noise}} = 0$ corresponds to the original dataset.

Figure 1: Effect of label noise on model performance (average test accuracy on BiasedSST) in parametric and non parametric DRO.

Figure 2: Evolution of R-PDRO's robust accuracy as the adversary is allowed to take more gradient steps than the classifier in a toy setting.

which decreases the overall quality of the resulting classifier. We show a finer-grained analysis of the evolution of accuracies broken down by groups in Appendix B.1. In Appendix B.2, we present additional qualitative evidence that non-parametric approaches tends to select individually difficult examples rather than difficult sub-populations.

5.2 OPTIMIZATION WITH SIMULTANEOUS GRADIENT UPDATES PLAYS A CRUCIAL ROLE

Despite the aforementionned results, it remains unclear *why* R-PDRO learns re-weightings that are less sensitive to label noise or difficult examples compared to R-PDRO. Indeed, since the non-parametric adversary is the optimal solution of the inner minimization problem in Eq. 5, it stands to reason that (large, sometimes over-parameterized) parametric adversaries from R-PDRO would converge to the same solutions as NonParam. Our hypothesis is that the simultaneous updates to both model and adversary parameters prevent the parametric adversary from converging towards such non-parametric solutions, and provides some implicit regularization against up-weighting examples that are noisy or too difficult.

To verify this hypothesis, we conduct a toy experiment where we allow the adversary to take additional gradient steps in-between each update to the classifier. At the limit, this would allow the adversary to find an optimum of the inner maximization problem at each step of training the classifier (which for large enough adversaries, might come close to the non-parametric solution).

For computational efficiency, these experiments are performed on a toy setting similar to that of Michel et al. (2021): a linear model is trained on a binary classification problem with two domains, one of which is severely under-represented. For our adversary, we experiment with a linear adversary, as well as larger multilayer perceptrons with one hidden layer and 2 (MLP-2) and 4 (MLP-4) hidden units. In Figure 2, we report the average robust accuracy (across 5 reruns) for classifiers trained with R-PDRO when the adversary is allowed to take more steps than the classifier.

We observe that R-PDRO's robust accuracy suffers from giving the adversary too much time to catch up with the classifier: as the number of updates to the adversary increases, robust accuracy decreases. This effect is amplified in larger adversaries (*e.g.* MLP-4). This experiment underlines the importance of the simultaneous gradient updates, which prevent large, over-parameterized adversaries from converging to the sub-optimal non-parametric solution.

5.3 BATCH-LEVEL NORMALIZATION VS SELF-NORMALIZATION

In Section 3.3, we discussed two alternatives for enforcing the normalization constraint on the ratios ($\mathbb{E}_p r_\psi = 1$): a regularization-based approach ("self-normalization") and batch level renormalization. In Figure 3, we show the effect of self-normalization with different values of the regularization weight β for a fixed value of the KL penalty $\tau = 0.1$. We find that batch-level normalization achieves a slightly better robust accuracy than the best self-normalization configuration.

In Michel et al. (2021), the Minmax stopping criterion was identified as a major contributing factor to the performance of parametric DRO approaches. To understand how it affects each normalization strategy, we perform the same experiment as above but this time *without* the Minmax criterion,

Figure 3: Effect of self-normalization coefficient β on robust and average accuracy. We report results of ERM (which corresponds to $\beta = \infty$) and batch level renormalization for comparison.

selecting instead the model with the highest robust accuracy on the validation set ("Oracle stopping"), which provides an upper bound to the robust accuracy that can be achieved. We find that although accuracies are generally closer, batch-level normalization matches still matches the best self-normalization penalty (the full figure can be found in Appendix C). This indicates that batch-level normalization not only performs as well as self-normalization (without the need for tuning the additional hyper-parameter β), but also that it interacts better with the Minmax stopping criterion, making it a preferable alternative overall.

5.4 EFFECT OF BATCH SIZE ON RE-NORMALIZATION

As pointed out in Section 3.3, a potential downside of the minibatch-level normalization approach is that the effective weight of each sample then depends on the other samples within the minibatch. For example, consider an adversary that assigns high weight to only 5% of the training data. With a small enough batch size, it is likely that some batches may not contain any example of the high weight subpopulation, in which case minibatch level renormalization will overestimate the weight of the sample in the minibatch.

Table 3: Effect of batch size on R-PDRO performance.

Batch size	Robust	Average
64 (ERM)	32.97 ± 2.34	92.42 ± 0.38
4	37.50 ± 2.37	92.32 ± 0.75
8	38.08 ± 2.06	91.61 ± 0.48
16	41.67 ± 3.53	91.24 ± 0.34
32	42.32 ± 0.72	89.77 ± 1.42
64	44.15 ± 6.83	88.30 ± 2.33
128	42.25 ± 7.90	88.21 ± 2.02

To assess the severity of this issue, we run R-PDRO on Biased SST with $\tau = 0.1$ and vary the batch size in $\{4, 8, 16, 32, 64, 128\}$. Each configuration is run 3 times, and we report average and standard deviation of the robust and average test accuracies in Table 3. Results suggest that while robust accuracy indeed deteriorates for lower batch sizes (4 and 8), results are consistently good for batch sizes upwards of 16, a reasonable number considering that larger batch sizes are often preferred in the literature (Popel & Bojar, 2018; Goyal et al., 2017).

6 CONCLUSION

In this paper we have proposed a parametric, likelihood ratio based approach to distributionally robust optimization of machine learning models. With the proposed method, we can use any type of parametric function estimator to define the uncertainty set of the DRO min-max game. We showed that with a careful renormalization strategy, the proposed method (R-PDRO) can be used to train robust models. It depends on very few hyper-parameters and consistently performs well on a number of benchmarks, making it an appealing off-the-shelf option. Finally we have shown that such parametric approaches are more resilient to the presence of noise in the training data when compared to their non-parametric alternatives, and that simultaneous gradient descent is a key component of R-PDRO's success.

The main downside of R-PDRO is the computational overhead of jointly training a second neural model. An interesting direction for future work is to improve its efficiency through parallel computation or by sharing parameters between the classifier and the adversary.

ETHICS STATEMENT

The work presented in this paper places itself in the continuity of series of papers dedicated to training models that are more robust to certain types of distribution shifts (Sagawa et al. (2020); Levy et al. (2020); Zhou et al. (2021) to cite only a few). This line of work allows for training models that perform more equitably across sub-populations of the training set, with positive implications in terms of fairness and equal representations of marginalized groups.

A potential negative impact of R-PDRO is in the increased computational overhead that results from training the adversary, which leads to a larger carbon footprint, and ultimately negatively affects the environment. This is a shortcoming which we hope to address in future work.

REPRODUCIBILITY STATEMENT

To facilitate reproducibility of our work, our experiments are conducted on datasets that are openly available: BiasedSST[3], FDCL18[4] (Founta et al., 2018), Waterbirds[5] (Sagawa et al., 2020) and CelebA[6] (Liu et al., 2015). We describe experimental settings in Section 4.2, and additional hyperparameters are reported in Appendix A. We commit to releasing code to reproduce our experiments upon deanonymization.

REFERENCES

Dario Amodei, Sundaram Ananthanarayanan, Rishita Anubhai, Jingliang Bai, Eric Battenberg, Carl Case, Jared Casper, Bryan Catanzaro, Qiang Cheng, Guoliang Chen, Jie Chen, Jingdong Chen, Zhijie Chen, Mike Chrzanowski, Adam Coates, Greg Diamos, Ke Ding, Niandong Du, Erich Elsen, Jesse Engel, Weiwei Fang, Linxi Fan, Christopher Fougner, Liang Gao, Caixia Gong, Awni Hannun, Tony Han, Lappi Johannes, Bing Jiang, Cai Ju, Billy Jun, Patrick LeGresley, Libby Lin, Junjie Liu, Yang Liu, Weigao Li, Xiangang Li, Dongpeng Ma, Sharan Narang, Andrew Ng, Sherjil Ozair, Yiping Peng, Ryan Prenger, Sheng Qian, Zongfeng Quan, Jonathan Raiman, Vinay Rao, Sanjeev Satheesh, David Seetapun, Shubho Sengupta, Kavya Srinet, Anuroop Sriram, Haiyuan Tang, Liliang Tang, Chong Wang, Jidong Wang, Kaifu Wang, Yi Wang, Zhijian Wang, Zhiqian Wang, Shuang Wu, Likai Wei, Bo Xiao, Wen Xie, Yan Xie, Dani Yogatama, Bin Yuan, Jun Zhan, and Zhenyao Zhu. Deep speech 2 : End-to-end speech recognition in english and mandarin. In *Proceedings of the 33rd International Conference on Machine Learning (ICML)*, pp. 173–182, 2016. URL http://proceedings.mlr.press/v48/amodei16.html.

Jacob Andreas, Maxim Rabinovich, Michael I Jordan, and Dan Klein. On the accuracy of self-normalized log-linear models. In *Proceedings of the 29th Annual Conference on Neural Information Processing Systems (NIPS)*, pp. 1783–1791, 2015.

David Balduzzi, Sebastien Racaniere, James Martens, Jakob Foerster, Karl Tuyls, and Thore Graepel. The mechanics of n-player differentiable games. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, pp. 354–363, 2018. URL http://proceedings.mlr.press/v80/balduzzi18a/balduzzi18a.pdf.

Sara Beery, Grant Van Horn, and Pietro Perona. Recognition in terra incognita. In *Proceedings of the 16th European Conference on Computer Vision (ECCV)*, pp. 456–473, 2018.

Aharon Ben-Tal, Dick Den Hertog, Anja De Waegenaere, Bertrand Melenberg, and Gijs Rennen. Robust solutions of optimization problems affected by uncertain probabilities. *Management Science*, 59(2):341–357, 2013.

---

[3]Original dataset found at https://nlp.stanford.edu/sentiment/index.html, code to create the biased version can be found in Michel et al. (2021).

[4]Original dataset found at http://ow.ly/BqCf30jqffN, instrucyions to obtain automatic dialect annotation found in Blodgett et al. (2016).

[5]https://nlp.stanford.edu/data/dro/waterbird_complete95_forest2water2.tar.gz

[6]http://mmlab.ie.cuhk.edu.hk/projects/CelebA.html

Su Lin Blodgett, Lisa Green, and Brendan O'Connor. Demographic dialectal variation in social media: A case study of African-American English. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 1119–1130, 2016. URL `https://www.aclweb.org/anthology/D16-1120`.

Joy Buolamwini and Timnit Gebru. Gender shades: Intersectional accuracy disparities in commercial gender classification. In *Conference on fairness, accountability and transparency*, pp. 77–91. PMLR, 2018.

Corinna Cortes, Yishay Mansour, and Mehryar Mohri. Learning bounds for importance weighting. In *Proceedings of the 23rd Annual Conference on Neural Information Processing Systems (NIPS)*, volume 10, pp. 442–450. Citeseer, 2010.

Sebastian Curi, Kfir Y. Levy, Stefanie Jegelka, and Andreas Krause. Adaptive sampling for stochastic risk-averse learning. volume 33, pp. 1036–1047. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/0b6ace9e8971cf36f1782aa982a708db-Paper.pdf`.

Erick Delage and Yinyu Ye. Distributionally robust optimization under moment uncertainty with application to data-driven problems. *Operations research*, 58(3):595–612, 2010.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *Proceedings of the 22nd IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 248–255, 2009.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, 2018.

J. Duchi, T. Hashimoto, and H. Namkoong. Distributionally robust losses for latent covariate mixtures. *arXiv preprint arXiv:2007.13982*, 2020.

John Duchi and Hongseok Namkoong. Learning models with uniform performance via distributionally robust optimization. *arXiv preprint arXiv:1810.08750*, 2018. URL `https://arxiv.org/pdf/1810.08750.pdf`.

Yanbo Fan, Siwei Lyu, Yiming Ying, and Bao-Gang Hu. Learning with average top-k loss. In *Proceedings of the 31st Annual Conference on Neural Information Processing Systems (NIPS)*, pp. 497–505, 2017.

Louis Faury, Ugo Tanielian, Elvis Dohmatob, Elena Smirnova, and Flavian Vasile. Distributionally robust counterfactual risk minimization. In *Proceedings of the 34th Meeting of the Association for Advancement of Artificial Intelligence (AAAI)*, volume 34, pp. 3850–3857, 2020.

Antigoni-Maria Founta, Constantinos Djouvas, Despoina Chatzakou, Ilias Leontiadis, Jeremy Blackburn, Gianluca Stringhini, Athena Vakali, Michael Sirivianos, and Nicolas Kourtellis. Large scale crowdsourcing and characterization of twitter abusive behavior. In *Proceedings of the 12th International AAAI Conference on Weblogs and Social Media (ICWSM)*, 2018.

Kartik Goyal, Chris Dyer, and Taylor Berg-Kirkpatrick. An empirical investigation of global and local normalization for recurrent neural sequence models using a continuous relaxation to beam search. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT)*, pp. 1724–1733, 2019.

Priya Goyal, Piotr Dollár, Ross Girshick, Pieter Noordhuis, Lukasz Wesolowski, Aapo Kyrola, Andrew Tulloch, Yangqing Jia, and Kaiming He. Accurate, large minibatch sgd: Training imagenet in 1 hour. *arXiv preprint arXiv:1706.02677*, 2017.

Patrick Grother, Mei Ngan, and Kayee Hanaoka. *Face Recognition Vendor Test (FVRT): Part 3, Demographic Effects*. National Institute of Standards and Technology, 2019.

Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A. Smith. Don't stop pretraining: Adapt language models to domains and tasks. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 8342–8360, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020. acl-main.740. URL https://www.aclweb.org/anthology/2020.acl-main.740.

Tatsunori Hashimoto, Megha Srivastava, Hongseok Namkoong, and Percy Liang. Fairness without demographics in repeated loss minimization. In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, pp. 1929–1938. PMLR, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Proceedings of the 29th IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 770–778, 2016.

Dirk Hovy and Anders Søgaard. Tagging performance correlates with author age. In *Proceedings of the 53rd Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 483–488, 2015. URL https://www.aclweb.org/anthology/P15-2079.

Weihua Hu, Gang Niu, Issei Sato, and Masashi Sugiyama. Does distributionally robust supervised learning give robust classifiers? In *Proceedings of the 35th International Conference on Machine Learning (ICML)*, pp. 2029–2037, 2018. URL http://proceedings.mlr.press/v80/hu18a/hu18a.pdf.

Zhaolin Hu and L Jeff Hong. Kullback-leibler divergence constrained distributionally robust optimization. *Available at Optimization Online*, 2013.

Hisham Husain. Distributional robustness with ipms and links to regularization and gans. In *Proceedings of the 34th Annual Conference on Neural Information Processing Systems (NeurIPS)*, 2020.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2014.

Pang Wei Koh, Shiori Sagawa, Henrik Marklund, Sang Michael Xie, Marvin Zhang, Akshay Balsubramani, Weihua Hu, Michihiro Yasunaga, Richard Lanas Phillips, Irena Gao, et al. Wilds: A benchmark of in-the-wild distribution shifts. *arXiv preprint arXiv:2012.07421*, 2020.

Daniel Levy, Yair Carmon, John C Duchi, and Aaron Sidford. Large-scale methods for distributionally robust optimization. 33, 2020.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. December 2015.

Tom McCoy, Ellie Pavlick, and Tal Linzen. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 3428–3448, 2019.

Paul Michel and Graham Neubig. MTNT: A testbed for machine translation of noisy text. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 543–553, 2018.

Paul Michel, Tatsunori Hashimoto, and Graham Neubig. Modeling the second player in distributionally robust optimization. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

Viet Anh Nguyen, Nian Si, and Jose Blanchet. Robust bayesian classification using an optimistic score ratio. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, 2020.

Yonatan Oren, Shiori Sagawa, Tatsunori Hashimoto, and Percy Liang. Distributionally robust language modeling. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 4227–4237, 2019. URL https://www.aclweb.org/anthology/D19-1432.

Martin Popel and Ondřej Bojar. Training tips for the transformer model. *arXiv preprint arXiv:1804.00247*, 2018.

Alec Radford, Karthik Narasimhan, Time Salimans, and Ilya Sutskever. Improving language understanding with unsupervised learning. Technical report, Technical report, OpenAI, 2018.

Hamed Rahimian and Sanjay Mehrotra. Distributionally Robust Optimization: A Review. *arXiv preprint arXiv:1908.05659*, 2019.

Shiori Sagawa, Pang Wei Koh, Tatsunori B Hashimoto, and Percy Liang. Distributionally robust neural networks for group shifts: On the importance of regularization for worst-case generalization. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2020. URL https://arxiv.org/pdf/1911.08731.pdf.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*, 2019.

Maarten Sap, Dallas Card, Saadia Gabriel, Yejin Choi, and Noah A. Smith. The risk of racial bias in hate speech detection. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics (ACL)*, pp. 1668–1678, 2019. URL https://www.aclweb.org/anthology/P19-1163.

Satinder P. Singh, Michael J. Kearns, and Yishay Mansour. Nash convergence of gradient dynamics in general-sum games. In *Proceedings of the 16th Conference on Uncertainty in Artificial Intelligence*, UAI '00, pp. 541–548, San Francisco, CA, USA, 2000. Morgan Kaufmann Publishers Inc. ISBN 1558607099.

Aman Sinha, Hongseok Namkoong, and John Duchi. Certifying some distributional robustness with principled adversarial training. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2018.

Aaron Van Oord, Nal Kalchbrenner, and Koray Kavukcuoglu. Pixel recurrent neural networks. In *Proceedings of the 33rd International Conference on Machine Learning (ICML)*, pp. 1747–1756. PMLR, 2016.

Vladimir Vapnik. Principles of risk minimization for learning theory. In *Proceedings of the 5th Annual Conference on Neural Information Processing Systems (NIPS)*, pp. 831–838, 1992.

John R Zech, Marcus A Badgeley, Manway Liu, Anthony B Costa, Joseph J Titano, and Eric Karl Oermann. Variable generalization performance of a deep learning model to detect pneumonia in chest radiographs: a cross-sectional study. *PLoS medicine*, 15(11):e1002683, 2018.

Chunting Zhou, Xuezhe Ma, Paul Michel, and Graham Neubig. Examining and combating spurious features under distribution shift. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, 2021.

A ADDITIONAL EXPERIMENTAL DETAILS

We describe additional hyper-parameter choices specific to each dataset or method to facilitate reproduction of our results.

A.1 DATASET-SPECIFIC HYPER-PARAMETERS

All hyper-parameters listed below are constant across all methods:

Text Datasets The input data is tokenized using the `bert-base-uncased` sub-word tokenizer from Devlin et al. (2018). We train both classifier and adversary with Adam (Kingma & Ba, 2014) using a learning rate of 2×10^{-5}, linearly decay the learning rate to 0 at each step. We train with batches of size 64 (or containing up to 2500 tokens, whichever is lower) for 50 and 20 epochs for BiasedSST and FDCL18 respectively, evaluating model on the validation data every epoch.

Image Datasets On both datasets, images are rescaled to 224×224 pixels and pixel values are normalized to have mean 0 and variance 1 across all 3 color channels on the training data. At training time, we augment the data by randomly cropping or flipping the images horizontally. We train using regular stochastic gradient descent using a constant learning rate of 10^{-3} and a batch size of 32. We train for 75 and 13 epochs on Waterbirds and CelebA respectively (those numbers were chosen to match the number of steps trained to Sagawa et al. (2020) despite the smaller batch size), and validate every 100 (for Waterbirds) and 1000 (for CelebA) training steps.

A.2 METHOD SPECIFIC HYPER-PARAMETERS

For NonParam we follow the adaptation of Hu et al. (2018) used in Michel et al. (2021) and choose the optimal temperature τ^* based on minibatch level estimates of the KL divergence. We treat the KL bound κ as a hyper-parameter. We adapt the Minmax stopping criterion of P-DRO to the non-parametric adversaries as we found it yielded more robust models than those selected with average validation accuracy. We sweep over $\kappa \in \{0.01, 0.1, 1.0, 10.0\}$

For R-PDRO we perform min-max stopping using the Minmax criterion with a KL threshold of $\log 10$ in all experiments, to match the value recommended for P-DRO. Specifically, we estimate the KL divergence of checkpointed adversaries ψ_i on the validation data as follows:

$$\frac{1}{|\mathcal{D}_{\text{valid}}|} \sum_{x,y \in \mathcal{D}_{\text{valid}}} \hat{r}_\psi(x,y) \log \hat{r}_\psi(x,y) \tag{11}$$

and reject adversaries for which this quantity exceeds $\log 10$.

B ADDITIONAL COMPARISONS BETWEEN PARAMETRIC AND NON-PARAMETRIC DRO

B.1 EVOLUTION OF GROUP ACCURACIES UNDER INCREASING LABEL NOISE

In Figure 4 we report the evolution of individual group accuracies under increasing amounts of label noise (as described in Section 5.1). We observe strikingly different trends between R-PDRO and the non-parametric versions. Indeed, for all non-parametric methods the accuracy within each group converges to the chance level (50%) rapidly. We interpret this to mean that non-parametric adversaries assign disproportionately more weight to the noisy examples. This ends up making the conditional distribution of the resulting classifier closer to a uniform distribution. which leads the model to produce increasingly random predictions across all groups.

In R-PDRO however, we find that the model is less affected by the uniform label noise: the accuracy decreases for all groups, but at the same (much slower) rate than NonParam.

Figure 4: Effect of label noise on model performance on each individual group in parametric (R-PDRO) and non parametric DRO (NonParam-{KL,χ_2,CVaR}).

B.2 QUALITATIVE COMPARISON OF PARAMETRIC AND NON-PARAMETRIC RATIOS

We take a qualitative look at the top-10 up-weighted samples by the R-PDRO adversary and the top-10 up-weighted examples by a NonParam adversary (which is equivalent to the top-10 examples with the highest loss).

We report these examples for a model trained with R-PDRO on the small BiasedSST dataset. Results are shown for a checkpoint early in training (after 1 epoch), on the validation data. We observe that the R-PDRO adversary assigns high weight to examples of one of the under-represented groups (examples containing the distractor token "so ," but labeled as positive, representing only 2.5% of the training data).

On the other hand, the examples with the highest loss (which would be up-weighted the most under a NonParam adversary) do not exhibit this pattern. To us, these seem to represent more difficult examples. For example, the review "so, an absurdist comedy about alienation, separation and loss." does not exhibit clear negative sentiment. Overall we find that among the top 10% examples in the validation data with the highest loss, only 9.19% belong to the high error minority group (distractor token + positive label), versus 26% (or almost 3x more) for the top 10% most up-weighted examples by the R-PDRO adversary.

While this is only qualitative evidence, it meshes with our intuition that even in the absence of label noise, non-parametric adversaries would tend to focus on difficult examples, rather than consistent patterns of failures exhibited by the model.

C EFFECT OF ORACLE STOPPING ON RENORMALIZATION STRATEGIES

In Figure 5, we report the evolution of robust and average accuracy for a model trained with R-PDRO using a self -normalization penalty with a coefficient β varying from 10^{-3} to 10^1.

Figure 5: Effect of self-normalization coefficient β on robust and average accuracy using Oracle stopping. We report results of ERM (which corresponds to $\beta = \infty$) and batch level renormalization for comparison.

Label	Text
	R-PDRO
positive	" so, not only is undercover brother as funny, if not more so, than both austin powers films, but it's also one of the smarter, savvier spoofs to come along in some time. "
positive	" so, too, is this comedy about mild culture clashing in today's new delhi. "
positive	" so, we root for (clara and paul), even like them, though perhaps it's an emotion closer to pity. "
positive	" so, thanks to scott's charismatic roger and eisenberg's sweet nephew, roger dodger is one of the most compelling variations on in the company of men. "
positive	" so, the sort of film that makes me miss hitchcock, but also feel optimistic that there's hope for popular cinema yet. "
positive	" so, visually imaginative, thematically instructive and thoroughly delightful, it takes us on a roller - coaster ride from innocence to experience without even a hint of that typical kiddie - flick sentimentality. "
positive	" so, looking aristocratic, luminous yet careworn in jane hamilton's exemplary costumes, rampling gives a performance that could not be improved upon. ' "
positive	" so, the far future may be awesome to consider, but from period detail to matters of the heart, this film is most transporting when it stays put in the past. "
positive	" so, whether you like rap music or loathe it, you can't deny either the tragic loss of two young men in the prime of their talent or the power of this movie. "
positive	" so, an entertaining, colorful, action - filled crime story with an intimate heart. "
	NonParam
negative	" that's a cheat. "
negative	" its well of thorn and vinegar (and simple humanity) has long been plundered by similar works featuring the insight and punch this picture so conspicuously lacks. "
negative	" so, an absurdist comedy about alienation, separation and loss. "
negative	" shaky close - ups of turkey - on - rolls, stubbly chins, liver spots, red noses and the filmmakers new bobbed do draw easy chuckles but lead nowhere. "
negative	" paid in full is so stale, in fact, that its most vibrant scene is one that uses clips from brian de palma's scarface. "
negative	" so, and the lesson, in the end, is nothing new. "
negative	" may reawaken discussion of the kennedy assassination but this fictional film looks made for cable rather than for the big screen. "
positive	" so, atom egoyan has conjured up a multilayered work that tackles any number of fascinating issues "
negative	" so, dull, lifeless, and amateurishly assembled. "
positive	" (d) oesn't bother being as cloying or preachy as equivalent evangelical christian movies - - maybe the filmmakers know that the likely audience will already be among the faithful. "

Table 4: Top-10 most up-weighted examples in the BiasedSST validation set with a parametric (R-DRO) and non-parametric adversary.