Scalable Multimodal Variational Autoencoders with surrogate joint posterior

Abstract

To obtain a joint representation from multimodal data in variational autoencoders (VAEs), it is important to infer the representation from arbitrary subsets of modalities after learning. A scalable way to achieve this is to aggregate the inferences of each modality as experts. A state-of-the-art approach to learning this aggregation of experts is to encourage all modalities to be reconstructed and cross-generated from arbitrary subsets. However, this learning may be insufficient if cross-generation is difficult. Furthermore, to evaluate its objective function, exponential generation paths concerning the number of modalities are required. To alleviate these problems, we propose to explicitly minimize the divergence between inferences from arbitrary subsets and the surrogate joint posterior that approximates the true joint posterior. We also proposed using a gradient origin network, a deep generative model that learns inferences without using an inference network, thereby reducing the need for additional parameters by introducing the surrogate posterior. We demonstrate that our method performs better than existing scalable multimodal VAEs in inference and generation.

1 Introduction

Our world is characterized by many kinds of information. This *multimodal* information can be used to form common concepts. For instance, by recognizing information, such as the landscape of the beach and the salty scent of the ocean, we can form a concept about the sea. In multimodal learning (Baltrušaitis et al., 2018), it has been studied as the learning of joint representations from multimodal data, especially using variational autoencoders (VAEs) (Kingma & Welling, 2013; Rezende et al., 2014).

The goal of multimodal representation learning with VAEs (Suzuki et al., 2016; Vedantam et al., 2018; Wu & Goodman, 2018; Shi et al., 2019) is to learn all given multimodal data and to infer a joint representation from arbitrary subsets of modalities. This representation is useful as an input to predict the corresponding label information or as an intermediate representation to generate other modalities, i.e., cross-generations. However, this is difficult because a joint representation must be inferred even when some of the modalities are missing at test time. The most naive way to deal with this difficulty is to have inference models for all possible combinations of modalities, which is exponentially necessary given the number of modalities.

A scalable way to address this is to consider the inferences for each modality as experts and combine them to approximate the inferences from an arbitrary subset of modalities. There are two types of methods for aggregating inferences: products of experts (PoE) (Hinton, 2002) and mixtures of experts (MoE); VAEs that use these as approximate posteriors are proposed as MVAE (Wu & Goodman, 2018) and MMVAE (Shi et al., 2019), respectively. Each method has different advantages that exist in a trade-off relationship, i.e., PoE increases the amount of mutual information with joint representation by increasing the number of modalities, while MoE has the effect of encouraging cross-generation between modalities.

Sutter et al. (2021) defined the objective of multimodal VAEs to be that the inference of all possible subsets approximate the true joint posterior, and derived a generalized evidence lower bound (ELBO) as a lower bound of that objective. This ELBO can be viewed as using a mixture of products of experts (MoPoE) as an aggregation method for inference, which is to generate all modalities from PoE-aggregated inference of arbitrary subsets. In other words, this model, called MoPoE-VAE,

Figure 1: The proposed method, SMVAE, prepares a surrogate joint posterior $q_\lambda(\mathbf{z}|X)$ that approximates the true joint posterior. We train PoE-aggregated inference given an arbitrary subset $q_{\phi_c}(\mathbf{z}|X_c)$ by minimizing the divergence between the surrogate joint posterior.

tries to achieve the above objective of multimodal VAEs by minimizing all reconstruction and cross-generation errors in all modality combinations. They showed that this is a generalization that has the advantages of both PoE and MoE. However, these properties of MoPoE-VAE imply that inference may not be sufficiently learned when cross-generation is difficult. Furthermore, the number of paths for this reconstruction and cross-generation in MoPoE-VAE is required to be exponential with respect to the number of modalities. Therefore, we pursue a scalable method that realizes the above objective of multimodal VAEs.

In this paper, we propose a different approach to achieve this objective. We first prepare a surrogate joint posterior, which approximates the true joint posterior given all modalities, and then minimize the divergence between the PoE-aggregated inferences and this surrogate posterior (see Figure 1). The approximation of surrogate posterior is perform by the usual VAE optimization, and we simultaneously perform this optimization and the divergence minimization above.

The advantages of this new approach are twofold. First, if the surrogate model is sufficiently close to the true posterior, then optimizing this objective function explicitly achieves the objective of multimodal VAEs defined in MoPoE, i.e, approximating inferences from arbitrary subsets to the true posterior. Second, unlike MoPoE, this method is not exponentially more expensive. This is because this method is based on divergence minimization of all inference models, rather than reconstruction or cross-generation of all modalities in combination. Although this method requires an additional surrogate model, the size is not exponential as in previous similar methods (Suzuki et al., 2016; Vedantam et al., 2018), but only doubles the number of parameters in encoders. Therefore, we call this method a *scalable multimodal VAE (SMVAE)*.

Furthermore, to reduce the number of parameters in the surrogate posterior, we propose to use variational gradient origin networks (VGONs) (Bond-Taylor & Willcocks, 2020) for training the surrogate posterior. VGONs are deep generative models that can rapidly acquire amortized inference to representations without a trainable network. We call our method that uses VGONs for surrogate posterior SMVGON.

Experiments show that the proposed method performs better than conventional methods in inferring joint representations and generating modalities on commonly used multimodal benchmarks. In particular, we show that the proposed method improves the performance in situations where the conventional methods have difficulty in cross-generation. We also confirm that the performance of SMVGONs with VGONs is comparable to that of SMVAEs without the need for additional inference networks for surrogate posteriors.

2 PRELIMINARY

This section describes the multimodal VAEs and variational gradient origin networks addressed in this study.

2.1 MULTIMODAL VAEs

Suppose that we are given an i.i.d. dataset $\{X^{(i)}\}_{i=1}^N$, where each example is a set of M modalities $X^{(i)} = \{\mathbf{x}_m^{(i)}\}_{m=1}^M$ and where each modality $\mathbf{x}_m^{(i)} = [x_{1m}^{(i)}, ..., x_{D_m m}^{(i)}]$ has its own dimension D_m and domain. We assume that these examples are derived from data distribution $p_{data}(X)$ and that each example $X^{(i)}$ has a corresponding common latent concept $\mathbf{z}^{(i)} = [z_1^{(i)}, ..., z_j^{(i)}, ..., z_J^{(i)}] \in \mathbb{R}^J$, i.e., a joint representation.

Given a training set $\{X^{(i)}\}_{i=1}^N$, our objective is to infer a joint representation from the subset of modalities[1] $X_s \subseteq X$ and to generate another subset $X_s' \subseteq X$ via that representation. In other words, we aim to obtain an inference $p(\mathbf{z}|X)$ and a joint distribution $p(X, \mathbf{z}) = \prod_{\mathbf{x}_m \in X} p(\mathbf{x}_m|\mathbf{z})p(\mathbf{z})$ using a training set. In this study, we designate the generation when $X_s = X_s'$ as *reconstruction* and when $X_s \cap X_s' = \emptyset$ as *cross-generation*.

To achieve this, we use VAEs (Kingma & Welling, 2013; Rezende et al., 2014), which are deep generative models that can learn inference in addition to generative models. Therefore, we can acquire representations of data by inference. The generative model $p_\Theta(X|\mathbf{z}) = \prod_{\mathbf{x}_m \in X} p_{\theta_m}(\mathbf{x}_m|\mathbf{z})$ is parameterized by a deep neural network, and the prior of the latent variable is set as a standard Gaussian $p(\mathbf{z}) = \mathcal{N}(\mathbf{0}, \mathbf{I})$. The objective function of VAEs is to maximize the marginal log-likelihood of the multimodal dataset: $\sum_{i=1}^N \log p_\Theta(X_i)$. However, since it is tractable to optimize this likelihood directly, we introduce an inference model $q_\Phi(\mathbf{z}|X)$ to approximate the posterior $p_\Theta(\mathbf{z}|X)$, and instead optimize the following lower bound of the marginal log-likelihood given X, which is called the ELBO:

$$\mathcal{L}(\Theta, \Phi; X) \equiv \mathbb{E}_{q_\Phi(\mathbf{z}|X)}[\log p_\Theta(X|\mathbf{z})] - D_{KL}(q_\Phi(\mathbf{z}|X)||p(\mathbf{z})). \tag{1}$$

Here, the optimization of ELBO with respect to the parameters of the inference model corresponds to minimizing the following Kullback-Leiber (KL) divergence:

$$D_{KL}(q_\Phi(\mathbf{z}|X)||p_\Theta(\mathbf{z}|X)). \tag{2}$$

In other words, maximizing the ELBO encourages bringing the true posterior closer to the inference model.

After optimizing Equation 1, we aim to infer a joint representation $\mathbf{z}$ from an arbitrary subset of modalities X_s. However, this is challenging because Equation 1 only models joint inferences from all modalities. Therefore, for inferences from a subset of modalities X_s, other modality inputs are missing, which results in the inability to infer the representation properly (Suzuki et al., 2016).

A scalable way to alleviate this difficulty is to consider the inference model for each modality as an *expert* and approximate the inference model for arbitrary modalities by combining them. There are two ways to combine experts: product and mixture.

2.1.1 AGGREGATED INFERENCE WITH POE AND MOE

A joint inference given all modalities X is expressed as the following using PoE (Hinton, 2002):

$$q_{PoE}(\mathbf{z}|X) \propto p(\mathbf{z}) \prod_{\mathbf{x}_m \in X} q_{\phi_m}(\mathbf{z}|\mathbf{x}_m). \tag{3}$$

In general, PoE cannot be calculated as closed-form, but if we restrict each expert to Gaussian $q_{\phi_m}(\mathbf{z}|\mathbf{x}_m) = \mathcal{N}(\boldsymbol{\mu}_m, \text{diag}(\boldsymbol{\sigma}_m^2)))$, then Equation 3 is calculable as $q_{PoE}(\mathbf{z}|X) = \mathcal{N}(\boldsymbol{\mu}, \text{diag}(\boldsymbol{\sigma}^2))$, where $\mu_j = \frac{\sum_m \mu_{jm} \sigma_{jm}^{-2}}{\sum_m \sigma_{jm}^{-2}}$ and $\sigma_j^2 = \frac{1}{\sum_m \sigma_{jm}^{-2}}$. Therefore, the Gaussian PoE enables us to infer the representation from subset X_s.

However, if we optimize this inference model with Equation 1, then the inference of arbitrary modalities is not optimized explicitly. Wu & Goodman (2018) proposed to train ELBOs with PoE-aggregated inferences of all modality combinations $\sum_{X_s \in \mathcal{X}} \mathcal{L}(\Theta_s, \Phi_s; X_s)$; however, since the

---

[1] We denote the multimodal set and any subset of it by X and X_s, respectively. We also omit the index of each example for brevity.

number of ELBOs increases exponentially, they used the subsampled version. The model that learns PoE inference by this objective function is called MVAE (Wu & Goodman, 2018).

Another method to combine experts is to use MoE as

$$q_{MoE}(\mathbf{z}|X) = \sum_{\mathbf{x}_m \in X} w_m q_{\phi_m}(\mathbf{z}|\mathbf{x}_m), \tag{4}$$

where w_m is a mixing coefficient of each expert and where $\sum_{\mathbf{x}_m \in X} w_m = 1$. Shi et al. (2019) proposed a VAE with MoE-aggregated inference models called MMVAE.

There is a trade-off between the approximate posterior with PoE and MoE. PoE can perform inference given any subset and MVAE can learn inference explicitly during training. PoE also has the property that increasing the size of the subset, i.e., the number of input modalities, leads to an increase in the information content of the inferred latent variables. However, the objective function of MVAE does not guarantee that the inferences from any subset are the same, since it only learns reconstruction and not cross-generation. Sutter et al. (2021) also pointed out that its objective function by subsampling is not a valid lower bound.

MMVAE based on MoE, on the other hand, has a valid ELBO and learns to explicitly encourage cross-generation, which ensures that the inferences from each modality remain consistent. However, this method only learns inferences from a single modality, and increasing the number of modalities does not necessarily increase the information content of the representation.

2.1.2 MoPoE-VAE

Sutter et al. (2021) considered optimization on all possible subsets, i.e., the powerset $\mathcal{P}(X)$, and reestablished minimizing the following KL divergence as the objective of multimodal VAEs:

$$\underset{\phi}{\arg\min} \sum_{X_c \in \mathcal{P}(X)} D_{\mathrm{KL}}\left(q_{\phi_c}\left(\mathbf{z}|X_k\right) \| p_{\Theta}(\mathbf{z}|X)\right). \tag{5}$$

They then proposed a generalized ELBO that is an valid lower bound on the log-likelihood $p_{\Theta}(X)$ and whose maximization corresponds to the minimization of Equation 5:

$$\mathbb{E}_{q_{MoPoE}(\mathbf{z}|X)}[\log p_{\Theta}(X|\mathbf{z})] - D_{KL}(q_{MoPoE}(\mathbf{z}|X)\|p(\mathbf{z})), \tag{6}$$

where the form of the posterior of $q_{MoPoE}(\mathbf{z}|X)$ is called MoPoE, and is defined as follows:

$$q_{MoPoE}(\mathbf{z}|X) = \frac{1}{2^M} \sum_{X_c \in \mathcal{P}(X)} q_{PoE}(\mathbf{z}|X_c). \tag{7}$$

A feature of the model that maximizes Equation 6, called MoPoE-VAE, is that it learns to generate all modalities from all possible subsets, including reconstruction and cross-generation, which improves the performance of inference and generation from all subsets. In addition, they showed that this MoPoE-VAE is a generalization of MVAE and MMVAE, specifically, MVAE when the summation in Equation 7 is taken only for a set of all modalities X, and MMVAE when it is taken for the single modalities $\{\mathbf{x}_m\}_{m=1}^M$. Therefore, MoPoE-VAE can be regarded as having the advantages of both MVAE and MMVAE.

2.2 Variational gradient origin networks

Variational gradient origin networks (VGONs) (Bond-Taylor & Willcocks, 2020) are deep generative models that can perform amortized inference equivalent to VAEs without an inference network [2].

Given a observed variable $\mathbf{x}$ and a latent variable $\mathbf{z}$, let the generative model be $p_\theta(\mathbf{x}|\mathbf{z})$, and the inference model be $q_{\phi,\mathbf{z}_0}(\mathbf{z}) = \mathcal{N}(\mu_\phi(\mathbf{z}_0), \sigma_\phi^2(\mathbf{z}_0)\mathbf{I})$ with the mean and variance mapped by trainable

---

[2]In the original paper (Bond-Taylor & Willcocks, 2020), gradient origin networks were introduced first, and then variational GONs and implicit GONs were introduced as an extension of them.

linear transformations (μ_ϕ and σ_ϕ^2) from a parameter $\mathbf{z}_0$. These objective function, ELBO, given $\mathbf{x}$ is defined as follows:

$$\mathcal{L}_{VGON}(\theta, \phi, \mathbf{z}_0; \mathbf{x}) \equiv \mathbb{E}_{q_{\phi, \mathbf{z}_0}(\mathbf{z})}[\log p_\theta(\mathbf{x}|\mathbf{z})] - D_{KL}(q_{\phi, \mathbf{z}_0}(\mathbf{z})||p(\mathbf{z})). \qquad (8)$$

In VGONs, the estimator for $\mathbf{z}_0$ is calculated by a single update based on the gradient of Equation 8 as follows:

$$\hat{\mathbf{z}}_0 = \mathbf{z}_0 + \nabla_{\mathbf{z}_0} \mathcal{L}_{VGON}(\theta, \phi, \mathbf{z}_0; \mathbf{x}), \qquad (9)$$

where $\mathbf{z}_0 = \mathbf{0}$, i.e, the initial value of $\mathbf{z}_0$ is set to origin. Using this estimator $\hat{\mathbf{z}}_0$, we can obtain inference as $\mathbf{z} \sim q_{\phi, \hat{\mathbf{z}}_0}(\mathbf{z})$ and can evaluate the objective function as $\mathcal{L}_{VGON}(\theta, \phi, \hat{\mathbf{z}}_0; \mathbf{x})$. In learning, we also backpropagate the gradient of the objective function through Equation 9, which allows us to learn both inference and generation simultaneously as in VAEs.

3 METHODS

3.1 ISSUES OF MOPOE-VAE

MoPoE-VAE aims at the objective of Equation 5 by maximizing the ELBO of Equation 6. The two are equivalent in variational inference, but have different implications for learning including generative models, i.e., whether the Equation 5 is achieved depends on the performance of all modalities of reconstruction and cross-generation. Therefore, in situations where cross-generation is difficult, this objective may not be fully achieved.

Another issue is that the computational cost of evaluating Equation 6 increases exponentially with the number of modalities. Specifically, we consider a computational path that generates modalities from inferred representations. In this case, since there are 2^M representations to be inferred by MoPoE, the generation path required to evaluate Equation 6 is $M \times 2^M$; therefore, as the number of modalities increases, the evaluation of the ELBO becomes more intractable and might also lead to insufficient learning of cross-generation.

3.2 INTRODUCTION OF A SURROGATE JOINT POSTERIOR AND REFORMULATION OF OBJECTIVE

To address the above issues, we aim to explicitly realize Equation 5. However, since the true posterior cannot be obtained, we prepare a surrogate joint posterior $q_\Lambda(\mathbf{z}|X)$ that approximates the true posterior. We then reformulate our objective as minimizing the KL divergence between subset inferences and this surrogate posterior:

$$\arg\min_\phi \sum_{X_c \in \mathcal{P}(X)} D_{KL}\left(q_{\phi_c}(\mathbf{z}|X_k) \| q_\Lambda(\mathbf{z}|X)\right). \qquad (10)$$

If $D_{KL}(q_\Lambda(\mathbf{z}|X)||p_\Theta(\mathbf{z}|X)) = 0$ is satisfied, then this optimization problem is the same as Equation 5. However, since the surrogate joint posterior is assumed to be a parameterized model, it cannot be satisfied exactly; therefore, we instead find a parameter that minimizes this KL divergence $D_{KL}(q_\Lambda(\mathbf{z}|X)||p_\Theta(\mathbf{z}|X))$, which is equivalent to maximizing the ELBO as described in Section 2.1. Hence, our objective function for multimodal VAEs is as follows:

$$\mathcal{L}(\Theta, \Lambda; X) - \frac{\beta}{2^M} \sum_{X_c \in \mathcal{P}(X)} D_{KL}\left(q_{\phi_c}(\mathbf{z}|X_c) \| q_\Lambda(\mathbf{z}|X)\right), \qquad (11)$$

where β is a hyperparameter that adjusts for the effect of KL divergence in the objective function. We use PoE for inference from subsets $q_{\phi_c}(\mathbf{z}|X_c)$. We train this objective function in an end-to-end fashion, and at test time, we infer representations from subsets using a PoE-aggregated inference model.

The advantages of this objective function are as follows. First, inference models from arbitrary subsets are learned not by cross-generation, but by explicitly minimizing the divergence between them and the surrogate posterior. Moreover, the surrogate posterior is learned based on the maximization of ELBO $\mathcal{L}(\Theta, \Lambda; X)$, i.e., based on the reconstruction in all modalities, rather than cross-generation.

Therefore, it is unlikely that the performance of inference and generation will be degraded by the difficulty of cross-generation.

Secondly, the computational cost can be significantly reduced compared to MoPoE-VAE. There is only one pass of generation in evaluating this objective function for each modality in $\mathcal{L}(\Theta, \Lambda; X)$. Also, the second term of Equation 11 computes the inference for all possible subsets, which is obtained by aggregating the inferences for each modality; therefore, the inference pass is also only once for each modality.

We call the proposed model a scalable multimodal variational autoencoder (SMVAE) because it is scalable to the number of modalities while explicitly optimizing toward the objective of multimodal VAEs.

3.3 REDUCING THE PARAMETERS IN SURROGATE INFERENCE MODELS

Although the proposed method alleviate the issues of previous multimodal VAEs, it also has the disadvantage of requiring more parameters for the inference model. The added surrogate posterior requires as many parameters as all of the unimodal inference models, i.e., the parameter size of the inference model is twice as large as that of previous models such as MoPoE-VAE. Note that existing studies of multimodal VAEs such as JMVAE (Suzuki et al., 2016), which will be described in related studies, also use additional inference models, but the parameter size increases exponentially because an inference model is required for each subset. In comparison, SMVAE keeps the number of required parameters linear with respect to the number of modalities.

To reduce the number of required parameters, we propose to use VGONs to train the surrogate posterior and generative models for all modalities. In the VGON framework, the surrogate posterior given mutlimodal inputs can be defined as $q_{\lambda, \mathbf{z}_0}(\mathbf{z}) = \mathcal{N}(\mu_\lambda(\mathbf{z}_0), \sigma_\lambda^2(\mathbf{z}_0)\mathbf{I})$, where the estimator of $\mathbf{z}_0$ is calculated as $\hat{\mathbf{z}}_0 = \nabla_{\mathbf{z}_0} \mathcal{L}_{VGON}(\Theta, \lambda, \mathbf{z}_0; X)$. Therefore, the objective function of the proposed method using VGONs is as follows:

$$\mathcal{L}_{VGON}(\Theta, \lambda, \mathbf{z}_0; X) - \frac{\beta}{2^M} \sum_{X_c \in \mathcal{P}(X)} D_{\mathrm{KL}}\left(q_{\phi_c}(\mathbf{z}|X_k) \| q_{\lambda, \mathbf{z}_0}(\mathbf{z})\right). \tag{12}$$

We refer to this model as *SMVGON* to distinguish it from SMVAE.

Note that the surrogate posterior is used to approximate the aggregated inference model during training and is not used during testing; therefore, an iterative inference algorithm can be used. In this study, however, we used VGONs, which can perform inference in a single iteration, to avoid slow training.

4 RELATED WORKS

For learning unsupervised joint representations from multimodal data, autoencoder-based methods have been used (Ngiam et al., 2011; Silberer & Lapata, 2014); however, they have difficulties in the challenge of missing modalities. Joint representation learning using deep belief networks (Hinton, 2009) or deep Boltzmann machines (Salakhutdinov & Hinton, 2009) can adequately handle missing modalities (Srivastava & Salakhutdinov, 2012; Srivastava et al., 2012; Sohn et al., 2014), but has difficulty scaling to large dataset.

Early multimodal learning using VAEs dealt with cross-generation of two modalities, such as conditional VAEs (Sohn et al., 2015; Kingma et al., 2014) and conditional multi-modal autoencoders (Pandey & Dukkipati, 2017). However, because these methods directly learn conditional generative models, they cannot perform bidirectional generation between modalities, nor can they obtain joint latent representations of different modalities.

Suzuki et al. (2016) introduced JMVAE that learns a joint generative model. They also pointed out the need to deal with the missing modality and suggested explicitly bringing the unimodal inference closer to the joint inference during training. Vedantam et al. (2018) introduced TELBO as another objective function for learning joint and unimodal inference models. These models require inference models for all combinations of modalities, i.e., the number of inference models grows exponentially with the number of modalities. Our proposed method is similar to these methods in that it introduces

an additional inference model. However, unlike these methods, required memory cost is linear in the number of modalities. When the number of modalities is two, the proposed method is similar to JMVAE, except that the direction of KL divergence is reversed and PoE-aggregation is used for inference. Please refer to Appendix A for the similarity and performance difference between JMVAE and our proposed method. When the number of modalities is two, the performance of the representations is comparable, but our method outperforms in the cross-generation.

The other topic in multimodal VAEs is the acquisition of modality-specific latent variables, apart from the global latent variables that embed all modalities (Tsai et al., 2018; Hsu & Glass, 2018; Sutter et al., 2020). Our study is in a different direction from these, since we are addressing the possibility of inferring a single joint representation from arbitrary subset of modalities (Equation 5). In the experiments, we confirm that the proposed method achieves high performance with a single latent variable in a task where the conventional method achieves such performance by adding modality-specific latent variables.

Recently, contrastive-based multimodal (multi-view) learning (Tian et al., 2019; Alayrac et al., 2020; Tsai et al., 2021) has been gaining attention instead of autoencoder-based, but these aim to acquire *coordinated* representations (Baltrušaitis et al., 2018), i.e., they do not assume inference from a subset of arbitrary modalities.

5 EXPERIMENTS

We use MNIST-SVHN-Text (Sutter et al., 2020) and Bimodal CelebA (Sutter et al., 2020) datasets for evaluation. MNIST-SVHN-Text is the MNIST-SVHN (Shi et al., 2019) with the addition of the text modality, which represents the English name of each number as text and randomly changes the starting index to give a diversity. Bimodal CelebA is a dataset of face images from the CelebA (Liu et al., 2015) with additional text describing the corresponding attribute labels.

We confirm that the proposed model realizes the objective of Equation 5, i.e., it can properly infer representations or generate modalities from arbitrary subsets. To evaluate this quantitatively, we estimate the performance of the representation by training a linear classifier under inference from all modalities and predicting by it from the representation inferred from subsets. If this evaluation results in high performance on different subsets, it means that the inference from the subsets is successful. We also perform cross-generation from arbitrary modalities and evaluate the performance of the generated modalities by pre-trained classifiers from Sutter et al. (2020). [3] The interpretation of this evaluation is the same as in the case of representation.

For the network architectures, we follow Sutter et al. (2020), with 32-dimensional latent variables. The distributions for images are set to Laplace, and Text is set to categorical. To align the scaling of the likelihoods for each modality, we divided each likelihood by the dimension of each modality and multiplied the largest dimension value by all likelihoods so that the coefficient of the likelihood term with the largest dimension was 1. We use Adam (Kingma & Ba, 2014) for optimization, with a learning rate of 0.001, and a mini-batch size of 256. We set $\beta = 1$ and train all models for 50 epochs. All experimental results are the average of three runs. We implement them using PyTorch (Paszke et al., 2019) and Pixyz (Suzuki et al., 2021).

5.1 MNIST-SVHN-TEXT

Before validating our proposed method, we first confirm that VGON performs well enough as a surrogate inference model. Table 1 shows the inference and generation performance of VAE and VGON for multimodal inputs. It can be seen that VGON can generally learn inference models equivalent to VAE without inference networks, although its performance is slightly lower than that of VAE.

Next, we compare the performance of our proposed method with that of existing methods. Table 2 shows the results of the performance of representations in MNIST-SVHN-Text. MVAE has better performance for joint representations, but poorer performance for representations inferred from single modalities. MMVAE has better performance for inference from single modalities, but worse performance for joint inference. The performance of MoPoE compensates for the shortcomings of

---

[3]https://github.com/thomassutter/mmjsd

Table 1: Classification accuracy on the latent representation and generated modalities in MNIST-SVHN-Text. M, S and T respectively stand for MNIST, SVHN, and Text, indicating that the representations are inferred from these modalities. M+S means both M and S.

| | LATENT REPRESENTATION | GENERATION | | |
MODEL	M+S+T	M+S+T $\rightarrow$ M	M+S+T$\rightarrow$S	M+S+T$\rightarrow$T
VAE	0.999	0.968	0.870	0.999
VGON	0.997	0.918	0.858	0.998

Table 2: Classification accuracy on the latent representation in MNIST-SVHN-Text. Bold represents the highest accuracy in each modality.

MODEL	M	S	T	M+S	M+T	S+T	M+S+T
MVAE	0.823	0.431	0.850	0.859	0.978	0.821	0.978
MMVAE	**0.970**	**0.825**	**0.999**	0.897	0.985	0.912	0.932
MoPoE-VAE	0.884	0.748	**0.999**	0.914	0.975	0.931	0.981
SMVAE	0.946	0.783	**0.999**	0.964	0.992	0.994	**0.999**
SMVGON	0.956	0.800	**0.999**	0.975	0.995	0.998	**0.999**

both methods. In contrast, the proposed method outperforms MoPoE in inference from most of the subsets, though it is lower than MMVAE for single modalities. This indicates that approximations that minimize the divergence from the surrogate posterior are more effective than computationally expensive approximations based on cross-generation. In addition, the performance of SMVGON is almost the same as that of SMVAE, which means that the surrogate posterior using VGON is sufficient as a joint inference model even without inference networks.

The results for generation in Table 3 are similar to those of the inference of the representation. It can be seen that the performance of the previous work on generating SVHN from subsets is greatly degraded. This is thought to be due to the difficulty in cross-generation to SVHN, which resulted in poor learning. On the other hand, the proposed method is able to generate from subsets with the same performance as from all modalities. This shows that the proposed method achieves our objective, i.e., to make inference from any modality as good as from all modalities.

Figure 2 shows the results of SVHN generation given different modalities for MoPoE-VAE, SM-VAE, and SMVGON. We can see that MoPoE-VAE fails to generate SVHN from both MNIST and Text modalities. On the other hand, SMVAE can generate corresponding and diverse SVHN images from each modality. Sutter et al. (2020) attempted this generation by introducing modality-specific latent variables, but these results suggest that our proposed SMVAE can perform cross-generation of SVHN with only a single latent variable. In addition, it can be confirmed that SMVGON can generate images with similar performance, indicating that the objective of this study can be achieved without inference networks.

5.2 BIMODAL CELEBA

Table 4 shows the results of representation and generation for Bimodal CelebA. On this dataset, SMVAE performs better than the other methods. We believe this is due to the challenging nature of this dataset. Although this dataset is bimodal, it has a larger diversity of images and text compared to MNIST-SVHN-Text. Therefore, it becomes difficult to learn reconstructions and cross-generations from a single modality, which makes previous methods that rely on this to learn inference insuffi-

Table 3: Classification accuracy of image generations on MNIST-SVHN-Text.

| | M | | | | S | | | | T | | | |
MODEL	S	T	S+T	M+S+T	M	T	M+T	M+S+T	M	S	M+S	M+S+T
MVAE	0.225	0.173	0.268	0.948	0.441	0.366	0.653	0.783	0.968	0.187	0.251	0.998
MMVAE	0.801	0.999	0.905	0.922	0.363	0.380	0.373	0.450	0.968	**0.821**	0.894	0.930
MoPoE-VAE	**0.791**	**0.998**	0.939	0.962	0.344	0.346	0.353	0.854	**0.969**	0.807	**0.975**	0.985
SMVAE	0.724	0.990	0.967	**0.971**	0.740	0.816	0.768	**0.897**	0.938	0.741	0.952	**0.999**
SMVGON	0.751	0.997	**0.980**	0.969	**0.752**	**0.820**	**0.781**	0.896	0.933	0.753	0.946	**0.999**

Figure 2: Cross-generation of SVHN on MoPoE, SMVAE, and SMVGON. Each row of SVHN in each cross-generation corresponds to a different sample from the inference model.

Table 4: Performance on the latent representation and modality generation in Bimodal CelebA. I and T respectively stand for Image and Text. We report the mean average precision across all modalities.

| | LATENT REPRESENTATION | | | GENERATION | | | |
| | | | | I | | T | |
MODEL	I	T	I+T	T	I+T	I	I+T
MVAE	0.483	0.385	0.543	0.300	0.506	0.254	0.495
MMVAE	0.508	0.478	0.496	0.447	0.454	0.339	0.341
MoPoE-VAE	0.508	0.433	0.529	0.423	0.502	0.315	0.399
SMVAE	**0.557**	**0.560**	**0.587**	0.464	**0.532**	**0.361**	**0.499**
SMVGON	0.501	0.556	0.515	**0.473**	0.451	0.315	0.453

cient. Our proposed method, on the other hand, learns the surrogate joint posterior by reconstructing all modalities, and approximates the inferences from arbitrary subsets to be close to it. Therefore, our method is less sensitive to the difficulty of cross-generation. On the other hand, SMVGON has not reached the same level of performance as SMVAE. This may be due to the difficulty of the multimodal dataset, which makes VGON's inference insufficient. For the training results of VGON alone on this dataset, please refer to Appendix B.

5.3 CONCLUSION

In this study, we proposed SMVAE, which approximates inference from subsets by explicitly minimizing the divergence from the surrogate posterior distribution. The model is scalable with respect to the number of modalities and shows high performance in inference and generation, especially in the case where cross-generation is difficult. Furthermore, to reduce the parameters of the inference model, we introduced SMVAE-GON using VGON, which can learn inference without inference networks. The remaining task of this study is to find a way to introduce a surrogate posterior distribution that will result in good inference with low memory and computational costs. VGON performed well on MNIST-SVHN-Text, but did not perform well on challenging problem settings such as Bimodal CelebA. In the future, we would like to address this issue and pursue effective methods for a wide range of multimodal datasets.

6 ETHICS STATEMENT

This work is a state-of-the-art method for multimodal VAEs, which will have an impact on the machine learning domain due to its scalability. Our method can cross-generate from one modality to another corresponding modality; therefore, we have to be aware that it can be used to generate non-existent facial images, text, spoken voices, etc. In addition, since the attributes in the CelebA dataset used for training in this study have biases (Prabhu et al., 2019), it is necessary to remove these biases when training the proposed method in practice.

7 REPRODUCIBILITY STATEMENT

All codes and datasets necessary to reproduce the experiments in this paper will be available after the paper review is concluded. The hyperparameters and other details in the training were written at the beginning of Section 5, and the architecture of the networks is the same as in Sutter et al. (2020).

REFERENCES

Jean-Baptiste Alayrac, Adrià Recasens, Rosalia Schneider, Relja Arandjelović, Jason Ramapuram, Jeffrey De Fauw, Lucas Smaira, Sander Dieleman, and Andrew Zisserman. Self-supervised multimodal versatile networks. *arXiv preprint arXiv:2006.16228*, 2020.

Tadas Baltrušaitis, Chaitanya Ahuja, and Louis-Philippe Morency. Multimodal machine learning: A survey and taxonomy. *IEEE transactions on pattern analysis and machine intelligence*, 41(2): 423–443, 2018.

Sam Bond-Taylor and Chris G Willcocks. Gradient origin networks. *arXiv preprint arXiv:2007.02798*, 2020.

Geoffrey E Hinton. Training products of experts by minimizing contrastive divergence. *Neural computation*, 14(8):1771–1800, 2002.

Geoffrey E Hinton. Deep belief networks. *Scholarpedia*, 4(5):5947, 2009.

Wei-Ning Hsu and James Glass. Disentangling by partitioning: A representation learning framework for multimodal sensory data. *arXiv preprint arXiv:1805.11264*, 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

Diederik P Kingma, Danilo J Rezende, Shakir Mohamed, and Max Welling. Semi-supervised learning with deep generative models. *arXiv preprint arXiv:1406.5298*, 2014.

Ziwei Liu, Ping Luo, Xiaogang Wang, and Xiaoou Tang. Deep learning face attributes in the wild. In *Proceedings of International Conference on Computer Vision (ICCV)*, December 2015.

Jiquan Ngiam, Aditya Khosla, Mingyu Kim, Juhan Nam, Honglak Lee, and Andrew Y Ng. Multimodal deep learning. In *ICML*, 2011.

Gaurav Pandey and Ambedkar Dukkipati. Variational methods for conditional multimodal deep learning. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pp. 308–315. IEEE, 2017.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 32*, pp. 8024–8035. Curran Associates, Inc., 2019.

Vinay Uday Prabhu, Dian Ang Yap, Alexander Wang, and John Whaley. Covering up bias in celeba-like datasets with markov blankets: A post-hoc cure for attribute prior avoidance. *arXiv preprint arXiv:1907.12917*, 2019.

Danilo Jimenez Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *International conference on machine learning*, pp. 1278–1286. PMLR, 2014.

Ruslan Salakhutdinov and Geoffrey Hinton. Deep boltzmann machines. In *Artificial intelligence and statistics*, pp. 448–455. PMLR, 2009.

Yuge Shi, Narayanaswamy Siddharth, Brooks Paige, and Philip Torr. Variational mixture-of-experts autoencoders for multi-modal deep generative models. In *Advances in Neural Information Processing Systems*, pp. 15718–15729, 2019.

Carina Silberer and Mirella Lapata. Learning grounded meaning representations with autoencoders. In *Proceedings of the 52nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 721–732, 2014.

Kihyuk Sohn, Wenling Shang, and Honglak Lee. Improved multimodal deep learning with variation of information. *Advances in neural information processing systems*, 27:2141–2149, 2014.

Kihyuk Sohn, Honglak Lee, and Xinchen Yan. Learning structured output representation using deep conditional generative models. *Advances in neural information processing systems*, 28: 3483–3491, 2015.

Nitish Srivastava and Ruslan Salakhutdinov. Learning representations for multimodal data with deep belief nets. In *International conference on machine learning workshop*, volume 79, pp. 3, 2012.

Nitish Srivastava, Ruslan Salakhutdinov, et al. Multimodal learning with deep boltzmann machines. In *NIPS*, volume 1, pp. 2. Citeseer, 2012.

Thomas M Sutter, Imant Daunhawer, and Julia E Vogt. Multimodal generative learning utilizing jensen-shannon-divergence. *arXiv preprint arXiv:2006.08242*, 2020.

Thomas M Sutter, Imant Daunhawer, and Julia E Vogt. Generalized multimodal elbo. *arXiv preprint arXiv:2105.02470*, 2021.

Masahiro Suzuki, Kotaro Nakayama, and Yutaka Matsuo. Joint multimodal learning with deep generative models. *arXiv preprint arXiv:1611.01891*, 2016.

Masahiro Suzuki, Takaaki Kaneko, and Yutaka Matsuo. Pixyz: a library for developing deep generative models. *arXiv preprint arXiv:2107.13109*, 2021.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. *arXiv preprint arXiv:1906.05849*, 2019.

Yao-Hung Hubert Tsai, Paul Pu Liang, Amir Zadeh, Louis-Philippe Morency, and Ruslan Salakhutdinov. Learning factorized multimodal representations. *arXiv preprint arXiv:1806.06176*, 2018.

Yao-Hung Hubert Tsai, Yue Wu, Ruslan Salakhutdinov, and Louis-Philippe Morency. Self-supervised learning from a multi-view perspective. In *International Conference on Learning Representations*, 2021.

Ramakrishna Vedantam, Ian Fischer, Jonathan Huang, and Kevin Murphy. Generative models of visually grounded imagination. In *International Conference on Learning Representations*, 2018.

Mike Wu and Noah Goodman. Multimodal generative models for scalable weakly-supervised learning. In *Advances in Neural Information Processing Systems*, pp. 5575–5585, 2018.

A   COMPARISON BETWEEN SMVAE AND JMVAE WHEN THE NUMBER OF MODALITIES IS 2

When the number of modalities is two, the objective function of JMVAE (Suzuki et al., 2016) is as follows:

$$\mathcal{L}(\Theta, \Lambda; X) - \beta D_{\mathrm{KL}}\left(q_\Lambda(\mathbf{z}|X)||q_{\phi_1}\left(\mathbf{z}|\mathbf{x}_1\right)\right) - \beta D_{\mathrm{KL}}\left(q_\Lambda(\mathbf{z}|X)||q_{\phi_2}\left(\mathbf{z}|\mathbf{x}_2\right)\right). \tag{13}$$

Compared to Equation 11, the difference is that the direction of KL divergence is reversed and aggregation by PoE is not used. Table 5 shows the results of comparing SMVAE and JMVAE on the Bimodal CelebA dataset. The performance of the representations is almost the same, but the generation results are better for SMVAE. This may indicate that the KL divergence direction of SMVAE is better for cross-generation.

Table 5: Performance on the latent representation and modality generation in Bimodal CelebA.

| | Latent representation | | | Generation | | | |
| | | | | I | | T | |
MODEL	I	T	I+T	T	I+T	I	I+T
JMVAE	0.556	0.556	**0.591**	0.419	**0.543**	0.304	0.486
SMVAE	**0.557**	**0.560**	0.587	**0.464**	0.532	**0.361**	**0.499**

Table 6: Classification accuracy on the latent representation and generated modalities in Bimodal CelebA.

| | LATENT REPRESENTATION | GENERATION | |
MODEL	I+T	I+T $\rightarrow$ I	I+T$\rightarrow$T
VAE	0.593	0.968	0.499
VGON	0.572	0.918	0.448

B COMPARISON OF VAE AND VGON IN BIMODAL CELEBA

Table 6 shows the comparison between VAE and VGON in Bimodal Celeba. The results confirm that the performance of VGON is lower than that of VAE in all tasks.