Decision Transformer: Trajectory Modeling for Reinforcement Learning

Abstract

We propose a hypothesis that effective policies can be learned from data without dynamic programming bootstrapping. To investigate this, we consider replacing traditional reinforcement learning (RL) algorithms – which bootstrap against a learned value function – with a sequence modeling objective. We train a transformer model on sequences of returns, states, and actions with an autoregressive prediction loss, reducing policy sampling to sequence generation. By training a transformer model using a supervised loss function, we can remove the need for dynamic programming bootstrapping, which is known to be unstable with function approximation. Furthermore, we can also leverage the long-range memory capabilities of transformers and their mature training infrastructure. Through experiments in diverse set of offline RL benchmarks including Atari, OpenAI Gym, and Key-to-Door, we show that our decision transformer model can learn to generate diverse behaviors by conditioning on desired returns. In particular, our decision transformer conditioned with high desired returns produces a policy that is competitive or better than state of the art model-free offline RL algorithms.

Figure 1: Decision Transformer architecture. States, actions, and returns are fed into modality-specific linear embeddings and a positional episodic timestep encoding is added. Tokens are fed into a GPT architecture which predicts actions autoregressively using a causal self-attention mask.

1 Introduction

Recent work has shown transformers [56] can model large-scale distributions of semantic concepts, including capable zero-shot generalization in language [8] and impressive out-of-distribution image generation [48]. This stands in sharp contrast to much work in reinforcement learning (RL), which

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Figure 2: Illustrative example of finding shortest path for a fixed graph (left) posed as reinforcement learning. Training dataset consists of random walk trajectories and their per-node returns-to-go (middle). Conditioned on a starting state and generating largest possible return at each node, Decision Transformer sequences optimal paths.

learns a single policy to model a particular narrow behavior distribution. Given the diversity of applications and impact of transformer models, we seek to examine their application to sequential decision making problems. In particular, instead of using transformers as an architectural choice for traditional RL algorithms [43, 61], we seek to study if trajectory modeling (analogous to language modeling) can serve as a *replacement* for conventional RL algorithms.

We consider the following shift in paradigm: instead of training a policy through conventional RL algorithms like temporal difference (TD) learning [55], the dominant paradigm in RL for improving sample-efficiency, we will train transformer models on collected experience using a sequence modeling objective. This will allow us to bypass the need for bootstrapping to propagate returns – thereby avoiding one of the "deadly triad" [55] known to destabilize RL. It also avoids the need for discounting future rewards, as typically done in TD-learning, which may induce undesirable short-sighted behaviors. Additionally, we can make use of existing transformer frameworks widely used in language and vision that are easy to scale, utilizing a large body of work studying stable training of transformer models. This approach removes the need for specialized RL frameworks by appealing only to commonplace supervised learning systems. Given their demonstrated ability to model long sequences and wide data distributions, transformers also have other advantages. Transformers can perform credit assignment directly via self-attention, in contrast to Bellman backups which slowly propagate rewards and are prone to "distractor" signals [28]. This can enable transformers to still work effectively in the presence of sparse or distracting rewards. Furthermore, a transformer modeling approach can model a wide distribution of behaviors, enabling better generalization and transfer.

We explore our hypothesis by considering offline RL, where we will task agents with learning policies from suboptimal data – producing maximally effective behavior from fixed, limited experience. This task is traditionally challenging due to error propagation and value overestimation [37]. However, it is a natural task when training with a sequence modeling objective. By training an autoregressive model on sequences of states, actions, and returns, we reduce policy sampling to autoregressive generative modeling. We can specify the expertise of the policy – which "skill" to query – by manually setting the return tokens, acting as a prompt for generation.

Illustrative example. To get an intuition for our proposal, consider the task of finding a shortest path on a directed graph posed as an RL problem. The reward is 0 when at the goal node and −1 otherwise. We train a GPT [46] model to predict next token in a sequence of returns-to-go (sum of future rewards), states, and actions. Training only on random walk data – with no expert demonstrations – we can at test time generate *optimal* trajectories by adding a prior to generate highest possible returns (see more details and empirical results in the Appendix) and subsequently generate actions conditioned on that. Thus, by combining the tools of sequence modeling with hindsight return information, we achieve policy improvement without the need for dynamic programming.

Motivated by this observation, we propose Decision Transformer, where we use the GPT architecture to autoregressively model trajectories (shown in Figure 1). We study whether sequence modeling can perform policy optimization by evaluating Decision Transformer on offline RL benchmarks in Atari [6], OpenAI Gym [7], and Key-to-Door [40] environments. We show that – *without using dynamic programming* – Decision Transformer performs comparably on these benchmarks to state-of-the-art model-free offline RL algorithms [2, 36]. Furthermore, in tasks where long-term credit assignment is required, Decision Transformer capably outperforms RL algorithms. With this work, we hope to bridge vast recent progress in transformer models with reinforcement learning problems.

2 Preliminaries

2.1 Offline reinforcement learning

We consider learning in a Markov decision process (MDP) described by the tuple $(\mathcal{S}, \mathcal{A}, P, \mathcal{R})$. The MDP tuple consists of states $s \in \mathcal{S}$, actions $a \in \mathcal{A}$, transition dynamics $P(s'|s, a)$, and a reward function $r = \mathcal{R}(s, a)$. We use s_t, a_t, and $r_t = \mathcal{R}(s_t, a_t)$ to denote the state, action, and reward at timestep t, respectively. The goal in reinforcement learning is to learn a policy which maximizes the expected return $\mathbb{E}\left[\sum_{t=1}^{T} r_t\right]$ in an MDP. In offline reinforcement learning, instead of obtaining data via environment interactions, we only have access to some fixed limited dataset consisting of trajectories from the environment. This setting is harder as it removes the ability for agents to explore the environment and collect additional feedback.

2.2 Transformers

Transformers were proposed by Vaswani et al. [56] as an architecture to efficiently model sequences. They consist of stacked self-attention layers with residual connections. Each self-attention layer receives n embeddings $\{x_i\}_{i=1}^n$ corresponding to unique input tokens, and outputs n embeddings $\{z_i\}_{i=1}^n$, preserving the input dimensions. The i-th token is mapped via linear transformations to a key k_i, query q_i, and value v_i. The i-th output of the self-attention layer is given by weighting the values v_j by the normalized dot product between the query q_i and other keys k_j:

$$z_i = \sum_{j=1}^{n} \texttt{softmax}(\{\langle q_i, k_{j'} \rangle\}_{j'=1}^n)_j \cdot v_j. \tag{1}$$

This allows the layer to assign "credit" by implicitly forming state-return associations via similarity of the query and key vectors (maximizing the dot product). In this work, we use the GPT architecture [46], which modifies the transformer architecture with a causal self-attention mask to enable autoregressive generation, replacing the summation/softmax over the n tokens with only the previous tokens in the sequence ($j \in [1, i]$). We defer the other architecture details to the original papers.

3 Method

In this section, we present Decision Transformer, which models trajectories autoregressively with minimal modification to the transformer architecture, as summarized in Figure 1.

Trajectory representation. The key desiderata in our choice of trajectory representation are (a) it should enable transformers to learn meaningful patterns and (b) we should be able to conditionally generate actions at test time. It is nontrivial to model rewards since we would like the model to generate actions based on *future* desired returns, rather than past rewards. As a result, instead of modeling the rewards directly, we model the returns-to-go $\widehat{R}_t = \sum_{t'=t}^{T} r_{t'}$. This leads to the following trajectory representation which is amenable to autoregressive training and generation:

$$\tau = \left(\widehat{R}_1, s_1, a_1, \widehat{R}_2, s_2, a_2, \ldots, \widehat{R}_T, s_T, a_T\right). \tag{2}$$

At test time, we can specify the desired performance (e.g. 1 for success or 0 for failure), as well as the environment starting state, to initialize generation. After executing the generated action, we decrement the target return by the achieved reward and repeat until episode termination.

Architecture. We feed the last K timesteps into Decision Transformer, for a total of $3K$ tokens (one for each modality: return-to-go, state, or action). To obtain token embeddings, we learn a linear layer for each modality, which projects raw inputs to the embedding dimension, followed by layer normalization [5]. For environments with visual inputs, the state is fed into a convolutional encoder instead of a linear layer. Additionally, an embedding for each timestep is learned and added to each token – note this is different than the standard positional embedding used by transformers, as one timestep corresponds to three tokens. The tokens are then processed by a GPT [46] model, which predicts future action tokens via autoregressive modeling.

Training. We sample minibatches of sequence length K from the dataset. The prediction head corresponding to the input token s_t is trained to predict a_t – either with cross-entropy loss for discrete

Figure 3: Results comparing Decision Transformer (ours) to TD learning (CQL) and behavior cloning across Atari, OpenAI Gym, and Minigrid. On a diverse set of tasks, Decision Transformer performs comparably or better than traditional approaches.

actions or mean-squared error for continuous actions – and the losses for each timestep are averaged. We did not find predicting the states or returns-to-go to be necessary for good performance, although it is possible (as shown in Section 5.3) and would be an interesting study for future work.

4 Evaluations on offline RL benchmarks

In this section, we investigate if Decision Transformer can perform well compared to standard TD and imitation learning approaches for offline RL. TD learning algorithms represent the conventional state-of-the-art, while imitation learning algorithms have similar formulations to Decision Transformer. The exact algorithms depend on the environment but our motivations are as follows:

- **TD learning**: most of these methods use an action-space constraint or value pessimism, and will be the most faithful comparison to Decision Transformer, representing standard RL methods. A state-of-the-art model-free method is Conservative Q-Learning (CQL) [36] which serves as our primary comparison. In addition, we also compare against other prior model-free RL algorithms like BEAR [34] and BRAC [58].

- **Imitation learning**: this regime similarly uses supervised losses for training, rather than Bellman backups. We use behavior cloning here, and include a more detailed discussion in Section 5.1.

We evaluate on both discrete (Atari [6]) and continuous (OpenAI Gym [7]) control tasks. The former requires long-term credit assignment, while the latter requires fine-grained continuous control, representing a diverse set of tasks. Our main results are summarized in Figure 3, where we show averaged expert normalized performance for each domain.

4.1 Atari

In this section, we consider Atari games [6], a widely-used RL benchmark. The Atari benchmark is challenging due to its high-dimensional visual inputs and difficulty of credit assignment arising from the delay between actions and resulting rewards. We evaluate our method on 1% of all samples in the DQN-replay dataset as per Agarwal et al. [2], representing 500 thousand of the 50 million transitions observed by an online DQN agent [41] during training; we report the mean and standard deviation of 3 seeds. We normalize scores based on a professional gamer, following the protocol of Hafner et al. [24], where 100 represents the professional gamer score and 0 represents a random policy.

We compare to CQL [36], REM [2], and QR-DQN [11] on four Atari tasks (Breakout, Qbert, Pong, and Seaquest) that are evaluated in Agarwal et al. [2]. We use context lengths of $K = 30$ for Decision

Game	DT (Ours)	CQL	QR-DQN	REM	BC
Breakout	$\mathbf{267.5 \pm 97.5}$	211.1	21.1	32.1	138.9 ± 61.7
Qbert	25.1 ± 18.1	$\mathbf{104.2}$	1.7	1.4	17.3 ± 14.7
Pong	106.1 ± 8.1	$\mathbf{111.9}$	20.0	39.1	85.2 ± 20.0
Seaquest	$\mathbf{2.4 \pm 0.7}$	1.7	1.4	1.0	2.1 ± 0.3

Table 1: Gamer-normalized scores for the 1% DQN-replay Atari dataset. We report the mean and variance across 3 seeds. Best mean scores are highlighted in bold. Decision Transformer (DT) performs comparably to CQL on 3 out of 4 games, and outperforms other baselines.

Transformer (except $K = 50$ for Pong). We also report the performance of behavior cloning (BC), which utilizes the same network architecture and hyperparameters as Decision Transformer but does not have return-to-go conditioning[1]. For CQL, REM, and QR-DQN baselines, we report numbers directly from the CQL paper. We show results in Table 1. Our method is competitive with CQL in 3 out of 4 games and outperforms or matches REM, QR-DQN, and BC on all 4 games.

4.2 D4RL (OpenAI Gym)

In this section, we consider the continuous control tasks from the D4RL benchmark [20]. We also consider a 2D reacher environment that is not part of the benchmark, and generate the datasets using a similar methodology to the D4RL benchmark. Reacher is a goal-conditioned task and has sparse rewards, so it represents a different setting than the standard locomotion environments (HalfCheetah, Hopper, and Walker). The different dataset settings are described below.

1. Medium: 1 million timesteps generated by a "medium" policy that achieves approximately one-third the score of an expert policy.

2. Medium-Replay: the replay buffer of an agent trained to the performance of a medium policy (approximately 25k-400k timesteps in our environments).

3. Medium-Expert: 1 million timesteps generated by the medium policy concatenated with 1 million timesteps generated by an expert policy.

We compare to CQL [36], BEAR [34], BRAC [58], and AWR [44]. CQL represents the state-of-the-art in model-free offline RL, an instantiation of TD learning with value pessimism. Score are normalized so that 100 represents an expert policy, as per Fu et al. [20]. CQL numbers are reported from the original paper; BC numbers are run by us; and the other methods are reported from the D4RL paper. Our results are shown in Table 2. Decision Transformer achieves the highest scores in a majority of the tasks and is competitive with the state of the art in the remaining tasks.

Dataset	Environment	DT (Ours)	CQL	BEAR	BRAC-v	AWR	BC
Medium-Expert	HalfCheetah	**86.8 ± 1.3**	62.4	53.4	41.9	52.7	59.9
Medium-Expert	Hopper	107.6 ± 1.8	**111.0**	96.3	0.8	27.1	79.6
Medium-Expert	Walker	**108.1 ± 0.2**	98.7	40.1	81.6	53.8	36.6
Medium-Expert	Reacher	**89.1 ± 1.3**	30.6	-	-	-	73.3
Medium	HalfCheetah	42.6 ± 0.1	44.4	41.7	**46.3**	37.4	43.1
Medium	Hopper	**67.6 ± 1.0**	58.0	52.1	31.1	35.9	63.9
Medium	Walker	74.0 ± 1.4	79.2	59.1	**81.1**	17.4	77.3
Medium	Reacher	**51.2 ± 3.4**	26.0	-	-	-	48.9
Medium-Replay	HalfCheetah	36.6 ± 0.8	46.2	38.6	**47.7**	40.3	4.3
Medium-Replay	Hopper	**82.7 ± 7.0**	48.6	33.7	0.6	28.4	27.6
Medium-Replay	Walker	**66.6 ± 3.0**	26.7	19.2	0.9	15.5	36.9
Medium-Replay	Reacher	18.0 ± 2.4	**19.0**	-	-	-	5.4
Average (Without Reacher)		**74.7**	63.9	48.2	36.9	34.3	46.4
Average (All Settings)		**69.2**	54.2	-	-	-	47.7

Table 2: Results for D4RL datasets[3]. We report the mean and variance for three seeds. Decision Transformer (DT) outperforms conventional RL algorithms on almost all tasks.

5 Discussion

5.1 Does Decision Transformer perform behavior cloning on a subset of the data?

In this section, we seek to gain insight into whether Decision Transformer can be thought of as performing imitation learning on a subset of the data with a certain return. To investigate this, we propose a new method, Percentile Behavior Cloning (%BC), where we run behavior cloning on only the top $X\%$ of timesteps in the dataset, ordered by episode returns. The percentile $X\%$ interpolates

---

[1]We also tried using an MLP with $K = 1$ as in prior work, but found this was worse than the transformer.

[3]Given that CQL is generally the strongest TD learning method, for Reacher we only run the CQL baseline.

Dataset	Environment	DT (Ours)	10%BC	25%BC	40%BC	100%BC	CQL
Medium	HalfCheetah	42.6 ± 0.1	42.9	43.0	43.1	43.1	**44.4**
Medium	Hopper	$\mathbf{67.6 \pm 1.0}$	65.9	65.2	65.3	63.9	58.0
Medium	Walker	74.0 ± 1.4	78.8	**80.9**	78.8	77.3	79.2
Medium	Reacher	51.2 ± 3.4	51.0	48.9	58.2	**58.4**	26.0
Medium-Replay	HalfCheetah	36.6 ± 0.8	40.8	40.9	41.1	4.3	**46.2**
Medium-Replay	Hopper	$\mathbf{82.7 \pm 7.0}$	70.6	58.6	31.0	27.6	48.6
Medium-Replay	Walker	66.6 ± 3.0	**70.4**	67.8	67.2	36.9	26.7
Medium-Replay	Reacher	18.0 ± 2.4	**33.1**	16.2	10.7	5.4	19.0
Average		56.1	**56.7**	52.7	49.4	39.5	43.5

Table 3: Comparison between Decision Transformer (DT) and Percentile Behavior Cloning (%BC).

between standard BC ($X = 100\%$) that trains on the entire dataset and only cloning the best observed trajectory ($X \to 0\%$), trading off between better generalization by training on more data with training a specialized model that focuses on a desirable subset of the data.

We show full results comparing %BC to Decision Transformer and CQL in Table 3, sweeping over $X \in [10\%, 25\%, 40\%, 100\%]$. Note that the only way to choose the optimal subset for cloning is to evaluate using rollouts from the environment, so %BC is not a realistic approach; rather, it serves to provide insight into the behavior of Decision Transformer. When data is plentiful – as in the D4RL regime – we find %BC can match or beat other offline RL methods. On most environments, Decision Transformer is competitive with the performance of the best %BC, indicating it can hone in on a particular subset after training on the entire dataset distribution.

In contrast, when we study low data regimes – such as Atari, where we use 1% of a replay buffer as the dataset – %BC is weak (shown in Table 4). This suggests that in scenarios with relatively low amounts of data, Decision Transformer can outperform %BC by using all trajectories in the dataset to improve generalization, even if those trajectories are dissimilar from the return conditioning target. Our results indicate that Decision Transformer can be more effective than simply performing imitation learning on a subset of the dataset. On the tasks we considered, Decision Transformer either outperforms or is competitive to %BC, without the confound of having to select the optimal subset.

Game	DT (Ours)	10%BC	25%BC	40%BC	100%BC
Breakout	$\mathbf{267.5 \pm 97.5}$	28.5 ± 8.2	73.5 ± 6.4	108.2 ± 67.5	138.9 ± 61.7
Qbert	$\mathbf{25.1 \pm 18.1}$	6.6 ± 1.7	16.0 ± 13.8	11.8 ± 5.8	17.3 ± 14.7
Pong	$\mathbf{106.1 \pm 8.1}$	2.5 ± 0.2	13.3 ± 2.7	72.7 ± 13.3	85.2 ± 20.0
Seaquest	$\mathbf{2.4 \pm 0.7}$	1.1 ± 0.2	1.1 ± 0.2	1.6 ± 0.4	2.1 ± 0.3

Table 4: %BC scores for Atari. We report the mean and variance across 3 seeds. Decision Transformer (DT) outperforms all versions of %BC.

5.2 How well does Decision Transformer model the distribution of returns?

We evaluate the ability of Decision Transformer to understand return-to-go tokens by varying the desired target return over a wide range – evaluating the multi-task distribution modeling capability of transformers. Figure 4 shows the average sampled return accumulated by the agent over the course of the evaluation episode for varying values of target return. On every task, the desired target returns and the true observed returns are highly correlated. On some tasks like Pong, HalfCheetah and Walker, Decision Transformer generates trajectories that almost perfectly match the desired returns (as indicated by the overlap with the oracle line). Furthermore, on some Atari tasks like Seaquest, we can prompt the Decision Transformer with higher returns than the maximum episode return available in the dataset, demonstrating that Decision Transformer is sometimes capable of extrapolation.

5.3 Does Decision Transformer perform effective long-term credit assignment?

To evaluate long-term credit assignment capabilities of our model, we consider a variant of the Key-to-Door environment proposed in Mesnard et al. [40]. This is a grid-based environment with a

Figure 4: Sampled (evaluation) returns accumulated by Decision Transformer when conditioned on the specified target (desired) returns. **Top:** Atari. **Bottom:** D4RL medium-replay datasets.

sequence of three phases: (1) in the first phase, the agent is placed in a room with a key; (2) then, the agent is placed in an empty room; (3) and finally, the agent is placed in a room with a door. The agent receives a binary reward when reaching the door in the third phase, but **only** if it picked up the key in the first phase. We train on datasets of trajectories generated by applying random actions and report success rates in Table 5. Methods that use highsight return information: our Decision Transformer model and %BC (trained only on successful episodes) are able to learn effective policies – producing near-optimal paths, despite only training on random walks. TD learning (CQL) cannot effectively propagate Q-values over the long horizons involved and gets poor performance.

Dataset	DT (Ours)	CQL	BC	%BC	Random
1K Random Trajectories	**71.8**%	13.1%	1.4%	69.9%	3.1%
10K Random Trajectories	94.6%	13.3%	1.6%	**95.1**%	3.1%

Table 5: Success rate for Key-to-Door environment. Methods using hindsight (Decision Transformer, %BC) can learn successful policies, while TD learning struggles to perform credit assignment.

5.4 Can transformers be accurate critics in sparse reward settings?

In previous sections, we established that decision transformer can produce effective policies (actors). We now evaluate whether transformer models can also be effective critics. We modify Decision Transformer to output return tokens in addition to action tokens on the Key-to-Door environment. We find that the transformer continuously updates reward probability based on events during the episode, shown in Figure 5 (Left). Furthermore, we find the transformer attends to critical events in the episode (picking up the key or reaching the door), shown in Figure 5 (Right), indicating formation of state-reward associations as discussed in Raposo et al. [49] and enabling accurate value prediction.

Figure 5: **Left:** Averages of running return probabilities predicted by the transformer model for three types of episode outcomes. **Right:** Transformer attention weights from all timesteps superimposed for a particular successful episode. The model attends to steps near pivotal events in the episode, such as picking up the key and reaching the door.

5.5 Does Decision Transformer perform well in sparse reward settings?

A known weakness of TD learning algorithms is that they require densely populated rewards in order to perform well, which can be unrealistic and/or expensive. In contrast, Decision Transformer can improve robustness in these settings since it makes minimal assumptions on the density of the reward. To evaluate this, we consider a delayed return version of the D4RL benchmarks where the agent does not receive any rewards along the trajectory, and instead receives the cumulative reward of the trajectory in the final timestep. Our results for delayed returns are shown in Table 6. Delayed returns minimally affect Decision Transformer; and due to the nature of the training process have no effect on the imitation learning methods. Despite TD learning collapsing, Decision Transformer and %BC still perform well, indicating that Decision Transformer can be more robust to delayed rewards.

Dataset	Environment	Delayed (Sparse)		Agnostic		Original (Dense)	
		DT (Ours)	CQL	BC	%BC	DT (Ours)	CQL
Medium-Expert	Hopper	$\mathbf{107.3 \pm 3.5}$	9.0	59.9	102.6	107.6	111.0
Medium	Hopper	60.7 ± 4.5	5.2	63.9	$\mathbf{65.9}$	67.6	58.0
Medium-Replay	Hopper	$\mathbf{78.5 \pm 3.7}$	2.0	27.6	70.6	82.7	48.6

Table 6: Results for D4RL datasets with delayed (sparse) reward. Decision Transformer (DT) and imitation learning are minimally affected by the removal of dense rewards, while CQL fails.

5.6 Why does Decision Transformer avoid the need for value pessimism or behavior regularization?

One key difference between Decision Transformer and prior offline RL algorithms is that we do not require policy regularization or conservatism to achieve good performance. Our conjecture is that TD-learning based algorithms learn an approximate value function and improve the policy by optimizing this value function. This act of optimizing a learned function can exacerbate and exploit any inaccuracies in the value function approximation, causing failures in policy improvement. Since Decision Transformer does not require explicit optimization using learned functions as objectives, it avoids the need for regularization or conservatism.

5.7 How can Decision Transformer benefit online RL regimes?

Offline RL and the ability to model behaviors has the potential to enable sample-efficient online RL for downstream tasks. Works studying the transition from offline to online generally find that likelihood-based approaches, like our sequence modeling objective, are more successful [22, 42]. As a result, although we studied offline RL in this work, we believe Decision Transformer can meaningfully improve online RL methods by serving as a strong model for behavior generation. For instance, Decision Transformer can serve as a powerful "memorization engine" and in conjunction with powerful exploration algorithms like Go-Explore [16], has the potential to simultaneously model and generative a diverse set of behaviors.

6 Related work

6.1 Offline and supervised reinforcement learning

To mitigate the impact of distribution shift in offline RL, prior algorithms either (a) constrain the policy action space [21, 33, 52] or (b) incorporate value pessimism [21, 36], or (c) incorporate pessimism into learned dynamics models [31, 60]. Since we do not use Decision Transformers to explicitly learn the dynamics model, we primarily compare against model-free algorithms in our work. Another line of work explores learning wide behavior distribution from an offline dataset by learning a task-agnostic set of skills, either with likelihood-based approaches [3, 9, 45, 53] or by maximizing mutual information [17, 39, 51]. Our work is similar to the likelihood-based approaches, although we use a simpler sequence modeling objective instead of a variational method, and use rewards for conditional generation of behaviors. Furthermore, other works have proposed return conditioning/"supervised RL" methods: Kumar et al. [35] and Srivastava et al. [54] train Markovian agents with a supervised loss to predict actions conditioned on episode returns for online RL. While

these methods are similar to ours, Decision Transformers benefit from the use of long contexts for behavior modeling as long-term credit assignment.

6.2 Credit assignment

Many works have studied better credit assignment via state-association, learning an architecture which decomposes the reward function such that certain "important" states comprise most of the credit [18, 25, 40]. They use the learned reward function to change the reward of an actor-critic algorithm to help propagate signal over long horizons. In particular, similar to our long-term setting, some works have specifically shown such state-associative architectures can perform better in delayed reward settings [4, 28, 38, 49]. In contrast, we allow these properties to naturally emerge in a transformer architecture, without having to explicitly learn a reward function or a critic.

6.3 Conditional language generation

Various works have studied guided generation for images [29] and language [23, 57]. Several works [19, 27, 47, 59, 62, 30] have explored training or fine-tuning of models for controllable text generation. Class-conditional language models can also be used to learn disciminators to guide generation [13, 23, 26, 32]. However, these approaches mostly assume constant "classes", while in reinforcement learning the reward signal is time-varying. Furthermore, it is more natural to prompt the model desired target return and continuously decrease it by the observed rewards over time, since the transformer model and environment jointly generate the trajectory.

6.4 Attention and transformer models

Transformers [56] have been applied successfully to many tasks in natural language processing [14, 46] and computer vision [10, 15]. However, transformers are relatively unstudied in RL, mostly due to differing nature of the problem, such as higher variance in training. Zambaldi et al. [61] showed that augmenting transformers with relational reasoning improve performance in combinatorial environments and Ritter et al. [50] showed iterative self-attention allowed for RL agents to better utilize episodic memories. Parisotto et al. [43] discussed design decisions for more stable training of transformers in the high-variance RL setting. Unlike our work, these still use actor-critic algorithms for optimization, focusing on novelty in architecture. Additionally, in imitation learning, some works have studied transformers as a replacement for LSTMs: Dasari & Gupta [12] study one-shot imitation learning, and Abramson et al. [1] combine language and image modalities.

7 Conclusion

We proposed Decision Transformer, seeking to unify ideas in language/sequence modeling and reinforcement learning. On standard offline RL benchmarks, we showed Decision Transformer can match or outperform strong algorithms designed explicitly for offline RL with minimal modifications from standard language modeling architectures.

We hope this work inspires more investigation into using large transformer models for RL. We used a simple supervised loss that was effective in our experiments, but applications to large-scale datasets could benefit from self-supervised pretraining tasks. In addition, one could consider more sophisticated embeddings for returns, states, and actions – for instance, conditioning on return distributions to model stochastic settings instead of deterministic returns. Transformer models can also be used to model the state evolution of trajectory, potentially serving as an alternative to model-based RL, and we hope to explore this in future work.

For real-world applications, it is important to understand the types of errors transformers make in MDP settings and possible negative consequences, which are underexplored. It will also be important to consider the datasets we train models on, which can potentially add destructive biases, particularly as we consider studying augmenting RL agents with more data which may come from questionable sources. For instance, reward design by nefarious actors can thus potentially generate unintended behaviors as our model generates behaviors by conditioning on desired returns.

References

[1] Abramson, Josh, Ahuja, Arun, Barr, Iain, Brussee, Arthur, Carnevale, Federico, Cassin, Mary, Chhaparia, Rachita, Clark, Stephen, Damoc, Bogdan, Dudzik, Andrew, et al. Imitating interactive intelligence. *arXiv preprint arXiv:2012.05672*, 2020.

[2] Agarwal, Rishabh, Schuurmans, Dale, and Norouzi, Mohammad. An optimistic perspective on offline reinforcement learning. In *International Conference on Machine Learning*, 2020.

[3] Ajay, Anurag, Kumar, Aviral, Agrawal, Pulkit, Levine, Sergey, and Nachum, Ofir. Opal: Offline primitive discovery for accelerating offline reinforcement learning. *arXiv preprint arXiv:2010.13611*, 2020.

[4] Arjona-Medina, Jose A, Gillhofer, Michael, Widrich, Michael, Unterthiner, Thomas, Brandstetter, Johannes, and Hochreiter, Sepp. Rudder: Return decomposition for delayed rewards. *arXiv preprint arXiv:1806.07857*, 2018.

[5] Ba, Jimmy Lei, Kiros, Jamie Ryan, and Hinton, Geoffrey E. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[6] Bellemare, Marc G, Naddaf, Yavar, Veness, Joel, and Bowling, Michael. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

[7] Brockman, Greg, Cheung, Vicki, Pettersson, Ludwig, Schneider, Jonas, Schulman, John, Tang, Jie, and Zaremba, Wojciech. Openai gym. *arXiv preprint arXiv:1606.01540*, 2016.

[8] Brown, Tom B, Mann, Benjamin, Ryder, Nick, Subbiah, Melanie, Kaplan, Jared, Dhariwal, Prafulla, Neelakantan, Arvind, Shyam, Pranav, Sastry, Girish, Askell, Amanda, et al. Language models are few-shot learners. *arXiv preprint arXiv:2005.14165*, 2020.

[9] Campos, Víctor, Trott, Alexander, Xiong, Caiming, Socher, Richard, Giro-i Nieto, Xavier, and Torres, Jordi. Explore, discover and learn: Unsupervised discovery of state-covering skills. In *International Conference on Machine Learning*, 2020.

[10] Carion, Nicolas, Massa, Francisco, Synnaeve, Gabriel, Usunier, Nicolas, Kirillov, Alexander, and Zagoruyko, Sergey. End-to-end object detection with transformers. In *European Conference on Computer Vision*, 2020.

[11] Dabney, Will, Rowland, Mark, Bellemare, Marc, and Munos, Rémi. Distributional reinforcement learning with quantile regression. In *Conference on Artificial Intelligence*, 2018.

[12] Dasari, Sudeep and Gupta, Abhinav. Transformers for one-shot visual imitation. *arXiv preprint arXiv:2011.05970*, 2020.

[13] Dathathri, Sumanth, Madotto, Andrea, Lan, Janice, Hung, Jane, Frank, Eric, Molino, Piero, Yosinski, Jason, and Liu, Rosanne. Plug and play language models: A simple approach to controlled text generation. *arXiv preprint arXiv:1912.02164*, 2019.

[14] Devlin, Jacob, Chang, Ming-Wei, Lee, Kenton, and Toutanova, Kristina. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

[15] Dosovitskiy, Alexey, Beyer, Lucas, Kolesnikov, Alexander, Weissenborn, Dirk, Zhai, Xiaohua, Unterthiner, Thomas, Dehghani, Mostafa, Minderer, Matthias, Heigold, Georg, Gelly, Sylvain, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[16] Ecoffet, Adrien, Huizinga, Joost, Lehman, Joel, Stanley, Kenneth O, and Clune, Jeff. Go-explore: a new approach for hard-exploration problems. *arXiv preprint arXiv:1901.10995*, 2019.

[17] Eysenbach, Benjamin, Gupta, Abhishek, Ibarz, Julian, and Levine, Sergey. Diversity is all you need: Learning skills without a reward function. In *International Conference on Learning Representations*, 2019.

[18] Ferret, Johan, Marinier, Raphaël, Geist, Matthieu, and Pietquin, Olivier. Self-attentional credit assignment for transfer in reinforcement learning. *arXiv preprint arXiv:1907.08027*, 2019.

[19] Ficler, Jessica and Goldberg, Yoav. Controlling linguistic style aspects in neural language generation. *arXiv preprint arXiv:1707.02633*, 2017.

[20] Fu, Justin, Kumar, Aviral, Nachum, Ofir, Tucker, George, and Levine, Sergey. D4rl: Datasets for deep data-driven reinforcement learning. *arXiv preprint arXiv:2004.07219*, 2020.

[21] Fujimoto, Scott, Meger, David, and Precup, Doina. Off-policy deep reinforcement learning without exploration. In *International Conference on Machine Learning*, 2019.

[22] Gao, Yang, Xu, Huazhe, Lin, Ji, Yu, Fisher, Levine, Sergey, and Darrell, Trevor. Reinforcement learning from imperfect demonstrations. *arXiv preprint arXiv:1802.05313*, 2018.

[23] Ghazvininejad, Marjan, Shi, Xing, Priyadarshi, Jay, and Knight, Kevin. Hafez: an interactive poetry generation system. In *Proceedings of ACL, System Demonstrations*, 2017.

[24] Hafner, Danijar, Lillicrap, Timothy, Norouzi, Mohammad, and Ba, Jimmy. Mastering atari with discrete world models. *arXiv preprint arXiv:2010.02193*, 2020.

[25] Harutyunyan, Anna, Dabney, Will, Mesnard, Thomas, Azar, Mohammad, Piot, Bilal, Heess, Nicolas, van Hasselt, Hado, Wayne, Greg, Singh, Satinder, Precup, Doina, et al. Hindsight credit assignment. *arXiv preprint arXiv:1912.02503*, 2019.

[26] Holtzman, Ari, Buys, Jan, Forbes, Maxwell, Bosselut, Antoine, Golub, David, and Choi, Yejin. Learning to write with cooperative discriminators. *arXiv preprint arXiv:1805.06087*, 2018.

[27] Hu, Zhiting, Yang, Zichao, Liang, Xiaodan, Salakhutdinov, Ruslan, and Xing, Eric P. Toward controlled generation of text. In *International Conference on Machine Learning*, 2017.

[28] Hung, Chia-Chun, Lillicrap, Timothy, Abramson, Josh, Wu, Yan, Mirza, Mehdi, Carnevale, Federico, Ahuja, Arun, and Wayne, Greg. Optimizing agent behavior over long time scales by transporting value. *Nature communications*, 10(1):1–12, 2019.

[29] Karras, Tero, Laine, Samuli, and Aila, Timo. A style-based generator architecture for generative adversarial networks. In *Conference on Computer Vision and Pattern Recognition*, 2019.

[30] Keskar, Nitish Shirish, McCann, Bryan, Varshney, Lav R, Xiong, Caiming, and Socher, Richard. Ctrl: A conditional transformer language model for controllable generation. *arXiv preprint arXiv:1909.05858*, 2019.

[31] Kidambi, Rahul, Rajeswaran, Aravind, Netrapalli, Praneeth, and Joachims, Thorsten. Morel: Model-based offline reinforcement learning. In *Advances in Neural Information Processing Systems*, 2020.

[32] Krause, Ben, Gotmare, Akhilesh Deepak, McCann, Bryan, Keskar, Nitish Shirish, Joty, Shafiq, Socher, Richard, and Rajani, Nazneen Fatema. Gedi: Generative discriminator guided sequence generation. *arXiv preprint arXiv:2009.06367*, 2020.

[33] Kumar, Aviral, Fu, Justin, Soh, Matthew, Tucker, George, and Levine, Sergey. Stabilizing off-policy q-learning via bootstrapping error reduction. In *Advances in Neural Information Processing Systems*, 2019.

[34] Kumar, Aviral, Fu, Justin, Tucker, George, and Levine, Sergey. Stabilizing off-policy q-learning via bootstrapping error reduction. *arXiv preprint arXiv:1906.00949*, 2019.

[35] Kumar, Aviral, Peng, Xue Bin, and Levine, Sergey. Reward-conditioned policies. *arXiv preprint arXiv:1912.13465*, 2019.

[36] Kumar, Aviral, Zhou, Aurick, Tucker, George, and Levine, Sergey. Conservative q-learning for offline reinforcement learning. In *Advances in Neural Information Processing Systems*, 2020.

[37] Levine, Sergey, Kumar, Aviral, Tucker, George, and Fu, Justin. Offline reinforcement learning: Tutorial, review, and perspectives on open problems. *arXiv preprint arXiv:2005.01643*, 2020.

[38] Liu, Yang, Luo, Yunan, Zhong, Yuanyi, Chen, Xi, Liu, Qiang, and Peng, Jian. Sequence modeling of temporal credit assignment for episodic reinforcement learning. *arXiv preprint arXiv:1905.13420*, 2019.

[39] Lu, Kevin, Grover, Aditya, Abbeel, Pieter, and Mordatch, Igor. Reset-free lifelong learning with skill-space planning. *arXiv preprint arXiv:2012.03548*, 2020.

[40] Mesnard, Thomas, Weber, Théophane, Viola, Fabio, Thakoor, Shantanu, Saade, Alaa, Harutyunyan, Anna, Dabney, Will, Stepleton, Tom, Heess, Nicolas, Guez, Arthur, et al. Counterfactual credit assignment in model-free reinforcement learning. *arXiv preprint arXiv:2011.09464*, 2020.

[41] Mnih, Volodymyr, Kavukcuoglu, Koray, Silver, David, Rusu, Andrei A, Veness, Joel, Bellemare, Marc G, Graves, Alex, Riedmiller, Martin, Fidjeland, Andreas K, Ostrovski, Georg, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[42] Nair, Ashvin, Dalal, Murtaza, Gupta, Abhishek, and Levine, Sergey. Accelerating online reinforcement learning with offline datasets. *arXiv preprint arXiv:2006.09359*, 2020.

[43] Parisotto, Emilio, Song, Francis, Rae, Jack, Pascanu, Razvan, Gulcehre, Caglar, Jayakumar, Siddhant, Jaderberg, Max, Kaufman, Raphael Lopez, Clark, Aidan, Noury, Seb, et al. Stabilizing transformers for reinforcement learning. In *International Conference on Machine Learning*, 2020.

[44] Peng, Xue Bin, Kumar, Aviral, Zhang, Grace, and Levine, Sergey. Advantage-weighted regression: Simple and scalable off-policy reinforcement learning. *arXiv preprint arXiv:1910.00177*, 2019.

[45] Pertsch, Karl, Lee, Youngwoon, and Lim, Joseph J. Accelerating reinforcement learning with learned skill priors. *arXiv preprint arXiv:2010.11944*, 2020.

[46] Radford, Alec, Narasimhan, Karthik, Salimans, Tim, and Sutskever, Ilya. Improving language understanding by generative pre-training. 2018.

[47] Rajani, Nazneen Fatema, McCann, Bryan, Xiong, Caiming, and Socher, Richard. Explain yourself! leveraging language models for commonsense reasoning. *arXiv preprint arXiv:1906.02361*, 2019.

[48] Ramesh, Aditya, Pavlov, Mikhail, Goh, Gabriel, Gray, Scott, Voss, Chelsea, Radford, Alec, Chen, Mark, and Sutskever, Ilya. Zero-shot text-to-image generation. *arXiv preprint arXiv:2102.12092*, 2021.

[49] Raposo, David, Ritter, Sam, Santoro, Adam, Wayne, Greg, Weber, Theophane, Botvinick, Matt, van Hasselt, Hado, and Song, Francis. Synthetic returns for long-term credit assignment. *arXiv preprint arXiv:2102.12425*, 2021.

[50] Ritter, Sam, Faulkner, Ryan, Sartran, Laurent, Santoro, Adam, Botvinick, Matt, and Raposo, David. Rapid task-solving in novel environments. *arXiv preprint arXiv:2006.03662*, 2020.

[51] Sharma, Archit, Gu, Shixiang, Levine, Sergey, Kumar, Vikash, and Hausman, Karol. Dynamics-aware unsupervised discovery of skills. In *International Conference on Learning Representations*, 2020.

[52] Siegel, Noah Y, Springenberg, Jost Tobias, Berkenkamp, Felix, Abdolmaleki, Abbas, Neunert, Michael, Lampe, Thomas, Hafner, Roland, and Riedmiller, Martin. Keep doing what worked: Behavioral modelling priors for offline reinforcement learning. In *International Conference on Learning Representations*, 2020.

[53] Singh, Avi, Liu, Huihan, Zhou, Gaoyue, Yu, Albert, Rhinehart, Nicholas, and Levine, Sergey. Parrot: Data-driven behavioral priors for reinforcement learning. In *International Conference on Learning Representations*, 2021.

[54] Srivastava, Rupesh Kumar, Shyam, Pranav, Mutz, Filipe, Jaśkowski, Wojciech, and Schmidhuber, Jürgen. Training agents using upside-down reinforcement learning. *arXiv preprint arXiv:1912.02877*, 2019.

[55] Sutton, Richard S and Barto, Andrew G. *Reinforcement learning: An introduction*. MIT Press, 2018.

[56] Vaswani, Ashish, Shazeer, Noam, Parmar, Niki, Uszkoreit, Jakob, Jones, Llion, Gomez, Aidan N, Kaiser, Lukasz, and Polosukhin, Illia. Attention is all you need. In *Advances in Neural Information Processing Systems*, 2017.

[57] Weng, Lilian. Controllable neural text generation. *lilianweng.github.io/lil-log*, 2021. URL https://lilianweng.github.io/lil-log/2021/01/02/controllable-neural-text-generation.html.

[58] Wu, Yifan, Tucker, George, and Nachum, Ofir. Behavior regularized offline reinforcement learning. *arXiv preprint arXiv:1911.11361*, 2019.

[59] Yu, Lantao, Zhang, Weinan, Wang, Jun, and SeqGAN, Yong Yu. Sequence generative adversarial nets with policy gradient. arxiv e-prints, page. *arXiv preprint arXiv:1609.05473*, 2016.

[60] Yu, Tianhe, Thomas, Garrett, Yu, Lantao, Ermon, Stefano, Zou, James, Levine, Sergey, Finn, Chelsea, and Ma, Tengyu. Mopo: Model-based offline policy optimization. In *Advances in Neural Information Processing Systems*, 2020.

[61] Zambaldi, Vinicius, Raposo, David, Santoro, Adam, Bapst, Victor, Li, Yujia, Babuschkin, Igor, Tuyls, Karl, Reichert, David, Lillicrap, Timothy, Lockhart, Edward, et al. Deep reinforcement learning with relational inductive biases. In *International Conference on Learning Representations*, 2018.

[62] Ziegler, Daniel M, Stiennon, Nisan, Wu, Jeffrey, Brown, Tom B, Radford, Alec, Amodei, Dario, Christiano, Paul, and Irving, Geoffrey. Fine-tuning language models from human preferences. *arXiv preprint arXiv:1909.08593*, 2019.