Variational Dynamic Mixtures

Abstract

Deep probabilistic time series forecasting models have become an integral part of machine learning. While several powerful generative models have been proposed, we provide evidence that their associated inference models are oftentimes too limited and cause the generative model to predict mode-averaged dynamics. Mode-averaging is problematic since many real-world sequences are highly multi-modal, and their averaged dynamics are unphysical (e.g., predicted taxi trajectories might run through buildings on the street map). To better capture multi-modality, we develop variational dynamic mixtures (VDM): a new variational family to infer sequential latent variables. The VDM approximate posterior at each time step is a mixture density network, whose parameters come from propagating multiple samples through a recurrent architecture. This results in an expressive multi-modal posterior approximation. In an empirical study, we show that VDM outperforms competing approaches on highly multi-modal datasets from different domains.

1 Introduction

Making sense of time series data is an important challenge in various domains, including ML for climate change. One important milestone to reach the climate goals is to significantly reduce the CO_2 emissions from mobility (Rogelj et al., 2016). Accurate forecasting models of typical driving behavior and of typical pollution levels over time can help both lawmakers and automotive engineers to develop solutions for cleaner mobility. In these applications, no accurate physical model of the entire dynamic system is known or available. Instead, data-driven models, specifically deep probabilistic time series models, can be used to solve the necessary tasks including forecasting.

The dynamics in such data can be highly multi-modal. At any given part of the observed sequence, there might be multiple distinct continuations of the data that are plausible, but the average of these behaviors is unlikely, or even physically impossible. Consider for example a dataset of taxi trajectories[1]. In each row of Fig. 1a, we have selected 50 routes from the dataset with similar starting behavior (blue). Even though these routes are quite similar to each other in the first 10 way points, the continuations of the trajectories (red) can exhibit quite distinct behaviors and lead to points on any far edge of the map. The trajectories follow a few main traffic arteries, these could be considered the main modes of the data distribution. We would like to learn a generative model of the data, that based on some initial way points, can forecast plausible continuations for the trajectories.

Many existing methods make restricting modeling assumptions such as Gaussianity to make learning tractable and efficient. But trying to capture the dynamics through unimodal distributions can lead either to "over-generalization", (i.e. putting probability mass in spurious regions) or on focusing only on the dominant mode and thereby neglecting important structure of the data. Even neural approaches, with very flexible generative models can fail to fully capture this multi-modality because their capacity is often limited through the assumptions of their *inference model*. To address this, we develop variational dynamic mixtures (VDM). Its generative process is a sequential latent variable model. The main novelty is a new multi-modal variational family which makes learning and inference multi-modal yet tractable. In summary, our contributions are

- **A new inference model.** We establish a new type of variational family for variational inference of sequential latent variables. By successively marginalizing over previous latent states, the procedure can be efficiently carried-out in a single forward pass and induces a multi-modal posterior

---

[1]https://www.kaggle.com/crailtap/taxi-trajectory

| (a) Taxi Data | (b) VDM (ours) | (c) AESMC | (d) CF-VAE | (e) VRNN | (f) RKN |

Figure 1: Forecasting taxi trajectories is challenging due to the highly multi-modal nature of the data (Fig. 1a). VDM (Fig. 1b) succeeds in generating diverse plausible predictions (red), based the beginning of a trajectory (blue). The other methods, AESMC (Le et al., 2018), CF-VAE (Bhattacharyya et al., 2019), VRNN Chung et al. (2015), RKN Becker et al. (2019), suffer from mode averaging.

approximation. We can see in Fig. 1b, that VDM trained on a dataset of taxi trajectories produces forecasts with the desired multi-modality while other methods overgeneralize.

- **An evaluation metric for multi-modal tasks.** The negative log-likelihood measures predictive accuracy but neglects an important aspect of multi-modal forecasts – sample diversity. In Section 4, we derive a score based on the Wasserstein distance (Villani, 2008) which evaluates both sample quality and diversity. This metric complements our evaluation based on log-likelihoods.
- **An extensive empirical study.** in Section 4, we use VDM to study various datasets, including a synthetic data with four modes, a stochastic Lorenz attractor, the taxi trajectories, and a U.S. pollution dataset with the measurements of various pollutants over time. We illustrate VDM's ability in modeling multi-modal dynamics, and provide quantitative comparisons to other methods showing that VDM compares favorably to previous work.

2 RELATED WORK

Neural recurrent models. Recurrent neural networks (RNNs) such as LSTMs (Hochreiter & Schmidhuber, 1997) and GRUs (Chung et al., 2014) have proven successful on many time series modeling tasks. However, as deterministic models they cannot capture uncertainties in their dynamic predictions. Stochastic RNNs make these sequence models non-deterministic (Chung et al., 2015; Fraccaro et al., 2016; Gemici et al., 2017; Li & Mandt, 2018). For example, the variational recurrent neural network (VRNN) (Chung et al., 2015) enables multiple stochastic forecasts due to its stochastic transition dynamics. This paper adopts a simplified version of the VRNN as a generative model (removing autoregressive feedback of observations), but improves its inference model to better capture multi-modality. Another line of related methods rely on particle filtering (Naesseth et al., 2018; Le et al., 2018; Hirt & Dellaportas, 2019) and in particular sequential Monte Carlo (SMC) to improve the evidence lower bound. In contrast, VDM adopts an explicitly multi-modal posterior approximation. Another SMC-based work (Saeedi et al., 2017) employs search-based techniques for multi-modality but is limited to models with finite discrete states. Recent works (Schmidt & Hofmann, 2018; Schmidt et al., 2019; Ziegler & Rush, 2019) use normalizing flows in the latent space to model the transition dynamics. A normalizing flow requires many layers to transform its base distribution into a truly multi-modal distribution in practice. In contrast, mixture density networks (as used by VDM) achieve multi-modality by mixing only one layer of neural networks.

Deep state-space models. Classical State-space models (SSMs) are popular due to their tractable inference and interpretable predictions. Similarly, *deep* SSMs with locally linear transition dynamics enjoy tractable inference (Karl et al., 2017; Fraccaro et al., 2017; Rangapuram et al., 2018; Becker et al., 2019). However, these models are often not expressive enough to capture complex (or highly multi-modal) dynamics. Nonlinear deep SSMs (Krishnan et al., 2017; Zheng et al., 2017; Doerr et al., 2018; De Brouwer et al., 2019; Gedon et al., 2020) are more flexible. Their inference is often no longer tractable and requires variational approximations. Unfortunately, in order for the inference model to be tractable, the variational approximations are often simplistic and don't approximate multi-modal posteriors well with negative effects on the trained models. Multi-modality

| (a) Generation (Eqs. (1) and (2)) | (b) Inference (Eqs. (3), (5) and (7)) |

Figure 2: Graphical illustrations of VDM. Thin lines denote deterministic dependencies such as transformations, marginalization, or computing the mean, as explained in the main text, while bold lines denote stochastic dependencies. The half-shaded node for s_t indicates that s_t is being marginalized out as opposed to conditioned on.

can be incorporated via additional discrete switching latent variables, such as recurrent switching linear dynamical systems (Linderman et al., 2017; Nassar et al., 2018; Becker-Ehmck et al., 2019). However, these discrete states make inference more involved.

Sequence forecasting. VAE-like models (Bhattacharyya et al., 2018; 2019) and GAN-like models (Sadeghian et al., 2019; Kosaraju et al., 2019) show good results on various tasks, including forecasting. Unlike VDM and other sequential models, such models have no temporal latent states and rather represent the trajectories in terms of time-independent latent variables. With a deterministic decoder, these models don't capture multi-modal dynamics and local details very well.

3 VARIATIONAL DYNAMIC MIXTURES

We develop VDM, a new sequential latent variable model for multi-modal dynamics. Given sequential observations $\mathbf{x}_{1:T} = (\mathbf{x}_1, \ldots, \mathbf{x}_T)$, VDM assumes that the underlying dynamics are governed by latent states $\mathbf{z}_{1:T} = (\mathbf{z}_1, \ldots, \mathbf{z}_T)$. We first present the generative process and the multi-modal inference model of VDM. We then derive a new variational objective that encourages multi-modal posterior approximations and we explain how it is regularized via hybrid-training. Finally, we introduce a new sampling method used in the inference procedure.

Generative model. The generative process consists of a transition model and an emission model. The transition model $p(\mathbf{z}_t \mid \mathbf{z}_{<t})$ describes the temporal evolution of the latent states and the emission model $p(\mathbf{x}_t \mid \mathbf{z}_{\leq t})$ maps the states to observations. We assume they are parameterized by two separate neural networks, the transition network ϕ^{tra} and the emission network ϕ^{dec}. To give the model the capacity to capture longer range temporal correlations we parametrize the transition model with a recurrent architecture ϕ^{GRU} (Auger-Méthé et al., 2016; Zheng et al., 2017) such as a GRU (Chung et al., 2014). The latent states $\mathbf{z}_t$ are sampled recursively from

$$\mathbf{z}_t \mid \mathbf{z}_{<t} \sim \mathcal{N}(\mu_{0,t}, \sigma_{0,t}^2 \mathbb{I}), \quad \text{where} \quad [\mu_{0,t}, \sigma_{0,t}^2] = \phi^{tra}(\mathbf{h}_{t-1}), \ \mathbf{h}_{t-1} = \phi^{\mathrm{GRU}}(\mathbf{z}_{t-1}, \mathbf{h}_{t-2}), \quad (1)$$

and are then decoded such that the observations can be sampled from the emission model,

$$\mathbf{x}_t \mid \mathbf{z}_{\leq t} \sim \mathcal{N}(\mu_{x,t}, \sigma_{x,t}^2 \mathbb{I}), \quad \text{where} \quad [\mu_{x,t}, \sigma_{x,t}^2] = \phi^{dec}(\mathbf{z}_t, \mathbf{h}_{t-1}). \quad (2)$$

This generative process is similar to (Chung et al., 2015), though we did not incorporate autoregressive feedback due to its negative impact on long-term generation (Ranzato et al., 2016; Lamb et al., 2016). The competitive advantage of VDM comes from a more expressive inference model.

Inference model. Our main contribution is the development of a variational posterior approximation for VDM that explicitly encourages multi-modality. It relies on maintaining a distribution over recurrent states of the RNN. For this we introduce the random variable s_t, with $\mathbf{h}_t = \mathbb{E}[\mathbf{s}_t]$. We will see that by including the distribution of recurrent states s_t in the variational model, we can efficiently marginalize the entire history of latent states. It also enables us to construct a posterior

approximation for each time step $q(\mathbf{z}_t \mid \mathbf{x}_{\leq t})$ that resembles a mixture density network (which is a convenient choice to model multi-modal distributions). We first define the variational distributions of the recurrent states, before discussing their role in the posterior approximation of VDM.

We choose the variational distribution of the recurrent state to factorize as $q(\mathbf{s}_{t-1} \mid \mathbf{x}_{\leq t}) = \omega(\mathbf{s}_{t-1}, \mathbf{x}_t)\tilde{q}(\mathbf{s}_{t-1} \mid \mathbf{x}_{<t})$. The choice of weighting function $\omega(\cdot)$ will be discussed later. The distribution $\tilde{q}(\mathbf{s}_{t-1} \mid \mathbf{x}_{<t})$ is parametrized as a transformation of the variational posterior $q(\mathbf{z}_{t-1} \mid \mathbf{x}_{<t})$,

$$\tilde{q}(\mathbf{s}_{t-1} \mid \mathbf{x}_{<t}) \propto \int \delta(\mathbf{s}_{t-1} - \phi^{\text{GRU}}(\mathbf{z}_{t-1}, \mathbf{h}_{t-2}))q(\mathbf{z}_{t-1} \mid \mathbf{x}_{<t})\mathrm{d}\mathbf{z}_{t-1}. \tag{3}$$

The Kronecker δ-function compares whether the stochastic variable $\mathbf{s}_{t-1}$ equals the deterministic output of the RNN ϕ^{GRU} (which has the same parameters as in the generative model). For VDM inference, we only need samples from Eq. (3), which are obtained by sampling from the posterior approximation $q(\mathbf{z}_{t-1} \mid \mathbf{x}_{<t})$ and feeding the samples through the RNN.

Maintaining these RNN state distributions allows us to infuse temporal structure into the posterior approximation of VDM, which we assume factorizes over time steps as follows:

$$q(\mathbf{z}_{1:T} \mid \mathbf{x}_{1:T}) = \prod_{t=1}^{T} q(\mathbf{z}_t \mid \mathbf{x}_{\leq t}) = \prod_{t=1}^{T} \int q(\mathbf{z}_t \mid \mathbf{s}_{t-1}, \mathbf{x}_t)q(\mathbf{s}_{t-1} \mid \mathbf{x}_{\leq t})\mathrm{d}\mathbf{s}_{t-1}. \tag{4}$$

While the factorization over time steps resembles the mean-field assumption, the temporal structure at each time step comes from marginalizing out recurrent states (which contain information about the history of the latent states). We assume $q(\mathbf{z}_t \mid \mathbf{s}_{t-1}, \mathbf{x}_t)$ to be Gaussian and use an inference network ϕ^{inf} to model the effect of the observation $\mathbf{x}_t$ and recurrent state $\mathbf{s}_{t-1}$ on the mean and variance of this distribution. We approximate the marginalization over recurrent states with k samples. By making the sampling-based marginalization part of our variational approximation, the variational distribution $q(\mathbf{z}_t \mid \mathbf{x}_{\leq t})$ becomes a mixture density network (Bishop, 2006),

$$q(\mathbf{z}_t \mid \mathbf{x}_{\leq t}) = \sum_{i}^{k} \omega_t^{(i)}\mathcal{N}(\mu_{z,t}^{(i)}, \sigma_{z,t}^{(i)2}\mathbb{I}), \ [\mu_{z,t}^{(i)}, \sigma_{z,t}^{(i)2}] = \phi^{inf}(\mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t), \ \mathbf{s}_{t-1}^{(i)} \sim \tilde{q}(\mathbf{s}_{t-1} \mid \mathbf{x}_{<t}). \tag{5}$$

The mixture weights $\omega_t^{(i)} := \omega(\mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t)/k$ come from the variational distribution $q(\mathbf{s}_{t-1} \mid \mathbf{x}_{\leq t}) = \omega(\mathbf{s}_{t-1}, \mathbf{x}_t)\tilde{q}(\mathbf{s}_{t-1} \mid \mathbf{x}_{<t})$. We are free to choose how to parametrize the weights, as long as all variational distributions are properly normalized. This can be achieved by setting

$$\omega_t^{(i)} = \omega(\mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t)/k := \mathbb{1}(i = \arg\max_{j} p(\mathbf{x}_t \mid \mathbf{s}_{t-1}^{(j)})). \tag{6}$$

In Appendix A, we explain the connection to importance sampling and in Appendix G, we compare the performance of VDM under alternative variational choices for the weights.

In the next time-step, plugging the variational distribution $q(\mathbf{z}_t \mid \mathbf{x}_{\leq t})$ into Eq. (3) yields the next distribution over recurrent states $q(\mathbf{s}_t \mid \mathbf{x}_{\leq t})$. For this, the expected recurrent state $\mathbf{h}_{t-1}$ is required. We approximate the update using the same k samples (and therefore the same weights) as in Eq. (5).

$$\mathbf{h}_{t-1} = \mathbb{E}[\mathbf{s}_{t-1}] = \int \mathbf{s}_{t-1}\, q(\mathbf{s}_{t-1} \mid \mathbf{x}_{\leq t})\mathrm{d}\mathbf{s}_{t-1} \approx \sum_{i}^{k} \omega_t^{(i)}\mathbf{s}_{t-1}^{(i)}. \tag{7}$$

A schematic view of the generative and inference model of VDM is shown in Fig. 2. In summary, the inference model of VDM alternates between Eqs. (3), (5) and (7). Latent states are sampled from the posterior approximation of the previous time-step and transformed by Eq. (3) into samples of the recurrent state of the RNN. These are then combined with the new observation $\mathbf{x}_t$ to produce the next variational posterior Eq. (5) and the expected recurrent state is updated (Eq. (7)). These are then used in Eq. (3) again. Approximating the marginalization in Eq. (4) with a single sample, recovers the inference model of VRNN (Chung et al., 2015), and fails in modeling multi-modal dynamics as shown in Fig. 3. In comparison, VDM's approximate marginalization over the recurrent states with multiple samples succeeds in modeling multi-modal dynamics.

Variational objective. We develop an objective to optimize the variational parameters of VDM $\phi = [\phi^{tra}, \phi^{dec}, \phi^{\text{GRU}}, \phi^{inf}]$. The evidence lower bound (ELBO) at each time step is

$$
\mathcal{L}_{\text{ELBO}}(\mathbf{x}_{\leq t}, \phi) := \frac{1}{k} \sum_i^k \omega(\mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t) \mathbb{E}_{q(\mathbf{z}_t | \mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t)} \left[\log p(\mathbf{x}_t \mid \mathbf{z}_t, \mathbf{s}_{t-1}^{(i)}) + \log \frac{p(\mathbf{z}_t \mid \mathbf{s}_{t-1}^{(i)})}{q(\mathbf{z}_t \mid \mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t)} \right]
$$
$$
- \frac{1}{k} \sum_i^k \omega(\mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t) \log \omega(\mathbf{s}_{t-1}^{(i)}, \mathbf{x}_t) \tag{8}
$$

Claim 1. *The ELBO in Eq. (8) is a lower bound on the log evidence* $\log p(\mathbf{x}_t \mid \mathbf{x}_{<t})$,

$$
\log p(\mathbf{x}_t \mid \mathbf{x}_{<t}) \geq \mathcal{L}_{\text{ELBO}}(\mathbf{x}_{\leq t}, \phi), \qquad \textit{(see proof in Appendix B)} . \tag{9}
$$

In addition to the ELBO, the objective of VDM has two regularization terms,

$$
\mathcal{L}_{\text{VDM}}(\phi) = \sum_{t=1}^T \mathbb{E}_{p_{\text{data}}} \left[-\mathcal{L}_{\text{ELBO}}(\mathbf{x}_{\leq t}, \phi) - \omega_1 \mathcal{L}_{pred}(\mathbf{x}_{\leq t}, \phi) \right] + \omega_2 \mathcal{L}_{adv}(\mathbf{x}_{\leq t}, \phi) . \tag{10}
$$

In an ablation study in Appendix D, we compare the effect of including and excluding the regularization terms in the objective. VDM is competitive without these terms, but we got the strongest results by setting $\omega_{1,2} = 1$ (this is the only nonzero value we tried. This hyperparameter could be tuned even further.) The first regularization term $\mathcal{L}_{pred}$, encourages the variational posterior (from the previous time step) to produce samples that maximize the predictive likelihood,

$$
\mathcal{L}_{pred}(\mathbf{x}_{\leq t}, \phi) = \log \mathbb{E}_{q(\mathbf{s}_{t-1} | \mathbf{x}_{<t})} \left[p(\mathbf{x}_t \mid \mathbf{s}_{t-1}, \mathbf{x}_{<t}) \right] \approx \log \frac{1}{k} \sum_i^k p(\mathbf{x}_t \mid \mathbf{s}_{t-1}^{(i)}) . \tag{11}
$$

This regularization term is helpful to improve the prediction performance, since it depends on the predictive likelihood of samples, which isn't involved in the ELBO. The second optional regularization term $\mathcal{L}_{adv}$ (Eq. (12)) is based on ideas from hybrid adversarial-likelihood training (Grover et al., 2018; Lucas et al., 2019). These training strategies have been developed for generative models of images to generate sharper samples while avoiding "mode collapse". We adapt these ideas to generative models of dynamics. The adversarial term $\mathcal{L}_{adv}$ uses a forward KL-divergence, which enables "quality-driven training" to discourage probability mass in spurious areas.

$$
\mathcal{L}_{adv}(\mathbf{x}_{\leq t}, \phi) = \mathcal{D}_{\text{KL}}(p(\mathbf{x}_t \mid \mathbf{x}_{<t}) \| p_{\mathcal{D}}(\mathbf{x}_t \mid \mathbf{x}_{<t})) = \mathbb{E} \left[\log p(\mathbf{x}_t \mid \mathbf{x}_{<t}) - \log p_{\mathcal{D}}(\mathbf{x}_t \mid \mathbf{x}_{<t}) \right] \tag{12}
$$

The expectation is taken w.r.t. $p(\mathbf{x}_t \mid \mathbf{x}_{<t})$. The true predictive distribution $p_{\mathcal{D}}(\mathbf{x}_t \mid \mathbf{x}_{<t})$ is unknown. Instead, we can train the generator of a conditional GAN (Mirza & Osindero, 2014), while assuming an optimal discriminator. As a result, we optimize Eq. (12) in an adversarial manner, conditioning on $\mathbf{x}_{<t}$ at each time step. Details about the discriminator are in Appendix F.

Stochastic cubature approximation (SCA). The variational family of VDM is defined by a number of modeling choices, including the factorization and marginal consistency assumptions of Eq. (4), the parametrization of the transition and inference networks Eqs. (3) and (5), and the choice of weighting function $\omega(\cdot)$. It is also sensitive to the choice of sampling method which we discuss here. In principle, we could use Monte-Carlo methods. However, for a relatively small number of samples k, Monte-Carlo methods don't have a mechanism to control the quality of samples. We instead develop a semi-stochastic approach based on the cubature approximation (Wan & Van Der Merwe, 2000; Wu et al., 2006; Arasaratnam & Haykin, 2009), which chooses samples more carefully. The cubature approximation proceeds by constructing $k = 2d + 1$ so-called simga points, which are optimally spread out on the d-dimensional Gaussian with the same mean and covariance as the distribution we need samples from. In SCA, the deterministic sigma points are infused with Gaussian noise to obtain stochastic *sigma variables*. A detailed derivation of SCA is in Appendix C.

We use SCA for various reasons: First, it typically requires fewer samples than Monte-Carlo methods because the sigma points are carefully chosen to capture the first two moments of the underlying distribution. Second, it ensures a persistence of the mixture components; when we resample, we sample another nearby point from the mixture component and not an entirely new location.

4 EVALUATION AND EXPERIMENTS

In this empirical study, we evaluate VDM's ability to model multi-modal dynamics and show its competitive forecasting performance in various domains. We first introduce the evaluation metrics and baselines. Experiments on synthetic data demonstrate that VDM is truly multi-modal thereby supporting the modeling choices of Section 3, especially for the inference model. Then, experiments on real-world datasets with challenging multi-modal dynamics show the benefit of VDM over state-of-the art (deep) probabilistic time-series models.

Evaluation metrics. In the experiments, we always create a training set, a validation set, and a test set. During validation and test, each trajectory is split into two parts; initial observations (given to the models for inference) and continuations of the trajectories (to be predicted and not accessible to the models). The inference models are used to process the initial observations and to infer latent states. These are then processed by the generative models to produce forecasts.

We use 3 criteria to evaluate these forecasts (i) multi-steps ahead prediction $p(\mathbf{x}_{t+1:t+\tau} \mid \mathbf{x}_{1:t})$, (ii) one-step-ahead prediction $p(\mathbf{x}_{t+1} \mid \mathbf{x}_{1:t})$, and (iii) empirical Wasserstein distance. As in other work (Lee et al., 2017; Bhattacharyya et al., 2018; 2019), (i) and (ii) are reported in terms of negative log-likelihood. While the predictive distribution for one-step-ahead prediction is in closed-form, the long-term forecasts have to be computed using samples. For each ground truth trajectory $\mathbf{x}$ we generate $n = 1000$ forecasts $\hat{\mathbf{x}}_i$ given initial observations from the beginning of the trajectory

$$NLL = -\log\left(\frac{1}{n}\sum_i^n \frac{1}{\sqrt{2\pi}}\exp\left(-\frac{(\hat{\mathbf{x}}_i - \mathbf{x})^2}{2}\right)\right),\tag{13}$$

This evaluates the predictive accuracy but neglects a key aspect of multi-modal forecasts – diversity.

We propose a new evaluation metric, which takes both diversity and accuracy of predictions into account. It relies on computing the Wasserstein distance between two empirical distributions P, Q

$$W(P,Q) = \inf_\pi\left(\frac{1}{n}\sum_i^n\|(\mathbf{x}_i - \mathbf{y}_{\pi(i)}\|_2\right),\tag{14}$$

where $\mathbf{x}$ and $\mathbf{y}$ are the discrete samples of P and Q, and π denotes all permutations (Villani, 2008). To use this as an evaluation measure for multi-modal forecasts, we do the following. We select n samples from the test set with similar initial observations. If the dynamics in the data are multi-modal the continuations of those n trajectories will be diverse and this should be reflected in the forecasts. For each of the n samples, the model generates 10 forecasts and we get n groups of samples. With Eq. (14) the empirical W-distance between the n true samples, and each group of generated samples can be calculated. The averaged empirical W-distance over groups evaluates how well the generated samples match the ground truth. Repeating this procedure with different initial trajectories evaluates the distance between the modeled distribution and the data distribution.

Baselines. We choose baselines from three classes of models. Two stochastic recurrent models are variational recurrent neural network (VRNN) (Chung et al., 2015) and auto-encoding sequential Monte Carlo (AESMC) (Le et al., 2018). VRNN has a similar but more powerful generative model than VDM, and AESMC uses SMC to achieve a tighter lower bound. But compared to VDM, both methods have a less powerful inference model which limits their capacity to capture multi-modal distributions. The third baseline is a deep SSM. The recurrent Kalman network (RKN) (Becker et al., 2019) models the latent space with a locally linear SSMs, which makes the prediction step and update step analytic (as for Kalman filters (Kalman, 1960)). A final baseline is the conditional flow variational autoencoder (CF-VAE) (Bhattacharyya et al., 2019), which uses conditional normalizing flows to model a global prior for the future continuations and achieves state-of-the-art performances.

To investigate the necessity of taking multiple samples in the VDM inference model, we also compared to VDM($k = 1$) which uses only a single sample in Eq. (5). VDM($k = 1$) has a simpler generative model than VRNN (it considers no autoregressive feedback of the observations $\mathbf{x}$), but the same inference model. More ablations for the modeling choices of VDM are in Appendix G.

For fair comparison, we fix the dimension of the latent variables $\mathbf{z}_t$ and $\mathbf{h}_t$ to be the same for VDM, AESMC, and VRNN which have the same resulting model size (except for the additional autoregressive feedback in VRNN). AESMC and VDM always use the same number of particles/samples.

VDM($k=9$)	VDM($k=1$)	AESMC($k=9$)

$\tilde{\mathbf{D}}$ $\quad p(\mathbf{z}_2|\mathbf{D})\ p(\mathbf{z}_2|\mathbf{x}_{\leq 1})$ $\qquad$ $\tilde{\mathbf{D}}$ $\quad p(\mathbf{z}_2|\mathbf{D})\ p(\mathbf{z}_2|\mathbf{x}_{\leq 1})$ $\qquad$ $\tilde{\mathbf{D}}$ $\quad p(\mathbf{z}_2|\mathbf{D})\ p(\mathbf{z}_2|\mathbf{x}_{\leq 1})$

Figure 3: **Experiments on 2-d synthetic data with 4 modes highlight the multi-modality of VDM.** We train VDM($k=9$) (left), VDM($k=1$) (middle), and AESMC($k=9$) (right) on a training set of trajectories $\mathbf{D}$ and plot generated trajectories $\tilde{\mathbf{D}}$ (two colors for the two dimensions). We also plot the aggregated posterior $p(\mathbf{z}_2|\mathbf{D})$, and the predictive prior $p(\mathbf{z}_2|\mathbf{x}_{\leq 1})$. Only VDM learns a multi-modal predictive prior, which explains its success in modeling multi-modal dynamics.

RKN does not have recurrent states, so we choose a higher latent dimension to make model size comparable. In contrast, CF-VAE has only one global latent variable which needs more capacity and we make it higher-dimensional than $\mathbf{z}_t$. Details for each experiment are in Appendix F.

Synthetic data with multi-modal dynamics We generate synthetic data with two dimensions and four modes and compare the performance of VDM with 9 samples (Fig. 3, left), VDM with a single sample (Fig. 3, middle), and AESMC using 9 particles (Fig. 3, right). Since variational inference is known to try to match the aggregated posterior with the predictive prior (Tomczak & Welling, 2018), it is instructive to fit all three models and to look at their predictive prior $p(\mathbf{z}_2|\mathbf{x}_{\leq 1})$ and the aggregated posterior $p(\mathbf{z}_2|\mathbf{D})$. Because of the multi-modal nature of the problem, all 3 aggregated posteriors are multi-modal, but only VDM($k=9$) learns a multi-modal predictive prior (thanks to its choice of variational family). Although AESMC achieves a good match between the prior and the aggregated posterior, the predictive prior does not clearly separate into different modes. In contrast, the inference model of VDM successfully uses the weights (Eq. (6)), which contain information about the incoming observation, to separate the latent states into separate modes.

Stochastic Lorenz attractor The Lorenz attractor is a system governed by ordinary differential equations. We add noise to the transition and emission function to make it stochastic (details in Appendix E.1). Under certain parameter settings it is chaotic – even small errors can cause considerable differences in the future. This makes forecasting its dynamics very challenging. All models

(a) True sample (b) VDM (ours) (c) AESMC (d) CF-VAE (e) VRNN (f) RKN

Figure 4: Generated samples from VDM and baselines for stochastic Lorenz attractor. The models generate the remaining 990 observations (blue) based on the first 10 observations (red). Due to the chaotic property, the reconstruction is impossible even the model learns the right dynamics. VDM and AESMC capture the dynamics very well, while RKN fails in capturing the stochastic dynamics.

Table 1: Prediction error on stochastic Lorenz attractor for three evaluation metrics (details in main text). VDM($k=13$) achieves the best performance, and AESMC also gives comparable results.

	RKN	VRNN	CF-VAE	AESMC	VDM($k=1$)	VDM($k=13$)
Multi-steps	104.41	65.89±0.21	32.41±0.13	25.01±0.22	25.03±0.28	**24.46**±0.12
One-step	1.88	-1.63	n.a	-1.69	-1.81	**-1.81**
W-distance	16.16	16.14±0.006	8.44±0.005	7.29±0.005	7.31±0.002	**7.28**±0.002

are trained and then tasked to predict 90 future observations given 10 initial observations. Fig. 4 illustrates qualitatively that VDM (Fig. 4b) and AESMC (Fig. 4c) succeed in modeling the chaotic dynamics of the stochastic Lorenz attractor, while CF-VAE (Fig. 4d) and VRNN (Fig. 4e) miss local details, and RKN (Fig. 4f) which lacks the capacity for stochastic transitions does not work at all. VDM achieves the best scores on all metrics (Table 1). Since the dynamics of the Lorenz attractor are governed by ordinary differential equations, the transition dynamics at each time step are not obviously multi-modal, which explains why all models with stochastic transitions do reasonably well. Next, we will show the advantages of VDM on real-world data with multi-modal dynamics.

Taxi trajectories The taxi trajectory dataset involves taxi trajectories with variable lengths in Porto, Portugal. Each trajectory is a sequence of two dimensional locations over time. Here, we cut the trajectories to a fixed length of 30 to simplify the comparison (details in Appendix E.2). The task is to predict the next 20 observations given 10 initial observations. Ideally, the forecasts should follow the street map (though the map is not accessible to the models). The results in Ta-

Table 2: Prediction error on taxi trajectories for three evaluation metrics (details in main text). CF-VAE gives the best result in multi-steps prediction, since it uses one global latent variable, while sequential models rely on a sequence of local latent variables. Meanwhile, VDM($k = 13$) outperforms all sequential models, and performs better in other metrics than CF-VAE.

	RKN	VRNN	CF-VAE	AESMC	VDM($k = 1$)	VDM($k = 13$)
Multi-steps	4.25	5.51±0.002	**2.77**±0.001	3.31±0.001	3.26±0.001	2.85±0.002
One-step	-2.90	-2.77	n.a	-2.87	-2.99	**-3.62**
W-distance	2.07	2.43±0.0002	0.76±0.0003	0.66±0.0004	0.69±0.0005	**0.56**±0.0005

ble 2 show that VDM outperforms the other *sequential* latent variable models in all evaluations. However, it turns out that for multi-step forecasting learning global structure is advantageous, and CF-VAE which is a global latent variable model, achieves the highest results. However, this value doesn't match the qualitative results in Fig. 1. Since CF-VAE has to encode the entire structure of the trajectory forcast into a single latent variable, its predictions seem to average over plausible continuations but are locally neither plausible nor accurate. In comparison, VDM and the other models involve a sequence of latent variables. As the forecasting progresses, the methods update their distribution over latest states, and the impact of the initial observations becomes weaker and weaker. As a result, local structure is captured more accurately. While the forecasts are plausible and can be highly diverse, they potentially evolve into other directions than the ground truth. For this reason, their multi-step prediction results are worse in terms of log-likelihood. That's why the empirical W-distance is useful to complement the evaluation of multi-modal tasks. It reflects that the forecasts of VDM are diverse and plausible.

U.S. pollution data In this experiment, we study VDM on the U.S. pollution dataset (details in Appendix E.3). The data is collected from counties in different states from 2000 to 2016. Each observation has 12 dimensions (mean, max value, and air quality index of NO2, O3, SO2, and O3). The goal is to predict monthly pollution values for the coming 18 months, given observations of the previous six months. We ignore the geographical location and time information to treat the development tendency of pollution in different counties and different times as i.i.d.. The unknown context information makes the dynamics multi-modal and challenging to predict accurately. Due

Table 3: Prediction error on U.S. pollution data for two evaluation metrics (details in main text). VDM makes the most accurate multi-step and one-step predictions.

	RKN	VRNN	CF-VAE	AESMC	VDM($k = 1$)	VDM($k = 17$)
Multi-steps	53.13	49.32±0.13	45.86±0.04	41.14±0.13	42.33±0.11	**36.72**±0.08
One-step	6.98	8.69	n.a	6.93	7.97	**6.05**

to the small size and high dimensionality of the dataset, there are not enough samples with very similar initial observations. Thus, we cannot evaluate empirical W-distance in this experiment. In multi-step predictions and one-step predictions, VDM outperforms the other methods.

5 CONCLUSION

We have presented variational dynamic mixtures (VDM), a sequential latent variable model for multi-modal dynamics. The main contribution is a new variational family. It propagates multiple samples through an RNN to parametrize the posterior approximation with a mixture density network. Additionally, we have introduced the empirical Wasserstein distance for the evaluation of multi-modal forecasting tasks, since it accounts for forecast accuracy and diversity. VDM succeeds in learning challenging multi-modal dynamics and outperforms existing work in various applications.

REFERENCES

Ienkaran Arasaratnam and Simon Haykin. Cubature kalman filters. *IEEE Transactions on automatic control*, 54(6):1254–1269, 2009.

Marie Auger-Méthé, Chris Field, Christoffer M Albertsen, Andrew E Derocher, Mark A Lewis, Ian D Jonsen, and Joanna Mills Flemming. State-space models dirty little secrets: even simple linear gaussian models can have estimation problems. *Scientific reports*, 6(1):1–10, 2016.

Philipp Becker, Harit Pandya, Gregor Gebhardt, Cheng Zhao, James Taylor, and Gerhard Neumann. Recurrent kalman networks: Factorized inference in high-dimensional deep feature spaces. In *Thirty-sixth International Conference on Machine Learning*, 2019.

Philip Becker-Ehmck, Jan Peters, and Patrick Van Der Smagt. Switching linear dynamics for variational bayes filtering. In *International Conference on Machine Learning*, pp. 553–562, 2019.

Apratim Bhattacharyya, Bernt Schiele, and Mario Fritz. Accurate and diverse sampling of sequences based on a best of many sample objective. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 8485–8493, 2018.

Apratim Bhattacharyya, Michael Hanselmann, Mario Fritz, Bernt Schiele, and Christoph-Nikolas Straehle. Conditional flow variational autoencoders for structured sequence prediction. *arXiv preprint arXiv:1908.09008*, 2019.

Christopher M Bishop. *Pattern recognition and machine learning*. springer, 2006.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

Junyoung Chung, Kyle Kastner, Laurent Dinh, Kratarth Goel, Aaron C Courville, and Yoshua Bengio. A recurrent latent variable model for sequential data. In *Advances in neural information processing systems*, pp. 2980–2988, 2015.

Edward De Brouwer, Jaak Simm, Adam Arany, and Yves Moreau. Gru-ode-bayes: Continuous modeling of sporadically-observed time series. In *Advances in Neural Information Processing Systems*, pp. 7377–7388, 2019.

Andreas Doerr, Christian Daniel, Martin Schiegg, Duy Nguyen-Tuong, Stefan Schaal, Marc Toussaint, and Sebastian Trimpe. Probabilistic recurrent state-space models. In *Thirty-fifth International Conference on Machine Learning*, 2018.

Marco Fraccaro, Søren Kaae Sønderby, Ulrich Paquet, and Ole Winther. Sequential neural models with stochastic layers. In *Advances in neural information processing systems*, pp. 2199–2207, 2016.

Marco Fraccaro, Simon Kamronn, Ulrich Paquet, and Ole Winther. A disentangled recognition and nonlinear dynamics model for unsupervised learning. In *Advances in Neural Information Processing Systems*, pp. 3601–3610, 2017.

Daniel Gedon, Niklas Wahlström, Thomas B Schön, and Lennart Ljung. Deep state space models for nonlinear system identification. *arXiv preprint arXiv:2003.14162*, 2020.

Mevlana Gemici, Chia-Chun Hung, Adam Santoro, Greg Wayne, Shakir Mohamed, Danilo J Rezende, David Amos, and Timothy Lillicrap. Generative temporal models with memory. *arXiv preprint arXiv:1702.04649*, 2017.

Aditya Grover, Manik Dhar, and Stefano Ermon. Flow-gan: Combining maximum likelihood and adversarial learning in generative models. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Marcel Hirt and Petros Dellaportas. Scalable bayesian learning for state space models using variational inference with smc samplers. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 76–86, 2019.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8): 1735–1780, 1997.

Rudolph Emil Kalman. A new approach to linear filtering and prediction problems. 1960.

Maximilian Karl, Maximilian Soelch, Justin Bayer, and Patrick Van der Smagt. Deep variational bayes filters: Unsupervised learning of state space models from raw data. In *5th International Conference on Learning Representations*, 2017.

Vineet Kosaraju, Amir Sadeghian, Roberto Martín-Martín, Ian Reid, Hamid Rezatofighi, and Silvio Savarese. Social-bigat: Multimodal trajectory forecasting using bicycle-gan and graph attention networks. In *Advances in Neural Information Processing Systems*, pp. 137–146, 2019.

Rahul G Krishnan, Uri Shalit, and David Sontag. Structured inference networks for nonlinear state space models. In *Thirty-first aaai conference on artificial intelligence*, 2017.

Alex M Lamb, Anirudh Goyal Alias Parth Goyal, Ying Zhang, Saizheng Zhang, Aaron C Courville, and Yoshua Bengio. Professor forcing: A new algorithm for training recurrent networks. In *Advances In Neural Information Processing Systems*, pp. 4601–4609, 2016.

Tuan Anh Le, Maximilian Igl, Tom Rainforth, Tom Jin, and Frank Wood. Auto-encoding sequential monte carlo. In *International Conference on Learning Representations*, 2018.

Namhoon Lee, Wongun Choi, Paul Vernaza, Christopher B Choy, Philip HS Torr, and Manmohan Chandraker. Desire: Distant future prediction in dynamic scenes with interacting agents. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 336–345, 2017.

Yingzhen Li and Stephan Mandt. Disentangled sequential autoencoder. In *Thirty-fifth International Conference on Machine Learning*, 2018.

Scott Linderman, Matthew Johnson, Andrew Miller, Ryan Adams, David Blei, and Liam Paninski. Bayesian learning and inference in recurrent switching linear dynamical systems. In *Artificial Intelligence and Statistics*, pp. 914–922, 2017.

Thomas Lucas, Konstantin Shmelkov, Karteek Alahari, Cordelia Schmid, and Jakob Verbeek. Adaptive density estimation for generative models. In *Advances in Neural Information Processing Systems*, pp. 11993–12003, 2019.

Mehdi Mirza and Simon Osindero. Conditional generative adversarial nets. *arXiv preprint arXiv:1411.1784*, 2014.

Christian Naesseth, Scott Linderman, Rajesh Ranganath, and David Blei. Variational sequential monte carlo. In *International Conference on Artificial Intelligence and Statistics*, pp. 968–977. PMLR, 2018.

Josue Nassar, Scott Linderman, Monica Bugallo, and Il Memming Park. Tree-structured recurrent switching linear dynamical systems for multi-scale modeling. In *International Conference on Learning Representations*, 2018.

Syama Sundar Rangapuram, Matthias W Seeger, Jan Gasthaus, Lorenzo Stella, Yuyang Wang, and Tim Januschowski. Deep state space models for time series forecasting. In *Advances in neural information processing systems*, pp. 7785–7794, 2018.

Marc'Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. Sequence level training with recurrent neural networks. In *4th International Conference on Learning Representations*, 2016.

Joeri Rogelj, Michel Den Elzen, Niklas Höhne, Taryn Fransen, Hanna Fekete, Harald Winkler, Roberto Schaeffer, Fu Sha, Keywan Riahi, and Malte Meinshausen. Paris agreement climate proposals need a boost to keep warming well below 2 c. *Nature*, 534(7609):631–639, 2016.

Amir Sadeghian, Vineet Kosaraju, Ali Sadeghian, Noriaki Hirose, Hamid Rezatofighi, and Silvio Savarese. Sophie: An attentive gan for predicting paths compliant to social and physical constraints. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 1349–1358, 2019.

Ardavan Saeedi, Tejas D Kulkarni, Vikash K Mansinghka, and Samuel J Gershman. Variational particle approximations. *The Journal of Machine Learning Research*, 18(1):2328–2356, 2017.

Florian Schmidt and Thomas Hofmann. Deep state space models for unconditional word generation. In *Advances in Neural Information Processing Systems*, pp. 6158–6168, 2018.

Florian Schmidt, Stephan Mandt, and Thomas Hofmann. Autoregressive text generation beyond feedback loops. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3391–3397, 2019.

Jakub M Tomczak and Max Welling. Vae with a vampprior. In *21st International Conference on Artifi-cial Intelligence and Statistics*, 2018.

Cédric Villani. *Optimal transport: old and new*, volume 338. Springer Science & Business Media, 2008.

Eric A Wan and Rudolph Van Der Merwe. The unscented kalman filter for nonlinear estimation. In *Proceedings of the IEEE 2000 Adaptive Systems for Signal Processing, Communications, and Control Symposium (Cat. No. 00EX373)*, pp. 153–158. Ieee, 2000.

Yuanxin Wu, Dewen Hu, Meiping Wu, and Xiaoping Hu. A numerical-integration perspective on gaussian filters. *IEEE Transactions on Signal Processing*, 54(8):2910–2921, 2006.

Xun Zheng, Manzil Zaheer, Amr Ahmed, Yuan Wang, Eric P Xing, and Alexander J Smola. State space lstm models with particle mcmc inference. *arXiv preprint arXiv:1711.11179*, 2017.

Zachary M Ziegler and Alexander M Rush. Latent normalizing flows for discrete sequences. In *Thirty-sixth International Conference on Machine Learning*, 2019.