MIRROR DESCENT POLICY OPTIMIZATION

ABSTRACT

Mirror descent (MD), a well-known first-order method in constrained convex optimization, has recently been shown as an important tool to analyze trust-region algorithms in reinforcement learning (RL). However, there remains a considerable gap between such theoretically analyzed algorithms and the ones used in practice. Inspired by this, we propose an efficient RL algorithm, called *mirror descent policy optimization* (MDPO). MDPO iteratively updates the policy by *approximately* solving a trust-region problem, whose objective function consists of two terms: a linearization of the standard RL objective and a proximity term that restricts two consecutive policies to be close to each other. Each update performs this approximation by taking multiple gradient steps on this objective function. We derive *on-policy* and *off-policy* variants of MDPO, while emphasizing important design choices motivated by the existing theory of MD in RL. We highlight the connections between on-policy MDPO and two popular trust-region RL algorithms: TRPO and PPO, and show that explicitly enforcing the trust-region constraint is in fact *not* a necessity for high performance gains in TRPO. We then show how the popular soft actor-critic (SAC) algorithm can be derived by slight modifications of off-policy MDPO. Overall, MDPO is derived from the MD principles, offers a unified approach to viewing a number of popular RL algorithms, and performs better than or on-par with TRPO, PPO, and SAC in a number of continuous and discrete control tasks.

1 INTRODUCTION

An important class of RL algorithms consider an additional objective in their policy optimization that aims at constraining the consecutive policies to remain close to each other. These algorithms are referred to as *trust region* or *proximity-based*, resonating the fact that they make the new policy to lie within a trust-region around the old one. This class includes the theoretically grounded conservative policy iteration (CPI) algorithm [14], as well as the state-of-the-art deep RL algorithms, such as trust-region policy optimization (TRPO) [25] and proximal policy optimization (PPO) [27]. The main difference between these algorithms is in the way that they enforce the trust-region constraint. TRPO enforces it explicitly through a line-search procedure that ensures the new policy is selected such that its KL-divergence with the old policy is below a certain threshold. PPO takes a more relaxed approach and updates its policies by solving an unconstrained optimization problem in which the ratio of the new to old policies is clipped to remain bounded. It has been shown that this procedure does not prevent the policy ratios to go out of bound, and only reduces its probability [30, 8].

Mirror descent (MD) [5, 3] is a first-order optimization method for solving constrained convex problems. Although MD is theoretically well-understood in optimization [2, 13], only recently, has it been investigated for policy optimization in RL [24, 11, 19, 28]. Despite the progress made by these results in establishing connections between MD and trust-region policy optimization, there are still considerable gaps between the trust-region RL algorithms that have been theoretically analyzed in their *tabular* form [28] and those that are used in practice, such as TRPO and PPO.

In this paper, motivated by the theory of MD in *tabular* RL, our goal is to derive scaleable and practical RL algorithms from the MD principles, and to use the MD theory to better understand and explain the popular trust-region policy optimization methods. Going beyond the tabular case, when the policy belongs to a parametric class, the trust-region problems for policy update in RL cannot be solved in closed-form. We propose an algorithm, called **mirror descent policy optimization** (MDPO), that addresses this issue by *approximately* solving these trust-region problems via taking **multiple gradient steps** on their objective functions. We derive *on-policy* and *off-policy* variants of MDPO (Section 4). We highlight the connection between on-policy MDPO and TRPO and PPO (Section 4.1), and empirically compare it against these algorithms on several continuous control tasks

from OpenAI Gym [6] (Section 5.3). We then show that if we define the trust-region w.r.t. the *uniform policy*, instead of the old one, our off-policy MDPO coincides with the popular soft actor-critic (SAC) algorithm [12]. We discuss this connection in detail (Section 4.2) and empirically compare these algorithms using the same set of continuous control problems (Section 5.4).

Our observations on the comparison between the MDPO algorithms and TRPO, PPO, and SAC are a result of extensive empirical studies on different versions of these algorithms (Section 5 and Appendices E and F). In particular, we first compare the vanilla versions of these algorithms in order to better understand how the core of these methods work relative to each other. We then add a number of code-level optimization techniques derived from the code-bases of TRPO, PPO, and SAC to these algorithms to compare their best form (those that obtain the best results reported in the literature) against each other, while also evaluating MDPO with PPO on 21 Atari games. We address the common belief within the community that explicitly

Figure 1: **Overall Comparison**. Between MDPO, PPO, and TRPO, MDPO provides the best trade-off in terms of best average performance, less (normalized) wall clock times, and least number of algorithm specific hyper parameters used.

enforcing the trust-region constraint is a necessity for good performance in TRPO, by showing that MDPO, a trust-region method based on the MD principles, does not require enforcing a hard constraint and achieves strong performance by solely solving an unconstrained problem. We address another common belief that PPO is a better performing algorithm than TRPO. By reporting results of both the vanilla version and the version loaded with code-level optimization techniques for all algorithms, we show that in both cases, TRPO consistently outperforms PPO. This is in line with some of the findings from a recent study on PPO and TRPO [8]. Finally, we provide an optimization perspective for SAC, instead of its initial motivation as an entropy-regularized *(soft)* approximate dynamic programming algorithm. Through comprehensive experiments, we show that on-policy and off-policy MDPO achieve state-of-the-art performance across a number of benchmark tasks, and can be excellent alternatives to popular policy optimization algorithms, such as TRPO, PPO, and SAC.

2 PRELIMINARIES

In this paper, we assume that the agent's interaction with the environment is modeled as a γ-discounted Markov decision process (MDP), denoted by $\mathcal{M} = (\mathcal{S}, \mathcal{A}, P, R, \gamma, \mu)$, where $\mathcal{S}$ and $\mathcal{A}$ are the state and action spaces; $P \equiv P(s'|s, a)$ is the transition kernel; $R \equiv r(s, a)$ is the reward function; $\gamma \in (0, 1)$ is the discount factor; and μ is the initial state distribution. Let $\pi : \mathcal{S} \to \Delta_{\mathcal{A}}$ be a stationary Markovian policy, where $\Delta_{\mathcal{A}}$ is the set of probability distributions on $\mathcal{A}$. The discounted frequency of visiting a state s by following a policy π is defined as $\rho_\pi(s) \equiv (1-\gamma)\mathbb{E}[\sum_{t\geq0} \gamma^t \mathbb{I}\{s_t = s\}|\mu, \pi]$. The value function of a policy π at a state $s \in \mathcal{S}$ is defined as $V^\pi(s) \equiv \mathbb{E}[\sum_{t\geq0} \gamma^t r(s_t, a_t)|s_0 = s, \pi]$. Similarly, the action-value function of π is defined as $Q^\pi(s, a) = \mathbb{E}[\sum_{t\geq0} \gamma^t r(s_t, a_t)|s_0 = s, a_0 = a, \pi]$. The difference between the action-value Q and value V functions is referred to as the advantage function $A^\pi(s, a) = Q^\pi(s, a) - V^\pi(s)$.

Since finding an optimal policy for an MDP involves solving a non-linear system of equations and the optimal policy may be deterministic (less explorative), many researchers have proposed to add a regularizer in the form of an entropy term to the reward function, and then solve the entropy-regularized (or *soft*) MDP (e.g., [15, 29, 24]). In this formulation, the reward function is modified as $r_\lambda(s, a) = r(s, a) + \lambda H(\pi(\cdot|s))$, where λ is the regularization parameter and H is an entropy-related term, such as Shannon entropy [9, 22], Tsallis entropy [16, 23], or relative entropy [1, 21]. Setting $\lambda = 0$, we return to the original formulation, also referred to as the *hard* MDP. In what follows, we use the terms 'regularized' and 'soft' interchangeably.

2.1 MIRROR DESCENT IN CONVEX OPTIMIZATION

Mirror Descent (MD) [3] is a first-order trust-region optimization method for solving constrained convex problems, i.e., $x^* \in \arg\min_{x \in C} f(x)$, where f is a convex function and the constraint set C is convex compact. In each iteration, MD minimizes a sum of two terms: **1)** a linear approximation

of the objective function f at the previous estimate x_k, and **2)** a proximity term that measures the distance between the updated x_{k+1} and current x_k estimates. MD is considered a trust-region method, since the proximity term keeps the updates x_k and x_{k+1} close to each other. We may write the MD update as

$$x_{k+1} \in \arg\min_{x \in C} \ \langle \nabla f(x_k), x - x_k \rangle + \frac{1}{t_k} B_\psi(x, x_k), \tag{1}$$

where $B_\psi(x, x_k) := \psi(x) - \psi(x_k) - \langle \nabla\psi(x_k), x - x_k \rangle$ is the Bregman divergence associated with a strongly convex *potential* function ψ, and t_k is a step-size determined by the MD analysis. When $\psi = \frac{1}{2}\|\cdot\|_2^2$, the Bergman divergence is the Euclidean distance $B_\psi(x, x_k) = \frac{1}{2}\|x - x_k\|_2^2$, and (1) becomes the *projected gradient descent* algorithm [2]. When ψ is the negative Shannon entropy, the Bregman divergence term takes the form of the KL divergence, i.e., $B_\psi(x, x_k) = \text{KL}(x, x_k)$. In this case, when the constraint set C is the unit simplex, $C = \Delta_{\mathcal{X}}$, MD becomes the *exponentiated gradient descent* algorithm and (1) has the following closed form [3]:

$$x_{k+1}^i = \frac{x_k^i \exp\big(-t_k \nabla_i f(x_k)\big)}{\sum_{j=1}^n x_k^j \exp\big(-t_k \nabla_j f(x_k)\big)}, \tag{2}$$

where x_k^i and $\nabla_i f$ are the i^{th} coordinates of x_k and ∇f.

3 MIRROR DESCENT IN RL

The goal in RL is to find an optimal policy π^*. Two common notions of optimality, and as a result, two distinct ways to formulate RL as an optimization problem are as follows:

$$\textbf{(a)} \quad \pi^*(\cdot|s) \in \arg\max_{\pi} \ V^\pi(s), \ \ \forall s \in \mathcal{S}, \qquad \textbf{(b)} \quad \pi^* \in \arg\max_{\pi} \ \mathbb{E}_{s \sim \mu}\big[V^\pi(s)\big]. \tag{3}$$

In (3a), the value function is optimized over the entire state space $\mathcal{S}$. This formulation is mainly used in value function based RL algorithms. On the other hand, the formulation in (3b) is more common in policy optimization, where a scalar that is the value function at the initial state ($s \sim \mu$) is optimized.

Unlike the MD optimization problem, the objective function is not convex in π in either of the above two RL optimization problems. Despite this issue, [11] and [28] have shown that we can still use the general MD update rule (1) and derive MD-style RL algorithms with the update rules

$$\pi_{k+1}(\cdot|s) \leftarrow \arg\max_{\pi \in \Pi} \ \mathbb{E}_{a \sim \pi}\big[A^{\pi_k}(s,a)\big] - \frac{1}{t_k}\text{KL}(s; \pi, \pi_k), \quad \forall s \in \mathcal{S}, \tag{4}$$

$$\pi_{k+1} \leftarrow \arg\max_{\pi \in \Pi} \ \mathbb{E}_{s \sim \rho_{\pi_k}}\Big[\mathbb{E}_{a \sim \pi}\big[A^{\pi_k}(s,a)\big] - \frac{1}{t_k}\text{KL}(s; \pi, \pi_k)\Big], \tag{5}$$

for the optimization problems (3a) and (3b), respectively. Note that while in (4), the policy is optimized uniformly over the state space $\mathcal{S}$, in (5), it is optimized over the measure ρ_{π_k}, i.e., the state frequency induced by the current policy π_k.

4 MIRROR DESCENT POLICY OPTIMIZATION

In this section, we derive *on-policy* and *off-policy* RL algorithms based on the MD-style update rules (4) and (5). We refer to our algorithms as *mirror descent policy optimization* (MDPO). Since the trust-region optimization problems in the update rules (4) and (5) cannot be solved in closed-form, we approximate these updates with multiple steps of stochastic gradient descent (SGD) on the objective functions of these optimization problems. In our *on-policy* MDPO algorithm, described in Section 4.1, we use the update rule (5) and compute the SGD updates using the Monte-Carlo (MC) estimate of the advantage function A^{π_k} gathered by following the current policy π_k. On the other hand, our *off-policy* MDPO algorithm, described in Section 4.2, is based on the update rule (4) and calculates the SGD update by estimating A^{π_k} using samples from a replay buffer.

In our MDPO algorithms, we define the policy space, Π, as a class of smoothly parameterized stochastic polices, i.e., $\Pi = \{\pi(\cdot|s; \theta) : s \in \mathcal{S}, \theta \in \Theta\}$. We refer to θ as the policy parameter. We will use π and θ to represent a policy, and Π and Θ to represent the policy space, interchangeably.

4.1 ON-POLICY MDPO

In this section, we derive an on-policy RL algorithm based on the MD-based update rule (5), whose pseudo-code is shown in Algorithm 1 in Appendix A. We refer to this algorithm as *on-policy* MDPO. We may write the update rule (5) for the policy space Θ (defined above) as

$$\theta_{k+1} \leftarrow \arg\max_{\theta \in \Theta} \Psi(\theta, \theta_k), \quad \text{where} \quad \Psi(\theta, \theta_k) = \mathbb{E}_{s \sim \rho_{\theta_k}} \left[\mathbb{E}_{a \sim \pi_\theta} \left[A^{\theta_k}(s, a) \right] - \frac{1}{t_k} \text{KL}(s; \pi_\theta, \pi_{\theta_k}) \right]. \quad (6)$$

Each policy update in (6) requires solving a constrained (over Θ) optimization problem. In on-policy MDPO, instead of solving this problem, we update the policy by performing multiple SGD steps on the objective function $\Psi(\theta, \theta_k)$. Interestingly, performing only a single SGD step on $\Psi(\theta, \theta_k)$ is not sufficient as $\nabla_\theta \text{KL}(\cdot; \pi_\theta, \pi_{\theta_k})|_{\theta=\theta_k} = 0$, and thus, if we perform a single-step SGD, i.e.,

$$\nabla_\theta \Psi(\theta, \theta_k)|_{\theta=\theta_k} = \mathbb{E}_{\substack{s \sim \rho_{\theta_k} \\ a \sim \pi_\theta}} \left[\nabla \log \pi_{\theta_k}(a|s) A^{\theta_k}(s, a) \right],$$

the resulting algorithm would be equivalent to *vanilla policy gradient* and misses the entire purpose of enforcing the trust-region constraint. As a result, the policy update at each iteration k of on-policy MDPO involves m SGD steps as

$$\theta_k^{(0)} = \theta_k, \qquad \text{for} \quad i = 0, \dots, m-1, \qquad \theta_k^{(i+1)} \leftarrow \theta_k^{(i)} + \eta \nabla_\theta \Psi(\theta, \theta_k)|_{\theta=\theta_k^{(i)}}, \qquad \theta_{k+1} = \theta_k^{(m)},$$

where the gradient of the objective function

$$\nabla_\theta \Psi(\theta, \theta_k)|_{\theta=\theta_k^{(i)}} = \mathbb{E}_{\substack{s \sim \rho_{\theta_k} \\ a \sim \pi_{\theta_k}}} \left[\frac{\pi_{\theta_k}^{(i)}}{\pi_{\theta_k}} \nabla \log \pi_{\theta_k^{(i)}}(a|s) A^{\theta_k}(s, a) \right] - \frac{1}{t_k} \mathbb{E}_{s \sim \rho_{\theta_k}} \left[\nabla_\theta \text{KL}(s; \pi_\theta, \pi_{\theta_k})|_{\theta=\theta_k^{(i)}} \right] \quad (7)$$

can be estimated in an *on-policy* fashion using the data generated by the current policy π_{θ_k}. Since in practice, the policy space is often selected as Gaussian, we use the closed-form of KL in this estimation. Our on-policy MDPO algorithm (Algorithm 1, Appendix A) has close connections to two popular on-policy trust-region RL algorithms: TRPO [25] and PPO [27]. We now discuss the similarities and differences between on-policy MDPO and these algorithms.

Comparison with TRPO. At each iteration k, TRPO considers the constrained optimization problem

$$\max_{\theta \in \Theta} \mathbb{E}_{\substack{s \sim \rho_{\theta_k} \\ a \sim \pi_{\theta_k}}} \left[\frac{\pi_\theta(a|s)}{\pi_{\theta_k}(a|s)} A^{\theta_k}(s, a) \right], \quad \text{s.t.} \quad \mathbb{E}_{s \sim \rho_{\theta_k}} \left[\text{KL}(s; \pi_{\theta_k}, \pi_\theta) \right] \leq \delta, \quad (8)$$

and updates its policy parameter by taking a step in the direction of the *natural gradient* of the objective function in (8) as $\theta_{k+1} \leftarrow \theta_k + \eta F^{-1} \mathbb{E}_{\substack{s \sim \rho_{\theta_k} \\ a \sim \pi_{\theta_k}}} \left[\nabla \log \pi_{\theta_k}(a|s) A^{\theta_k}(s, a) \right]$, where $F = \mathbb{E}_{\substack{s \sim \rho_{\theta_k} \\ a \sim \pi_{\theta_k}}} \left[\nabla \log \pi_{\theta_k}(a|s) \nabla \log \pi_{\theta_k}(a|s)^\top \right]$ is the *Fisher information matrix* for the current policy π_{θ_k}. It then explicitly enforces the trust-region constraint in (8) by a *line-search*: computing the KL-term for $\theta = \theta_{k+1}$ and checking if it is larger than the threshold δ, in which case, the step size is reduced until the constraint is satisfied.

In comparison to TRPO, **first,** on-policy MDPO does not explicitly enforce the trust-region constraint, but approximately satisfies it by performing multiple steps of SGD on the objective function of the optimization problem in the MD-style update rule (6). We say "*it approximately satisfies the constraint*" because instead of fully solving (6), it takes multiple steps in the direction of the gradient of its objective function. **Second,** on-policy MDPO uses simple SGD instead of natural gradient, and thus, does not have to deal with the computational overhead of computing (or approximating) the inverse of the Fisher information matrix.[1] **Third,** the direction of KL in on-policy MDPO, $\text{KL}(\pi, \pi_k)$, is consistent with that in the MD update rule in convex optimization and is different than that in TRPO, $\text{KL}(\pi_k, \pi)$. This does not cause any sampling problem for either algorithm, as both calculate the KL-term in closed-form (Gaussian policies). **Fourth,** while TRPO uses heuristics to define the step-size and to reduce it in case the trust-region constraint is violated, on-policy MDPO uses a simple schedule, motivated by the theory of MD [3], and sets $t_k = 1 - k/K$, where K is the maximum number of iterations. This way it anneals the step-size t_k from 1 to 0 over the iterations of the algorithm.

---

[1]TRPO does not explicitly invert F, but instead, approximates the natural gradient update using conjugate gradient descent.

Comparison with PPO. At each iteration k, PPO performs multiple steps of SGD on the objective function of the following unconstrained optimization problem:

$$\max_{\theta \in \Theta} \mathbb{E}_{\substack{s \sim \rho_{\theta_k} \\ a \sim \pi_{\theta_k}}} \left[\min \left\{ \frac{\pi_\theta(a|s)}{\pi_{\theta_k}(a|s)} A^{\theta_k}(s,a), \text{clip}\left(\frac{\pi_\theta(a|s)}{\pi_{\theta_k}(a|s)}, 1-\epsilon, 1+\epsilon \right) A^{\theta_k}(s,a) \right\} \right], \quad (9)$$

in which the hyper-parameter ϵ determines how the policy ratio, $\pi_\theta/\pi_{\theta_k}$, is clipped. It is easy to see that the gradient of the objective function in (9) is zero for the state-action pairs at which the policy ratio is clipped and is non-zero, otherwise. However, since the gradient is averaged over all the state-action pairs in the batch, the policy is updated even if its ratio is out of bound for some state-action pairs. This phenomenon, which has been reported in [30] and [8], shows that clipping in PPO does not prevent the policy ratios to go out of bound, but it only reduces its probability. This means that despite using clipping, PPO does not guarantee that the trust-region constraint is always satisfied. In fact, recent results, including those in [8] and our experiments in Section 5.3, show that most of the improved performance exhibited by PPO is due to code-level optimization techniques, such as learning rate annealing, observation and reward normalization, and in particular, the use of generalized advantage estimation (GAE) [26]. Although both on-policy MDPO and PPO take multiple SGD steps on the objective function of unconstrained optimization problems (6) and (9), respectively, the way they handle the trust-region constraint is completely different.

Another interesting observation is that the adaptive and fixed KL algorithms (we refer to as KL-PPO here), proposed in the PPO paper [27], have policy update rules similar to on-policy MDPO. However, these algorithms have not been used much in practice, because it was shown in the same paper that they perform much worse than PPO. Despite the similarities, there are three main differences between the update rules of KL-PPO and on-policy MDPO. **First,** KL-PPO uses mini-batches whereas MDPO uses the entire data for their multiple (m) gradient updates at each round. **Second,** the scheduling scheme used for the t_k parameter is quite different in KL-PPO and MDPO. In particular, KL-PPO either uses a fixed t_k or defines an adaptive scheme that updates (increase/decrease) t_k based on the KL divergence magnitude at that time step. On the other hand, on-policy MDPO uses an annealed schedule to update t_k, starting from 1 and slowly bringing it down to near 0. **Third,** similar to TRPO, the direction of KL in KL-PPO, $\text{KL}(\pi_k, \pi)$, is different than that in on-policy MDPO, $\text{KL}(\pi, \pi_k)$. Since in our experiments, on-policy MDPO performs significantly better than PPO (see Section 5.3), we conjecture that either any or a combination of the above differences, especially the first two, is the reason for the inferior performance of KL-PPO, compared to PPO, as reported in [27].

4.2 OFF-POLICY MDPO

In this section, we derive an off-policy RL algorithm based on the MD update rule (4). We refer to this as *off-policy* MDPO and provide the pseudo-code in Algorithm 2 in Appendix A. To emulate the uniform sampling over the state space required by (4), Algorithm 2 samples a batch of states from a replay buffer $\mathcal{D}$ (Line 4). While this sampling scheme is not truly uniform, it makes the update less dependent on the current policy. Similar to the on-policy case, we write the update rule (4) for the policy class Θ as

$$\theta_{k+1} \leftarrow \operatorname*{arg\,max}_{\theta \in \Theta} \Psi(\theta, \theta_k), \quad \text{where} \quad \Psi(\theta, \theta_k) = \mathbb{E}_{s \sim \mathcal{D}} \left[\mathbb{E}_{a \sim \pi_\theta} \left[A^{\theta_k}(s,a) \right] - \frac{1}{t_k} \text{KL}(s; \pi_\theta, \pi_{\theta_k}) \right]. \quad (10)$$

The main idea in Algorithm 2 is to estimate the advantage or action-value function of the current policy, A^{θ_k} or Q^{θ_k}, in an off-policy fashion, using a batch of data randomly sampled from the replay buffer $\mathcal{D}$. In a similar manner to the policy update of our on-policy MDPO algorithm (Algorithm 1), described in Section 4.1, we then update the policy by taking multiple SGD steps on the objective function $\Psi(\theta, \theta_k)$ of the optimization problem (10) (by keeping θ_k fixed). Algorithm 2 uses two neural networks V_ϕ and Q_ψ to estimate the value and action-value functions of the current policy. It then uses them to estimate the advantage function, i.e., $A^{\theta_k} \approx Q_\psi^{\theta_k} - V_\phi^{\theta_k}$. The Q_ψ update is done in a TD(0) fashion, while the V_ϕ update involves fitting the value function to the Q_ψ estimate of the current policy. For policy update, Algorithm 2 uses the reparameterization trick and replaces the objective function Ψ in (10) with the following loss:

$$L(\theta, \theta_k) = \mathbb{E}_{\substack{s \sim \mathcal{D} \\ \epsilon \sim \mathcal{N}}} \left[\log \pi_\theta \left(\widetilde{a}_\theta(\epsilon, s)|s \right) - \log \pi_{\theta_k} \left(\widetilde{a}_\theta(\epsilon, s)|s \right) - t_k Q_\psi^{\theta_k} \left(s, \widetilde{a}_\theta(\epsilon, s) \right) \right], \quad (11)$$

where $\widetilde{a}_\theta(\epsilon, s)$ is the action generated by sampling the ϵ noise from a zero-mean normal distribution $\mathcal{N}$. We can easily modify Algorithm 2 to optimize *soft* (entropy regularized) MDPs. In this case,

in the critic update (Line 12 of Algorithm 2), the Q_ψ update remains unchanged, while in the V_ϕ update, the target changes from $\mathbb{E}_{a\sim\pi_{\theta_{k+1}}}[Q_\psi(\cdot,a)]$ to $\mathbb{E}_{a\sim\pi_{\theta_{k+1}}}[Q_\psi(\cdot,a)-\lambda\log\pi(a|\cdot)]$. The loss function (11) used for the actor (policy) update (Lines 7-9 of Algorithm 2) is also modified, Q_ψ becomes the soft Q-function and a term $\lambda t_k \log \pi_{\theta_k}(\widetilde{a}_\theta(\epsilon,s)|s)$ is added inside the expectation.

Similarly to on-policy MDPO that has close connection to TRPO and PPO, discussed in Section 4.1, off-policy MDPO (Algorithm 2) is related to the popular soft actor-critic (SAC) algorithm [12]. We now derive SAC by slight modifications in the derivation of off-policy MDPO. This gives an optimization interpretation to SAC, which we then use to show strong ties between the two algorithms.

Comparison with SAC. Soft actor-critic is an approximate policy iteration algorithm in soft MDPs. At each iteration k, it first estimates the (soft) Q-function of the current policy, Q^{π_k}, and then sets the next policy to the (soft) greedy policy w.r.t. the estimated Q-function as

$$\pi_{k+1}(a|s) \leftarrow \exp\left(Q^{\pi_k}(s,a)\right) / Z^{\text{SAC}}(s), \tag{12}$$

where $Z^{\text{SAC}}(s) = \mathbb{E}_{a\sim\pi_k(\cdot|s)}\left[\exp\left(Q^{\pi_k}(s,a)\right)\right]$ is a normalization term. However, since tractable policies are preferred in practice, SAC suggests to project the improved policy back into the policy space considered by the algorithm, using the following optimization problem:

$$\theta_{k+1} \leftarrow \underset{\theta\in\Theta}{\arg\min}\ \mathcal{L}^{\text{SAC}}(\theta,\theta_k), \qquad \mathcal{L}^{\text{SAC}}(\theta,\theta_k) = \mathbb{E}_{s\sim\mathcal{D}}\left[\text{KL}\left(s;\pi_\theta,\frac{\exp\left(Q^{\theta_k}(s,\cdot)\right)}{Z^{\text{SAC}}(s)}\right)\right]. \tag{13}$$

This update rule computes the next policy as the one with the minimum KL-divergence to the term on the RHS of (12)

Since the optimization problem in (13) is invariant to the normalization term, unlike (12), the policy update (13) does not need to compute $Z^{\text{SAC}}(s)$. By writing the KL definition and using the reparameterization trick in (13), SAC updates its policy by minimizing the following loss function:

$$L^{\text{SAC}}(\theta,\theta_k) = \mathbb{E}_{\substack{s\sim\mathcal{D}\\\epsilon\sim\mathcal{N}}}\left[\lambda\log\pi_\theta\left(\widetilde{a}_\theta(\epsilon,s)|s\right) - Q_\psi^{\theta_k}\left(s,\widetilde{a}_\theta(\epsilon,s)\right)\right]. \tag{14}$$

Comparing the loss in (14) with the one used in off-policy MDPO (Eq. 11), we notice that despite the similarities, the main difference is the absence of the current policy, π_{θ_k}, in the SAC loss function. To explain the relationship between off-policy MDPO and SAC, recall from Section 2.1 that if the constraint set is the unit simplex, i.e., $C = \Delta_\mathcal{X}$, the MD update has the closed-form shown in (2). Thus, if the policy class (constraint set) Π in the update rule (4) is the entire space of stochastic policies, then we may write (4) in closed-form as (see e.g., [20, 28])

$$\pi_{k+1}(a|s) \leftarrow \pi_k(a|s)\exp\left(t_k Q^{\pi_k}(s,a)\right) / Z(s), \tag{15}$$

where $Z(s) = \mathbb{E}_{a\sim\pi_k(\cdot|s)}\left[\exp\left(t_k Q^{\pi_k}(s,a)\right)\right]$ is a normalization term. The closed-form solution (15) is equivalent to solving the constrained optimization problem (4) in two phases (see [13]): **1)** solving the *unconstrained* version of (4) that leads to the numerator of (15), followed by **2)** *projecting* this (unconstrained) solution back into the constrained set (all stochastic policies) using the same choice of Bregman divergence (KL in our case), which accounts for the normalization term in (15). Hence, when we optimize over the parameterized policy space Θ (instead of all stochastic policies), the MD update would be equivalent to finding a policy $\theta \in \Theta$ with minimum KL-divergence to the solution of the *unconstrained* optimization problem obtained in the first phase (the numerator of Eq. 15). This leads to the following policy update rule:

$$\theta_{k+1} \leftarrow \underset{\theta\in\Theta}{\arg\min}\ \mathcal{L}(\theta,\theta_k), \qquad \mathcal{L}(\theta,\theta_k) = \mathbb{E}_{s\sim\mathcal{D}}\left[\text{KL}\left(s;\pi_\theta,\pi_{\theta_k}\exp(t_k Q^{\theta_k})\right)\right]. \tag{16}$$

If we write the definition of KL and use the reparameterization trick in (16), we will rederive the loss function (11) used by our off-policy MDPO algorithm.[2] Note that both SAC (13) and off-policy MDPO (16) use KL projection to project back to the set of policies. For SAC, the authors argue that any projection can be chosen arbitrarily. However, our derivation clearly shows that the selection of KL projection is dictated by the choice of the Bregman divergence.

---

[2]In soft MDPs, Q^{π_k} is replaced by its soft version and a term $-\lambda t_k \log \pi_{\theta_k}(a|s)$ is added to the exponential in (15). This will result in the same changes in (16). Similar to the hard case, applying the reparameterization trick to the the soft version of (16) gives us the soft version of the loss function (11).

As mentioned earlier, the main difference between the loss functions used in the policy updates of SAC (14) and off-policy MDPO (11) is the absence of the current policy, π_{θ_k}, in the SAC's loss function.[3] The current policy, π_{θ_k}, appears in the policy update of off-policy MDPO, because it is a trust-region algorithm, and thus, tries to keep the new policy close to the old one. On the other hand, following the original interpretation of SAC as an approximate dynamic programming algorithm, its policy update does not contain a term to keep the new and old policies close to each other. It is interesting to note that SAC's loss function can be re-obtained by repeating the derivation which leads to off-policy MDPO, and replacing the current policy, π_{θ_k}, with the *uniform policy* in the objective (10) of off-policy MDPO. Therefore, SAC can be considered as a trust-region algorithm w.r.t. the uniform policy (or an entropy regularized algorithm). This means its update encourages the new policy to remain *explorative*, by keeping it close to the uniform policy.

SAC as FTRL. The above perspective suggests that both off-policy MDPO and SAC use similar regularization techniques to optimize the policy. This view allows us to regard the *hard* version of SAC as an RL implementation of the *follow-the-regularized-leader* (FTRL) algorithm. Thus, the equivalency between MD and FTRL (see e.g., [13]) suggests that off-policy MDPO and SAC are in fact closely related and somewhat equivalent. This is further confirmed by our experimental results reported in Section 5.4.

Due to space constraints, we defer a discussion on the forward and reverse KL directions (including the ECPO [20] algorithm) to Appendix D.

5 EXPERIMENTAL RESULTS

In this section, we empirically evaluate our on-policy and off-policy MDPO algorithms on a number of continuous control tasks from OpenAI Gym [6], and compare them with state-of-the-art baselines: TRPO, PPO, and SAC. We report all experimental details, including the hyper-parameter values used by the algorithms, in Appendix B. In the tabular results, both in the main paper and in Appendices E and F, we report the final training scores averaged over 5 runs and their 95% confidence intervals (CI). We bold-face the values with the best mean scores. We also compare on-policy MDPO and PPO on 21 Atari games from the ALE benchmark [4], showing averages over 5 random seeds. We strictly follow the hyperparameters reported in the PPO paper, and use $m = 3$ for all games.

For off-policy MDPO, we experiment with two potential functions ψ to define the Bregman divergence B_ψ: **1)** Shannon entropy, which results in the KL version (described in Section 4.2), and **2)** Tsallis entropy, which results in the Tsallis version of off-policy MDPO. We refer the reader to Appendix C for the complete description and detailed derivation of the Tsallis version. Note that we did not pursue a similar bifurcation between Tsallis and KL induced Bregman divergences for the on-policy case since the exact derivations are more tedious there. Another important point to note is that the Tsallis entropy gives us a range of entropies, controlled by the parameter $q \in (0, 2]$ (see Appendix C). Two special cases are **1)** Shannon entropy for $q = 1.0$, and **2)** sparse Tsallis for $q = 2.0$ [16, 17, 23].

5.1 ON MULTIPLE SGD STEPS

In on-policy MDPO, we implement the multi-step update at each MD iteration of the algorithm, by sampling M trajectories from the current policy, generating estimates of the advantage function, and performing m gradient steps using the same set of trajectories. We evaluated on-policy MDPO for different values of m in all tasks. We show the results for Walker2d in Figure 2 (top). The results for all tasks show a clear trade-off between m and the performance. Moreover, $m = 10$ seems to be the best value across the tasks. This is

Figure 2: **Performance of on-policy (top) and off-policy (bottom) MDPO** (code level optimizations included) for different values of m on the Walker2d task.

Env	On-Policy			Off-Policy		
	MDPO	TRPO	PPO	MDPO-KL	MDPO-Tsallis	SAC
Hopper-v2	**2361** ($\pm$ 518)	1979 ($\pm$ 672)	2051 ($\pm$ 241)	**2428** ($\pm$ 395)	**2428** ($\pm$ 395), $q = 1.0$	1870 ($\pm$ 404)
Walker2d-v2	**4834** ($\pm$ 607)	4473 ($\pm$ 558)	1490 ($\pm$ 292)	3591 ($\pm$ 366)	**4028** ($\pm$ 287), $q = 2.0$	3738 ($\pm$ 312)
HalfCheetah-v2	**4172** ($\pm$ 1156)	3751 ($\pm$ 910)	2041 ($\pm$ 1319)	11823 ($\pm$ 154)	11823 ($\pm$ 154), $q = 1.0$	**11928** ($\pm$ 342)
Ant-v2	**5211** ($\pm$ 43)	4682 ($\pm$ 278)	59 ($\pm$ 133)	4434 ($\pm$ 749)	**5486** ($\pm$ 737), $q = 2.0$	4989 ($\pm$ 579)
Humanoid-v2	3234 ($\pm$ 566)	**4414** ($\pm$ 132)	529 ($\pm$ 47)	5323 ($\pm$ 348)	**5611** ($\pm$ 260), $q = 1.2$	5191 ($\pm$ 312)
H. Standup-v2	**155261** ($\pm$ 3898)	149847 ($\pm$ 2632)	97223 ($\pm$4479)	143955 ($\pm$ 4499)	**165882** ($\pm$ 16604), $q = 1.4$	154765 ($\pm$ 11721)

Table 1: **Comparisons on MuJoCo**. Averaged (over 5 runs) returns for **Loaded+GAE** version of MDPO, TRPO, PPO, and SAC algorithms, together with their 95% confidence intervals. **On-policy** results are for **10M** timesteps. The values with the best mean scores are bold-faced.

why we use $m = 10$ in all our on-policy MDPO experiments. Our results clearly indicate that using $m = 1$ leads to inferior performance as compared to $m = 10$, reaffirming the theory that suggests solving the trust-region problem in RL requires taking several gradient steps at each MD iteration.

Finally, we ran a similar experiment for TRPO which shows that performing multiple gradient steps at each iteration of TRPO does not lead to any improvement. In fact our results showed that in some cases, it even leads to worse performance than when performing a single-step update.

For off-policy MDPO, performing multiple SGD steps at each MD iteration (Lines 6 to 10 in Algorithm 2) becomes increasingly time-consuming as the value of m grows. This is because off-policy algorithms perform substantially more gradient updates than their on-policy counterparts (a gradient step per environment step vs. a gradient step per almost $1,000$ environment steps). To address this issue, we resort to staying close to an m-step old copy of the current policy, while performing a single gradient update at each iteration of the algorithm. This copy is updated every m iterations with the parameters of the current policy. Our results for the Hopper domain in Appendix G.1 show that the performance of MDPO can be improved by performing m gradient updates at each iteration, but we omit from performing these experiments at scale because of their unreasonably high wall-clock time. Finally, we evaluated off-policy MDPO for different values of m in all tasks and show the results for Walker2d in Figure 2 (bottom). We found it hard to identify a single best value of m for all tasks. However, $m = 1000$ had the most reasonable performance across the tasks, and thus, we use it in all our off-policy MDPO experiments.

5.2   ON CODE-LEVEL OPTIMIZATIONS

There are certain "code-level optimization techniques" used in code-bases of TRPO, PPO, and SAC that result in enhanced performance. In [8], the authors provided a case study of these techniques in TRPO and PPO. We provide a detailed description of these techniques in Appendix B, and report the performance of the algorithms without these techniques (vanilla or minimal version) and with these techniques (loaded and loaded+GAE versions) in Appendices E and F. Note that the loaded+GAE version of TRPO and PPO match their state-of-the-art results in the literature.

Overall, the key takeaway from our results is that MDPO performs significantly better than PPO and on-par or better than TRPO and SAC, while being much simpler to implement, and more general as being derived from the theory of MD in RL. In the next two sections, we report our main observations from our on-policy and off-policy experiments.

5.3   ON-POLICY RESULTS

We implemented three versions of on-policy MDPO, TRPO, and PPO: **1)** the vanilla or minimal version, **2)** the loaded version in which we add the code-level optimization techniques to these algorithms, and **3)** the loaded version plus GAE, whose results are reported in Table 1. The results for all three versions are reported in Appendix E.

We elicit the following observations from our results. **First,** on-policy MDPO performs better than or on par with TRPO and better than PPO across all tasks. This contradicts the common belief that explicitly enforcing the constraint (e.g., through line-search) as done in TRPO is necessary for achieving good performance. **Second,** on-policy MDPO can be implemented more efficiently than TRPO, because it does not require the extra line-search step. Notably, TRPO suffers from scaling issues as it requires computing the correct step-size of the gradient update using a line search, which presents as an incompatible part of the computation graph in popular auto-diff packages, such as TensorFlow. Moreover, MDPO performs significantly better than PPO, while remaining equally

efficient in terms of implementation. **Third,** TRPO performs better than PPO consistently, both in the vanilla case and when the code-level optimizations (including GAE) are added to both algorithms. This is in contrast to the common belief that PPO is a better performing algorithm than TRPO. Our observation is in line with what noted in the empirical study of these two algorithms in [8], and we believe it further reinforces it. Adding code-level optimizations and GAE improve the performance of PPO, but not enough to outperform TRPO, when it also benefits from these additions. Lastly, **fourth,** it was shown in [30] that PPO is prone to instability issues. Our experiments show that this is indeed the case as PPO's performance improves until the standard time-step mark of 1M, and then decreases in some tasks. For example, in the Ant-v2 domain, both PPO and TRPO get to a similar score (1000) around the 1M mark but then PPO's performance decreases whereas TRPO continues to increase, as can be seen in Table 1 and Appendix E.

Atari results. To show that MDPO can be robustly used as an excellent substitute for PPO, we compare the two algorithms on 21 games from the ALE benchmark. Our results show that MDPO performs better or on par than PPO on 15 out of 21 games, while performing better than PPO on 6 out of 21 games. Due to space constraints, we report the full training plots in Appendix 10. Interestingly, both MDPO and PPO behave quite differently in a lot of games. Since we do not optimize any hyperparameters for MDPO, it might be possible to get more gains with further finetuning. Note that it is well known that TRPO leads to much inferior performance than PPO on the ALE benchmark. Indeed, comparing our results with those in the TRPO paper, we see that both MDPO and PPO win in 5 out of the 6 games reported in the TRPO paper.

5.4 OFF-POLICY RESULTS

Similar to the on-policy case, we implemented both vanilla and loaded versions of off-policy MDPO and SAC. We report the results of the loaded version in this section (Table 1), and the complete results in Appendix F. We observe the following from these results. **First,** off-policy MDPO-KL performs on par with SAC across all tasks. **Second,** off-policy MDPO-Tsallis that has an extra hyper-parameter q to tune can outperform SAC across all tasks. We observe that the best performing values of q are different for each domain but always lie in the interval $[1.0, 2.0]$. **Third,** off-policy MDPO results in a performance increase in most tasks, both in terms of sample efficiency and final performance, in comparison to on-policy MDPO. This is consistent with the common belief about the superiority of off-policy to on-policy algorithms.

Similar to off-policy MDPO, we can incorporate the Tsallis entropy in SAC. In [17], the authors showed performance improvement over SAC by properly tuning the value of q in SAC-Tsallis. However, in domains like Humanoid-v2 and Ant-v2, they only reported results for the 1M time-step mark, instead of the standard 3M. In our preliminary experiments with SAC-Tsallis in Appendix G.3, we did not see much improvement over SAC by tuning q, unlike what we observed in our MDPO-Tsallis results. More experiments and further investigation are hence needed to better understand the effect of Tsallis entropy (and q) in these algorithms.

6 CONCLUSIONS

We derived on-policy and off-policy algorithms from the theory of MD in RL. Each policy update in our MDPO algorithms is formulated as a trust-region optimization problem. However, our algorithms do not update their policies by solving these problems, instead, update them by taking *multiple gradient steps* on the objective function of these problems. We described in detail the relationship between on-policy MDPO and TRPO and PPO. We also discussed how SAC can be derived by slight modifications of off-policy MDPO. Finally, using a comprehensive set of experiments, we showed that on-policy and off-policy MDPO can achieve performance better than or equal to these three popular RL algorithms, and thus can be considered as excellent alternatives to them.

We can think of several future directions. In addition to evaluating MDPO algorithms in more complex and realistic problems, we would like to see their performance in discrete action problems in comparison with algorithms like DQN and PPO. Investigating the use of Bregman divergences other than KL seems to be promising. Our work with Tsallis entropy is in this direction but more algorithmic and empirical work needs to be done. Finally, there are recent theoretical results on incorporating exploration into the MD-based updates. Applying exploration to MDPO could prove most beneficial, especially in complex environments.

REFERENCES

[1] M. Azar, V. Gómez, and H. Kappen. Dynamic policy programming. *Journal of Machine Learning Research*, 13:3207–3245, 2012.

[2] A. Beck. First-order methods in optimization. *SIAM*, 25, 2017.

[3] A. Beck and M. Teboulle. Mirror descent and nonlinear projected subgradient methods for convex optimization. *Operations Research Letters*, 31(3):167–175, 2003.

[4] Marc G Bellemare, Yavar Naddaf, Joel Veness, and Michael Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, 2013.

[5] C. Blair. Problem complexity and method efficiency in optimization (A. Nemirovsky and D. Yudin). *SIAM Review*, 27(2):264, 1985.

[6] G. Brockman, V. Cheung, L. Pettersson, J. Schneider, J. Schulman, J. Tang, and W. Zaremba. OpenAI Gym. *Preprint arXiv:1606.01540*, 2016.

[7] P. Dhariwal, C. Hesse, O. Klimov, A. Nichol, M. Plappert, A. Radford, J. Schulman, S. Sidor, Y. Wu, and P. Zhokhov. OpenAI baselines, 2017.

[8] L. Engstrom, A. Ilyas, S. Santurkar, D. Tsipras, F. Janoos, L. Rudolph, and A. Madry. Implementation matters in deep RL: A case study on PPO and TRPO. In *Proceeding of the 8th International Conference on Learning Representations*, 2020.

[9] R. Fox, A. Pakman, and N. Tishby. Taming the noise in reinforcement learning via soft updates. In *Proceedings of the Thirty-Second Conference on Uncertainty in Artificial Intelligence*, pp. 202–211, 2016.

[10] S. Fujimoto, H. Hoof, and D. Meger. Addressing function approximation error in actor-critic methods. In *International Conference on Machine Learning*, pp. 1587–1596, 2018.

[11] M. Geist, B. Scherrer, and O. Pietquin. A theory of regularized Markov decision processes. In *Proceedings of the 36th International Conference on Machine Learning*, 2019.

[12] T. Haarnoja, A. Zhou, P. Abbeel, and S. Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 1861–1870, 2018.

[13] E. Hazan. Introduction to online convex optimization. *arXiv preprint arXiv:1909.05207*, 2019.

[14] S. Kakade and J. Langford. Approximately optimal approximate reinforcement learning. In *Proceedings of the 19th International Conference on Machine Learning*, pp. 267–274, 2002.

[15] H. Kappen. Path integrals and symmetry breaking for optimal control theory. *Journal of Statistical Mechanics*, 11, 2005.

[16] K. Lee, S. Choi, and S. Oh. Sparse Markov decision processes with causal sparse Tsallis entropy regularization for reinforcement learning. *Robotics and Automation Letters*, 2018.

[17] K. Lee, S. Kim, S. Lim, S. Choi, and S. Oh. Tsallis reinforcement learning: A unified framework for maximum entropy reinforcement learning. *Preprint arXiv:1902.00137*, 2019.

[18] T. Lillicrap, J. Hunt, A. Pritzel, N. Heess, T. Erez, Y. Tassa, D. Silver, and D. Wierstra. Continuous control with deep reinforcement learning. *Preprint arXiv:1509.02971*, 2015.

[19] B. Liu, Q. Cai, Z. Yang, and Z. Wang. Neural trust region/proximal policy optimization attains globally optimal policy. In *Proceedings of Advances in Neural Information Processing Systems*, 2019.

[20] J. Mei, C. Xiao, R. Huang, D. Schuurmans, and M. Muller. On principled entropy exploration in policy optimization. In *Proceedings of the 28th Joint Conference on Artificial Intelligence*, pp. 3130–3136, 2019.

[21] O. Nachum, M. Norouzi, K. Xu, and D. Schuurmans. Trust-PCL: An off-policy trust region method for continuous control. *Preprint arXiv:1707.01891*, 2017.

[22] O. Nachum, M. Norouzi, K. Xu, and D. Schuurmans. Bridging the gap between value and policy based reinforcement learning. In *Proceedings of the 31st Conference on Neural Information Processing Systems*, pp. 2772–2782, 2017.

[23] O. Nachum, Y. Chow, and M. Ghavamzadeh. Path consistency learning in Tsallis entropy regularized mdps. In *Proceedings of the 35th International Conference on Machine Learning*, pp. 979–988, 2018.

[24] G. Neu, A. Jonsson, and V. Gómez. A unified view of entropy-regularized markov decision processes. *Preprint arXiv:1705.07798*, 2017.

[25] J. Schulman, S. Levine, P. Abbeel, M. Jordan, and P. Moritz. Trust region policy optimization. In *Proceedings of the 32nd International conference on machine learning*, pp. 1889–1897, 2015.

[26] J. Schulman, P. Moritz, S. Levine, M. Jordan, and P. Abbeel. High-dimensional continuous control using generalized advantage estimation. *Preprint arXiv:1506.02438*, 2015.

[27] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *Preprint arXiv:1707.06347*, 2017.

[28] L. Shani, Y. Efroni, and S. Mannor. Adaptive trust region policy optimization: Global convergence and faster rates for regularized MDPs. In *Proceedings of the 33rd AAAI Conference on Artificial Intelligence*, 2020.

[29] E. Todorov. Linearly-solvable Markov decision problems. In *Proceedings of the 19th Advances in Neural Information Processing*, pp. 1369–1376, 2006.

[30] Y. Wang, H. He, and X. Tan. Truly proximal policy optimization. In *Proceeding of the 35th Conference on Uncertainty in Artificial Intelligence*, 2019.