DELTAMEM: Incremental Experience Memory for LLM Agents via Residual Trees

Abstract

Large Language Model (LLM)-based agents increasingly rely on memory to learn from experiences over continual interactions. However, storing experiences as independent, flat units leads to substantial redundancy and retrieval conflicts, as similar episodes repeat overlapping content and subtle scene variations cause retrieved memories to offer contradictory guidance. To address this, we introduce residual experience, positing that newly acquired experience is often an incremental variation of existing knowledge. We propose DELTAMEM, a framework that organizes experience memory into two independent residual trees, one storing goal-conditioned task experience as reusable skills and another for scene-level environment knowledge. Each tree uses a root node for generalized base experiences and incremental delta nodes for subsequent variations, allowing related experiences to share a common foundation without duplication. For retrieval, a failure-penalized similarity scan locates the best match, reconstructing the full experience via root-to-match chain composition. An autonomous consolidation mechanism distills high-frequency paths into new root nodes, enabling the trees to self-organize from general heuristics to specialized variants. Experiments across diverse interactive environments show that DELTAMEM consistently outperforms existing baselines. To facilitate future research, we release the code at https://anonymous.4open.science/r/DeltaMem-F75C/.

1 Introduction

Driven by the rapid progress of large language models (LLMs) in reasoning and planning (Wang et al., 2024a), autonomous agents show great promise in tackling long-horizon, complex sequential decision-making tasks across domains like web navigation, embodied manipulation, and scientific experimentation (Tan et al., 2026). However, the inherent stateless nature and context limits of LLMs force

Figure 1: Three memory storage paradigms. **Left**: flat trajectory storage. **Middle**: compact workflow/insight extraction. **Right**: DELTAMEM's residual tree with a generalized base experience and incremental Δ-nodes.

agents to reason from scratch in each episode, without benefiting from past trials (Zhao et al., 2024). Equipping agents with memory has therefore become a central mechanism. Memory enables experience learning, allowing agents to accumulate past interactions, adapt to changing environments, and improve their behavioral policies over successive episodes (Zhang et al., 2025).

Current memory mechanisms for experience learning generally fall into two broad categories, as illustrated in Figure 1. The first category stores complete or compressed historical trajectories as memory units (Zheng et al., 2024). During inference, it retrieves the most relevant past episodes to serve as few-shot demonstrations. The second category focuses on extracting high-level insights, reflections, or rules from past experiences rather than using raw trajectory steps (Ouyang et al., 2025; Wang et al., 2024b). These extracted insights are then added to the agent's context as textual prompts to guide future decision-making.

Despite their wide use, both approaches treat each memory item as an *independent, flat unit*, whether that item is a trajectory example or an extracted insight. Storing complete episodes from similar scenes creates substantial redundancy and ignores cross-episode connections. At read time, differences in source tasks or contexts of retrieved memories can cause conflicts, providing contradictory guidance that degrades decision quality

and limits continual adaptation. For example, two episodes of placing an object on a desk in different room layouts, when retrieved together, give conflicting advice on where to search while duplicating placement steps, mixing reusable task logic with scene-specific spatial facts in a single flat entry.

To address these limitations, we introduce DELTAMEM, a dual-tree residual memory framework that decouples experience into a Task-Tree for goal-conditioned action strategies and an Env-Tree for scene-level declarative knowledge. Rather than saving complete trajectories or extracting insights into flat and isolated repositories, each tree stores some generalized base experience from task or environment as root nodes and records new episodes as compact residual delta nodes, preserving only their incremental differences. During retrieval, a global similarity scan with failure-node penalty reconstructs a coherent and conflict-free experience context via root-to-match chain composition. Inspired by neuroscientific memory consolidation (McGaugh, 2000), high-frequency convergent paths are autonomously distilled into new root nodes, allowing the memory to self-organize over time. To facilitate community adoption, we release the code at https://anonymous.4open.science/r/DeltaMem-F75C/.

In summary, our contributions are as follows:
• We introduce the concept of residual experience via incremental delta storage to eliminate memory redundancy and retrieval conflicts. Based on this foundation, we propose DELTAMEM, a dual-tree framework that further decouples task policy from environment knowledge, enabling independent retrieval and evolution of each dimension.
• We design a tree-internal memory consolidation mechanism that distills high-frequency convergent paths into new root nodes, enabling the memory hierarchy to self-organize autonomously over successive episodes.
• We systematically evaluate DELTAMEM across diverse interactive environments demonstrating consistent and significant improvements over existing experience memory baselines.

2 Related Work

LLM-Based Agents. LLM-based autonomous agents are commonly structured around four core components, namely *profile*, *planning*, *memory*, and *action* (Wang et al., 2024a; Sumers et al., 2023). ReAct (Yao et al., 2022b) establishes a Thought-Action-Observation loop grounded in environment feedback; Reflexion (Shinn et al., 2023) adds verbal self-criticism for within-episode refinement. Chain-of-thought prompting (Wei et al., 2022) further improves multi-step reasoning within a single episode. Planning has been extended via tree-search (Yao et al., 2023) and hierarchical frameworks (Tan et al., 2026). Despite strong per-episode performance, these systems treat each episode independently, and cross-episode experience accumulation remains an open and active research challenge.

Agent Memory. Memory is widely studied in dialogue and personal-assistant settings (Zhang et al., 2025; Tan et al., 2025; Zhang et al., 2026a). For explicit memory, MemGPT (Packer et al., 2023) introduces OS-style paging to extend LLM context, Mem0 (Chhikara et al., 2025) supports scalable long-term personal memory, Generative Agents (Park et al., 2023) maintain a perception-reflection-retrieval stream, and MemTree (Rezazadeh et al., 2025) organizes memories into a tree structure for structured retrieval. Zhang et al. (2026b) further explore implicit memory by encoding past interactions into model parameters. For interactive task agents, memory is used to accumulate executable experience across episodes. Synapse (Zheng et al., 2024) retrieves the most similar successful trajectory as a few-shot exemplar, but storage grows linearly; AWM (Wang et al., 2024b) and ExpeL (Zhao et al., 2024) extract workflow rules into flat per-task files; ReasoningBank (Ouyang et al., 2025) tags distilled lessons as success or failure entries. Voyager (Wang et al., 2023) builds a growing skill library through open-ended exploration, while ReMEmbR (Anwar et al., 2025) structures episodic memory for robot navigation. These flat structures cannot generalize across scene variants or decouple task policy from environment knowledge.

In contrast, DELTAMEM addresses these limitations with a dual residual tree that decouples task policy (Task-Tree) from environment knowledge (Env-Tree) and stores each new experience as a compact delta relative to the most similar existing chain, enabling cross-scene generalization without incurring linear storage growth.

3 Method

DELTAMEM is built around two complementary principles: *structural decoupling* and *residual compression*. Rather than treating each episode as an independent, flat memory unit, DELTAMEM sepa-

Figure 2: Overview of DELTAMEM. **Top**: End-to-end pipeline. A task instruction triggers retrieval from the dual trees, the reconstructed memory context is injected into the agent for environment interaction, and the resulting experience is extracted back into the trees via online learning. **Bottom-left**: Tree details showing node content structure, global search across all trees, and the reconstructed root-to-match path. **Bottom-right**: Chain reconstruction that assembles a Base Skill with Δ Skill deltas and Base Knowledge with Δ Knowledge deltas into a complete, conflict-free memory context for the downstream agent.

rates experience into two orthogonal dimensions: goal-conditioned procedural experience and scene-level environment knowledge, storing each new interaction as an incremental delta relative to the most similar prior experience. Figure 2 gives a system-level overview, showing the dual-tree structure in the left panel, the global flat retrieval with failure-node penalty in the middle panel, and the root-to-match chain reconstruction that assembles a complete, noise-free experience context for the LLM in the right panel of Figure 2.

3.1 Dual-Tree Memory Architecture

Agent experience spans two qualitatively distinct dimensions. *Task policy* captures goal-conditioned procedural actions specific to a given objective, whereas *environment knowledge* covers scene-level declarative facts such as object features, spatial layouts, and interaction rules that remain globally consistent and task-agnostic. Conflating these two dimensions forces task-specific heuristics to mix with general scene facts, which leads to cross-task knowledge interference when the agent attempts novel goals within familiar environments. For instance, the step-by-step action sequence for finding and placing an object belongs to task policy, while observations such as where objects of a given type tend to be stored constitute scene knowledge that

transfers across many different task goals.

To achieve this decoupling, DELTAMEM maintains two independent hierarchical memory structures. The **Task-Tree** ($\mathcal{T}_{\text{task}}$) stores procedural experience entries, each organized as a reusable *skill* with three components:

$$\text{Skill} = \langle \alpha, \pi, \omega \rangle \tag{1}$$

where α is the activation condition that specifies when this skill applies; π is the execution procedure, a self-contained ordered action sequence; and ω is the termination condition indicating when the skill is complete. The task goal extracted from the current instruction serves as the query to the Task-Tree at inference time.

Concurrently, the **Env-Tree** ($\mathcal{T}_{\text{env}}$) stores *scene knowledge entries*, each capturing environment-level declarative facts:

$$\text{Knowledge} = \langle \alpha, \kappa \rangle \tag{2}$$

where α is the scene-level descriptive trigger used for matching, and κ represents the declarative content, such as object layouts and interaction rules. Rather than relying on a separately generated environment description, the Env-Tree query is obtained by extracting the environment relevant portion from the task instruction or initial observation

Figure 3: Autonomous memory consolidation in DELTAMEM. Residual nodes accumulate with success-hit counts (Phase 1); upon reaching K_{cons}, an LLM fuses the chain into a new root node R^* (Phase 2); subsequent queries match R^* directly, bypassing chain traversal (Phase 3).

(*e.g.*, scene descriptions, and spatial context), decoupling it from the goal specification. These two trees evolve asynchronously and independently; their respective retrieved chains are fused only at inference time, ensuring clean, interference-free representations for agent memory.

3.2 Residual Tree Structure

To directly address the massive memory redundancy caused by storing complete, flat trajectories, DELTAMEM organizes experiences into a residual tree architecture. Each node v in either tree is formally defined as:

$$v = \langle \text{type}, \text{label}, d(v), c(v), \mathbf{e}_v, P \rangle \quad (3)$$

where type $\in \{\text{ROOT}, \text{RESIDUAL}\}$; label $\in \{\text{SUCCESS}, \text{FAILURE}\}$ records the episode outcome; $d(v)$ denotes the node depth; $c(v)$ is the success-hit count, incremented when successful episodes terminate at v; $\mathbf{e}_v$ is the dense embedding of the node's descriptive trigger; and P is the actual payload, either Skill or Knowledge.

Root nodes serve as the foundational anchor, storing a complete, generalized base experience for a specific scene class. **Residual nodes**, by contrast, store only a delta payload ΔP. This delta encodes the incremental modification relative to its parent chain, covering additions such as extra steps, boundary-condition extensions, or newly discovered object states, without repeating shared historical content. As a result, successive interactions within variants of the same scene share a common root and record only their incremental behavioral differences, eliminating trajectory duplication.

Write Decision. After each episode, the system evaluates the retrieval outcome to determine the nature of the newly extracted node v_{new}:

$$\text{type}(v_{\text{new}}) = \begin{cases} \text{ROOT} & s(v^*) < \tau_{\text{base}} \\ \text{RESIDUAL} & s(v^*) \geq \tau_{\text{base}} \end{cases} \quad (4)$$

A *cold start* indicates that no similar experience exists; the system inserts a self-contained root node. A *warm start* appends an incremental residual delta to the best-matching retrieved chain.

Attachment Rule. To prevent unbounded chain growth and maintain efficient retrieval depth, the new node is mounted according to the following rule, where r_0 denotes the virtual root:

$$\text{parent}(v_{\text{new}}) = \begin{cases} r_0 & \text{type} = \text{ROOT} \\ v^* & d(v^*) < D_{\text{max}} \\ \text{parent}(v^*) & \text{otherwise} \end{cases} \quad (5)$$

If the best-matching node v^* has already reached the maximum allowed depth D_{max}, the new node is attached as a sibling of v^* rather than further deepening the existing branch.

3.3 Retrieval and Chain Reconstruction

Standard flat retrieval often aggregates memories from disparate past scenarios, surfacing contradictory plans. DELTAMEM addresses this through a global scan combined with hierarchical reconstruction to ensure a coherent, conflict-free context.

Given a query text q, DELTAMEM scans all nodes v across the corresponding tree and computes an adjusted similarity score:

$$s(v) = \cos(\mathbf{e}_q, \mathbf{e}_v) - \varepsilon \cdot \mathbb{I}(\text{label}_v = \text{FAILURE}) \quad (6)$$

where $\mathbb{I}(\cdot)$ is the indicator function and ε is a configurable failure-node penalty (default $\varepsilon = 0.05$). The globally highest-scoring node $v^* = \arg\max_v s(v)$ is accepted as v_{match} strictly if $s(v^*) \geq \tau_{\text{base}}$.

The failure penalty suppresses previously unsuccessful strategies without discarding them, turning past mistakes into retrieval guardrails, while the global flat search directly locates the best-matching node at any depth, bypassing irrelevant branches.

Once v_{match} is identified, the system assembles the root-to-v_{match} path into a complete experience context:

$$\mathcal{C} = \langle P_{v_0}^{(0)}, \Delta P_{v_1}, \ldots, \Delta P_{v_{\text{match}}} \rangle \tag{7}$$

The reconstructed task chain $\mathcal{C}_{\text{task}}$ and environment chain $\mathcal{C}_{\text{env}}$ are then concatenated. This fusion provides the LLM with a focused, noise-free decision context that reflects the specifics of the current task.

3.4 Experience Extraction Protocol

Following each episode, DELTAMEM prompts an LLM to distill the raw trajectory, alongside the retrieved memory chain if applicable, into a structured node. We design explicit extraction templates based on the node type and episode outcome.

For the Task-Tree, **Root-Success** extracts a complete base skill $\langle \alpha, \pi, \omega \rangle$, abstracting away environment-specific constants to maximize generalizability. **Root-Failure** records the observed actions and unexpected environment responses without hallucinating arbitrary replacements. **Residual-Success** extracts a minimal ΔSkill that covers *only* the procedural variations not captured by the retrieved parent chain. If the parent chain perfectly covers the new episode, no redundant node is written. **Residual-Failure** documents the exact breakdown point and the corresponding environment feedback relative to the retrieved chain.

For the Env-Tree, **Root-Knowledge** is triggered upon the first encounter with a scene class, extracting a foundational entry $\langle \alpha, \kappa \rangle$ that maps object layouts and baseline interaction rules. **Residual-Knowledge** is triggered during subsequent interactions with scene variants, extracting a delta $\Delta \kappa$ that documents only novel spatial relationships or newly observed rule deviations.

3.5 Autonomous Memory Consolidation

To prevent the residual trees from fragmenting over prolonged continual learning, DELTAMEM introduces an autonomous memory consolidation mechanism, illustrated in Figure 3. The system tracks a success-hit count $c(v)$ for each non-root node.

When a specific path proves highly reliable ($c(v) \geq K_{\text{cons}}$), the LLM is invoked to fuse the root-to-v chain into a single optimized node P^*:

$$\mathcal{C} = \langle P_{v_0}^{(0)}, \Delta P_{v_1}, \ldots, \Delta P_{v_k} \rangle \xrightarrow{\text{Distill}} P^* \tag{8}$$

This distilled experience P^* is written back into the tree as a new root node, while the original node v is marked as consolidated to prevent redundant re-triggering of the same path.

This mechanism affects both trees in distinct ways. The Task-Tree consolidates convergent, multi-step action strategies into self-contained skills. The Env-Tree solidifies stable observations into reusable scene descriptions. Over time, high-frequency interaction paths are promoted to root nodes, leaving low-frequency or highly specific variants as fine-grained residuals. The memory architecture thereby self-organizes from general heuristics into a hierarchy of specialized variants, without relying on external routing caches.

4 Experiments

4.1 Experimental Settings

Benchmarks. We evaluate on three interactive decision-making benchmarks spanning embodied environments and web navigation. **ALF-World** (Shridhar et al., 2020) is a text-based household environment with six task categories such as pick-and-place, heating or cooling objects, and examining items under a lamp. We evaluate on two splits: *Seen* (eval_in_distribution, 140 episodes) and *Unseen* (eval_out_of_distribution, 134 episodes), each capped at 30 steps. The two splits are treated as independent evaluation runs, each starting from an empty memory bank. Since ALF-World assigns binary reward per episode, its average reward is numerically equivalent to task success rate. **ScienceWorld** (Wang et al., 2022b) is a text-based science experiment environment covering 24 task types such as measuring melting points, testing conductivity, and species classification. We evaluate on *Seen* (dev, 194 episodes) and *Unseen* (test, 211 episodes), also treated as independent runs from empty memory; steps per episode are task-dependent. **WebShop** (Yao et al., 2022a) is a simulated e-commerce environment where agents must search for and purchase products matching a natural language instruction. Following the settings of previous work, we evaluate on a set of 200 episodes(Song et al., 2024).

Baselines. We compare DELTAMEM with four methods, all using the same underlying LLM and prompt framework. **No Memory**, which solves each episode independently with only the system prompt and one ICL demonstration, serving as the zero-shot baseline. **Synapse** (Zheng et al., 2024), which retrieves the most similar successful trajectory from a dense-embedding indexed pool as a few-shot exemplar. **AWM** (Wang et al., 2024b), which induces reusable workflow descriptions from successful trajectories and maintains per-task-type workflow files updated online. And **Reasoning-Bank** (Ouyang et al., 2025), which accumulates distilled lessons tagged as success strategies or failure warnings and injects the most relevant entries into the agent's decision prompt.

Implementation details. All methods query the DeepSeek-V4-flash API (DeepSeek-AI, 2026) at a decoding temperature of 0 using the ReAct framework (Yao et al., 2022b). Node embeddings are computed with E5-base-v2 (Wang et al., 2022a), running locally on the scenario description text. Each benchmark retains one human-annotated task example as the in-context demonstration ($n_{icl} = 1$). Since DELTAMEM relies on dense-embedding similarity, the thresholds τ_{base} and K_{cons} of per tree cannot be set heuristically as their appropriate values depend on each benchmark's embedding space. We select these parameters by sampling a small subset of episodes from each benchmark and examining the empirical similarity score distribution to determine appropriate threshold ranges. The final parameter values for each benchmark are listed in Appendix A. Further sensitivity analysis is reported in Section 4.5.

Evaluation protocol. All methods follow an *online learning* protocol: the agent starts from an empty memory and processes episodes sequentially, with experience extracted and memory updated after each episode. The primary metric across all benchmarks is **average reward** (AvgRew).

4.2 Main Results

Table 1 reports the main results across all benchmarks. DELTAMEM achieves the best or competitive performance across all splits and benchmarks.

On ALFWorld, DELTAMEM consistently leads on both splits. Synapse performs well on Seen but degrades sharply on Unseen, even falling below No-Memory, suggesting that complete-trajectory storage memorizes specific layouts without capturing

Table 1: Main results across all benchmarks, measured by AvgRew (↑). ALF. = ALFWorld, Sci. = ScienceWorld, Web. = WebShop. Best result per column is shown in **bold**.

Method	ALF		Sci		Web
	Seen	*Uns.*	*Seen*	*Uns.*	*—*
No Memory	0.7071	0.7985	0.7716	0.7186	0.3674
Synapse	0.7929	0.7015	0.8452	0.8558	0.5890
AWM	0.6429	0.8134	0.8052	0.7453	0.3337
RBank	0.7429	0.7463	0.7942	0.6898	0.3498
DELTAMEM	**0.8500**	**0.8358**	**0.8498**	**0.8688**	**0.6254**

Table 2: Offline memory bank utilization. Memory is built on the training split, then transferred to the Seen splits. F = Frozen (bank fixed), U = Unfrozen (bank continues updating). RBank = ReasoningBank. All values are AvgRew (↑). **Bold** = best per column.

Method	ALFWorld	ScienceWorld
AWM (F)	0.7071	0.8319
AWM (U)	0.6714	0.8199
RBank (F)	0.7429	0.7358
RBank (U)	0.7357	0.7495
DELTAMEM (F)	**0.7929**	0.8284
DELTAMEM (U)	**0.7929**	**0.8373**

transferable knowledge. AWM struggles on Seen, likely because high-level workflow abstraction discards fine-grained action detail. DELTAMEM's residual structure generalizes naturally by abstracting a shared base and recording only incremental behavioral differences, avoiding the redundancy of storing complete trajectories.

On ScienceWorld, DELTAMEM achieves the best results on both splits. The gap is more pronounced on Unseen, suggesting that the dual-tree structure accumulates increasingly reliable knowledge, while flat-storage methods plateau as memory redundancy steadily accumulates.

On WebShop, DELTAMEM performs on par with the best baseline. The relatively homogeneous nature of product-search tasks limits the additional signal provided by the Env-Tree, explaining the smaller differentiation compared to the physically grounded benchmarks above.

On average, residual nodes store roughly half the tokens of root nodes, confirming that shared content is not duplicated across episodes. Despite the structured skill format, per-memory token counts remain comparable to insight-based methods and well below full-trajectory storage; detailed statistics are in Appendix B.

Figure 4: Performance across a grid of $(\tau_{\text{base}}^{\text{task}}, \tau_{\text{base}}^{\text{env}})$ under four K_{cons} levels for ALFWorld (top) and SciWorld (bottom). Gold box marks the per-subplot optimum for each consolidation setting.

Table 3: Component ablation on the Seen split. *Task Only*: Task Tree only. *Env Only*: Env Tree only. All values are AvgRew ($\uparrow$). **Bold** = best per column.

Method	ALFWorld	SciWorld	WebShop
DELTAMEM	**0.8500**	**0.8498**	**0.5889**
Env Tree Only	0.7857	0.7540	0.5112
Task Tree Only	0.8143	0.7669	0.5346

4.3 Offline Memory Bank Utilization

The main experiments adopt an *online* protocol in which memory is accumulated from scratch throughout evaluation. To assess the practical value of a pre-built, reusable memory bank, we introduce a *train-to-test* protocol. First, in the **Build** phase, the agent runs on the training split under the standard online-learning protocol to accumulate a full memory bank. Then, in the **Evaluate** phase, the pre-built bank is loaded onto the Seen splits under two settings: *Frozen*, where the bank is fixed and no updates are made during evaluation; and *Unfrozen*, where the bank serves as a warm start and continues updating online during evaluation. Table 2 reports results for both settings.

DELTAMEM achieves the best results across both benchmarks and both evaluation settings (Table 2), demonstrating that the pre-built residual tree transfers effectively to new episodes without reconstruction from scratch. Notably, the Frozen and Unfrozen variants of DELTAMEM perform comparably on ALFWorld, indicating that the memory bank is already sufficient to guide new episodes; on ScienceWorld, the Unfrozen variant yields a

slight gain, consistent with continued refinement in a richer scientific environment.

In contrast, AWM's Unfrozen variant degrades on ALFWorld, suggesting that online updates to flat workflows introduce conflicting modifications; ReasoningBank shows a similar pattern. DELTAMEM's non-destructive tree structure avoids this by appending new delta nodes rather than overwriting previously stored entries.

4.4 Ablation Study

We ablate the two memory components of DELTAMEM: the Task-Tree and the Env-Tree. Table 3 reports performance when each component is disabled, confirming that both trees provide independent and complementary contributions.

Removing either tree leads to consistent performance drops across all benchmarks. On ALFWorld, the Task-Tree contributes more, reflecting the procedural nature of household manipulation where fine-grained action sequences are the primary bottleneck. On ScienceWorld, both single-tree variants fall substantially below the full model, indicating that precise scene-level knowledge and goal-conditioned task policy are jointly necessary for effective scientific experiment planning. The consistent gap between any single-tree variant and the full DELTAMEM confirms that the two trees capture orthogonal aspects of experience, with their combination yielding gains that neither achieves alone. On WebShop, both single-tree variants also show clear drops, confirming that the dual-tree design

Figure 5: Node distribution by tree depth under different parameter settings. Top row: ALFWorld; bottom row: SciWorld. Stacked bars show node counts at each depth level. **Left**: varying K_{cons} with thresholds fixed. **Middle**: varying $\tau_{\text{base}}^{\text{task}}$ with $\tau_{\text{base}}^{\text{env}}$ and K_{cons} fixed. **Right**: varying $\tau_{\text{base}}^{\text{env}}$ with $\tau_{\text{base}}^{\text{task}}$ and K_{cons} fixed.

benefits even relatively homogeneous task distributions such as product search.

4.5 Parameter Sensitivity Analysis

We study how the retrieval thresholds $\tau_{\text{base}}^{\text{task}}$, $\tau_{\text{base}}^{\text{env}}$, and the consolidation threshold K_{cons} jointly affect task performance and overall tree topology.

Performance sensitivity to retrieval thresholds. Figure 4 shows performance across all threshold combinations under four consolidation settings. When consolidation is active, *i.e.* $K_{\text{cons}} < \infty$, the performance landscape is broad and flat: a wide range of threshold pairs yields near-optimal results, confirming that DELTAMEM is not sensitive to the exact threshold values. As K_{cons} increases toward ∞ (no consolidation), the optimal region narrows and the gap between the best and worst threshold configurations widens. This suggests that consolidation has a regularizing effect on retrieval quality, making the system more tolerant of suboptimal retrieval threshold settings.

Effect of K_{cons} on tree structure. As shown in Figure 5 (left), the tree depth distribution shifts consistently with K_{cons} across both benchmarks. When K_{cons} is small, high-frequency paths are consolidated into root-level nodes more often, so Depth-1 nodes account for a larger share of the tree. As K_{cons} increases toward ∞, consolidation rarely triggers and nodes accumulate at greater depths instead. This is especially clear in the Env-Tree, where Depth-1 count drops monotonically as K_{cons} increases, confirming that consolidation effectively compresses convergent scene observations into reusable root entries.

Effect of retrieval thresholds on tree structure. Figure 5 (middle and right) vary one threshold at a time while keeping the other fixed. A stricter task threshold $\tau_{\text{base}}^{\text{task}}$ leads to more root-level entries in the Task-Tree: when an episode fails to match any existing node above the threshold, it is stored as a new root rather than a residual delta. A looser threshold, by contrast, attaches more episodes to existing chains and produces deeper trees. The Env-Tree shows the same pattern under $\tau_{\text{base}}^{\text{env}}$, though the effect is somewhat weaker given the more constrained vocabulary of scene descriptions. In both cases the performance landscape remains stable across the tested range (Figure 4), which is consistent with the threshold selection strategy described in detail in Section 4.1.

5 Conclusion

We presented DELTAMEM, a dual-tree residual memory framework designed to resolve the redundancy and retrieval conflicts of existing flat-storage approaches. By decoupling task policies from environment knowledge and organizing experiences as residual delta nodes, DELTAMEM compresses storage while preserving full semantic content for cleaner reuse. Through failure-penalized global retrieval and chain reconstruction, the framework successfully provides agents with a coherent and conflict-free context. Additionally, autonomous memory consolidation promotes high-frequency paths into a self-organizing hierarchy of base skills and specialized variants. Experiments across three benchmarks demonstrate consistent improvements in both task success rates and storage efficiency, offering a robust foundation for scalable and continually-learning agents.

Limitations

DELTAMEM relies on LLM-generated experience extraction at each episode, incurring additional inference cost beyond the base agent. The quality of extracted experience entries and deltas is sensitive to the capability of the underlying LLM, and low-quality extractions may introduce noise into the memory tree. The retrieval threshold τ_{base} (per tree) and the consolidation threshold K_{cons} are selected per benchmark on small held-out samples, which may not generalize automatically to new task domains without re-tuning. Additionally, the current framework does not model temporal decay of outdated experience; nodes reflecting stale environment states (*e.g.* website layout changes) may persist and mislead future retrieval.

Ethics Statement

The data used in this paper comes from publicly available licensed datasets, used for research purposes under their respective licenses. This work complies with the ACL Code of Ethics, and we declare no ethical issues.

References

Abrar Anwar, John Welsh, Joydeep Biswas, Soha Pouya, and Yan Chang. 2025. Remembr: Building and reasoning over long-horizon spatio-temporal memory for robot navigation. In *2025 IEEE International Conference on Robotics and Automation (ICRA)*, pages 2838–2845. IEEE.

Prateek Chhikara, Dev Khant, Saket Aryan, Taranjeet Singh, and Deshraj Yadav. 2025. Mem0: Building production-ready ai agents with scalable long-term memory. *arXiv preprint arXiv:2504.19413*.

DeepSeek-AI. 2026. Deepseek-v4: Towards highly efficient million-token context intelligence.

James L McGaugh. 2000. Memory–a century of consolidation. *Science*, 287(5451):248–251.

Siru Ouyang, Jun Yan, I Hsu, Yanfei Chen, Ke Jiang, Zifeng Wang, Rujun Han, Long T Le, Samira Daruki, Xiangru Tang, and 1 others. 2025. Reasoningbank: Scaling agent self-evolving with reasoning memory. *arXiv preprint arXiv:2509.25140*.

Charles Packer, Vivian Fang, Shishir_G Patil, Kevin Lin, Sarah Wooders, and Joseph_E Gonzalez. 2023. Memgpt: towards llms as operating systems.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pages 1–22.

Alireza Rezazadeh, Zichao Li, Wei Wei, and Yujia Bao. 2025. From isolated conversations to hierarchical schemas: Dynamic tree memory representation for llms. In *International Conference on Learning Representations*, volume 2025, pages 990–1023.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik Narasimhan, and Shunyu Yao. 2023. Reflexion: Language agents with verbal reinforcement learning. *Advances in neural information processing systems*, 36:8634–8652.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Côté, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. 2020. Alfworld: Aligning text and embodied environments for interactive learning. *arXiv preprint arXiv:2010.03768*.

Yifan Song, Da Yin, Xiang Yue, Jie Huang, Sujian Li, and Bill Yuchen Lin. 2024. Trial and error: Exploration-based trajectory optimization of llm agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7584–7600.

Theodore Sumers, Shunyu Yao, Karthik R Narasimhan, and Thomas L Griffiths. 2023. Cognitive architectures for language agents. *Transactions on Machine Learning Research*.

Haoran Tan, Zeyu Zhang, Chen Ma, Xu Chen, Quanyu Dai, and Zhenhua Dong. 2025. Membench: Towards more comprehensive evaluation on the memory of llm-based agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 19336–19352.

Haoran Tan, Zeyu Zhang, Chen Ma, Tianze Liu, Quanyu Dai, and Xu Chen. 2026. From coarse to fine: Self-adaptive hierarchical planning for llm agents. *arXiv preprint arXiv:2604.23194*.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. 2023. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*.

Lei Wang, Chen Ma, Xueyang Feng, Zeyu Zhang, Hao Yang, Jingsen Zhang, Zhiyuan Chen, Jiakai Tang, Xu Chen, Yankai Lin, and 1 others. 2024a. A survey on large language model based autonomous agents. *Frontiers of Computer Science*, 18(6):186345.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. 2022a. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*.

Ruoyao Wang, Peter Jansen, Marc-Alexandre Côté, and Prithviraj Ammanabrolu. 2022b. Scienceworld: Is your agent smarter than a 5th grader? In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 11279–11298.

Zora Zhiruo Wang, Jiayuan Mao, Daniel Fried, and Graham Neubig. 2024b. Agent workflow memory. *arXiv preprint arXiv:2409.07429*.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, and 1 others. 2022. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. 2022a. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35:20744–20757.

Shunyu Yao, Dian Yu, Jeffrey Zhao, Izhak Shafran, Tom Griffiths, Yuan Cao, and Karthik Narasimhan. 2023. Tree of thoughts: Deliberate problem solving with large language models. *Advances in neural information processing systems*, 36:11809–11822.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik Narasimhan, and Yuan Cao. 2022b. React: Synergizing reasoning and acting in language models. *arXiv preprint arXiv:2210.03629*.

Zeyu Zhang, Quanyu Dai, Xiaohe Bo, Chen Ma, Rui Li, Xu Chen, Jieming Zhu, Zhenhua Dong, and Ji-Rong Wen. 2025. A survey on the memory mechanism of large language model-based agents. *ACM Transactions on Information Systems*, 43(6):1–47.

Zeyu Zhang, Quanyu Dai, Luyu Chen, Zeren Jiang, Rui Li, Jieming Zhu, Xu Chen, Yi Xie, Zhenhua Dong, and Ji-Rong Wen. 2026a. Memsim: A bayesian simulator for evaluating memory of llm-based personal assistants. *Advances in Neural Information Processing Systems*, 38:90475–90511.

Zeyu Zhang, Yang Zhang, Haoran Tan, Rui Li, and Xu Chen. 2026b. Explicit vs implicit memory: Exploring multi-hop complex reasoning over personalized information. In *Proceedings of the 32nd ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 1*, pages 1964–1974.

Andrew Zhao, Daniel Huang, Quentin Xu, Matthieu Lin, Yong-Jin Liu, and Gao Huang. 2024. Expel: Llm agents are experiential learners. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 38, pages 19632–19642.

Longtao Zheng, Rundong Wang, Xinrun Wang, and Bo An. 2024. Synapse: Trajectory-as-exemplar prompting with memory for computer control. In *International Conference on Learning Representations*, volume 2024, pages 19036–19066.

A Parameter Settings

Table 4 lists the final threshold and consolidation parameters selected for each benchmark. For ALF-World and ScienceWorld, values were determined by inspecting the empirical similarity score distribution on a held-out sample; the configuration used in the main experiment is reported here. WebShop uses heuristically chosen values, as its product-search embedding space is more homogeneous.

Table 4: Selected parameter values per benchmark.

Benchmark	$\tau_{\text{base}}^{\text{task}}$	$\tau_{\text{base}}^{\text{env}}$	K_{cons}
ALFWorld	0.75	0.85	5
ScienceWorld	0.82	0.82	3
WebShop	0.85	0.85	3

B Memory Token Statistics

Table 5 reports the average number of tokens per stored memory unit for each method, measured on the ALFWorld online evaluation run. For DELTAMEM, root and residual nodes are counted separately; all other methods use one entry per memory unit. Token counts are estimated by whitespace tokenization on the stored text content. For ReasoningBank, the unit is one episode's distilled lesson set (*i.e.*, all items extracted from a single interaction); for AWM, it is one per-task-type workflow file.

Table 5: Average tokens per memory unit.

Method	Avg. tokens / memory
Synapse	448
AWM	59
ReasoningBank	148
DELTAMEM (Root)	257
DELTAMEM (Residual)	145

C Prompt Templates

DELTAMEM uses three categories of prompts: (1) per-benchmark agent system instructions that define the action space and interaction format; (2) a memory retrieval header injected between the in-context demonstration and the current task, which varies by method; and (3) six experience extraction prompts that guide tree updates after each episode. Experience extraction prompts are instantiated per benchmark; we show the **ALFWorld** canonical versions below as representative examples.

C.1 Agent System Instructions

ALFWorld Agent Instruction

```
Interact with a household to solve a task.
    Imagine you are an intelligent
agent in a household environment and your target
    is to perform actions to
complete the task goal. At the beginning of your
    interactions, you will be
given the detailed description of the current
    environment and your goal to
accomplish.
For each of your turn, you will be given the
    observation of the last turn.
You should choose from two actions: "Thought" or
    "Action". If you choose
"Thought", you should first think about the
    current condition and plan for
your future actions, and then output your action
    in this turn. Your output
must strictly follow this format:"Thought: your
    thoughts.\n Action: your
next action"; If you choose "Action", you should
    directly output the action
in this turn. Your output must strictly follow
    this format:
"Action: your next action".
The available actions are:
1. go to {recep}
2. take {obj} from {recep}
3. put {obj} in/on {recep}
4. open {recep}
5. close {recep}
6. toggle {obj} {recep}
7. clean {obj} with {recep}
8. heat {obj} with {recep}
9. cool {obj} with {recep}
where {obj} and {recep} correspond to objects
    and receptacles.
After your each turn, the environment will give
    you immediate feedback.
If the environment outputs "Nothing happened",
    the previous action is
invalid -- try more options.
Reminder:
1. The action must be chosen from the given
    available actions.
2. Think when necessary, try to act directly
    more in the process.
```

ScienceWorld Agent Instruction

```
You are a helpful assistant to do some
    scientific experiment in an
environment. In the environment, there are
    several rooms: kitchen,
foundry, workshop, bathroom, outside, living
    room, bedroom, greenhouse,
art studio, hallway. You should explore the
    environment and find the items
you need to complete the experiment. You can
    teleport to any room in one
step. All containers in the environment have
    already been opened, you can
directly get items from the containers.
For each of your turn, you will be given the
    observation of the last turn.
You should choose from two actions: "Thought" or
    "Action". If you choose
"Thought", your output must follow: "Thought:
    your thoughts.\n Action:
your next action". If you choose "Action": "
    Action: your next action".
Remember that you can only output one "Action:"
    per response.

The available actions are:
open OBJ / close OBJ / activate OBJ / deactivate
    OBJ
connect OBJ to OBJ / disconnect OBJ
use OBJ [on OBJ] / look around / examine OBJ /
    look at OBJ / read OBJ
```

```
move OBJ to OBJ / pick up OBJ / pour OBJ into
    OBJ / mix OBJ
teleport to LOC / focus on OBJ / wait / wait1
```

C.2 Agent Decision Prompt with Memory Injection

All methods share the same template structure; only the `memory_header` and `memory_context` fields differ by method.

Agent Decision Prompt Template (memory-injected)

```
{instruction}
---
Here is an example for a complete task
    trajectory.

{examples}
---

{memory_header}

{memory_context}

Now, it's your turn and here is the task.
{task}
```

C.3 DeltaMem Memory Retrieval Headers

The memory header appears between the ICL demonstration and the current task. It varies by benchmark to describe the domain-specific contents of each tree.

DeltaMem Memory Header – ALFWorld

```
Retrieved from your hierarchical memory system:
* Task Skill Memory -- HOW to solve this task
    type (Base Skill + Skill
  Deltas as patches)
* Environment Knowledge Memory -- WHERE objects
    are and HOW to operate
  receptacles/appliances
Note: 'Trigger'/'Applicable scenario' labels
    describe PAST episodes --
your actual task is at the end.
```

DeltaMem Memory Header – ScienceWorld

```
Retrieved from your hierarchical memory system:
* Task Skill Memory -- HOW to perform this
    science task type: exact action
  sequence, which room to find each item, device
    operation syntax
  (use/activate/connect), and what to watch out
    for.
* Environment Knowledge Memory -- WHERE specific
    items are located across
  ScienceWorld rooms, and HOW devices/equipment
    respond to actions.
Note: 'Trigger'/'Applicable scenario' labels
    describe PAST episodes --
your actual task is at the end.
```

DeltaMem Memory Header – WebShop

```
How to use the memory below -- READ CAREFULLY
The memory contains three kinds of entries:
  [Base Skill] -- a worked example trajectory
    from a SUCCESSFUL past
   shopping episode. This Base Skill ALWAYS
    applies to your current task.
   Its Trigger label is just an index/category
    tag, NOT a gating
   condition. You MUST treat it as a second ICL
    example and imitate its
   reasoning pattern (how it composed search
    keywords, how it picked the
   candidate from results, the order in which
    it clicked options, when it
   pressed Buy Now).
  [Skill Delta N] -- a short supplementary patch
    that adds extra advice ON
   TOP of the Base. Apply a patch only if its
    Trigger condition literally
   matches your current task; otherwise ignore
    that patch (but still apply
   the Base).
  [Failure Record / WARN] -- a warning about a
    trap. NEVER execute its
   procedure; use it only to AVOID the trap it
    describes.

How to actually use it (mandatory):
  STEP A -- Before your first Action, your
    Thought MUST contain one
   sentence stating how you are adapting the
    Base Skill's pattern to
   your current task.
  STEP B -- Write Action: search[...] using YOUR
    task's product/
   attributes/price, NOT the Base Skill's
    literal values.
  STEP C -- On the item page, follow the SAME
    option-selection order
   observed in the Base Skill but click YOUR
    task's values.
  STEP D -- If any Patch's Trigger literally
    matches your task, weave its
   advice into Steps B-C. Do NOT blend
    irrelevant patches.
```

C.4 Task Tree: Experience Extraction Prompts (ALFWorld)

Four prompts cover the combination of node type (root vs. residual) and episode outcome (success vs. failure). ScienceWorld, WebShop, and Mind2Web use analogous prompts with domain-specific field descriptions and syntax guidance.

Task Tree – Root Success

```
You are a Skill Extractor. Extract a reusable
    Base Skill from this
successful trajectory.
```

```
Environment: {env_description}
Task: {task_description}
Result: SUCCESS ({steps}/{max_steps} steps)

{trajectory}

Output a self-contained Base Skill -- future
    agents have NO access to
this trajectory:
- `activation_condition`: In plain natural
    language, describe when this
  skill applies and what distinguishes it from
    other tasks.
- `execution_procedure`: Concrete step sequence
    derived from this
  trajectory. Write out each individual action
    -- do not collapse
  multi-step operations into a single abstract
    phrase.
- `termination_condition`: When the skill is
    complete.

Output ONLY the JSON:
{
    "activation_condition": "...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

Task Tree – Root Failure

```
You are a Failure Recorder. This is a FAILURE
    RECORD -- NOT a skill to
execute. Future agents will see a [WARN] warning
     with this.

Environment: {env_description}
Task: {task_description}
Result: FAILURE ({steps}/{max_steps} steps)

{trajectory}

- `activation_condition`: In plain natural
    language, describe what task
  situation this applies to and what wrong
    assumption caused the failure.
- `execution_procedure`:
  [FAILED]: Actions tried and environment
    responses showing they failed.
  [UNEXPLORED]: Plausible approaches never
    attempted.
- `termination_condition`: Leave empty string.

Output ONLY the JSON:
{
    "activation_condition": "...",
    "execution_procedure": "[FAILED]: ...\n[
    UNEXPLORED]: ...",
    "termination_condition": ""
}
```

Task Tree – Residual Success (Node)

```
You are a Skill Delta Extractor. Extract ONLY
    the minimal new patch not
covered by existing skills.

=== EXISTING SKILL MEMORIES ===
{retrieved_task_memory}
=== END ===

Environment: {env_description}
Task: {task_description}
Result: SUCCESS ({steps}/{max_steps} steps)

{trajectory}

Output {"skip": true} ONLY if you can satisfy
    ALL of the following,
with direct evidence:
1. Identify ONE existing skill whose
    execution_procedure explicitly lists
  every distinct action type in this trajectory
    -- quote the exact phrase
```

```
    from that skill for each action.
2. No action required a recovery step, different
     object category, or
  procedural order not covered by that quoted
    text.
If you cannot quote matching text for even ONE
  action, you MUST write a
delta.

Otherwise, output the smallest delta (1-3 new
    observations max):
- `activation_condition`: The specific new
    condition that makes this delta
  necessary -- must differ from existing
    triggers.
- `execution_procedure`: New steps only,
    concrete and self-contained.
- `termination_condition`: When this delta is
    done.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

Task Tree – Residual Failure (Node)

```
You are a Failure Recorder. Record the gap in
    existing skills that caused
this failure.

=== EXISTING SKILL MEMORIES ===
{retrieved_task_memory}
=== END ===

Environment: {env_description}
Task: {task_description}
Result: FAILURE ({steps}/{max_steps} steps)

{trajectory}

Output {"skip": true} ONLY if an existing
    failure record describes the
EXACT SAME failure: you must quote the specific
    failed actions and the
exact environment responses from that record. If
     the failed action
sequence or environment response differs in any
    way, you MUST write a new
record.

Otherwise, output the gap as a trap record:
- `activation_condition`: The specific situation
     that existing skills
  failed to handle.
- `execution_procedure`:
  [FAILED]: What was tried and why it failed.
  [UNEXPLORED]: Approaches never attempted.
- `termination_condition`: Leave empty string.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "...",
    "execution_procedure": "[FAILED]: ...\n[
    UNEXPLORED]: ...",
    "termination_condition": ""
}
```

C.5 Environment Tree: Extraction Prompts (ALFWorld)

The Environment Tree uses a single prompt template per node type (root or residual), shared across both success and failure episodes—environmental observations are valid knowledge regardless of task

outcome.

Environment Tree – Root (First Episode)

```
You are an Environment Knowledge Extractor.
    Extract declarative facts
about this household environment from the
    trajectory -- regardless of
whether the task succeeded or failed, the
    environmental observations are
valid knowledge.

Environment: {env_description}
Task: {task_description}
Outcome: {result} ({steps}/{max_steps} steps)

{trajectory}

Output self-contained Base Environment Knowledge
     -- FACTS about the world,
not a procedure:
- `activation_condition`: "Applicable in [
    environment_type] environments
  where ..." -- key structural features.
- `execution_procedure`: CATEGORY-LEVEL patterns
     only --
  (A) what TYPES of objects tend to be in what
     TYPES of locations
    (e.g., "condiment-type objects tend to be on
     countertops or in kitchen
    drawers"),
  (B) how receptacle/appliance types behave,
  (C) pitfalls observed.
  Write as observations ("X-type objects tend to
     be on Y"), not commands.
  Do NOT record specific instances (e.g., "
    cabinet 3 had saltshaker 1") --
  ALFWorld randomizes object placement each
    episode.
- `termination_condition`: When this knowledge
    has been fully applied.

Output ONLY the JSON:
{
    "activation_condition": "Applicable in [
    environment_type] environments
where ...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

Environment Tree – Residual Node

```
You are an Environment Knowledge Extractor.
    Extract ONLY new environment
facts not covered by existing knowledge --
    regardless of whether the task
succeeded or failed.

=== EXISTING ENVIRONMENT KNOWLEDGE ===
{retrieved_env_memory}
=== END ===

Environment: {env_description}
Task: {task_description}
Outcome: {result} ({steps}/{max_steps} steps)

{trajectory}

Output {"skip": true} ONLY when EVERY specific
    object location AND EVERY
appliance/receptacle interaction rule observed
    in this trajectory is
already explicitly stated in the existing
    knowledge above. If even ONE
location or rule is not explicitly covered, you
    MUST write an update.

Otherwise, output the smallest new update (1-3
    new facts max):
- `activation_condition`: "Applicable in [
    environment_type] environments
  where ..." -- the new structural feature.
- `execution_procedure`: CATEGORY-LEVEL patterns
     only -- new
```

```
  object-type -> location-type tendencies or
    appliance behavior rules not
  in existing knowledge. Write as observations,
    not commands. Do NOT record
  specific instances.
- `termination_condition`: When this adaptation
    is complete.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "Applicable in [
    environment_type] environments
where ...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

C.6 Task Tree: Experience Extraction Prompts (ScienceWorld)

Task Tree – Root Success (ScienceWorld)

```
You are a Skill Extractor. Extract a reusable
    Base Skill from this
successful science experiment trajectory.

Environment: {env_description}
Task: {task_description}
Result: SUCCESS (Steps: {steps}, Reward: {reward
    }/1.0)

{trajectory}

Output a self-contained Base Skill -- future
    agents have NO access
to this trajectory:
- `activation_condition`: The science task TYPE
    and distinguishing
  features (e.g., "boiling tasks where the goal
    is to heat a liquid
  until it reaches its boiling point, requiring
    a heat source and
  thermometer").
- `execution_procedure`: Concrete step-by-step
    procedure using exact
  ScienceWorld syntax (teleport to LOC / pick up
     OBJ / use OBJ on OBJ
  / focus on OBJ / pour OBJ into OBJ / mix OBJ /
     activate OBJ /
  connect OBJ to OBJ). Include: (1) which room
    each item is found in,
  (2) the full action sequence in order, (3) any
     critical preconditions
  or pitfalls.
- `termination_condition`: When the skill is
    complete (e.g., reward > 0
  confirmed / target substance reached required
    state).

Output ONLY the JSON:
{
    "activation_condition": "...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

Task Tree – Root Failure (ScienceWorld)

```
You are a Failure Recorder. This is a FAILURE
    RECORD -- NOT a skill
to execute. Future agents will see a [WARN]
    warning with this.

Environment: {env_description}
Task: {task_description}
Result: FAILURE (Steps: {steps}, Reward: {reward
    }/1.0)
Note: Reward > 0 means some sub-goals were
    completed before failure.

{trajectory}
```

```
- 'activation_condition': Task type + the
    specific wrong assumption or
  failure condition that caused this outcome.
- 'execution_procedure':
  [FAILED]: Actions attempted and exact
    environment responses showing
  failure. If reward > 0, identify which sub-
    goals succeeded before
  breakdown.
  [UNEXPLORED]: Plausible approaches this agent
    never attempted.
- 'termination_condition': Leave empty string.

Output ONLY the JSON:
{
    "activation_condition": "...",
    "execution_procedure": "[FAILED]: ...\n[
    UNEXPLORED]: ...",
    "termination_condition": ""
}
```

Task Tree – Residual Success (ScienceWorld)

```
You are a Skill Delta Extractor. Extract ONLY
    the minimal new patch
not covered by existing skills.

=== EXISTING TASK SKILL MEMORIES ===
{retrieved_task_memory}
=== END ===

Environment: {env_description}
Task: {task_description}
Result: SUCCESS (Steps: {steps}, Reward: {reward
    }/1.0)

{trajectory}

Output {"skip": true} ONLY if ALL of the
    following hold with evidence:
1. Reward is 1.0 (full success).
2. Identify ONE existing skill whose
    execution_procedure explicitly
  lists every distinct action performed --
    quote the exact phrase.
3. No action required a recovery step, different
    item, or procedural
  order not covered by that quoted text.
If ANY condition fails, you MUST write a delta.

Otherwise, output the smallest delta (1-3 new
    observations max):
- 'activation_condition': The SPECIFIC NEW
    condition for this delta.
- 'execution_procedure': NEW steps/rules only,
    using exact ScienceWorld
  action syntax.
- 'termination_condition': When this delta
    modification is complete.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

Task Tree – Residual Failure (ScienceWorld)

```
You are a Failure Recorder. Record the gap in
    existing skills that
caused this failure.

=== EXISTING TASK SKILL MEMORIES ===
{retrieved_task_memory}
=== END ===

Environment: {env_description}
Task: {task_description}
Result: FAILURE (Steps: {steps}, Reward: {reward
    }/1.0)
```

```
Note: Reward > 0 means some sub-goals were
    completed before failure.

{trajectory}

Output {"skip": true} ONLY if an existing
    failure record describes the
EXACT SAME failure: quote the specific failed
    actions and exact
environment responses from that record. If any
    detail differs, write a
new record.

Otherwise, output the gap as a trap record:
- 'activation_condition': The specific situation
    existing skills failed
  to handle.
- 'execution_procedure':
  [FAILED]: Actions attempted and exact
    environment responses. Note
  which existing skill guidance was followed but
    did not work.
  [UNEXPLORED]: Plausible approaches never
    attempted.
- 'termination_condition': Leave empty string.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "...",
    "execution_procedure": "[FAILED]: ...\n[
    UNEXPLORED]: ...",
    "termination_condition": ""
}
```

C.7 Environment Tree: Extraction Prompts (ScienceWorld)

Unlike ALFWorld, ScienceWorld rooms have consistent item placement across episodes, so the Env-Tree records specific room-to-item mappings rather than category-level tendencies.

Environment Tree – Root (ScienceWorld)

```
You are an Environment Knowledge Extractor.
    Extract declarative facts
about this ScienceWorld environment --
    regardless of task outcome,
the observations are valid knowledge.

Environment: {env_description}
Task: {task_description}
Outcome: Steps={steps}, Reward={reward}/1.0

{trajectory}

Important: ScienceWorld rooms have CONSISTENT
    item placement across
episodes. Record SPECIFIC room->item mappings (e
    .g., "the thermometer
is in the kitchen"), not just category-level
    tendencies.

- 'activation_condition': "Applicable in
    ScienceWorld environments
  where ..." -- describe the task context or
    room configuration.
- 'execution_procedure': Factual observations:
  (A) specific item locations by room (e.g., "
    thermometer: kitchen",
    "battery: workshop"),
  (B) device/equipment operation rules with
    exact action syntax
    (e.g., "use thermometer on OBJ to read
    temperature"),
  (C) efficient room search order for common
    items,
  (D) any pitfalls observed.
  Write as facts, not commands.
```

```
- 'termination_condition': When this environment
    knowledge has been
  fully applied.

Output ONLY the JSON:
{
    "activation_condition": "Applicable in
    ScienceWorld environments
where ...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

828

Environment Tree – Residual Node (ScienceWorld)

```
You are an Environment Knowledge Extractor.
    Extract ONLY new
environment facts not covered by existing
    knowledge -- regardless of
task outcome.

=== EXISTING ENVIRONMENT KNOWLEDGE ===
{retrieved_env_memory}
=== END ===

Environment: {env_description}
Task: {task_description}
Outcome: Steps={steps}, Reward={reward}/1.0

Important: ScienceWorld rooms have CONSISTENT
    item placement. Record
specific room->item mappings when newly observed
    .

Output {"skip": true} ONLY when EVERY item
    location AND EVERY
device/equipment interaction rule observed in
    this trajectory is
already explicitly stated in the existing
    knowledge above.

Otherwise, output the smallest new update (1-3
    new facts max):
- 'activation_condition': "Applicable in
    ScienceWorld environments
  where ..." -- the new context covered.
- 'execution_procedure': NEW facts only --
    specific item locations or
  device rules not in existing knowledge.
    Written as facts, not
  commands.
- 'termination_condition': When this environment
    adaptation is
  complete.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "Applicable in
    ScienceWorld environments
where ...",
    "execution_procedure": "...",
    "termination_condition": "..."
}
```

829

830
831

C.8 Task Tree: Experience Extraction Prompts (WebShop)

Task Tree – Root Success (WebShop)

```
You are saving a SUCCESSFUL WebShop trajectory
    as a reference example
for future agents -- like a curated 1-shot ICL
    exemplar, NOT an
abstract instruction manual.

Product Category: {env_description}
Task: {task_description}
Result: SUCCESS ({steps}/{max_steps} steps)

=== RAW TRAJECTORY ===
{trajectory}
```

832

```
=== END ===

Clean and condense the raw trajectory into a
    SHORT illustrative dialog
the future agent can IMITATE. Keep Observation
    -> Thought -> Action
format.

Rules:
- KEEP every Action that contributed to success
    (search, candidate
  click, option selections, Buy Now). DROP
    failed/backtracked attempts.
- For each kept Observation, TRIM noise but
    preserve lines that justify
  the next Action. One Observation block <= 60
    words.
- Add a brief Thought before each Action
    explaining WHY (<= 25 words).
- End after the successful Action: click[Buy Now
    ].

- 'activation_condition': Short noun phrase
    naming when this exemplar
  is relevant. Specific to the product category
    but not exact
  constraints. <= 30 words.
- 'execution_procedure': The cleaned trajectory
    text. Multi-line,
  plain text, Obs/Thought/Action format.
- 'termination_condition': "After Action: click[
    Buy Now] succeeds with
  full reward."

Output ONLY the JSON (escape newlines as \n in
    execution_procedure):
{
    "activation_condition": "...",
    "execution_procedure": "Observation: ...\
    nThought: ...\nAction:
search[...]\n...\nAction: click[Buy Now]",
    "termination_condition": "..."
}
```

833

Task Tree – Root Failure (WebShop)

```
You are a Failure Recorder. This is a FAILURE
    RECORD -- NOT a skill
to execute. Future agents will see a [WARN]
    warning with this.

Product Category: {env_description}
Task: {task_description}
Result: FAILURE ({steps}/{max_steps} steps)

{trajectory}

- 'activation_condition': Describe what WebShop
    task situation this
  applies to and what wrong assumption caused
    the failure (e.g.,
  too-broad search keywords, picking without
    checking constraints,
  missing option selection before Buy Now).
- 'execution_procedure':
  [FAILED]: Actions tried and how WebShop
    responded (e.g., "search
  returned 0 results", "Buy Now pressed without
    selecting size").
  [UNEXPLORED]: Plausible alternative keywords /
    candidates / options
  never attempted.
- 'termination_condition': Leave empty string.

Output ONLY the JSON:
{
    "activation_condition": "...",
    "execution_procedure": "[FAILED]: ...\n[
    UNEXPLORED]: ...",
    "termination_condition": ""
}
```

834

Task Tree – Residual Success (WebShop)

```
You are writing a Skill Patch that supplements
    an existing Base Skill
-- NOT another standalone procedure.

=== EXISTING SKILL CHAIN (Base + previous
    patches) ===
{retrieved_task_memory}
=== END ===

Product Category: {env_description}
Task: {task_description}
Result: SUCCESS ({steps}/{max_steps} steps)

{trajectory}

Write a patch ONLY if the trajectory reveals a
    new tactic or
special-case observation the base skill does NOT
    already cover.
Examples: a new search-keyword trick for this
    sub-category, a new
option-selection ordering, a common failure mode
    and how to avoid it.

Rules:
- DO NOT restate the base procedure.
- Write ONLY what is different/additional for
    this sub-category.
- 1-4 short bullets, <= 80 words in
    execution_procedure.
- activation_condition names the SPECIFIC
    trigger.
- execution_procedure starts with "In addition
    to the base:" or
  "Replace base step N with:".

Output {"skip": true} if the trajectory shows
    nothing new beyond the
base skill.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "When [specific sub-
    category / constraint
combo] applies...",
    "execution_procedure": "In addition to the
    base: ...",
    "termination_condition": ""
}
```

Task Tree – Residual Failure (WebShop)

```
You are recording a Failure Patch -- a warning
    supplementing the
existing Base Skill, not a standalone failure
    log.

=== EXISTING SKILL CHAIN (Base + previous
    patches/warnings) ===
{retrieved_task_memory}
=== END ===

Product Category: {env_description}
Task: {task_description}
Result: FAILURE ({steps}/{max_steps} steps)

{trajectory}

Identify the SPECIFIC trap this trajectory hit
    and write a SHORT
warning to help future agents avoid it.

Rules:
- DO NOT restate base procedure. Just the trap.
- activation_condition: name the specific sub-
    category + symptom.
- execution_procedure (<= 80 words): start with
    [TRAP]: followed by
  what caused the wrong action, then [FIX]:
    followed by the corrective
  tactic.
```

```
- termination_condition: leave empty.

Output {"skip": true} ONLY if an existing
    failure record already warns
about the exact same trap.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "When [specific sub-
    category + trap
symptom]...",
    "execution_procedure": "[TRAP]: ...\n[FIX]:
    ...",
    "termination_condition": ""
}
```

C.9 Environment Tree: Extraction Prompts (WebShop)

In WebShop, the Env-Tree captures UI behavior patterns for each product category rather than physical scene layouts.

Environment Tree – Root (WebShop)

```
You are a WebShop Site Knowledge Extractor.
    Extract declarative FACTS
about WebShop's UI behaviour for this product
    category, written so
they remain useful when a future agent shops in
    the same category for
a different item.

Product Category: {env_description}
Task this episode: {task_description}
Outcome: {result} ({steps}/{max_steps} steps)

{trajectory}

Output self-contained Base Site Knowledge --
    FACTS, NOT step-by-step
procedure:
- 'activation_condition': "Applicable when
    shopping for
  {env_description} on WebShop." Add structural
    traits observed (e.g.,
  "items in this category expose size and color
    as required options
  before Buy Now").
- 'execution_procedure': Three groups of FACTS:
  (A) Option dimensions exposed for this
    category (size? color? scent?
    pack-size?) and which are REQUIRED before
    Buy Now for full reward.
  (B) Search-keyword patterns that worked -- as
    patterns, not literal
    strings.
  (C) Pitfalls observed (e.g., "Buy Now without
    selecting size ->
    partial reward only").
- 'termination_condition': When the agent has
    applied these facts to
  inform a correct selection.

Output ONLY the JSON:
{
    "activation_condition": "Applicable when
    shopping for
{env_description} on WebShop ...",
    "execution_procedure": "(A) ... (B) ... (C)
    ...",
    "termination_condition": "..."
}
```

Environment Tree – Residual Node (WebShop)

```
You are writing a Site Knowledge Patch -- a
    small note supplementing
```

```
existing site knowledge, NOT a restatement of it
    .

=== EXISTING SITE KNOWLEDGE ===
{retrieved_env_memory}
=== END ===

Product Category: {env_description}
Task this episode: {task_description}
Outcome: {result} ({steps}/{max_steps} steps)

{trajectory}

Note a NEW site fact this trajectory revealed
    that the existing
knowledge does not already state (e.g., a
    required option dimension,
a pagination detail, a quantity default).

Rules:
- DO NOT restate existing knowledge. Just the
    new fact.
- 1-3 short bullets, <= 60 words in
    execution_procedure.
- activation_condition names the SPECIFIC sub-
    category trigger.

Output {"skip": true} ONLY if every UI fact
    observed here is already
in the existing knowledge above.

Output ONLY one of these two JSON formats:
{"skip": true}
OR
{
    "activation_condition": "When shopping for {
    env_description} on
WebShop ...",
    "execution_procedure": "...",
    "termination_condition": ""
}
```