Divisive Feature Normalization Improves Image Recognition Performance and Increases Manifold Capacity, Sparsity, and Low-Frequency Representation in Deep Nets

Abstract

Local divisive normalization provides a phenomenological description of many nonlinear response properties of neurons across visual cortical areas. To gain insight into the utility of this operation, we studied the effects on AlexNet of a local divisive normalization between features, with learned parameters. Developing features were arranged in a line topology, with the influence between features determined by an exponential function of the distance between them. We compared an AlexNet model with no normalization or with canonical normalizations (Batch, Group, Layer) to the same models with divisive normalization added (before the canonical normalization, when those were used). The normalization was performed after the RELU in all five convolutional layers. Divisive normalization always improved performance for models with batch or group or no normalization, generally by 1-2 percentage points, on both the CIFAR-100 and ImageNet databases. Divisive followed by batch normalization showed best performance. To gain insight into mechanisms underlying the improved performance, we examined several aspects of network representations. In the early layers both canonical and divisive normalizations reduced manifold capacities and increased average dimension of the individual categorical manifolds. In later layers the capacity was higher and manifold dimension lower for models roughly in order of their performance improvement. We also use the Gini index, a measure of the inequality of a distribution, as a metric for sparsity of the distribution of activities within a given layer. Divisive normalization layers increase the Gini index (i.e. increase sparsity), whereas the other normalizations decrease the Gini index in their respective layers. Nonetheless, in the final layer, the sparseness of activity increases in the order of no normalization, divisive, combined, and canonical. We also investigate how the receptive fields (RFs) in the first convolutional layer (where RFs are most interpretable) change with normalization. Divisive normalization enhances RF Fourier power at low wavelengths, and divisive+canonical enhances power at mid (batch, group) or low (layer) wavelengths, compared to canonical alone or no normalization. In conclusion, divisive normalization enhances image recognition performance, most strongly when combined with canonical normalization, and in doing so it reduces manifold capacity and sparsity in early layers while increasing them in final layers, and increases low- or mid-wavelength power in the first-layer receptive fields.

1 Introduction

Although neural networks (NN's) in general and convolutional NN's (CNN's) in particular were originally inspired by the brain, the study of NN's has diverged far from concerns about biological realism. Nonetheless, a number of important questions remain about relationships between the study of biological and artificial NN's, in particular: what can each learn from the other? Here we show that a biological form of "divisive normalization", which is postulated to be a canonical computation of at least sensory cortex (Carandini & Heeger, 2012), can enhance the image classification performance

of AlexNet (Krizhevsky et al., 2012), and examine some aspects of the changes in representation that this normalization induces.

Divisive normalization is a phenomenological description (Geisler & Albrecht, 1992; Heeger, 1992) of nonlinear neuronal response properties observed throughout sensory cortex: when multiple stimuli are simultaneously presented, either within a neuron's receptive field (the region of sensory space in which appropriate stimuli can drive a given neuron's response) or in both the receptive field (in the "center") and outside the receptive field ("surround"), then (1) responses tend to be less than the sum of the responses to the stimuli shown individually, that is, summation is sublinear; but (2) when stimuli are weak, the summation becomes more linear or even supralinear (more than the sum of the responses to the individual stimuli). The phenomenological description posits that a neuron's response is its unnormalized response, divided by a function of a constant plus a sum over the unnormalized responses (perhaps raised to a power) of all of the other surrounding neurons in a "normalization pool". Thus, anything that adds to the collective response of the population also suppresses responses of each individual neuron, representing an effective inhibition between neurons within the pool. However, the divisive function reduces to the constant for weak unnormalized responses, thus removing the effects of the normalization for weak stimuli. The unnormalized response is often modeled as an expansive function, e.g. a rectified quadratic, in which case the response to multiple weak stimuli can show supralinear summation.

There are other standard forms of normalization being used in neural networks (Ren et al., 2016), which we will call "canonical". These include (but are not limited to) batch (Ioffe & Szegedy, 2015), layer (Ba et al., 2016), instance (Ulyanov et al., 2016), and group (Wu & He, 2018) normalization. These all standardize (zero mean, unit variance) and then affinely transform sets of activations in a given layer; they differ in the sets of channels and images over which standardization is performed (for all, the sets include all of space). These normalizations prevent or reduce covariate shifts and can have other advantages. The set includes one image for all but batch normalization, which uses all images in a batch. The first three do not lead to competition between channels, as the set either includes a single channel (batch or instance) or all channels (layer), and the same operations are being applied to all channels in the set. However, in group normalization, the channels are divided into non-overlapping groups, with standardization performed separately over each group. Thus there is competition within the group – one channel's activation is determined by its unnormalized activity relative to that of others within the group, so one channel's strong activity can suppress the activity of other channels in the group, relative to the activities of channels in other groups. This is closest to divisive normalization, which is competitive.

In our formulation of divisive normalization, the group with which a neuron is competing changes continuously with the neuron, to constitute some local region around each neuron. We will take this local region to be a single point of space and a learnable span of channels about a given channel (more precisely, the channels are topologically arranged on a line; and the contribution of nearby channels is weighted, according to the distance between it and the channel being normalized, by a decaying exponential with a learnable length constant). Divisive normalization does not prevent covariate shifts, so we will find it useful to combine divisive normalization with one of the other normalizations.

Our contributions in this paper are demonstrating that:

- Addition of divisive normalization improves performance for image recognition by AlexNet on ImageNet and CIFAR-100 for models with no normalization or with batch or group normalization.

- Divisive normalization alone increases the large wavelength Fourier modes in the first layer receptive fields. Combined normalization models (e.g. Divisive+Batch) increase mid-scale Fourier modes.

- At interior layers, canonical and divisive normalizations tend to reduce the network's manifold capacity and correspondingly increase the average correlation, radii (except divisive normalization), and dimension of object manifolds. However, they lead to increased manifold capacity in the final layers, with the pairing of divisive with canonical normalization showing the highest capacity, and to correspondingly decreased manifold radii and dimension.

- When included in a model alone or combined with another normalization scheme, divisive normalization consistently increases the sparsity of activations (Gini index) at each normalization step and in the output layer.

2 RELATED WORK

Recent work has revealed a circuit that, although not designed to achieve normalization in any obvious way, dynamically replicates the phenomena summed up as divisive normalization (Ahmadian et al., 2013; Rubin et al., 2015). This has raised our interest in understanding its possible functions. There are many hypotheses as to the function of divisive normalization, of which we mention only a few. It has been postulated to keep activations within an appropriate dynamic range for the neurons (Carandini & Heeger, 2012). It has been shown to remove higher-order statistical dependencies in responses to auditory or visual stimuli (Schwartz & Simoncelli, 2001). It has also been shown to arise from statistical inference of the reflectances underlying a model of the statistics of natural scenes, the Gaussian scale mixture model (GSM) (Coen-Cagli et al., 2012; 2015; Echeveste et al., 2020).

The original AlexNet (Krizhevsky et al., 2012) included local response normalization (LRN), much like ours (Eq. 1) but with a linear numerator and the sum in the denominator over ± 2 neighbors without exponential weighting. Parameter values were hyperparameters set using a validation set; the equivalent of our parameter $k\alpha/\lambda$ was 10^{-4}, with $k = 2$, making it difficult to understand how LRN could have had much impact. Nonetheless it was said to improve performance, but this was disputed by Simonyan & Zisserman (2015). Ren et al. (2016) developed a unified mathematical framework for slightly modified batch, layer, and divisive normalization, combined it with an L1 regularizer, and showed that various forms of this (learned) regularized normalizer improved performance on CIFAR-10 and CIFAR-100 in a network with 3 convolutional and 2 fully connected layers, with the best performance by a modified batch norm. Their divisive normalization included in a unit's normalization pool all channels in a local spatial region about the unit. Giraldo & Schwartz (2019) explored a flexible, stimulus-dependent form of divisive normalization across space, based on the GSM, with learned parameters, that was added to the 2nd layer of a pretrained Alexnet to model contextual modulation in V1. Burg et al. (2021) implemented a learnable form of divisive normalization in a model trained end-to-end to replicate spike counts of V1 neurons. The model included a single convolutional layer of 32 filters with batch normalization, followed by divisive normalization and a readout layer. The filters developed with no topology, that is, normalization weights were learned between each directed pair of channels.

The work most similar to our own was done independently by Pan et al. (2021). They considered a form of divisive normalization in which channels were partitioned into groups of 8, which normalized one another, followed by an affine transformation. They also considered adding a spatially local normalization pool restricted to a unit's own channel. For every unit, the affine transformations and the weights from every member of its normalization pool were learned. They also considered the divisive normalization (DN) of Ren et al. (2016). They found that, compared to canonical normalizations, their channel normalization, but not the additional spatial normalization nor DN, improved performance on CIFAR-10 in shallow convolutional nets but not in deeper ones (4-5 or more layers). They attributed the improved performance on shallow networks to their channel normalization making activity distributions in early layers more Gaussian, Their channel normalization also showed some improvement over canonical normalizations for AlexNet on ImageNet. Our normalization pool size is learned (determined by the space constant of an exponential kernel), we examine pairings of divisive and canonical normalization which we find important to avoid failures to learn of divisive alone, and we examine several properties – receptive fields and their Fourier power, manifold capacity, sparsity – that characterize ways in which the normalizations change representations.

3 METHODS

Architecture. We studied 8 models, each a variant of AlexNet (5 convolutional layers and 3 fully connected layers; Krizhevsky et al., 2012) with different normalization layers, with a Kaiming He initialization (He et al., 2015) and without pytorch local response normalization (LRN). The filters are 11x11 for ImageNet and 3x3 for CIFAR-100 in the first layer, 3x3 in all subsequent layers. For the models with normalization (Divisive, Batch, Group, Layer), we place it after each ReLU in

the convolutional layers. For combined models, divisive normalization is followed by a canonical normalization (Batch, Group, Layer).

Normalization Formalisms. For divisive normalization, the channels in a given layer develop topologically arranged on a line. Given n channels in a layer, numbered from 1 to n, we let $a_c(x)$ be the rectified output of the convolution with the filter of channel c at 2D spatial position x. We take the unnormalized activation of this channel to be $a_c(x)^2$. We then divisively normalize, using as a "normalization pool" an exponentially weighted sum of the unnormalized activations of nearby channels at the same spatial position, to yield the unit's normalized activity $b_c(x)$:

$$b_c(x) = \frac{a_c(x)^2}{\left(k\left(1 + \frac{\alpha}{\lambda}\sum_{j=-4\lambda}^{4\lambda} a_{c+j}(x)^2 e^{-|j|/\lambda}\right)\right)^{\beta}} \tag{1}$$

Here, β, α, k and λ are all learnable parameters, learned independently for each convolutional layer.

We also considered models in which each divisive normalization was followed by a "canonical" normalization: either batch, group, or layer. In all three, the normalization is of the form:

$$\tilde{z}_{n,j} = \gamma \frac{z_{n,j} - \mathbb{E}\left[z_n\right]}{\sqrt{Var[z_n] + \epsilon}} + \beta \tag{2}$$

Here γ and β are learnable parameters. The subscript n denotes the set that is normalized together. For example, in batch normalization, for an input of dimension $N \times c \times H \times W$, in which c is the number of features, H and W the spatial dimensions and N the number of images in a batch, the mean and variance in Eq. 2 are calculated for a given feature across all of space and the whole batch. For layer normalization, the mean and variance are calculated across the spatial and feature dimensions for each image. For group normalization, the feature dimension is divided into 4 equal-sized groups in each layer, and the normalization is done within each group across space for each image.

Hyperparameters. Unless otherwise specified, the learning rate used in the models was .01. Batch sizes were 128. The initial normalization parameters were $\lambda = 10.$, $\alpha = .1$, $\beta = 1.$, $k = 10$, except for the Divisive model with no other normalizations, for which initial $\lambda = 1.$ and $k = 0.5$ to make learning reliable (further discussed in Results). The Weight initialization method followed that of He et al. (2015). That initialization was formulated for ReLU activation functions to keep the expected activation variances constant across layers. We used the same principle for our networks with divisive normalization and arrived at the same weight initialization, and used the same initialization for combined divisive/canonical models. See Appendix A and B for more information.

The CIFAR training and validation images were resized to $32 \times 32 \times 3$ and horizontally flipped; Imagenet training images resized to $224 \times 224 \times 3$ and horizontally flipped; Imagenet validation images resized to $256 \times 256 \times 3$ and center cropped. In both data sets, each color channel was standardized.

4 RESULTS

Top-1 Accuracy. Tables 1-2 show top-1 accuracies at epoch 90 for the various models on ImageNet and CIFAR-100. The models are named by the type(s) of normalization used. For a name with two normalizations, the second normalization was applied immediately after the first, for example DivisiveBatch means divisive and then batch normalization were applied after each convolutional layer and ReLU. NoNorm indicates that none of the normalizations were used, simply a vanilla AlexNet. For ImageNet, these numbers are based on a single trial per model, while CIFAR-100 results show mean±stderr across 30 trials per model. Performance curves for CIFAR-100 (Fig. 4) show that performance differences were relatively stable from the earliest epochs.

For NoNorm and each canonical normalization, addition of divisive normalization almost always improved performance (exception: layer normalization for CIFAR-100). DivisiveBatch showed the best performance. Conversely, adding a canonical normalization almost always improved performance for divisive normalization (exception: Divisive and DivisiveLayer were statistically tied for CIFAR-100) and also improved reliability of learning. The Divisive model (without a canonical normalization) was less able to learn than the others; a parameter search on the divisive normalization parameters found that it learned reliably only for small values of λ and k (see Eq. 1). Applying a canonical

Model	Validation Acc	Training Acc
NoNorm	54.12	49.17
Layer	58.18	54.68
Group	57.05	53.99
Batch	57.87	52.91
Divisive	58.14	54.10
DivisiveBatch	**59.74**	56.15
DivisiveGroup	58.4	**56.2**
DivisiveLayer	58.24	55.03

Table 1: ImageNet Top-1 Accuracies

Model	Validation Acc	Training Acc
NoNorm	$49.45 \pm .072$	$56.00 \pm .04$
Layer	$52.06 \pm .07$	$65.00 \pm .05$
Group	$51.55 \pm .07$	$63.62 \pm .05$
Batch	$53.96 \pm .07$	$65.79 \pm .04$
Divisive	$50.11 \pm .21$	$58.46 \pm .32$
DivisiveBatch	$\mathbf{54.88 \pm .07}$	$\mathbf{66.35 \pm .03}$
DivisiveGroup	$52.75 \pm .15$	$63.92 \pm .05$
DivisiveLayer	$50.18 \pm .11$	$61.74 \pm .10$

Table 2: CIFAR-100 Top-1 Accuracies

Figure 1: Performance curves for validation (left) and training (right) accuracy for each model across 30 trials on the CIFAR-100 dataset. Standard errors are plotted but are too small to see. Dashed curves are the models with a single type of normalization (canonical or divisive), black is the vanilla AlexNet (NoNorm), and solid curves are models with divisive normalization followed by a canonical normalization. Performance order is stable across epochs.

normalization to standardize the activations after the divisive normalization made learning reliable. Additionally, across the DivisiveBatch, DivisiveGroup, and DivisiveLayer models, the divisive parameters quickly evolved to their final values, and were similar between the three different models for a given initial condition (Appendix C). While the models tended to perform better with a larger λ and k when we fixed these parameters (Appendix B), we also found that, when these parameters were learned, the initial divisive parameters chosen did not greatly change performance (Appendix C).

Receptive Fields and Fourier Power. Divisive normalization is a biologically motivated computation, seen throughout the visual cortical stream. Therefore, to better understand how it improves image classification performance, it is informative to study the receptive fields (RFs; i.e., filters) learned by the models. We focus on the 11x11 filters learned for each channel in the first layer of the ImageNet-trained models, which are the filters that are most interpretable and most easily compared to those seen in primary visual cortex. The RFs of the models with divisive normalization show increased long-wavelength (Divisive and DivisiveLayer) or medium-wavelength (DivisiveBatch and DivisiveGroup) Fourier power compared to the other models (Fig. 2). This can be seen in comparing the first 16 of the 96 RFs for the Divisive model (Fig. 3) to those of the NoNorm model (Fig. 4) (RFs for the other models are shown in the Appendix G). Compared to the Divisive model, the NoNorm model RFs have many more irregular and small scale structures, and fewer (and higher-frequency) grating-like RFs resembling the orientation-selective simple cells found in primary visual cortex (*e.g.*, Hubel & Wiesel, 1962). In Appendix I, we plot the layer-wise 1D correlations between feature weights, noting a de-correlation for nearby features in models with divisive normalization.

Replica-based Mean Field Manifold Geometry. When an image classification model is trained, the activity patterns of N neurons for the images in a class form a manifold corresponding to that

Figure 2: The radial Fourier power (*i.e.*, integrated over θ in polar coordinates) averaged over the 96 receptive fields (filters) in layer 1 of AlexNet for each architecture. Columns are red, green, and blue channels respectively. Rows show models with batch (blue lines), group (green lines) and layer (orange lines) respectively; darker color is divisive+canonical, lighter is canonical alone. The purple (Divisive) and black (NoNorm) lines are identical in all three rows of a given column, repeated for comparison with the various divisive+canonical and canonical models. Shading shows standard errors. While the small wavelength (high frequency) power is relatively similar from model to model, the long wavelength power is increased for the Divisive and DivisiveLayer models, while the mid-wavelength power is increased for the DivisiveGroup and the DivisiveBatch models.

class in the N-dimensional space of activities. DiCarlo et al. (2012) argued that, in a feed-forward convolutional neural network, these object manifolds are hierarchically untangled such that, at higher layers, the individual classes are more linearly separable. A well performing model should produce object manifolds that are readily separable and therefore distinguishable. The potential for a model to distinguish P manifolds can be quantified as a function of its system load, $\alpha = \frac{P}{N}$, where P is the number of object manifolds and N is the number of neurons (Gardner, 1988; Chung et al., 2018). The classification capacity of a neural network is the maximum load for which most dichotomies of manifolds are linearly separable. Thus, a model that has a higher performance on a specific dataset should have a higher classification capacity of object manifolds.

Using mean field theory methods developed by Chung et al. (2018), we measured the capacity of object manifolds and their geometric properties [1]. This depends on three quantities that describe the structure of the neural manifolds:

- **Radius**: The average size of a neural manifold across the classes considered.
- **Dimension**: The average embedding dimension of an individual object manifold from the perspective of a linear classification of manifold dichotomies.
- **Correlation**: The average correlation between the centers of the individual class neural manifold representations in state space. A lower correlation means that the individual neural manifolds would be more distinguishable (less entangled).

The manifold capacity – the ability to separate the object manifolds – is larger for smaller radius, dimension, and correlation.

In Figure 5, we plot the manifold capacity and properties for the NoNorm, Divisive, DivisiveBatch, and Batch models (results involving group and layer normalization, and changes in manifold parameters after each individual normalization or convolutional layer, are presented in Appendix D). In the

---

[1]The analysis code used in this work is from `https://github.com/schung039/neural_manifolds_replicaMFT` from prior work by Stephenson et al. (2019).

Figure 3: The receptive fields for each of the 3 channels for the first 16 features (out of 96) in layer one for the Divisive model show many wide-set Gabor-like filters.

Figure 4: The receptive fields for each of the 3 channels for the first 16 features (out of 96) in layer one for the NoNorm model show a wider variety of filters with more irregularity and more small-scale features.

early layers, models using batch and/or divisive normalization, and particularly the Batch model, tend to have lower capacities and higher manifold dimension, radii, and correlation compared to NoNorm. The most notable change is the pronounced jump in correlation between manifold centers at interior ReLU layers. By the fully connected layers, the situation has reversed, with the two models involving divisive normalization having largest manifold capacity and smallest radius and dimensions, followed by the Batch model, with NoNorm last (for correlation, the three normalized models have the same ordering, but NoNorm is smallest). It is intriguing that somehow, by creating early representations with lower capacity and higher-dimensional object manifolds, the network with these normalizations can arrive in the end at a higher-capacity representation with lower-dimensional object manifolds.

Sparsity. Firing in sensory cortex is relatively sparse, with long-tailed activity distributions (Shafi et al., 2007; Hromadka et al., 2008; O'Connor et al., 2010; Barth & Poulet, 2012), particularly for responses to natural stimuli (Froudarakis et al., 2014). Both higher areas of visual cortex and higher layers of AlexNet and other deep nets trained for visual object recognition respond better to stimuli with naturalistic statistics than those without them (Zhuang et al., 2017), and in the deep net higher layers this property is strongly correlated with sparsity of firing and not with any other tested property (Zhuang et al., 2017). Sparseness of neural firing has been postulated to have many functions, including improving discrimination, learning, memory capacity, disentangling and linear readout, and other properties by reducing overlap between activity patterns for different stimuli (*e.g.*, Olshausen & Field, 2004; Ganguli & Sompolinsky, 2012). More generally, by various criteria there is an optimal level of sparsity, such as optimizing a tradeoff between discrimination and generalization (Barak et al., 2013) or optimizing the dimensionality of a representation (Litwin-Kumar et al., 2017).

While there are various measures of sparsity, we use the Gini index, which is designed to capture the kind of sparsity represented by heavy-tailed distributions. The Gini index is a general metric for measuring inequality, typically across countries. It is defined in terms of the Lorenz curve: a graph of the cumulative activations in each layer (or income) as a function of the cumulative % of activations (or incomes) counted, where the activations are arranged from smallest to largest. For the most extreme inequality, the curve would be at zero as the x-axis moves from 0 to 100%, and

Figure 5: The mean field theory manifold capacity is calculated on the 50 least correlated classes (Cohen et al., 2020) for the ImageNet training data, using responses to 100 images randomly selected for each class. Results are shown for the ReLU layers of the NoNorm, DivisiveBatch, Batch, and Divisive models. Vertical grey lines indicate ReLU layers. Error bars denote the standard error across five different samples of these 100 randomly selected images in each class.

Figure 6: The sparsity, as measured by the Gini index (1 = most sparse, 0 = all activations equal), for the validation set of images at epoch 90, for CIFAR-100 models. Results are show for canonical (*e.g.*, Batch; dashed color) and combined divisive-canonical (*e.g.*, Divisive Batch, solid color) models involving the batch norm (blue, left panel), the group norm (green, middle), and the layer norm (orange, right), as well as NoNorm (black) and Divisive (purple) models (repeated in all 3 panels, for comparisons). The vertical purple lines indicate where the divisive normalization occurs for models that have it. Similarly the vertical blue, green, and orange lines indicate where a canonical normalization, *e.g.* batch, group, or layer norm respectively, occurs.

then jump to 1 at 100%, meaning all of the activation is in a single unit. In contrast, the diagonal represents equality of all activations. The Gini index is defined as the area between the diagonal and the Lorenz curve, divided by the area under the diagonal. Thus, it is 1 for the case of most extreme inequality or sparseness, and 0 for complete equality.

We examined the Gini index in each layer for the models trained on CIFAR-100. (Distributions of probabilities of activation are in Appendix F.) The Gini index is slightly increased (*i.e.*, sparsity is increased) by a divisive normalization layer, while canonical normalization layers strongly reduce the Gini index. In the first four layers, after all normalizations, the Divisive and NoNorm models are most sparse, while canonical and combined divisive-canonical models are less so. By the final, fully-connected layers, the canonical models are most sparse (mean probability of activation $\sim 10\%$, Figs. 17-19, Appendix F), followed by combined divisive-canonical and Divisive (probability $\sim 20\%$), and NoNorm model (probability $\sim 30\%$), with the exception that for layer norm, the DivisiveLayer model is equally as sparse as the Layer model. Thus divisive normalization strongly impacts sparsity of activations, generally fixing sparsity of the final representation at an intermediate level ($\sim 20\%$) but producing stronger sparsity when combined with layer norm.

5 DISCUSSION

Divisive normalization is a phenomenological model that captures nonlinear response properties seen ubiquitously in sensory cortical areas (Carandini & Heeger, 2012). Furthermore these properties arise from a simple circuit model (Rubin et al., 2015) given the expansive or supralinear input/output functions seen in cortical neurons in vivo (Miller & Troyer, 2002; Hansel & van Vreeswijk, 2002; Priebe & Ferster, 2008). While many functions have been proposed for these properties, why cortical neurons have them remains an open question. Here we approached that question by asking how a learnable divisive normalization changed performance and the learned representations in an object recognition task.

Channels were learned in a line topology, with the normalization pool of each unit determined by the channels to either side of it weighted by a learnable exponential kernel. We implemented this divisive normalization in all convolutional layers of an AlexNet which was then trained on ImageNet or CIFAR-100. We found that Divisive normalization improves performance on these datasets by a few percent, but it is prone to failing to learn. Because of this, we also studied combined models, in which Divisive normalization was followed by batch, group, or layer norm, which learned much more reliably. A similar stabilizing role biologically might be played by forms of homeostatic plasticity, which keep neural activities in a desired operating range (Turrigiano, 2011) (it could be interesting to substitute homeostatic plasticity for canonical normalizations in the present and similar studies). For batch, group, and no normalization, addition of divisive normalization always improved performance, with the DivisiveBatch model performing best of all studied models.

As measures of how representations are changed by the normalizations, we studied the receptive fields (RFs) of the first layer of the models, analyzed the neural manifold geometry in each layer, and calculated the sparsity in each layer. The Divisive model's first layer RFs have increased power at large wavelengths and the combined models similarly have increased power at large and/or mid-scale wavelengths. More work is needed to determine why this is helpful, but it is intriguing to imagine that this might help the network to respond more to larger scale structure representing shapes and less to smaller scale textures. Convolutional networks primarily rely on texture rather than shape for object recognition, unlike humans, which makes them less robust to a variety of input distortions (Geirhos et al., 2018; Brendel & Bethge, 2019). This can be studied by examining performance of networks with divisive normalization on "stylized" data in which shapes are preserved but textures altered.

This also led us to briefly explore adversarial robustness of our models (Appendix H). Models with divisive normalization (except DivisiveGroup) performed modestly better than the other models against the highest levels of Gaussian noise, and DivisiveGroup performed best for somewhat lower levels, raising the possibility that divisive normalization might improve robustness to image distortions. For two white box, gradient-based attacks, however, divisive normalization in general gave no advantage and in fact generally performed worse than no normalization.

Models with divisive normalization generally keep sparsity of activations of final layers at a level intermediate between those of purely "canonical" normalizations (more sparse) and unnormalized models (less sparse). Surprisingly, the normalized models (except purely divisive) are less sparse than unnormalized ones in earlier layers, which somehow leads to a more sparse final representation. Various tradeoffs can lead to an optimal sparsity level for different computational tasks (Barak et al., 2013; Litwin-Kumar et al., 2017). It will be interesting to understand whether the sparsity levels achieved by the normalizations aid in object recognition or other computations.

As with sparsity, the manifold analysis shows that normalized models produce representations in earlier layers with lower manifold capacity, and correspondingly higher-dimensional, larger, and more correlated object manifolds, yet produce increased capacity and the opposite manifold properties in the final layer. The reasons for these reversing behaviors present an intriguing problem.

Divisive normalization might have advantages that would be better revealed by other tasks, such as object recognition in more cluttered scenes, object segmentation, or analysis of videos. It should be determined whether representations developed with divisive normalization show any improvement in explaining biological representations, *e.g.* using Brainscore (Schrimpf et al., 2018). Normalization across space as well as channels needs to be studied. More generally, we hope this study contributes to a fruitful interaction between studies of deep networks and of neuroscience that benefits both.

REPRODUCIBILITY

All software used in this project will be deposited in a publicly accessible github repository no later than the time of the 2022 ICLR meeting.

REFERENCES

Y. Ahmadian, D. B. Rubin, and K. D. Miller. Analysis of the stabilized supralinear network. Neural Computation, 25:1994–2037, 2013.

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization, 2016.

O. Barak, M. Rigotti, and S. Fusi. The sparseness of mixed selectivity neurons controls the generalization-discrimination trade-off. J Neurosci, 33:3844–3856, 2013.

A. L. Barth and J. F. Poulet. Experimental evidence for sparse firing in the neocortex. Trends Neurosci., 35:345–355, 2012.

Wieland Brendel and Matthias Bethge. Approximating cnns with bag-of-local-features models works surprisingly well on imagenet. CoRR, abs/1904.00760, 2019. URL http://arxiv.org/abs/1904.00760.

Max F. Burg, Santiago A. Cadena, George H. Denfield, Edgar Y. Walker, Andreas S. Tolias, Matthias Bethge, and Alexander S. Ecker. Learning divisive normalization in primary visual cortex. bioRxiv, 2021. doi: 10.1101/767285. URL https://www.biorxiv.org/content/early/2021/03/08/767285.

M. Carandini and D. J. Heeger. Normalization as a canonical neural computation. Nat. Rev. Neurosci., 13:51–62, 2012.

SueYeon Chung, Daniel D. Lee, and Haim Sompolinsky. Classification and geometry of general perceptual manifolds. Phys. Rev. X, 8:031003, Jul 2018. doi: 10.1103/PhysRevX.8.031003. URL https://link.aps.org/doi/10.1103/PhysRevX.8.031003.

R. Coen-Cagli, P. Dayan, and O. Schwartz. Cortical Surround Interactions and Perceptual Salience via Natural Scene Statistics. PLoS Comput Biol, 8:e1002405, 2012.

R. Coen-Cagli, A. Kohn, and O. Schwartz. Flexible gating of contextual influences in natural vision. Nat Neurosci, 18:1648–1655, 2015.

Uri Cohen, SueYeon Chung, Daniel D Lee, and Haim Sompolinsky. Separability and geometry of object manifolds in deep neural networks. Nature communications, 11(1):1–13, 2020.

J. DiCarlo, D. Zoccolan, and N. Rust. How does the brain solve visual object recognition? Neuron, 73:415–434, 2012.

R. Echeveste, L. Aitchison, G. Hennequin, and M. Lengyel. Cortical-like dynamics in recurrent circuits optimized for sampling-based probabilistic inference. Nat Neurosci, 23:1138–1149, 2020.

E. Froudarakis, P. Berens, A. S. Ecker, R. J. Cotton, F. H. Sinz, D. Yatsenko, P. Saggau, M. Bethge, and A. S. Tolias. Population code in mouse V1 facilitates readout of natural scenes through increased sparseness. Nat Neurosci, 17:851–857, 2014.

S. Ganguli and H. Sompolinsky. Compressed sensing, sparsity, and dimensionality in neuronal information processing and data analysis. Annu Rev Neurosci, 35:485–508, 2012.

E Gardner. The space of interactions in neural network models. Journal of Physics A: Mathematical and General, 21(1):257–270, jan 1988. doi: 10.1088/0305-4470/21/1/030. URL https://doi.org/10.1088/0305-4470/21/1/030.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A. Wichmann, and Wieland Brendel. Imagenet-trained cnns are biased towards texture; increasing shape bias improves accuracy and robustness. CoRR, abs/1811.12231, 2018. URL http://arxiv.org/abs/1811.12231.

W. S. Geisler and D. G. Albrecht. Cortical neurons: isolation of contrast gain control. Vis. Res., 32:1409–1410, 1992.

L. G. S. Giraldo and O. Schwartz. Integrating Flexible Normalization into Midlevel Representations of Deep Convolutional Neural Networks. Neural Comput, 31:2138–2176, 2019.

Ian J. Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples, 2015.

D. Hansel and C. van Vreeswijk. How noise contributes to contrast invariance of orientation tuning in cat visual cortex. J. Neurosci., 22:5118–5128, 2002.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification. CoRR, abs/1502.01852, 2015. URL http://arxiv.org/abs/1502.01852.

D. J. Heeger. Normalization of cell responses in cat striate cortex. Vis. Neurosci., 9:181–198, 1992.

T. Hromadka, M. R. Deweese, and A. M. Zador. Sparse representation of sounds in the unanesthetized auditory cortex. PLoS Biol., 6(1):e16, 2008.

D. H. Hubel and T. N. Wiesel. Receptive fields, binocular interaction and functional architecture in the cat's visual cortex. J. Physiol., 160:106–154, 1962.

S. Ioffe and C. Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. arXiv:1502.03167 [cs.LG], 2015.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. Imagenet classification with deep convolutional neural networks. In F. Pereira, C. J. C. Burges, L. Bottou, and K. Q. Weinberger (eds.), Advances in Neural Information Processing Systems 25, pp. 1097–1105. Curran Associates, Inc., 2012.

A. Litwin-Kumar, K. D. Harris, R. Axel, H. Sompolinsky, and L. F. Abbott. Optimal Degrees of Synaptic Connectivity. Neuron, 2017.

K. D. Miller and T. W. Troyer. Neural noise can explain expansive, power-law nonlinearities in neural response functions. J. Neurophysiol., 87:653–659, 2002.

D. H. O'Connor, S. P. Peron, D. Huber, and K. Svoboda. Neural activity in barrel cortex underlying vibrissa-based object localization in mice. Neuron, 67:1048–1061, 2010.

B. A. Olshausen and D. J. Field. Sparse coding of sensory inputs. Curr Opin Neurobiol, 14:481–487, 2004.

Xu Pan, Luis Gonzalo Sánchez Giraldo, Elif Kartal, and Odelia Schwartz. Brain-inspired weighted normalization for cnn image classification. bioRxiv, 2021. doi: 10.1101/2021.05.20. 445029. URL https://www.biorxiv.org/content/early/2021/05/22/2021.05.20.445029.

N. J. Priebe and D. Ferster. Inhibition, spike threshold and stimulus selectivity in primary visual cortex. Neuron, 57:482–497, 2008.

Jonas Rauber, Wieland Brendel, and Matthias Bethge. Foolbox: A python toolbox to benchmark the robustness of machine learning models. In Reliable Machine Learning in the Wild Workshop, 34th International Conference on Machine Learning, 2017. URL http://arxiv.org/abs/1707.04131.

Jonas Rauber, Roland Zimmermann, Matthias Bethge, and Wieland Brendel. Foolbox native: Fast adversarial attacks to benchmark the robustness of machine learning models in pytorch, tensorflow, and jax. Journal of Open Source Software, 5(53):2607, 2020. doi: 10.21105/joss.02607. URL https://doi.org/10.21105/joss.02607.

Mengye Ren, Renjie Liao, Raquel Urtasun, Fabian H. Sinz, and Richard S. Zemel. Normalizing the normalizers: Comparing and extending network normalization schemes. CoRR, abs/1611.04520, 2016. URL http://arxiv.org/abs/1611.04520.

D. B. Rubin, S. D. Van Hooser, and K. D.. Miller. The stabilized supralinear network: A unifying circuit motif underlying multi-input integration in sensory cortex. Neuron, 85:402–417, 2015.

Martin Schrimpf, Jonas Kubilius, Ha Hong, Najib J. Majaj, Rishi Rajalingham, Elias B. Issa, Kohitij Kar, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, Daniel L. K. Yamins, and James J. DiCarlo. Brain-score: Which artificial neural network for object recognition is most brain-like? bioRxiv, 2018. doi: 10.1101/407007. URL https://www.biorxiv.org/content/early/2018/09/05/407007.

O. Schwartz and E. P. Simoncelli. Natural signal statistics and sensory gain control. Nat Neurosci, 4: 819–825, 2001.

M. Shafi, Y. Zhou, J. Quintana, C. Chow, J. Fuster, and M. Bodner. Variability in neuronal activity in primate cortex during working memory tasks. Neuroscience, 146:1082–1108, 2007.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition, 2015.

Cory Stephenson, Jenelle Feather, Suchismita Padhy, Oguz Elibol, Hanlin Tang, Josh McDermott, and SueYeon Chung. Untangling in invariant speech recognition. In NeurIPS, 2019.

G. Turrigiano. Too many cooks? Intrinsic and synaptic homeostatic mechanisms in cortical circuit refinement. Annu. Rev. Neurosci., 34:89–103, 2011.

Dmitry Ulyanov, Andrea Vedaldi, and Victor S. Lempitsky. Instance normalization: The missing ingredient for fast stylization. CoRR, abs/1607.08022, 2016. URL http://arxiv.org/abs/1607.08022.

Yuxin Wu and Kaiming He. Group normalization. In ECCV, 2018.

C. Zhuang, Y. Wang, D. Yamins, and X. Hu. Deep Learning Predicts Correlation between a Functional Signature of Higher Visual Areas and Sparse Firing of Neurons. Front Comput Neurosci, 11:100, 2017.

Part I

Appendix

A INITIALIZATIONS

We utilize a Kaiming He initialization (He et al., 2015). The traditional Kaiming He initialization is formulated for ReLU activation functions by calculating the variance of the output for a layer and then obtaining values for the initial weights such that the network will remain stable. In the original formulation, He utilizes the variance of the response in each layer:

$$\mathbf{y}_l = W_l \mathbf{x}_l + \mathbf{b}_l$$

Similar to the original He paper, we take $\mathbf{b}_l$ to be 0 for all $b'_l s$. Additionally, w_l and x_l are independent of one another and the y_l, w_l and x_l variables are random variables.

Then they pass $\mathbf{y}_l$ through a ReLU function denoted as:

$$\mathbf{x}_l = f(\mathbf{y}_{l-1})$$

where in the initial He formulation, $f(\cdot)$ is the rectifying function, $max(0, \mathbf{y}_{l-1})$. In our formulation, instead of a ReLU, the function goes through the divisive normalization after the ReLU.

$$\mathbf{x}_l = f(\mathbf{y}_{l-1}) = \frac{max(0, \mathbf{y}_{l-1})_c^2}{\left(k(1 + \frac{\alpha}{\lambda} \sum_{j=1}^{N} max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda})\right)^{\beta}}$$

The original He derivation does the following: It takes the variance of y_l, taking y_l and w_l to be mean zero.

$$Var[y_l] = n_l Var[w_l x_l]$$
$$Var[y_l] = n_l(\mathbb{E}[w_l^2 x_l^2] - \mathbb{E}[w_l x_l])^2)$$
$$Var[y_l] = n_l(\mathbb{E}[w_l^2]\mathbb{E}[x_l^2] - \mathbb{E}[w_l x_l])^2)$$

Here we can rewrite and substitute $\mathbb{E}[x_l^2] = Var[x_l] + \mathbb{E}[x_l]^2$ and $\mathbb{E}[w_l^2] = Var[w_l] + \mathbb{E}[w_l]^2$

$$Var[y_l] = n_l((Var[x_l] + \mathbb{E}[x_l]^2)(Var[w_l] + \mathbb{E}[w_l]^2) - \mathbb{E}[w_l x_l]^2)$$
$$Var[y_l] = n_l(Var[x_l]Var[w_l] + Var[w_l]\mathbb{E}[x_l]^2 + Var[x_l]\mathbb{E}[w_l]^2 + \mathbb{E}[x_l]^2\mathbb{E}[w_l]^2 - \mathbb{E}[w_l x_l]^2)$$
$$Var[y_l] = n_l(Var[w_l]Var[x_l] + Var[w_l]\mathbb{E}[x_l]^2 + Var[x_l]\mathbb{E}[w_l]^2)$$
$$Var[y_l] = n_l(Var[w_l](\mathbb{E}[x_l^2] - \mathbb{E}[x_l]^2) + Var[w_l]\mathbb{E}[x_l]^2)$$
$$Var[y_l] = n_l(Var[w_l](\mathbb{E}[x_l^2]))$$

Above we used the independence of the variables x_l and w_l to say $\mathbb{E}[w_l x_l]^2 = \mathbb{E}[w_l]^2\mathbb{E}[w_l]^2$. Additionally, $\mathbb{E}[w_l] = 0$ as the weights are initialized with mean 0. In the initial He form, $x_l = max(0, y_{l-1})$, which as a ReLU does not have mean 0, but y_{l-1} does have mean zero. Using symmetry of the ReLU function, we can see that $\mathbb{E}[x_l] = \frac{1}{2}Var[y_{l-1}]$. :

By still modifying the variance of y_l to consider our the added stages of going through the divisive normalization function

$$Var[y_l] = n_l Var[w_l x_l]$$
$$Var[y_l] = n_l Var[w_l]Var[x_l]$$
$$Var[y_l] = n_l Var[w_l]Var[\frac{max(0, \mathbf{y}_{l-1})_c^2}{k^{\beta}\left(1 + \frac{\alpha}{\lambda}\sum_{j=1}^{N} max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^{\beta}}]$$

The purpose of this formulation is ultimately to get an expression for $Var[w_l]$ such that the weights will not blow up or die out across subsequent layers. Thus, we need to hone in on and simplify the variance of the quotient. Recalling that the variance of a quotient of two random variables x and y is in the form $Var[x/y] = Var[x] + Var[y] - 2Var[x]Var[y]corr(x, y)$ such that

$$Var[\frac{max(0, \mathbf{y}_{l-1})_c^2}{k^\beta \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta}] =$$

$$= Var[max(0, \mathbf{y}_{l-1})_c^2] + Var[k^\beta \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta] -$$

$$2Var[max(0, \mathbf{y}_{l-1})_c^2] \times Var[k^\beta \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta] \times corr(\cdot, \cdot)$$

For our purposes, we will assume the correlation between the numerator and the denominator is small enough to be negligible. (This is still possibly a big assumption because the denominator does have a "self" term, but we are assuming this self term is small relative to the sum of all of the other terms to make the math tenable. This makes a little more sense when we assume large λ.

$$Var[\frac{max(0, \mathbf{y}_{l-1})_c^2}{k^\beta \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta}] =$$

$$= Var[max(0, \mathbf{y}_{l-1})_c^2] + Var[k^\beta \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta]$$

$$= \frac{1}{2}Var[(y_{l-1})_c^2] + Var[k^\beta \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta]$$

Trying to actually take the variance of the second term when β, λ, α and k are all variable parameters, the math becomes intractable. Particularly because any given power of value β will give an intractable binomial expansion. Since this calculation only depends on the initial values of the parameters, we initialize $\beta = 1$.

$$= \frac{1}{2}Var[(y_{l-1})_c^2] + Var[k \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)]$$

Now in order to make the rest of this tractable, we hone in on the second term. The term is calculating the variance of the convolution of the ReLU output with an exponential kernel along the feature dimension.

If we notice that $e^{-|c-j|/\lambda}$ will always be bounded by 1, then we can see there will be an upper bound for the value within the parentheses when considering some maximum activation value for a given layer. The input images have dimensions $H \times W \times N$, where H is the height, W is the width and N. Further, for an exponential probability distribution, 98% of the distribution falls within 4λ of the center. Therefore, it is a reasonable assumption to approximate an upper bound of the variance to be in terms of 4λ neighbors.

$$Var[k \left(1 + \frac{\alpha}{\lambda} \sum_{j=1}^N max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)] \le Var[k \left(1 + \frac{\alpha}{\lambda} 4\lambda max(0, \mathbf{y}_{l-1})_{max}^2\right)]$$

$$\le Var[k \left(1 + 4\alpha max(0, \mathbf{y}_{l-1})_{max}^2\right)]$$

$$\le Var[k \left(1 + \frac{\alpha}{\lambda} N max(0, \mathbf{y}_{l-1})_{max}^2\right)]$$

This upper bound corresponds to using a uniform kernel rather than an exponential kernel in which each of the neighbors would be considered equally important up to N neighbors or more realistically, 4λ neighbors. If the quantity 4α is sufficiently small then this term will drop out when calculating the variance. This bounds the variance of our expression by zero, and since the variance can only be a nonzero term, it is approximately zero. Further noting that $Var[1 + x] = Var[x]$ and $Var[kx] = k^2 Var[x]$, where k is a constant, we can rewrite the variance

$$Var[k\left(1 + \frac{\alpha}{\lambda}\sum_{j=1}^{N} max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)] \le k^2 Var[(1 + 4\alpha max(0, \mathbf{y}_{l-1})_{max}^2)]$$

$$\le k^2 Var[(4\alpha max(0, \mathbf{y}_{l-1})_{max}^2)]$$
$$\le 16k^2\alpha^2 Var[(max(0, \mathbf{y}_{l-1})_{max}^2)]$$
$$\le 16k^2\alpha^2 \frac{1}{2} Var[(\mathbf{y}_{l-1}{}_{max}^2)]$$
$$\le 8k^2\alpha^2 Var[(\mathbf{y}_{l-1}{}_{max}^2)]$$

Thus we can rewrite an approximate upper bound for the variance of the divisive normalization term below:

$$Var[\frac{max(0, \mathbf{y}_{l-1})_c^2}{k^\beta\left(1 + \frac{\alpha}{\lambda}\sum_{j=1}^{N} max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)^\beta}] \approx \frac{1}{2}Var[(y_{l-1})_c^2] + Var[k\left(1 + \frac{\alpha}{\lambda}\sum_{j=1}^{N} max(0, \mathbf{y}_{l-1})_j^2 e^{-|c-j|/\lambda}\right)]$$

$$\le \frac{1}{2}Var[(y_{l-1})_c^2] + 8k^2\alpha^2 Var[(\mathbf{y}_{l-1}{}_{max}^2)]$$

Empirically, we see early in training that the activations after the ReLUs layers for the NoNorm, Divisive, DivisiveBatch and the Batch models are all on the order of 1. Thus, it is reasonable to assume that if we use a small enough α and k upon initialization, then the second term will become negligible relative to the first term so we can approximate the overall $Var[y_l]$:

$$Var[y_l] \approx n_l Var[w_l]\frac{1}{2}Var[(y_{l-1})_c^2]$$

$$Var[y_L] \approx Var[(y_1)_c^2]\left(\Pi_{l=2}^{L}\frac{1}{2}n_l Var[w_l]\right)$$

Using similar arguments made in the Kaiming He initialization, we want to avoid the magnitudes of the input signals from growing unboundedly. Thus, we can approximately set a sufficient condition for stable learning using the Kaiming He initialization bet requiring:

$$\frac{1}{2}n_l Var[w_l] = 1, \forall l$$

This allows us to initialize the weights of the Divisive model to be zero mean with a standard deviation of $\sigma = \sqrt{\frac{2}{n_l}}$

Through this section of the appendix, we have found a set of values for the Divisive normalization parameter such that we can use Kaiming He initialization for the weights when implementing Divisive normalization after each ReLU in AlexNet use the Kaiming He. If we initialize β=1 and have α and k to be reasonably small, we can address the vanishing/exploding gradient problem. Namely, these values for α and k are .1 and .5 respectively. However, despite addressing vanishing/exploding gradient problem, we found the Divisive model does not reliably learn in isolation when placed in all five layers. This helped motivate including the more canonical normalizations such as Batch norm, Group norm and Layer norm after the Divisive normalization layers. The next section disucsses our parameter exploration.

B DIVISIVE NORMALIZATION PARAMETER CHOICES

In the prior section we determined a stable initialization for the divisive parameters to avoid the exploding/vanishing gradient problem by leaning on the Kaiming He initialization. While this derivation required we fix β to be 1.0 and keep α and k small, it left λ free to vary at initialization. Because of this, we explored the parameter space for the Divisive normalization on the CIFAR-100 dataset to determine whether the initial values of these parameters impact learning performance. In particular, we considered initial values for λ of 1, 2, 5, and 10 and for k of .1, .5, 1 and 10. Unfortunately, the Divisive model failed to learn reliably when varying these two parameters, so for the Divisive model we used initial values of 1.0 for λ and 0.5 for k. Varying values beyond these usually did not produce Divisive models that could learn. However, the combined models, in which Divisive normalization was paired with Batch, Layer, or Group normalization, learned for a wide range of initial values. Figures 7, 8, 9 show the validation accuracies of these models for each different parameter pairing of λ and k. Typically, for the DivisiveBatch model, the initial values did not drastically impact performance. However, for the DivisiveGroup model, there seemed to be improved performance for larger k and λ values. Further, the DivisiveLayer model performed a few points better when the initial λ values were larger. The initial k value did not seem to have much of an impact on the DivisiveLayer model. Because of this, all models other than Divisive in the main paper have the same initial values. We chose to initialize k to be 10 and λ to be 10 both on the CIFAR-100 dataset and on ImageNet.

Figure 7: Dependence of performance on initial normalization parameters λ and k for the Divisive-Batch model. Red, orange, blue, and purple indicate initial λ values of 1, 2, 5, and 10 respectively. The solid, dashed, dashdot, and dotted lines correspond to k values of .1, .5, 1 and 10 respectively. The initial value of λ does not obviously impact performance. There appears to be very modest improvement with larger k values.

Figure 8: Dependence of performance on initial normalization parameters λ and k for the DivisiveGroup model. Larger λ values result in a modest performance improvement, as does larger k.

Figure 9: Dependence of performance on normalization parameters λ and k for the DivisiveLayer model. There appears to be a clear preference in the DivisiveLayer model to initialize with a larger λ and k. This improvement is more pronounced relative to the DivisiveGroup model in which a larger λ only gave modest improvement

C DIVISIVE NORMALIZATION PARAMETERS LEARNED

Using the parameter initializations explored in the prior section we plot the resulting normalization parameters that develop. All of the models learn slightly different divisive normalization parameters depending on the initial conditions. The Divisive model did not learn reliably enough for such a parameter search to be informative. However, there are some common trends across the combined models. For example, generally λ and k are relatively stable throughout learning. In contrast, the α and β values change a lot initially and settle to some steady state after about 20 epochs.

In the DivisiveBatch model, the learned α value tends to get larger with a larger initial λ and k. Such a trend is less clear in the DivisiveLayer model. In the DivisiveGroup model, it is less clear. For example, in layers 3 and 5, it appears a larger λ will give a smaller α.

Across all of the models in all of the layers, the β values range from 0 to 2. In the DivisiveBatch and DivisiveGroup models, they tend to be around 1 or less except in the last layer where β gets much larger. In the DivisiveLayer model, the learned β parameter steadily increases across the layers. Meanwhile, the learned α steadily decreases across the layers and then increases again in layer 5. We see similar behavior in the DivisiveBatch model, in which α tends to get smaller regardless of the other parameter initializations but then begins to increase again in layers 4 and 5. For the DivisiveGroup model, the α values tend to be between 0 and 1 throughout all five layers.

Figure 10: The different normalization parameters learned for the DivisiveBatch model over epochs. Each curve represents a slightly different set of initial conditions. Darker lines correspond to a larger initial λ. It is clear that the k values and λ values do not vary much.

Figure 11: The different normalization parameters learned for the DivisiveBatch model over epochs. Each curve represents a slightly different set of initial conditions. Similar to the DivisiveBatch model, the parameters roughly approach a steady state after about 20 epochs.

Figure 12: The different normalization parameters learned for the DivisiveLayer model over epochs. Each curve represents a slightly different set of initial conditions. In layer 3, β is larger for smaller λ and k, but in layer 2 and 5, it modestly gets smaller.

D   NEURAL MANIFOLD ANALYSIS WITH GROUP AND LAYER NORM MODELS

While we only discussed a few of the normalized models for the Replica-based mean field geometry analysis in section 4 (primarily Batch, Divisive, and DivisiveBatch models), the other normalized models exhibit similar behavior. We also include the same results as Figure 5, but showing results after each normalization and convolutional layer rather than only for the ReLU layers. In the combined models, at a given layer, the divisive normalization tends to decrease the capacity or leave it unchanged.

The correlations between the manifolds are much more complex when looking at all of the layers. When only looking at the ReLUs, the normalized models have much higher correlations at the interior layers. However, when considering the convolutional and normalization layers, the normalized models have lower correlations. The convolutional layers increase the correlations between the manifolds, while ReLUs decrease the correlations layer-wise. For normalized models, after going through a convolutional-ReLU pair, the variation in the correlations is still more narrow than the variation in the NoNorm model. In other words, the correlation after a convolutional layer is higher in a NoNorm model relative to a normalized model, but the correlation after the ReLU is lower relative to that in a normalized model.

Figure 13: The mean field theory manifold capacity is calculated on the 50 least correlated classes (Cohen et al., 2020), using responses to 100 images randomly selected for each class, for the ReLU layers of the NoNorm, DivisiveBatch, Batch, and Divisive models. Vertical purple lines indicate where divisive normalization would occur, vertical blue lines indicate where Batch normalization would occur, and vertical grey lines indicate ReLU or convolutional layers. Error bars denote the standard error across five different samples of these 100 randomly selected images in each class. For the models with Batch normalization, there is a consistent jump in number of dimensions that describe the neural manifolds in the early layers. There is also a reduction in capacity in the early layers, more prominently in the Batch model. After each divisive normalization layer in the Divisive model, the correlation is consistently reduced. In the DivisiveBatch model, the divisive normalization layer decreases the correlation in layers 2, 4, and 5. Batch normalization consistently decreases the correlation between the neural manifolds in each layer, while in the Batch model, it consistently increases the correlation.

Figure 14: The mean field theory manifold capacity is calculated on the 50 least correlated classes Cohen et al. (2020) with 100 images randomly selected for each class for the ReLU layers of the NoNorm, DivisiveGroup, Group, and Divisive models. Vertical purple lines indicate where divisive normalization would be present, vertical green lines indicate where Group normalization would be present, and vertical grey lines indicate ReLU or convolutional layers. Error bars denote the standard error across five different samples of these 100 randomly selected images in each class.

Figure 15: The mean field theory manifold capacity is calculated on the 50 least correlated classes Cohen et al. (2020) with 100 images randomly selected for each class for the ReLU layers of the NoNorm, DivisiveLayer, Layer, and Divisive models. Vertical purple lines indicate where divisive normalization would be present, vertical orange lines indicate where Layer normalization would be present, and vertical grey lines indicate ReLU or convolutional layers. Error bars denote the standard error across five different samples of these 100 randomly selected images in each class.

E COMPARISON BETWEEN THEORETICAL AND EMPIRICAL MANIFOLD CAPACITY

The manifold capacity reported in section 4 is that calculated using a replica-based mean field theory. The manifold capacity can be also measured empirically with a bisection search to find a critical number of features such that the fraction of linearly separably manifold dichotomies is close to 1/2 Chung et al. (2018); Cohen et al. (2020). As a sanity check, Figure 16 plots the mean field theory capacity calculations relative to the empirically calculated manifold capacity.

Figure 16: Left shows the Mean Field Theory (MFT) capacity plotted relative to the simulation capacity values layer by layer. The black line is the unity line. The second plot shows the layer-wise MFT capacities with the standard error plotted for each ReLU in the network. The third plot shows the layer-wise simulation capacities plotted for each ReLU. Deviations from the simulation capacity in the MFT capacity plot could indicate real changes in the underlying neural manifold geometry.

F   SPARSITY OF ACTIVATION

In the main text we presented the Gini index as a measure of sparsity of the distribution of activations. Here we present the full activity distributions across layers for models involving batch (figure 17), group (figure 18) and layer (figure 19) normalization. In the main text we defined the Gini index in terms of the Lorenz curve. It is worth noting that an equivalent definition of the Gini index for n different activities a_i, $i = 1, \ldots, n$ in a given layer is given by:

$$G = \frac{\sum_{i=1}^{n} \sum_{j=1}^{n} |a_i - a_j|}{2n \sum_{j=1}^{n} a_j}$$

Figure 17: Distribution of activities for the validation set of images at epoch 90, for CIFAR-100 models involving batch normalization, along with the divisive and NoNorm models: Batch (lighter blue), DivisiveBatch (darker blue), Divisive (purple), NoNorm (black).

Figure 18: Distribution of activities for the validation set of images at epoch 90, for CIFAR-100 models involving group normalization, along with the divisive and NoNorm models: Group (lighter green), DivisiveGroup (darker green), Divisive (purple), NoNorm (black).

Figure 19: Distribution of activities for the validation set of images at epoch 90, for CIFAR-100 models involving layer normalization, along with the divisive and NoNorm models: Layer (lighter orange), DivisiveLayer (darker orange), Divisive (purple), NoNorm (black).

For each neuron, we calculate the average probability of activation for all images in the validation set for CIFAR-100. We then plot the distribution of these probabilities for each layer. This is plotted for the activations corresponding to the last of: the ReLU; the divisive normalization; and the canonical (batch, group, layer) normalization.

G RECEPTIVE FIELDS

We plot the first 25 features and each model to have a closer look at the characteristics of the receptive fields. There is a slightly wider range of intensity for the receptive fields in the Divisive model relative to the NoNorm model. For the form, the values of the receptive fields rang in values from -.96 to 1.18, whereas the latter range from -.79 to +.94. Visually, it is clear the Gabor-like receptive fields are wider field and have lower frequency oscillations than those of the NoNorm model. There are fewer small-scale structures in the Divisive model receptive fields.

Perhaps unsurprisingly from the Fourier analysis, there are still small scale fluctuations and structure from the DivisiveBatch and the Batch models in their receptive fields. Recall the Fourier modes were larger for mid to small scale structure in the combined and canonical models. Interestingly, the Batch model appears to have more amorphous and Gaussian-like receptive fields as opposed to Gabor-like. While there are still some small-scale structures, there are more small-scale structures in the DivisiveBatch mode receptive fields.

Figure 20: The receptive fields for the first 25 features of the Divisive model. They are clearly wide field Gabor-like receptive fields of various orientations in most channels. Some are more amorphous or even Gaussian-like.

Figure 21: For the first 25 features of the receptive fields in the NoNorm model, there are more small scale fluctuations that are not as prevalent in the receptive fields of the normalized models.

Figure 22: For the first 25 features of the receptive fields in the DivisiveBatch model, there are more small scale fluctuations than those seen in the Divisive model. This could mean that the DivisiveBatch model, while it performs better in accuracy, may not be filtering out small scale fluctuations as well.

Figure 23: The first 25 features of the receptive fields in the Batch model. There are more rounded receptive fields that appear Gaussian-like. The larger structures could be more large-scale edge detectors.

H ADVERSARIAL ATTACKS

Neural network performance can be drastically reduced with very simple modifications to an image known as adversarial examples. Such examples can take two different forms: white box and black box. White box "attacks" are images which have some information (such as the gradients) about the network that is used to create adversarial examples that disrupt the performance. Black box "attacks" have no information about the model. For example, additive Gaussian noise is a black box attack since the noise added to the images is randomly generated regardless of any of the weights or other parameters of the network.

As a beginning exploration of the performance of the various normalizations against adversarial attacks, we tested the models against three different adversarial attacks: two white box attacks, Projective Gradient Descent (PGD) and Fast Gradient Sign Method (FGSM) Goodfellow et al. (2015); and one black box attack, L2 Additive Gaussian Noise (Figs. 24-26). We did this using the FoolBox package developed by Rauber et al. (2020; 2017), The L2 Additive Gaussian noise adds Gaussian noise with a given L2 size (*i.e.*, standard deviation) to the input. FGSM adds noise to the input with a given L2 size that corresponds to the direction of the gradient of the loss function with respect to the data. The PGD method is similar in that it aims to find a perturbation to the pixel that maxmimizes the loss.

While it is hard to generalize from these limited studies, a few results are notable. The Layer model is the most robust of the models in the sense that it is the only model that outperforms the NoNorm model for all three models for (almost) all values of attack strengths (all but the strongest Gaussian noise attack). The models with divisive normalization (except DivisiveGroup) are the most robust against the strongest Gaussian noise. They generally do not perform well against white box models.

Figure 24: **Projective gradient descent (PGD) attacks**: Using batch sizes of 64, the inputs were given perturbations of L2 norm ϵ in the direction of the gradient of the loss function with respect to the input. The Layer model is the most robust. Models with divisive normalization tend to be the least robust.

Figure 25: **Fast Gradient Sign Method (FGSM) attacks**: Similarly to the PGD attack, ϵ measures the strength of the attack. Models with divisive normalization perform poorly relative to NoNorm, except for the DivisiveGroup model for a range of stronger attacks. The most robust models are Layer (weaker attacks) and Batch (stronger attacks).

Figure 26: **L2 Additive Gaussian Noise attack**: Using batch sizes of 64, the inputs were perturbed by random Gaussian noise of standard deviation ϵ. For the largest perturbations, most of the models with Divisive normalization (Divisive, DivisiveBatch, DivisiveLayer) are more robust than the other models. For somewhat weaker perturbations, DivisiveGroup is the most robust of the models.

I CORRELATIONS

For the models trained on ImageNet, we examine the correlations (correlation coefficient; cosine of the angle between the vectors) between features as a function of the distance between them along the feature dimension (Figs. 27-29). This can provide insight into the scale of the impact that Divisive normalization has on developing features, and also reveals some more global effects of the different normalizations. We saw similar behavior for the models trained on CIFAR-100 (not shown).

In any of the models with Divisive normalization, there tends to be an anti-correlation induced for nearby neighbors in the first four layers, generally most strongly for the combined divisive/canonical models. That is, features that suppress one another through normalization tend to develop to be anticorrelated. In Layer 5, the DivisiveBatch model shows a weakening, and the DivisiveGroup and DivisiveLayer models a strengthening, of positive correlations between nearby features.

In addition, the combined divisive/canonical models tend to globally decorrelate features, so that correlation is less across all distances than for the other models. This is true in most layers of all the models. For example, for the batch-norm models (figure 27), the DivisiveBatch model has globally weaker correlations than the other models in all layers except layer 1. Furthermore, the models with the canonical normalizations (Batch, Group, Layer) tend to globally have the most positive correlations (for Batch and Group, particularly for layers 2 and 5; for Layer, for layer 5).

Figure 27: The mean 1D pairwise correlations between features, as a function of the distance between them in the feature dimension, for each convolutional layer, for the DivisiveBatch (Blue,Dashed), Batch (Blue), Divisive (Purple), and NoNorm (Black) models. Shaded regions indicate the standard error of the pairwise correlations. Fluctuations in the correlations grow significantly for further distances as the sample size decreases. This is because many of these layers only have 256 or 384 features, so for correlation distances of 250+ there are very few pairs.

Figure 28: The mean 1D pairwise correlations between features, as a function of the distance between them in the feature dimension, for each convolutional layer, for the DivisiveGroup (Green,Dashed), Group (Green), Divisive (Purple), and NoNorm (Black) models. Otherwise as in figure 27.

Figure 29: The mean 1D pairwise correlations between features, as a function of the distance between them in the feature dimension, for each convolutional layer, for the DivisiveLayer (Orange,Dashed), Layer (Orange), Divisive (Purple), and NoNorm (Black) models.