UNIVERSALITY OF DEEP NEURAL NETWORK LOTTERY TICKETS: A RENORMALIZATION GROUP PERSPECTIVE

ABSTRACT

Foundational work on the Lottery Ticket Hypothesis has suggested an exciting corollary: winning tickets found in the context of one task can be transferred to similar tasks, possibly even across different architectures. While this has become of broad practical and theoretical interest, to date, there exists no detailed understanding of why winning ticket universality exists, or any way of knowing *a priori* whether a given ticket can be transferred to a given task. To address these outstanding open questions, we make use of renormalization group theory, one of the most successful tools in theoretical physics. We find that iterative magnitude pruning, the method used for discovering winning tickets, is a renormalization group scheme. This not only opens the door to a wealth of existing numerical and theoretical tools, some of which we leverage to examine winning ticket universality in large scale lottery ticket experiments, but additionally sheds new light on the success iterative magnitude pruning has found in the field of sparse machine learning.

1 INTRODUCTION

The lottery ticket hypothesis (LTH) for deep neural networks (DNNs) proposes that DNNs contain sparse subnetworks that can be trained in isolation and can reach performance that is equal to, or better, than that of the full DNN in the same number of training iterations (Frankle & Carbin, 2019; Frankle et al., 2020). These subnetworks are called winning lottery tickets. The LTH has provided new insight into the success of dense DNNs, suggesting a key role for the emergence of winning tickets with increasing sie, reminiscent of the maxim "more is different" (Anderson, 1972). In recent years, researchers have found an intriguing corollary: winning tickets found in the context of one task can be transferred to related tasks (Mehta, 2019; Morcos et al., 2019; Soelen & Sheppard, 2019; Chen et al., 2020a; Gohil et al., 2020; Chen et al., 2021a; Sabatelli et al., 2021), possibly even across different architectures (Chen et al., 2021c). In addition to having applications of practical interest, these results imply that winning tickets can be used to study how tasks are "similar" and which features of said tasks are similarly "relevant". While exciting, to date there exists no principled understanding of why winning tickets can be transferred between tasks, nor does there exist a way to know, *a priori*, which tasks a given winning ticket can be transferred to. Finally, there is a lack of theoretical work on iterative magnitude pruning (IMP) (Elesedy et al., 2021), the most common method used to find winning tickets.

This is in striking analogy to the state of statistical physics in the early-to-mid–20[th] century. Empirical evidence suggested that disparate systems, governed by seemingly different underlying physics, exhibited the *same*, universal properties near their phase transitions. While heuristic methods provided insight (Kadanoff, 1966), a full theory from first principle on this universality was not realized until the development of the renormalization group (RG) (Wilson, 1971a;b; 1975).

RG theory has not only provided a framework for explaining universal behavior at phase transitions, but also a scheme for grouping systems by that behavior. This classification, introduced via the notion of universality classes, has allowed for a detailed understanding of materials (Tougaard, 1997; Winter & Mours, 1997; Durin & Zapperi, 2000; Bonilla et al., 2010), and provides immediate knowledge as to what other classified systems a given material behaves like.

Figure 1: **The RG and IMP.** Both the RG and IMP are applied iteratively to coarse-grain systems, revealing "relevant" features (left columns). Certain observables are known to have regimes where they follow power-law scaling as the RG and IMP are applied (upper right). In the case of the RG, this scaling, and its universality, is associated with properties of the flow it induces in a certain, abstract space (lower right). The nature of the flow IMP induces, has not been previously studied, but none-the-less similarly exists.

The analogy between RG theory and the universality of winning tickets becomes strengthened under the following consideration. Recently, Rosenfeld et al. (2020) found that when the density (i.e. the percentage of parameters remaining) of a DNN being pruned via IMP is in a certain range, $d_L < d < d_C$, the network's error scales according to the following power law

$$e \sim (d_C - d)^{-\gamma} = \Delta d^{-\gamma}. \tag{1}$$

Similarly, when the temperature of a classical spin system, such as the two-dimensional Ising model, is near, but below, the critical temperature, $t < t_C$, the magnetization scales as

$$m \sim (t_C - t)^{-\beta} = \Delta t^{-\beta}. \tag{2}$$

These similarities hint at a more fundamental connection between the universality present in winning tickets and RG theory (see Fig. 1 and Table 1). Indeed, in this work, we extend the RG theory to show that *IMP is a RG scheme*. By analyzing winning ticket transfer experiments (Chen et al., 2021a), we find that there exists universality in the IMP flow (i.e. the way in which the parameters of the DNN change after each iteration of IMP). Our contributions are the following:

- A theoretical basis for understanding the success of IMP and the transferability of winning tickets;

- Experimental support of the theory in large scale lottery ticket experiments, providing insight into previously known heuristic based results;

- A new set of tools for interrogating and classifying DNN architecture, task, and optimizer triplets.

2 THE RENORMALIZATION GROUP AND ITERATIVE MAGNITUDE PRUNING

The RG operator, $\mathcal{R}$, can be viewed as a method for "coarse-graining". That is, each application of $\mathcal{R}$ replaces local degrees of freedom with a composite of their values. An example of this for the two-dimensional Ising model is shown in the left-hand column Fig. 1, where neighborhoods of four spins are replaced by their mode.

The formal way to study $\mathcal{R}$ is to consider its action on the Hamiltonian (i.e. energy function). For classical spin systems (e.g. the two-dimensional Ising model), $\mathcal{H}$ has the general form

$$\mathcal{H}(\mathbf{k}) = -\sum_i k_1 s_i - \sum_{\langle i,j \rangle} k_2 s_i s_j - ..., \tag{3}$$

where the s_i are the spins of the system (e.g. $s_i \in \{-1, +1\}$), $\langle \cdot, \cdot \rangle$ represents sites on the lattice that are nearest neighbors, and the k_i are the strengths of the different coupling constants (e.g. k_2 is the strength of the nearest neighbor coupling).

Due to the fact that coarse-graining amalgamates spins, the coarse-grained spin system can be viewed as equivalent to the original system, but with a new set of coupling constants. Therefore, the coarse-grained system has a different Hamiltonian, which is given by

$$\mathcal{R}\mathcal{H}(\mathbf{k}) = \mathcal{H}(\mathcal{T}\mathbf{k}) = \mathcal{H}(\mathbf{k}'), \tag{4}$$

where $\mathbf{k}'$ is the new set of couplings determined by the operator $\mathcal{T} : \mathbb{R}^K \to \mathbb{R}^K$. Here K is the maximum number of couplings considered, usually introduced for convenience to keep the considered operators finite.

The RG can be applied iteratively, defining a flow through the function space of Hamiltonians, with an associated flow in the space of coupling constants. The latter is commonly referred to as the RG flow. While $\mathcal{R}$ is often a complicated, non-linear function, $\mathcal{T}$ can be linearized near fixed points of the flow (Goldenfeld, 2005). It will therefore have eigenvalues greater than, less than, and equal to 1. The flow will grow in the direction of the eigenvectors $\mathbf{v}_r$ with eigenvalues $\lambda_r > 1$ and will shrink along the $\mathbf{v}_i$ for $\lambda_i < 1$. These combinations of coupling constants, or directions, are called **relevant** and **irrelevant**, respectively. A schematic example of these directions, and the general RG flow, is presented in Fig. 1. Thus, by examining the $\mathcal{R}$ associated with a given system, and its flow in the space of coupling constants, it is possible to find which components of the system are necessary for certain macroscopic behavior, and which are not. Systems belonging to a particular universality class, have the same relevant and irrelevant directions.

Interestingly, many of the properties discussed above can be analogously found in iterative magnitude pruning (IMP). To see this, let $\boldsymbol{\theta}$ represent the parameters of a DNN with loss function, $\mathcal{L}(\boldsymbol{\theta})$, and let $\mathcal{I}$ represent a single application of the IMP process. The parameters of the DNN pruned via an application of $\mathcal{I}$ is related to the original DNN by

$$\mathcal{I}\mathcal{L}(\boldsymbol{\theta}) = \mathcal{L}(\mathcal{T}\boldsymbol{\theta}) = \mathcal{L}(\boldsymbol{\theta}'), \tag{5}$$

where the new set of parameters, $\boldsymbol{\theta}'$, are given by an operator $\mathcal{T}$. The similarities between Eqs. 4 and 5 are strong.

We note here that $\mathcal{T}$ is the composition of a masking operator, $\mathcal{M}$, and a refining operator $\mathcal{F}$. That is, $\mathcal{T} = \mathcal{F} \circ \mathcal{M} : \mathbb{R}^N \to \mathbb{R}^N$, where N is the number of parameters of the DNN. $\mathcal{M}$ is defined via the iterative pruning procedure implemented (e.g. pruning based on magnitude). While we are considering IMP here because of its connection to the Lottery Ticket Hypothesis (Frankle & Carbin, 2019; Frankle et al., 2020), there are many other pruning procedures (such as Hessian based pruning (LeCun et al., 1989)), all of which have their own $\mathcal{M}$. Similarly, $\mathcal{F}$ is defined via the refinement procedure used, making it dependent on the choice of optimizer and whether or not the DNN parameters are left alone or "rewound" to their value at a previous point during training (Frankle et al., 2020; Renda et al., 2020).

For n iterations of $\mathcal{I}$, the resulting network is given by

$$\mathcal{I}^n \mathcal{L}(\boldsymbol{\theta}^{(0)}) = \mathcal{L}(\mathcal{T}^n \boldsymbol{\theta}^{(0)}) = \mathcal{L}(\boldsymbol{\theta}^{(n-1)}). \tag{6}$$

Table 1: Analogous quantities in RG and IMP theory.

RG	IMP
Spins (s_i)	Unit activations (a_i)
Coupling constants (k_i)	Parameters (θ_i)
Hamiltonian ($\mathcal{H}[\mathbf{s}, \mathbf{k}]$)	Loss function ($\mathcal{L}[\mathbf{a}, \boldsymbol{\theta}]$)

This defines a trajectory in parameter space (i.e. $\boldsymbol{\theta}^{(0)} \to \boldsymbol{\theta}^{(1)} \to ... \to \boldsymbol{\theta}^{(n-1)}$), which we will refer to as the IMP flow. A schematic illustration of what the IMP might look like is given in Fig. 1. Just as in the case of RG theory, the directions of the IMP flow are determined by the eigenfunctions of $\mathcal{T}$, which grow or shrink exponentially by the magnitude of the associated eigenvalues.

2.1 CONNECTION BETWEEN THE RG AND STANDARD LTH FRAMEWORKS

Before we formally show that IMP is an RG scheme, we discuss how the standard theory that has emerged from studying the lottery ticket hypothesis (LTH) is related to RG theory.

In the familiar picture, the success of winning tickets is attributed to the surviving sparse DNN being able to find a local minima in the loss landscape (Frankle & Carbin, 2019; Frankle et al., 2020). This may be possible because the training of DNNs via stochastic gradient descent (SGD) appears to be rapidly confined to a low-dimensional subspace (Gur-Ari et al., 2018). This implies that the DNN only "feels" changes to a small number of parameters (or linear combinations of parameters) during much of training. Parameters that are not in this low-dimensional subspace can, therefore, be removed with minimal impact. If a sparse DNN is initialized in this subspace (as late rewinding aims to do), then it may be possible for training to find the same local minima as the full DNN (Evci et al., 2020b; Maene et al., 2021).

In this way, the parameters that do not lie in the low-dimensional subspace are irrelevant, and repeated applications of IMP are expected to remove them. On the other hand, the relevant parameters are those that span this subspace, and their removal changes the local minima the sparse DNN converges to. Therefore, certain observable functions of the DNN, such as error, are expected to be only sensitive to the relevant, but not irrelevant, parameters.

If two models share the same low-dimensional subspace, then they should be able to transfer winning tickets between each other. Note that this transferability of "potential for learning", as opposed to learned representations, is highly non-trivial. Indeed, it was only with the development of the LTH, and then subsequent experimental work, that this was even considered to be a possibility (Frankle & Carbin, 2019; Mehta, 2019; Morcos et al., 2019; Soelen & Sheppard, 2019). It is, in general, difficult to find these subspaces and accurately compare them across experiments. RG theory provides us with tools for finding relevant and irrelevant directions, which do not rely on explicitly constructing the subspace. In particular, RG theory says that if two models have the same eigenfunctions of $\mathcal{T}$ and if they have the same eigenvalues, then they have the same relevant parameters.

2.2 IMP AS AN RG SCHEME

To make the connection between IMP and RG more precise, we show that IMP fits the definition of an RG scheme. To do this, we consider the projection operator, $\mathcal{P}$, that is associated with the RG operator. In the case of classical spin systems, the projection operator maps the spins, s_i, to a coarse-grained spin system, s'_I, such that it satisfies

$$\text{Tr}_{\{s_i\}} \mathcal{P}(s_i, s'_I) \exp\left[\mathcal{H}(\mathbf{k}, s_i)\right] = \exp\left[\mathcal{H}'(\mathbf{k}', s'_I)\right], \tag{7}$$

where $\text{Tr}_{\{s_i\}}$ is the trace operator over the values that the s_i can take (e.g. ± 1) (Goldenfeld, 2005). For the two-dimensional Ising model, it is standard to take

$$\mathcal{P}(s_i, s'_I) = \prod_I \delta\left[s'_I - \text{sign}\left(\sum_{j \in I} s_j\right)\right], \tag{8}$$

where δ is the kronecker delta function and $\text{sign}(\cdot)$ is $+1$ if the argument is positive and -1 if it is negative (Goldenfeld, 2005). Eq. 8 formally defines the mapping from $s_i \to s'_I$ as

$$s'_I = \text{sign}\left(\sum_{j \in I} s_j\right). \tag{9}$$

The projection operator is not unique, but must satisfy the following three properties (Goldenfeld, 2005):

1. $\mathcal{P}(s_i, s_I') \geq 0$;
2. $\mathcal{P}(s_i, s_I')$ respects the symmetry of the system;
3. $\sum_{\{s_I'\}} \mathcal{P}(s_i, s_I') = 1$.

To find a projection operator associated with $\mathcal{I}$, we will take the opposite approach and see if we can find a mapping between the activations of all the units, $\mathbf{a}$, before and after an application of IMP. Without loss of generality, we can consider the activation of unit j in layer i as being defined by

$$a_j^{(i)} = h \left[\sum_k g_k(\boldsymbol{\theta}, \mathbf{a}) \right], \tag{10}$$

where h is the activation function (e.g. ReLu, sigmoid) and the g_k are functions that determine how the different parameters and activations of other units affect $a_j^{(i)}$. For instance, in a feedforward DNN, the impact of the bias of unit j in layer i is given by $g_0 = \theta_j^{(i)}$, and the weighted input from the previous layer is given by $g_1 = \sum_{k=1}^{N^{(i-1)}} \theta_{jk}^{(i)} a_k^{(i-1)}$. Here $N^{(i-1)}$ is the number of units in layer $i-1$.

As discussed above, IMP changes the parameters $\boldsymbol{\theta}$ by the operator $\mathcal{T}$, which is defined by a composition of $\mathcal{M}$ and $\mathcal{F}$. Therefore, the activation of unit j in residual block i, after an application of $\mathcal{I}$, is given by

$$a_j'^{(i)} = h \left[\sum_k g_k(\mathcal{F} \circ \mathcal{M}\boldsymbol{\theta}, \mathbf{a}) \right], \tag{11}$$

and thus, the projection operator associated with $\mathcal{I}$ is

$$\mathcal{P} \left(a_j^{(i)}, a_j'^{(i)} \right) = \prod_{j=1}^{N} \delta \left\{ a_j'^{(i)} - h \left[\sum_k g_k(\mathcal{F} \circ \mathcal{M}\boldsymbol{\theta}, \mathbf{a}) \right] \right\}. \tag{12}$$

We can easily verify that the projection operator defined by Eq. 12 satisfies all three properties needed for an RG projection operator. First, property #1 is satisfied, as Eq. 12 is a product of delta functions. Property #2 is satisfied, as IMP only removes parameters, so the form of $a_j^{(i)}$ given in Eq. 11 remains intact until layer collapse (i.e. when all the weights from one layer to another are removed). There is often a non-trivial regime of density where this does not occur. Finally, for property #3 to be satisfied, we can fix the test and training sample ordering for each epoch (as is done when the random seed is fixed). In such a case, both the mask and refining operators in Eq. 12 are deterministic and $\mathcal{P} \left(a_j^{(i)}, a_j'^{(i)} \right)$ will be unique.

3 RESULTS

3.1 UNIVERSALITY IN THE IMP FLOW

We start by examining the IMP flow. The goal of this analysis is to find the relevant and irrelevant parameters (or more likely, some function of the relevant and irrelevant parameters), so that we can examine whether different pruned models are in the same universality classes. If they are, then, as discussed above, a prediction of the theory would be that they should be able to transfer winning tickets.

While winning tickets do not derive their success purely from their topology (randomly re - initializing parameter values, while maintaining the pruning mask, was shown to lead to a significant decrease in performance by Frankle & Carbin (2019)), the topology nonetheless plays an important role. For instance, we note that the parameters in the first residual block of a ResNet architecture not only impact the activations in that block, but all subsequent blocks. This is in contrast to the last residual block, whose parameters influence only that block. We might, therefore, expect to see differences in how thoroughly each layer gets pruned.

Figure 2: **Universality in the IMP flow.** Two-dimensional slices through the four-dimensional space that the IMP flow lives in for ResNet-50 pre-trained on ImageNet via three different methods: supervised ImageNet training, and self-supervised simCLR and MoCo training. Blue corresponds to a single application of the IMP (density equal to 80%) and red corresponds to 17 applications of the IMP (density to 1.44%).

We consider how the distribution of remaining non-zero parameters changes in each residual block. That is, we considered the functions,

$$M_i(t) = \sum_{j=1}^{N^{(i)}} m_j^{(i)}(t) \bigg/ \sum_{k=1}^{N} m_k(t) \tag{13}$$

where $M_i(t)$ describes the percentage of all non-zero parameters in residual block i at IMP iteration t. The numerator sums run over all $N^{(i)}$ of the elements of the pruning mask restricted to residual block i, $m^{(i)}$. Each $m_j^{(i)} \in \{0, 1\}$. The denominator sums the entire pruning mask, making it equivalent to the number of non-pruned parameters in the entire DNN. Because ResNet-50 has four residual blocks, IMP induces a four-dimensional flow in the space of M_i. To visualize the trajectory, we examined two-dimensional slices. Examples of these are plotted in Fig. 2, for ResNet-50s pre-trained on ImageNet (Huh et al., 2016) via supervised learning and via self-supervised learning with simCLR (Chen et al., 2020b) and MoCo (He et al., 2020). This data comes from experiments done by Chen et al. (2020a). Importantly, we find that the behavior of all three trajectories in these projected spaces to be similar.

If the M_i are eigenfunctions of the IMP operator, then they will scale exponentially with respect to IMP iteration number. That is, $M_i(t + 1) = \lambda_i M_i(t)$, where λ_i is the eigenvalue governing the exponential growth/decay. To find λ_i, all that is needed is a simple inversion, $\lambda_i = M_i(t+1)/M_i(t)$. As long as $M_i(t) \neq 0$, this is well defined and we can estimate λ_i by doing these for each pair of data points. Doing this, we find that ImageNet, simCLR, and MoCo have eigenvalues that are within a standard deviation of each other for all residual blocks (Table 2). In addition, the standard deviation is $< 1\%$, suggesting that it is indeed reasonable to consider the M_i being eigenfunctions of $\mathcal{I}$.

These results suggest that there is universality in the behavior of all three pre-training strategies, despite their seemingly profound differences (i.e. supervised vs. self-supervised training). In particular, all three have one irrelevant direction that is captured by M_4 and three relevant directions that are captured by M_{1-3} (although M_3 could possibly be a marginal direction, i.e. an eigenfunction

Table 2: Computed eigenvalues of the putative eigenfunctions, M_i, for ResNet-50. Red (green) corresponds to those eigenfunctions that are relevant (irrelevant).

Data-set	λ_1	λ_2	λ_3	λ_4
ImageNet	1.13 ± 0.01	1.08 ± 0.01	1.02 ± 0.01	0.96 ± 0.02
simCLR	1.15 ± 0.01	1.09 ± 0.02	1.02 ± 0.01	0.95 ± 0.02
MoCo	1.14 ± 0.01	1.08 ± 0.02	1.01 ± 0.003	0.97 ± 0.01

whose eigenvalue is equal to 1). This universality may be due to the fact that the first few residual blocks learn the low level statistics of the data (Neyshabur et al., 2020), which for natural images scales in specific, non-trivial ways (Ruderman & Bialek, 1994; Saremi & Sejnowski, 2013).

The sensitivity to the first three residual blocks, which are the furthest from the output layer, is in contrast to standard classical spin systems. In the case of the usual two-dimensional Ising model, the RG removes long-range interactions (i.e. couplings between next-nearest neighbors, next next-nearest neighbors, etc.), which are usually assumed, for physical reasons, to be weak. Systems with relevant long-range interactions have been found to have unique properties, such as the existence of a phase transition in one-dimension (Dyson, 1969), which is known not to happen for the standard Ising model. The importance of these long-range interactions may therefore be another interpretation for the success of normalized initializations (e.g. He initialization) for convolutional DNNs, which set parameters in the earlier residual blocks to be larger. This, presumably, is what sets the DNN to be in the long-range interaction regime.

Lastly, we note that the eigenvalues of the M_i's suggest that, if the first three residual blocks had sparse parameters that were properly set, the final residual block could be removed. Given the size of the last block, this could provide considerable savings in energy and memory bandwidth (Han et al., 2015). This also provides us insight into the function of the last residual block, namely that it acts to "clean-up" and add small corrections to the representations found in the first three blocks.

3.2 ELASTIC LOTTERY TICKET HYPOTHESIS

Recent work has extended the notion of tranferability by finding it possible to transform winning lottery tickets found on one DNN, to another with a slightly different architecture (Chen et al., 2021c). In particular, it was found that, for architectures in the same family (e.g. ResNets, VGGs), it was possible to either squeeze (by removing residual blocks) or stretch (by replicating residual blocks) winning tickets so that they could transfer. These results support the "Elastic Lottery Ticket Hypothesis" (E-LTH).

Three results from this study of the E-LTH are particularly noteworthy:

1. The smallest ResNet considered (ResNet-14) had the weakest transferability properties;
2. The more unique residual blocks replicated, the better the performance.
3. Removing the later residual blocks, in the case of shrinking, and replicating the earliest residual blocks, in the case of stretching, lead to best results;

While preliminary hypotheses about the origin of these results were developed by Chen et al. (2021c), involving dynamical systems and unrolled estimation perspectives, detailed theoretical understanding was left to future work. Given that the RG framework developed above led to insight into the nature of the universality of winning tickets in the case of different tasks, we wondered whether it could similarly help to explain the nature of these E-LTH results.

As discussed in Sec. 2, two tasks that have the same IMP flow can transfer winning tickets between themselves. Therefore, we expect that transformed a given winning ticket from one architecture (source) to another (target) will be successful if its IMP flow matches that of the target. In particular, we reasoned that the success (or lack-thereof) may rely on whether the number of relevant, irrelevant, and marginal residual blocks in the target architecture is matched by the transformed ticket.

Table 3: Computed eigenvalues of the eigenfunctions M_i for the first stage of various ResNet archiectures. Red (green) corresponds to those eigenfunctions that are relevant (irrelevant). Any M_i that is within a standard deviation of $\lambda = 1$ is considered marginal, and colored cyan.

ResNet architecture	Stage 1
ResNet-14	1.07
ResNet-20	1.07, 1.07
ResNet-32	0.99, 1.06, 1.06, 1.08
ResNet-44	1.00, 0.98, 1.06, 1.06, 1.05, 1.07
ResNet-56	1.02, 0.98, 1.07, 1.06, 1.05, 1.06, 1.04, 1.08

To test this, we computed the eigenvalues associated with the eigenfunctions M_i, as defined by Eq. 13, for each "normal" residual block of ResNet-14, ResNet-20, ResNet-32, ResNet-44, and ResNet-56 (data from Chen et al. (2021c)). As discussed in the original paper, the down-sampling residual block in each stage was not transformed between winning tickets, so those were not considered. The eigenvalues for the first stage are presented in Table 3.

First, we find that, while the smaller ResNets (ResNet-14 and ResNet-20) have only relevant residual blocks, the larger ones have at least one non-relevant block. This offers a straightforward explanation to why ResNet-14 had particularly poor transferability: using it as the source necessarily leads to the transformed ticket have only relevant residual blocks, which does not match the source tickets structure. Having only relevant residual blocks may make the first stage too sensitive as the depth of the ResNet is increased, leading to poorer performance. Relatedly, we find that replicating a few unique residual blocks (i.e. replicating only block 1 or blocks 1 and 2) can lead to an over representation of either relevant or non-relevant blocks. This mismatch is predicted by the theory to lead to worse transferability.

FInally, we find that most of the non-relevant residual blocks are in the early part of the first stage (four out of five). Therefore, removing the first several blocks when shrinking a winning ticket (e.g. dropping the first four blocks to go from ResNet-56 to ResNet-32), or replicating the last several blocks when stretching a winning ticket (e.g. adding the last two blocks to go from ResNet-32 to ResNet-44), will lead to too many relevant residual blocks. As noted previously, this may make the transformed ticket too sensitive, and thus, have worse performance.

Note that for the later two stages (Table 4 of Appendix 1), the nature of the distribution of eigenvalues is different. In particular, stage 2 has only relevant and marginal directions, and stage 3 has only marginal and non-relevant directions. However, there is consistent evidence for the fact that the number of each type of eigenfunction is related to the three results from the original E-LTH paper (Chen et al., 2021c) we highlighted.

4 DISCUSSION

Inspired by similarities between the current state of the sparse machine learning community and that of the statistical physics community in the early-to-mid–20[th], we found that iterative magnitude pruning (IMP), the principle method used to discover winning tickets, is directly related to the renormalization group (RG). Given that the development of the RG led to a first principled understanding of universality of behavior near phase transitions, and a way in which to characterize materials by such behavior, we reasoned that viewing the IMP from an RG perspective may lead to new insight on the universality of winning tickets (Mehta, 2019; Morcos et al., 2019; Soelen & Sheppard, 2019; Chen et al., 2020a; Gohil et al., 2020; Chen et al., 2021a; Sabatelli et al., 2021).

By viewing IMP as inducing a flow in a certain four-dimensional space, we show that different pre-training methods of ResNet-50 on ImageNet have trajectories with the same properties. In addition to suggesting an underlying reason for winning ticket transferability, these results also provide new perspective on the importance of normalized initializations (e.g. He initialization) and the early residual blocks. Taking the RG framework to recent work which extended the notion of winning ticket universality by finding ways to transform tickets between different architectures, we again found that the IMP flow appeared related to experimentally found results.

A wealth of theory has been developed around RG theory, including a number of numerical and theoretical tools that go beyond what we used here. Given the connection between IMP and the RG proposed in this work, we believe that there is a considerable potential for future collaboration between the two fields. Possible directions of future study include:

- Bringing the RG framework to other sparsficiation methods, like RigL (Evci et al., 2020a), which can also be viewed as RG schemes;
- Bringing the RG framework to study winning tickets beyond computer vision models, such as in natural language processing (Chen et al., 2020a) and lifelong learning (Chen et al., 2021b);
- Computing and classifying systems by their critical exponents (such as γ in Eq. 1). While our attempts to this were promising, having few independent seeds and a scaling function with multiple free parameters (Rosenfeld et al., 2020) led to large differences between critical exponents of systems that displayed qualitatively similar scaling behavior (Appendix B). Bringing methods such as finite scaling () and increasing the number of independent seeds may alleviate this problem;
- Exploring the connection between the RG framework developed here and the work to build effective theories of DNN behavior. (Roberts et al., 2021).

ACKNOWLEDGMENTS

We would like to thank Jonathan Rosenfeld for his advice on performing the fits described by Eq. 14 (Appendix B).

REFERENCES

P. W. Anderson. More is different. *Science*, 177(4047):393–396, 1972. ISSN 0036-8075. doi: 10.1126/science.177.4047.393. URL https://science.sciencemag.org/content/177/4047/393.

Claudia Marcela Bonilla, Julia Herrero-Albillos, Fernando Bartolomé, Luis Miguel García, María Parra-Borderías, and Victorino Franco. Universal behavior for magnetic entropy change in magnetocaloric materials: An analysis on the nature of phase transitions. *Phys. Rev. B*, 81:224424, Jun 2010. doi: 10.1103/PhysRevB.81.224424. URL https://link.aps.org/doi/10.1103/PhysRevB.81.224424.

Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Zhangyang Wang, and Michael Carbin. The lottery ticket hypothesis for pre-trained bert networks. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 15834–15846. Curran Associates, Inc., 2020a. URL https://proceedings.neurips.cc/paper/2020/file/b6af2c9703f203a2794be03d443af2e3-Paper.pdf.

Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Michael Carbin, and Zhangyang Wang. The lottery tickets hypothesis for supervised and self-supervised pre-training in computer vision models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16306–16316, June 2021a.

Tianlong Chen, Zhenyu Zhang, Sijia Liu, Shiyu Chang, and Zhangyang Wang. Long live the lottery: The existence of winning tickets in lifelong learning. In *International Conference on Learning Representations*, 2021b. URL https://openreview.net/forum?id=LXMSvPmsm0g.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 1597–1607. PMLR, 13–18 Jul 2020b. URL http://proceedings.mlr.press/v119/chen20j.html.

Xiaohan Chen, Yu Cheng, Shuohang Wang, Zhe Gan, Jingjing Liu, and Zhangyang Wang. The elastic lottery ticket hypothesis, 2021c.

Gianfranco Durin and Stefano Zapperi. Scaling exponents for barkhausen avalanches in polycrystalline and amorphous ferromagnets. *Phys. Rev. Lett.*, 84:4705–4708, May 2000. doi: 10.1103/PhysRevLett.84.4705. URL `https://link.aps.org/doi/10.1103/PhysRevLett.84.4705`.

Freeman J. Dyson. Existence of a phase-transition in a one-dimensional ising ferromagnet. *Communications in Mathematical Physics*, 12(2):91–107, 1969. doi: 10.1007/BF01645907. URL `https://doi.org/10.1007/BF01645907`.

Bryn Elesedy, Varun Kanade, and Yee Whye Teh. Lottery tickets in linear models: An analysis of iterative magnitude pruning, 2021.

Utku Evci, Trevor Gale, Jacob Menick, Pablo Samuel Castro, and Erich Elsen. Rigging the lottery: Making all tickets winners. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 2943–2952. PMLR, 13–18 Jul 2020a. URL `https://proceedings.mlr.press/v119/evci20a.html`.

Utku Evci, Yani A. Ioannou, Cem Keskin, and Yann Dauphin. Gradient flow in sparse neural networks and how lottery tickets win, 2020b.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. In *7th International Conference on Learning Representations, ICLR 2019, New Orleans, LA, USA, May 6-9, 2019*. OpenReview.net, 2019. URL `https://openreview.net/forum?id=rJl-b3RcF7`.

Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In Hal Daumé III and Aarti Singh (eds.), *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pp. 3259–3269. PMLR, 13–18 Jul 2020. URL `http://proceedings.mlr.press/v119/frankle20a.html`.

Varun Gohil, S. Deepak Narayanan, and Atishay Jain. [Re] One ticket to win them all: generalizing lottery ticket initializations across datasets and optimizers. *ReScience C*, 6(2):4, May 2020. doi: 10.5281/zenodo.3818619. URL `https://zenodo.org/record/3818619/files/article.pdf`.

Nigel Goldenfeld. *Lectures on Phase Transitions and the Renormalization Group*. Levant Books, 2005.

Guy Gur-Ari, Daniel A. Roberts, and Ethan Dyer. Gradient descent happens in a tiny subspace, 2018.

Song Han, Jeff Pool, John Tran, and William Dally. Learning both weights and connections for efficient neural network. In C. Cortes, N. Lawrence, D. Lee, M. Sugiyama, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 28, pp. 1135–1143. Curran Associates, Inc., 2015. URL `https://proceedings.neurips.cc/paper/2015/file/ae0eb3eed39d2bcef4622b2499a05fe6-Paper.pdf`.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 9726–9735, 2020. doi: 10.1109/CVPR42600.2020.00975.

Minyoung Huh, Pulkit Agrawal, and Alexei A. Efros. What makes imagenet good for transfer learning?, 2016.

Leo P. Kadanoff. Scaling laws for ising models near T_c. *Physics Physique Fizika*, 2:263–272, Jun 1966. doi: 10.1103/PhysicsPhysiqueFizika.2.263. URL `https://link.aps.org/doi/10.1103/PhysicsPhysiqueFizika.2.263`.

Yann LeCun, John S. Denker, and Sara A. Solla. Optimal brain damage. In David S. Touretzky (ed.), *Advances in Neural Information Processing Systems 2, [NIPS Conference, Denver, Colorado, USA, November 27-30, 1989]*, pp. 598–605. Morgan Kaufmann, 1989. URL `http://papers.nips.cc/paper/250-optimal-brain-damage`.

Jaron Maene, Mingxiao Li, and Marie-Francine Moens. Towards understanding iterative magnitude pruning: Why lottery tickets win, 2021.

Rahul Mehta. Sparse transfer learning via winning lottery tickets, 2019.

Ari Morcos, Haonan Yu, Michela Paganini, and Yuandong Tian. One ticket to win them all: generalizing lottery ticket initializations across datasets and optimizers. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL `https://proceedings.neurips.cc/paper/2019/file/a4613e8d72a61b3b69b32d040f89ad81-Paper.pdf`.

Behnam Neyshabur, Hanie Sedghi, and Chiyuan Zhang. What is being transferred in transfer learning? In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 512–523. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/0607f4c705595b911a4f3e7a127b44e0-Paper.pdf`.

Alex Renda, Jonathan Frankle, and Michael Carbin. Comparing rewinding and fine-tuning in neural network pruning. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net, 2020. URL `https://openreview.net/forum?id=S1gSj0NKvB`.

Daniel A. Roberts, Sho Yaida, and Boris Hanin. The principles of deep learning theory, 2021.

Jonathan S. Rosenfeld, Jonathan Frankle, Michael Carbin, and Nir Shavit. On the predictability of pruning across scales, 2020.

Daniel L. Ruderman and William Bialek. Statistics of natural images: Scaling in the woods. *Phys. Rev. Lett.*, 73:814–817, Aug 1994. doi: 10.1103/PhysRevLett.73.814. URL `https://link.aps.org/doi/10.1103/PhysRevLett.73.814`.

Matthia Sabatelli, Mike Kestemont, and Pierre Geurts. On the transferability of winning tickets in non-natural image datasets. In *Proceedings of the 16th International Joint Conference on Computer Vision, Imaging and Computer Graphics Theory and Applications - Volume 4: VISAPP,*, pp. 59–69. INSTICC, SciTePress, 2021. ISBN 978-989-758-488-6. doi: 10.5220/0010196300590069.

Saeed Saremi and Terrence J. Sejnowski. Hierarchical model of natural images and the origin of scale invariance. *Proceedings of the National Academy of Sciences*, 110(8):3071–3076, 2013. ISSN 0027-8424. doi: 10.1073/pnas.1222618110. URL `https://www.pnas.org/content/110/8/3071`.

Ryan Van Soelen and John W. Sheppard. Using winning lottery tickets in transfer learning for convolutional neural networks. In *2019 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8, 2019. doi: 10.1109/IJCNN.2019.8852405.

Sven Tougaard. Universality classes of inelastic electron scattering cross-sections. *Surface and Interface Analysis*, 25(3):137–154, 1997.

Kenneth G. Wilson. Renormalization group and critical phenomena. i. renormalization group and the kadanoff scaling picture. *Phys. Rev. B*, 4:3174–3183, Nov 1971a. doi: 10.1103/PhysRevB.4.3174. URL `https://link.aps.org/doi/10.1103/PhysRevB.4.3174`.

Kenneth G. Wilson. Renormalization group and critical phenomena. ii. phase-space cell analysis of critical behavior. *Phys. Rev. B*, 4:3184–3205, Nov 1971b. doi: 10.1103/PhysRevB.4.3184. URL `https://link.aps.org/doi/10.1103/PhysRevB.4.3184`.

Kenneth G. Wilson. The renormalization group: Critical phenomena and the kondo problem. *Rev. Mod. Phys.*, 47:773–840, Oct 1975. doi: 10.1103/RevModPhys.47.773. URL `https://link.aps.org/doi/10.1103/RevModPhys.47.773`.

Horst Henning Winter and Marian Mours. *Rheology of Polymers Near Liquid-Solid Transitions*, pp. 165–234. Springer Berlin Heidelberg, Berlin, Heidelberg, 1997.