Rethinking Class-Prior Estimation for Positive-Unlabeled Learning

Abstract

Given only *positive* (P) and *unlabeled* (U) data, PU learning can train a binary classifier without any *negative* data. It has two building blocks: PU *class-prior estimation* (CPE) and PU classification; the latter has been well studied while the former has received less attention. Hitherto, the distributional-assumption-free CPE methods rely on a critical assumption that *the support of the positive data distribution cannot be contained in the support of the negative data distribution.* If this is violated, those CPE methods will systematically *overestimate* the class prior; it is even worse that we *cannot verify* the assumption based on the data. In this paper, we rethink CPE for PU learning—can we remove the assumption to make CPE always valid? We show an affirmative answer by proposing Regrouping CPE (ReCPE) that builds an *auxiliary* probability distribution such that the support of the positive data distribution is never contained in the support of the negative data distribution. ReCPE can work with any CPE method by treating it as the base method. Theoretically, ReCPE *does not affect* its base if the assumption already holds for the original probability distribution; otherwise, it *reduces the positive bias* of its base. Empirically, ReCPE improves all state-of-the-art CPE methods on various datasets, implying that the assumption has indeed been violated here.

1 Introduction

Positive-unlabeled (PU) learning can date back to 1990s (Denis, 1998; De Comité et al., 1999; Letouzey et al., 2000), and there has been a surge of interest in this learning scenario in recent years because of the difficulty to annotate large-scale datasets (Ren et al., 2014; du Plessis et al., 2014; 2015; Christoffel et al., 2016; Jain et al., 2016; Ramaswamy et al., 2016; Sakai et al., 2018; Kato et al., 2018; Bekker & Davis, 2018; Kwon et al., 2019; Tanielian & Vasile, 2019; Gong et al., 2019). It is also fallen into diffferent applications, such as knowledge-base completion (Galárraga et al., 2015; Neelakantan et al., 2015), text classification (Lee & Liu, 2003; Li & Liu, 2003), and medical diagnosis (Claesen et al., 2015; Zuluaga et al., 2011).

PU Learning can be divided into two different settings based on different data generation processes. The first setting is called *censoring* PU learning (Elkan & Noto, 2008), which follows a one-sample configuration. Specifically, an sample S is randomly drawn from the unlabeled data distribution P_{u}, and a positive sample S_{p} is then distilled from it, i.e., randomly selecting some positive instances contained in the unlabeled data to be the positive sample. The second setting is called *case-control* PU learning (Kiryo et al., 2017). In this setting, a positive sample $S_{\mathrm{p}} = \{x_i\}_{i=1}^{k}$ is randomly drawn from the positive class-conditional distribution $P_{\mathrm{p}} = P(X|Y = 1)$, and an unlabeled sample $S_{\mathrm{u}} = \{x_i\}_{i=k+1}^{n}$ is randomly drawn from the unlabeled data distribution P_{u}. Because case-control PU learning is more general than censoring PU learning (Niu et al., 2016), therefore, we will focus on the setting of case-control PU learning.

Under the setting of case-control PU learning, a lot of classification methods have been proposed (Ren et al., 2014; du Plessis et al., 2014; 2015; Christoffel et al., 2016; Sakai et al., 2018; Kato et al., 2018; Bekker & Davis, 2018; Kwon et al., 2019; Tanielian & Vasile, 2019; Gong et al., 2019). However, the *class-prior estimation* (CPE) (Elkan & Noto, 2008; Jain et al., 2016; Ramaswamy et al., 2016; Christoffel et al., 2016; Kato et al., 2018) has received less attention. Formally, CPE is defined as a problem of estimating $\pi = P(y = 1) \in (0, 1)$ given a sample from the marginal distribution P_{u} and a sample from positive class-conditional distribution P_{p}. The marginal distribution P_{u} is mixed

Figure 1: (a) The unlabeled data distribution P_u and the positive class-conditional distribution P_p are given. (b) Assume that the latent negative class-conditional distribution P_n is fixed, i.e., $0.5P_\mathrm{n}$ is shown by the green curve, and that the class-prior π is 0.5, i.e., $P_\mathrm{u} = 0.5P_\mathrm{n} + 0.5P_\mathrm{p}$. (c) The existing distributional-assumption-free CPE methods will output 0.7 instead of 0.5 because they always output the maximum proportion κ^* of P_u in P_p. (d) Applying the proposed ReCPE method, a auxiliary distribution $P_{\mathrm{p}'}$ will be created and the existing CPE methods will output $\pi' = 0.49$ instead of 0.7 with input $P_{\mathrm{p}'}$ and P_u instead of P_p and P_u.

with both positive and negative class-conditional distributions, i.e., $P_\mathrm{u} = \pi P_\mathrm{p} + (1-\pi)P_\mathrm{n}$. CPE acts as a crucial building block for state-of-the-art PU classification methods, and it is essential to build statistically-consistent PU classifiers (du Plessis et al., 2014; Scott, 2015; Jain et al., 2016; Kiryo et al., 2017). The formulation of these classification methods involves the class-prior π, but π is usually unknown in practice. If π is poorly estimated, the classification accuracy of the state-of-the-art PU classification methods (du Plessis et al., 2014; 2015; Kiryo et al., 2017) could be degraded.

The mixture proportion estimation (MPE) is closely related to CPE (Blanchard et al., 2010; Scott, 2015). In the setting of MPE, there is a mixture distribution

$$F = (1 - \kappa^*)G + \kappa^* H, \tag{1}$$

where H and G are called component distributions. Given the samples randomly drawn from F and H, respectively, MPE aims to estimate the maximum proportion $\kappa^* \in (0, 1)$ of H in F. Thereby, if the maximum proportion κ^* is identical to the class-prior π, the MPE methods can be employed to obtain π by letting P_u and P_p be the mixture distribution F and the component distribution H, respectively; otherwise, the MPE methods cannot be employed. To the best of our knowledge, most of state-of-the-art CPE methods (Blanchard et al., 2010; Liu & Tao, 2015; Scott, 2015; Ramaswamy et al., 2016; Jain et al., 2016) are based on MPE, which do not rely on assumptions that the data are drawn from a given parametric family of probability distributions (i.e., they are distributional-assumption-free methods).

To let these distributional-assumption-free methods can be used to identify class-prior π, κ^* must be identical to the class-prior π. The *irreciblility* assumption (Blanchard et al., 2010) has been proposed to make them identical, which is employed be all these CPE methods implicitly or explicitly, to the best of our knowledge. It assumes that the support of the positive class-conditional distribution P_p is not contained in the support of the negative class-conditional distribution P_n. However, it is strong and hard to be verified in PU learning, since P_n is a latent distribution, such that we do not have any prior knowledge about it. Additionally, since the applications of PU learning are diverse (Hsieh et al., 2019; Bekker & Davis, 2020), it is hard to guarantee that the support of P_p is not in the support of P_n.

If irreciblility assumption cannot be satisfied, the existing distributional-assumption-free CPE methods will suffer from overestimation of π. For example, in Figure 1(a), we show both the unlabeled data distribution P_u and the component distribution P_p. In Figure 1(b), we assume the latent negative class-conditional distribution P_n is fixed as shown in the green color, and the positive class-prior $\pi = 0.5$. In Figure 1(c), we show the existing distributional-assumption-free CPE methods will output the biased class-prior 0.7. It is different from the ground truth 0.5, since the support of P_p is contained in the support of P_n. When the irreciblility assumption is not held, how to improve the estimations of distributional-assumption-free PU learning methods is challenging but useful.

Because the irreciblility assumption is impossible to check without making any assumption on P_n. Thereby, in this paper, we rethink those CPE methods and propose a novel method called *Regrouping CPE* (ReCPE) which improves the estimations of the current PU learning methods without irreciblility assumption. The main idea of our method is that, instead of estimating

the maximum proportion of P_p in P_u, we builds a new CPE problem by creating a new auxiliary distribution $P_{\mathrm{p}'}$ always guaranteeing the irreduciblility assumption. Then we use the existing CPE method to obtain the maximum proportion of $P_{\mathrm{p}'}$ in P_u, which is denoted by π'. We show that, with both theoretical analyses and experimental validations, when the irreduciblility assumption holds, our ReCPE method does not affect the prediction of the existing estimators; when the irreduciblility assumption does not hold, our method will help the current estimators have less estimation bias, which could improve the performances of PU classification tasks. For example, in Figure 1(d), we create a new class-conditional (auxiliary) distribution $P_{\mathrm{p}'}$. By solving it, $\pi' = 0.51$. The estimation bias of the existing estimators will reduce to $\pi' - \pi = 0.01$ instead of $\kappa^* - \pi = 0.2$.

The rest of the paper is organized as follows. In Section 2, we review the irreduciblility assumption and its variants. We discuss the difficulty of checking the assumptions. In Section 3, we provide the estimation biases of the existing consistent distributional-assumption-free CPE methods. Then we propose our method ReCPE, followed by theoretically analysis of its estimation bias and the implementation details. All the proofs are listed in Appendix A. The experimental validations are given in Section 4. Section 5 concludes the paper.

2 IRREDUCIBILITY OF CPE

In this section, we briefly review the assumptions used for existing distributional-assumption-free CPE estimators. Then we provide the estimation bias introduced by consistent distributional-assumption-free CPE methods when the assumptions does not hold.

The irreduciblility assumption. Let P_p and P_u be probability measures (distributions) on a measurable space $(\mathcal{X}, \mathfrak{S})$, where $\mathcal{X}$ is the sample space, and $\mathfrak{S}$ is the σ-algebra. Let κ^* be the maximum proportion of P_p in P_u. To let κ^* be identical to π, the irreduciblility assumption was proposed by Blanchard et al. (2010).

Definition 1 (Irreducibility). *P_n and P_p are said to satisfy the irreduciblility assumption if P_n is not a mixture containing P_p. That is, there does not exist a decomposition $P_\mathrm{n} = (1 - \beta)Q + \beta P_\mathrm{p}$, where Q is a probability distribution on the measurable space $(\mathcal{X}, \mathfrak{S})$, and $0 < \beta \leq 1$.*

Equivalently, the assumption assumes the support of P_p is hardly contained in the support of P_n. It means that with the selection of different set S, the probability $P_\mathrm{n}(S)$ can be arbitrarily close to 0, and $P_\mathrm{p}(S) > 0$. Suppose we can access the distributions $P_\mathrm{u}, P_\mathrm{p}$ and the set $\mathcal{C}$ containing all possible latent distributions, then the class-prior π can be found as follows:

$$\pi = \kappa^* \triangleq \sup\{\alpha | P_\mathrm{u} = (1 - \alpha)K + \alpha P_\mathrm{p}, K \in \mathcal{C}\} = \inf_{S \in \mathfrak{S}, P_\mathrm{p}(S) > 0} \frac{P_\mathrm{u}(S)}{P_\mathrm{p}(S)}. \tag{2}$$

To the best of our knowledge, all existing distributional-assumption-free CPE methods (Blanchard et al., 2010; Scott et al., 2013; Liu & Tao, 2015; Scott, 2015; Ramaswamy et al., 2016; Ivanov, 2019) are variants of estimating the maximum proportion κ^* of P_p in P_u. Many of them are statistically consistent estimators (Blanchard et al., 2010; Scott et al., 2013; Liu & Tao, 2015; Scott, 2015).

The variants of the irreducibility. Based on the irreduciblility assumption, estimators can be designed with theoretical guarantees that they will converge to the class-prior π (Blanchard et al., 2010). However, the convergence rate can be arbitrarily slow (Scott, 2015). The reason is that the irreduciblility assumption implies the following fact (Blanchard et al., 2010; Scott et al., 2013)

$$\inf_{S \in \mathfrak{S}, P_\mathrm{p}(S) > 0} \frac{P_\mathrm{n}(S)}{P_\mathrm{p}(S)} = 0, \tag{3}$$

i.e., the maximum proportion of P_p in P_n approaches to 0. To obtain the class-prior π, it requires to find a sequence of the sets S converging to the infimum, which empirically can be hard to found. Therefore, the convergence rate of the designed estimators based on Eq. (3) will be arbitrarily slow. To ensure a fixed rate of convergence, the *anchor set* assumption, a stronger variant of the irreduciblility assumption, has been proposed (Scott, 2015; Liu & Tao, 2015). It assumes that

$$\min_{S \in \mathfrak{S}, P_\mathrm{p}(S) > 0} \frac{P_\mathrm{n}(S)}{P_\mathrm{p}(S)} = 0, \tag{4}$$

i.e., there exists a set can achieve the minimum 0, which is called an anchor set. An other stronger variant is the *separability* assumption (Ramaswamy et al., 2016) which extends the anchor set assumption to a function space. It is proposed to bound the convergence rate of the method based on kernel-mean-matching (KMM) technique (Gretton et al., 2012).

3 REGROUPING FOR CPE (ReCPE)

In this section, we propose a general method named regrouping for CPE (ReCPE). We discuss how to theoretically and empirically mitigate the overestimation problem of the class-prior π.

3.1 MOTIVATION

In general, it is impossible to verify the irreduciblility assumption for CPE. To check the assumption, we need to make P_n itself to be observable and verify that whether the distribution P_n is a mixture containing the distribution P_p, which obviously contradicts to the setting of PU learning. However, in practice, the irreduciblility assumption may not hold for many real-world problems, because the negative class is diverse (Hsieh et al., 2019; Bekker & Davis, 2020) in PU learning. If the assumption does not hold, P_n is said to be reducible to P_p, and distributional-assumption-free CPE methods will introduce an *estimation bias*.

Proposition 1. *Let* $\beta^* = \inf_{S \in \mathfrak{S}, P_p(S) > 0} \frac{P_n(S)}{P_p(S)}$ *be the maximum proportion of* P_p *in* P_n, *given* $P_u = (1 - \pi)P_n + \pi P_p$, *for* $0 < \pi \le 1$, *we have*

$$\kappa^* = \pi + (1 - \pi) \inf_{S \in \mathfrak{S}, P_p(S) > 0} \frac{P_n(S)}{P_p(S)} = \pi + (1 - \pi)\beta^*. \tag{5}$$

According to Proposition 1, if the irreduciblility assumption does not hold, then there exists $\beta > 0$. In this case, maximum proportion κ^* can still be obtained, but it is different from π but equal to $\pi + (1 - \pi)\beta^*$. In this case, if we directly employ existing distributional-assumption-free CPE methods, they could introduce an arbitrary estimation bias $(1 - \pi)\beta^*$ which depends on P_n.

To reduce the estimation bias, we propose ReCPE. The process of regrouping is to change the original class-conditional distributions P_n and P_p into new class-conditional distributions $P_{n'}$ and $P_{p'}$ by transporting the probability mass of the set A from the negative class to the positive class. After regrouping, new class-conditional distributions are guaranteed to satisfy the irreduciblility assumption, and therefore, the new positive class-prior π' can be identified by current CPE methods. To get the intuition, we provide an concrete example as follows.

Suppose that P_p is the uniform on $[\frac{1}{2}, 1]$, P_n is uniform on $[0, 1]$, and $\pi = \frac{1}{2}$. Then we have P_u such that it is uniform on $[0, \frac{1}{2})$ and $[\frac{1}{2}, 1]$, respectively. Specifically, the probabilities are

$$P_u\left([0, \frac{1}{2})\right) = \frac{1}{4}, \quad P_u\left([\frac{1}{2}, 1]\right) = \frac{3}{4}.$$

In this case, by Eq. 5, the maximum proportion of P_p in P_u is $\pi^* = \frac{3}{4}$. Let $\rho > 0$ be a small constant and let $A = (1 - \rho, 1]$. In this case, the mass of A in P_u from P_n is $\pi P_n(A) = \frac{\rho}{2}$. After transporting the mass $\frac{\rho}{2}$ from P_n to P_p, we have a new positive class-prior π' and a new class-conditional $P_{p'}$ which is uniform on $[\frac{1}{2}, 1 - \rho)$ and $[1 - \rho, 1]$, respectively. Specifically,

$$\pi' = \frac{1 + \rho}{2}, \quad P_{p'}\left([\frac{1}{2}, 1 - \rho)\right) = \frac{1 - 2\rho}{1 + \rho}, \quad P_{p'}\left([1 - \rho, 1]\right) = \frac{3\rho}{1 + \rho}.$$

As we can see from the left equation above, the new class-prior π' is dependent on ρ or the size of A. By controlling set A or ρ to be small, π' can be as close to π as possible. This is the intuition of how regrouping works.

3.2 PRACTICAL IMPLEMENTATION

In practice, we have to implement the aforementioned idea of regrouping based on positive sample S_p and unlabeled sample S_u. Since negative sample is unavailable, we cannot "cut and paste" any

---

Algorithm 1 ReCPE

    Input: An unlabeled sample S_u i.i.d. drawn from P_u, a positive sample S_p i.i.d. drawn from P_p, and the percentage p of the sample needed to copy from S_u to S_p.

1: Train a binary classifier h with the unlabeled sample S_u and positive sample S_p by treating S_u as a negative sample;

2: Assign each example $x \in S_u$ with the negative class-posterior probability $P(Y = -1|X = x)$ predicted by the trained classifier a h;

3: Obtain $S_{p'}$ by copying $p \times |S_u|$ examples with the smallest negative class-posterior probability $P(Y = -1|X = x)$ from S_u to S_p;

4: Estimate the class-prior π' by employing an algorithm based on Eq. (5) with inputs S_u and $S_{p'}$.

    Output: The estimated new class-prior $\hat{\pi}'$.

---

example from negative class to positive sample S_p; instead, we can "copy and past" some unlabeled examples to S_p. When doing so, we should select a small set of samples $\hat{A}^*$ which look the most similar to the positive class and dissimilar to the negative class, which could encourage the difference between the original P_n, P_p, and ρ and π, $P_{p'}$, and π' to be small. This is why $\hat{A}^* = (1 - \rho, 1]$ was selected in the above intuitive example, i.e., $\hat{A}^*$ belongs geometrically and visually to the positive class with the highest confidence among all subsets of $[0, 1]$ of size ρ.

A hyper-parameter $p \in (0, 1)$ is introduced to control the size of set $\hat{A}^*$, theoretically, we prefer the set $\hat{A}^*$ to have a small size. Empirically, p cannot be so small: the existing estimators are insensitive to tiny modifications (they are designed to be robust in such a way, in order to be good estimators). For example, the difference between the estimated class-priors by employing samples S_u and S_p and the one by employing samples S_u and $S_{p'}$ can be hardly observed if S_p and $S_{p'}$ only differ from in one or two points. Specifically, $p = 10\%$ is selected for the experiments on all datasets, which leads to a significant improvement of the estimation accuracy. The details on the selection of the hyper-parameter value will be explained in Section 4.1. The algorithm is summarized in Algorithm 1.

There are two fundamental concerns for copying $\hat{A}^*$ to S_p. 1). When we have irreducibility, might regrouping make $\hat{\pi}'$ be a worse approximation? 2). When we lack irreducibility, must regrouping make $\hat{\pi}'$ be a better approximation? While these concerns will be formally clarified later, we give here intuitive implications of regrouping.

1). If we have irreducibility, the $P_n(\hat{A}^*)$ should be rather small (if not zero), and $\hat{A}^*$ should be drawn from the positive component P_p of the mixture P_u. In this case, regrouping will generally not change P_p but only increase number of examples in P_p. Hence, it will not make $\hat{\pi}'$ worse.

2). If we lack irreducibility, $\hat{A}^*$ may be drawn from either P_p or P_n. By regrouping, $\hat{A}^*$ becomes present in $S_{p'}$, which encourages the probability of the set $\hat{A}^*$ in $P_{p'}$ to be large. This will modify P_p as we expected towards irreducibility. As a consequence, regrouping will make $\hat{\pi}'$ better.

3.3 THEORETICAL JUSTIFICATION

In the regrouping approach described above, the auxiliary class-conditional distribution $P_{p'}$ and $P_{n'}$ are created by regrouping a small set A from P_p and P_n. Here, we analyze the properties of regrouping and theoretically justify it.

A formal definition of regrouping In order to analyze the properties, we need to formally define how to split, transport, and regroup a set A (or the mass of A).

Definition 2. *Let M be a probability measure on a measurable space $(\mathcal{X}, \mathfrak{S})$. Given a set $A \in \mathfrak{S}$, we define a measure M^A on the σ-algebra $\mathfrak{S}$ as follows:*

$$\forall S \in \mathfrak{S}, M^A(S) = M(S \cap A). \tag{6}$$

It is easy to see that given two measures M^A and M^{A^c} obtained according to Definition 2, where $A^c = \mathcal{X} \setminus A$, then M^A and M^{A^c} have the following property.

Lemma 1. *Let M be a probability measure over a measurable space $(\mathcal{X}, \mathfrak{S})$. For any set $A \in \mathfrak{S}$, we have $M^A + M^{A^c} = M$.*

Now, we introduce the theory of regrouping. Fixing a set $A \in \mathfrak{S}$, we split P_{n} as $P_{\mathrm{n}}^{A^c}$ and P_{n}^A, transport P_{n}^A to P_{p} to regroup them together, i.e.,

$$P_{\mathrm{u}} = (1-\pi)P_{\mathrm{n}} + \pi P_{\mathrm{p}} = (1-\pi)\underbrace{(P_{\mathrm{n}}^A + P_{\mathrm{n}}^{A^c})}_{\text{split into two}} + \pi P_{\mathrm{p}} = (1-\pi)P_{\mathrm{n}}^{A^c} + \underbrace{((1-\pi)P_{\mathrm{n}}^A + \pi P_{\mathrm{p}})}_{\text{regroup as one}}.$$

Finally, we can rewrite the unlabeled data distribution P_{u} as a mixture of two new class-conditional distributions $P_{\mathrm{n}'}$ and $P_{\mathrm{p}'}$ defined in Theorem 1 by renormalization.

Theorem 1. *Let $P_{\mathrm{u}} = (1-\pi)P_{\mathrm{n}} + \pi P_{\mathrm{p}}$. Let $A \subset \mathrm{support}(P_{\mathrm{u}})$. By regrouping P_{n}^A to P_{p}, P_{u} can be written as a mixture, i.e., $P_{\mathrm{u}} = (1-\pi')P_{\mathrm{n}'} + \pi'P_{\mathrm{p}'}$, where*

$$\pi' = \pi + (1-\pi)P_{\mathrm{n}}(A), \tag{7}$$

$$P_{\mathrm{n}'} = \frac{P_{\mathrm{n}}^{A^c}}{P_{\mathrm{n}}(A^c)}, \quad P_{\mathrm{p}'} = \frac{(1-\pi)P_{\mathrm{n}}^A + \pi P_{\mathrm{p}}}{(1-\pi)P_{\mathrm{n}}(A) + \pi}, \tag{8}$$

and $P_{\mathrm{n}'}$ and $P_{\mathrm{p}'}$ satisfy the anchor set assumption.

When class-conditional distributions P_{n} and P_{p} do not satisfy the irreduciblility assumption, π cannot be obtained by using CPE methods based on MPE, which will lead to an estimation bias discussed before. However, Theorem 1 shows that the new proportion π' is always identifiable as $P_{\mathrm{n}'}$ and $P_{\mathrm{p}'}$ always satisfy the anchor set assumption. Thus, after regrouping, π' is identifiable and can be estimated by the existing CPE methods.

Bias reduction According to Theorem 1, to make π' closer to π, we expect to find the set A looks most dissimilar to the negative class, i.e., $P_{\mathrm{n}}(A)$ is small.

Theorem 2. *Let $P_{\mathrm{p}'}$ and $P_{\mathrm{n}'}$ be obtained by regrouping a set $A^* := \arg\min_{A \in \mathfrak{S}} \frac{P_{\mathrm{n}}(A)}{P_{\mathrm{p}}(A)}$[1] from P_{p} and P_{n}. 1). If P_{n} and P_{p} satisfy the irreduciblility assumption, then $\pi' = \pi$; 2). if P_{n} and P_{p} dissatisfy the irreduciblility assumption, then $\pi < \pi' < \pi + (1-\pi)\beta^* = \kappa^*$.*

Theorem 2 shows that how to properly select a set used for regrouping to make π' a good approximation of π. Specifically, once A^* is selected for regrouping, if P_{n} and P_{p} satisfy the irreduciblility assumption, the new estimation π' will be identical to π; if P_{n} and P_{p} dissatisfy the irreduciblility assumption, π' obtained by employing the distributions P_{u} and $P_{\mathrm{p}'}$ will contain a smaller estimation bias compared to κ^* obtained by employing the distributions P_{u} and P_{p}.

Convergence analysis For completeness, we illustrate the convergence property of ReCPE, which is presented by employing the estimator proposed by Blanchard et al. (2010). Let S_{u}, S_{p} and $S_{\mathrm{p}'}$ be the samples i.i.d. drawn from P_{u}, P_{p} and $P_{\mathrm{p}'}$, respectively. Let A be the set used for regrouping. Let $h : \mathcal{X} \to \mathbb{R}, h \in \mathcal{H}$, be a function that predicts 1 for all elements in the set A and 0 otherwise, where $\mathcal{H}$ denotes a *hypothesis space*. Let $|S|$ denote the cardinality of a set S. Let $\mathbb{1}_{\{h(x)=1\}}$ be an indicator function which returns 1 if $h(x)$ predicts 1 and 0 otherwise. Then $P_{\mathrm{u}}(A)$ can be expressed as $\int_{x \in \mathcal{X}} p_{\mathrm{p}}(x)\mathbb{1}_{\{h(x)=1\}}\mathrm{d}x$, where p_{p} is the density function of the distribution P_{u}. Let $\hat{P}_{\mathrm{u}}(A)$ be the empirical version of $P_{\mathrm{u}}(A)$, i.e., $\hat{P}_{\mathrm{u}}(A) = \frac{1}{|S_{\mathrm{u}}|}\sum_{x \in \mathcal{X}} \mathbb{1}_{\{h(x)=1\}}$. Similarly, let $\hat{P}_{\mathrm{p}'}(A)$ be the empirical version of $P_{\mathrm{p}'}(A)$. Let the error $\epsilon_{\delta,\mathcal{H}}(S_{\mathrm{u}})$ denote the difference between $P_{\mathrm{u}}(A)$ and $\hat{P}_{\mathrm{u}}(A)$ obtained by exploiting the *empirical Rademacher complexity* (Mohri et al., 2018). Similarly, let $\epsilon_{\delta,\mathcal{H}}(S_{\mathrm{p}'})$ denote the difference between $P_{\mathrm{p}'}(A)$ and $\hat{P}_{\mathrm{p}'}(A)$. We have the following theorem.

Theorem 3. *Let $P_{\mathrm{u}} = (1-\pi)P_{\mathrm{n}} + \pi P_{\mathrm{p}}$. By selecting a set A and regrouping P_{n}^A to P_{p}. Then, with probability $1 - 2\delta$, the estimated class-prior $\hat{\pi}'$ based on solving $\inf_{S \in \mathfrak{S}, \hat{P}_{\mathrm{p}'}(S) > 0} \frac{\hat{P}_{\mathrm{u}}(S)}{\hat{P}_{\mathrm{p}'}(S)}$ satisfies*

$$|\hat{\pi}' - \pi| \leq \frac{\epsilon_{\delta,\mathcal{H}}(S_{\mathrm{p}'})}{\hat{P}_{\mathrm{p}'}(A) + \epsilon_{\delta,\mathcal{H}}(S_{\mathrm{p}'})} + \frac{\epsilon_{\delta,\mathcal{H}}(S_{\mathrm{u}})}{\hat{P}_{\mathrm{p}'}(A) + \epsilon_{\delta,\mathcal{H}}(S_{\mathrm{p}'})} + (1-\pi)P_{\mathrm{n}}(A), \tag{9}$$

where $\epsilon_{\delta,\mathcal{H}}(S) \triangleq 2\hat{\mathfrak{R}}_S(\mathcal{H}) + 3\sqrt{\frac{\log\frac{4}{\delta}}{2|S|}}$, and $\hat{\mathfrak{R}}_S(\mathcal{H})$ is the empirical Rademacher complexity of $\mathcal{H}$.

---

[1]We have defined that the fraction tends to infinite if its numerator is larger than 0 and its denominator is 0. Additionally, the infimum may not be always exist, if it does not exist, we could use a sequence of sets that converges to the infimum value, but the convergence rate can be arbitrarily slow (Scott, 2015).

To make $\epsilon_{\delta,\mathcal{H}}(S)$ converge to 0 with the increasing of the sample size of S, a *universal approximation* assumption has been proposed by Scott (2015) to ensure that the hypothesis space is large enough to represent a wide variety of interesting functions. Under the assumption, Scott (2015) proved that, with increasing of the size of samples S_{u} and $S_{\mathrm{p}'}$, the error between $P_{\mathrm{u}}(A)$ and $\hat{P}_{\mathrm{u}}(A)$ will converge to 0 at a rate $\mathcal{O}\left(\sqrt{\frac{\log|S_{\mathrm{u}}|}{|S_{\mathrm{u}}|}}\right)$, similarly to $P_{\mathrm{p}'}(A)$ and $\hat{P}_{\mathrm{p}'}(A)$. Since the empirical Rademacher complexity $\hat{\mathfrak{R}}_X(\mathcal{H})$ of a hypothesis space $\mathcal{H}$ can be upper-bounded by its VC-dimension (Mohri et al., 2018), the both errors based on the empirical Rademacher complexity will also converge to zero with increasing of the sample size. Consequently, the estimation $\hat{\pi}' = \frac{\hat{P}_{\mathrm{u}}(A)}{\hat{P}_{\mathrm{p}'}(A)}$ will converge to

$\pi' = \frac{P_{\mathrm{u}}(A)}{P_{\mathrm{p}'}(A)} = \pi + (1-\pi)P_{\mathrm{n}}(A)$ at a rate $\mathcal{O}\left(\sqrt{\frac{\log(\min(|S_{\mathrm{u}}|,|S_{\mathrm{p}'}|))}{\min(|S_{\mathrm{u}}|,|S_{\mathrm{p}'}|)}}\right)$.

Computationally efficient identification of A^* The following theorem presents how to identify A^* with P_{u} and P_{p}. Let us define another auxiliary distribution $q(X,C)$, where $C \in \{0,1\}$ is the positive-vs-unlabeled label i.e., a class label distinguishing between the positive component and the whole mixture. Specifically, priors are $q(C=1) := \frac{\pi}{1-\pi}$ and $q(C=0) := \frac{1}{1-\pi}$; conditional densities are $q(X|C=1) := P_{\mathrm{p}}$ and $q(X|C=0) := P_{\mathrm{u}}$; class-posterior probabilities are $q(C=0|X)$ and $q(C=1|X)$. We have the following theorem.

Theorem 4. *Let p_{u} and p_{p} be density functions of P_{u} and P_{p}, respectively. Let $q = P(C = 0)p_{\mathrm{u}} + P(C=1)p_{\mathrm{p}}$. Let $\mathbb{1}_A : \mathcal{X} \to \{0,1\}$ be the identity function which outputs 1 if $x \in \mathcal{X}$ is in the set A, and 0 otherwise. Then the set $A^* = \arg\min_{A \in \mathfrak{S}} \frac{\mathbb{E}_{x \sim q(X)}[\mathbb{1}_A(X=x)q(C=0|X=x)]}{\mathbb{E}_{x \sim q(X)}[\mathbb{1}_A(X=x)q(C=1|X=x)]}$.*

For the above optimization, its objective function has two expectations over q, which can have the "exact" empirical solution obtained by replacing expectations with empirical averages: $A^* = \arg\min_{A \subset S} \frac{\sum_{x \in A} q(C=0|X=x)}{\sum_{x \in A} q(C=1|X=x)}$.

Approximation of $P_{\mathrm{p}'}$ with a surrogate As we do not have examples drawn from P_{n}, it is hard to create $P_{\mathrm{p}'}$, let alone to sample from it. We approximate $P_{\mathrm{p}'}$ by using $P_{\tilde{\mathrm{p}}'} = \frac{P_{\mathrm{u}}^A + P_{\mathrm{p}}}{P_{\mathrm{u}}(A)+1}$. The following proposition shows that when $P_{\mathrm{u}}(A)$ is small, $P_{\tilde{\mathrm{p}}'}$ is almost identical to $P_{\mathrm{p}'}$.

Proposition 2. *Let $P_{\tilde{\mathrm{p}}'} = \frac{P_{\mathrm{u}}^A + P_{\mathrm{p}}}{P_{\mathrm{u}}(A)+1}$ and $P_{\mathrm{u}}(A) < \epsilon$. $\forall \epsilon > 0$ and $S \in \mathfrak{S}$, $|P_{\mathrm{p}'}(S) - P_{\tilde{\mathrm{p}}'}(S)| \leq \mathcal{O}(\epsilon)$.*

Since the gap has the same order as $P_{\mathrm{u}}(A)$ uniformly over S, it is guaranteed that whenever $P_{\mathrm{u}}(A)$ is small, the gap is also small. Practically, we can control the parameter ϵ in the above proposition to be small. Specifically, using a small value of the hyper-parameter p in Algorithm 1 will lead to the set A in Theorem 1 to be small, as well as $P_{\mathrm{u}}(A)$. As a consequence, the practical implementation of regrouping is a good approximation of the theory of regrouping as we expected. By now, we have analyzed all of the properties of regrouping and theoretically justified all of the points in its design.

4 EXPERIMENTS

We run experiments on 2 synthetic datasets and 9 real word datasets[2]. The objectives of employing synthetic datasets are to validate that whether the proposed regrouping CPE method reduces the estimation error of the consistent distributional-assumption-free CPE method on the dataset satisfying the irreduciblility assumption and does not influence the prediction of the CPE method on the dataset dissatisfying the irreduciblility assumption. The hyper-parameter p is also selected from the synthetic datasets. The real-word datasets are used to illustrate the effectiveness of our methods. Although we have introduced a hyper-parameter p and used approximations in the implementation, empirical results on all synthetic and real-world datasets consistently show the superiority of ReCPE.

To have a rigorous performance evaluation, for each dataset, $6 \times 3 \times 10$ experiments are conducted via random sampling. Specifically, we select $\{0.25, 0.5, 0.75\}$ fraction of positive examples to be the sample of the positive distribution P_{p}. We let the rest of the examples to be the sample of the unlabeled distribution P_{u}. In such way, 3 pairs of empirical positive and unlabeled distributions are generated. Then, we create other 3 pairs of distributions by flipping the labels of all instances in the

---

[2]The real word datasets are downloaded from the UCL machine learning database. Multi-class datasets are used as binary datasets by either grouping or ignoring classes.

original datasets. For each pair of distributions, we randomly draw positive and unlabeled samples with sizes of 800, 1600 and 3200, respectively, which are used as input data. Note that, the positive and unlabeled samples have the same size as did in Ramaswamy et al. (2016). For each sample size, 10 repeated experiments are carried out with random sampling. For all experiments, we employ a neural network [3] with 2 hidden layers. Each hidden layer contains 50 hidden units. The batch normalization (Ioffe & Szegedy, 2015) is also employed. The stochastic gradient descent optimizer is used with the batch size 50. The network is trained for 350 epochs with learning rate 0.01 and momentum 0. The weight decay is set to $1e-5$. The model with the best validation accuracy is used to estimate the positive class-posterior probability $P(Y = 1|X = x)$. We sample the validation set with 20% of the training data size.

4.1 EXPERIMENTS ON SYNTHETIC DATASETS

We create two datasets with one satisfying the irreduciblility assumption while the other not. The dataset satisfying the irreduciblility assumption is created by sampling from 2 different 10-dimensional Gaussian distributions as the component distributions. One of the distribution has 10-zero means and unit covariance matrix. Another one has 10-unit means and unit covariance matrix. The dataset dissatisfying the irreduciblility assumption is also created by drawing examples from 2 different 10-dimensional Gaussian distributions. One of the distribution has zero mean and unit covariance matrix. Another one has unit mean and covariance matrix. Then we remove all the data points with $P(Y = 1|X) \geq 0.98$ or $P(Y = 1|X) \leq 0.02$. For simplicity, in Figure 2, we name two datasets irreducible data and reducible data, respectively.

To validate the correctness of our method and to select a suitable value of the hyper-parameter p, we carry out two experiments. The consistent CPE method KM2 is used as the baseline, which is compared to our method ReKM2, i.e., regrouping version of the KM2. Firstly, we compare the magnitude differences between $\hat{\pi}$ and $\hat{\pi}'$ (i.e., $\hat{\pi} - \hat{\pi}'$) with the different fractions of points to be copied from the mixture sample F to the component sample H, which is illustrated in Figure 2(a). Then we compare differences of the absolute error (i.e., $|\hat{\pi} - \pi| - |\hat{\pi}' - \pi|$) between the baseline and our method with the increasing of the copy fractions. Note that each point in Figure 2 is obtained by averaging over $6 \times 3 \times 10$ experiments.

Figure 2(a) validates the correctness of our Theorem 2 and Eq. (7). Theorem 2 states that, by properly selecting the set A, on the dataset dissatisfying the irreduciblility assumption (reducible data), π' should be smaller than the maximum proportion κ^*; on the dataset satisfying the irreduciblility assumption (irreducible data), π' should be close to π. Figure 2(a) perfectly matches this statement. It shows that, on the reducible data, the

(a)

(b)

Figure 2: Experiments of the hyperparameter selection on synthetic datasets. With increasing of the copy fraction p, (a) average estimation differences between KM2 and Regrouping KM2 (ReKM2) and (b) average differences of the absolute error between KM2 and Regrouping KM2 (ReKM2).

values of $\hat{\pi}'$ are continuously smaller than $\hat{\pi}$ with the copy fraction $\leq 22.5\%$; on the irreducible data, $\hat{\pi}'$ and $\hat{\pi}$ have the similar values until the copy fraction $\geq 17.5\%$. According to Eq. (7), the positive bias of our estimator should become larger with the increasing of $P_n(A)$. This fact is reflected by the differences of $\hat{\pi} - \hat{\pi}'$ become smaller on the both datasets when the copy fraction $> 15\%$.

Figure 2(b) illustrates the average differences of absolute error between the baseline and the proposed method. On the reducible data, our method continuously outperforms the baseline with the copy fraction $\leq 22.5\%$. However, the differences of average absolute error start to decrease with the copy fraction $> 15\%$. On the irreducible data, the differences of average absolute error are close to zero until the copy fraction $> 15\%$.

---

[3] We employ the neural network because it has a high approximation capability (Csáji et al., 2001).

	AM	ReAM	DPL	ReDPL	EN	ReEN	KM1	ReKM1	KM2	ReKM2	ROC	ReROC	RPG	ReRPG
adult (800)	**0.127**	0.13	0.122	**0.108**∗	0.316	**0.295**	0.255	**0.132**	0.164	**0.153**	0.176	**0.153**	0.135	**0.134**
adult (1600)	**0.122**	0.124	0.089∗	0.089∗	0.31	**0.29**	0.131	**0.091**	**0.12**	0.13	0.121	**0.095**	**0.123**	0.137
adult (3200)	0.105	**0.086**	0.054	0.057	0.297	**0.279**	0.054	**0.04**∗	0.082	0.089	0.089	**0.067**	**0.114**	0.128
avila (800)	0.168	**0.152**	**0.129**	0.147	0.447	**0.422**	0.105	**0.075**∗	0.104	**0.081**	0.263	**0.228**	0.119	**0.111**
avila (1600)	0.165	**0.132**	0.104	**0.084**	0.439	**0.418**	0.086	**0.076**∗	0.108	**0.092**	0.191	**0.16**	0.123	**0.121**
avila (3200)	0.156	**0.133**	**0.05**∗	0.061	0.436	**0.42**	0.092	**0.078**	0.112	**0.092**	0.131	**0.095**	**0.121**	0.122
bank (800)	**0.135**	0.158	**0.116**∗	0.132	0.282	**0.264**	0.356	**0.216**	0.266	**0.238**	0.163	**0.15**	**0.163**	0.185
bank (1600)	**0.117**	0.167	**0.087**∗	0.105	0.262	**0.244**	0.178	**0.128**	0.203	**0.198**	0.129	**0.118**	**0.157**	0.167
bank (3200)	0.104	0.127	**0.073**∗	0.091	0.248	**0.237**	0.124	**0.09**	0.15	0.16	**0.093**	0.106	**0.159**	0.18
card (800)	0.131	**0.127**∗	0.174	**0.161**	0.465	**0.444**	0.293	**0.176**	0.203	**0.158**	0.247	**0.233**	0.177	**0.155**
card (1600)	0.173	**0.14**	0.14	0.14	0.459	**0.437**	0.19	**0.135**	0.159	**0.129**	0.194	**0.163**	0.126	**0.115**∗
card (3200)	0.164	**0.134**	0.127	**0.12**	0.455	**0.435**	0.161	**0.113**	0.142	**0.122**	0.159	**0.152**	0.11	**0.108**∗
covtype (800)	0.16	**0.123**	0.155	**0.151**	0.367	**0.343**	0.157	**0.142**	**0.122**	0.13	0.291	**0.258**	0.116	**0.105**∗
covtype (1600)	0.12	**0.1**∗	0.132	**0.109**	0.364	**0.339**	0.116	**0.113**	**0.121**	0.123	0.199	**0.161**	0.109	**0.108**
covtype (3200)	0.128	**0.09**	0.093	**0.083**∗	0.354	**0.334**	0.097	0.109	**0.124**	0.128	0.157	**0.113**	0.109	**0.107**
egg (800)	0.153	**0.106**∗	0.218	0.225	0.505	0.505	**0.173**	0.264	**0.119**	0.131	0.476	**0.396**	0.171	**0.124**
egg (1600)	0.137	**0.12**	0.121	0.142	0.486	0.489	0.234	**0.214**	0.116	**0.108**∗	0.315	**0.238**	0.151	**0.114**
egg (3200)	0.126	**0.113**	**0.057**∗	0.073	**0.485**	0.489	0.26	**0.193**	0.134	**0.113**	0.163	**0.139**	0.142	**0.102**
magic04 (800)	0.099	**0.077**	0.072	**0.071**	0.312	**0.296**	0.111	**0.1**	0.071	**0.064**	0.141	**0.124**	0.055	**0.054**∗
magic04 (1600)	0.071	**0.056**	0.044	**0.043**∗	0.292	**0.274**	0.084	**0.072**	0.079	**0.065**	0.1	**0.073**	0.058	**0.052**
magic04 (3200)	0.069	**0.054**	**0.035**∗	0.036	0.274	**0.258**	0.07	**0.047**	0.085	**0.063**	0.065	**0.047**	0.054	**0.052**
robot (800)	**0.053**	0.062	0.049	**0.047**∗	0.19	**0.187**	0.232	**0.215**	**0.111**	0.114	**0.119**	0.144	**0.077**	0.084
robot (1600)	0.053	**0.038**∗	0.087	**0.054**	0.139	**0.132**	0.15	**0.141**	**0.098**	0.099	0.08	**0.075**	**0.076**	0.079
robot (3200)	0.052	**0.039**∗	0.156	**0.119**	0.091	**0.085**	0.079	**0.077**	0.084	0.084	0.063	**0.043**	**0.06**	0.066
shuttle (800)	0.083	**0.031**	**0.016**∗	0.02	0.041	**0.035**	**0.058**	0.083	**0.035**	0.065	**0.042**	0.047	**0.035**	0.051
shuttle (1600)	0.09	**0.045**	**0.011**∗	0.018	0.04	**0.034**	**0.048**	0.079	**0.024**	0.05	**0.029**	0.043	**0.026**	0.039
shuttle (3200)	0.076	**0.028**	**0.012**∗	0.021	0.043	**0.038**	**0.046**	0.07	**0.018**	0.03	**0.038**	0.045	**0.028**	0.042
average	0.116	**0.1**	0.094	**0.092**∗	0.311	**0.297**	0.146	**0.121**	0.117	**0.111**	0.157	**0.136**	0.106	**0.105**

Table 1: Absolute estimation errors on real-world datasets. The first column provides the names of the datasets and the total number sample length. We bold the smaller average estimation errors by compared each baseline method with its regrouped version. The smallest average estimation error among all methods for each row is highlighted with ∗. The last row are obtained by averaging over all the experiments. Variances and the results of Wilcoxon signed rank test are reported in Appendix B. The proposed Regrouping methods are significantly better than most of the baselines.

By observing Figure 2, we found the prediction of the KM2 estimator will not change much if the copy fraction p is too small. For example, the difference between the estimated mixture proportion by employing samples S_u and X_P and the ones by employing samples S_u and X'_P can be hardly observed if X_P and X'_P only differ from in one or two points. For simplicity and consistency, we select hyper-parameter p to be 10% for all the following experiments.

4.2 EXPERIMENTS ON REAL-WORLD DATASETS

We illustrate the absolute estimation errors of different estimators on the real-world datasets. Totally, 7 baseline methods are used in the experiments, which are AlphaMax (AM) (Jain et al., 2016), DEDPUL (DPL) (Ivanov, 2019), Elkan-Noto (EN) (Elkan & Noto, 2008), KM1, KM2 (Ramaswamy et al., 2016), ROC (Scott, 2015), and Rankpruning (RPG) (Northcutt et al., 2017). By using our method, the regrouped version of them are implemented, which are called ReAM, ReDPL, ReEN, ReKM1, ReKM2, ReROC, and ReRPG. In Table 1, we compare the absolute estimation errors of each baseline with those of its regrouped version on different datasets with different sample lengths. Each number in Table 1 is the average over 6×10 experiments.

Table 1 reflects the effectiveness of our regrouping CPE method. Overall, by using our method, the estimation accuracy is increased for most of the popular CPE methods among the most of the datasets with different sample lengths. By observing the last row, the regrouped version of the estimators have much smaller average estimation errors except DPL, KM2, and RPG. On the real-world datasets, Regrouping AlphaMax (ReAM) results the smallest average estimation error among all methods.

5 CONCLUSION

In this paper, we investigate how to reduce the estimation bias of the distributional-assumption-free CPE method without irreduciblility assumption for PU learning. We have proposed regrouping CPE which can be employed on top of most existing CPE methods. It only requires to train a binary classifier addition to the existing CPE methods. We have also theoretically analyzed the estimation bias of ReCPE. By running experiments on both synthetic and benchmark datasets, its correctness and effectiveness are also empirically justified. It improves all popular CPE methods on various datasets. One future work will focus on how to generate a sample from $P_{p'}$ instead of using an approximation.

REPRODUCIBILITY STATEMENT

For theoretical results, we have clearly explained of any assumptions. A complete proof of the claims can be founded in the appendix. We have also included a anonymous source code in our supplementary material. For any datasets used in the experiments, a complete description of the data processing steps is provided In Section 4.

REFERENCES

Jessa Bekker and Jesse Davis. Estimating the class prior in positive and unlabeled data through decision tree induction. In *Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

Jessa Bekker and Jesse Davis. Learning from positive and unlabeled data: a survey. *Mach. Learn.*, 109(4):719–760, 2020.

Gilles Blanchard, Gyemin Lee, and Clayton Scott. Semi-supervised novelty detection. *Journal of Machine Learning Research*, 11(Nov):2973–3009, 2010.

Marthinus Christoffel, Gang Niu, and Masashi Sugiyama. Class-prior estimation for learning from positive and unlabeled data. In *Asian Conference on Machine Learning*, pp. 221–236, 2016.

Marc Claesen, Frank De Smet, Pieter Gillard, Chantal Mathieu, and Bart De Moor. Building classifiers to predict the start of glucose-lowering pharmacotherapy using belgian health expenditure data. *arXiv preprint arXiv:1504.07389*, 2015.

Balázs Csanád Csáji et al. Approximation with artificial neural networks. *Faculty of Sciences, Etvs Lornd University, Hungary*, 24(48):7, 2001.

Francesco De Comité, François Denis, Rémi Gilleron, and Fabien Letouzey. Positive and unlabeled examples help learning. In *International Conference on Algorithmic Learning Theory*, pp. 219–230. Springer, 1999.

François Denis. Pac learning from positive statistical queries. In *International Conference on Algorithmic Learning Theory*, pp. 112–126. Springer, 1998.

Marthinus du Plessis, Gang Niu, and Masashi Sugiyama. Convex formulation for learning from positive and unlabeled data. In *International conference on machine learning*, pp. 1386–1394, 2015.

Marthinus C du Plessis, Gang Niu, and Masashi Sugiyama. Analysis of learning from positive and unlabeled data. In *Advances in neural information processing systems*, pp. 703–711, 2014.

Charles Elkan and Keith Noto. Learning classifiers from only positive and unlabeled data. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*, pp. 213–220. ACM, 2008.

Luis Galárraga, Christina Teflioudi, Katja Hose, and Fabian M Suchanek. Fast rule mining in ontological knowledge bases with amie. *The VLDB Journal*, 24(6):707–730, 2015.

Chen Gong, Hong Shi, Tongliang Liu, Chuang Zhang, Jian Yang, and Dacheng Tao. Loss decomposition and centroid estimation for positive and unlabeled learning. *IEEE transactions on pattern analysis and machine intelligence*, 2019.

Arthur Gretton, Karsten M Borgwardt, Malte J Rasch, Bernhard Schölkopf, and Alexander Smola. A kernel two-sample test. *Journal of Machine Learning Research*, 13(Mar):723–773, 2012.

Yu-Guan Hsieh, Gang Niu, and Masashi Sugiyama. Classification from positive, unlabeled and biased negative data. In *International Conference on Machine Learning*, pp. 2820–2829, 2019.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International conference on machine learning*, pp. 448–456. PMLR, 2015.

Dmitry Ivanov. Dedpul: Method for mixture proportion estimation and positive-unlabeled classification based on density estimation. *arXiv preprint arXiv:1902.06965*, 2019.

Shantanu Jain, Martha White, Michael W Trosset, and Predrag Radivojac. Nonparametric semi-supervised learning of class proportions. *arXiv preprint arXiv:1601.01944*, 2016.

Masahiro Kato, Liyuan Xu, Gang Niu, and Masashi Sugiyama. Alternate estimation of a classifier and the class-prior from positive and unlabeled data. *arXiv preprint arXiv:1809.05710*, 2018.

Ryuichi Kiryo, Gang Niu, Marthinus C du Plessis, and Masashi Sugiyama. Positive-unlabeled learning with non-negative risk estimator. In *Advances in neural information processing systems*, pp. 1675–1685, 2017.

Yongchan Kwon, Wonyoung Kim, Masashi Sugiyama, and Myunghee Cho Paik. Principled analytic classifier for positive-unlabeled learning via weighted integral probability metric. *Machine Learning*, pp. 1–20, 2019.

Wee Sun Lee and Bing Liu. Learning with positive and unlabeled examples using weighted logistic regression. In *ICML*, volume 3, pp. 448–455, 2003.

Fabien Letouzey, François Denis, and Rémi Gilleron. Learning from positive and unlabeled examples. In *International Conference on Algorithmic Learning Theory*, pp. 71–85. Springer, 2000.

Xiaoli Li and Bing Liu. Learning to classify texts using positive and unlabeled data. In *IJCAI*, volume 3, pp. 587–592, 2003.

Tongliang Liu and Dacheng Tao. Classification with noisy labels by importance reweighting. *IEEE Transactions on pattern analysis and machine intelligence*, 38(3):447–461, 2015.

Mehryar Mohri, Afshin Rostamizadeh, and Ameet Talwalkar. *Foundations of machine learning*. MIT press, 2018.

Arvind Neelakantan, Benjamin Roth, and Andrew McCallum. Compositional vector space models for knowledge base completion. In *ACL*, 2015.

Gang Niu, Marthinus Christoffel du Plessis, Tomoya Sakai, Yao Ma, and Masashi Sugiyama. Theoretical comparisons of positive-unlabeled learning against positive-negative learning. In *Advances in neural information processing systems*, pp. 1199–1207, 2016.

Curtis G Northcutt, Tailin Wu, and Isaac L Chuang. Learning with confident examples: Rank pruning for robust classification with noisy labels. *stat*, 1050:9, 2017.

Harish Ramaswamy, Clayton Scott, and Ambuj Tewari. Mixture proportion estimation via kernel embeddings of distributions. In *International Conference on Machine Learning*, pp. 2052–2060, 2016.

Yafeng Ren, Donghong Ji, and Hongbin Zhang. Positive unlabeled learning for deceptive reviews detection. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pp. 488–498, 2014.

Tomoya Sakai, Gang Niu, and Masashi Sugiyama. Semi-supervised auc optimization based on positive-unlabeled learning. *Machine Learning*, 107(4):767–794, 2018.

Clayton Scott. A rate of convergence for mixture proportion estimation, with application to learning from noisy labels. In *Artificial Intelligence and Statistics*, pp. 838–846, 2015.

Clayton Scott, Gilles Blanchard, and Gregory Handy. Classification with asymmetric label noise: Consistency and maximal denoising. In *Conference On Learning Theory*, pp. 489–511, 2013.

Ugo Tanielian and Flavian Vasile. Relaxed softmax for pu learning. In *Proceedings of the 13th ACM Conference on Recommender Systems*, pp. 119–127, 2019.

Maria A Zuluaga, Don Hush, Edgar JF Delgado Leyton, Marcela Hernández Hoyos, and Maciej Orkisz. Learning from only positive and unlabeled data to detect lesions in vascular ct images. In *International Conference on Medical Image Computing and Computer-Assisted Intervention*, pp. 9–16. Springer, 2011.