Differentiable Optimization of Generalized Nondecomposable Functions using Linear Programs

Abstract

We propose a framework which makes it feasible to directly train deep neural networks with respect to popular families of task-specific non-decomposable performance measures such as AUC, multi-class AUC, F-measure and others. A feature of the optimization model that emerges from these tasks is that it involves solving a Linear Programs (LP) during training where representations learned by upstream layers characterize the constraints or the feasible set. The constraint matrix is not only large but the constraints are also modified at each iteration. We show how adopting a set of ingenious ideas proposed by Mangasarian for 1-norm SVMs – which advocates for solving LPs with a generalized Newton method – provides a simple and effective solution that can be run on the GPU. In particular, this strategy needs little unrolling, which makes it more efficient during backward pass. Further, even when the constraint matrix is too large to fit on the GPU memory (say large minibatch settings), we show that running the Newton method in a lower dimensional space yields accurate gradients for training, by utilizing a statistical concept called *sufficient* dimension reduction. While a number of specialized algorithms have been proposed for the models that we describe here, our module turns out to be applicable without any specific adjustments or relaxations. We describe each use case, study its properties and demonstrate the efficacy of the approach over alternatives which use surrogate lower bounds and often, specialized optimization schemes. Frequently, we achieve superior computational behavior and performance improvements on common datasets used in the literature.

1 Introduction

Commonly used losses such as cross-entropy used in deep neural network (DNN) models can be expressed as a sum over the per-sample losses incurred by the current estimate of the model. This allows the direct use of mature optimization routines, and is sufficient for a majority of use cases. But in various applications ranging from ranking/retrieval systems to class imbalanced learning, the most suitable losses for the task do not admit a "decompose over samples" form. Examples include Area under the ROC curve (AUC), multi-class variants of AUC, F-score, Precision at a fixed recall (P@R) and others. Optimizing such measures in a scalable manner can pose challenges even in the shallow setting. For AUC maximization, we now know that convex surrogate losses can be used in a linear model [18, 27] in the so-called ERM framework. These ideas have been incorporated within a deep neural network and solved using SGD type method in [19]. These kinds of computational results on stochastic and online data models have also been explored in [4, 7, 12]. There are also results for measures other than the AUC: [26, 8] gives exact algorithms for optimizing F-score and [9, 32] proposes scalable methods for non-decomposable objectives which utilizes Lagrange multipliers to construct the proxy objective. The authors in [25] propose to use a structured hinge-loss upper bound to optimize average precision and NDCG. Recently, [10] presented a general formulation for such

nondecomposable measures using adversarial prediction framework, and showed that it is indeed possible to incorporate such measures into differentiable pipelines using ADMM based techniques.

Our work described here utilizes the simple observation that a number of these non-decomposable objectives can be expressed in the form of an integer program that can be relaxed to a linear program (LP). Our approach is based on the premise that tackling the LP form of the non-decomposable objective as a module within the DNN, one which permits forward and reverse mode differentiation and can utilize in-built support for specialized GPU hardware in modern libraries such as PyTorch, is desirable. First, as long as a suitable LP formulation for an objective is available, the module may be directly used. Second, based on which scheme is used to solve the LP, one may be able to provide guarantees for the non-decomposable objective based on simple calculations (e.g., number of constraints, primal-dual gap). The current tools, however, do not entirely address all these requirements, as we briefly describe next. A characteristic of the LPs that arise from the losses mentioned above is that the constraints (including the mini-batch of samples themselves) are modified at each iteration – as a function of the updates to the representations of the data in the upstream layers.

In principle, of course, backpropagating through a convex optimization model (and in particular, LPs) is not an unsolved problem. For LPs, we can take derivatives of the optimal value (or the optimal solution) of the model with respect to the LP parameters, and this can be accomplished by calling a powerful external solver. Often, this would involve the overhead of running the solver on the CPU. Solvers within CVXPY, are effective but due to their general-purpose nature, rely on interior point methods. OptNet [2] is quite efficient but designed for quadratic programs (QP): the theoretical results and its efficiency depends on factorizing a matrix in the quadratic term in the objective (which is zero/non-invertible for LPs). The primal-dual properties and implicit differentiation for QPs do not easily translate to LPs due to the polyhedral geometry in LPs. The ideas in [23] are only applicable when the number of constraints is approximately equal to the number of variables – an invalid assumption for the models that we study here.

In Section 2, we provide LP formulations of widely used nondecomposable terms that satisfy the requirements for our solver. In Section 3, we show that the modified Newton's algorithm in [20] can be used for deep neural network (DNN) training in an end-to-end manner without requiring external solvers where support for GPUs remains limited. Specifically, by exploiting self-concordance of the objective, we show that the algorithm can converge globally *without* line search strategies. We then analyze the gradient properties of our approach, and some modifications to improve stability during backpropagation. Our experiments in Section 4 show that this scheme based on Mangasarian's parametric exterior penalty formulation of the primal LP is a computationally effective and scalable strategy to solve LPs with a large number of constraints. On the practical side, we provide two ways to deal with the scaling issue when the constraint matrix is large. On the one hand, we show that sufficient dimension reduction can be used in our solver to solve the problem in a lower dimension space. On the other hand, when the matrix is sparse, with our new sparse implementation, we show that we can train Resnet-18 with $10\times$ mini-batch size (memory savings) on a 2080TI Nvidia GPU – our code will be available integrated within a popular package, see Fig 1.

2 Nondecomposable Functions and corresponding LP models

We first present a standard LP form and then reparameterize several generalized nondecomposable objectives in this way, summarized in a table in the supplement. We start with the binary AUC, extend it to multi-class AUC, and then later, discuss a ratio objective, F-score. We have included a discussion of other objectives that are amenable to our method in the supplement.

2.1 Notations and Generalized LP formulation

Notations. We use the following notations:
(i) n: number of samples used in training.
(ii) $X \in \mathbb{R}^{n \times d}$: the explanatory features fed to a classifier (e.g., parameterized by $\mathbf{w}$);
(iii) $f(x_i)$ (or $f(i)$): a score function for the classifier where $x_i \in X$ such that $f(X) = \mathbf{w}X$;
(iv) $Y \in \{0, 1\}$: target label and $\hat{Y} \in \{0, 1\}$: predicted label for binary classification, both in $\mathbb{R}^n$;
(v) $\phi(\cdot)$: non linear function applied on $f(X)$;
(vi) $A \otimes B$: Kronecker product of matrices A and B.

Figure 1: Overview of how to compute differentiable non-decomposable metric and code example of our LP solver. We provide sparse support for operations which are not supported in official Pytorch library (colored operations in the figure).

(vii) I_r: Identity matrix of size r and $\mathbb{1}$ is the indicator function.

(viii) $\mathbf{B}_{k,-}$ (and $\mathbf{B}_{|,k'}$) gives the k-th row (and k'-th column) of $\mathbf{B}$.

LP formulation. We consider a general linear program (LP) that contains nonnegative variables as well as inequality and equality constraints. The form of the LP is given as

$$\max_{u,v} g^T u + h^T v \quad \text{subject to} \quad Eu + Fv \leq p, \quad Bu + Gv = q \quad u, v \geq 0$$

We can write it more succinctly as

$$\text{Variable } x = [u\ v]; \quad \text{Coefficient } c = [-g\ -h]; \quad \text{Constraints } A = \begin{bmatrix} E & B & -B \\ F & G & -G \end{bmatrix}^T; \quad \text{Constants } b = [p\ q\ -q]^T$$

The corresponding primal LP becomes $\min_x c^T x$ subject to $Ax \leq b,\ x \geq 0$.

2.2 Maximizing AUC

The Area under the ROC Curve (AUC) calculates the probability that a classifier $f(\cdot)$ will rank a randomly chosen positive sample higher than a randomly chosen negative sample. AUC varies between 0 and 1, where 1 represents all positives being ranked above the negatives. AUC may be estimated using the Wilcoxon-Mann-Whitney (WMW) Statistic [14], as

Definition 2.1 (AUC). Let n be the number of samples. Let X_+ (and X_- resp.) be the set of positive (and negative resp.) samples such that $|X_+| + |X_-| = n$ where $|\cdot|$ is the cardinality of the set. Then, AUC is given as $\left(\sum_{i=1}^{|X_+|} \sum_{i=1}^{|X_-|} \mathbb{1}_{f(x_i)>f(x_j)} \right) / \left(|X_+|\,|X_-| \right)$ for $x_i : i \in \{1, \cdots, n\}$.

Here, we follow [4] to calculate the AUC based on the WMW statistic as follows.

$$\min_{z_{ij}} \sum_{i=1}^{|X_+|} \sum_{j=1}^{|X_-|} z_{ij} \quad \text{s.t.} \quad f(x_i) - f(x_j) \geq \epsilon - z_{ij} \quad \text{where } x_i \in X_+, x_j \in X_-; \quad z_{ij} \geq 0, \quad (1)$$

where ϵ is a given constant. Problem (1) maximizes AUC indirectly by minimizing the number of pairs (one each from the positive and negative classes) where the positive sample is not ranked higher than the negative sample: so, the number of zero entries in z equals the number of pairs where this condition is not true. For a given z, we have that,

$$\text{AUC} = \left(n - \|z\|_0\right) / \left(|X_+|\,|X_-|\right) = \left(n - \sum_i \sum_j \epsilon^{-1}\text{relu}(0, -z_{ij} + \epsilon) \right) / \left(|X_+|\,|X_-| \right).$$

If z_{ij} is 0, then $\epsilon^{-1}\text{relu}(0, -z_{ij} + \epsilon)$ equals 1. Otherwise $z_{ij} > 0$, it follows from the first constraint in (1), that $z_{ij} \geq \epsilon$, so $\epsilon^{-1}\text{relu}(0, -z_{ij} + \epsilon)$ equals 0. Observe that in (1), the number of constraints is $|X||X_-|$, which is $O\left(n^2\right)$.

2.3 Maximizing Multi-class AUC

An extension of AUC to the multi-class setting, AUC_μ, is defined in [17]. The AUC_μ objective optimizes an indicator matrix calculated on the orientation function, $O_{i,j}$ defined as,

Definition 2.2 (Orientation Function; [17]). Assume we have K classes $\{y_1, \cdots, y_K\}$. Let $\mathbf{f}(x_i, -) \in \mathbb{R}^K$ (extension of $f(.)$ to multi-class setting) indicate the model's prediction on x_i for each of the K classes (class-specific probability). Let x_i^* provide the index of x_i's true class label. Let $\mathbf{P} \in \mathbb{R}^{k \times k}$ be a partition matrix where $\mathbf{P}_{k,k'}$ is the cost of classifying a sample as class k when it should be k'. Define,

$$\mathbf{v}_{kk'} = \mathbf{P}_{k,-} - \mathbf{P}_{k',-} \text{ and } \widetilde{\mathbf{v}} = \mathbf{v}_{x_i^* x_j^*} \in \mathbb{R}^K; \quad O_{i,j} = (\widetilde{\mathbf{v}}_{x_i^*} - \widetilde{\mathbf{v}}_{x_j^*})(\langle \widetilde{\mathbf{v}}, \mathbf{f}(x_i, -) \rangle - \langle \widetilde{\mathbf{v}}, \mathbf{f}(x_j, -) \rangle).$$

The LP formulation of $\text{AUC}_m u$ is fully characterized by $\mathbf{P}$. We can set $\mathbf{P}(k, k) = 0\ \forall k$ and 1 for all other entries. We can also define a $\mathbf{P}$ with arbitrary entries or formulate AUC in a one-vs-all setting (denoted as AUC^{ova}). Here, for presentation, use the simplified 0/1 partition matrix $\mathbf{P}$. Let $\widetilde{\mathbf{f}}(i, j) = \mathbf{f}(x_i, x_i^*) - \mathbf{f}(x_j, x_i^*) + \mathbf{f}(x_j, x_j^*) - \mathbf{f}(x_i, x_i^*)$. Then the LP formulation is given by,

$$\text{AUC}_\mu^{\text{bin}} : \min_{z_{ij}} \sum_{i=1}^n \sum_{j=1:x_i^* < x_j^*}^n z_{ij} \quad \text{s.t.} \quad \widetilde{\mathbf{d}}_{ij} \widetilde{\mathbf{f}}(i, j) \geq \epsilon - z_{ij}, \quad \forall i, j : x_i^* < x_j^* \quad z_{ij} \geq 0 \quad (2)$$

where $\widetilde{\mathbf{d}}_{ij} = \widetilde{\mathbf{v}}_{x_i^*} - \widetilde{\mathbf{v}}_{x_j^*}$. Problem 2 can be seen as an extension of our binary AUC model, where the z_{ij} is the ranking between a pair of points defined for multiple classes.

2.4 Maximizing F-score

The F-score (or F-measure) is a representative of objectives expressed as ratios of some combination of True positives (TP), False positives (FP), True negatives (TN) and False negatives (FN). We utilize the result in [8] to express the F-score in the ratio form and further relax it into the LP form. The detailed LP formulation of F-score and other ratio functions is in supplement.

3 Backpropagation via Fast Exterior Penalty Optimization

Unlike traditional feedforward networks, where the output of each layer is a relatively simple (albeit non-linear) function of the previous layer, a LP layer must solve a constrained problem, therefore implementing scalable/efficient backpropagation schemes that minimizes overhead requires more care and is an active topic of research. This problem is, of course, not unique to LPs and manifests in differentiable sorting [22] and formulating quadratic or cone programs [3]. One may unroll gradient descent steps [3, 13, 24] or use projections [34]. Recently [1] introduced a package for differentiable constrained convex programming, which includes LPs as a special case. For LPs, [23] presents an unrolled scheme and [6] shows that we can differentiate through LP formulations of sorting/ranking *exactly* by using smooth approximations of projection steps. [5] describes an interesting approach where one computes approximate gradients through ranking/shortest path problems by stochastic perturbation techniques.

Remark 1. *Some previous works [34] have considered LPs where the constraints are deterministic (for a fixed input dimension), i.e., do not depend on the data X, which is different from the LPs in Sections 2.2–2.4.*

Note that perturbation techniques in [5] are applicable to our LPs as well. The Fenchel Young losses in [5] is attractive because there is no need to compute the Jacobian. Implementation-wise, one could think of the backward pass as a function given the input and output of the forward pass. But the gradient expressions of the losses is an expectation and hence may require multiple calls to a LP solver in order to approximate the expectation. although parallelization and warm starts were shown to alleviate this dependency by sampling in parallel.

Rationale for our approach. Consider a LP with a large m number of constraints in fixed dimensions n ($n \ll m$). This assumption holds in all formulations in Section 2. This is because we assume that the architecture is fixed whereas minibatch size depends on the complexity of the task (stable gradient or when noise in gradient is high). Hence, solving such LPs using off-the-shelf solvers as

in [5], in the general case, could slow down training. The strategy in [1] does offer benefits over [2] for sparse QPs. Our strategy is to run Mangasarian's Newton's method on an exterior penalty function of the LP. There are two advantages: **(i)** during **forward** pass, quadratic local convergence of Newton's method indicates that unrolling the method may be reasonable; and further **(ii)** based on the relationship between dual and primal variables, and the exactness of the exterior penalty we can show that **backward** pass is independent of m. We will discuss both results and some modifications to deal with discontinuous Hessian (and its inverse) that is required for Newton's method. A similar approach is adopted in [2] where Primal-Dual Interior Point methods with implicit differentiation is used for differentiation purposes. But the exterior penalty in (3) satisfies a nice property: primal and dual solutions are related by a *closed form* expression which can be exploited for efficient backpropagation.

3.1 Forward Pass using Newton's Algorithm on a Sufficiently Reduced Space

Fast automatic (forward or reverse mode) differentiation requires performing the *forward* pass efficiently. In our setting, we seek to solve and backpropagate through an LP. We will focus on reverse mode differentiation since it is the most suitable for DNN training.

Given a primal LP, for a fixed accuracy $\epsilon > 0$, [20] solves an unconstrained problem,

$$\min_y g(y) := \frac{1}{2} \|\sigma(Ay - b)\|^2 + \epsilon c^T y, \tag{3}$$

where $\sigma(\cdot) = \max(\cdot, 0)$ represents the elementwise relu function. A modified Newton's method can be used to solve (3) that performs the following iterations:

$$y = y + \lambda d \tag{4}$$

where $d = \tilde{H}(y)^{-1}\nabla g(y) := (\nabla^2 g(y) + \rho I)^{-1}\nabla g(y)$. In large scale settings of A, b, such Newton methods are known to perform empirically better than gradient descent [21, 15]. We will evaluate if this holds for our purposes shortly.

Why is Newton's method applicable for minibatches? In general, the convergence of Newton's method depends strongly on initialization, i.e., we can only provide local convergence results. However, this is not the case for our problems since in our examples, either the level sets are bounded from below; or the feasible set is compact, as noted in [20]. There are two reasons why the result, by itself, is insufficient for our purposes: **(i)** it assumes that we can perform line search to satisfy Armijo condition; **(ii)** even with line search, the result does not provide a *rate* of convergence. In DNN training, such line search based convergence results can be very expensive. The key difficulty is handling the discontinuity in the Hessian. As a remedy, we use self concordance of (3) to guarantee global convergence of (4) iterations for the exterior penalty formulation in (3). To do so, we first show a result (proof in supplement) that characterizes the discrepancy between the actual Hessian of (3) and the modified one in (4) when A is randomly distributed.

Lemma 1. *Assume that A is a random matrix, and fix some $y \in \mathbb{R}^n$. Then with probability one, g in (3) can be approximated by a constant function (given by $\tilde{H}, \nabla g(y)$) over a sufficiently small neighborhood of y.*

Intuitively, Lemma 1 states that with probability one, each y has a neighborhood in which the Hessian is constant. In addition, the modified Hessian is nonsingular at all points (in particular the optimal y^*), and so we can then show the following global convergence result.

Theorem 2. *Newton's method converges globally at a linear rate with local quadratic convergence.*

Proof. (Sketch) First, we use the fact that the objective in equation 3 is piecewise quadratic, and hence self concordant. Second, observe that the possible choices of Hessian are finite, and so we can choose $\rho > 0$ so that there is a descent direction *without* line search, i.e., there exist a step size $\lambda > 0$ such that $\lambda\nabla g(x)^T d < 0$. Finally, we use Thm. 4.1.12 in [28] to claim the result. □

Please see supplement for the proof. The loss function is almost surely quadratic in the neighborhood of any y, thus intuitively suggests local quadratic convergence independent of the starting point.

Remark 2. *Convergence in Thm. 2 is guaranteed under standard constraint qualification assumptions. Linear Independent Constraint Qualification (LICQ) is satisfied for AUC, and Multi-class AUC formulations in §2. But the F-score formulation does not satisfy LICQ, hence we need safeguarding principles in the initial iterations (until iterates get close to the optimal solution).*

Our analysis of the Newton's method for LP so far indicate that we may be able to use a constant step size λ (avoid linesearch) to obtain fast convergence provided that we are able to choose ρ sufficiently small. For our purposes, we assume λ to be a hyperparameter and can be tuned by cross validation.

Sketching d using Sufficient Dimension Reduction (SDR). For training the backbone network, we have to compute d in (4) several times within each training iteration. But each minibatch corresponds to an LP instantiation in (3), so it may suffice to compute an approximate d in each Newton's iteration. To approximate d, we use sufficient dimension reduction in which a lower dimensional LP obtained by projecting A is solved [35, 16]. That is, instead of the inverse of $\tilde{H}$, we will compute a lower dimensional sketch of $\tilde{H}$ by using SA (and Sb) instead of A (and b) for some sampling matrix S and solve problem (3). *The advantage of using SDR (as opposed to naive sketching) is that the lower dimensional space can also be chosen using data driven cross validation techniques, making it ideal for training.* So, the size of minibatch does not matter – as long as the minibatch can be sufficiently reduced, our solver is directly applicable, especially for low resource, memory constrained applications. For a fixed (low) dimension parameter, our sketched $\underline{d}$ is,

$$\underline{d} = \underline{H}^{-1}\underline{g} \quad \text{where} \quad \underline{g} = \frac{\partial}{\partial y}(\|\text{relu}(Ay - b)\|_2^2) \approx (SA)^T S \cdot \text{relu}(\text{sign}(Ay - b)), \tag{5}$$

$$\underline{H} \approx (\text{diag}(S \cdot \text{relu}(\text{sign}(Ay - b)) \odot S \cdot \text{relu}(\text{sign}(Ay - b))) \cdot SA)^T \cdot SA. \tag{6}$$

It is easy to see that the approximate update can be seen as equivalent to Iterative Hessian Sketch algorithm which has geometric convergence rate [29].

3.2 Backward Pass using Optimal Dual Variables Aided by Unrolling

The advantage of optimizing the exterior penalty in (3) is that given an iterate y_t, accuracy ϵ, we can get the optimal dual solution v_t by simple thresholding, i.e., $v_t = 1/\epsilon(A^T\sigma(Ay - b))$. By complementarity slackness, nonzero coordinates of v_t specify the set of active constraints in $Ax \le b$. So, given an approximate y_t such that $\nabla g(y_t)\tilde{H}(y_t)^{-1}\nabla g(y_t) \le \epsilon$, to get the primal solution x^*, we solve the "active" linear system given by $\tilde{A}\tilde{b}$, where $\tilde{A}$ denotes the active rows of A and the corresponding subvector $\tilde{b}$. So, backpropagation through the layer reduces to computing derivatives of $\tilde{A}^{-1}\tilde{b}$ (simple via automatic differentiation). Supplement gives a systematic way of choosing ϵ.

How to backpropagate through unrolled iterations? We assume that the chain rule is applicable up to this LP layer and is $\frac{\partial L}{\partial x}\frac{\partial x}{\partial A}$ (for one of the parameters A), and note that it is possible to find $\frac{\partial L}{\partial x}$ (either directly or using a chain rule). Therefore we focus our attention on $\frac{\partial x}{\partial A}$, which involves the LP layer. Indeed, unrolling each iteration in (4) is equivalent to a "sublayer". So in order to backpropagate we have to show the partial derivatives of each operation or step wrt to the LP parameters A, b, and c.

Our goal is to calculate $\frac{\partial d}{\partial A}$ where $d = Q^{-1}q$, $Q = \tilde{H}$ and $u = \nabla g(y)$. We can use the product rule to arrive at: $\partial d = -\left(u^T Q^{-1} \otimes Q^{-1}\right)\partial Q + Q^{-1}\partial u$. To see this, note that we have used the chain rule to differentiate through the inverse in the first term. The second term is easy to compute similar to the computation of Hessian. For each of these terms we eventually have to compute $\frac{\partial Q}{\partial z}$ or $\frac{\partial u}{\partial z}$ where $z \in \{c, A, b\}$ which can also be done by another application of chain rule. Please see supplement for empirical verification of unrolled gradient and the one provided by $\tilde{A}^{-1}\tilde{b}$.

Before proceeding, we should note an issue that comes up when differentiating each step of the unrolled algorithm because the Hessian is piecewise linear (constant) as a function of the input to that particular layer. Here, some possible numerical approximations are needed, as we describe below.

Remark 3. *Note that the diagonal matrix term in $\frac{\partial Q}{\partial A}$ is nondifferentiable due to the presence of the step function. However, the step function is a piecewise constant function, and hence has zero derivative almost surely, that is, in any bounded set S, $x \in S$, if a ball (of radius $r > 0$,) $B_r(x) \subseteq S$, then the Lebesgue measure of the set of nondifferentiable points on S is zero. Please see supplement for a formal justification where we show this by approximating the step function using a sequence of logistic functions with increasing slope parameter at the origin.*

Therefore, in this setting, Remark 3 provides a way to compute an approximate sub-gradient when using Newton's method based LP layers. The function is a piece-wise quadratic function and differentiable everywhere, and the inverse of the Hessian acts as a preconditioner.

Summary. Our forward pass involved three steps: **(1)** finite steps of Newton's method using which we **(2)** computed the dual variable by a thresholding operation, and **(3)** finally, to get the primal solution, these dual variables are first used to identify the active constraints followed by solving a linear system. To backpropagate through these three steps, we must differentiate through each layer of our procedure including $\tilde{A}^{-1}\tilde{b}$: this is independent of whether we use unrolling or Danskin's theorem. For instance, using Danskin's theorem here would involve differentiating through the fixed point of the Newton's iterations similar to (regularized) gradient descent iterations in iMAML [31].

4 Experiments

In this section, we conduct experiments on commonly used benchmarks to show that our framework can be used to optimize multiple different objectives within deep neural networks and lead to performance gain. We start with binary AUC optimization, and then extend to multi class AUC optimization and F-score optimization. We also show that nonnegative matrix factorization can be optimized in linear programming form in our framework.

Optimizing Binary AUC

We follow the current state-of-the-art work on AUC optimization [19] to conduct experiments on optimizing AUC score directly with deep neural networks. The baseline algorithms we compare with for binary AUC are cross-entropy loss and two algorithms (PPD-SG and PPD-AdaGrad) from [19].

Datasets: Cat&Dog, CIFAR10, CIFAR100, and STL10 (See supplement for introduction of these datasets). We follow [19] to use 19k/1k, 45k/5k, 45k/5k, 4k/1k training/validation split on Cat&Dog, CIFAR10, CIFAR100, STL10 respectively.

Experimental setting. We construct imbalanced binary classification task by using half of the classes as positive class and another half as negative class, and dropping samples from negative class by a certain ratio, which is reflected by the positive ratio (the ratio of the majority class to the minority class) in Table 1. During the experiment, We use the same random seed, learning rate and total number of iterations in all of our experiments including multi class AUC and F-score experiments. (See supplement for details of model architecture, learning rate, etc.)

Table 1: Binary AUC optimization results on four benchmark datasets.

AUC(%)	Cat&Dog				CIFAR10			
Positive Ratio	91%	83%	71%	50%	91%	83%	71%	50%
Cross-Entropy	67.6	74.6	85.1	87.4	65.2	73.3	78.1	**83.7**
PPD-SG	**79.1**	**81.5**	85.5	87.1	69.8	73.9	**79.1**	82.6
PPD-AdaGrad	77.3	80.6	83.7	86.3	69.7	74.1	78.4	83.1
Ours	78.6	81.3	**85.6**	**87.8**	**72.5**	**74.4**	78.3	82.7
AUC(%)	CIFAR100				STL10			
Positive Ratio	91%	83%	71%	50%	91%	83%	71%	50%
Cross-Entropy	57.8	58.4	62.2	66.3	63.5	67.1	72.7	80.8
PPD-SG	56.5	58.9	61.6	65.2	**70.7**	71.6	75.1	77.4
PPD-AdaGrad	56.2	59.0	62.6	67.6	68.5	**72.4**	76.7	78.5
Ours	**58.2**	**60.5**	**64.5**	**69.0**	68.4	71.1	**76.7**	**81.6**

Results. The results are shown in Table 1. We can see that our method slightly outperforms [19] and outperforms cross-entropy loss by a large margin, especially on imbalanced datasets, where the AUC objective shows superiority over cross-entropy loss.

Influence of ϵ. We test the influence of ϵ using Cat&Dog as an example. Results (see supplement for the table) show that $\epsilon = 0.1$ gets slightly worse performance than $\epsilon = 0.01$, while $\epsilon = 0.001$ performs much worse. To choose ϵ, we follow the approach proposed by [20]. If for two successive values of $\epsilon_1 > \epsilon_2$, the value of the ϵ perturbed quadratic function is the same, then it is the least 2-norm solution of the dual. Therefore, we simply choose an ϵ that satisfies this property, which is chosen to be 0.01 in our experiments.

Optimizing Multiclass AUC

We further demonstrate our method for optimizing multiclass AUC. Similar to previous section on binary AUC, we construct imbalanced multiclass datasets by dividing datasets into 3 classes and drop samples from 2 of them and report the one-versus-all AUC (denoted as AUC$^{\text{ova}}$) and AUC$^{\text{bin}}_{\mu}$ score . For STL10, we group class $0 - 2, 3 - 5, 6 - 9$ into the three classes, and drop samples from the first two classes. For CIFR100, we group class $0 - 32, 33 - 65, 66 - 99$ into three classes, and also drop samples from the first two classes.

Results. Results are in Table 2. In addition to one-versus-all AUC metric, we also report the performance in terms of AUC_μ [17] which is specifically designed for measuring multiclass AUC and preserves nice properties of binary AUC such as being insensitive to class skew. We can see that our method outperforms cross-entropy loss on all four datasets and under all different skewed ratios.

Table 2: Multiclass AUC optimization results on STL10 and CIFAR100. Drop rate is the proportion used when dropping samples from two of three classes.

$AUC^{ova}(\%)$	CIFAR100				STL10			
Drop rate	90%	80%	60%	0%	90%	80%	60%	0%
Cross-Entropy	54.3	**59.4**	62.7	63.5	66.9	68.0	74.8	81.0
Ours	**58.4**	59.2	**64.1**	**65.7**	**72.9**	**72.5**	**75.7**	**82.7**
$AUC_\mu^{bin}(\%)$	CIFAR100				STL10			
Drop rate	90%	80%	60%	0%	90%	80%	60%	0%
Cross-Entropy	55.1	60.6	65.0	64.0	68.9	69.6	75.8	82.2
Ours	**60.1**	**61.2**	**66.0**	**67.2**	**76.1**	**74.4**	**77.7**	**84.5**

(a) Positive class: 0   (b) Positive class: 1   (c) Positive class: 2

Figure 2: ROC curve of multiclass AUC optimization on STL10 with 90% drop rate. We divide STL10 into 3 classes and use one as positive class and other two as negative class to plot the ROC.

(a) Evaluation of the quality of $F1$-score predicted by our solver and Ap-Perf.

(b) Runtime comparison of our solver and blackbox solver [30]

(c) The relationship between reduced size and accuracy when using SDR on constraint matrix A.

Figure 3: Three numerical experiments to show the properties of our solver.

Optimizing $F1$-score

We show that by directly optimizing $F1$-score, we can achieve a better performance than when using cross entropy loss. In addition to cross entropy loss, we perform evaluations with two other methods that can also directly optimize the $F1$-score. First, we replace our solver with CVXPY-SCS [1], which is a differentiable general purpose linear programming solver; second, we perform comparisons with AP-Perf [10] which offers differentiable optimization of $F1$-score using an adversarial prediction framework. The datasets and our setup to group them into two classes remain the same as in binary AUC section. The results show that Our method yields consistent improvement over cross-entropy loss in terms of $F1 - score$. The accuracy of cross-entropy loss on Cat&Dog, CIFAR10, CIFAR100 and STL10 is 76.0%, 70.3%, 60.4%, 71.8%, respectively, while our method gives **77.8%**, **72.6%**, **63.4%**, **72.7%**. When we optimize $F1$-score directly, there exists a local optimal point where assigning all examples to the positive class leads to $F1$-score of 66.7%. Both CVXPY-SCS and AP-Perf fall into this local optimal on four datasets (except that CVXPY-SCS gets out of the local optimal point on Cat&Dog and gives 70.1% accuracy). Note that although our solver, CVXPY-SCS and AP-Perf are trying to solve the same objective, the backward gradient will be different due to different approximations used by the methods.

Comparing with blackbox solvers. Recently, several results [30, 5] use blackbox solvers for solving combinatorial problems, which can also been used as a LP solver for problems where we need dx^*/dc

Table 3: Properties of different methods. c, A, b are the parameters describing a linear programming: $\min cx, s.t. Ax \leq b$. x^* denotes the optimal solution. The extra cost for computing backward gradient for [5], depending on implementation, can either be N times time cost, or N times memory cost plus some time cost brought by increased batch size (see supplement for detailed explanation).

	Ours	CVXPY-SCS	Perturbed solver [5]
Gradients support	$\frac{dx^*}{dc}, \frac{dx^*}{dA}, \frac{dx^*}{db}$	$\frac{dx^*}{dc}, \frac{dx^*}{dA}, \frac{dx^*}{db}$	$\frac{dx^*}{dc}$
GPU support	✓	✗	depends on solver
Sparsity support	✓	✗	depends on solver
Extra cost for computing backward gradient (denote forward time cost as 1)	Nearly zero	around 1	N (# perturbations)

(c is the cost vector in standard form LP). These methods can utilize existing LP solvers and compute backward gradient by calling the LP solvers on perturbed LP problems. To our knowledge, the current state-of-the-art LP solvers are often CPU based, which means that one needs to transfer the LP parameters from GPU to CPU, then solve the LP on the CPU before getting the solution back. These CPU-based solvers will usually be slower than our GPU based solver, especially when the batch size is large. To evaluate this property, we randomly construct LP problems using AUC as an example and make the cost vector the parameter to optimize. In Fig. 3b, we compare the runtime of our solver and the blackbox solver in [30] (with the LP solver from scipy package). We can see that our GPU based solver is not sensitive to the increase in the batch size, while the CPU based solver is, due to the lack of support for mini-batch operations. Our solver has a more clear advantage in backward pass because the matrix needed for computing gradient is already computed during forward pass thus the backward pass is nearly **free**, while the blackbox solver [30] needs at least the same time as forward pass to compute backward gradient. We also compare our solver with [5] in Table 3.

Dealing with large scale LP. In practice we often encounter large scale LPs whose constraint matrix may be too large to fit into the GPU memory. We first show that we can utilize sufficient dimension reduction in Fig. 3c, which demonstrates a reasonable tradeoff between reduced size and accuracy. Then we show that when the constraint matrix is sparse, we can readily utilize sparse operations to save memory. We have incorporated functionality to use sparsity within our solver [11, 33]. Consider AUC maximization in which the constraint matrix is extremely sparse. With our sparse implementation, we are able to run SGD on Resnet-18 with minibatch size upto 200 on a 2080Ti GPU with just 1GB memory whereas the same problem can take upto 11GB using dense operations ($\approx 10\times$ memory savings) with some overhead.

Limitations. Scaling is still a key limitation for differentiable LP solvers. We present two ways to mitigate these problems but there is an associated cost. Our proposed SDR sacrifices some accuracy. Partly due to support within available libraries sparse operations can sometimes be slow when the size of the matrices is large which should improve with better sparsity support in existing libraries.

5 Conclusions

We demonstrated that various non-decomposable objectives can be optimized within deep neural networks in a differentiable way under the same general framework of LPs using a modified Newton's algorithm proposed by Mangasarian. A number of recent papers have studied the general problem of backpropagating through convex optimization modules, and this literature provides several effective approaches although scalability remains a topic of active research. Our work complements these results and shows that the operations needed can be implemented to utilize the capabilities of modern deep learning libraries. While our experimental results suggest that promising results on binary AUC, multi-class AUC and F-score optimization within DNNs is achievable, we believe that the module may have other applications where the number of constraints are large and data-dependent.

Potential negative societal impacts. Optimizing non-decomposable measures such as AUC is a fundamental task in statistics/machine learning and not tied to specific applications, so we do not see a negative societal impact of the technical development described here. It is possible, however, that modules such as these can be used within general applications that are detrimental to society.

References

[1] A. Agrawal, B. Amos, S. Barratt, S. Boyd, S. Diamond, and J. Z. Kolter. Differentiable convex optimization layers. In *Advances in neural information processing systems*, pages 9562–9574, 2019.

[2] B. Amos and J. Z. Kolter. Optnet: Differentiable optimization as a layer in neural networks. *ICML*, 2017.

[3] B. Amos, L. Xu, and J. Z. Kolter. Input convex neural networks. In *International Conference on Machine Learning*, pages 146–155, 2017.

[4] K. Ataman, W. N. Street, and Y. Zhang. Learning to rank by maximizing auc with linear programming. In *The 2006 IEEE International Joint Conference on Neural Network Proceedings*, pages 123–129. IEEE, 2006.

[5] Q. Berthet, M. Blondel, O. Teboul, M. Cuturi, J.-P. Vert, and F. Bach. Learning with differentiable perturbed optimizers. *ICLR*, 2020.

[6] M. Blondel, O. Teboul, Q. Berthet, and J. Djolonga. Fast differentiable sorting and ranking. In *International Conference on Machine Learning*, 2020.

[7] C. Cortes and M. Mohri. Auc optimization vs. error rate minimization. In *Advances in neural information processing systems*, pages 313–320, 2004.

[8] K. J. Dembczynski, W. Waegeman, W. Cheng, and E. Hüllermeier. An exact algorithm for f-measure maximization. In J. Shawe-Taylor, R. S. Zemel, P. L. Bartlett, F. Pereira, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems 24*, pages 1404–1412. Curran Associates, Inc., 2011.

[9] E. Eban, M. Schain, A. Mackey, A. Gordon, R. Rifkin, and G. Elidan. Scalable learning of non-decomposable objectives. In *Artificial Intelligence and Statistics*, pages 832–840, 2017.

[10] R. Fathony and Z. Kolter. Ap-perf: Incorporating generic performance metrics in differentiable learning. In *International Conference on Artificial Intelligence and Statistics*, pages 4130–4140. PMLR, 2020.

[11] flaport. torch-sparse-solve. `https://github.com/flaport/torch_sparse_solve`, 2020.

[12] W. Gao, R. Jin, S. Zhu, and Z.-H. Zhou. One-pass auc optimization. In *International conference on machine learning*, pages 906–914, 2013.

[13] I. Goodfellow, M. Mirza, A. Courville, and Y. Bengio. Multi-prediction deep boltzmann machines. In *Advances in Neural Information Processing Systems*, pages 548–556, 2013.

[14] J. A. Hanley and B. J. McNeil. The meaning and use of the area under a receiver operating characteristic (roc) curve. *Radiology*, 143(1):29–36, 1982.

[15] S. S. Keerthi, V. Sindhwani, and O. Chapelle. An efficient method for gradient-based adaptation of hyperparameters in svm models. In *Advances in neural information processing systems*, pages 673–680, 2007.

[16] K. Kim, B. Li, Z. Yu, L. Li, et al. On post dimension reduction statistical inference. *Annals of Statistics*, 48(3):1567–1592, 2020.

[17] R. Kleiman and D. Page. Aucμ: A performance metric for multi-class machine learning models. In *International Conference on Machine Learning*, pages 3439–3447, 2019.

[18] M. Liu, X. Zhang, Z. Chen, X. Wang, and T. Yang. Fast stochastic auc maximization with $o(1/n)$-convergence rate. In *International Conference on Machine Learning*, pages 3189–3197, 2018.

[19] M. Liu, Z. Yuan, Y. Ying, and T. Yang. Stochastic auc maximization with deep neural networks. *ICLR*, 2019.

[20] O. Mangasarian. A newton method for linear programming. *Journal of Optimization Theory and Applications*, 121(1):1–18, 2004.

[21] O. L. Mangasarian. Exact 1-norm support vector machines via unconstrained convex differentiable minimization. *Journal of Machine Learning Research*, 7(Jul):1517–1530, 2006.

[22] G. Mena, D. Belanger, S. Linderman, and J. Snoek. Learning latent permutations with gumbel-sinkhorn networks. *ICLR*, 2018.

[23] Z. Meng, S. N. Ravi, and V. Singh. Physarum powered differentiable linear programming layers and applications. *arXiv preprint arXiv:2004.14539*, 2020.

[24] L. Metz, B. Poole, D. Pfau, and J. Sohl-Dickstein. Unrolled generative adversarial networks. *ICLR*, 2017.

[25] P. Mohapatra, M. Rolinek, C. Jawahar, V. Kolmogorov, and M. Pawan Kumar. Efficient optimization for rank-based loss functions. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pages 3693–3701, 2018.

[26] Y. Nan, K. M. Chai, W. S. Lee, and H. L. Chieu. Optimizing f-measure: A tale of two approaches. *arXiv preprint arXiv:1206.4625*, 2012.

[27] M. Natole, Y. Ying, and S. Lyu. Stochastic proximal algorithms for auc maximization. In *International Conference on Machine Learning*, pages 3710–3719, 2018.

[28] Y. Nesterov. *Introductory lectures on convex optimization: A basic course*, volume 87. Springer Science & Business Media, 2013.

[29] M. Pilanci and M. J. Wainwright. Iterative hessian sketch: Fast and accurate solution approximation for constrained least-squares. *Journal of Machine Learning Research*, 17(53):1–38, 2016. URL `http://jmlr.org/papers/v17/14-460.html`.

[30] M. V. Pogančić, A. Paulus, V. Musil, G. Martius, and M. Rolinek. Differentiation of blackbox combinatorial solvers. In *International Conference on Learning Representations*, 2019.

[31] A. Rajeswaran, C. Finn, S. M. Kakade, and S. Levine. Meta-learning with implicit gradients. In *Advances in Neural Information Processing Systems*, pages 113–124, 2019.

[32] S. N. Ravi, A. Venkatesh, G. M. Fung, and V. Singh. Optimizing nondecomposable data dependent regularizers via lagrangian reparameterization offers significant performance and efficiency gains. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 5487–5494, 2020.

[33] rusty1s el al. pytorch-sparse. `https://github.com/rusty1s/pytorch_sparse`, 2020.

[34] X. Zeng, R. Liao, L. Gu, Y. Xiong, S. Fidler, and R. Urtasun. Dmm-net: Differentiable mask-matching network for video object segmentation. In *Proceedings of the IEEE International Conference on Computer Vision*, pages 3929–3938, 2019.

[35] X. Zhang, Q. Mai, and H. Zou. The maximum separation subspace in sufficient dimension reduction with categorical response. *Journal of Machine Learning Research*, 21(29):1–36, 2020. URL `http://jmlr.org/papers/v21/17-788.html`.