Scaling Channel-Invariant Self-Supervised Learning for Microscopy Images

Abstract

Recent advances in self-supervised pre-training of foundation models for natural images have made them a popular choice for various visual systems and applications. Self-supervised strategies have also shown promise in non-RGB scientific imaging domains such as in biology, medical and satellite imagery, but their broader application is hampered by heterogeneity in channel composition and semantics between relevant datasets: two datasets may contain different numbers of channels, and these may reveal distinct aspects of objects of interest. This work explores this challenge in the context of fluorescent microscopy images. We revisit existing deep-learning approaches in that field and build upon the DINOv2 architecture and self-supervised pre-training objective to propose a general purpose feature extractor for biological microscopy images that handles images with varying numbers of channels and reliably generalizes to unseen channel combinations at evaluation time.

1 Introduction

By enabling scientists to reveal the substructural composition and dynamics of cells and tissues, fluorescent microscopy has enabled countless scientific discoveries that collectively underpin modern medicine and our understanding of life. Owing to a recent confluence of effective protocols to reveal distinct subcellular structures across multiple channels, and to automate image acquisition across hundreds of experimental conditions and thousands of cells, high-content fluorescent microscopy is emerging as a powerful platform to decipher mechanisms of disease, to accelerate drug discovery, and to broadly interrogate cellular biology at scale (Chandrasekaran et al., 2021). Self-supervised deep learning strategies are particularly well suited to mine microscopy imaging datasets for biologically meaningful features and to yield with them foundational models of cellular state that can be leveraged for scientific discovery (Doron et al., 2023). Indeed, by delaying the use of labeled data to a later stage, the features are less biased and more robust.

However, the application of deep learning to microscopy images comes with its own set of challenges. Deep learning methods for vision generally assume a fixed number of channels per image, for instance three for RGB. By contrast, to observe specific biological phenomena of interest, biologists routinely design bespoke imaging protocols to reveal distinct sets of cellular structures over any of typically 2-8 channels (depending on the type of microscope and fluorophores used). The landscape of fluorescent microscopy thus consists of a vast number of small-to-moderate scale datasets with highly variable channel content and number (Chen et al., 2024). Moreover, designed to reveal distinct parts of the cell, the correlation between channels is substantially lower than for natural images (Bao et al., 2024).

Models trained on one dataset can thus typically not be re-used in other studies, and lack of sufficient training data limit their performance even on IID tasks. Learning more powerful biological representations and moving towards a unified feature extraction model requires strategies to train models across data with variable number of channels and that are robust to distinct channel interactions and biological semantics. Here, we investigate the performance and scaling properties of state-of-the-art self-supervised learning when adapted with different channel-invariant training strategies.

Recently proposed methods for channel-invariant learning can be broadly divided into either strategies that jointly encode the channels, relying on customizations of vision transformers (ViTs) to account for varying channel number up to some maximum (Bao et al., 2024; Bourriez et al., 2024; Pham & Plummer, 2024), or approaches that encode the channels independently (Xun et al., 2024; Kraus

Figure 1: **Training across fluorescent microscopy datasets.** (A) We consolidate images from Human Protein Atlas (2019)(HPA-FOV), Le et al. (2022)(HPA-SC), Cho et al. (2022)(OpenCell), Viana et al. (2023)(WTC) and Doron et al. (2023)(Cell Painting), into a dataset (ExtendedCHAMMI) that reflects the diversity in channel number, order, and semantics, that characterizes fluorescent microscopy studies. Despite some conventions (e.g. the nucleus is usually imaged using blue fluorescing stains), there is no necessary correspondence between specific channels and/or wavelengths, and their biological semantics. Images are pseudo-colored according to emission wavelength. CellPainting visualizes Plasma Membrane (PM) and Actin in one channel. (B) We benchmark self-supervised channel-invariant strategies on their capacity to yield features that generalize to OOD tasks. Our DINO BoC approach compares favorably.

et al., 2024). However, these studies are either based on supervised learning, employ relatively small datasets, or do not evaluate performance across different cell datasets. In this work, we leverage the DINOv2 (Oquab et al., 2023) pre-training strategy, which has been shown to be a powerful approach to learn rich features from natural images at large scale . We hypothesize that the same approach can facilitate scaling channel-invariant models across larger collections of microscopy datasets with disparate channel configurations. We illustrate the problem in Figure 1.

Our contributions are the following:

- We revisit and scale the approach of encoding the channels independently, using ViTs and DINOv2, to establish channel-agnostic ViTs for fluorescent microscopy which we term *DINO Bag of Channels* (DINO BoC).

- We assess scaling properties of joint and independent channel encoding strategies across large-scale datasets and on cross-dataset generalization setups, and report superior performance gains for DINOv2 and DINO BoC in particular.

- We further analyze the impact of joint versus independent channel encoding through a novel channel-invariant strategy that leverages a Hierarchical Attention scheme, named DINO HA.

- We compare in-domain and out-of-distribution (OOD) performance of different approaches on the challenging CHAMMI benchmark and find that DINO BoC outperforms all baselines including the best supervised one on two datasets out of three.

2 RELATED WORK

Vision transformers and self-supervised learning. The goal of self-supervised learning (SSL) is to learn to project the data onto an embedding space such that the features retain the information contained in the original data while being organized in a way that reflects high-level relationships between the data points. In SSL this is achieved by using the samples themselves as the source of

supervision, without leveraging additional labels. Learning task-agnostic representations has become pervasive both in Natural Language Processing (Devlin et al., 2019; Radford et al., 2019; Touvron et al., 2023) and, more recently, in Computer Vision (Chen et al., 2020; Caron et al., 2021; He et al., 2022; Assran et al., 2023). The promise of this approach is that it enables the use of large amounts of unlabeled data to learn multi-purpose features that can be applied off the shelf, without fine-tuning, to any downstream tasks – such as classification, object-detection, segmentation, and others – surpassing the performance of task-specific models. A widely adopted approach involves the use of a contrastive objective, which is the case of DINOv2 (Oquab et al., 2023) – currently the state-of-the-art in SSL models for computer vision. In contrast, generative models, such as Masked Autoencoders (MAE) (He et al., 2022), are trained by reconstructing masked or corrupted regions of the input.

Applications of SSL to microscopy images. The literature on self-supervised learning for cellular microscopy focuses mainly on models designed for specific datasets (Doron et al., 2023; Kobayashi et al., 2022) or imaging protocols, such as the Cell Painting assay (Kim et al., 2023). However, these pre-trained models cannot be reused across studies with different microscopy configurations. Furthermore, while valuable for large-scale datasets, this approach is not viable for learning powerful feature representations for small-scale datasets.

To overcome this limitation, CytoImageNet (Hua et al., 2021) proposed to convert images to a grayscale representation by averaging over the channels. This approach loses the semantic information carried by distinct channels. Alternatively, Microsnoop (Xun et al., 2024) proposed to encode each channel individually with a U-Net Ronneberger et al. (2015) trained with a masked SSL strategy, and reassembling whole-image representations post-hoc by concatenating the embeddings obtained for each channel.

In contrast, ChAda-ViT (Bourriez et al., 2024), Channel-ViT (Bao et al., 2024), Kraus et al. (2024) and (Pham & Plummer, 2024) studied joint channel encoding with ViTs by converting the variable number of channels problem into a variable sequence length problem, as such, channel interactions can be readily learned. Channel-ViT (Bao et al., 2024), in particular, tackles a problem distinct to channel-invariant learning, they focus rather on robustness to missing channels. Supervised frameworks, such as those of Hua et al. (2021), Bao et al. (2024) and Pham & Plummer (2024) do not fully align with the end goal of channel-invariant models, which aim to be transferable across new microscopy studies, thus requiring features that are task-agnostic.

We here pioneer the strategy of independent channel encoding with ViT backbones and the DINOv2 SSL framework and benchmark it against Microsnoop and joint channel encoding (Channel-ViT) methods, while scaling both model and dataset sizes.

3 METHOD

3.1 INDEPENDENT CHANNEL ENCODING

Given a channel-heterogeneous dataset $\mathbb{X}$, where a sample $x^{(j)}$ has K_j channels, let $K_{\max}$ denote the maximum number of channels across all images. The goal of channel-invariant learning is to propose a model that is able to accommodate images with a variable number of channels.

A straightforward strategy to deal with channel number variability is to separately encode each channel, using a common backbone. The individual features obtained for each channel can then be aggregated, e.g., via concatenation, to obtain the image-level representation.

This is the strategy employed by Microsnoop (Xun et al., 2024), a tool for profiling heterogeneous microscopy images based on a convolutional U-Net (Ronneberger et al., 2015) backbone and trained with a masked SSL strategy.

In this work we pioneer independent channel modeling using ViTs and the DINOv2 SSL framework. We denominate our approach the *DINO Bag of Channels* model (DINO BoC). We demonstrate its superior performance compared to Microsnoop, as well as the advantages of DINOv2 over alternative SSL frameworks. Furthermore, we benchmark it against channel-adaptive methods, that model the channels jointly, disproving the claimed benefits of incorporating inter-channel attention.

Figure 2: Overview of different channel-invariant strategies. (A) Joint channel encoding strategy of Channel-ViT (Bao et al., 2024; Bourriez et al., 2024): the image is reshaped into a sequence of single-channel patches and channel embeddings are used to retain channel information. (B) Hierarchical Attention model: a specialized attention mask is used to enforce independent channel encoding via channel class tokens x_{CH}, while the global class token x_{CLS} supports inter-channel reasoning. (C) Independent channel encoding strategy, note that a common backbone is used. (B) Attention mask of the Hierarchical Attention model.

3.2 JOINT CHANNEL ENCODING

The challenge of joint channel encoding on datasets with variable number of channels has been addressed by ChAda-ViT (Bourriez et al., 2024) and Channel-ViT (Bao et al., 2024), specifically for transformer architectures. In particular, they propose an adaptation of the patchfication process, and introduce the concept of channel embeddings.

Multi-channel patch model. In the original ViT architecture proposed by Dosovitskiy et al. (2021), given an input image $x \in \mathbb{R}^{K \times H \times W}$ and a patch size S, the image is reshaped into a sequence of flattened multi-channel patches:

$$x = \begin{bmatrix} x_1 & x_2 & \cdots & x_N \end{bmatrix}, \quad x_i \in \mathbb{R}^{KS^2},$$

where K is the number of channels and $N = HW/S^2$. A linear embedding layer is applied to each patch x_i resulting in a sequence of patch embeddings h_i of dimension D, to which a learnable class token x_{CLS} is prepended:

$$h = \begin{bmatrix} x_{\text{CLS}} & h_1 & \cdots & h_N \end{bmatrix} \in \mathbb{R}^{D \times (1+N)},$$

In order to retain positional information, learnable position embeddings are added to the patch embeddings.

Single-channel patch model. To accommodate images with variable number of channels, Bourriez et al. (2024) and Bao et al. (2024) reshape an image into a sequence of flattened single-channel patches:

$$x = [x_{1,1} \quad \cdots \quad x_{1,N} \quad \cdots \quad x_{K,1} \quad \cdots \quad x_{K,N}], \quad x_{k,i} \in \mathbb{R}^{S^2},$$

where, in $x_{k,i}$, k indicates the channel the patch belongs to and i its raster position in that channel. After projecting the patches with a linear embedding layer and prepending the class tokens one obtains:

$$h = [x_{\text{CLS}} \quad h_{1,1} \quad \cdots \quad h_{1,N} \quad \cdots \quad h_{K,1} \quad \cdots \quad h_{K,N}] \in \mathbb{R}^{D \times (1+NK)},$$

As a result, the variable number of channels problem becomes a variable sequence length one, benefiting from the transformer's inherent capability of handling arbitrary sequence lengths.

Channel embeddings. In the single-channel patch model, the approach of Bourriez et al. (2024) and Bao et al. (2024) to retain channel information, as well as position information, is to add both position embeddings and channel embeddings to the patch embeddings $h_{k,i}$. Let p_i $(i = 1, \ldots, N)$ denote the position embeddings and c_k $(k = 1, \ldots, K)$ the channel embeddings. The resulting sequence of patch embeddings for a sample x is:

$$[x_{\text{CLS}} \quad h_{1,1} + p_1 + c_1 \quad \cdots \quad h_{K,N} + p_N + c_K].$$

Note that, if the maximum number of channels per image on the pre-training data is $K_{\max}$, this method cannot be used on images that have more channels than $K_{\max}$, as there will be no trained channel embeddings for the extra channels.

Bourriez et al. (2024) used a ViT-S architecture and the DINO pre-training recipe. For fairness of comparison with DINO BoC, we scale the model using a ViT-L architecture and update the pre-training recipe to the improved DINOv2. This model will be referred to as the *Channel-ViT* model.

Note that Channel-ViT outputs a single constant-sized embedding regardless of the channel-composition of the input data, contrary to the strategy of obtaining separate features for each channel. The utility of producing a constant-sized embedding irrespective of the number of channels is questionable (see Appendix G). We also tested a channel sampling technique introduced by Bao et al. (2024) for the training of Channel-ViT, however it did not improve the performance of the model, as shown in Appendix E.

Bourriez et al. (2024) claimed superiority of the joint channel encoding strategy over independent encoding, attributing it to the inter-channel attention mechanism. However we have found that, at scale, combining independent channel encoding with the DINOv2 SSL method brings superior performance and robustness.

3.2.1 HIERARCHICAL ATTENTION MODEL

This work introduces a novel approach that balances joint and independent channel encoding strategies. This method plays a critical role in testing the hypothesis that limiting inter-channel interactions enhances the performance of channel-invariant models.

In this approach, the image is reshaped into a sequence of single-channel patches $x \in \mathbb{R}^{S^2 \times NK}$. After embedding the patch tokens with a linear layer, both a global class token x_{CLS} and channel class tokens x_{CH} are inserted into the sequence, only position embeddings are used:

$$[x_{\text{CLS}} \quad x_{\text{CH}_1} \quad h_{1,1} + p_1 \quad \cdots \quad h_{1,N} + p_N \quad \cdots \quad x_{\text{CH}_K} \quad h_{K,1} + p_1 \quad \cdots \quad h_{K,N} + p_N].$$

A specialized attention mask is employed in the Multi-Head Self-Attention blocks. Tokens within a single channel (channel class token and corresponding patch tokens) can only attend to other tokens within that same channel, therefore, at this level, the channels are processed independently. The global class token, however, attends to all channel class tokens, enabling inter-channel reasoning at a higher semantic level.

This approach, termed DINO *Hierarchical Attention* (DINO HA) model, and the attention mask are illustrated in Figure 2 (see Appendix C for more details).

4 EXPERIMENTS

We test the merits of DINO BoC on diverse biological benchmarks, and compare it to existing channel-invariant strategies. Section 4.1 introduces the datasets used in this work, including the CHAMMI benchmark. Section 4.3 demonstrates the impact of choosing the SSL DINOv2 method (Oquab et al., 2023) instead of MAE He et al. (2022), and compares DINO BoC to Channel-ViT and Microsnoop (Xun et al., 2024). In section 4.4, we further investigate the advantages of DINO BoC on cross-dataset generalization tasks. Then, in section 4.5 we evaluate self-supervised DINO BoC, Channel-ViT, and DINO HA models in the CHAMMI benchmark, designed to assess performance in in-distribution and OOD tasks; we compare the models to state-of-the-art supervised channel-invariant approaches.

4.1 DATASETS AND BENCHMARKS

We leverage multiple microscopy datasets with varying numbers of channels. In particular, we use the Human Protein Atlas, WTC-11 and JUMP-CP datasets for evaluation tasks. Additionally, we employ the CHAMMI benchmark, a standardized evaluation framework for channel-invariant models.

Human Protein Atlas dataset. The subset of the Human Protein Atlas (HPA) data that is considered is the one of the Kaggle competition Human Protein Atlas (2019), concerned with the subcellular distribution of the proteins encoded by different genes. It covers 35 cell lines and 28 subcellular structures of protein localization. There are $113,545$ images in total, with four channels. There is also a single cell version of the same dataset (Le et al., 2022), obtained through segmentation of the field-of-view (FOV) images. The *HPA Single Cell* dataset contains $839,612$ images.

WTC-11 dataset. This dataset is a version of the WTC-11 hiPSC Single-Cell Image Dataset v1 (Viana et al., 2023) of the Allen Institute curated for the CytoData Symposium 2022 hackathon (Allen Institute, 2022). The dataset contains $214,037$ 3D images of cells, we used the maximum z-projection of the original images. The dataset provides cell-cycle stage annotations, with six stages. The images have one bright-field channel and three fluorescence channels; the bright-field channel was excluded.

Cell Painting dataset. We utilize the Cell Painting (CP) dataset curated by Moshkov et al. (2024), totaling $8,423,455$ images with five channels. The dataset has the objective of allowing the study of the response of cells to different compound treatments and gene over-expression experiments.

JUMP-CP dataset. This dataset, used by Bao et al. (2024), is a processed version of the data made available by the JUMP-Cell Painting Consortium Broad Institute (2021). It contains $229,228$ single cell images. We used only the five fluorescence channels in our work.

OpenCell dataset. The OpenCell dataset was introduced by Kobayashi et al. (2022), and encompasses $1,311$ different tagged proteins. In total, $1,134,592$ images were made available, with two fluorescence channels. More details on the five datasets mentioned above are given in Appendix A.

CHAMMI benchmark. The CHAMMI benchmark (Chen et al., 2024) includes a dataset curated from the WTC-11, HPA Single Cell and Cell Painting datasets. In total there are $220,284$ images, of which $100,145$ are used for training. The benchmark is a standardized evaluation framework for channel-invariant models. It presents a comprehensive set of nine tasks for channel-invariant models of varying complexity, that evaluate the ability of the models to generalize to new biologically-relevant experimental regimes. As such it positions itself as an indispensable benchmark to evaluate those models. The images from each data source present in the CHAMMI dataset are split into one training set and several test sets, designed for specific tasks. Tasks with suffix 1 are IID classification problems, where the test and train data follow the same distribution. Tasks with suffix greater than 1 evaluate the OOD (OOD) generalization capabilities of the model, and simulate biologically-relevant application scenarios (see Appendix B.1 for a detailed description of each task).

ExtendedCHAMMI dataset We extend the CHAMMI train set to a total of $7,748,662$ images, incorporating additional data from both the source datasets and new data sources. The extended training dataset preserves the OOD characteristics of the CHAMMI tasks (see Appendix B.2).

4.2 IMPLEMENTATION DETAILS

When pre-training the models, care was taken to ensure that the models processed the same amount of data. For the DINO BoC model, a sample consists of a single channel, whereas for the other models, a sample is an image with all of its channels. Therefore the former must be trained for more iterations to achieve fair comparison.

For each pre-training dataset, the Channel-ViT and DINO HA models were pre-trained for $45,000$ iterations. Taking into account the average number of channels in the pre-training dataset, the Bag of Channels model was trained for a proportionally larger number of epochs. The batch size used was of 1024 for all models, and the batch size per GPU was set to 8, except for DINO BoC model, for which 32 fits in memory. On our largest dataset, we trained the models for about 2 days using 16 nodes, or 4 nodes for the DINO BoC model. Unless specified otherwise, we trained ViT large models. More details are provided in Appendix D.

On the ExtendedCHAMMI dataset, the channel-invariant models were pre-trained with balanced sampling across data sources.

4.3 SCALING CHANNEL AGNOSTIC FEATURE REPRESENTATIONS WITH DINOv2

Table 1 displays the results for channel-invariant models pre-trained on the ExtendedCHAMMI dataset, as well as of baseline fixed-channel models (Doron et al., 2023) pre-trained either on the HPA-FOV, JUMP-CP or WTC dataset. We evaluate the models on the HPA-FOV, JUMP-CP and WTC datasets, note that the fixed-channel models can only be evaluated on the datasets they are pre-trained on. The JUMP-CP dataset is not included in ExtendedCHAMMI, therefore it evaluates the generalization capability of channel-invariant models on novel data sources. Results for an ablation removing datasets from the ExtendedCHAMMI dataset are presented in Appendix H, and results on all 8 JUMP-CP channels are listed in Appendix I.

First of all – comparing DINO BoC to Channel-VIT using the same SSL method and network size – we observe that the strategy of independently encoding the channels significantly outperforms the one of jointly encoding them across all tasks.

We also observe that DINO BoC has stronger performance than fixed-channel models on 3 out of 4 tasks, including when evaluating on the novel WTC dataset. This shows that DINO BoC successfully leverages diverse microscopy data to learn an improved encoder, justifying the interest in channel-invariant models.

Table 1 also shows that DINO outperforms MAE as a learning objective, demonstrating that DINOv2 is a key component of the success of our approach.

Furthermore, we evaluate the impact of the network size on DINO BoC. Although using a ViT-L leads to improved performance, even with a ViT-S, DINO BoC outperforms ViT-L MAE BoC and Channel-ViT models.

Absent the ability of directly pre-training Microsnoop on ExtendedCHAMMI due to the unavailability of the training code, the performance of MAE BoC serves as a proxy for Microsnoop performance, as it uses the same SLL method. In addition, we demonstrate in Table 2 that DINO BoC outperforms Microsnoop on the challenging Cyclops dataset (on which they reported the largest gains) by a substantial margin, while especially fortifying performance on rare classes (up to 20 points).

We thus establish the most powerful independent channel encoding model, and indeed most powerful channel-invariant model overall.

4.4 CROSS-DATASET GENERALIZATION

We further analyze the surprising result that inter-channel reasoning is detrimental to the performance and robustness of channel-invariant models by investigating the cross-dataset generalization capabilities of the DINO Channel-VIT, DINO HA and DINO BoC models.

Table 1: **Comparison of channel-invariant models trained on the ExtendedCHAMMI dataset and fixed-channel models.** The first three rows are fixed-channel baseline models, separately pre-trained either on the HPA-FOV, JUMP-CP or WTC datasets. The channel-invariant models were pre-trained with balanced sampling across data sources. Best channel-invariant results in bold; best results overall are underlined.

Model	SSL method	Network size	Channel invariant	Training set	HPA-FOV F1 Protein loc.	HPA-FOV F1 Cell type	JUMP-CP Accuracy	WTC F1 Cell cycle st.
CellDINOv2	DINOv2	ViT-L	✗	HPA-FOV	65.0	89.3	✗	✗
CellDINOv2	DINOv2	ViT-L	✗	JUMP-CP	✗	✗	44.3	✗
CellDINOv1	DINOv1	ViT-L	✗	WTC	✗	✗	✗	82.3
Channel-ViT	DINOv2	ViT-L	✓	ExtendedCHAMMI	56.7 -8.3	90.4 +1.1	39.5 -4.8	87.2 +4.9
BoC	MAE	ViT-L	✓	ExtendedCHAMMI	54.0 -11.0	90.8 +1.5	39.3 -5.0	89.4 +7.1
	DINOv2	ViT-S	✓		55.6 -9.4	90.7 +1.4	44.5 +0.2	**91.0** +8.7
	DINOv2	ViT-L	✓		**61.7** -3.3	**91.1** +1.8	**45.2** +0.9	90.5 +8.2

Table 2: **Comparison to Microsnoop on the Cyclops dataset.** DINO BoC largely outperforms Microsnoop, especially on the less frequent classes out of 16.

	Budtip	Cell periphery	Budneck	Actin	All
Class frequency	1.5 %	1.9%	2.4%	3.8%	
Microsnoop (Xun et al., 2024)	32.1	96.4	43.4	48.0	75.9
DINO BoC	**62.1**	**97.5**	**72.6**	**63.7**	**83.1**

We train the models either on HPA-FOV or JUMP-CP, and evaluate them on HPA-FOV, JUMP-CP and WTC, the results are shown in Table 3. DINO BoC outperforms DINO Channel-ViT on all cross-dataset tasks. A further point of analysis is the DINO HA model, which balances joint and independent channel encoding characteristics. DINO HA yields systematically better performances than Channel-ViT, while falling behind DINO BoC, corroborating the conclusion that independent channel encoding is the winning strategy for channel-invariant models.

Table 3: **Comparison of cross-dataset generalization of channel-invariant models**. DINO-BOC shows superior performance on unseen channel-combinations. In-dataset results are shown in gray for reference.

Model	Channel invariant	Training set	HPA-FOV F1 Protein loc.	HPA-FOV F1 Cell type	JUMP-CP Accuracy	WTC F1 Cell cycle st.
DINO Channel-ViT	✓	HPA-FOV	66.6	90.2	35.3	78.0
DINO HA (Ours)	✓	HPA-FOV	66.7	91.3	37.3	88.9
DINO BoC (Ours)	✓	HPA-FOV	65.2	91.5	**40.2**	**89.8**
DINO Channel-ViT	✓	JUMP-CP	29.5	79.4	53.3	79.4
DINO HA (Ours)	✓	JUMP-CP	30.3	**85.2**	52.0	84.2
DINO BoC (Ours)	✓	JUMP-CP	**31.6**	85.0	41.3	**90.5**

4.5 PERFORMANCE ON CHAMMI

Table 4 reports results on the CHAMMI benchmark using the 1-NN classifier protocol as defined in Chen et al. (2024). The table provides a comparison to the results of Chen et al. (2024) for supervised models trained from scratch, where the best performance is obtained by the HyperNet model. The approach, inspired by Hypernetworks (Ha et al., 2017), uses a CNN backbone and a MLP that generates kernel weights for the initial convolutional layer of each input channel. Note that while the model is channel-invariant, it is supervised and requires labels during training, as is the case for all other channel-invariant models in CHAMMI (Chen et al., 2024). Despite the small size of the CHAMMI training set of about 100k images, not ideal for pre-training, Table 4

demonstrates improved F1 scores of our DINO BoC approach on OOD tasks on two datasets out of three, outperforming the best supervised baseline by 8% on WTC and 14% on Cell Painting on average.

4.5.1 SCALING SELF-SUPERVISED CHANNEL-INVARIANT APPROACHES

SSL methods tend to benefit from pre-training on a larger corpus of data. To explore the scaling properties for channel-invariant models, we hence leverage the ExtendedCHAMMI dataset, which has almost 8M images and preserves the OOD characteristics of the CHAMMI tasks.

The flexibility to extend the training set with new images with no labels is an advantage of SSL pre-training. In contrast, supervised methods are constrained by the need for more annotated data. Table 5 presents results for the SSL models pre-trained on the ExtendedCHAMMI dataset.

Table 4: **F1 scores for 1-NN search on the CHAMMI test set. The models were pre-trained on the CHAMMI train split.** Lines 1-6 report the results of Chen et al. (2024) for CNN-based models trained from scratch in a *supervised* fashion. Line 1 reports the performance of FixedChannels, that consists on a separate model trained for each fixed channel combination. Lines 2-6 are channel-invariant models. Lines 7-9 are self-supervised channel-invariant ViTs. Best results between channel-invariant self-supervised approaches are in bold.

| Model | Average OOD | | | | WTC | | HPA | | | CP | | | |
	Mean	WTC	HPA	CP	Task1	Task2	Task1	Task2	Task3	Task1	Task2	Task3	Task4
FixedChannels	50.0	64.8	59.2	25.9	64.9	64.8	80.7	76.3	42.1	66.0	48.1	23.0	6.6
Depthwise	51.7	65.2	64.4	25.6	68.9	65.2	84.9	81.3	47.5	67.3	47.8	22.4	6.5
TargetParam	49.6	59.0	62.3	27.3	69.5	59.0	83.7	79.4	45.2	71.7	50.8	23.4	7.7
SliceParam	45.7	56.8	54.6	25.6	61.6	56.8	77.0	69.0	40.3	64.6	47.5	22.2	7.1
HyperNet	53.7	66.1	67.1	27.8	72.6	66.1	88.7	85.8	48.3	72.0	51.7	24.7	6.9
Template mixing	46.6	56.5	57.7	25.7	63.1	56.5	80.8	74.1	41.3	67.1	46.8	22.7	7.5
DINO Channel-ViT	42.6	45.3	**53.6**	29.0	68.7	45.3	**92.2**	**65.2**	**42.0**	**95.2**	51.5	**25.2**	10.3
DINO BoC (Ours)	**48.8**	**71.4**	43.3	**31.6**	**79.4**	**71.4**	87.0	56.4	30.2	93.5	58.5	20.1	**16.3**

Table 5: **F1 scores for 1-NN search on the CHAMMI test set. The self-supervised models were pre-trained on the ExtendedCHAMMI dataset.** Line 1 presents the best performing *supervised* baseline (HyperNet), which can only be trained on the annotated subset of CHAMMI.

| Model | Average OOD | | | | WTC | | HPA | | | CP | | | |
	Mean	WTC	HPA	CP	Task 1	Task 2	Task 1	Task 2	Task 3	Task 1	Task 2	Task 3	Task 4
HyperNet	53.7	66.1	67.1	27.8	72.6	66.1	88.7	85.8	48.3	72.0	51.7	24.7	6.9
DINO Channel-ViT	43.6	46.2	**55.6**	28.9	64.5	46.2	**92.1**	**65.3**	**45.9**	89.0	53.5	21.8	11.3
DINO BoC (Ours)	**51.6**	**79.0**	43.0	**32.7**	**79.4**	**79.0**	86.6	59.3	29.6	**92.6**	57.6	22.1	**18.5**

Comparing Tables 4 and 5, it is evident that the models benefit from scaling the dataset size, even though part of the additional data comes from datasets unrelated to those on which the models are evaluated on. DINO BoC show the greatest improvements, gaining 2.8 points in the average OOD score, while Channel-ViT gains only 1.0 point. This is a promising result for channel-invariant models, especially for DINO BoC, demonstrating that by leveraging diverse data sources, more robust biological feature extractors can be learned, bringing advantages over study-specific models.

4.5.2 OUT-OF-DISTRIBUTION PERFORMANCE ON CHAMMI

Analyzing Table 5, among the self-supervised models, DINO BoC has the best performance. Furthermore, the OOD results of DINO BoC strongly outperform all previous attempts on the WTC and CP datasets, including the supervised HyperNet strategy. This result suggests that self-supervision can help overcome the limitations of supervised learning for OOD generalization. Supervised learning may capture spurious correlations in the training set, leading to poor performance on OOD tasks. In contrast, self-supervised learning leverages only image-based information, resulting in an unbiased representation that can be more robust to domain shifts.

We point out that the Channel-ViT and DINO BoC models were pre-trained in a self-supervised fashion while the results reported in the CHAMMI paper (Chen et al., 2024) reflect models pre-trained with a supervised ProxyNCA++ loss (Teh et al., 2020), which represents each training class with a proxy in the embedding space, and draws the samples towards their corresponding proxies. It therefore naturally encourages the clustering of the data in the embedding space according to their labels, facilitating the one nearest neighbor search. By contrast, without the benefit of label information to organize the embedding space according to a given downstream task, the SSL approaches yield nested embedding spaces. For example, for the HPA task, the features first cluster by cell type, while the protein localization are retained as a nested factor of variation (see Appendix F). This organization is ill-suited to nearest-neighbor protein localization classification on a novel cell type (HPA Task 2), or on a known cell type but for which there are no examples of the targeted protein localization (HPA Task 3). In light of this, the performance of the models was further evaluated using a linear probe.

Table 6: **F1 scores for a linear probe on CHAMMI test set.** Self-supervised models were pre-trained on the ExtendedCHAMMI dataset, while the supervised HyperNet was pre-trained on CHAMMI.

	Average OOD			WTC		HPA			CP			
Model	Mean	WTC	HPA	CP	Task1	Task2	Task1	Task2	Task 3	Task1	Task2	Task3	Task4
HyperNet	65.4	85.3	82.9	27.9	87.9	85.3	94.4	92.5	73.2	93.5	51.5	17.3	15.0
DINO Channel-ViT	59.8	66.9	76.7	35.9	83.1	66.9	88.2	**84.9**	68.4	80.5	54.5	23.3	30.0
DINO HA (Ours)	62.7	76.2	72.4	39.5	88.0	76.2	**88.5**	82.4	62.4	**91.7**	**61.6**	**27.5**	29.3
DINO BoC (Ours)	**69.3**	**89.2**	79.0	**39.7**	**90.5**	**89.2**	88.3	84.7	**73.2**	90.5	60.5	25.8	**32.7**

Linear probe results. The use of a linear probe is of particular interest for DINO BoC. The approach generalizes well to OOD tasks even when no explicit cross-channel interactions are incorporated, even a minimal opportunity to relate information across channels may lead to further performance gains. Indeed, comparing Tables 5 and 6, the use of a linear probe significantly improves the scores on HPA Task 2 and 3, corroborating the hypothesis that the poor performance of nearest neighbor search on these tasks is due to the nesting of the factors of variation. Moreover, employing a linear classifier, DINO BoC surpasses the HyperNet supervised baseline on the mean OOD score, as well as Channel-ViT on HPA, suggesting that ample information suitable to cross-channel integration is preserved in its channel-specific embeddings. This highlights the potential of this simple strategy to yield a powerful biological feature extractor.

5 CONCLUSIONS

We report results on a large-scale study into self-supervised channel-invariant training strategies, as a step towards general-purpose feature extractors for fluorescent microscopy that are compatible with arbitrary channel configurations and cell-biological semantics. Scaling the approach of independent channel encoding using Vision Transformers and the state-of-the-art self-supervised DINOv2 method (DINO BoC model), outperforms models that rely on inter-channel reasoning positions, and positions it as the leading channel-invariant approach.

We found that DINO BoC presents superior performances and more robust OOD generalization compared to existing channel-invariant models, both supervised and self-supervised, as well as to study-specific models. In addition to its strong performances, DINO BoC is notable for its simplicity, lacking any priors, rendering it suitable to arbitrary channel combinations. It also exhibited superior performance scaling with dataset size.

We expect that this work, along with the public release of the code, will advance the development of channel-invariant models and foster collaboration across microscopy imaging communities, thereby accelerating progress in biomedical research.

REFERENCES

Allen Institute. Cytodata symposium 2022. https://alleninstitute.org/events/cytodata-symposium-2022/, 2022.

Mahmoud Assran, Quentin Duval, Ishan Misra, Piotr Bojanowski, Pascal Vincent, Michael Rabbat, Yann LeCun, and Nicolas Ballas. Self-supervised learning from images with a joint-embedding predictive architecture. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023.

Yujia Bao, Srinivasan Sivanandan, and Theofanis Karaletsos. Channel vision transformers: An image is worth c × 16 × 16 words. In *International Conference on Learning Representations*, 2024.

Nicolas Bourriez, Ihab Bendidi, Ethan Cohen, Gabriel Watkinson, Maxime Sanchez, Guillaume Bollot, and Auguste Genovesio. Chada-vit: Channel adaptive attention for joint representation learning of heterogeneous microscopy images. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

M.A. Bray, S. Singh, H. Han, et al. Cell painting, a high-content image-based assay for morphological profiling using multiplexed fluorescent dyes. *Nature Protocols*, 11:1757–1774, 2016.

Mark-Anthony Bray, Sigrun M. Gustafsdottir, Mohammad H. Rohban, Shantanu Singh, Vebjorn Ljosa, Katherine L. Sokolnicki, Joshua A. Bittker, et al. A dataset of images and morphological profiles of 30 000 small-molecule treatments using the cell painting assay. *GigaScience*, 6(12), 2017.

Broad Institute. Jump-cell painting consortium. https://jump-cellpainting.broadinstitute.org/, 2021.

Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jegou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2021.

Srinivas Niranj Chandrasekaran, Hugo Ceulemans, Justin D. Boyd, and Anne E. Carpenter. Image-based profiling for drug discovery: due for a machine-learning upgrade? *Nature Reviews Drug Discovery*, 20:145–149, 2021.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *Proceedings of the 37th International Conference on Machine Learning*, 2020.

Zitong Sam Chen, Chau Pham, Siqi Wang, Michael Doron, Nikita Moshkov, Bryan Plummer, and Juan C Caicedo. CHAMMI: A benchmark for channel-adaptive models in microscopy imaging. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, 2024.

Nathan H Cho, Keith C Cheveralls, Andreas-David Brunner, Kibeom Kim, André C Michaelis, Preethi Raghavan, Hirofumi Kobayashi, Laura Savy, Jason Y Li, Hera Canaj, et al. Opencell: Endogenous tagging for the cartography of human cellular organization. *Science*, 375(6585), 2022.

Yezhen Cong, Samar Khanna, Chenlin Meng, Patrick Liu, Erik Rozi, Yutong He, Marshall Burke, David Lobell, and Stefano Ermon. Satmae: Pre-training transformers for temporal and multi-spectral satellite imagery. *Advances in Neural Information Processing Systems*, 35:197–211, 2022.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics*, 2019.

Michael Doron, Théo Moutakanni, Zitong S Chen, Nikita Moshkov, Mathilde Caron, Hugo Touvron, Piotr Bojanowski, Wolfgang M Pernice, and Juan C Caicedo. Unbiased single-cell morphology with self-supervised vision transformers. *bioRxiv*, 2023.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations*, 2021.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. In *International Conference on Learning Representations*, 2017.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2022.

Stanley Bryan Z Hua, Alex X Lu, and Alan M Moses. Cytoimagenet: A large-scale pretraining dataset for bioimage transfer learning, 2021.

Human Protein Atlas. Human protein atlas image classification. https://www.kaggle.com/competitions/human-protein-atlas-image-classification/overview, 2019.

Jeremy Irvin, Lucas Tao, Joanne Zhou, Yuntao Ma, Langston Nashold, Benjamin Liu, and Andrew Y Ng. Usat: A unified self-supervised encoder for multi-sensor satellite imagery. *arXiv preprint arXiv:2312.02199*, 2023.

Vladislav Kim, Nikolaos Adaloglou, Marc Osterland, Flavio M Morelli, Marah Halawa, Tim König, David Gnutt, and Paula A Marin Zapata. Self-supervision advances morphological profiling by unlocking powerful image representations. *BioRxiv*, 2023.

Hirofumi Kobayashi, Keith C Cheveralls, Manuel D Leonetti, and Loic A Royer. Self-supervised deep learning encodes high-resolution features of protein subcellular localization. *Nature Methods*, 19:995–1003, 2022.

Oren Kraus, Kian Kenyon-Dean, Saber Saberian, Maryam Fallah, Peter McLean, Jess Leung, Vasudev Sharma, Ayla Khan, Jia Balakrishnan, Safiye Celik, et al. Masked autoencoders for microscopy are scalable learners of cellular biology. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024.

Trang Le, Casper F Winsnes, Ulrika Axelsson, Hao Xu, Jayasankar Mohanakrishnan Kaimal, Diana Mahdessian, Shubin Dai, Ilya S Makarov, Vladislav Ostankovich, Yang Xu, et al. Analysis of the human protein atlas weakly supervised single-cell classification competition. *Nature Methods*, 19: 1221–1229, 2022.

Nikita Moshkov, Michael Bornholdt, Santiago Benoit, Matthew Smith, Claire McQuin, Allen Goodman, Rebecca A Senft, Yu Han, Mehrtash Babadi, Peter Horvath, et al. Learning representations for image-based profiling of perturbations. *Nature Communications*, 15:1594, 2024.

Dilxat Muhtar, Zhenshi Li, Feng Gu, Xueliang Zhang, and Pengfeng Xiao. Lhrs-bot: Empowering remote sensing with vgi-enhanced large multimodal language model. *arXiv preprint arXiv:2402.02544*, 2024.

Maxime Oquab, Timothée Darcet, Théo Moutakanni, Huy Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, et al. Dinov2: Learning robust visual features without supervision. *Transactions on Machine Learning Research*, 2023.

Chao Pang, Xingxing Weng, Jiang Wu, Jiayu Li, Yi Liu, Jiaxing Sun, Weijia Li, Shuai Wang, Litong Feng, Gui-Song Xia, and Conghui He. Vhm: Versatile and honest vision language model for remote sensing image analysis, 2024.

Chau Pham and Bryan A Plummer. Enhancing feature diversity boosts channel-adaptive vision transformers. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, 2024.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Colorado J Reed, Ritwik Gupta, Shufan Li, Sarah Brockman, Christopher Funk, Brian Clipp, Kurt Keutzer, Salvatore Candido, Matt Uyttendaele, and Trevor Darrell. Scale-mae: A scale-aware masked autoencoder for multiscale geospatial representation learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4088–4099, 2023.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In Nassir Navab, Joachim Hornegger, William M. Wells, and Alejandro F. Frangi (eds.), *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2015*, pp. 234–241, Cham, 2015. Springer International Publishing. ISBN 978-3-319-24574-4.

Eu Wern Teh, Terrance DeVries, and Graham W Taylor. Proxynca++: Revisiting and revitalizing proxy neighborhood component analysis. In *European Conference on Computer Vision*, 2020.

Hugo Touvron, Louis Martin, Kevin Stone, Pierre-Emmanuel Albert, Amjad Almahairi, Yassine Babaei, Denis Bashlykov, Siddharth Batra, Anurag Bhargava, Shruti Bhosale, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

Matheus P Viana, Jianxu Chen, Theo A Knijnenburg, Ritvik Vasan, Calysta Yan, Joy E Arakaki, Matte Bailey, Ben Berry, Antoine Borensztejn, Eva M Brown, et al. Integrated intracellular organization and its variations in human iPS cells. *Nature*, 613:345–354, 2023.

G.P. Way, T. Natoli, A. Adeboye, L. Litichevskiy, A. Yang, X. Lu, J.C. Caicedo, B.A. Cimini, K. Karhohs, D.J. Logan, M.H. Rohban, M. Kost-Alimova, K. Hartland, M. Bornholdt, S.N. Chandrasekaran, M. Haghighi, E. Weisbart, S. Singh, A. Subramanian, and A.E. Carpenter. Morphology and gene expression profiling provide complementary information for mapping cell state. *Cell Systems*, 13:911–923, 2022.

Dejin Xun, Rui Wang, Xingcai Zhang, and Yi Wang. Microsnoop: A generalist tool for microscopy image representation. *The Innovation*, 5, 2024.

Bryan Zhu, Nicholas Lui, Jeremy Irvin, Jimmy Le, Sahil Tadwalkar, Chenghao Wang, Zutao Ouyang, Frankie Y Liu, Andrew Y Ng, and Robert B Jackson. Meter-ml: A multi-sensor earth observation benchmark for automated methane source mapping. *arXiv preprint arXiv:2207.11166*, 2022.

A DATASETS

This section provides a detailed description of the datasets, and of the channels they encompass.

Human Protein Atlas dataset.   The Human Protein Atlas (HPA) is an initiative that aims to map all human proteins across cells, tissues and organs. The subset of the data that is considered is the one of the Kaggle competition Human Protein Atlas (2019), concerned with the subcellular distribution of the proteins encoded by different genes. It covers 35 cell lines and 28 subcellular structures of protein localization. It covers thirty five cell lines and more than $13,000$ proteins. The subcellular localization of each protein was classified into one or more of 28 subcellular structures.

The images were acquired using immunofluorescence and confocal microscopy. Four fluorescence dyes binding to (0) microtubules, (1) encoded protein, (3) nucleus and (4) encoplasmic reticulum are imaged in different channels. There are $113,545$ images in total.

There is also a single cell version of the same dataset Le et al. (2022) obtained through segmentation of the FOV images. The *HPA Single Cell* dataset contains $839,612$ images.

WTC-11 dataset.   The dataset contains $214,037$ 3D images of cells, spanning 25 cellular structures. Other than tagging the structure of interest with a fluorescent protein (FP), fluorescent DNA and cell-membrane dyes were employed. The images have four-channels: bright-field; nucleus; cell membrane; structure of interest. Given that the focus of this work is to develop a foundation channel-invariant model for fluorescent microscopy, the bright-field channel was discarded.

The dataset provides cell-cycle stage annotations. The six possible labels are M0, M1M2, M3, M4M5, M6M7_single, M6M7_complete; where M0 through M7 denote cell cycle stages.

Cell Painting dataset.   The Cell Painting Dataset Doron et al. (2023) used is the combination of the LINCS (Way et al., 2022), BBBC036 (Bray et al., 2017) and a third curated dataset (Moshkov et al., 2024), which includes BBBC022. All of those datasets were obtained following the Cell Painting protocol Bray et al. (2016), a standardized morphological profiling assay that images six fluorescent dyes in five channels, revealing eight cellular components. The components visualized in each channel are (0) nucleus; (1) endoplasmic reticulum; (2) nucleoli, cytoplasmic reticulum; (3) actin, golgi, plasma membrane; and (4) mitochondria. The goal of the studies included in the Cell Painting Dataset was to quantify the response of the cells to different perturbations: either compound treatments or gene over-expression experiments. Overall, the dataset includes 400 compounds and 80 gene over-expression experiments, totaling $8,423,455$ images.

CHAMMI dataset.   The CHAMMI dataset was curated from the WTC-11, HPA Single Cell and Cell Painting datasets. It includes $65,103$ images from the WTC-11 dataset covering six tagged structures; $66,936$ images from the HPA Single-Cell dataset covering 18 cell lines and 8 protein localization classes, only images with a single protein localization annotation were selected; and $88,245$ images from the Cell Painting dataset covering seven compound experiments, including the negative control. In total there are $220,284$ images, of which $100,145$ are used for training.

JUMP-CP dataset.   We considered the version of the JUMP-CP dataset used by Bao et al. (2024); it is a processed version of the data made available by the JUMP-Cell Painting Consortium Broad Institute (2021). Each image includes the five Cell Painting channels and three brightfield channels (HighZBF, LowZBF and brightfield).

The datasets generated by the JUMP-Cell Painting Consortium have the goal of enabling image-based drug mechanisms of action determination. As such, it encompasses multiple chemical and genetic perturbations. This particular version of the JUMP-CP dataset contains $229,228$ single cell images.

OpenCell dataset.   The OpenCell dataset was introduced by Kobayashi et al. (2022), and consists of confocal images encompassing $1,311$ different tagged proteins. On average, each protein was imaged in 18.59 field of view images. Crops containing from 1 to 3 complete cells were extracted from each image, resulting in approximately 800 cropped images per protein. In total, $1,134,592$ images were made available. In addition to the tagged protein, a nuclear marker was used to visualize

the nucleus. From the nuclear channel, they constructed a distance map and segmentation masks. However those two additional channels were not used for the purposes of this work.

B DETAILS ON THE CHAMMI BENCHMARK AND DATASET EXTENSION

B.1 CHAMMI BENCHMARK

The CHAMMI benchmark Chen et al. (2024) is a standardized evaluation framework for channel-invariant models. It presents a comprehensive set of nine tasks for channel-invariant models of varying complexity, that evaluates the ability of the models to generalize to new biologically-relevant experimental regimes. The images from each data source present in the CHAMMI dataset are split into one training set and several test sets, designed for specific tasks. Tasks with suffix 1 are IID classification problems, where the test and train data follow the same distribution. Originally, the CHAMMI benchmark considers a Nearest Neighbor (NN) evaluation.

The WTC-11 data is used for cell-cycle stage classification. The train set contains images with one of four cellular structures tagged: nuclear speckles, mitochondria, microtubules, or Golgi apparatus. Images of *W_Task2* are tagged with three novel cellular structures, the task evaluates whether the model is able to classify cell-cycle stages when an unseen cellular structure is tagged.

The HPA data supports protein localization classification. The train split covers 17 cell lines and four protein localizations: nuclear speckles, mitochondria, microtubules, or Golgi apparatus. The *H_Task2* images come from a novel cell line but covering the same protein localizations as the train split. The *H_Task3* images come from the same cell lines as the train split, but labeled with one of three novel protein localizations.

Lastly, the Cell Painting data is used for perturbation classification. The train set includes images of cells coming from 9 plates and perturbed with one of three treatments, as well as negative controls; The *C_Task2* images are perturbed with the same treatments as the train split and coming from the same data sources, however they belong to a set of 3 novel plates. The *C_Task3* includes the same treatments as the train split, but coming from the BBBC022 dataset and covering 4 novel plates. Finally, the *C_Task4* images are from the same set of plates and data sources as the train split, but the cells are perturbed with novel treatments.

For tasks that introduce new labels that are not present in the train set (HPA Task 3 and CP Task 4), a leave-one-out evaluation strategy is employed. Taking the example of HPA Task 3, the test data is split into sub-groups according to the cell line. Then, for each sub-group, the NN search is computed on both the training data and the remaining sub-groups. For CP Task 4, the data is split by plate ID.

B.2 EXTENDEDCHAMMI DATASET

The ExtendedCHAMMI dataset extends the CHAMMI train split to a total of $7,748,662$ images, using additional data from both the source datasets and new data sources, while preserving the OOD characteristics of the CHAMMI tasks.

In order to build the *ExtendedCHAMMI* dataset, the HPA FOV, HPA Single Cell, WTC-11, Cell Painting and OpenCell datasets were used. The samples belonging to the IID tasks W_Task1, H_Task1 and C_Task1 were removed from the WTC-11, HPA Single Cell and Cell Painting datasets, respectively. Furthermore, the images of the HPA FOV dataset containing cells present on H_Task1 were removed as well. With respect to the OOD tasks, the unseen tagged cellular structures for WTC-11; cell lines and protein localizations for HPA FOV and HPA Single Cell; and plates, data sources and treatments for Cell Painting were removed. The resulting number of images per dataset is summarized in Table 7.

C HIERARCHICAL ATTENTION MODEL TRAINING OBJECTIVE

The hierarchical attention model is based on a single-channel patch approach and, in addition to a global CLS token, it also inserts into the sequence channel CLS tokens. Moreover, it leverages a hierarchical attention mask (Figure 2), that constrains a channel's patch and CLS tokens to only

Table 7: **Data included on the ExtendedCHAMMI dataset.** The third column lists the amount of data that was included on ExtendedCHAMMI over the total size of the data source. For each data source, the number of channels and image type is specified: field-of-view (FOV) images, cropped FOV images containing a smaller number of cells, or images of a single cell. The last column lists which biological or experimental factors were discarded from the original datasets to preserve the OOD characteristic of the CHAMMI tasks.

Dataset	Image type	Size	Channels	Discarded factors
HPA Single Cell	One cell	$296,670/839,612$	4	Cell line (HEK 293); protein localization (cytosol, endoplasmic reticulum, nucleoplasm)
WTC	One cell	$179,994/214,037$	3	Tagged cellular components (centrioles, tight junctions, actin bundles)
OpenCell	Cropped FOV	$1,134,592/1,134,592$	2	None
Cell Painting	Cropped FOV	$6,103,565/8,423,455$	5	Plates (SQ00015125, SQ00015168, SQ00015221); data source (BBBC022); treatments (BRD-K11129031, BRD-K62310379, BRD-K77947974)
HPA FOV	FOV	$33,841/102,190$	4	Cell line (HEK 293); protein localization (cytosol, endoplasmic reticulum, nucleoplasm)

interact with one another, while the global CLS token attends to the channel CLS tokens. Consequently, the model produces both a global image representation, and channel-level representations. In view of this, additional loss terms were included in the DINOv2 training objective, to account for the channel-level representations.

Consider an image x, and let $\mathcal{G}(x)$ denote the set of global crops of x, and $\mathcal{C}(x)$ the set of all crops of x, note that $\mathcal{G}(x) \subset \mathcal{C}(x)$. Furthermore, let $p_s^{[\text{CLS}]}(u)$ and $p_t^{[\text{CLS}]}(u)$ be the CLS tokens, transformed into probability vectors, output by the student and teacher networks for a crop u. Then, the DINO loss for a sample x is:

$$\sum_{u \in \mathcal{G}(x)} \sum_{\substack{v \in \mathcal{C}(x) \\ v \neq u}} H\left(p_t^{[\text{CLS}]}(u), p_s^{[\text{CLS}]}(v)\right),$$

where $H(\cdot)$ denotes the cross-entropy. With the additional channel CLS tokens, $[\text{CH}_1], \ldots, [\text{CH}_\text{C}]$, the DINO loss is extended to:

$$\sum_{u \in \mathcal{G}(x)} \sum_{\substack{v \in \mathcal{C}(x) \\ v \neq u}} \left(\lambda_{\text{dino}}^{[\text{CLS}]} H\left(p_t^{[\text{CLS}]}(u), p_s^{[\text{CLS}]}(v)\right) + \lambda_{\text{dino}}^{[\text{CH}]} \sum_{i=1}^{C} H\left(p_t^{[\text{CH}_\text{i}]}(u), p_s^{[\text{CH}_\text{i}]}(v)\right) \right)$$

Another component of the DINOv2 loss is the KoLeo regularizer, that encourages the uniform span of features within a batch. Other than applying the KoLeo loss to the set of global CLS tokens for a batch, the loss is also separately applied to the set of all channel CLS tokens in the batch, with weights $\lambda_{\text{koleo}}^{[\text{CLS}]}$ and $\lambda_{\text{koleo}}^{[\text{CH}]}$. The remaining component of the DINOv2 loss, the iBOT masked-image-modeling loss, is left unchanged. We gave an equal weight to the losses on the global and channel CLS tokens. For the pre-training on the small scale CHAMMI dataset only, the DINO and KoLeo losses on channel class tokens were discarded, due to instabilities during training.

D TRAINING AND EVALUATION DETAILS

D.1 PRE-TRAINING DETAILS

Unless specified otherwise, we trained ViT-Large models with default patch size 16, and the default parameters of DINOv2 except a drop path rate of 0.1, a teacher momentum of 0.996, a learning rate of $5.0 \cdot 10^{-4}$, and 20 warm-up epochs. Transforms used include random contrast and brightness augmentations, flips and random resize crops of size 224.

D.2 Evaluation details

The feature vector used in the evaluations are obtained by concatenating the CLS tokens across across the last 4 layers, as well as the channel-wise average pooled patch tokens. If D is the dimension of the tokens (for a ViT-L $D = 1024$), and K is the number of channels, then the feature size for Channel-ViT is $4D + KD$, for DINO BoC it is $4KD + KD$ and for DINO HA it is $4(1 + K)D + KD$.

We used the AdamW optimizer and a one cycle Cosine scheduler. We used the same train/val/test splits as Bao et al. (2024) for the JUMP-CP dataset. For HPA, we used the same train/val splits as Doron et al. (2023). For WTC, we created $80\% - 10\% - 10\%$ uniformly distributed train/val/test splits. For every evaluation, we trained 14 classifiers varying the learning rate between 10^{-4} and 1, and selected the best classifier on the val set. We trained all classifiers for 4350 iterations on 8 GPUs with a batch size per gpu of 32 for HPA-FOV and WTC, and 128 for JUMP-CP. To train the linear classifiers on HPA-FOV, the following transforms are used : random crop of size 384, flips and self normalization. For evaluation, a center crop of size 384×384 is taken, followed by self normalization. For JUMP-CP, we used the same normalization as in Bao et al. (2024) instead of self normalization, and crops of size 224. For WTC, we used self normalization and crops of size 224.

E Influence of Hierarchical Channel Sampling

Bao et al. (2024) introduced a channel sampling technique for the training of ChannelViT, denoted hierarchical channel sampling (HCS). For an image x with K channels, HCS consists in sampling a number $m \in \{1, \ldots, K\}$ uniformly at random and then randomly selecting m channels from x without replacement.

Results summarized in Table 8 suggest that Hierarchical Channel Sampling (Bao et al., 2024) hinders the performance of single-channel patch models. The channel sampling technique was found by Bao et al. (2024) to boost performance when pre-training and evaluating on the same dataset, mainly in the supervised scenario of missing channels at evaluation time. However it does not translate into improvements on the channel heterogeneous setting explored in this work. We postulate that it plays the role of a regularizer in the supervised context, but that this strategy is not well adapted to SSL.

Table 8: **Influence of HSC on DINO Channel-ViT models.** The models were pre-trained on the ExtendedCHAMMI dataset and evaluated on CHAMMI.

Model	HCS	Average OOD				WTC		HPA			CP			
		Mean	WTC	HPA	CP	Task1	Task2	Task1	Task2	Task3	Task1	Task2	Task3	Task4
DINO Channel-ViT	✗	**43.6**	**46.2**	**55.6**	**28.9**	64.5	**46.2**	**92.1**	**65.3**	**45.9**	89.0	53.5	21.8	**11.3**
DINO Channel-ViT	✓	39.9	39.5	51.9	28.4	**66.4**	39.5	88.5	62.3	41.5	**90.2**	**56.0**	**22.3**	6.9

F Hierarchy of factors of variation in the feature space

SSL methods learn image representations using the samples themselves as the supervisory signal, therefore no label information controls the organization of the features in the embedding space.

In the channel-invariant models pre-trained on HPA FOV, we observe an emerging clustering of the features according to a hierarchy of semantic concepts, as illustrated in Figure 3. The features first cluster by cell type, while the protein localization is retained as a nested factor of variation.

G Channels as confounders in a unified feature space

To assess the utility of a unified feature space produced by channel-invariant models such as the one proposed by Bourriez et al. (2024), we explore the effect of ablating channels in the HPA FOV dataset. Specifically, we remove nucleus and ER channels from a random half of the dataset and compare the resulting features against those of images with all channels within a jointly computed UMAP space (Figure 4).

We observe that the data is clustered into distinct groups depending on the channels, and samples with different channels can hardly be compared to one another, even if their features have the same

(a)   (b)

Figure 3: **UMAP of the HPA FOV dataset highlighting different factors of variation.** UMAP space of the HPA FOV features obtained from the DINO BoC model pre-trained on the same dataset, colored according to (a) cell type and (b) protein localization. In (b) only samples with a single protein localization are displayed. The features are obtained separately for each channel, and then concatenated.

dimension. Therefore a common embedding space does not constitute an advantage of Channel-ViT over DINO BoC.

(a)   (b)

Figure 4: **UMAP of the HPA FOV dataset to assess utility of unified feature space.** a) UMAP space of the HPA FOV features obtained from the Channel-ViT model pre-trained on the same dataset, comparing features computed when the model sees all four channels of the dataset, in blue, and features computed with only two channels (microtobules and protein), in orange. b) Same UMAP as in (a) but filtered for images with only one protein localization and colored according to them.

Table 9: **Ablation removing one dataset from the ExtendedCHAMMI dataset.** We report the linear evaluation results for DINO BoC.

Training set	HPA-FOV F1 Protein loc.	HPA-FOV F1 Cell type	Accuracy on JUMP-CP	WTC F1 Cell cycle st.
ExtendedCHAMMI	61.1	91.2	44.9	91.0
minus WTC	60.4 $_{-0.7}$	**91.1** $_{-0.1}$	43.7 $_{-1.2}$	90.9 $_{-0.1}$
minus Cell painting	60.2 $_{-0.9}$	**91.1** $_{-0.1}$	44.1 $_{-0.8}$	89.8 $_{-1.2}$
minus HPA (FOV, single cell)	41.7 $_{-19.4}$	89.9 $_{-1.3}$	**46.9** $_{+2.0}$	**92.3** $_{+1.3}$
minus OpenCell	**60.9** $_{-0.2}$	91.0 $_{-0.2}$	44.2 $_{-0.7}$	90.0 $_{-1.0}$

H IMPACT OF THE REMOVAL OF DIFFERENT PRE-TRAINING DATASETS

To study the influence of specific pre-training datasets on the performance on others, we remove some pre-training datasets in Table 9 and evaluate the performance on HPA-FOV, JUMP-CP and WTC. As expected, when removing both HPA datasets, the protein localization performance is severely altered, but the cell type classification, a much easier task remains accurate. Not much difference is observed on the HPA tasks when removing the other datasets. In general, removing any dataset hurts the overall performance.

I RESULTS ON THE 8 CHANNELS OF JUMP-CP

As shown in Table 10, both DINO HA and DINO BoC are flexible, resulting in improved performance when the downstream tasks involves a larger number of channels than at pre-training time. Here, the pre-training dataset contains up to 5 channels, while the models are evaluated with up to 8.

Note that the Channel ViT approach cannot be evaluated on images that contain more channels than the maximum number of channels per image of the pre-training data, since there are no trained cahnnel embeddings for the extra channels.

Table 10: **Mean accuracy on the JUMP-CP dataset with models pre-trained on Extended-CHAMMI with a maximum of 5 channels.**

	JUMP-CP 5 channels	JUMP-CP 8 channels
Channel ViT	39.5	✗
DINO HA	**45.2**	51.4
DINO BoC	**45.2**	**51.6**

J EXPERIMENTS ON AERIAL IMAGERY

To demonstrate the capability of our DINO BoC approach to obtain useful features for imaging domains other than microcopy, we train and benchmark the performance of DINO BoC on the Meter-ML dataset introduced by Zhu et al. (2022) in Table 11.

The Meter-ML dataset contains images acquired by multiple sensors: four channels for NAIP images at resolution 720×720, four channels from Sentinel-2 at resolution 72×72, and lower resolution images from Sentinel-2 and Sentinel-1. Zhu et al. (2022) showed that the NAIP images led to better performance, and S2 could improve the result of one class accuracy. We trained one DINO BoC model on NAIP, and one on NAIP and S2 images, with only the highest resolution channels. The task consists in classifying sources of methane emissions in six categories (CAFOs, Landfills, Mines, ProcessingPlants, RefineriesAndTerminals, WWTreatment).

Using the exact same normalization and evaluation protocol than for the microscopy benchmarks, the performance of our DINO BoC approach is close to state-of-the-art approaches, even though it

Table 11: **DINO BoC performs on par with state-of-the-art models on the Meter-ML dataset.**
Top: AUROC of models trained on NAIP and Sentinel data. Bottom: AUROC of models using only
NAIP channels at inference.

Approach	Test dataset	Pre-training dataset	mAP
Meter-ML Zhu et al. (2022)	NAIP, S2, S1	NAIP, S2, S1 (85K)	51.7
LHRS-bot Muhtar et al. (2024)	NAIP, S2, S1	LHRS-Align-Recap (1.1M images & text)	71.8
VHM Pang et al. (2024)	NAIP, S2, S1	VersaD (14M images & text)	72.7
DINO BoC(ours)	NAIP, S2	Meter-ML NAIP, S2 train (85K)	70.9
Approach	Test dataset	Pre-training dataset	mAP
Meter-ML Zhu et al. (2022)	NAIP	NAIP (85K)	54.8
SatMAE Cong et al. (2022)	NAIP	fMoW Sentinel	76.9
ScaleMAE Reed et al. (2023)	NAIP	fMoW RGB (363K)	78.4
USatMAE Irvin et al. (2023)	NAIP	USAtlas NAIP (3.6M)	83.7
DINO BoC(ours)	NAIP	NAIP (85K)	82.2
DINO BoC(ours)	NAIP	NAIP, S2 (85K)	81.9

is pre-trained with an orders of magnitude smaller dataset, and does not use text nor other remote-
sensing specific architectures. This demonstrates the generality of our approach to a wider range of
imaging domains.