PlayFusion: Skill Acquisition via Diffusion from Language-Annotated Play

Abstract: Learning from unstructured and uncurated data has become the dominant paradigm for generative approaches in language and vision. Such unstructured and unguided behavior data, commonly known as *play*, is also easier to collect in robotics but much more difficult to learn from due to its inherently multimodal, noisy, and suboptimal nature. In this paper, we study this problem of learning goal-directed skill policies from unstructured play data which is labeled with language in hindsight. Specifically, we leverage advances in diffusion models to learn a multi-task diffusion model to extract robotic skills from play data. Using a conditional denoising diffusion process in the space of states and actions, we can gracefully handle the complexity and multimodality of play data and generate diverse and interesting robot behaviors. To make diffusion models more useful for skill learning, we encourage robotic agents to acquire a vocabulary of skills by introducing discrete bottlenecks into the conditional behavior generation process. In our experiments, we demonstrate the effectiveness of our approach across a wide variety of environments in both simulation and the real world. Video results available at https://play-fusion.github.io.

Keywords: Diffusion Models, Learning from Play, Language-Driven Robotics

1 Introduction

Humans reuse past experience via a broad repertoire of skills learned through experience that allows us to quickly solve new tasks and adapt across environments. For example, if one knows how to operate and load a dishwasher, many of the skills (e.g., opening the articulated door, adjusting the rack, putting objects in) will transfer seamlessly. How to learn such skills for robots and from what kind is a long-standing research question. Robotic skill abstraction has been studied as a way to transfer knowledge between environments and tasks [1, 2, 3]. It has been common to use primitives as actions in the options framework [4, 5], which are often hand-engineered [6, 7, 8, 9, 10, 11] or learned via imitation [12, 13, 14]. These allow for much more sample-efficient control but require knowledge of the task and need to be tuned for new settings. On the other hand, there have been efforts to *automatically* discover skills using latent variable models [15, 16, 17, 18, 19, 20, 21, 22]. While they can work in any setting, such models are often extremely data-hungry and have difficulty scaling to the real world due to the data quality at hand.

As a result, real-world paradigms are based on imitation or offline reinforcement learning (RL) but both these require several assumptions about the datasets. In imitation learning, human teleoperators must perform tasks near-perfectly, reset the robot to some initial state, perform the task near-perfectly again, and repeat several times. In offline RL, data is assumed to contain reward labels, which is impractical in many real-world setups where reward engineering is cumbersome. In contrast, it is much easier to collect uncurated data from human teleoperators if they are instructed only to explore, resulting in *play data* [21, 22, 23]. Learning from play (LfP) has emerged as a viable alternative to traditional data collection methods for behavior generation. It offers several advantages: (1) it is

Submitted to the 7th Conference on Robot Learning (CoRL 2023). Do not distribute.

Figure 1: Across multiple real-world and simulated robotic settings, we show that our model can extract semantically meaningful skills from language-annotated play data. Such data is highly multimodal and offers no optimality guarantees. Video results of PlayFusion are available at https://play-fusion.github.io.

efficient because large datasets of play can be collected without the need for setting up and executing perfect demonstrations, and (2) the data collected is rich and diverse because it contains a broad distribution of behavior ranging from completions of complex tasks to random meandering around the environment. An important quality of such data is that it is grounded with some semantic goal that the "player" is aiming to achieve. We believe a simple abstraction for this is *language* instructions, which can describe almost any play trajectory.

A major challenge in learning from play is that the data is highly multimodal, i.e., there are many different ways to achieve a specific goal, and given a sample from the play data, there are many different goals that could have generated it. One popular way to handle highly multimodal data is by modeling the full distribution via generative models. In recent years, there has been remarkable progress in large generative models [24, 25, 26, 27], especially in the class of diffusion models [28, 29], which have been shown to generate high-resolution images – a property well suited for vision-based robotic control. In fact, diffusion models have shown to be effective in capturing complex, continuous actions [30, 31, 29, 32, 33] in the context of robotics. However, these diffusion model-based approaches are still limited to learning from demonstrations or reward-labeled datasets, expensive data collection methods that may introduce undesirable assumptions to real-world robotics. We argue that the ability of diffusion models to fully capture complex data paired with their potential for text-driven generation can make them good candidates to learn from language-annotated play data.

One additional consideration is that in reality, humans only deal with a few skills. Almost every task manipulation task involves some grasping and some post-grasp movement. We believe that learning *discrete skills* will not only make the whole process more efficient but will also allow interpolation between skills and generalizations to new tasks. To address this, we propose **PlayFusion**, a diffusion model which can learn from language-annotated play data via discrete bottlenecks. We maintain the multimodal properties of our current system while allowing for a more discrete representation of skills. Empirically, we show that our method outperforms state-of-the-art approaches on six different environments: three challenging real-world manipulation settings as well as the CALVIN [34], Franka Kitchen [22], and Ravens [35, 36] simulation benchmarks.

2 Related Work

Goal and Language Conditioned Skill Learning One method of specifying the task is via goal-conditioned learning, often by using the actual achieved last state as the goal [37, 38, 39, 40]. There is also recent work on using rewards to condition robot behavior [41], but this requires a reward-labeled dataset, which makes stronger assumptions than play data. Furthermore, there is a large body of work on language-conditioned learning [42, 36, 43, 44, 45, 46, 47], which specifies the task through language instructions. Instead of conditioning the policy on fully labeled and curated data, we take advantage of unstructured play data which is annotated with language in hindsight.

Figure 2: Overview of how PlayFusion extracts useful skills from language-annotated play by leveraging discrete bottlenecks in both the language embedding and diffusion model U-Net. We generate robot trajectories via an iterative denoising process conditioned on language and current state.

Learning from Play Unlike demonstrations, play data is not assumed to be optimal for any specific task as it is collected by human teleoperators who are instructed only to explore. Play-LMP [21] generates behaviors by learning motor primitives from play data using a VAE [48, 49]. RIL [22] is a hierarchical imitation learning approach and C-BeT [23] generates behaviors using a transformer-based policy and leverages action discretization to handle multimodality.

Behavior Modeling with Generative Models A promising architecture for behavior modeling with generative models is the diffusion probabilistic model [28, 50, 51, 52]. Diffuser [30], Decision Diffuser [31], Diffusion-QL [29] and IDQL [32] apply diffusion models to the offline reinforcement learning (RL) problem. In real-world robotic applications, Diffusion Policy [33] demonstrated strong results in visuomotor policy learning from demonstrations. Different from these works, we learn from play data containing semantic labels instead of offline RL datasets or expert demonstrations.

Discrete control A key challenge in robot learning is the exponentially large, continuous action space. Option or skill-based learning is appealing as it can circumvent this problem and allow the agent to learn in a structured, countable action space [53, 54, 55, 56]. Learned action discretization [50, 23] has allowed approaches to scale to complex tasks. C-BeT [23] applies real-world robotic control with transformers [41, 57, 58] to the goal-conditioned setting; [59] train a dynamics model over discrete latent states. We leverage the discrete properties of VQ-VAEs and their natural connection to language-labeled skills.

3 Background

Denoising Diffusion Probabilistic Models (DDPMs) DDPMs [28] model the output generation process as a denoising process, which is often referred to as Stochastic Langevin Dynamics. To generate the output, the DDPM starts by sampling x^K from a Gaussian noise distribution. It then performs a series of denoising iterations, totaling K iterations, to generate a sequence of intermediate outputs, $x^k, x^{k-1}, \cdots, x^0$. This iterative process continues until a noise-free output x^0 is produced. The denoising process is governed by the following equation:

$$x^{k-1} = \alpha(x^k - \gamma\epsilon_\theta(x^k, k) + N(0, \sigma^2 I)) \tag{1}$$

Here, ϵ_θ represents the noise prediction network with a learnable parameter θ, and $N(0, \sigma^2 I)$ denotes the Gaussian noise added at each iteration. This equation is used to generate intermediate outputs with gradually decreasing noise levels until a noise-free output is obtained. To train the DDPM, the process begins by randomly selecting x^0 from the training dataset. For each selected sample, a denoising iteration k is randomly chosen, and a noise ϵ^k is sampled with the appropriate variance for the selected iteration. The noise prediction network is then trained to predict the noise by minimizing:

$$\mathcal{L} = ||\epsilon^k - \epsilon_\theta(x^0 + \epsilon^k, k)||^2 \tag{2}$$

Discrete Representations We utilize VQ-VAE [60] inspired models in PlayFusion as they can provide a way to discretize the skill space. Given an input x, a VQ-VAE trains an encoder E to predict latent $E(x) = z$ and maintains a codebook of discrete latent codes e. The VQ layer selects j as $\arg\min_i ||z - e_i||$, finding the closest code to the embedding, which is used to reconstruct x. The training loss is

$$\mathcal{L}_{\text{VQVAE}} = \mathcal{L}_{\text{recon}}(x, D(e_j)) + ||z - sg(e_j)||_2 + ||sg(z) - e_j||_2 \tag{3}$$

where D is the VQ-VAE decoder. The reconstruction loss is augmented with a quantization loss, bringing chosen codebook embedding vectors e_j toward the encoder outputs in order to train the codebook, as well a loss to encourage the encoder to "commit" to one of the embeddings.

Learning from Play Data (LfP) In the LfP setting, we are given a dataset $\{(s, a)\} \in S \times A$. There are no assumptions about tasks performed in these sequences or the optimality of the data collection method. Similar to the formulation of [23], the goal is to learn a policy $\pi = S \times S \rightarrow A$ where the input is the current state s_t and goal $g = s_T$. In some cases, (including ours), the goals are instead described via language annotations.

4 PlayFusion: Discrete Diffusion for Language-Annotated Play

Humans do not think about low-level control when performing everyday tasks. Our understanding of skills like door opening or picking up objects has already been grounded in countless prior experiences, and we can comfortably perform these in new settings. Skills are acquired through our prior experiences – successes, failures, and everything in between. PlayFusion focuses on learning these skills through *language-annotated* play data.

However, learning from play data is still difficult as continuous control skills are not easy to identify due to several challenges: (1) data can come from multiple modalities as there are many actions that the robot could have taken at any point, (2) we want the model to acquire a vocabulary of meaningful skillsm and (3) we want to generalize *beyond* the training data and have the model transfer skills to new settings. To address the challenges, we leverage recent advances in **diffusion-model** large-scale text-to-image generation. Such models [33, 30, 29] can inherently model multimodality via their iterative denoising process. To effectively transfer skills to new settings, we propose a modified diffusion model with the ability to **discretize** learned behavior from language-annotated data. Figure 2 shows an overview of our method.

4.1 Language Conditioned Play Data

Our setup consists of language conditioned play data [21] $D_{\text{play}} = \{(s_t^{(i)}, a_t^{(i)})\}_{i=1}^N$: long sequences of robot behavior data containing many kinds of behaviors, collected by human operators instructed to perform interesting tasks. In this setting, we assume that there is some optimality to the data, i.e. $a_t \sim \mathcal{F}(s_t, z_g)$, where z_g is a latent variable that models the intention of the operator. We thus leverage *language* labels to estimate z_g. Given a sequence $\tau = \{s_i, a_i\}_{t=k}^H$, label τ with an instruction l which is passed into a language model [61], g_{lang}, referring to it as z_l throughout the paper. One can also use goal images, but we might not have access to these at test time. While our method can use any z_g as conditioning, assume that the play data has access to language annotations l. Our policy $\pi(a_t|s_t, z_l)$ contains a few simple components. We use a ResNet[62]-based visual encoder ϕ_v to encode s_t (a sequence of images) and an MLP based langauge encoder ϕ_l to downproject the language embedding z_l. The policy uses $g = [\phi_l(z_l), \phi_v(s_t)]$ as conditioning to the action decoder f_{act}. Previous approaches [21, 34] use latent variable models to deal with multimodality. We find that modelling f_{act} as a diffusion process enables us to circumvent this.

4.2 Multi-modal Behavior Generation via Diffusion

With f_{act}, we aim to predict robot actions given the current state, using a DDPM to approximate the conditional distribution $P(a_t|s_t)$. In our setting, we additionally condition on the goal g. Formally,

CALVIN	Franka Kitchen	Ravens
Sink	Dining Table	Cooking

Figure 3: Simulated (top row) and real-world (bottom row) environments used for our evaluations. In each real-world setup, the robot is tasked with picking up one of the objects (e.g., plate, cup, carrot, bread, corn) and relocating it to a specified location (e.g., drying rack, plate, toaster, grill, pot).

we train the model to generate robot actions a_t conditioned on goal g and current state s_t, so we modify Equations 1 and 7 to obtain:

$$a_t^{k-1} = \alpha(a_t^k - \gamma\epsilon_\theta(g, s_t, a_t^k, k) + N(0, \sigma^2 I)) \tag{4}$$

$$\mathcal{L} = ||\epsilon^k - \epsilon_\theta(g, s_t, a_t^0 + \epsilon^k, k)||_2 \tag{5}$$

We use the notation above for simplicity, but in practice, we predict a sequence of T_a future actions $a_t, \cdots, a_{t+T_a}$ instead of only the most immediate action, a technique known as *action chunking*. This is done in some recent works [33, 63] and is shown to improve temporal consistency.

4.3 Discrete Diffusion for Control

Moreover, humans often break down tasks into smaller skills, which are often repeatable. In fact, most tasks can be achieved with a relatively small set. On the other hand, both the latent goals that we learn as well as the action diffusion process are continuous. Making sure learnt skills are discrete can not only allow for better performance but also better generalization to new settings. However, naively enforcing discretization can lead to suboptimal behavior. We want to ensure that conditioned on a latent goal, g, action predictions from f_{act} are both multimodal and yet only represent a few modes. Thus, we propose a discrete *bottleneck* instead.

For the action generation process to represent a useful skill space, we want to enforce discreteness where the actions interact with latent goal. PlayFusion adds a vector quantization bottleneck in the diffusion process, specifically in the network $\epsilon_\theta(x) = \epsilon_\theta(g, s_t, a_t^0 + \epsilon^k, k)$. ϵ_θ is U-Net which fuses the language conditioning into the action denoising. We modify the U-Net architecture with a codebook of discrete latent codes e_u, a discrete bottleneck for the diffusion model. Given an input x the U-Net encoder produces a latent $\psi_\epsilon(x)$, which is passed into the decoder to produce $\epsilon_\theta(x) = \gamma_\epsilon(\psi_\epsilon(x))$. This bottleneck layer selects j as $\arg\min_i ||\psi_\epsilon(x) - e_i||$, finding the closest code to the embedding, which is used to reconstruct x. To account for this, we augment the training procedure with the quantization and commitment losses, similar to VQ-VAE.

Generalization via discrete language conditioning Consider an agent that has learnt skills formed from the atomic units A, B, C and C, of the form A + B, B + C and C + D. To truly extend its capabilities beyond the initial training data, the agent must learn to interpolate and extrapolate from these existing skills, being able to perform tasks like A + D that it hasn't explicitly been trained on. Given that the action generation in the diffusion process is already quantized, our hypothesis is that a discrete goal space will be synergestic and allow the policy to compose skills better. Thus, we

	Simulation					Real World		
	CALVIN A	CALVIN B	Kitchen A	Kitchen B	Ravens	Dining Table	Cooking	Sink
C-BeT [23]	27.0	21.7	40.0	20.0	12.5	20.0	0.0	10.0
Play-LMP [21]	22.5	21.3	0.0	0.0	5.0	0.0	0.0	0.0
GCBC [21]	23.8	29.5	**45.7**	10.0	2.5	5.0	0.0	5.0
Ours	**47.1**	**59.0**	**45.7**	**23.3**	**40.9**	**45.0**	**30.0**	**20.0**

Table 1: Success rates for PlayFusion and the baselines on simulation and real-world settings. PlayFusion consistently outperforms all of the baselines.

maintain a codebook of discrete latent codes e_l for the language embeddings output by the language goal network $\phi_l(z_l)$, selecting $e_{l,j}$ which is closest to $\phi_l(z_l)$. The full loss function that we use to train PlayFusion is as follows:

$$\mathcal{L}_{PlayFusion} = ||\epsilon^k - \epsilon_\theta(x^0 + \epsilon^k, k)||_2 + \beta_1 ||sg(\psi_\epsilon(x) - e_{u,j})||_2 + \beta_1 ||\psi_\epsilon(x) - sg(e_{u,j})||_2 \quad (6)$$
$$+ \beta_2 ||sg(\phi_l(z_l)) - e_{l,j}||_2 + \beta_2 ||\phi_l(z_l) - sg(e_{l,j})||_2 \quad (7)$$

where β_1 and β_2 are coefficients to determine the tradeoff between covering a diversity of possible behaviors and encouraging behaviors belonging to similar skills to be brought close to each other.

Sampling from PlayFusion Given a novel language instruction at test time z', we obtain the quantized encoding $\phi_l(z')$, combining it with the visual encoding to get conditioning g'. We sample a set of actions $a_{t:t+k} \sim \mathcal{N}(0, 1)$, pass them through the discrete denoising process in Equation 4.

5 Experiments

In this section, we investigate PlayFusion and its ability to scale to complex tasks, as well as generalization to new settings. We ask the following questions: (1) Can PlayFusion allow for learning complex manipulation tasks from language annotated play data? (2) Can our method perform efficiently in the real-world setup beyond the simulated environment? (3) How well can PlayFusion generalize to out of distribution settings? (4) Can PlayFusion in fact learn discrete skills? (5) How do various design choices, such as quantization, language conditioning, etc., affect PlayFusion? We aim to answer these through experiments in three different simulation and real world settings.

Environmental Setup We test our approach across a wide variety of environments in both simulations as well as the real world. For simulation, we evaluate three benchmarks: (a) CALVIN [34], (b) Franka Kitchen [22], and (c) Language-Conditioned Ravens [35, 36]. For the real-world setup, we create three different environments: `cooking`, `dining table` and `sink`, shown in Figure 3. More details of the environment setup are in the supplementary.

Baselines We handle task conditioning in the same way for our method as well as all baselines, using the same visual and language encoders. We compare our method with the following baselines: (a) *Learning Motor Primitives from Play (Play-LMP)*: Play-LMP [21] generates behaviors by learning motor primitives from play data using a VAE, which encodes action sequences into latents and then decodes them into actions. (b) *Conditional Behavior Transformer (C-BeT)*: C-BeT [23] generates behaviors using a transformer-based policy and leverages action discretization to handle multimodality. (c) *Goal-Conditioned Behavior Cloning (GCBC)*: GCBC [21, 64] is conditional behavior cloning.

5.1 Results in Simulation and Real World

PlayFusion in simulation Table 1 shows success rates for PlayFusion, Play-LMP, C-BeT, and GCBC on the simulation benchmarks. On both CALVIN setups, we outperform the baselines by a wide margin, which demonstrates the effectiveness of our method in large-scale language-conditioned

policy learning from complex, multimodal play data. The baselines perform comparatively better on the Franka Kitchen environments, where the training datasets are smaller and the data covers a more narrow behavior distribution and the benefit of handling multimodality is smaller; however, PlayFusion still outperforms or matches all baselines. PlayFusion also achieves significantly higher success rate than the baselines on Ravens, which is not as large-scale as CALVIN but covers a large portion of the possible state space due to the diversity of possible language instructions.

Long horizon tasks   Using the Long Horizon CALVIN evaluation suite, we test the ability of agents to stitch together different tasks, with transitioning between tasks being particularly difficult. One such long horizon chain might be "turn on the led" → "open drawer" → "push the blue block" → "pick up the blue block" → "place in slider". We rollout 128 different long horizon chains containing five instructions each and record the number of instructions successfully completed. As shown in Table 2, we find that PlayFusion significantly outperforms the baselines in both CALVIN A and CALVIN B. The diffusion process gracefully handles the multimodality of not only each individual task in the chain but also of the highly varied data the agent has seen of transitions between tasks.

	Av. Seq Len	No. of Instructions				
		1	2	3	4	5
CALVIN A :						
C-BeT	0.262	25.2	1.0	0.0	0.0	0.0
Play-LMP	0.175	16.5	1.0	0.0	0.0	0.0
GCBC	0.194	19.4	0.0	0.0	0.0	0.0
CALVIN B :						
C-BeT	0.272	27.2	0.0	0.0	0.0	0.0
Play-LMP	0.117	11.7	0.0	0.0	0.0	0.0
GCBC	0.291	27.2	1.9	0.0	0.0	0.0
Ours (A)	**0.417**	**37.1**	**2.9**	**1.0**	0.0	0.0
Ours (B)	**0.611**	**54.4**	**6.0**	0.0	0.0	0.0

Table 2: Average sequence length on Long Horizon CALVIN and success rate for the n-th instructions.

Generalization in the real world   Table 1 shows results for PlayFusion and the baselines in our real world evaluation setups. These setups are particularly challenging for two reasons: (1) inherent challenges with real-world robotics such as noisier data and constantly changing environment conditions such as lighting, and (2) they are designed to test skill-level compositional generalization. Specifically, the agents are required to compose skills `A + B` and `C + D` into `A + D`; for example, they might be trained on "pick up the carrot and place it in the pan" and "pick up the bread and put it in the toaster" and must generalize to "pick up the carrot and put it in the toaster". Our method significantly outperforms the baselines in these settings, showcasing the ability of the diffusion model in modeling complex distributions and the emergence of learned skills via the discrete bottleneck. Video results are at `https://play-fusion.github.io`.

5.2   Analysis of Discrete Representations

Learning discrete skills   Table 3 studies the impact of our discrete bottlenecks. The success rate (averaged over CALVIN A and B) is worsened with the removal of either the U-Net discretization and the language embedding discretization. We also qualitatively study whether semantically similar skills are actually mapped to similar areas of the latent space and should therefore be brought together by the discrete bottleneck. In Figure 4, we show that skills involving similar locations (e.g., pan) or objects (e.g.,

Figure 4: Visualization of the codebook embeddings for various real-world skills.

carrot) are encoded into similar embeddings. In Figure 4, we show the embeddings of different trajectories. The top two rows share the first skill (which is to remove the lid from the pan) and place an object in the pan. The bottom two rows share the second skill (grasping the carrot). Embeddings that contain the same skill have a similar pattern, which further indicates that the latent skill space being learned is somewhat discretized.

Balancing the discrete bottlenecks   In Table 4, we study the effects of different β_1 and β_2 values on CALVIN A performance, i.e., the relative weightings for the additional terms in the loss function corresponding to the U-Net discretization and language embedding discretization. We find that $\beta_1 = \beta_2 = 0.5$ results in the best performance. In general, equally weighing the four additional losses (two for U-Net and two for language) leads to improved performance over imbalanced weightings. $\beta_1 = \beta_2 = 0.5$ is also better than $\beta_1 = \beta_2 = 1$, indicating that over-incentivizing discretization can be detrimental to diffusion model learning.

Methods	Success Rate
Ours	**53.1**
No U-Net discretization	51.2
No lang discretization	45.1

Table 3: Effect of discrete bottlenecks.

5.3 Ablations of Design Choices

Effect of language model   Although our method is orthogonal to the language model used, we test its sensitivity to this. As shown in Table 4, we find that common models such as MiniLM [61], Distilroberta [65], MPNet [66], and BERT [67] have similar performance, showing that PlayFusion is mostly robust to this design choice. We hypothesize that the discrete bottleneck applied to the language embeddings helps to achieve this robustness. CLIP [68] embeddings result in much lower success rates, most likely due the fact that Internet images may not contain similar "play data" instructions.

Effect of conditioning   Table 4 studies various different possibilities for conditioning the diffusion model generations on language and vision in CALVIN A. When working with diffusion models there are multiple different ways we can approach how to feed it goals, images of the scene etc. We found that PlayFusion is mostly robust to this, with global conditioning providing benefits for smaller models (such as those in the real world). We also attempted to condition the diffusion model noise on the goal but found that this negatively impacted performance. For the visual conditioning, we studied the effect of initializing the image encoder with large-scale pre-trained models [69]), finding that it does not help, and PlayFusion can learn the visual encoder. end-to-end from scratch

	Success Rate
Effect of conditioning:	
Global	54.1
Conditional Noise	40.2
Visual Pre-training	38.1
Effect of language model:	
all-MiniLM-L6-v2	47.1
all-distilroberta-v1	48.4
all-mpnet-base-v2	48.8
BERT	48.8
CLIP (ResNet50)	35.2
CLIP (ViTB32)	43.9
Loss weights (U-Net & Language) :	
0.5 & 0.5	47.1
1 & 1	45.1
0.1 & 1	45.5
1 & 0.1	43.4
0.25 & 0.75	37.7
0.75 & 0.25	43.4

Table 4: Effects of conditioning, language model, and loss weights.

Model design choices   Figure 5 studies the impact of the main design choices in our model architecture in CALVIN A. PlayFusion is mostly robust to the action horizon T_a (Figure 5a). We empirically found t_a of around 20% of the overall horizon worked the best. We find that PlayFusion is relatively robust to the discrete latent codebook sizes (Figure 5b).

(a) Action Horizon	(b) Codebook size

Figure 5: Effect of model design choices.

6 Limitations and Discussion

In this paper, we introduced a novel approach for learning a multi-task robotic control policy using a denoising diffusion process on trajectories, conditioned on language instructions. Our method exploits the effectiveness of diffusion models in handling multimodality and introduces two discrete bottlenecks in the diffusion model in order to incentivize the model to learn semantically meaningful skills. PlayFusion does require the collection of teleoperated play data paired with after-the-fact language annotations, which still require human effort despite being already less expensive and time-consuming to collect than demonstrations. It would be interesting to label the play data with a captioning model or other autonomous method. Furthermore, there is room for improvement in our performance on our real-world setups. Additionally, our real-world experiments could be expanded to even more complex household settings such as study rooms, bed rooms, and living rooms. Overall, our approach can significantly enhance the ability of robots to operate autonomously in complex and dynamic environments, making them more useful in a wide range of applications.

References

[1] R. S. Sutton, D. Precup, and S. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial intelligence*, 112(1-2):181–211, 1999.

[2] S. Thrun, C. Faloutsos, T. Mitchell, and L. Wasserman. Automated learning and discovery state-of-the-art and research topics in a rapidly growing field. *Ai Magazine*, 20(3):78–78, 1999.

[3] M. Pickett and A. G. Barto. Policyblocks: An algorithm for creating useful macro-actions in reinforcement learning. In *ICML*, volume 19, pages 506–513, 2002.

[4] P.-L. Bacon, J. Harb, and D. Precup. The option-critic architecture. In *AAAI*, 2017.

[5] R. S. Sutton, D. Precup, and S. Singh. Between mdps and semi-mdps: A framework for temporal abstraction in reinforcement learning. *Artificial Intelligence*, 1999.

[6] C. Daniel, G. Neumann, O. Kroemer, and J. Peters. Hierarchical relative entropy policy search. *Journal of Machine Learning Research*, 2016.

[7] F. Stulp, E. A. Theodorou, and S. Schaal. Reinforcement learning with sequences of motion primitives for robust manipulation. *Transactions on Robotics*, 2012.

[8] J. Kober and J. Peters. Learning motor primitives for robotics. In *ICRA*, 2009.

[9] P. Pastor, M. Kalakrishnan, S. Chitta, E. Theodorou, and S. Schaal. Skill learning and task outcome prediction for manipulation. In *ICRA*, 2011.

[10] M. Dalal, D. Pathak, and R. R. Salakhutdinov. Accelerating robotic reinforcement learning via parameterized action primitives. *NeurIPS*, 2021.

[11] S. Nasiriany, H. Liu, and Y. Zhu. Augmenting reinforcement learning with behavior primitives for diverse manipulation tasks. In *ICRA*, 2022.

[12] K. Pertsch, Y. Lee, and J. Lim. Accelerating reinforcement learning with learned skill priors. In *Conference on robot learning*, pages 188–204. PMLR, 2021.

[13] S. Bahl, A. Gupta, and D. Pathak. Hierarchical neural dynamic policies. *RSS*, 2021.

[14] K. Pertsch, R. Desai, V. Kumar, F. Meier, J. J. Lim, D. Batra, and A. Rai. Cross-domain transfer via semantic skill imitation. *arXiv preprint arXiv:2212.07407*, 2022.

[15] B. Eysenbach, A. Gupta, J. Ibarz, and S. Levine. Diversity is all you need: learning skills without a reward function. *arXiv preprint arXiv:1802.06070*, 2018.

[16] A. Sharma, S. Gu, S. Levine, V. Kumar, and K. Hausman. Dynamics-aware unsupervised discovery of skills. *arXiv preprint arXiv:1907.01657*, 2019.

[17] J. Merel, S. Tunyasuvunakool, A. Ahuja, Y. Tassa, L. Hasenclever, V. Pham, T. Erez, G. Wayne, and N. Heess. Catch & carry: reusable neural controllers for vision-guided whole-body tasks. *ACM Transactions on Graphics (TOG)*, 39(4):39–1, 2020.

[18] T. Shankar and A. Gupta. Learning robot skills with temporal variational inference. In *International Conference on Machine Learning*, pages 8624–8633. PMLR, 2020.

[19] T. Kipf, Y. Li, H. Dai, V. Zambaldi, A. Sanchez-Gonzalez, E. Grefenstette, P. Kohli, and P. Battaglia. Compile: Compositional imitation learning and execution. In *International Conference on Machine Learning*, pages 3418–3428. PMLR, 2019.

[20] W. Whitney, R. Agarwal, K. Cho, and A. Gupta. Dynamics-aware embeddings. *arXiv preprint arXiv:1908.09357*, 2019.

[21] C. Lynch, M. Khansari, T. Xiao, V. Kumar, J. Tompson, S. Levine, and P. Sermanet. Learning latent plans from play. *arXiv preprint arXiv:1903.01973*, 2019.

[22] A. Gupta, V. Kumar, C. Lynch, S. Levine, and K. Hausman. Relay policy learning: Solving long-horizon tasks via imitation and reinforcement learning. *arXiv preprint arXiv:1910.11956*, 2019.

[23] Z. J. Cui, Y. Wang, N. Muhammad, L. Pinto, et al. From play to policy: Conditional behavior generation from uncurated robot data. *arXiv preprint arXiv:2210.10047*, 2022.

[24] A. Ramesh, M. Pavlov, G. Goh, S. Gray, C. Voss, A. Radford, M. Chen, and I. Sutskever. Zero-shot text-to-image generation. In *International Conference on Machine Learning*, pages 8821–8831. PMLR, 2021.

[25] A. Ramesh, P. Dhariwal, A. Nichol, C. Chu, and M. Chen. Hierarchical text-conditional image generation with clip latents. *arXiv preprint arXiv:2204.06125*, 2022.

[26] R. Rombach, A. Blattmann, D. Lorenz, P. Esser, and B. Ommer. High-resolution image synthesis with latent diffusion models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10684–10695, 2022.

[27] T. Brown, B. Mann, N. Ryder, M. Subbiah, J. D. Kaplan, P. Dhariwal, A. Neelakantan, P. Shyam, G. Sastry, A. Askell, et al. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901, 2020.

[28] J. Ho, A. Jain, and P. Abbeel. Denoising diffusion probabilistic models. *Advances in Neural Information Processing Systems*, 33:6840–6851, 2020.

[29] Z. Wang, J. J. Hunt, and M. Zhou. Diffusion policies as an expressive policy class for offline reinforcement learning. *arXiv preprint arXiv:2208.06193*, 2022.

[30] M. Janner, Y. Du, J. B. Tenenbaum, and S. Levine. Planning with diffusion for flexible behavior synthesis. *arXiv preprint arXiv:2205.09991*, 2022.

[31] A. Ajay, Y. Du, A. Gupta, J. Tenenbaum, T. Jaakkola, and P. Agrawal. Is conditional generative modeling all you need for decision-making? *arXiv preprint arXiv:2211.15657*, 2022.

[32] P. Hansen-Estruch, I. Kostrikov, M. Janner, J. G. Kuba, and S. Levine. Idql: Implicit q-learning as an actor-critic method with diffusion policies. *arXiv preprint arXiv:2304.10573*, 2023.

[33] C. Chi, S. Feng, Y. Du, Z. Xu, E. Cousineau, B. Burchfiel, and S. Song. Diffusion policy: Visuomotor policy learning via action diffusion. *arXiv preprint arXiv:2303.04137*, 2023.

[34] O. Mees, L. Hermann, E. Rosete-Beas, and W. Burgard. Calvin: A benchmark for language-conditioned policy learning for long-horizon robot manipulation tasks. *IEEE Robotics and Automation Letters*, 7(3):7327–7334, 2022.

[35] A. Zeng, P. Florence, J. Tompson, S. Welker, J. Chien, M. Attarian, T. Armstrong, I. Krasin, D. Duong, V. Sindhwani, and J. Lee. Transporter networks: Rearranging the visual world for robotic manipulation. *CoRL*, 2020.

[36] M. Shridhar, L. Manuelli, and D. Fox. Cliport: What and where pathways for robotic manipulation. In *Conference on Robot Learning*, pages 894–906. PMLR, 2022.

[37] L. P. Kaelbling. Learning to achieve goals. In *IJCAI*, volume 2, pages 1094–8. Citeseer, 1993.

[38] M. Andrychowicz, F. Wolski, A. Ray, J. Schneider, R. Fong, P. Welinder, B. McGrew, J. Tobin, O. Pieter Abbeel, and W. Zaremba. Hindsight experience replay. *Advances in neural information processing systems*, 30, 2017.

[39] D. Ghosh, A. Gupta, A. Reddy, J. Fu, C. Devin, B. Eysenbach, and S. Levine. Learning to reach goals via iterated supervised learning. *arXiv preprint arXiv:1912.06088*, 2019.

[40] A. Goyal, A. Friesen, A. Banino, T. Weber, N. R. Ke, A. P. Badia, A. Guez, M. Mirza, P. C. Humphreys, K. Konyushova, et al. Retrieval-augmented reinforcement learning. In *International Conference on Machine Learning*, pages 7740–7765. PMLR, 2022.

[41] L. Chen, K. Lu, A. Rajeswaran, K. Lee, A. Grover, M. Laskin, P. Abbeel, A. Srinivas, and I. Mordatch. Decision transformer: Reinforcement learning via sequence modeling. *Advances in neural information processing systems*, 34:15084–15097, 2021.

[42] C. Lynch and P. Sermanet. Grounding language in play. *arXiv preprint arXiv:2005.07648*, 40: 105, 2020.

[43] E. Jang, A. Irpan, M. Khansari, D. Kappler, F. Ebert, C. Lynch, S. Levine, and C. Finn. Bc-z: Zero-shot task generalization with robotic imitation learning. In *Conference on Robot Learning*, pages 991–1002. PMLR, 2022.

[44] M. Ahn, A. Brohan, N. Brown, Y. Chebotar, O. Cortes, B. David, C. Finn, K. Gopalakrishnan, K. Hausman, A. Herzog, et al. Do as i can, not as i say: Grounding language in robotic affordances. *arXiv preprint arXiv:2204.01691*, 2022.

[45] S. Nair, E. Mitchell, K. Chen, S. Savarese, C. Finn, et al. Learning language-conditioned robot behavior from offline data and crowd-sourced annotation. In *Conference on Robot Learning*, pages 1303–1315. PMLR, 2022.

[46] O. Mees, L. Hermann, and W. Burgard. What matters in language conditioned robotic imitation learning over unstructured data. *IEEE Robotics and Automation Letters*, 7(4):11205–11212, 2022.

[47] M. Shridhar, L. Manuelli, and D. Fox. Perceiver-actor: A multi-task transformer for robotic manipulation. In *Conference on Robot Learning*, pages 785–799. PMLR, 2023.

[48] D. P. Kingma and M. Welling. Auto-encoding variational bayes. *arXiv preprint arXiv:1312.6114*, 2013.

[49] D. J. Rezende, S. Mohamed, and D. Wierstra. Stochastic backpropagation and approximate inference in deep generative models. *arXiv preprint arXiv:1401.4082*, 2014.

[50] N. M. Shafiullah, Z. Cui, A. A. Altanzaya, and L. Pinto. Behavior transformers: Cloning k modes with one stone. *Advances in neural information processing systems*, 35:22955–22968, 2022.

[51] D. Hafner, T. Lillicrap, I. Fischer, R. Villegas, D. Ha, H. Lee, and J. Davidson. Learning latent dynamics for planning from pixels. *arXiv preprint arXiv:1811.04551*, 2018.

[52] D. Hafner, T. Lillicrap, J. Ba, and M. Norouzi. Dream to control: Learning behaviors by latent imagination. *arXiv preprint arXiv:1912.01603*, 2019.

[53] D. Silver, J. Schrittwieser, K. Simonyan, I. Antonoglou, A. Huang, A. Guez, T. Hubert, L. Baker, M. Lai, A. Bolton, Y. Chen, T. Lillicrap, F. Hui, L. Sifre, G. van den Driessche, T. Graepel, and D. Hassabis. Mastering the game of go without human knowledge. *Nature*, 2017.

[54] D. Silver, A. Huang, C. J. Maddison, A. Guez, L. Sifre, G. Van Den Driessche, J. Schrittwieser, I. Antonoglou, V. Panneershelvam, M. Lanctot, et al. Mastering the game of go with deep neural networks and tree search. *nature*, 529(7587):484, 2016.

[55] V. Mnih, K. Kavukcuoglu, D. Silver, A. A. Rusu, J. Veness, M. G. Bellemare, A. Graves, M. Riedmiller, A. K. Fidjeland, G. Ostrovski, S. Petersen, C. Beattie, A. Sadik, I. Antonoglou, H. King, D. Kumaran, D. Wierstra, S. Legg, and D. Hassabis. Human-level control through deep reinforcement learning. *Nature*, 518(7540):529–533, Feb. 2015.

[56] M. G. Bellemare, Y. Naddaf, J. Veness, and M. Bowling. The arcade learning environment: An evaluation platform for general agents. *Journal of Artificial Intelligence Research*, 47:253–279, jun 2013.

[57] M. Janner, Q. Li, and S. Levine. Offline reinforcement learning as one big sequence modeling problem. *Advances in neural information processing systems*, 34:1273–1286, 2021.

[58] P. Wu, A. Majumdar, K. Stone, Y. Lin, I. Mordatch, P. Abbeel, and A. Rajeswaran. Masked trajectory models for prediction, representation, and control. *arXiv preprint arXiv:2305.02968*, 2023.

[59] S. Ozair, Y. Li, A. Razavi, I. Antonoglou, A. Van Den Oord, and O. Vinyals. Vector quantized models for planning. In *International Conference on Machine Learning*, pages 8302–8313. PMLR, 2021.

[60] A. van den Oord, O. Vinyals, et al. Neural discrete representation learning. In *NeurIPS*, pages 6309–6318, 2017.

[61] N. Reimers and I. Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. *arXiv preprint arXiv:1908.10084*, 2019.

[62] K. He, X. Zhang, S. Ren, and J. Sun. Deep residual learning for image recognition. *CoRR*, abs/1512.03385, 2015. URL http://arxiv.org/abs/1512.03385.

[63] T. Z. Zhao, V. Kumar, S. Levine, and C. Finn. Learning fine-grained bimanual manipulation with low-cost hardware. *arXiv preprint arXiv:2304.13705*, 2023.

[64] Y. Ding, C. Florensa, M. Phielipp, and P. Abbeel. Goal-conditioned imitation learning. *arXiv preprint arXiv:1906.05838*, 2019.

[65] Y. Liu, M. Ott, N. Goyal, J. Du, M. Joshi, D. Chen, O. Levy, M. Lewis, L. Zettlemoyer, and V. Stoyanov. Roberta: A robustly optimized bert pretraining approach. *arXiv preprint arXiv:1907.11692*, 2019.

[66] K. Song, X. Tan, T. Qin, J. Lu, and T.-Y. Liu. Mpnet: Masked and permuted pre-training for language understanding. *Advances in Neural Information Processing Systems*, 33:16857–16867, 2020.

[67] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. 2018.

[68] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, et al. Learning transferable visual models from natural language supervision. In *International conference on machine learning*, pages 8748–8763. PMLR, 2021.

[69] S. Nair, A. Rajeswaran, V. Kumar, C. Finn, and A. Gupta. R3m: A universal visual representation for robot manipulation. *arXiv preprint arXiv:2203.12601*, 2022.