Improving Self-Supervised Learning by Characterizing Idealized Representations

Abstract

Despite the empirical successes of self-supervised learning (SSL) methods, it is unclear what characteristics of their representations lead to high downstream accuracies. In this work, we characterize properties that SSL representations should *ideally* satisfy. Specifically, we prove necessary and sufficient conditions such that for any task invariant to given data augmentations, desired probes (e.g., linear or MLP) trained on that representation attain perfect accuracy. These requirements lead to a unifying conceptual framework for improving existing SSL methods and deriving new ones. For contrastive learning, our framework prescribes simple but significant improvements to previous methods such as using asymmetric projection heads. For non-contrastive learning, we use our framework to derive a simple and novel objective. Our resulting SSL algorithms outperform baselines on standard benchmarks, including SwAV+multicrops on linear probing of ImageNet.

1 Introduction

We study self-supervised learning (SSL), where the goal is to learn representations from minimal supervision, such that simple probes trained on these representations achieve high downstream accuracy. Recently, there has been many different SSL methods achieving impressive empirical results (e.g. SimCLR [1], SwAV [2]) using label-preserving augmentations (e.g. cropping or color jittering) as supervision. We dub this setting *invariant SSL* (ISSL). Despite these empirical successes, it remains unclear how these various SSL methods relate to one another, how to improve them, and how to derive new ones. Our goal is to provide a simple conceptual framework to think about those questions.

To derive such a framework, we ask ourselves: *what are the ideal requirements that ISSL representations should aim to satisfy?* We prove necessary and sufficient requirements to ensure that probes from a specified family, e.g. linear or multi-layer perceptron (MLP), perfectly classify any task that is invariant to desired data augmentations. This complements theoretical work in ISSL [3–8], which analyze specific ISSL algorithms. Our work instead focuses on properties of representations that should serve as a goal for any ISSL algorithm. These ideal properties are: (i) desired predictors should be able to distinguish positive and negative examples from the representation; (ii) the dimensionality of the representation should be sufficiently large; (iii) augmented inputs should map to the same representations.

Previous ISSL methods can be seen as approximations of our ideal requirements. Using our requirements, we derive simple improvements to those approximations as well as new ISSL objectives. Our theory thus results in a unifying conceptual ISSL framework, with practical prescriptions including:

- improvements to existing methods, such as increasing the dimensionality of representations and using asymmetric projections heads, which lead to 5% point gains on TinyImageNet;
- a novel non-contrastive ISSL objective that outperforms all baselines, including SwAV+multicrops, by at least 1% point on linear classification of ImageNet;
- extensions of ISSL algorithms to learn representations that are better suited for non-linear probes.

2 Problem statement

2.1 Invariant Self-Supervised Learning

SSL learns an encoder ϕ that maps an input x from a finite space $\mathcal{X}$ (e.g., 256×256 images) into a representation $\phi(x) \in \mathbb{R}^d$. Given the encoder and a dataset $\mathcal{D}_t$ drawn from some task of interest $p_t(X, Y)$, we fit a classifier f from a desired family of probes $\mathcal{F}$. Families of probes are sets of k-ary classifiers for any $k \geq 2$ such as linear or MLP probes. For clarity, we consider linear probes $\mathcal{F}$ until Sec. 5.

Figure 1: ISSL setting. (Top) 1D inputs, partitioned into 3 equivalence classes (shapes), are encoded by ϕ into a 2D representation. (Bot. left) 3 $\sim$-invariant tasks, where labels are the colors. (Bot. right) examples of probes for 2 of the invariant tasks.

Supervision for ISSL comes from unlabeled data p_X and label-preserving augmentations. Augmentations are ways of sampling "positive" x, x^+ examples that are equivalent for downstream classification tasks. We formalize this using an equivalence relation $x \sim x^+$ that partitions the inputs $\mathcal{X}$ into equivalent classes $[x] \in \mathcal{X}/\sim$, and we consider the following downstream tasks $\mathcal{T}$ whose labelings are deterministic and constant within these classes (we allow stochastic labeling in appendices).

Definition 1. The $\sim$-*invariant tasks* $\mathcal{T}$, is the set of all input-label distributions $p_t(X, Y)$ such that the labeling $p_t(Y|X)$ is deterministic and invariant to $\sim$, i.e.,

$$\text{for all } p_t \in \mathcal{T}, x, x^+ \in \mathcal{X} : \qquad x \sim x^+ \implies \arg\max_{y \in \mathcal{Y}} p_t(y|x) = \arg\max_{y \in \mathcal{Y}} p_t(y|x^+). \quad (1)$$

As an illustration, consider the 3 classes (triangle, square, and circle) shown in Fig. 1. Then $\mathcal{T}$ consists of all tasks that are predictable from those shapes, e.g., recognizing shapes with vertices (blue/orange in Fig. 1) or recognizing the shape (yellow/red/purple in Fig. 1). Importantly, equivalence classes (here shapes) are different from—and essentially refinements of—downstream classes $\mathcal{Y}$ (here colors). Note that equivalence relations can model arbitrary transformations including cropping and adding Gaussian noise, which contrasts with typical restrictions to augmentations defined by group actions[9–11].

2.2 Idealized representations for ISSL

In this section, we define the optimal encoders, those that induce idealized representations that ISSL should be striving for. Although such encoders exist, they will likely not be learned in practice. Those idealized representations will nevertheless allow us to derive practical algorithms in Sec. 4.

The goal of ISSL is to learn representations from which (typically simple) probes $f \in \mathcal{F}$ classify well downstream tasks $p_t \in \mathcal{T}$, i.e., they achieve low 0-1 risk $R_t(\phi, f) := \mathbb{E}_{p_t(X,Y)}[\mathbb{1}[Y \neq f(\phi(X))]]$. Ideally, for any task of interest $p_t \in \mathcal{T}$ there will be a probe that can classify it perfectly.

Definition 2. An encoder ϕ is *population optimal* for $\mathcal{T}, \mathcal{F}$, denoted as $\phi \in \Phi_{\text{pop}}$, iff predictors realize the Bayes error on any invariant task, i.e., for all $p_t \in \mathcal{T}$ we have $\inf_{f \in \mathcal{F}} R_t(\phi, f) = 0$.

Population optimality ensures the existence of perfect downstream probes, which would be learned with infinite downstream data. In practice, however, predictors will be trained from finite datasets $\mathcal{D}_t$ of possibly small size n with empirical risk minimization. When n is small a fitted probe (ERM) $\hat{f} \in \widehat{\mathcal{F}}(\mathcal{D}_t, \phi) := \arg\min_{f \in \mathcal{F}} |\mathcal{D}_t|^{-1} \sum_{x,y \in \mathcal{D}_t} \mathbb{1}[y \neq f(\phi(x))]$ could be a terrible population predictor even when the underlying encoder is population optimal. Ideally, representations would thus also guarantee that *any* ERM performs as well as possible for *any* desired task and dataset size n. This suggests minimizing the following worst-case expected risk over tasks and ERMs.

$$W_n(\phi, \mathcal{F}, \mathcal{T}) := \sup_{t \in \mathcal{T}} \mathbb{E}_{\mathcal{D}_t \overset{\text{iid}}{\sim} p_t^n(X,Y)} \left[\sup_{\hat{f} \in \widehat{\mathcal{F}}(\mathcal{D}_t, \phi)} R_t(\phi, \hat{f}) \right]. \quad (2)$$

Definition 3. An encoder ϕ^* is *sample optimal* for $\mathcal{T}, \mathcal{F}$ iff if it is population optimal and minimizes the worst-case expected risk of ERMs for arbitrary sample sizes, i.e.,

$$\text{for all } n \geq 1 : \qquad \phi^* \in \arg\min_{\phi \in \Phi_{\text{pop}}} W_n(\phi, \mathcal{F}, \mathcal{T}). \quad (3)$$

(a) M not predictable (b) M non-lin. predictable (c) M linearly predictable (d) Tasks are not lin. pred. (e) Population optimal

Figure 2: Representations are *population optimal* for linear $\mathcal{F}$ iff their dimensionality is sufficiently large and equivalence classes $M(X)$ are linearly classifiable. The first 2 figures show representations from which $M(X)$ is (a) never or (b) only non-linearly classifiable. Although (c) ensures linear classification of $M(X)$, there exist invariant tasks, e.g. (d), that are not classifiable linearly. (e) Linear classifiability of $M(X)$ ensures population optimality iff the dimensionality is at least $|\mathcal{X}/\sim| - 1$.

3   Theoretical framework for linear probes $\mathcal{F}$

3.1   Characterizing optimal encoders for linear ISSL

In this section, we characterize all sample-optimal encoders (Def. 3), with simple properties that give insights into the form of the idealized representation. The key for our theory is that any $\sim$-invariant function g can be written as a composition between some function c_g and a *maximal invariant* M [12], i.e., $g = c_g \circ M$ where $M : \mathcal{X} \to \{1, \ldots, |\mathcal{X}/\sim|\}$ indexes the equivalence class:

$$\text{for any } x, x^+ \in \mathcal{X} : \quad x \sim x^+ \iff M(x) = M(x^+). \tag{4}$$

To build intuition for the final characterization, let us first discuss population optimal encoders (Def. 2) for unconstrained probes, then linear probes, and finally sample optimality (Def. 3).

Unconstrained probes. By Def. 1, labels of downstream tasks $p_t \in \mathcal{T}$ are $\sim$-invariant. Labels can thus be written as some function c_t of M, i.e., $\arg\max_y p_t(y|X) = c_t(M(X))$. This shows that $M(X)$ contains all and only information about desired tasks $\mathcal{T}$. If probes are unconstrained, an encoder is population optimal iff $M(X)$ is predictable/classifiable, i.e., there exist an h_M such that $M(X) = h_M(\phi(X))$. Indeed, this ensures that the probe defined by $c_t \circ h_M$ can classify the task p_t.

Linear probes $\mathcal{F}$. The problem with constrained probes is that they might not be able to use the information about desired tasks. In particular, the previous probe might not be linear $c_t \circ h_M \notin \mathcal{F}$. As an illustration, consider 4 equivalence classes: cats, dogs, oranges, and lemons. Fig. 2b shows a representation from which $M(X)$ is predictable but invariant tasks are not linearly classifiable. In fact, even when $M(X)$ is linearly predictable, i.e., $h_M \in \mathcal{F}$ as in Fig. 2c, downstream labels might not be, i.e., $c_t \circ h_M \notin \mathcal{F}$ as shown in Fig. 2d. By standard VC dimension arguments [13, 14], such binary task is linearly predictable if the representation's dimensionality d is one less than the number of equivalence classes $|\mathcal{X}/\sim| - 1$, as in Fig. 2e. Building on this intuition we prove that population optimal encoders are essentially[1] those that induce $d \geq |\mathcal{X}/\sim| - 1$ dimensional representations from which $M(X)$ is linearly predictable.

Sample optimality. Although population optimality ensures the existence of a perfect linear probe, ERM probes trained on finite samples might still be bad due to generalization issues (Fig. 3 left). Intuitively, one can remove such bad ERMs by mapping equivalent examples to the same representation, i.e., by using invariant encoders. Indeed, this ensures that ERMs that correctly predict one example in an equivalence class also correctly predict all the other (Fig. 3 right). We prove that such invariance of population optimal encoders is necessary and sufficient for sample optimality.

Figure 3: Invariance of population-optimal encoders is (a) necessary and (b) sufficient to ensure that there exists no bad ERM.

---

[1]The difference with learning theory is that instead of (binary) shatterability of all examples, we want k-ary shatterability of all equivalence classes from representations. The key is that both notions coincide for specific probes (e.g. linear) and invariant encoders, which are necessary for sample optimality.

115 Putting all together gives the following necessary and sufficient properties of sample-optimal encoders.

Theorem 1. An encoder ϕ^* is sample optimal for $\sim$-invariant tasks $\mathcal{T}$ and linear $\mathcal{F}$ if and only if

117 • **$\mathcal{F}$-predictability of M**: there exists a max. invariant M and an $f \in \mathcal{F}$ s.t. $M(X) = f(\phi^*(X))$;

118 • **Invariance**: ϕ^* is $\sim$-invariant, i.e., for any $x, x^+ \in \mathcal{X}$ we have $x \sim x^+ \implies \phi^*(x) = \phi^*(x^+)$;

119 • **Dimensionality**: the effective dimensionality of the representations is at least one less than the
120 number of equivalence classes, i.e., $\dim(\mathrm{span}(\{\phi^*(x)|x \in \mathcal{X}\})) \geq |\mathcal{X}/\sim| - 1$.

3.2 The impact of augmentations on downstream performance

122 Let us compute the worst-case excess risk $\mathrm{W}_n(\phi, \mathcal{F}, \mathcal{T})$ of sample optimal encoders and show its
123 dependence on the invariance structure. The key is that since sample optimal encoders are invariant
124 (Theorem 1), ERMs only need to be trained on a single example per equivalence class to perfectly clas-
125 sify all other examples from that class. The risk then depends on the proportion of equivalence classes
126 seen when training the probe, which can be computed in closed form as a function of the number of
127 equivalence classes $|\mathcal{X}/\sim|$ and downstream samples n. For other similar results refer to Appx. B.3.

Proposition 2. The worst expected risk of a sample optimal ϕ^* for $\sim$-invariant tasks $\mathcal{T}$ and any $\mathcal{F}$ is

$$\mathrm{W}_n(\phi^*, \mathcal{F}, \mathcal{T}) = \left(1 - \frac{1}{|\mathcal{X}/\sim|}\right)^n \tag{5}$$

129 Prop. 2 shows that fewer equivalence classes, i.e., coarser $\sim$, leads to better downstream sample
130 efficiency. Of course, the convergence rate will be slower for practical encoders than for sample
131 optimal ones. The result nevertheless suggests that good augmentations should be as strong as
132 possible (induce coarser $\sim$), while being label-preserving. An example of coarse augmentations
133 are those in CLIP, [15] which map many images to similar sentences.

4 Practical ISSL objectives for linear probes $\mathcal{F}$

135 The main remaining question is how to practically enforce requirements from Theorem 1. In this
136 section, we derive simple objectives that learn optimal encoders in *ideal settings* (infinite data, perfect
137 optimizers, universal approximators). In the process, we shed light on why previously proposed ISSL
138 methods work, and how to improve them in practice.

139 Our key insight is that we can learn sample-optimal encoders by jointly
140 training the encoder and a logistic regression predicting $M(X)$ from the
141 representations. Indeed, the representations that arise from this joint pro-
142 cedure are characterized by three properties, each of which implies one of
143 the requirements from Theorem 1 ($\mathcal{F}$-predictability, invariance, effective
144 dimensionality). First, the representations will allow linear predictability of
145 $M(X)$ due to the linearity of logistic regression. Second, the variance of
146 same-class representations will collapse. Indeed, higher variance increases
147 log loss due to Jensen's inequality. Finally, the angle between representations
148 of different classes (and by extension the effective dimensionality) will be
149 maximal due to the symmetry of log loss. More formally, the joint procedure
150 will learn representations that form an simplex equiangular tight frame (sETF)
151 as illustrated in Fig. 4 and discussed in the neural collapse literature [16–21].

Figure 4: sETF are idealized representations that collapse same-class examples and maximize the angle across classes.

152 The previous discussion suggests optimizing the following *$\sim$-ISSL log loss*, which simply
153 corresponds to multinomial logistic regression of $M(X)$

$$\mathcal{L}_I(\phi; p_x) := \inf_{w \in \mathcal{W}_1} \mathbb{E}_{p_X}\left[-\log \frac{\exp\left(w(M(X))^\top \phi(X)\right)}{\sum_{m'=1}^{|\mathcal{X}/\sim|} \exp(w(m')^\top \phi(X))}\right], \tag{6}$$

154 where w maps classes to weights, e.g., by indexing a weight matrix. Following previous work on
155 neural collapse, we assume for this section that classes are equiprobable $p_x([x]) = 1/|\mathcal{X}/\sim|$, and that
156 classifier's weights and representations are unit-normalized, i.e., $w \in \mathcal{W}_1 := \{1, \ldots, |\mathcal{X}/\sim|\} \to \mathcal{S}$
157 and $\phi \in \Phi_1 := \mathcal{X} \to \mathcal{S}$ where $\mathcal{S}$ denotes the $(d-1)$-sphere (for relaxations see e.g. [22, 23]). We then
158 have that any high dimension encoder trained to minimize the ISSL log loss will be sample-optimal.

Proposition 3. Let p_X be a distribution with support $\mathcal{X}$ and equiprobable equivalence classes $p_X([x]) = 1/|\mathcal{X}/\sim|$, $\forall x \in \mathcal{X}$. If $d \geq |\mathcal{X}/\sim| - 1$ then any unit-normalized encoder that minimizes the $\sim$-ISSL log loss $\phi^* \in \arg\min_{\phi \in \Phi_1} \mathcal{L}_I(\phi; p_X)$ is sample-optimal for $\sim$-invariant tasks and linear $\mathcal{F}$.

Prop. 3 shows that the ISSL log loss is a perfect pretext task in ideal settings. This suggests optimizing the ISSL log loss in practice and provides a formal relation between self-supervised and classical supervised learning. The challenge is that we typically neither have access to the maximal invariant $M(X)$ nor the number of equivalence classes $|\mathcal{X}/\sim|$ required to compute the denominator of Eq. (6). Instead, knowledge about the equivalence structure comes from data augmentations $\mathrm{A}(\tilde{X}|X)$ from which we can sample examples that are equivalent to the input $\tilde{X} \sim X$.

Having established our framework, we can re-interpret previous ISSL methods as practical approximations of the ISSL log loss using data augmentations (e.g., SimCLR, SwAV, DINO [24], [2], SimSiam [25], MOCO [26]). These approximations are nevertheless suboptimal, in that none of them learn sample- (nor population-) optimal encoders in idealized settings. By directly deriving the ISSL methods from Eq. (6), we will prescribe improvements to previous ISSL objectives that ensure that sample-optimal encoders are learned in idealized settings. We broadly categorize previous methods into two families depending on whether they select the desired number of equivalence classes $|\mathcal{X}/\sim|$ or whether it is implicitly inferred from the augmentations. We call these approaches distillation and contrastive ISSL respectively. For derivations and theoretical claims see Appx. C.

4.1 Contrastive ISSL (CISSL)

Inspired by previous contrastive objectives [1, 27–29], we show how to optimize the ISSL log loss using data augmentations and negative samples to remove the need of knowing $M(X)$ and the number of classes $|\mathcal{X}/\sim|$. The resulting objective, dubbed *CISSL*, corresponds to SimCLR using only a projection head g on one branch. See Fig. 5. This asymmetry is necessary to learn population optimal encoders for linear $\mathcal{F}$.

CISSL bypasses the need for $M(X)$ by noticing that it only appears in the ISSL log loss through the class weights $w(M(X))$. CISSL thus learns a function g mapping equivalent (augmented) inputs $\tilde{X}$ to $w(M(\tilde{X}))$. Such mapping exists since M is invariant, e.g., $g := w \circ M$.

(a) SimCLR   (b) CISSL

Figure 5: CISSL corresponds to SimCLR with a single (asymmetric) projection head $g'(z^+)^\top z$. This ensures linear predictability of downstream tasks, which will be computed by $W_t^\top z$.

When augmentations satisfy the Markov Chain $\tilde{X} - M(X) - X$, we show that we can replace the class weights $w(M(X))$ in the ISSL loss by $g(\tilde{X})$, where g is optimized over. Intuitively, this is because predicting $\tilde{X}$ contains only information about $M(X)$ due to the data processing inequality.

The only remaining challenge is computing the denominator of Eq. (6) without summing over the unknown classes $\mathcal{X}/\sim$. To do so we use ranking conditional noise contrastive estimation (NCE; [30–32]). NCE replaces classification of equivalence classes by classification of positives in a batch $\tilde{\mathbf{X}} := \{\tilde{X}^+, \tilde{X}_1^-, \ldots, \tilde{X}_k^-\}$ where the positive $\tilde{X}^+$ is sampled from the conditional $\mathrm{A}(\tilde{X} \mid X)$, while the k negatives $\tilde{X}_i^-$ come from the marginal $\mathrm{A}(\tilde{X}) = \mathbb{E}_{p_X}[\mathrm{A}(\tilde{X}|X)]$. Using Monte Carlo (MC) estimates with an unlabeled dataset $\mathcal{D} \overset{\text{i.i.d.}}{\sim} p_X$ we get our final empirical CISSL objective

$$\hat{\mathcal{L}}_C(\phi; \mathcal{D}) := \inf_{g \in \mathcal{S}^{\mathcal{X}}} \sum_{x \in \mathcal{D}} \mathbb{E}_{p(\tilde{\mathbf{X}}|x, \mathcal{D})} \left[-\log \frac{\exp g(\tilde{X}^+)^\top \phi(x)}{\sum_{\tilde{X}' \in \tilde{\mathbf{X}}} \exp g(\tilde{X}')^\top \phi(x)} \right]. \tag{7}$$

By Prop. 3 and NCE's consistency [32], encoders trained with CISSL $\phi^* \in \arg\min_{\phi \in \Phi_1} \hat{\mathcal{L}}_C(\phi; \mathcal{D})$ are sample optimal for linear $\mathcal{F}$ in our ideal setting assumption ($|\mathcal{D}| \to \infty$ and unconstrained g) and when $\tilde{X} - M(X) - X$ forms a Markov Chain. While consistency (and thus optimality) holds for $k \geq 1$, more negatives k improves statistical efficiency [32].

Typically $\tilde{X}, X$ take value in the same space (e.g. images). If so, we can tie parameters by encoding $\tilde{X}$, i.e., we can replace g by $g' \circ \phi$ where $g' : \mathbb{R}^d \to \mathcal{S}$ is called a projection head. The logits

inside of Eq. (7) are then computed by $g'(\phi(\tilde{X}))^\top \phi(x)$ as shown in Fig. 5b. This is very similar to SimCLR's objective $g'(\phi(\tilde{X}))^\top g'(\phi(x))$ shown in Fig. 5a. The difference is that, by projecting the current representation, *SimCLR learns encoders that are not even population optimal for linear $\mathcal{F}$*. In contrast, CISSL learns sample optimal encoders in ideal settings. Intuitively, this is because CISSL trains the representations in the same way as they will be used in downstream tasks p_t. Indeed, representations $\phi(X)$ will be dotted with the downstream tasks' weights $W_t^\top \phi(x)$ to compute logits. In ISSL, representations $\phi(x)$—rather than their projections $g'(\phi(x))$—should thus be used in the inner product with ISSL weights $w(M(X)) = g'(\phi(\tilde{X}))$ to compute logits. CISSL thus derives, from first principles, an asymmetric use of projection heads.

4.2 Distillation ISSL (DISSL)

In practice, CISSL requires contrasting many negatives. To avoid contrastive estimation, we can directly approximate $M(X)$—instead of the weight $w(M(X))$—so that the denominator of Eq. (6) can be computed exactly. The resulting method, dubbed *DISSL* (Fig. 6), is a simpler and theoretically-grounded version of non-contrastive losses (e.g. SwAV, DINO, SimSiam). The challenge and main difference between each of those methods is how they estimate $M(X)$.

As $M(X)$ is discrete, we use a conditional categorical distribution $q(\hat{M} \mid X)$ to estimate $M(X)$ with a random variable $\hat{M}$. Replacing terms in the ISSL log loss then gives the following objective. Differences with Eq. (6) are in red.

Figure 6: DISSL. The teacher (top branch) is trained with the top loss to ensure $\hat{M}$ is a maximal invariant r.v. The student (bottom branch) distills the teacher by predicting $\hat{M}$.

$$\inf_{w \in \mathcal{W}_1} \mathbb{E}_{p_X q(\hat{M} \mid X)} \left[-\log s_{\phi,w}(\hat{M} \mid X) \right], \quad s_{\phi,w}(m \mid x) = \frac{\exp(w(m)^\top \phi(x))}{\sum_{m=1}^{C} \exp(w(m)^\top \phi(x))}, \quad (8)$$

To highlight similarities with previous methods [2, 24, 33] we refer to Eq. (8) as *distilling* the *teacher* $q(\hat{M} \mid X)$ into the student $s_{\phi,w}(\hat{M} \mid X)$. Importantly, Eq. (8) is exactly the ISSL log loss if the teacher outputs a maximal invariant random variable, i.e., $\hat{M} = M(X)$. By Prop. 3, distillation thus learns sample-optimal encoders when the teacher takes at least $C \geq |\mathcal{X}/\sim|$ values and satisfies the following requirements, which correspond to the definition of maximal invariance (Eq. (4)).

Deterministic the teacher is a deterministic distribution $\max_{m \in \{1,...,C\}} q(m \mid X) = 1$;
Invariant the teacher maps positives together $x \sim x^+ \implies q(\hat{M} \mid x) = q(\hat{M} \mid x)$;
Maximal the teacher maps negatives separately $x \not\sim x^- \implies q(\hat{M} \mid x) \neq q(\hat{M} \mid x^-)$.

There are many ways of enforcing these desired requirements for the teacher. In the following, we use information-theoretic quantities (entropies and KL divergences) as those are interpretable and can be computed in closed form for categorical distributions such as our teacher and student.

Determinism and Invariance. Both properties hold if and only if for any equivalent example $x \sim x^+$ the cross-entropy of the teacher's outputs is minimized $\mathbb{E}_{q(\hat{M} \mid x)}[-\log q(\hat{M} \mid x^+)] = 0$. Indeed, zero cross-entropy simultaneously minimizes the conditional entropy $\mathbb{H}[\hat{M} \mid x] = 0$ (equivalent to determinism) and the KL divergence $\mathbb{D}_{\mathrm{KL}}[q(\hat{M} \mid x) \| q(\hat{M} \mid x^+)] = 0$ (equivalent to invariance).

Maximality. A natural way of enforcing maximality is to train the teacher to predict differently negatives $x \not\sim x^-$. This requires accessing batches of negatives, which we wanted to avoid with DISSL. Instead, assume that we know (or have a prior on) the true distribution of equivalence classes $p(M(X))$. Then a deterministic and invariant teacher is maximal if and only if the KL divergence between its marginal $q(\hat{M}) = \mathbb{E}_{p_X}[q(\hat{M} \mid X)]$ and the true one is minimized $\mathbb{D}_{\mathrm{KL}}[q(\hat{M}) \| p(M(X))] = 0$. We can thus avoid contrasting negatives using (a prior on) the distribution of equivalence classes.

Using a Lagrangian relaxation (with multipliers λ, β) of the teacher's constraints with an MC estimate of the distillation loss (Eq. (8)) we get the following empirical DISSL loss $\hat{\mathcal{L}}_D(\phi; \mathcal{D}) :=$

$$\inf_{q,w} \lambda \underbrace{\mathbb{D}_{\mathrm{KL}}\left[q(\hat{M}) \middle\| p(M(X))\right]}_{\text{Maximality}} - \sum_{x \in \mathcal{D}} \mathbb{E}_{A(\tilde{X}|x)q(\hat{M} \mid x)} \left[\underbrace{\beta \log q(\hat{M} \mid \tilde{X})}_{\text{Det. and Inv.}} + \underbrace{\log s_{\phi,w}(\hat{M} \mid x)}_{\text{Distillation}} \right]. \quad (9)$$

In ideal settings ($|\mathcal{D}| \to \infty$, unconstrained q, known $p(M(X))$) and for $\lambda, \beta \to \infty$ we show that encoders trained with DISSL are sample optimal for linear $\mathcal{F}$ and tasks that are invariant to the equivalences defined by the connected components of the augmentation graph [8]. If the marginal is unknown, we follow the MaxEnt [34] and use a uniform prior $p(M(X)) = \mathrm{Unif}(1, C)$. The KL in Eq. (9) then corresponds to maximizing entropy $\mathbb{H}[\hat{M}]$.

As with CISSL, when $\tilde{X}, X$ are in the same space, we tie parameters by encoding $\tilde{X}$ before the teacher, i.e., $q(\hat{M} \mid X) = \mathrm{softmax}(g'(\phi(X)))$ for a head $g' : \mathbb{R}^d \to \mathbb{R}^C$. Algorithm 1 and Fig. 6 illustrate DISSL with a uniform prior, and a marginal $q(\hat{M})$ estimated from batches.

Algorithm 1 Batched DISSL

Require: head g, weights W, enc. ϕ, batched inputs X, aug. A, hyp. β, λ.
1: $\tilde{X}, \tilde{X}^+ \leftarrow \mathrm{sample}(\mathrm{A}(\tilde{X} \mid X), 2)$
2: $q(\hat{M} \mid \tilde{X}) = \mathrm{softmax}(g(\phi(\tilde{X}))$
3: $q(\hat{M} \mid \tilde{X}^+) = \mathrm{softmax}(g(\phi(\tilde{X}^+))$
4: $s(\hat{M} \mid \tilde{X}^+) = \mathrm{softmax}(W^T \phi(\tilde{X}^+))$
5: $q(M) = \mathrm{batch\_avg}(q(M \mid \tilde{X}))$
6: $\mathrm{mxml} = \sum_m q(m) \log q(m)$
7: $\mathrm{det\_inv} = \sum_m q(m|\tilde{X}) \log q(m|\tilde{X}^+)$
8: $\mathrm{dstl} = \sum_m q(m|\tilde{X}) \log s(m|\tilde{X}^+)$
9: **return** $\lambda * \mathrm{mxml} - \beta * \mathrm{det\_inv} - \mathrm{dstl}$

DISSL is one of the many distillation methods that can be derived from our teacher's requirements. These requirements generally lead to a framework for deriving, comparing, and analyzing distillation objectives. In Appx. E we provide a taxonomy of 12 previous SSL methods from this perspective— none of which recover sample optimal encoders. Typically, previous methods favor: (i) determinism by "sharpening" the teacher $q(\hat{M} \mid X)$ with a temperature parameter; (ii) invariance by making the teacher's and student's similar for equivalent inputs $q(\hat{M} \mid x^+) \approx s_{\phi,w}(\hat{M} \mid x)$; (iii) maximality through optimization tricks (e.g. stop gradients or momentum encoder) to avoid a constant teacher, i.e., referred to as "collapsing" [25, 26, 35, 36]. Note that avoiding constant collapse $q(\hat{M} \mid x') = q(\hat{M} \mid x)$ for any $x, x' \in \mathcal{X}$ is insufficient, e.g., mapping half the inputs to a constant is also undesirable. Maximality formalizes the desired requirement: non-equivalent examples should not be mapped together.

5 ISSL for non-linear predictors $\mathcal{F}^+$

Linear probes $\mathcal{F}$ are standard for evaluating representations [28, 37, 38]. However, if the goal is to maximize performance it is natural to consider non-linear predictors $\mathcal{F}^+$. The question then becomes how should we learn optimal representations for any $\mathcal{F}^+$? In Appx. B.5 we extend our framework to certain non-linear probes, such as neural networks, that separate into a hidden component h and linear layer, i.e., $f(\cdot) = W^T h(\cdot)$. We informally summarize the theory and implications below.

Theory. There are two main differences between our characterization of optimal encoders for linear and non-linear probes. First, encoders should ensure predictability of $M(X)$ for the desired $\mathcal{F}^+$. Second, the dimensionality requirement decreases with the complexity of $\mathcal{F}^+$, e.g., for universal $\mathcal{F}^+$ it is $d \geq 1$. More generally, the necessary dimension and the sufficient dimension for optimality do not coincide and respectively depend on the predictors' VC dimension [13] and memory capacity [39].

Implications. Both theoretical differences lead to direct implications for non-linear ISSL. First, we can decrease the dimensionality when performing ISSL for more complex non-linear probes. Second, we should use a projection head that ensures the predictability of the maximal invariant with using the desired probes $\mathcal{F}^+$. Similarly to the linear case, we should match how the representation is used in the ISSL log loss and downstream tasks. We should thus apply the non-linear predictor h in a similar asymmetric way. For CISSL we should thus compute the right hand side of Fig. 5 as $g(\phi(\tilde{X}))h(\phi(x))$. For DISSL, we should change the line 4 of Algorithm 1 to $s(\hat{M}|\tilde{X}^+) = \mathrm{softmax}(W^T h(\phi(\tilde{X}^+)))$.

6 Summary of insights and relation to previous work

Let summarize our framework's main insights and their relation to previous work. Details in Appx. E.

DISSL. DISSL is related to DINO and SwAV, as each method distill a categorical teacher but differ in how they enforce its maximality. DINO does it implicitly through optimization tricks, e.g., the teacher is an exponential moving average of the student and uses stop-gradients. SwAV enforces maximality explicitly by equiprobably clustering a queue of examples using Sinkhorn's algorithm [40] and stop-gradients. DISSL is also explicit but uses a simpler and more efficient max entropy regularization, which does not require queues or stop-gradients. Furthermore, both SwAV's and DINO's student use non-linear projection head, which do not ensure good linear probing (see Sec. 4.1).

Dimensionality. Theorem 1 suggests increasing the representation's dimensionality to ensure probes can classify all invariant tasks. To our knowledge increasing the dimensionality of SSL representations has never been investigated (note: this is different from the projection's dimensionality in [1, 41]). The closest empirical work concerns the benefits of avoiding dimensionality collapse [42, 43]. In the theoretical literature, the importance of large dimension has been indirectly suggested by the choice of assumptions (e.g. [8, 44]) but the exact necessary and sufficient dimension is novel.

Augmentations. Prior work have suggested that good augmentations remove nuisance information but preserve labels [12, 45–49]. Prop. 2 gives a new perspective on the benefits of such augmentations, by proving the exact relation between optimal sample efficiency and the number of equivalences.

Projection heads. Secs. 4 and 5 theoretically show how to chose projection heads, namely, one should be as large as possible while the other should have the architecture of downstream probes. To our knowledge, we are the first to relate the probing family and the projection head. Furthermore, our theory is the first to suggest why projection heads improve performances (e.g. [1, 25, 50]) in general SSL (note: this is unrelated to adding heads to avoid collapsing in non-contrastive learning [36, 51]).

Theoretical SSL. Theorem 1 characterizes optimal encoders for ISSL. This contrasts with standard theoretical work in SSL that typically analyze specific SSL algorithms [3, 5, 6, 8, 52–54] and / or focus on upper-bounding downstream performance [4]. The advantage of our theory is that it provides a simple unifying framework from which we can derive a variety of SSL methods and actionable insights. The downside is that by distancing itself from specific algorithms, the framework does not provide guarantees outside of ideal settings. We thus see our theory as complementary to prior work.

7 Experiments

The experiments in the main paper focus on evaluating our frameworks' prescriptive implications. For more results see Appx. H. For experimental details see Appx. G. Code is at `anonymous`.

In summary, our experimental results show that: (i) CISSL/DISSL outperform their respective baselines on standard benchmarks as suggested by Sec. 4; (ii) increasing dimensionality improves downstream probing as suggested by Theorem 1; (iii) coarser augmentations improve sample efficiency as in Prop. 2; (iv) smaller ISSL log loss improves downstream performance as suggested by Prop. 3; (v) projection heads should be related to probing family as discussed in Secs. 4 and 5.

For the first experiments, we use TinyImageNet [55], 300 pretraining epochs, and ResNet18s. Note that for ResNet18s the dimensionality of the representation (`res5avg`) is $d = 512$. For contrastive baselines we use SimCLR. For distilling baselines we use the best over DINO, SwAV, SimSiam.

CISSL/DISSL improve linear probing
Table 1 shows that each of our prescriptions significantly improve distillation and contrastive ISSL. "Ours" vs "Baselines" shows that removing one the non-linear projection heads (as in Fig. 5) gives a 1% gain in contrastive learning, while our new distillation objective achieves 3% gains compared to the best distillation baseline. "dim. ↑" shows that increasing the dimensionality of the representation from 512 to 2048 further improves linear probing by 1–2%. Finally, "coarse aug." shows that coarser

Table 1: Our prescriptive implications improves ISSL for linear $\mathcal{F}$ on TinyImageNet. Models are ResNet18s trained for 300 epochs. 3 seeds.

	CONTR.	DISTIL.
BASE. (SIMCLR | DINO)	$44.6_{\pm 0.1}$	$42.4_{\pm 0.0}$
OURS (CISSL | DISSL)	$45.8_{\pm 0.3}$	$45.5_{\pm 0.0}$
+ DIM. ↑	$47.5_{\pm 0.1}$	$46.9_{\pm 0.1}$
+ COARSE AUG.	$50.1_{\pm 0.1}$	$50.7_{\pm 0.2}$

augmentations (we double the strength of standard TinyImageNet augmentations [35] and add blurring), we further improve performance by 3–4%. All together our framework's insights significantly improves linear probing accuracy: 5% gains for contrastive learning and 8% for distillation.

Coarse augmentations improve sample efficiency. Prop. 2 suggests that coarser label-preserving augmentations improve downstream sample efficiency. We test that by introducing a hyperparameter α that controls the strength of standard augmentations. Specifically, α increases the probability of grayscaling (p=0.1α), each color jittering parameter (`brightness`=0.4α, `contrast`=0.1α, `saturation`=0.2α, `hue`=0.1α), and the cropping interval (`scale`=$[0.1/\alpha, 1]$). Fig. 7a shows four different DISSL encoders $\alpha \in \{0.25, 0.5, 1, 2\}$ evaluated at varying downstream samples sizes. As suggested by the theory, stronger label-preserving augmentations improve sample efficiency.

| | (a) Augmentations | (b) ISSL log loss | (c) Dimensionality |

Figure 7: As suggested by our theory: (a) coarsening augmentations improves sample efficiency; (b) decreasing ISSL log loss improves representations, which can be achieved by longer training; and (c) increasing the representation's dimensionality improves performance for linear $\mathcal{F}$ but less so for MLPs $\mathcal{F}^+$. Y-axis is TinyImageNet probing performance. Each point is obtained by sweeping: (a) augmentation strengths for DISSL and downstream sample sizes; (b) CISSL's optimization hyperparameters including epochs; and (c) the dimensionality of CISSL's representations.

ISSL log loss correlates with performance. Previous work [44] suggested that contrastive losses may not predict downstream performance. On the contrary, Prop. 3 shows that minimal ISSL log loss implies the optimality of encoders if d is large. This suggests that, for fixed augmentations, ISSL log loss is highly related to performance. To test this relation, we trained 80 CISSL models with various hyperparameters (e.g. optimizer, projection head, learning rate) while fixing augmentations and negatives k. Fig. 7b shows that the test ISSL loss and downstream accuracy are highly correlated (gray points). In Appx. H.3 we show similar correlation with the training ISSL loss.

Longer training decreases ISSL log loss. An efficient way of decreasing ISSL log loss is longer training (blue points in Fig. 7b only vary the number ISSL epochs). Prop. 3 thus provides an explanation of the well-known performance gains of longer ISSL training [1, 56]. Namely, longer training decreases ISSL log loss, which results in representations that are closer to optimality.

Increasing dimensionality improves performance. Theorem 1 shows that linear ISSL requires a dimensionality of $d = |\mathcal{X}/\sim| - 1$ to ensure predictability of all invariant tasks. In practice, the number of equivalence classes is most likely very large. Although such dimensionality is impractical, it does suggest increasing the dimensionality beyond the $d = 512$ of ResNet18s. To test this, we train CISSL with a larger dimensionality by increasing the output channels before the average pooling layer. To keep the number of parameters comparable, we use bottlenecks or low-rank linear layers before and after the representations layer as detailed in Appx. G. Fig. 7c shows that increasing the dimensionality has a significant effect on downstream performance for linear $\mathcal{F}$ (blue). In Appx. H.3 we show that, contrary to popular beliefs, the gains when going from ResNet18s to ResNet50s are due to an increase in dimensionality (512 to 2048) rather than the number of parameters (11M to 23M).

Previous results concern linear $\mathcal{F}$ which are standard for ISSL evaluation. In practice, one would likely use more complex probes $\mathcal{F}^+$ to improve results. In Sec. 5 we discussed how to perform ISSL for $\mathcal{F}^+$. In the following, we evaluate ISSL for MLPs $\mathcal{F}^+$ with two hidden layers of 2048 units.

Performing ISSL for MLPs $\mathcal{F}^+$. Table 2 shows that MLP probes ("$\mathcal{F}_{\text{EVAL}}$: MLP") outperforms linear ones ("$\mathcal{F}_{\text{EVAL}}$: lin.") even in few-shot regimes (10 shot). Furthermore, when predicting with MLP probes it is desirable to train the ISSL encoders for MLPs ("$\mathcal{F}_{\text{ISSL}}$: MLP") instead of linear probes (row 4 vs 3). As discussed in Sec. 5, the only difference between DISSL for different probes is that the student's representation is projected using a head with the same architecture as downstream probes.

Table 2: MLP probes outperform linear ones on TinyImageNet when using MLP ISSL.

	$\mathcal{F}_{\text{ISSL}}$	$\mathcal{F}_{\text{EVAL}}$	ALL	10 SHOT
DINO	-	MLP	$43.0_{\pm 0.3}$	$19.6_{\pm 0.2}$
DISSL	LIN.	LIN.	$45.5_{\pm 0.0}$	$25.3_{\pm 0.0}$
	LIN.	MLP	$46.1_{\pm 0.1}$	$25.6_{\pm 0.0}$
	MLP	MLP	$47.5_{\pm 0.2}$	$26.1_{\pm 0.1}$

Dimensionality affects less MLPs $\mathcal{F}^+$. In Sec. 5 we saw that the optimal dimensionality d decreases for more complex predictors $\mathcal{F}^+$. Fig. 7c indeed shows that larger dimensions result in smaller gains when the training and evaluation probe are MLPs $\mathcal{F}^+$ (orange) compared to linear ones $\mathcal{F}$ (blue).

Table 3: Our models outperform baselines on ImageNet. ResNet50 encoders are trained using 100 epochs, 3072 batch size, standard augmentations. Our models increase dimensionality to 8192.

	SIMCLR	SWAV	BARLOW T.	**CISSL**	**DISSL**
100 EPOCHS	65.3	64.3	66.1	67.2	**67.4**

Given encouraging TinyImageNet results, we investigated whether our objectives can be used as a replacement for standard objectives on ImageNet [57]. We specifically replaced SimCLR by our CISSL and SwAV by our DISSL in VISSL's codebase [58] without any tuning. Due to computational constraints we mostly consider 100 epochs of pretraining and do not use augmentations to train the probes.

Our models outperform baselines on ImageNet. Table 3 shows that CISSL's small modifications of SimCLR lead to important gains (1.8%). Both CISSL and our novel DISSL objective significantly outperform all the considered baselines including SwAV by a 3% when using standard augmentations.

Given encouraging results on standard augmentations, we compared the performance of DISSL with a near SOTA model: SwAV trained with their special multi-crop augmentations.

DISSL is competitive with SOTA models at scale. Table 4 shows that DISSL outperforms SwAV. Combined with Table 3 this suggests that DISSL works well in different settings. This is encouraging given the lack of tuning and the simplicity of DISSL's out-of-the-box objective. In contrast, SwAV requires stopping gradients, storing a queue, running Sinkhorn's algorithm, and freezing certain parameters during initial training steps.

Table 4: Our DISSL outperforms SwAV using $2 \times 160 + 4 \times 96$ multi-crops on ImageNet. 3072 batch size, ResNet50.

	100 EPOCHS	400 EPOCHS
SWAV	68.5	72.9
DISSL	**69.5**	**73.3**

Table 5: DISSL is competitive on transfer tasks. Same models as in Table 4 evaluated by linear probes.

	FOOD	CIFAR10	CIFAR100	CARS	AIRCRAFTS	DTD	PETS	CATLECH	FLOWERS
SWAV	75.5	92.0	76.2	58.2	**49.1**	72.6	86.9	**92.0**	94.7
DISSL	**77.9**	**93.6**	**77.6**	**62.2**	48.1	**73.9**	**88.0**	91.5	**95.3**

DISSL is competitive on transfer. Table 5 shows that DISSL generally outperforms SwAV on the standard transfer benchmarks from [59] even though our theory does not discuss transfer.

8 Summary and Outlook

We presented a simple conceptual framework to understand, compare and improve ISSL methods. Inspired by recent work on supervised [60] and robust [61] learning, we derived such framework by studying algorithmic-agnostic goals for ISSL. In particular, Theorem 1 provides the minimal and sufficient requirements for optimal encoders, and Prop. 2 gives the resulting probing risk as a function of pretraining augmentations. On the algorithmic side, Sec. 4 uses our framework to derive simpler and theoretically-motivated variants of prior SSL objectives. Altogether our framework provides actionable insights for ISSL such as how to choose: the SSL algorithm, the dimensionality of the representations, the projection heads, and the augmentations. On the empirical side, Sec. 7 shows that each of our prescriptions leads to significant gains. As a result, our final SSL algorithms outperform strong baselines such as SwAV+multicrop trained on linear probing of ImageNet.

There are many limitations that should be addressed for a more realistic prescriptive framework for ISSL. See Appx. F for more details. First, our theory is binary, e.g., augmentations are either label preserving or not, and encoders are optimal or not. Although our framework likely captures the right intuition, nuance would be more realistic. Second, we consider unconstrained encoders ϕ, dimensionality, and infinite unlabeled data. Such assumptions follow recent empirical trends in increasing data and models [62, 63], but it means that our framework currently cannot improve the computational or data efficiency of the pretraining phase. Finally, we consider all invariant tasks $\mathcal{T}$ even though only a subset of those are meaningful. Optimal representations for this subset will be different, and defining this subset likely requires considering inductive biases of encoders [44]. Despite those limitations, we showed that our framework's insights lead to substantial improvements in ISSL performance.

References

[1] T. Chen, S. Kornblith, M. Norouzi, and G. E. Hinton, "A Simple Framework for Contrastive Learning of Visual Representations," in *Proceedings of the 37th International Conference on Machine Learning, ICML 2020, 13-18 July 2020, Virtual Event*, ser. Proceedings of Machine Learning Research, vol. 119. PMLR, 2020, pp. 1597–1607. [Online]. Available: http://proceedings.mlr.press/v119/chen20j.html (Cited on 1, 5, 8, 9)

[2] M. Caron, I. Misra, J. Mairal, P. Goyal, P. Bojanowski, and A. Joulin, "Unsupervised Learning of Visual Features by Contrasting Cluster Assignments," *arXiv:2006.09882 [cs]*, Oct. 2020, arXiv: 2006.09882. [Online]. Available: http://arxiv.org/abs/2006.09882 (Cited on 1, 5, 6)

[3] N. Saunshi, O. Plevrakis, S. Arora, M. Khodak, and H. Khandeparkar, "A Theoretical Analysis of Contrastive Unsupervised Representation Learning," in *Proceedings of the 36th International Conference on Machine Learning, ICML 2019, 9-15 June 2019, Long Beach, California, USA*, ser. Proceedings of Machine Learning Research, K. Chaudhuri and R. Salakhutdinov, Eds., vol. 97. PMLR, 2019, pp. 5628–5637. [Online]. Available: http://proceedings.mlr.press/v97/saunshi19a.html (Cited on 1, 8)

[4] Y. Bansal, G. Kaplun, and B. Barak, "For self-supervised learning, Rationality implies generalization, provably," *arXiv:2010.08508 [cs, stat]*, Oct. 2020, arXiv: 2010.08508. [Online]. Available: http://arxiv.org/abs/2010.08508 (Cited on 8)

[5] J. D. Lee, Q. Lei, N. Saunshi, and J. Zhuo, "Predicting What You Already Know Helps: Provable Self-Supervised Learning," *arXiv:2008.01064 [cs, stat]*, Aug. 2020, arXiv: 2008.01064. [Online]. Available: http://arxiv.org/abs/2008.01064 (Cited on 8)

[6] C. Tosh, A. Krishnamurthy, and D. Hsu, "Contrastive learning, multi-view redundancy, and linear models," in *Proceedings of the 32nd International Conference on Algorithmic Learning Theory*. PMLR, Mar. 2021, pp. 1179–1206, iSSN: 2640-3498. [Online]. Available: https://proceedings.mlr.press/v132/tosh21a.html (Cited on 8)

[7] Z. Wen and Y. Li, "Toward Understanding the Feature Learning Process of Self-supervised Contrastive Learning," *arXiv:2105.15134 [cs, stat]*, May 2021, arXiv: 2105.15134. [Online]. Available: http://arxiv.org/abs/2105.15134

[8] J. Z. HaoChen, C. Wei, A. Gaidon, and T. Ma, "Provable Guarantees for Self-Supervised Deep Learning with Spectral Contrastive Loss," *arXiv:2106.04156 [cs, stat]*, Jun. 2021, arXiv: 2106.04156. [Online]. Available: http://arxiv.org/abs/2106.04156 (Cited on 1, 7, 8)

[9] T. Leen, "From Data Distributions to Regularization in Invariant Learning," in *Advances in Neural Information Processing Systems*, vol. 7. MIT Press, 1994. [Online]. Available: https://proceedings.neurips.cc/paper/1994/hash/7fa732b517cbed14a48843d74526c11a-Abstract.html (Cited on 2)

[10] S. Chen, E. Dobriban, and J. H. Lee, "A Group-Theoretic Framework for Data Augmentation," *arXiv:1907.10905 [cs, math, stat]*, Feb. 2020, arXiv: 1907.10905. [Online]. Available: http://arxiv.org/abs/1907.10905

[11] C. Lyle, M. v. d. Wilk, M. Kwiatkowska, Y. Gal, and B. Bloem-Reddy, "On the Benefits of Invariance in Neural Networks," *CoRR*, vol. abs/2005.00178, 2020, _eprint: 2005.00178. [Online]. Available: https://arxiv.org/abs/2005.00178 (Cited on 2)

[12] Y. Dubois, B. Bloem-Reddy, K. Ullrich, and C. J. Maddison, "Lossy Compression for Lossless Prediction," *arXiv:2106.10800 [cs, math, stat]*, Jun. 2021, arXiv: 2106.10800. [Online]. Available: http://arxiv.org/abs/2106.10800 (Cited on 3, 8)

[13] V. N. Vapnik and A. Y. Chervonenkis, "On the Uniform Convergence of Relative Frequencies of Events to Their Probabilities," *Theory of Probability & Its Applications*, vol. 16, no. 2, pp. 264–280, 1971, _eprint: https://doi.org/10.1137/1116025. [Online]. Available: https://doi.org/10.1137/1116025 (Cited on 3, 7)

[14] C. J. Burges, "A tutorial on support vector machines for pattern recognition," *Data mining and knowledge discovery*, vol. 2, no. 2, pp. 121–167, 1998, publisher: Springer. (Cited on 3)

[15] A. Radford, J. W. Kim, C. Hallacy, A. Ramesh, G. Goh, S. Agarwal, G. Sastry, A. Askell, P. Mishkin, J. Clark, G. Krueger, and I. Sutskever, "Learning Transferable Visual Models From Natural Language Supervision," *arXiv:2103.00020 [cs]*, Feb. 2021, arXiv: 2103.00020. [Online]. Available: http://arxiv.org/abs/2103.00020 (Cited on 4)

[16] V. Papyan, X. Y. Han, and D. L. Donoho, "Prevalence of Neural Collapse during the terminal phase of deep learning training," *Proceedings of the National Academy of Sciences*, vol. 117, no. 40, pp. 24 652–24 663, Oct. 2020, arXiv: 2008.08186. [Online]. Available: http://arxiv.org/abs/2008.08186 (Cited on 4)

[17] T. Ergen and M. Pilanci, "Revealing the Structure of Deep Neural Networks via Convex Duality," in *Proceedings of the 38th International Conference on Machine Learning*. PMLR, Jul. 2021, pp. 3004–3014, iSSN: 2640-3498. [Online]. Available: https://proceedings.mlr.press/v139/ergen21b.html

[18] J. Lu and S. Steinerberger, "Neural Collapse with Cross-Entropy Loss," *arXiv:2012.08465 [cs, math]*, Jan. 2021, arXiv: 2012.08465. [Online]. Available: http://arxiv.org/abs/2012.08465

[19] F. Graf, C. Hofer, M. Niethammer, and R. Kwitt, "Dissecting Supervised Contrastive Learning," in *Proceedings of the 38th International Conference on Machine Learning*. PMLR, Jul. 2021, pp. 3821–3830, iSSN: 2640-3498. [Online]. Available: https://proceedings.mlr.press/v139/graf21a.html

[20] J. Zarka, F. Guth, and S. Mallat, "Separation and Concentration in Deep Networks," arXiv, Tech. Rep. arXiv:2012.10424, Mar. 2021, arXiv:2012.10424 [cs] type: article. [Online]. Available: http://arxiv.org/abs/2012.10424

[21] E. Weinan and S. Wojtowytsch, "On the emergence of simplex symmetry in the final and penultimate layers of neural network classifiers," *arXiv:2012.05420 [cs, stat]*, Jun. 2021, arXiv: 2012.05420. [Online]. Available: http://arxiv.org/abs/2012.05420 (Cited on 4)

[22] Z. Zhu, T. Ding, J. Zhou, X. Li, C. You, J. Sulam, and Q. Qu, "A Geometric Analysis of Neural Collapse with Unconstrained Features," *arXiv:2105.02375 [cs, math, stat]*, May 2021, arXiv: 2105.02375. [Online]. Available: http://arxiv.org/abs/2105.02375 (Cited on 4)

[23] W. Ji, Y. Lu, Y. Zhang, Z. Deng, and W. J. Su, "An Unconstrained Layer-Peeled Perspective on Neural Collapse," *arXiv:2110.02796 [cs, stat]*, Oct. 2021, arXiv: 2110.02796. [Online]. Available: http://arxiv.org/abs/2110.02796 (Cited on 4)

[24] M. Caron, H. Touvron, I. Misra, H. Jégou, J. Mairal, P. Bojanowski, and A. Joulin, "Emerging Properties in Self-Supervised Vision Transformers," *arXiv:2104.14294 [cs]*, May 2021, arXiv: 2104.14294. [Online]. Available: http://arxiv.org/abs/2104.14294 (Cited on 5, 6)

[25] X. Chen and K. He, "Exploring Simple Siamese Representation Learning," in *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. Nashville, TN, USA: IEEE, Jun. 2021, pp. 15 745–15 753. [Online]. Available: https://ieeexplore.ieee.org/document/9578004/ (Cited on 5, 7, 8)

[26] K. He, H. Fan, Y. Wu, S. Xie, and R. Girshick, "Momentum Contrast for Unsupervised Visual Representation Learning," in *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*. Seattle, WA, USA: IEEE, Jun. 2020, pp. 9726–9735. [Online]. Available: https://ieeexplore.ieee.org/document/9157636/ (Cited on 5, 7)

[27] A. Mnih and K. Kavukcuoglu, "Learning word embeddings efficiently with noise-contrastive estimation," in *Advances in Neural Information Processing Systems*, vol. 26. Curran Associates, Inc., 2013. [Online]. Available: https://proceedings.neurips.cc/paper/2013/hash/db2b4182156b2f1f817860ac9f409ad7-Abstract.html (Cited on 5)

[28] A. v. d. Oord, Y. Li, and O. Vinyals, "Representation Learning with Contrastive Predictive Coding," *arXiv:1807.03748 [cs, stat]*, Jan. 2019, arXiv: 1807.03748. [Online]. Available: http://arxiv.org/abs/1807.03748 (Cited on 7)

[29] I. Misra and L. v. d. Maaten, "Self-Supervised Learning of Pretext-Invariant Representations," in *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2020, Seattle, WA, USA, June 13-19, 2020*. Computer Vision Foundation / IEEE, 2020, pp. 6706–6716. [Online]. Available: https://openaccess.thecvf.com/content_CVPR_2020/html/Misra_Self-Supervised_Learning_of_Pretext-Invariant_Representations_CVPR_2020_paper.html (Cited on 5)

[30] M. Gutmann and A. Hyvärinen, "Noise-contrastive estimation: A new estimation principle for unnormalized statistical models," in *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*. JMLR Workshop and Conference Proceedings, Mar. 2010, pp. 297–304, iSSN: 1938-7228. [Online]. Available: http://proceedings.mlr.press/v9/gutmann10a.html (Cited on 5)

[31] R. Jozefowicz, O. Vinyals, M. Schuster, N. Shazeer, and Y. Wu, "Exploring the Limits of Language Modeling," *arXiv:1602.02410 [cs]*, Feb. 2016, arXiv: 1602.02410. [Online]. Available: http://arxiv.org/abs/1602.02410

[32] Z. Ma and M. Collins, "Noise Contrastive Estimation and Negative Sampling for Conditional Models: Consistency and Statistical Efficiency," in *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*. Brussels, Belgium: Association for Computational Linguistics, Oct. 2018, pp. 3698–3707. [Online]. Available: https://www.aclweb.org/anthology/D18-1405 (Cited on 5)

[33] Z. Fang, J. Wang, L. Wang, L. Zhang, Y. Yang, and Z. Liu, "SEED: Self-supervised Distillation For Visual Representation," in *9th International Conference on Learning Representations, ICLR 2021, Virtual Event, Austria, May 3-7, 2021*. OpenReview.net, 2021. [Online]. Available: https://openreview.net/forum?id=AHm3dbp7D1D (Cited on 6)

[34] E. T. Jaynes, "Information Theory and Statistical Mechanics," *Physical Review*, vol. 106, no. 4, pp. 620–630, May 1957, publisher: American Physical Society. [Online]. Available: https://link.aps.org/doi/10.1103/PhysRev.106.620 (Cited on 7)

[35] A. Ermolov, A. Siarohin, E. Sangineto, and N. Sebe, "Whitening for Self-Supervised Representation Learning," *arXiv:2007.06346 [cs, stat]*, May 2021, arXiv: 2007.06346. [Online]. Available: http://arxiv.org/abs/2007.06346 (Cited on 7, 8)

[36] J.-B. Grill, F. Strub, F. Altché, C. Tallec, P. H. Richemond, E. Buchatskaya, C. Doersch, B. A. Pires, Z. Guo, M. G. Azar, B. Piot, K. Kavukcuoglu, R. Munos, and M. Valko, "Bootstrap Your Own Latent - A New Approach to Self-Supervised Learning," in *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, H. Larochelle, M. Ranzato, R. Hadsell, M.-F. Balcan, and H.-T. Lin, Eds., 2020. [Online]. Available: https://proceedings.neurips.cc/paper/2020/hash/f3ada80d5c4ee70142b17b8192b2958e-Abstract.html (Cited on 7, 8)

[37] Y. Bengio, A. Courville, and P. Vincent, "Representation Learning: A Review and New Perspectives," *arXiv:1206.5538 [cs]*, Apr. 2014, arXiv: 1206.5538. [Online]. Available: http://arxiv.org/abs/1206.5538 (Cited on 7)

[38] R. Zhang, P. Isola, and A. A. Efros, "Colorful Image Colorization," in *Computer Vision - ECCV 2016 - 14th European Conference, Amsterdam, The Netherlands, October 11-14, 2016, Proceedings, Part III*, ser. Lecture Notes in Computer Science, B. Leibe, J. Matas, N. Sebe, and M. Welling, Eds., vol. 9907. Springer, 2016, pp. 649–666. [Online]. Available: https://doi.org/10.1007/978-3-319-46487-9_40 (Cited on 7)

[39] T. M. Cover, "Geometrical and Statistical Properties of Systems of Linear Inequalities with Applications in Pattern Recognition," *IEEE Transactions on Electronic Computers*, vol. EC-14, no. 3, pp. 326–334, Jun. 1965. [Online]. Available: http://ieeexplore.ieee.org/document/4038449/ (Cited on 7)

[40] R. Sinkhorn and P. Knopp, "Concerning nonnegative matrices and doubly stochastic matrices," *Pacific Journal of Mathematics*, vol. 21, no. 2, pp. 343–348, 1967, publisher: Mathematical Sciences Publishers. (Cited on 7)

[41] J. Zbontar, L. Jing, I. Misra, Y. LeCun, and S. Deny, "Barlow Twins: Self-Supervised Learning via Redundancy Reduction," in *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, ser. Proceedings of Machine Learning Research, M. Meila and T. Zhang, Eds., vol. 139. PMLR, 2021, pp. 12 310–12 320. [Online]. Available: http://proceedings.mlr.press/v139/zbontar21a.html (Cited on 8)

[42] T. Hua, W. Wang, Z. Xue, S. Ren, Y. Wang, and H. Zhao, "On Feature Decorrelation in Self-Supervised Learning," *arXiv:2105.00470 [cs, stat]*, Aug. 2021, arXiv: 2105.00470. [Online]. Available: http://arxiv.org/abs/2105.00470 (Cited on 8)

[43] L. Jing, P. Vincent, Y. LeCun, and Y. Tian, "Understanding Dimensional Collapse in Contrastive Self-supervised Learning," *arXiv:2110.09348 [cs]*, Oct. 2021, arXiv: 2110.09348. [Online]. Available: http://arxiv.org/abs/2110.09348 (Cited on 8)

[44] N. Saunshi, J. Ash, S. Goel, D. Misra, C. Zhang, S. Arora, S. Kakade, and A. Krishnamurthy, "Understanding Contrastive Learning Requires Incorporating Inductive

Biases," *arXiv:2202.14037 [cs]*, Feb. 2022, arXiv: 2202.14037. [Online]. Available: http://arxiv.org/abs/2202.14037 (Cited on 8, 9, 10)

[45] Y.-H. H. Tsai, Y. Wu, R. Salakhutdinov, and L.-P. Morency, "Self-supervised Learning from a Multi-view Perspective," *arXiv:2006.05576 [cs, stat]*, Mar. 2021, arXiv: 2006.05576. [Online]. Available: http://arxiv.org/abs/2006.05576 (Cited on 8)

[46] Y. Tian, C. Sun, B. Poole, D. Krishnan, C. Schmid, and P. Isola, "What Makes for Good Views for Contrastive Learning?" *Advances in Neural Information Processing Systems*, vol. 33, pp. 6827–6839, 2020. [Online]. Available: https://papers.nips.cc/paper/2020/hash/4c2e5eaae9152079b9e95845750bb9ab-Abstract.html

[47] M. Federici, A. Dutta, P. Forré, N. Kushman, and Z. Akata, "Learning Robust Representations via Multi-View Information Bottleneck," *arXiv:2002.07017 [cs, stat]*, Feb. 2020, arXiv: 2002.07017. [Online]. Available: http://arxiv.org/abs/2002.07017

[48] J. Mitrovic, B. McWilliams, J. Walker, L. Buesing, and C. Blundell, "Representation Learning via Invariant Causal Mechanisms," *arXiv:2010.07922 [cs, stat]*, Oct. 2020, arXiv: 2010.07922. [Online]. Available: http://arxiv.org/abs/2010.07922

[49] M. Wu, C. Zhuang, M. Mosse, D. Yamins, and N. Goodman, "On Mutual Information in Contrastive Learning for Visual Representations," *arXiv:2005.13149 [cs, stat]*, Jun. 2020, arXiv: 2005.13149. [Online]. Available: http://arxiv.org/abs/2005.13149 (Cited on 8)

[50] T. Chen and L. Li, "Intriguing Properties of Contrastive Losses," *arXiv:2011.02803 [cs, stat]*, Nov. 2020, arXiv: 2011.02803. [Online]. Available: http://arxiv.org/abs/2011.02803 (Cited on 8)

[51] J. Chen, Z. Gan, X. Li, Q. Guo, L. Chen, S. Gao, T. Chung, Y. Xu, B. Zeng, W. Lu, F. Li, L. Carin, and C. Tao, "Simpler, Faster, Stronger: Breaking The log-K Curse On Contrastive Learners With FlatNCE," *arXiv:2107.01152 [cs, math, stat]*, Jul. 2021, arXiv: 2107.01152. [Online]. Available: http://arxiv.org/abs/2107.01152 (Cited on 8)

[52] C. Tosh, A. Krishnamurthy, and D. Hsu, "Contrastive estimation reveals topic posterior information to linear models," *arXiv:2003.02234 [cs, stat]*, Mar. 2020, arXiv: 2003.02234. [Online]. Available: http://arxiv.org/abs/2003.02234 (Cited on 8)

[53] K. Nozawa and I. Sato, "Understanding Negative Samples in Instance Discriminative Self-supervised Representation Learning," *arXiv:2102.06866 [cs, stat]*, Oct. 2021, arXiv: 2102.06866. [Online]. Available: http://arxiv.org/abs/2102.06866

[54] Y. Tian, X. Chen, and S. Ganguli, "Understanding self-supervised Learning Dynamics without Contrastive Pairs," *arXiv:2102.06810 [cs]*, Oct. 2021, arXiv: 2102.06810. [Online]. Available: http://arxiv.org/abs/2102.06810 (Cited on 8)

[55] Y. Le and X. Yang, "Tiny ImageNet Visual Recognition Challenge," p. 6, 2015. (Cited on 8)

[56] Z. Wu, Y. Xiong, S. Yu, and D. Lin, "Unsupervised Feature Learning via Non-Parametric Instance-level Discrimination," *arXiv:1805.01978 [cs]*, May 2018, arXiv: 1805.01978. [Online]. Available: http://arxiv.org/abs/1805.01978 (Cited on 9)

[57] J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei, "ImageNet: A large-scale hierarchical image database," in *2009 IEEE Conference on Computer Vision and Pattern Recognition*, Jun. 2009, pp. 248–255, iSSN: 1063-6919. (Cited on 10)

[58] P. Goyal, Q. Duval, J. Reizenstein, M. Leavitt, M. Xu, B. Lefaudeux, M. Singh, V. Reis, M. Caron, P. Bojanowski, A. Joulin, and I. Misra, "VISSL," 2021. [Online]. Available: https://github.com/facebookresearch/vissl (Cited on 10)

[59] S. Kornblith, T. Chen, H. Lee, and M. Norouzi, "Why Do Better Loss Functions Lead to Less Transferable Features?" in *Advances in Neural Information Processing Systems*, vol. 34. Curran Associates, Inc., 2021, pp. 28 648–28 662. [Online]. Available: https://proceedings.neurips.cc/paper/2021/hash/f0bf4a2da952528910047c31b6c2e951-Abstract.html (Cited on 10)

[60] Y. Dubois, D. Kiela, D. J. Schwab, and R. Vedantam, "Learning Optimal Representations with the Decodable Information Bottleneck," in *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*, H. Larochelle, M. Ranzato, R. Hadsell, M.-F. Balcan, and H.-T. Lin, Eds., 2020. [Online]. Available: https://proceedings.neurips.cc/paper/2020/hash/d8ea553c1b1eb087ac2e356253395d8-Abstract.html (Cited on 10)

[61] Y. Ruan, Y. Dubois, and C. J. Maddison, "Optimal Representations for Covariate Shift," Sep. 2021. [Online]. Available: https://openreview.net/forum?id=Rf58LPCwJj0 (Cited on 10)

[62] P. Goyal, M. Caron, B. Lefaudeux, M. Xu, P. Wang, V. Pai, M. Singh, V. Liptchinsky, I. Misra, A. Joulin, and P. Bojanowski, "Self-supervised Pretraining of Visual Features in the Wild," *arXiv:2103.01988 [cs]*, Mar. 2021, arXiv: 2103.01988. [Online]. Available: http://arxiv.org/abs/2103.01988 (Cited on 10)

[63] R. Bommasani, D. A. Hudson, E. Adeli, R. Altman, S. Arora, S. von Arx, M. S. Bernstein, J. Bohg, A. Bosselut, E. Brunskill, E. Brynjolfsson, S. Buch, D. Card, R. Castellon, N. Chatterji, A. Chen, K. Creel, J. Q. Davis, D. Demszky, C. Donahue, M. Doumbouya, E. Durmus, S. Ermon, J. Etchemendy, K. Ethayarajh, L. Fei-Fei, C. Finn, T. Gale, L. Gillespie, K. Goel, N. Goodman, S. Grossman, N. Guha, T. Hashimoto, P. Henderson, J. Hewitt, D. E. Ho, J. Hong, K. Hsu, J. Huang, T. Icard, S. Jain, D. Jurafsky, P. Kalluri, S. Karamcheti, G. Keeling, F. Khani, O. Khattab, P. W. Koh, M. Krass, R. Krishna, R. Kuditipudi, A. Kumar, F. Ladhak, M. Lee, T. Lee, J. Leskovec, I. Levent, X. L. Li, X. Li, T. Ma, A. Malik, C. D. Manning, S. Mirchandani, E. Mitchell, Z. Munyikwa, S. Nair, A. Narayan, D. Narayanan, B. Newman, A. Nie, J. C. Niebles, H. Nilforoshan, J. Nyarko, G. Ogut, L. Orr, I. Papadimitriou, J. S. Park, C. Piech, E. Portelance, C. Potts, A. Raghunathan, R. Reich, H. Ren, F. Rong, Y. Roohani, C. Ruiz, J. Ryan, C. Ré, D. Sadigh, S. Sagawa, K. Santhanam, A. Shih, K. Srinivasan, A. Tamkin, R. Taori, A. W. Thomas, F. Tramèr, R. E. Wang, W. Wang, B. Wu, J. Wu, Y. Wu, S. M. Xie, M. Yasunaga, J. You, M. Zaharia, M. Zhang, T. Zhang, X. Zhang, Y. Zhang, L. Zheng, K. Zhou, and P. Liang, "On the Opportunities and Risks of Foundation Models," *arXiv:2108.07258 [cs]*, Aug. 2021, arXiv: 2108.07258. [Online]. Available: http://arxiv.org/abs/2108.07258 (Cited on 10)