GENERATING ANTIMICROBIAL PEPTIDES FROM LATENT SECONDARY STRUCTURE SPACE

ABSTRACT

Antimicrobial peptides (AMPs) have shown promising results in broad-spectrum antibiotics and resistant infection treatments, which makes it attract plenty of attention in drug discovery. Recently, many researchers bring deep generative models to AMP design. However, few studies consider structure information during the generation, though it has shown crucial influence on antimicrobial activity in all AMP mechanism theories. In this paper, we propose `LSSAMP` that uses the multi-scale VQ-VAE to learn the positional latent spaces modeling the secondary structure. By Sampling in the latent secondary structure space, we can generate peptides with ideal amino acids and secondary structures at the same time. Experimental results show that our `LSSAMP` can generate peptides with multiply ideal physical attributes and a high probability of being predicted as AMPs by public AMP prediction models.

1 INTRODUCTION

Developing neural networks for drug discovery has attracted increasing attention recently. It can facilitate the discovery of potential therapies and reduce the time and cost for drug development (Stokes et al., 2020). Plenty of works have been done to employ deep generative models for searching for drug-like molecules with desired properties and achieved great success (Jin et al., 2018; Shi et al., 2019; Schwalbe-Koda & Gómez-Bombarelli, 2020; Xie et al., 2020). However, these works mainly focus on small molecules, and more complicated biochemicals, such as proteins, are still rarely explored.

Antimicrobial peptides (AMPs), defined as short proteins of less than 50 amino acids with potent antimicrobial activity, are an emerging category of therapeutic agents. AMPs exist widely in the natural immune system for all species and kill bacteria in a physical way (Aronica et al., 2021; Cardoso et al., 2020). They attach to the bacteria membrane and insert into the membrane to form pores, which leads to the death of bacteria by allowing cytoplasmic leakage. This mechanism makes them more promising for handling extensively drug-resistant bacteria than traditional antibiotics (Mahlapuu et al., 2016). However, the theoretical chemical space of peptides is enormous and the sequence number grows exponentially as the length increases. Thus, it is very challenging to search for valid peptides with antimicrobial properties from such a huge sequence space.

There are several factors that can affect the antimicrobial activity of peptides (Boman, 2003). Amino acids with positive charges are more likely to bind with bacteria membrane as most bacterial surfaces are anionic, while those with high hydrophobicities tend to move from the solution environment to the bacteria membrane. However, the mechanisms of antibacterial peptides need not only a reasonable sequence but also an appropriate structure. For example, by forming the helix structure, a peptide can gather the hydrophobic amino acids on one side and hydrophilic ones on the other. This ability, named amphipathy, helps it insert into the membrane and maintain a stable hole with other peptide molecules in the membrane, as shown in Figure 1. The hole will drain the cytoplasm and finally kill the bacteria. This mechanism of killing the bacteria is called 'barrel stave'. Amphipathy plays an important role in deciding the antibacterial activity of peptides and is closely related to the secondary structure of the peptide (Aronica et al., 2021).

The existing works mainly focus on sequential features of amino acids and ignore the secondary structure. The traditional methods replace subsequences with patterns from the pattern database in a given template (Porto et al., 2018). Inspired by success in deep neural networks, many researchers

Figure 1: An example of the 'barrel stave' antimicrobial mechanism. The blue indicates the hydrophobic amino acids, and the red ones are hydrophilic. On the left, although the peptides with reasonable amino acids has attached to the bacteria membrane, they still can not insert into it. However, by folding into the helix structure, as shown on the right, the peptides maintain a stable hole which breaks the membrane of bacteria.

apply neural generative models to AMP discovery. To control the antimicrobial activity, some of them introduce the sequential features as the conditioning vector. However, the generated sequences are usually of low correlation with the value dictated by the conditioning vector (Das et al., 2018). Others train extra classifiers to filter invalid sequences during the sampling. But it is difficult to take multiple related features into consideration at the same time. One way is to train one classifier for each feature and only those who satisfy all classifiers will be accepted, making the sampling phase inefficient (Capecchi et al., 2021; Das et al., 2021). The other is to use one classifier to predict the probability of being AMPs directly, resulting in poor interpretation and unreliable performance on new sequences (Van Oort et al., 2021).

As described above, the antimicrobial activity is determined by both the amino acid composition and secondary structure of the peptide. Thus, we propose LSSAMP to generate antimicrobial peptides from the latent semantic and structure space. By generating sequences with reasonable structures as well as amino acid patterns, our model can obtain peptides with multiply ideal AMP properties at the same time. Taking the peptide sequence as the time series, we assign a latent variable on each position. Since it is computationally intractable to sum continuous latent variables over all positions, we employ the VQ-VAE (van den Oord et al., 2017) to learn the discrete distribution for each position and further design a multi-scale codebooks strategy to capture different local patterns to fit various length ranges for amino acid and structure sequences. To enforce the positional latent distribution to model the structure information, we employ the secondary structure prediction on the latent space. During the generation process, LSSAMP will sample a backbone from the secondary structure latent space and generate the amino acid sequence at the same time.

We evaluate LSSAMP and several baselines through physical properties, such as net charge, hydrophobicity, and hydrophobic moment that are closely related to the antibacterial mechanism. Besides, we use some public AMP prediction models to predict the probability of generated sequences being AMPs as previous works (Das et al., 2020; Van Oort et al., 2021). To conclude, our contributions are as follows:

• We propose LSSAMP, a generative model which samples peptides from the latent secondary structure space to control the peptide properties.
• We develop a multi-scale VQ-VAE to learn positional latent spaces from different aspects and model semantic sequences and structural sequences in the same space.
• Experimental results show that LSSAMP can generate peptides with multiply ideal features such as positive charge, better hydrophobicity, and better amphipathicity. The results of public AMP classifiers also verify that our model can generate peptides with high AMP probability.

2 RELATED WORK

Antimicrobial Peptides Generation Traditional methods for AMP design can be divided into three types (Torres & de la Fuente-Nunez, 2019): (i) The pattern recognition algorithms first build a sequential pattern database from existing AMPs, and then pick a template peptide and replace local sequence with different patterns (Loose et al., 2006; Porto et al., 2018). (ii) The genetic algorithms

Figure 2: The framework of LSSAMP. The input sequence is first fed into the encoder to get the hidden representation h. Then, we use N pattern selectors to select local patterns with different scales and use the corresponding codebooks to obtain discrete latent variables for each position. The codebooks are made to learn the latent space of the secondary structure by employing the secondary structure prediction task on them. For inference, we generate peptides from the latent structure space by sampling the index sequences on the codebooks. We also try to use some conditions to restrict the structure motifs to further improve the generation performance.

analyze the AMP database and design some antibiotic activity functions. They evolve initial sequences to get AMP sequences (Maccari et al., 2013). (iii)The molecular modeling and molecular dynamics methods build 3D models of peptides and analyze activity by molecular dynamics simulation (Matyus et al., 2007; Bolintineanu & Kaznessis, 2011).

Deep generative models take a rapid growth in recent years. Dean & Walper (2020) encodes the peptide into the latent space and interpolates across a predictive vector between a known AMP and its scrambled version to generate novel peptides. The CLaSS (Das et al., 2021) employs a variational auto-encoder model to generate sequences and train several attribute classifiers on the latent space. The AMPGAN (Van Oort et al., 2021) uses the generative adversarial network to generate new peptide sequences with conditional variables. To our knowledge, we are the first to consider secondary structure information during the generative phase, which can help us to generate well-structured sequences with desired proprieties more efficiently.

Sequence Generation via VQ-VAE The variational auto-encoders (VAEs) were first proposed by Kingma & Welling (2014) for image generation, and then widely applied to sequence generation tasks such as language modeling (Bowman et al., 2016), paraphrase generation (Gupta et al., 2018), machine translation (Bao et al., 2019) and so on. Instead of mapping the input to a continuous latent space in VAE, the vector quantized-variational autoencoder (VQ-VAE) (van den Oord et al., 2017) learns the codebook to obtain a discrete latent representation. It can avoid issues of posterior collapse while has comparable performance with VAEs. Based on it, Razavi et al. (2019) uses a multi-scale hierarchical organization to capture global and local features for image generation. Bao et al. (2021) learns implicit categorical information of target words with VQ-VAE and models the categorical sequence with conditional random fields in non-autoregressive machine translation. In this paper, we employ the vector quantized technique to obtain the discrete representation for each position of the peptide. We capture features of various scales with different sub-codebooks to model sequential and structural information at the same time.

3 METHOD

Given a peptide sequence $x = \{a_1, a_2, \cdots, a_L\}$, where a belongs to the 20 common amino acids and L is the sequence length, the corresponding secondary structure can be denoted as

$\boldsymbol{y} = \{y_1, y_2, \cdots, y_L\}$, $y_i \in \{H, B, E, G, I, T, S, -\}$[1]. We first employ VQ-VAE for the sequence reconstruction task to learn the sequential latent space (Section 3.1). Then, we enforce the latent space to model the structure information by the secondary structure task (Section 3.2). Besides, we design the multi-scale codebooks to capture different local patterns (Section 3.3). Finally, we describe the training and inference phase in Section 3.4. The overview of our model is shown in Figure 2.

3.1 MODELING PEPTIDE SEQUENCES

For sequential information, we embed the input peptide $\boldsymbol{x} = \{a_1, a_2, \cdots, a_L\}$ to the latent space via the encoder and use the generator to reconstruct x. We assume that each a_i is determined by a latent variable z_i, and the input sequences $\boldsymbol{x} = a_{1:L}$ will be assigned to a latent sequence $\boldsymbol{z} = z_{1:L}$. Since it is computationally intractable to sum continuous latent variables over the sequence, we use VQ-VAE (van den Oord et al., 2017) to lookup the discrete embedding vector $\boldsymbol{z}_q = \{z_q(a_1), \cdots, z_q(a_L)\}$ for each position by vector quantization.

Specifically, the encoder output $z_e(a_i) \in \mathbb{R}^d$ will be replaced by the codebook embedding $z_q(a_i) \in \mathbb{R}^d$ via a nearest neighbors lookup from the codebook $\boldsymbol{B} \in \mathbb{R}^{K \times d}$:

$$z_q(a_i) = e_k, \text{and } k = \operatorname{argmin}_{j \in K} \|z_e(a_i) - e_j\|_2. \tag{1}$$

Here, K is the size of the codebook and d is the dimension of the codebook entry e. Then, the generator will take $z_q(a_i)$ as its input and reconstruct $\boldsymbol{x}$. The training objective L_r is defined as:

$$L_r = \log p\left(a_i | z_q(a_i)\right) + \|\text{sg}\left[z_e(a_i)\right] - z_q(a_i)\|_2^2 + \beta \|z_e(a_i) - \text{sg}[z_q(a_i)]\|_2^2. \tag{2}$$

Here, $sg(\cdot)$ is the stop gradient operator, which becomes 0 at the backward pass. β is the commit coefficient to control the codebook loss.

3.2 MODELING SECONDARY STRUCTURES

In order to model the categorical information of the secondary structure, we define an 8-category sequence labeling task on the latent space, which takes $\boldsymbol{x}$ as the input and the structure label sequence $\boldsymbol{y}$ as the target. Similar with sequence reconstruction, we use the same encoder to get $z_e(a_i)$ and employ VQ-VAE to obtain discrete representation. Then, $z_q'(a_i)$ is fed to a separate classifier for the secondary structure prediction:

$$L_s = \log p\left(y_i | z_q'(a_i)\right) + \|\text{sg}\left[z_e(a_i)\right] - z_q'(a_i)\|_2^2 + \beta \|z_e(a_i) - \text{sg}[z_q'(a_i)]\|_2^2. \tag{3}$$

Peptide sequences and structures have distinctive local features, which are often utilized in traditional design algorithms. The patterns of amino acids are often used for template-based design and feature-based recognition. For structure motifs such as α-helix with at least 3.6 consecutive amino acids, they will determine the position of amino acids in the 3D space and affect the function of peptides. However, the structure motifs are often much longer than sequence patterns. Therefore, we establish codebooks of multiple scales to learn latent spaces for different local patterns.

3.3 MULTI-SCALE VQ-VAE

For the encoder output $h_i = z_e^{(0)}(a_i)$, we first use N pattern selectors $F^{(n)}$ to extract local patterns from different scales, which will get $z_e^{(n)}(a_i) = F^{(n)}(h_i)$. Then, we establish the codebook for each pattern, and use Eqn. 1 to look up the nearest codebook embedding $z_q^{(n)}(a_i)$.

We share the codebooks between the sequence reconstruction and secondary structure prediction to capture common features and relationships between the amino acid and its structure. Specifically, we make N_r codebook for the sequence information and N_s for the structure. The $z_{q_r}(a_i)$ is the concatenation of N_r codebook embeddings and is fed to the sequence generator:

$$z_{q_r}(a_i) = \|_{n \in N_r} z_q^{(n)}(a_i), \tag{4}$$

---

[1]Following the definition in Kabsch & Sander (1983), there are 8 secondary structure types, including one unknown label.

Algorithm 1 Training phase of `LSSAMP`

Require: A pre-training dataset D_r, a peptide dataset with secondary structure D_s, and the AMP dataset D_{amp}. The model M_θ.
 1: Pre-train sequence reconstruction on D_r and update M_θ via Eqn. 5.
 2: Finetune sequence reconstruction as well as secondary structure prediction on D_s and update the M_θ via Eqn. 6.
 3: Further Finetune M_θ on D_{amp}.
 4: **for** $n = 1, 2, \cdots, N$ **do**
 5:     Create an empty dataset C_n.
 6:     **for** $x_i \in D_{amp}$ **do**
 7:         Save the n-th codebook index of x_i via Eqn. 1 to C_n
 8:     **end for**
 9:     Train an auto-regressive language model M_{prior_n} on C_n.
10: **end for**

Based on Eqn. 2, the reconstruction training objective for multi-scale VQ-VAE can be denoted as:

$$L_r = \log p\left(a_i | z_{q_r}(a_i)\right) + \sum_{n \in N_r} \left(\left\| \text{sg}\left[z_e^{(n)}(a_i)\right] - z_q^{(n)}(a_i) \right\|_2^2 + \beta \left\| z_e^{(n)}(a_i) - \text{sg}[z_q^{(n)}(a_i)] \right\|_2^2 \right). \tag{5}$$

The loss of secondary structure prediction task L_r can be formulated in the same way from Eqn. 3. And the total training loss is:

$$L = L_r + \gamma L_s, \tag{6}$$

where the γ is the weight of the secondary structure prediction.

3.4 TRAINING AND INFERENCE

We discuss the training and sampling process in this section. Since the AMP dataset D_{amp} is very small, we use two extra datasets D_r and D_s to pre-train the reconstruction and prediction task. The whole training process is described in Algorithm 1.

Training To enable the generator to generate valid peptide sequences, we first pre-train our model on a large protein dataset D_r for the sequence construction task. Then, we jointly train the sequence reconstruction and the structure prediction on a peptide dataset D_r with secondary structure information. This phase maps the positional latent space to an entangled sequential and structural distribution. Finally, we finetune our model on the small AMP dataset D_{amp} to capture the characteristics of AMPs.

Following Kaiser et al. (2018), we use exponential moving average (EMA) to update the embedding vectors in the codebooks. Specifically, we keep a count c_k measuring the number that the embedding vector e_k chosen as the nearest neighbor of $z_e(a_i)$ via Eqn. 1. Thus, the counts are updated with a sort of momentum: $c_k \leftarrow \lambda c_k + (1 - \lambda) \sum \mathbb{I}[z_q(a_i) = e_k]$, with the embedding e_k being updated as: $e_k \leftarrow \lambda e_k + (1 - \lambda) \sum \frac{\mathbb{I}[z_q(a_i) = e_k] z_e(a_i)}{c_k}$. Here, λ is the decay parameter.

Prior Model The prior distribution over the codebook is a categorical distribution and can be made auto-regressive by the extra prior model. In order to model the dependency between $z_{1:L}$, we train Transformer-based language models on the embedding entries. We extract the index sequences generated by Eqn. 1 for each codebook n and then train M_{prior_n} on them.

Inference We sample several index sequences from the prior models for each codebook n, and then lookup the codebook to get the embedding vector $z_q^{(n)}$. Finally, $z_q^{(n)}$ is fed to the generator and classifier to generate the sequence with its secondary structure. We also try to control the secondary structure by existing AMP structure patterns to further improve the generation quality.

4 EXPERIMENT

4.1 EXPERIMENT SETUP

Dataset The Universal Protein Resource (Uniprot)[2] is a comprehensive protein dataset. We download reviewed protein sequences (Swiss-prot) with the limitation of 100 in length as D_r (57k examples). Then we use ProSPr[3] (Billings et al., 2019) to predict the secondary structure for D_r and filter some low-quality examples. Therefore, we get D_s with 46k examples, which have both sequence and secondary structure information. For antimicrobial peptide dataset, we download from Antimicrobial Peptide Database (APD3)[4] (Wang et al., 2016) and filter repeated ones to get 3222 AMPs as D_{amp}. We randomly extract 3,000 examples as validation and 3,000 as test on D_r and D_s. For D_{amp}, the size of validation and test is both 100. Following Veltri et al. (2018), we establish a decoy set with negative examples that do not have antimicrobial activities to examine the evaluation metric. It first removes peptide sequences with anti-microbe activity from Uniprot, and then removes sequences with length < 10 and sequences with > 40 sequence identity with AMP sequences, resulting in 2021 non-AMP sequences.

Baseline We implement several baselines for our experiment. Traditional methods usually randomly substitute several amino acids on the existing AMPs and conducting biological experiments on them. Thus, we use the **Random** replacement with probability p as the baseline. Following Dean & Walper (2020), we use **VAE** to embed the peptides into the latent space and sample latent variable z from the standard Gaussian distribution $p \sim N(0, 1)$. For a fair comparison, we use the same Transformer architecture as our model LSSAMP and train on the Uniprot D_r and APD dataset D_{amp}. **AMP-GAN** is proposed by Van Oort et al. (2021), which uses a BiCGAN architecture with convolution layers. It consists of three components: the generator, discriminator, and encoder. The generator and discriminator share the same encoder. **MLPeptide** (Capecchi et al., 2021) is RNN-based generator. It is first trained on 3580 AMPs and then transfer against specific bacteria.

Implementation Details There are three main modules for LSSAMP. The encoder and decoder are based on 2-layer Transformer (Vaswani et al., 2017) with $d_{model} = 128$ and $head = 8$. The size of FFN projection is $d_{ffn} = 512$ and all drouput rate are 0.1. For the classifier, we use the same CNN block as Billings et al. (2019) with 32 input channels and a dilation scale of $[1, 2, 4, 8, 10]$. For multi-scale codebooks, we first apply CNN as $F^{(n)}$ to extract features. We set $n = 4$ and kernel width ranging in $[1, 2, 4, 8]$. The features will be padding to the same length as the input sequence. Then, we use 4 codebook with $K = 8$ and $d = 128$. The reconstruction and prediction share the same codebooks, which means $N_r = N_s = 4$. The commit coefficient is set to $\beta = 0.05$.

We optimize the parameter with Adam Optimizer (Kingma & Ba, 2015). During pre-training for sequence construction on D_r, we limit the max length to 100 and set batch size $batch$ as 30,000, learning rate lr as 0.01 with 8,000 warmup steps, and decoy weight for EMA as $\lambda = 0.8$. For secondary structure prediction on D_s, the max length is limited to 32, $batch = 10,000$, $lr = 0.003$, $\lambda = 0.95$, and the prediction loss coefficient $\gamma = 1$. Finally, we transfer to D_{amp} with the same hyperparameters except the $lr = 0.001$.

4.2 EVALUATION METRIC

To evaluate the antimicrobial activity of the generated peptide $S = \{a_1, a_2, \cdots, a_L\}$, we use several physical features according to the mechanism of AMPs. Besides, we also apply some open-source AMP predictive models to estimate the probability of the generated peptides being AMPs.

4.2.1 PHYSICAL ATTRIBUTES

Charge The bacteria membrane usually takes the negative charge, so peptides with the positive charge prefer to bind with the bacteria. The whole net charge of the peptide sequence S is defined as the sum of the charge of all its amino acids $C(a_i)$ at pH 7.4, which is $C(S) = \sum_{a_i \in S} C(a_i)$
Hydrophobicity The hydrophobicity reflects the tendency to bind lipids on the bacteria membrane.

---

[2]https://www.uniprot.org/

[3]https://github.com/dellacortelab/prospr/tree/prospr1

[4]https://aps.unmc.edu/

It is more likely for the peptide with a high hydrophobicity to move from the solution environment to the bacteria membrane. We use the hydrophobicity scale $H(a_i)$ in Eisenberg et al. (1984) to calculate the hydrophobicity of a sequence, which is $H(S) = \sum_{a_i \in S} H(a_i)$

Amphipathicity / Hydrophobic Momentum The amphipathicity measures the ability of the peptide to bind water and lipid at the same time, which is a definitive feature of antimicrobial peptides(Hancock & Rozek, 2002). It can be quantified by the hydrophobic momentum $uH(S, \theta)$, defined by Eisenberg et al. (1984). The hydrophobic momentum is determined by the hydrophobicity $H(a_i)$ of each amino acid a_i, along with the angle θ between amino acids. The angle can be estimated by the secondary structure. For the α-helix structure, θ is $100°$ and for β-sheet, θ is $180°$.

$$uH(S, \theta) = \sqrt{(\sum_{a_i \in S} H(a_i) * cos(i * \theta))^2 + (\sum_{a_i \in S} H(a_i) sin(i * \theta))^2} \tag{7}$$

For each peptide, we calculate the above properties to measure its antimicrobial activity. For comparison, we draw the distribution on APD and decoy dataset and choose a range for each property[5]. We use the percentage of peptides in the range for each attribute to leverage the generation performance and use **Combination** to measure the percentage of those that satisfy three conditions at the same time. The detailed information is attached in the appendix.

4.2.2 AMP CLASSIFIERS

Following previous works (Das et al., 2020; Van Oort et al., 2021), we also use several open-source AMP prediction tools to predict the AMP probability of generated sequence. Since these prediction tools are trained and report results in different AMP datasets, we first use them to predict sequences in APD and decoy dataset as a reference of their performance.

Thomas et al. (2010) trained on the AMP database of 3782 sequences with random forest (**RF**), discriminant analysis (**DA**), support vector machines (**SVM**)[6], and artificial neural network (ANN)[7] respectively. AMP Scanner v2[8] (Veltri et al., 2018), short as **Scanner**, is a CNN-&LSTM-based deep neural network trained on 1778 AMPs picked from APD. **AMPMIC**[9] (Witten & Witten, 2019) trained a CNN-based regression model on 6760 unique sequences and 51345 MIC measurement to predict MIC values. **IAMPE**[10] (Kavousi et al., 2020) is a model based on Xtreme Gradient Boosting. It achieves the highest correct prediction rate on a a set of ten more recent AMPs (Aronica et al., 2021). **ampPEP**[11] (Lawrence et al., 2021) is a random forest based model which is trained on 3268 AMP sequences. It has the best performance across multiple data sets (Aronica et al., 2021).

4.3 RESULTS AND ANALYSIS

We generate 5000 sequences for each baseline and filter the repeated ones. During the generation, we add some structural restrictions based on the antimicrobial mechanism on the secondary structure to improve the performance. Specifically, we reject peptides with more than 30% coil structure ('-'), which can hardly fold in the solution environment and insert into the bacteria membrane. Besides, we limit the minimum length of a helix structure ('H') to 4 based on physical rules. We name our model with structural control as **LSSAMP** and the model without extra conditions as **LSSAMP w/o condition**. We discuss the structure conditions and give some generated peptides in the appendix.

Physical Attributes As listed in Table 1, LSSAMP outperforms on the combination percentage by a large margin (6.27%), which indicates that our model can generate sequences satisfying multiple properties at the same time. If we do not control the structure, the combination percentage is similar to APD, which implies our model learns the latent distribution of APD. For the specific attribute, LSSAMP tends to generate peptides with higher hydrophobicity, while AMP-GAN and MLPeptide

---

[5]The requirements are $C \in [2, 10]$, $H \in [0.25, \infty]$, and $uH \in [0.5, 0.75] \cup [1.75, \infty]$.

[6]http://www.camp3.bicnirrh.res.in/prediction.php

[7]We drop the ANN model becasue its accuracy on APD is quite low (82.83%).

[8]https://www.dveltri.com/ascan/v2/ascan.html

[9]https://github.com/zswitten/Antimicrobial-Peptides

[10]http://cbb1.ut.ac.ir/AMPClassifier/Index

[11]https://github.com/tlawrence3/amPEPpy

	Size	C	H	uH	Combination
APD	3222	68.75%	27.96%	4.72%	6.15%
Decoy	2020	21.83%	8.81%	1.98%	0.10%
Random $p = 0.1$	4978	66.01%	26.84%	22.18%	2.69%
Random $p = 0.2$	5000	59.82%	23.40%	21.60%	1.70%
VAE	4988	23.62%	19.77%	13.17%	0.12%
AMP-GAN	4976	**88.44%**	16.76%	23.69%	1.91%
MLPeptide	4880	86.35%	10.45%	**35.27%**	3.61%
LSSAMP	4886	65.23%	**48.01%**	27.11%	**9.88%**
LSSAMP w/o condition	4893	60.37%	38.57%	23.30%	6.09%

Table 1: Physical attributes of generated sequences. We use the percentage of peptides meeting the range to measure the performance. **Size** is the number of unique sequences. **C**, **H**, **uH** correspond to charge, hydrophobicity, hydrophobic moment described in Section 4.2.1. **Combination** is the percentage satisfying three ranges at the same time. The best results are bold.

	SVM	RF	DA	Scanner	AMPMIC	IAMPE	amPEP	Average
APD	87.78%	91.24%	86.24%	94.66%	98.42%	97.83%	91.50%	92.52%
Decoy	17.43%	13.71%	16.04%	0.25%	18.07%	23.53%	52.92%	20.28%
Random $p = 0.1$	86.06%	86.12%	84.01%	93.23%	79.14%	95.60%	91.74%	87.99%
Random $p = 0.2$	76.66%	76.64%	74.83%	86.95%	68.57%	91.14%	87.89%	80.38%
VAE	24.90%	15.30%	13.83%	15.12%	15.25%	40.31%	24.30%	21.29%
AMP-GAN	78.62%	87.29%	83.82%	82.17%	89.58%	93.88%	80.52%	85.13%
MLPeptide	90.43%	**92.55%**	**93.08%**	**93.72%**	**96.34%**	**97.05%**	91.37%	**93.51%**
LSSAMP	**91.78%**	89.86%	91.09%	90.51%	93.40%	90.42%	**93.23%**	91.47%
LSSAMP w/o condition	77.98%	78.31%	78.00%	85.72%	76.71%	90.05%	84.32%	81.58%

Table 2: The percentage of generated sequences being predicted as AMP. The classifiers are described in Section 4.2.2. The first part is the prediction results on AMP and non-AMP dataset as the reference. The bold ones are the best model results.

have more positive sequences. Also, we can find that by control the secondary structure, all metrics can be improved. This verifies that secondary structure information has a great influence on peptide properties and it is beneficial to take it into consideration during the peptide generation.

AMP Prediction The results of prediction tools are shown in Table 2. By the comparison of LSSAMP and LSSAMP w/o condition, we can draw the same conclusion as above that controlling the secondary structure can further improve the generation performance. LSSAMP performs better than MLPeptide in SVM and amPEP but does not perform as well as it in other classifiers. On the classifier with the largest performance gap IAMPE, we can find that the results of LSSAMP and LSSAMP w/o condition are similar, which implies that different secondary structures do not affect the results of IAMPE. However, in real scenarios, the structure is very important for the antimicrobial mechanism, which makes the classifier less reliable.

	PPL ↓	Loss ↓	AA Acc.↑	SS Acc.↑
LSSAMP	**3.12**	**1.14**	**99.93**	**86.76**
w/o D_r	11.56	2.45	66.06	82.78
w/o D_s	3.83	1.34	99.58	85.87
w/o subbook	3.49	1.25	99.86	86.61

Codebook	PPL ↓	Loss ↓	AA Acc.↑	SS Acc.↑
[1]	17.04	2.84	67.96	85.06
[1, 2]	3.91	1.36	99.72	85.21
[1, 2, 4]	3.34	1.21	**100.00**	85.65
[1, 2, 4, 8]	**3.12**	**1.14**	99.93	**86.76**

Table 3: Ablation Study on validation set of D_{amp}. 'w/o' means that we remove the module from LSSAMP. ↓ means lower is better, while ↑ means higher is better. The detailed descriptions are in Section 4.3.

Table 4: The influence of the number of codebooks. '[1,2,4,8]' indicates that we use 4 codebooks to capture local features with window sizes of 1,2,4,8. The meanings of symbols are the same as Table 3.

Ablation Study We conduct the ablation study for our LSSAMP and show the results in Table 3. PPL is the perplexity of generated sequences that can measure fluency. $Loss$ is the model loss

Figure 3: The distribution of amino acids, charge, sequence length, hydrophobicity, hydrophobic momentum, and a 3D visualization for three physical attributes.

on the validation set. **AA Acc.** is the reconstruction accuracy of amino acids sequences and **SS Acc.** is the prediction accuracy of the secondary structure. We can find that without the first pre-training phase on D_r for sequence reconstruction, the model can hardly generate valid sequences. The second phase to train the model on the large-scale secondary structure dataset D_s will affect the prediction performance on the target AMP dataset. If we remove multiple sub-codebooks and use a single codebook with the same size, the performance will degrade a little.

Codebook Number We explore the effect of different numbers of codebooks on generation performance. From Table 4, we find that a single small codebook can hardly learn enough information to reconstruct the sequences. The PPL, loss, and secondary structure accuracy become better with the increase of codebook items. However, the reconstruction accuracy achieves the best performance when the codebook number is 3. This may be due to the relatively short local patterns for the amino acid sequence, which makes the window of size 8 too long for it.

Visualization We plot the distribution of amino acids, charge, sequence length, hydrophobicity, and hydrophobic momentum for APD, decoy, and our models in Figure 3. Without condition, the distribution of LSSAMP is similar to APD, which indicates that LSSAMP successfully learns the latent space of APD. However, if we control the secondary structure, it is more likely to generate sequences with a longer length and more positive charges. For hydrophobicity and hydrophobic momentum, the distribution of generated sequences is more concentrated.

5 CONCLUSION

In this paper, we propose a multi-scale VQ-VAE to generate from latent secondary structure space for AMPs. Motivated by the important role of structure in the antimicrobial mechanism, LSSAMP learns the latent spaces for each position with both sequential and structural features. Our model shows excellent performance on physical attributes related to antimicrobial activities and has a high probability to be predicted as AMPs by public AMP classifiers. As the structural feature determines the function of macromolecules, LSSAMP has great potential for macromolecules design, including proteins and RNAs.

REFERENCES

Pietro GA Aronica, Lauren M Reid, Nirali Desai, Jianguo Li, Stephen J Fox, Shilpa Yadahalli, Jonathan W Essex, and Chandra S Verma. Computational methods and tools in antimicrobial peptide research. *Journal of Chemical Information and Modeling*, 61(7):3172–3196, 2021.

Yu Bao, Hao Zhou, Shujian Huang, Lei Li, Lili Mou, Olga Vechtomova, Xinyu Dai, and Jiajun Chen. Generating sentences from disentangled syntactic and semantic spaces. In *Proc. of ACL*, July 2019.

Yu Bao, Shujian Huang, Tong Xiao, Dongqi Wang, Xinyu Dai, and Jiajun Chen. Non-autoregressive translation by learning target categorical codes. In *Proc. of NAACL-HLT*, pp. 5749–5759, 2021.

Wendy M Billings, Bryce Hedelius, Todd Millecam, David Wingate, and Dennis Della Corte. Prospr: democratized implementation of alphafold protein distance prediction network. *bioRxiv*, pp. 830273, 2019.

Dan S Bolintineanu and Yiannis N Kaznessis. Computational studies of protegrin antimicrobial peptides: a review. *Peptides*, 32(1):188–201, 2011.

HG Boman. Antibacterial peptides: basic facts and emerging concepts. *Journal of internal medicine*, 254(3):197–215, 2003.

Samuel R Bowman, Luke Vilnis, Oriol Vinyals, Andrew M Dai, Rafal Jozefowicz, and Samy Bengio. Generating sentences from a continuous space. In *20th SIGNLL Conference on Computational Natural Language Learning, CoNLL 2016*, pp. 10–21. Association for Computational Linguistics (ACL), 2016.

Alice Capecchi, Xingguang Cai, Hippolyte Personne, Thilo Kohler, Christian van Delden, and Jean-Louis Reymond. Machine learning designs non-hemolytic antimicrobial peptides. *Chemical Science*, 2021.

Marlon H Cardoso, Raquel Q Orozco, Samilla B Rezende, Gisele Rodrigues, Karen GN Oshiro, Elizabete S Cândido, and Octávio L Franco. Computer-aided design of antimicrobial peptides: are we generating effective drug candidates? *Frontiers in microbiology*, 10:3097, 2020.

Payel Das, Kahini Wadhawan, Oscar Chang, Tom Sercu, Cicero Dos Santos, Matthew Riemer, Vijil Chenthamarakshan, Inkit Padhi, and Aleksandra Mojsilovic. Pepcvae: Semi-supervised targeted design of antimicrobial peptide sequences. *arXiv preprint arXiv:1810.07743*, 2018.

Payel Das, Tom Sercu, Kahini Wadhawan, Inkit Padhi, Sebastian Gehrmann, Flaviu Cipcigan, Vijil Chenthamarakshan, Hendrik Strobelt, Cicero dos Santos, Pin-Yu Chen, et al. Accelerating antimicrobial discovery with controllable deep generative models and molecular dynamics. *arXiv preprint arXiv:2005.11248*, 2020.

Payel Das, Tom Sercu, Kahini Wadhawan, Inkit Padhi, Sebastian Gehrmann, Flaviu Cipcigan, Vijil Chenthamarakshan, Hendrik Strobelt, Cicero Dos Santos, Pin-Yu Chen, et al. Accelerated antimicrobial discovery via deep generative models and molecular dynamics simulations. *Nature Biomedical Engineering*, 5(6):613–623, 2021.

Scott N Dean and Scott A Walper. Variational autoencoder for generation of antimicrobial peptides. *ACS omega*, 5(33):20746–20754, 2020.

David Eisenberg, Robert M Weiss, and Thomas C Terwilliger. The hydrophobic moment detects periodicity in protein hydrophobicity. *Proceedings of the National Academy of Sciences*, 81(1): 140–144, 1984.

Ankush Gupta, Arvind Agarwal, Prawaan Singh, and Piyush Rai. A deep generative framework for paraphrase generation. In Sheila A. McIlraith and Kilian Q. Weinberger (eds.), *Proc. of AAAI*, pp. 5149–5156, 2018.

Robert EW Hancock and Annett Rozek. Role of membranes in the activities of antimicrobial cationic peptides. *FEMS microbiology letters*, 206(2):143–149, 2002.

Wengong Jin, Kevin Yang, Regina Barzilay, and Tommi Jaakkola. Learning multimodal graph-to-graph translation for molecule optimization. In *International Conference on Learning Representations*, 2018.

Wolfgang Kabsch and Christian Sander. Dictionary of protein secondary structure: pattern recognition of hydrogen-bonded and geometrical features. *Biopolymers: Original Research on Biomolecules*, 22(12):2577–2637, 1983.

Lukasz Kaiser, Samy Bengio, Aurko Roy, Ashish Vaswani, Niki Parmar, Jakob Uszkoreit, and Noam Shazeer. Fast decoding in sequence models using discrete latent variables. In *International Conference on Machine Learning*, pp. 2390–2399. PMLR, 2018.

Kaveh Kavousi, Mojtaba Bagheri, Saman Behrouzi, Safar Vafadar, Fereshteh Fallah Atanaki, Bahareh Teimouri Lotfabadi, Shohreh Ariaeenejad, Abbas Shockravi, and Ali Akbar Moosavi-Movahedi. Iampe: Nmr-assisted computational prediction of antimicrobial peptides. *Journal of Chemical Information and Modeling*, 60(10):4691–4701, 2020.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In Yoshua Bengio and Yann LeCun (eds.), *Proc. of ICLR*, 2015.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. 2014.

Travis J Lawrence, Dana L Carper, Margaret K Spangler, Alyssa A Carrell, Tomás A Rush, Stephen J Minter, David J Weston, and Jessy L Labbé. ampeppy 1.0: a portable and accurate antimicrobial peptide prediction tool. *Bioinformatics*, 37(14):2058–2060, 2021.

Christopher Loose, Kyle Jensen, Isidore Rigoutsos, and Gregory Stephanopoulos. A linguistic model for the rational design of antimicrobial peptides. *Nature*, 443(7113):867–869, 2006.

Giuseppe Maccari, Mariagrazia Di Luca, Riccardo Nifosí, Francesco Cardarelli, Giovanni Signore, Claudia Boccardi, and Angelo Bifone. Antimicrobial peptides design by evolutionary multiobjective optimization. *PLoS computational biology*, 9(9):e1003212, 2013.

Margit Mahlapuu, Joakim Håkansson, Lovisa Ringstad, and Camilla Björn. Antimicrobial peptides: an emerging category of therapeutic agents. *Frontiers in cellular and infection microbiology*, 6:194, 2016.

Edit Matyus, Christian Kandt, and D Peter Tieleman. Computer simulation of antimicrobial peptides. *Current medicinal chemistry*, 14(26):2789–2798, 2007.

William F Porto, Isabel CM Fensterseifer, Suzana M Ribeiro, and Octavio L Franco. Joker: An algorithm to insert patterns into sequences for designing antimicrobial peptides. *Biochimica et Biophysica Acta (BBA)-General Subjects*, 1862(9):2043–2052, 2018.

Ali Razavi, Aaron van den Oord, and Oriol Vinyals. Generating diverse high-fidelity images with vq-vae-2. In *Advances in neural information processing systems*, pp. 14866–14876, 2019.

Schrödinger, LLC. The AxPyMOL molecular graphics plugin for Microsoft PowerPoint, version 1.8. November 2015a.

Schrödinger, LLC. The JyMOL molecular graphics development component, version 1.8. November 2015b.

Schrödinger, LLC. The PyMOL molecular graphics system, version 1.8. November 2015c.

Daniel Schwalbe-Koda and Rafael Gómez-Bombarelli. Generative models for automatic chemical design. In *Machine Learning Meets Quantum Physics*, pp. 445–467. Springer, 2020.

Yimin Shen, Julien Maupetit, Philippe Derreumaux, and Pierre Tuffery. Improved pep-fold approach for peptide and miniprotein structure prediction. *Journal of chemical theory and computation*, 10(10):4745–4758, 2014.

Chence Shi, Minkai Xu, Zhaocheng Zhu, Weinan Zhang, Ming Zhang, and Jian Tang. Graphaf: a flow-based autoregressive model for molecular graph generation. In *International Conference on Learning Representations*, 2019.

Jonathan M Stokes, Kevin Yang, Kyle Swanson, Wengong Jin, Andres Cubillos-Ruiz, Nina M Donghia, Craig R MacNair, Shawn French, Lindsey A Carfrae, Zohar Bloom-Ackermann, et al. A deep learning approach to antibiotic discovery. *Cell*, 180(4):688–702, 2020.

Shaini Thomas, Shreyas Karnik, Ram Shankar Barai, Vaidyanathan K Jayaraman, and Susan Idicula-Thomas. Camp: a useful resource for research on antimicrobial peptides. *Nucleic acids research*, 38(suppl_1):D774–D780, 2010.

Marcelo Der Torossian Torres and Cesar de la Fuente-Nunez. Toward computer-made artificial antibiotics. *Current opinion in microbiology*, 51:30–38, 2019.

Aaron van den Oord, Oriol Vinyals, and Koray Kavukcuoglu. Neural discrete representation learning. In *Proceedings of the 31st International Conference on Neural Information Processing Systems*, pp. 6309–6318, 2017.

Colin M Van Oort, Jonathon B Ferrell, Jacob M Remington, Safwan Wshah, and Jianing Li. Ampgan v2: Machine learning-guided design of antimicrobial peptides. *Journal of Chemical Information and Modeling*, 2021.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. In Isabelle Guyon, Ulrike von Luxburg, Samy Bengio, Hanna M. Wallach, Rob Fergus, S. V. N. Vishwanathan, and Roman Garnett (eds.), *Proc. of NeurIPS*, pp. 5998–6008, 2017.

Daniel Veltri, Uday Kamath, and Amarda Shehu. Deep learning improves antimicrobial peptide recognition. *Bioinformatics*, 34(16):2740–2747, 2018.

Guangshun Wang, Xia Li, and Zhe Wang. Apd3: the antimicrobial peptide database as a tool for research and education. *Nucleic acids research*, 44(D1):D1087–D1093, 2016.

Jacob Witten and Zack Witten. Deep learning regression model for antimicrobial peptide design. *BioRxiv*, pp. 692681, 2019.

Yutong Xie, Chence Shi, Hao Zhou, Yuwei Yang, Weinan Zhang, Yong Yu, and Lei Li. Mars: Markov molecular sampling for multi-objective drug discovery. In *International Conference on Learning Representations*, 2020.

A APPENDIX

A.1 ATTRIBUTE DISTRIBUTION

To determine the threshold of net charge, hydrophobicity, and hydrophobic moment, we analyze the distribution of sequences in APD and decoy in Figure 4. For charge, we follow the rule summarized by specialists and choose sequences whose net charge is +2 to +10. For two characters left, we plot the histogram and compare the proportion in every bin. If the proportion of APD is larger than that in decoy, we add the bin into the acceptation range of the evaluation metric. The final ranges are $C \in [2, 10]$, $H \in [0.25, \infty]$, and $uH \in [0.5, 0.75] \cup [1.75, \infty]$.

Figure 4: The histogram of charge, hydrophobicity and hydrophobic moment on APD and decoy dataset.

A.2 GENERATED AMPS

We show 10 peptides generated by `LSSAMP` in Table 5, and build 3D models for four of them by PEPFold 3 (Shen et al., 2014) and draw the picture by PyMOL (Schrödinger, LLC, 2015c;a;b) in Figure 5. We can find that all these peptides have long helix structures, which make them more likely to have the antimicrobial ability. At the same time, although the model predicts a long continuous helix structure for peptide $ID = 4$ and $ID = 9$, in fact, they have a small coil structure between two helix structures. It indicates that our model tends to predict a long continuous secondary structure instead of several discontinuous small fragments.

ID	Sequence	Secondary Structure	C	H	uH
1	FLPLVRVWAKLI	–HHHHHHHHHH	2.0	0.471	0.723
2	FLSTVPYVAFKVVPTLFCPIAKTC	–HHHHHHHHHHHHHHHHHHHHT–	2.0	0.446	1.812
3	FFGVLARGIKSVVKHVMGLLMG	–HHHHHHHHHHHHHHHHHHH–	3.0	0.420	0.549
4	GVLPAFKQYLPGIMKIIVKF	–HHHHHHHHHHHHHH—	3.0	0.419	0.523
5	VFTLLGAIIHHLGNFVKRFSHVF	-HHHHHHHHHHHHHHHHHHHH–	2.0	0.416	0.514
6	FVPGLIKAAVGIGYTIFCKISKACYQ	–HHHHHHHHHHHHHHHHHHHHT—-	3.0	0.394	1.815
7	ALWCQMLTGIGKLAGKA	–HHHHHHHHHHHHHH	2.0	0.344	0.506
8	LLTRIIVGAISAVTSLIKKS	–HHHHHHHHHHHHHHH–	3.0	0.334	0.531
9	FLSVIKGVWAASLPKQFCAVTAKC	–HHHHHHHHHHHHHHHHHHHHT–	3.0	0.334	0.660
10	FLNPIIKIATQILVTAIKCFLKKC	–HHHHHHHHHHHHHHHHHHHHT–	4.0	0.334	1.940

Table 5: Ten generated peptides and their physical attributes and predicted structures. 'H' is the α-helix, 'T' is the Turn and '-' is the coil.

A.3 STRUCTURE CONDITION

As described above, controlling the secondary structure can affect the properties of generated peptides. Thus we limit the percentage of the coil structure with different ratio and calculate the physical attributes of generated peptides. The results are shown in Figure 6. We can find that with the decrease of number of coil structures, the percentage of positive peptides keep growing. However, for

(a) ID=1   (b) ID=4   (c) ID=9   (d) ID=10

Figure 5: 3D structures for sequence **FLPLVRVWAKLI**, **GVLPAFKQYLPGIMKIIVKF**, **FLSVIKGVWAASLPKQFCAVTAKC**, **FLNPIIKIATQILVTAIKCFLKKC**. ID corresponds to Table 5.

hydrophobicity and hydrophobic moment, the percentage drop after 0.3. Therefore, we limit the length of the coil structure to 30% in our main experiments.

Figure 6: The physical attributes of peptides with different percentage of the coil structure. The x-axis is the maximum percentage and y-axis is the percentage of peptides that meet the attribute range.