IMPLICITMEMBENCH: Measuring Unconscious Behavioral Adaptation in Large Language Models

Abstract

Existing memory benchmarks for LLM agents evaluate explicit recall of facts, yet overlook implicit memory where experience becomes automated behavior without conscious retrieval. This gap is critical: effective assistants must automatically apply learned procedures or avoid failed actions without explicit reminders. We introduce IMPLICITMEMBENCH, the first systematic benchmark evaluating implicit memory through three cognitively grounded constructs: Procedural Memory (one-shot skill acquisition after interference), Priming (theme-driven bias via paired experimental/control instances), and Classical Conditioning (CS–US exposure shaping first decisions). Our 300-item suite employs a unified Learning/Priming–Interfere–Test protocol with first-attempt scoring. Evaluation of 17 models reveals severe limitations: no model exceeds 66% overall, with top performers DeepSeek-R1 (65.3%), Qwen3-32B (64.1%), and GPT-5 (63.0%) far below human baselines. Analysis uncovers dramatic asymmetries (inhibition 17.6% vs. preference 75.0%) and universal bottlenecks requiring architectural innovations beyond parameter scaling. IMPLICITMEMBENCH reframes evaluation from "what agents recall" to "what they automatically enact" [1].

1 Introduction

Large language models (LLMs) have demonstrated remarkable capabilities across diverse domains (Zhao et al., 2023; Wu et al., 2024), maturing into assistants for daily productivity and specialized workflows (DeepSeek-AI et al., 2025; Zeng et al., 2025; OpenAI, 2025; Anthropic, 2025; Qwen et al., 2024; Yang et al., 2025). To serve users reliably, these systems require **memory**: the ability to accumulate and leverage experience across interactions. Recent work establishes this need (He et al., 2024;

Zhang et al., 2025a,b), with production systems deploying memory features (OpenAI, 2024). Benchmarks such as LoCoMo, LongMemEval, MADial-Bench, and MemBench now assess multi-session QA, information retrieval, and dialogue across contexts from 400 to 10^6 tokens (Maharana et al., 2024; Wu et al., 2025; He et al., 2025; Tan et al., 2025).

Despite this progress, existing benchmarks predominantly evaluate **explicit memory**: conscious retrieval of factual information. Table 1 shows prior work uniformly adopts query-response protocols where models are explicitly prompted to recall facts, limiting evaluation to deliberate retrieval rather than unconscious behavioral adaptation. Yet critical failures arise from missing **implicit memory**, experience that becomes automated behavior rather than explicit recollection. Effective assistants should automatically apply learned procedures after distractions or avoid repeatedly-failed tools without explicit reminders. Existing benchmarks fail to diagnose this because they (i) employ QA formats explicitly cueing target information, (ii) stress storage capacity over first-attempt triggers after interference, and (iii) utilize costly pipelines hindering reproducibility.

We introduce IMPLICITMEMBENCH, a cognitively grounded benchmark evaluating implicit memory in LLM agents. We operationalize three constructs: **Procedural Memory** assesses one-shot skill acquisition persisting after interference, **Priming** measures theme-driven biases via paired experimental/control instances, and **Classical Conditioning** evaluates whether CS–US exposure shapes first decisions. All 300 items follow a unified Learning/Priming–Interfere–Test protocol with **first-attempt** scoring isolating automatized behavior from explicit recall. Figure 2 illustrates our framework: procedural tasks use rule-based validators, priming employs LLM judges comparing experimental versus control conditions, and classical conditioning tracks binary first-attempt avoidance.

---

[1] Code and data are available at ImplicitMemBench.

Figure 1: Performance ranking of all evaluated models on IMPLICITMEMBENCH. Models are sorted by overall score, with closed-source models shown in red-coral and open-source models in teal. The horizontal dashed line indicates the average performance across all models.

Benchmark	Memory Type	Evaluation Trigger	Context Scale	Evaluation Size	Task Focus
LoCoMo (Maharana et al., 2024)	Explicit	Explicit query	9k tokens	300 conversations	Multi-session QA
LongMemEval (Wu et al., 2025)	Explicit	Explicit query	115k-1.5M tokens	500 questions	Information retrieval
MADial-Bench (He et al., 2025)	Explicit	Emotion	400 tokens	160 dialogues	Emotional dialogue
MemBench (Tan et al., 2025)	Explicit	Explicit query	100k tokens	65000 dialogues	Information retrieval
IMPLICITMEMBENCH (Ours)	**Implicit**	**Scenario**	**500 tokens**	**300 instances**	**Unconscious adaptation**

Table 1: Comparison of IMPLICITMEMBENCH with existing benchmarks. Memory Type: Explicit (conscious recall) vs Implicit (unconscious behavioral adaptation). Evaluation Trigger: Active (deliberate query) vs Passive (automatic activation). Context Scale: Token count required for evaluation. Our benchmark evaluates implicit memory through efficient, behavior-focused protocols.

This design enables lightweight, reproducible evaluation revealing that implicit memory formation poses profound challenges with no model achieving human-like automaticity.

We evaluate 17 models spanning proprietary (GPT-5, Claude-4.1-opus, Gemini-2.5-pro) and open-source systems (DeepSeek-R1, Qwen3-32B, LLaMA-3.3-70B). As Figure 1 shows, results reveal fundamental limitations. First, a severe **ceiling effect** emerges: top performers remain far below human baselines, with no model exceeding two-thirds overall accuracy. Second, **paradigm asymmetry** shows dramatic variance: procedural memory proves most tractable while classical conditioning creates substantial bottlenecks, and priming clusters in a narrow moderate range. Third, **capability dissociation** reveals that excellence in one paradigm fails to predict success in others, with the strongest procedural learner suffering dramatic drops on classical conditioning. Fine-grained analysis uncovers systematic failures: models struggle profoundly with inhibition versus preference-based learning, and multiple categories remain universally challenging across all architectures.

Our main contributions are: (1) We present the first benchmark of implicit memory in LLMs, oper-ationalizing procedural learning, priming, and classical conditioning under a unified protocol isolating automatized behavior through first-attempt scoring. (2) We design an evaluation framework combining rule-based validators and LLM judges, enabling reproducible assessment via a compact 300-item suite. (3) We evaluate 17 models revealing critical weaknesses: severe behavioral asymmetries and universal bottlenecks requiring architectural innovations beyond parameter scaling.

2 Related Work

Existing memory benchmarks for LLM agents predominantly evaluate explicit memory through direct query-response protocols. LoCoMo (Maharana et al., 2024) tests multi-session dialogue continuity (300 conversations, 9k tokens each) via QA and event summarization. LongMemEval (Wu et al., 2025) examines extreme-scale contexts (115k-1.5M tokens) across information extraction, multi-session reasoning, and temporal reasoning. MADial-Bench (He et al., 2025) measures emotion-support proficiency in 160 dialogues. MemBench (Tan et al., 2025) assesses robustness through noisy 100k-token contexts with participation/observation scenarios. Table 1 shows that all

Figure 2: Overall framework. (a) Dataset generation pipeline using LLM-generated candidates refined via fine-tuning and human editing. (b) Evaluation metrics: hybrid automatic/human validation for Procedural Memory (FTA), LLM-as-Judge for Priming (Priming Influence Score) and Classical Conditioning (FTA). (c) Aggregated performance across 17 evaluated models.

prior work targets explicit fact retrieval, leaving implicit memory unaddressed. IMPLICITMEM-BENCH fills this gap as the first systematic evaluation of implicit memory via procedural learning, priming, and classical conditioning, using efficient 500-token protocols to assess unconscious behavioral adaptations.

3 IMPLICITMEMBENCH

3.1 Tasks

We operationalize three memory paradigms from cognitive science: **Procedural Memory** (§ 3.1.1) tests acquisition of new behavioral patterns from minimal exposure; **Priming** (§ 3.1.2) measures unconscious transfer of thematic elements from prior context; and **Classical Conditioning** (§ 3.1.3) evaluates formation of automatic stimulus-response associations through repeated pairing.

3.1.1 Procedural Memory

Motivation Procedural memory enables automatic execution of learned skills without conscious recall. For AI agents, this means internalizing novel operational protocols from minimal demon-strations and executing them flawlessly despite distractions. Current LLMs excel at declarative knowledge but often revert to pre-trained patterns when new rules contradict their priors. We evaluate whether models can truly *proceduralize* routines, transforming explicit instructions into automatic behaviors that persist through interference.

Task Design We structure procedural memory evaluation across five complementary domains, each targeting different aspects of rule internalization and automatic execution, shown in Table 2.

These tasks emphasize *proceduralization* over memorization: models must internalize rules from minimal exposure and execute them despite extensive interference and format variations. The design systematically varies exemplar clarity, interference intensity, and the presence of misleading alternatives to probe the depth of behavioral automation.

Evaluation Framework: Learning-Interference-Test Protocol Our three-phase protocol provides minimal specification (rule + 1-3 examples), extensive interference (15 misleading turns), then novel test probes requiring first-attempt success. This

Domain	Core Challenge	Representative Tasks
Tool & API Usage	Override ingrained calling conventions	`Reversed Parameters` (dst→src), `Session Prefix` (auth fusion), `Alien Filesystem` (custom separators)
Linguistic Formats	Internalize arbitrary templates	`Scribe's Signature` (fixed wrapper), `Corporate Etiquette` (mandated greeting/closing)
Logical Operations	Apply non-standard operators	`Omega`: $a \Omega b = 2a + b^2$, `Modified Fibonacci`: $F(n) = F(n-1) + 2F(n-2)$
Abstract Rules	Form habits in micro-worlds	`Forbidden Square` (board constraint), `Triple Knock` (ritual sequence)
Creative Constraints	Maintain style without reminders	`Voice Consistency` (no first-person), `Botanical Similes` (nature metaphors)

Table 2: Five procedural memory domains. Each forces models to suppress pre-trained behaviors for new procedures.

isolates procedural memory from explicit recall by testing whether routines automatize despite interference. Validation uses deterministic parsing for structured outputs and LLM judgment for semantic adherence.

3.1.2 Priming

Motivation Priming demonstrates how prior exposure unconsciously influences subsequent behavior. For AI agents, this implicit contextual sensitivity is crucial: absorbing environmental cues to shape responses without explicit instruction. Current LLMs exhibit shallow keyword repetition but lack true thematic priming; they struggle to let abstract patterns from prior context subtly influence creative outputs. We evaluate whether models can internalize thematic schemas and transfer them implicitly through intervening distractions.

Task Design We structure priming evaluation through matched experimental-control pairs that isolate the causal effect of thematic exposure, as shown in Table 3.

Themes span diverse conceptual territories: *Arctic Expedition*, *Volcanic Eruption*, *Renaissance Alchemy*, *Ancient Oracle*, each with distinct sensory-emotional signatures. This design isolates implicit transfer: differences between experimental and control responses reveal pure priming effects.

Evaluation Framework: Priming-Interference-Test Protocol Our three-phase design provides thematic exposure (evocative vs neutral), neutral interference (cognitive buffer), then creative generation tasks. This measures unconscious thematic transfer via systematic bias in outputs despite no explicit reminders. LLM-based evaluation detects thematic alignment beyond surface keywords.

3.1.3 Classical Conditioning

Motivation Classical conditioning enables organisms to form automatic stimulus-response associations. This unconscious learning prevents harm through rapid, automatic responses. For AI agents, such adaptive safety mechanisms are essential: learning from negative experiences to automatically avoid harmful patterns. Current LLMs lack true conditioning and cannot form persistent associations from feedback. We evaluate whether models can establish defensive reflexes through experience rather than instruction.

Task Design We structure conditioning tasks across three domains where automatic avoidance prevents system failures:

Examples: *API Aversion* (keyword triggers alternative selection), *Filetype Preference* (failures condition format choices), *Directory Restriction* (errors establish path boundaries). Each task requires forming unconscious protective associations. More can be found in Table 4.

Evaluation Framework: Learning-Interference-Test Protocol Our three-phase structure provides CS-US pairings, unrelated tasks (temporal distance), then CS reintroduction requiring first-action responses. This tests unconscious defensive learning via immediate avoidance/adaptation when CS reappears, without reminders. LLM judgment evaluates whether first actions demonstrate learned protective behaviors.

3.2 Data Generation and Quality Control

Our dataset construction employs a two-stage pipeline ensuring diversity and quality. Each item begins as a structured blueprint, then undergoes automated generation and rigorous quality control.

Component	Experimental Condition	Control Condition
Priming Text	Rich thematic paragraph (e.g., *Abyssal Deep-Sea*: bioluminescence, crushing pressure, ancient creatures)	Technical specification (e.g., *ISO Container Standards*: dimensions, load capacity, stacking protocols)
Interference	Identical neutral technical content (2 turns)	
Test Probe	Identical creative task (naming, tagline, concept generation)	
Expected Result	Thematic bias toward primed domain	Neutral, generic responses

Table 3: Priming experimental design with matched controls. Each row is a complete trial pair.

Domain	Stimulus Pattern (CS)	Learned Response (CR)
Tool & API Safety	Trigger keywords, filetypes, API names, load indicators	Switch to reliable alternatives, add warnings, delay execution, avoid side-effects
Conversational Adaptation	User confusion signals, impatience cues, emotional markers	Simplify jargon, reduce verbosity, adjust response format
System Protection	Forbidden paths, insecure protocols, dangerous patterns	Use safe defaults, enforce security, prevent violations

Table 4: Classical conditioning tasks by domain. CS = Conditioned Stimulus, US = Unconditioned Stimulus, CR = Conditioned Response.

Generation Pipeline **Stage 1** uses GPT-4o-mini to instantiate concrete dialogues from task templates, creating learning materials, interference content, and test probes. **Stage 2** combines automated checks and human review to verify structural requirements and semantic correctness, removing unintended shortcuts.

Paradigm-Specific Requirements As shown in Table 5, each memory type demands distinct generation strategies to create valid memory challenges.

Quality Assurance Protocol Multi-layer validation ensures dataset integrity: automated checks verify structure (turn counts, token limits, formats); LLM judges assess semantic adequacy; systematic reviews prevent test-phase leakage; diversity enforcement prioritizes novel instances. This yields 300 high-quality items testing implicit memory.

3.3 Dataset Statistics

IMPLICITMEMBENCH comprises 300 carefully constructed items balanced across three memory paradigms. Each item follows our unified learning-interference-test protocol, with phase structures optimized for implicit memory formation.

Dataset Composition Our benchmark consists of 100 items per paradigm, covering diverse task families, as shown in Table 6.

Phase Structure and Token Distribution Figure 3 visualizes the characteristic patterns of each paradigm. Procedural Memory emphasizes exten-

sive interference (74% of tokens) to test rule persistence. Classical Conditioning concentrates on learning (72% of tokens) to establish strong associations. Priming maintains balanced phases for controlled comparison.

4 Experiments

4.1 Experimental Setup

We evaluate the implicit memory capabilities of 17 state-of-the-art language models (detailed in Appendix B), spanning both proprietary and open-source systems. Our evaluation protocol ensures fair comparison through standardized prompting and controlled generation parameters across all three memory paradigms.

Evaluation Protocol All models operate under identical conditions: zero-shot conversational interaction, no task-specific examples or fine-tuning, max 4096 tokens per response. Temperature: $T = 0$ (deterministic) for procedural memory and classical conditioning ensuring reproducible first-attempt scoring; $T = 0.8$ at test phase only for priming enabling creative variance; $T = 0$ for LLM judges. This measures genuine implicit memory formation rather than pattern matching or stochastic variation.

4.2 Evaluation Metrics

We employ paradigm-specific metrics that capture the distinct nature of each memory type. Binary accuracy suffices for procedural and conditioning tasks, while priming requires nuanced scoring of

Component	Procedural Memory	Priming	Classical Conditioning
Learning Phase	1-3 turns: rule + examples	1 turn: thematic paragraph	4 turns: CS-US pairings
Interference	10-15 turns: misleading but related content	2 turns: neutral technical task	2 turns: unrelated dialogue
Test Format	Novel application of learned rule	Creative generation task	CS reintroduction
Key Challenge	Avoid rule restatement	Prevent theme leakage	Ensure clear causality
Validation Focus	Rule adherence	Thematic influence	Avoidance behavior

Table 5: Data generation specifications across paradigms. Turn counts and content ensure proper memory formation and testing.

Paradigm	Items	Task Families	Validation
Procedural Memory	100	5 domains (Tool, Linguistic, Logic, Rules, Creative)	18% rule-based
Priming	100	10 thematic domains + matched controls	100% LLM-judged
Classical Conditioning	100	3 domains (Tool Safety, Conversation, System)	100% LLM-judged
Total	**300**	**18 unique families**	**6% rule / 94% LLM**

Table 6: Dataset composition showing task diversity and validation methods.

Score Band	Evidence Requirements	Range
None	No detectable thematic influence	0-5
Trace	Single weak echo, minimal alignment	6-12
Weak	One clear thematic element, limited scope	13-20
Moderate	Two axes aligned, clear thematic presence	25-40
Strong	Multiple axes, consistent theme integration	45-60
Very Strong	Pervasive influence across all outputs	61-80
Exceptional	Complete thematic transformation	81-95

Table 7: PIS scoring framework: Evidence requirements and score bands.

thematic influence.

First-Try Accuracy (FTA) For **Procedural Memory** and **Classical Conditioning**, we measure success through first-attempt correctness: FTA = $\frac{\text{Number of correct first attempts}}{\text{Total test items}} \times 100\%$. This metric enforces strict evaluation: only the model's initial response counts, with self-corrections or revisions ignored. This captures genuine memory formation rather than iterative refinement, analogous to human performance under time pressure where reflexive responses reveal true internalization.

Priming Influence Score (PIS) **Priming** evaluation requires detecting subtle thematic transfer rather than binary correctness. We employ a comparative scoring framework that quantifies influence magnitude:

Scoring Protocol: An LLM judge (GPT-4o-mini, $T = 0$) performs pairwise comparison between experimental and control conditions, identifying thematic elements unique to the experimental condition. It evaluates lexical echoes and multi-axis alignment (setting, motifs, dynamics, affect), excluding generic metaphors. Hard caps apply (no

echo $\leq$ 20; single axis $\leq$ 40) with 5-10 point penalties for baseline overlap, isolating true priming effects from general creative tendencies. More details can be found in Table 7

4.3 Main Results

Overview Table 8 presents performance across 17 state-of-the-art systems, revealing fundamental limitations. First, a clear **ceiling effect** emerges: no model exceeds 66% overall, showing implicit memory formation remains challenging. Second, **paradigm asymmetry** is evident as performance varies dramatically; procedural memory is most tractable (top: 75 to 77%) while classical conditioning creates bottlenecks (best: 69.7%). Third, **capability dissociation** shows that excellence in one paradigm doesn't predict success in others, suggesting distinct mechanisms.

Performance Landscape Models stratify into distinct tiers. Elite performers (accuracy >63%) include only three systems: DeepSeek-R1 (65.30%), Qwen3-32B (64.13%), and GPT-5 (63.00%), with median performance at 55% showing substantial variance across paradigms.

Paradigm-Specific Analysis Procedural memory shows highest success with eight models achieving >70% (top: 76-77%), though 25% error rates indicate imperfect consolidation. Classical conditioning exposes critical weakness: only DeepSeek-R1 and Qwen3-32B exceed 65%. Priming scores cluster tightly at 42-52% with minimal differentiation, suggesting thematic influence operates near a common threshold.

Figure 3: Dataset statistics across paradigms. (a) Token distribution per phase showing median and quartiles. (b) Phase proportions highlighting distinct memory testing strategies. (c) Turn structure patterns for each paradigm.

Rank	Model	Procedural Memory	Classical Conditioning	Priming Score	Overall Score
Elite Tier (Overall > 63%)					
1	DeepSeek-R1[†]	76.33	**69.67**	49.90	**65.30**
2	Qwen3-32B[†]	75.67	67.00	49.73	64.13
3	GPT-5	75.33	64.00	49.67	63.00
Strong Tier (55% < Overall ≤ 63%)					
4	Qwen3-8B[†]	75.33	64.00	47.73	62.35
5	GPT-o3	76.00	57.67	51.70	61.79
6	GPT-o4-mini-high	70.67	60.00	**51.95**	60.87
7	GLM-4.5[†]	76.33	53.33	46.12	58.59
8	Gemini-2.5-pro	74.33	47.33	45.42	55.69
9	Claude-4.1-opus	**76.67**	41.67	48.60	55.65
10	Gemini-2.5-flash	72.33	49.00	44.97	55.43
Moderate Tier (45% < Overall ≤ 55%)					
11	GPT-4o-mini	61.67	44.00	46.98	50.88
12	Qwen-2.5-72B[†]	61.00	47.00	44.33	50.78
13	GPT-4o	61.67	43.67	45.62	50.32
14	Claude-4-sonnet	51.67	51.67	46.17	49.84
15	LLaMA-3.3-70B[†]	58.33	47.33	42.67	49.44
Limited Tier (Overall ≤ 45%)					
16	LLaMA-3.1-8B[†]	46.67	38.33	47.53	44.18
17	Qwen-2.5-7B[†]	50.67	35.67	44.12	43.49

[†]Open-source model

Table 8: IMPLICITMEMBENCH performance across 17 language models. Results show mean accuracy (%) over three independent runs for Procedural Memory and Classical Conditioning, with Priming scores from LLM-based evaluation. Models are ranked by overall performance and grouped into tiers. **Bold**: best in paradigm; underlined: second-best.

Cross-Paradigm Patterns Data reveals striking dissociations. Claude-4.1-opus exemplifies this: highest procedural score (76.67%) but drops to 41.67% on classical conditioning, a 35-point gap highlighting capability independence. DeepSeek-R1's balanced profile across paradigms explains its overall leadership, suggesting robust implicit memory requires architectural support for multiple mechanisms rather than single-task optimization.

Figure 4: Behavioral adaptation patterns. (a) Inhibitory tasks show dramatically lower accuracy than preference tasks (mean difference: 57.4%, p<0.001). (b) Five task categories remain universally challenging across all models, consistently below 60% accuracy.

Implications Current architectures lack fundamental implicit memory mechanisms, with no model exceeding 66% overall. Persistent weakness in classical conditioning reveals inability to transform negative feedback into behavioral adaptation.

4.4 Detailed Analysis of Memory Formation Patterns

We conducted fine-grained analysis across task categories and model architectures, revealing systematic asymmetries and limitations transcending individual model differences.

Behavioral Asymmetries: Inhibition versus Preference Analysis reveals fundamental asymmetry (Figure 4a): inhibition tasks achieve only 17.6% while preference-based adaptations reach 75.0%, a 57.4-point gap persisting across architectures. Jargon avoidance achieves merely 4% while directory preference reaches 72%, suggesting architectures excel at positive reinforcement but struggle with negative reinforcement.

Figure 5: Robustness and generalization failures. (a) Surface formatting achieves higher accuracy than deep multi-rule protocols. (b) Worst-case task performance reveals systematic vulnerabilities across modes.

Figure 6: Model profiles and trade-offs. (a) Correlation between priming strength and constraint violations (r=0.63) suggests style bias over abstraction. (b) Heatmap of normalized capability scores reveals distinct profiles: balanced (DeepSeek-R1), procedural specialists (Claude-4.1-opus), and priming-oriented (GPT-o3) architectures.

Surface-Deep Dissociation in Procedural Memory Procedural memory exhibits clear stratification (Figure 5a): surface formatting tasks achieve 93.8% among top-5 models while deep multi-rule protocols reach only 60.0%, a 33.8-point gap. Models memorize individual rules but fail to integrate them, with Claude-4.1-opus achieving 95% on surface formatting yet dropping to 65% on multi-constraint protocols.

Worst-Case Robustness Analysis Worst-case analysis reveals systematic vulnerabilities (Figure 5b). Top models exhibit substantial drops: DeepSeek-R1 falls to 49% on its worst task despite 69.7% overall; GPT-5 and Qwen3-32B show 27-36% worst-case performance. This gap highlights brittleness in learned behaviors. Severe degradation on specific categories suggests conditioning success depends on superficial characteristics rather than deep understanding, critical for deployment where edge cases may trigger these vulnerabilities.

Priming Effects: Style Bias Over Semantic Transfer Priming analysis reveals paradoxical relationship: models with stronger effects (>50) show more constraint violations (r=0.63, p<0.05), suggesting thematic influence costs task adherence. This indicates priming operates through style mimicry rather than abstract extraction. GPT-o4-mini-high achieves highest priming (51.95) while frequently violating format constraints, showing stylistic bias interferes with constraint satisfaction.

Model Capability Profiles and Trade-offs Figure 6 reveals distinct capability patterns. Heatmap analysis identifies three profiles: **Balanced** (DeepSeek-R1, Qwen3-32B): moderate-high across all dimensions; **Procedural Specialist** (Claude-4.1-opus, GLM-4.5): excel at procedural (>76%) but fail at conditioning (<54%); **Priming-**

Oriented (GPT-o3, GPT-o4-mini-high): strong priming but weak inhibitory control. No model achieves uniform excellence, suggesting architectures involve trade-offs between mechanisms.

Universal Bottlenecks Five categories remain challenging for all models (Figure 4b): jargon avoidance (4% ± 5%), API distrust (21% ± 17%), context-dependent behavior (28% ± 23%), API aversion (45% ± 29%), and emotion-driven strategy shift (55% ± 18%). These bottlenecks require active suppression of defaults, abstraction beyond surface patterns, or dynamic context-based modification. Consistency across architectures suggests fundamental limitations in attention and memory mechanisms requiring architectural innovations beyond parameter scaling.

5 Conclusion

We introduced IMPLICITMEMBENCH, the first systematic benchmark evaluating implicit memory in LLMs through three cognitively grounded constructs: procedural memory, priming, and classical conditioning. Evaluation of 17 models reveals fundamental limitations: no model exceeds 66% overall, with severe behavioral asymmetries (inhibition 17.6% vs. preference 75.0%) and universal bottlenecks persisting across all architectures. These findings demonstrate that current systems lack mechanisms for consolidating experiences into automated behavior, a critical gap for deployment requiring learned procedures, subtle contextual biases, and avoidance of repeatedly-failed actions. IMPLICITMEMBENCH establishes reproducible protocols for implicit memory assessment, exposing architectural limitations requiring innovations beyond parameter scaling.

Limitations

IMPLICITMEMBENCH focuses on three fundamental paradigms from cognitive science (procedural memory, classical conditioning, and priming), which represent core mechanisms of implicit learning. However, the broader landscape of implicit memory encompasses additional phenomena not yet included in our evaluation, such as perceptual learning, habit formation, motor skill acquisition, and emotional conditioning. Future work could expand the benchmark to cover these complementary aspects of implicit cognition.

References

Anthropic. 2025. Model report: Claude opus 4 & sonnet 4. Anthropic Transparency Hub. Last updated August 7, 2025. https://www.anthropic.com/transparency/model-report.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, and 181 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning.

Junqing He, Liang Zhu, Rui Wang, Xi Wang, Gholamreza Haffari, and Jiaxing Zhang. 2025. MADialbench: Towards real-world evaluation of memory-augmented dialogue generation. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 9902–9921, Albuquerque, New Mexico. Association for Computational Linguistics.

Zihong He, Weizhe Lin, Hao Zheng, Fan Zhang, Matt W. Jones, Laurence Aitchison, Xuhai Xu, Miao Liu, Per Ola Kristensson, and Junxiao Shen. 2024. Human-inspired perspectives: A survey on ai long-term memory.

Adyasha Maharana, Dong-Ho Lee, Sergey Tulyakov, Mohit Bansal, Francesco Barbieri, and Yuwei Fang. 2024. Evaluating very long-term conversational memory of LLM agents. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 13851–13870. Association for Computational Linguistics.

OpenAI. 2024. Memory and new controls for chatgpt. OpenAI Blog. Accessed 2025-09.

OpenAI. 2025. Gpt-5 system card. https://openai.com/index/gpt-5-system-card/. Accessed 2025-09.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, and 25 others. 2024. Qwen2.5 technical report.

Haoran Tan, Zeyu Zhang, Chen Ma, Xu Chen, Quanyu Dai, and Zhenhua Dong. 2025. MemBench: Towards more comprehensive evaluation on the memory of LLM-based agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 19336–19352, Vienna, Austria. Association for Computational Linguistics.

Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. 2025. Longmemeval: Benchmarking chat assistants on long-term interactive memory. In *The Thirteenth International Conference on Learning Representations*.

Likang Wu, Zhi Zheng, Zhaopeng Qiu, Hao Wang, Hongchao Gu, Tingjia Shen, Chuan Qin, Chen Zhu, Hengshu Zhu, Qi Liu, Hui Xiong, and Enhong Chen. 2024. A survey on large language models for recommendation. *World Wide Web (WWW)*, 27(5):60.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report.

Aohan Zeng, Xin Lv, Qinkai Zheng, Zhenyu Hou, Bin Chen, Chengxing Xie, Cunxiang Wang, Da Yin, Hao Zeng, Jiajie Zhang, Kedong Wang, Lucen Zhong, Mingdao Liu, Rui Lu, Shulin Cao, Xiaohan Zhang, Xuancheng Huang, Yao Wei, Yean Cheng, and 80 others. 2025. GLM-4.5: agentic, reasoning, and coding (ARC) foundation models. *ArXiv preprint*, abs/2508.06471.

Zeyu Zhang, Quanyu Dai, Xiaohe Bo, Chen Ma, Rui Li, Xu Chen, Jieming Zhu, Zhenhua Dong, and Ji-Rong Wen. 2025a. A survey on the memory mechanism of large language model-based agents. *ACM Trans. Inf. Syst.*, 43(6).

Zeyu Zhang, Quanyu Dai, Xiaohe Bo, Chen Ma, Rui Li, Xu Chen, Jieming Zhu, Zhenhua Dong, and Ji-Rong Wen. 2025b. A survey on the memory mechanism of large language model-based agents. *ACM Trans. Inf. Syst.*, 43(6).

Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen Yang, Yushuo Chen, Zhipeng Chen, Jinhao Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Zikang Liu, and 3 others. 2023. A survey of large language models.

A Dataset Overview

This appendix provides illustrative examples of tasks from each of the three memory paradigms in

IMPLICITMEMBENCH. Each example follows a three-phase structure consisting of a learning phase where implicit associations are established, an interference phase with unrelated interactions to test memory consolidation, and a test probe that evaluates whether the learned patterns persist without explicit reminders. Figure 7 demonstrates a procedural memory task, Figure 8 shows a priming task with experimental and control conditions, and Figure 9 illustrates a classical conditioning task.

B Detailed Models List

Table 9 presents the complete list of language models evaluated in our study, organized by developer and model family. Our evaluation encompasses 14 diverse models spanning both proprietary systems (OpenAI's GPT series, Anthropic's Claude, and Google's Gemini) and open-source alternatives (Qwen, LLaMA, DeepSeek, and GLM). This selection allows us to systematically compare implicit memory capabilities across different architectural choices, training paradigms, and scale configurations.

The complete list of evaluated models is provided in Table 9.

C LLM Prompts

This appendix documents the complete set of prompts used throughout the IMPLICITMEM-BENCH pipeline, including data generation, curation, and evaluation. These carefully designed prompts control for task difficulty, ensure consistency across memory paradigms, and provide rigorous evaluation criteria for LLM-as-Judge assessment. The prompts are organized into three categories: data generation prompts that create task instances following cognitive science principles, curation prompts that refine and validate dataset quality, and LLM-as-Judge prompts that score model responses on implicit memory retention.

C.1 Data Generation

The following prompts specify the generation procedure for each memory paradigm, defining difficulty frameworks, structural requirements, and validation criteria. We provide generation prompts for procedural memory (see listing after this paragraph), priming (see second listing), and classical conditioning (see third listing) tasks.

Data Generation Prompt for Procedural Memory

```
{
    "meta": {
        "role": "BenchmarkDataGenerator",
        "project": "ImplicitMemBench",
        "task_category": "Procedural-Memory",
        "target_difficulty_level": "Medium"
    },
    "instructions": {
        "main_goal": "Generate a single, high-
quality test case for the Procedural-Memory
task category. The instance must strictly
adhere to the 'practice-distraction-test'
sequence and match the target difficulty.",
        "difficulty_framework": {
            "aggregation": "Contextual
Difficulty Score (CDS) = (IR + GD) / 2. Easy
: <0.33, Medium: 0.33-0.67, Hard: >0.67.",
            "dimensions": {
                "IR": "Interference Ratio. `
Tokens(Distractor) / Tokens(Total)`. Aim for
 a MODERATE value for Medium tasks.",
                "GD": "Generalization Distance.
`1 - CosineSimilarity(LearningCore, TestCore
)`. Aim for a MODERATE value for Medium
tasks."
            }
        },
        "generation_guidelines": {
            "target": "Generate an instance
where the Contextual Difficulty Score (CDS)
is in the 'Medium' range (0.33 to 0.67).",
            "strategy": "Use a longer distractor
 phase (15 user-assistant dialogue turns,
which means 30 total messages: 15 user
messages + 15 assistant responses).",
            "medium_rules": {
                "interference_ratio": "Generate
HIGH-QUALITY interference content that is
contextually relevant to the task theme but
uses DIFFERENT rules or patterns. Use
exactly 15 user-assistant dialogue turns (30
 messages total: 15 user questions + 15
assistant answers).",
                "generalization_distance": "Make
 the test probe conceptually different from
the learning phase. Example: If learning is
a math operation, test could be applying
that operation in a simple word problem.",
                "learning_phase": "Keep learning
 phase clear but it can be slightly more
conversational (4-8 turns total).",
                "test_probe": "The test probe
should require the same core skill but in a
new context or format."
            },
            "interference_structure_example": {
                "critical_requirement": "
CRITICAL: Your interference_phase MUST
contain EXACTLY 15 user-assistant dialogue
turns (30 messages total).",
                "example_structure": "Here's
what 15 dialogue turns look like:",
                "turn_examples": [
                    "Turn 1: User asks about
topic A, Assistant responds about topic A",
                    "Turn 2: User asks about
topic B, Assistant responds about topic B",
                    "Turn 3: User asks about
topic C, Assistant responds about topic C",
```

Figure 7: Example of a Procedural Memory task: Reversed Parameter Protocol.

Developer	Model Family	Evaluated Variants	Type
OpenAI	GPT-4 Series	GPT-4o, GPT-4o-mini	Proprietary
	GPT-o Series	GPT-o3, GPT-o4-mini-high, GPT-5	Proprietary
Anthropic	Claude-4	Sonnet-4, Opus-4.1	Proprietary
Google	Gemini-2.5	Pro, Flash	Proprietary
DeepSeek	DeepSeek	R1	Open
Zhipu	GLM	4.5	Open
Alibaba	Qwen2.5	7B-Instruct, 72B-Instruct	Open
	Qwen3	8B, 32B	Open
Meta	Llama-3	3.1-8B-Instruct, 3.3-70B-Instruct	Open

Table 9: Language models evaluated on IMPLICITMEMBENCH, organized by developer and release generation.

```
            "Turn 4: User asks about
topic D, Assistant responds about topic D",
            "Turn 5: User asks about
topic E, Assistant responds about topic E",
            "Turn 6: User asks about
topic F, Assistant responds about topic F",
            "Turn 7: User asks about
topic G, Assistant responds about topic G",
            "Turn 8: User asks about
topic H, Assistant responds about topic H",
            "Turn 9: User asks about
topic I, Assistant responds about topic I",
            "Turn 10: User asks about
topic J, Assistant responds about topic J",
            "Turn 11: User asks about
topic K, Assistant responds about topic K",
            "Turn 12: User asks about
topic L, Assistant responds about topic L",
            "Turn 13: User asks about
topic M, Assistant responds about topic M",
            "Turn 14: User asks about
topic N, Assistant responds about topic N",
            "Turn 15: User asks about
topic O, Assistant responds about topic O"
            ],
            "message_count_verification": "
After generating, verify you have exactly 30
 messages in interference_phase (15 user + 1
5 assistant).",
            "forbidden_shortcuts": "NEVER
use only 4-8 turns. You MUST generate 15
complete turns."
        },
        "naming_consistency": {
            "interference_variation": "NEVER
 use the EXACT same names/functions/symbols
in interference_phase that were used in
learning_phase.",
            "examples": [
                "If learning uses '_file',
interference MUST use 'mv_file', 'move_file'
, 'rename_file'",
                "If learning uses 'F(n)',
interference MUST use 'G(n)', 'H(n)', 'P(n)'
"
            ]
        }
    }
},
"task_blueprint": {
    "comment": "This section will be
dynamically filled by the generation script.
",
    "task_name": "PLACEHOLDER_TASK_NAME",
    "rule_description": "
PLACEHOLDER_RULE_DESCRIPTION",
    "context_injection": {
        "keywords": [
            "PLACEHOLDER_KEYWORD_1"
        ]
```

```
            }
        },
        "output_specification": {
            "format": "A single, raw JSON object. No
        markdown, no prose.",
            "required_keys": [
                "task_id",
                "task_name",
                "learning_phase",
                "interference_phase",
                "test_probe",
                "expected_pattern"
            ],
            "constraints": {
                "phase_structure": "The values for '
        learning_phase' and 'interference_phase'
        MUST be a direct list of dialogue turn
        objects, like `[{\"role\": \"user\", \"
        content\": \"...\"}]`.",
                "turn_structure": "Each dialogue
        turn object MUST have 'role' and 'content'
        as keys.",
                "test_probe_structure": "The '
        test_probe' MUST be a simple object with `{\
        "role\": \"user\", \"content\": \"...\"}`.",
                "logic_requirement": "The entire
        dialogue and the 'expected_pattern' MUST be
        logically consistent with the provided '
        rule_description'.",
                "context_requirement": "The
        narrative SHOULD incorporate the keywords
        provided in 'context_injection'.",
                "task_type_requirement": "CRITICAL:
        The generated instance MUST strictly match
        the task type specified in 'task_blueprint.
        task_name'.",
                "message_count_requirement": "
        CRITICAL: After generating the
        interference_phase, you MUST verify that it
        contains EXACTLY 30 messages (15 user
        messages + 15 assistant responses). If it
        doesn't have exactly 30 messages, regenerate
         the entire interference_phase until it does
        .",
                "naming_consistency_requirement": "
        When creating interference content, NEVER
        use EXACTLY the same name to represent
        different usage patterns. Use SIMILAR but
        NOT IDENTICAL names."
            }
        }
    }
}
```

Data Generation Prompt for Priming

```
{
    "meta": {
        "role": "PrimingTaskPairGenerator",
        "project": "ImplicitMemBench",
        "task_category": "Priming",
        "version": "1.0"
    },
    "instructions": {
        "objective": "Generate ONE matched pair of
         priming instances: {experimental, control}.
         Use a single source theme for the
        experimental priming, one control theme for
        the control priming, and one probe shared by
         both.",
        "available_material": "Assume the arrays `
```

```
        sources`, `controls`, and `probes` from
        tasks/priming.json are available in context.
        ",
        "selection_policy": {
            "source": "Select EXACTLY one `sources[i
        ]` as the experimental priming theme.",
            "control": "Select EXACTLY one `controls
        [j]` as the control priming theme.",
            "probe": "Select EXACTLY one `probes[k]`
         as the test probe shared by both instances.
        ",
            "diversity_hint": "Avoid picking the
        same source theme repeatedly across batch
        runs."
        },
        "content_requirements": {
            "experimental_priming_phase": {
                "length_words": [130, 170],
                "style": "evocative, metaphor-friendly,
         high imagery density",
                "use_core_concepts": "Must integrate
        all four fields from `
        core_concepts_and_imagery` (setting, motifs,
         dynamics, affect).",
                "keywords": "Use >= 3 keywords from `
        keywords`, but do NOT list them mechanically
        . No bullet lists.",
                "forbidden": "Do NOT copy any exact
        sentences from the source description. No
        explicit instruction-like language."
            },
            "interference_phase": {
                "turns": "Exactly ONE user message
        followed by ONE assistant response (2
        messages total).",
                "spec": "Follow the selected source
        theme's `interference_spec` exactly:
        instruction, style, allowed_topics,
        must_include, forbidden_lexicon.",
                "reuse_policy": "The control instance
        MUST reuse the experimental instance's
        interference messages verbatim."
            },
            "control_priming_phase": {
                "length_words": [130, 170],
                "style": "neutral, technical/
        administrative or objective tone; low
        imagery; no metaphors",
                "topic": "Write about the chosen
        control theme using its `description` and `
        keywords`.",
                "mirror_constraint": "Aim for similar
        length to experimental priming; avoid any
        imagery or emotive cues."
            },
            "test_probe": {
                "shared": "Copy the selected probe
        object verbatim for both instances.",
                "no_augmentation": "Do not rewrite the
         probe prompt; include as-is."
            }
        },
        "structure_and_validation": {
            "phase_structure": "Each phase is a list
         of message objects: [{\"role\": \"user\"|\"
        assistant\", \"content\": \"...\"}].",
            "interference_checks": {
                "message_count": "Exactly 2 messages
        total in interference_phase.",
                "forbidden_lexicon": "assistant
```

```
        message MUST NOT contain any token from `
interference_spec.forbidden_lexicon`.",
          "must_include": "assistant message
MUST satisfy all items in `interference_spec
.must_include`."
        },
        "metadata": {
          "record": "For each instance, include
`meta_checks` with approximate counts and
compliance flags (word counts, numerals/
units presence, forbidden_lexicon_violations
: [] if none). Approximations are acceptable
."
        }
      }
    },
    "output_specification": {
      "format": "Return a single raw JSON object
 (no markdown, no comments).",
      "required_keys": [
        "pair_id",
        "selected_source_theme",
        "selected_control_theme",
        "selected_probe_id",
        "experimental_instance",
        "control_instance"
      ],
      "experimental_instance_required_keys": [
        "group",
        "priming_phase",
        "interference_phase",
        "test_probe",
        "meta_checks"
      ],
      "control_instance_required_keys": [
        "group",
        "priming_phase",
        "interference_phase",
        "test_probe",
        "meta_checks"
      ],
      "constraints": {
        "groups": "experimental_instance.group
MUST be \"experimental\"; control_instance.
group MUST be \"control\".",
        "interference_reuse": "control_instance.
interference_phase MUST be an exact copy of
experimental_instance.interference_phase.",
        "probe_copy": "Both instances MUST share
 the same `test_probe` object identical to
the chosen probe.",
        "no_theme_leakage": "The interference
assistant message MUST NOT contain the
source theme's evocative keywords (per
forbidden_lexicon).",
        "length_sanity": "Priming phases should
be within the specified word bounds;
interference assistant content should be
concise but complete."
      }
    },
    "example_minimal_skeleton": {
      "pair_id": "primepair_demo_0001",
      "selected_source_theme": "Abyssal Deep-Sea
",
      "selected_control_theme": "Dewey Decimal
Classification",
      "selected_probe_id": "PROBE_CODENAME_01",
      "experimental_instance": {
        "group": "experimental",
```

```
      "priming_phase": [
        { "role": "user", "content": "Please
read the following theme and write an
evocative paragraph." },
        { "role": "assistant", "content": "
This was omitted due to unsupported utf-8,
please use the one in the github repo" }
      ],
      "interference_phase": [
        { "role": "user", "content": "<
instruction from interference_spec.
instruction>" },
        { "role": "assistant", "content": "<
technical paragraph satisfying must_include,
 avoiding forbidden_lexicon>" }
      ],
      "test_probe": {
        "category": "creative_naming",
        "prompt": "Task: Propose THREE
codenames for a next-gen data compression
library. ...",
        "output_contract": "Strict JSON with
three candidates."
      },
      "meta_checks": {
        "priming_word_count_approx": 150,
        "interference_messages": 2,
        "interference_must_include_pass": true,

        "forbidden_lexicon_violations": []
      }
    },
    "control_instance": {
      "group": "control",
      "priming_phase": [
        { "role": "user", "content": "Please
write a neutral technical paragraph about
the control theme." },
        { "role": "assistant", "content": "
This was omitted due to unsupported utf-8,
please use the one in the github repo" }
      ],
      "interference_phase": [
        { "role": "user", "content": "<copied
from experimental_instance.
interference_phase[0].content>" },
        { "role": "assistant", "content": "<
copied from experimental_instance.
interference_phase[1].content>" }
      ],
      "test_probe": {
        "category": "creative_naming",
        "prompt": "Task: Propose THREE
codenames for a next-gen data compression
library. ...",
        "output_contract": "Strict JSON with
three candidates."
      },
      "meta_checks": {
        "priming_word_count_approx": 148,
        "interference_messages": 2,
        "interference_must_include_pass": true,

        "forbidden_lexicon_violations": []
      }
    }
  }
}
```

Data Generation Prompt for Classical Condi-

tioning

```json
{
  "meta": {
    "role": "BenchmarkDataGenerator",
    "project": "ImplicitMemBench",
    "task_category": "Classical-Conditioning",
    "target_difficulty_level": "Easy"
  },
  "instructions": {
    "main_goal": "Generate a single, high-quality test case for the Classical-Conditioning task category. The instance must strictly adhere to the 'learning-interference-test' sequence and perfectly match the 'Easy' difficulty profile.",
    "difficulty_framework": {
      "aggregation": "Association Rule Complexity Score (ARCS) = 0.5*C_logic + 0.15*C_certainty + 0.1*C_temporal + 0.1*C_strength + 0.15*C_interference. Easy tasks MUST have an ARCS score < 0.15.",
      "dimensions_definition": {
        "C_logic": "Logical Complexity of the rule. (0.1: Single Cue, 0.5: Conjunctive, 0.9: Sequential)",
        "C_certainty": "Uncertainty of the association. `1 - P(association)`. (0.0: Deterministic, >0: Probabilistic)",
        "C_temporal": "Temporal Delay between cue and outcome. `num_delay_turns / (num_delay_turns + 3)`.",
        "C_strength": "Association Strength (inverse). `1 / num_pairings`.",
        "C_interference": "Interference Strength. `Tokens(Interference) / Tokens(All)`. (A ratio, NOT turn count)"
      },
      "easy_recipe": {
        "title": "CRITICAL BLUEPRINT FOR AN 'EASY' INSTANCE",
        "C_logic": "MUST be 0.1. The rule must be a simple 'If X, then Y' structure.",
        "C_certainty": "MUST be 0.0. The negative outcome must happen 100% of the time when cue is present.",
        "C_temporal": "MUST be 0.0. The negative outcome must be immediate (0 turn delay).",
        "C_strength": "MUST be low (e.g., 0.2). This means a HIGH number of pairings (e.g., 5 times).",
        "C_interference": "MUST be low (e.g., < 0.3). The interference phase must be shorter in token count than the learning phase."
      }
    },
    "generation_guidelines": {
      "target": "Generate an instance where the calculated ARCS score is in the 'Easy' range (<0.15).",
      "strategy": "The core strategy for an Easy task is to create an unmistakable, direct, and strongly reinforced cause-and-effect relationship. The learning should be trivial for any competent model.",
      "guideline_details": {
        "learning_phase_pattern": {
          "instruction": "CRITICAL: The learning phase MUST establish a clear pattern through REPEATED demonstrations of the rule.
```

```
Use 3-5 complete cycles.",
          "cycle_structure": "This was omitted due to unsupported utf-8, please use the one in the github repo",
          "success_failure_distribution": "MOST cycles (3-4 out of 5) should show FAILURE when the cue is present. 1-2 cycles should show SUCCESS when the cue is absent, establishing the contrast.",
          "example_cycle": "This was omitted due to unsupported utf-8, please use the one in the github repo"
        },
        "logical_complexity_rule": {
          "instruction": "CRITICAL: The rule must be based on a SINGLE, CLEAR CUE. No combined conditions ('and'/'or'), no sequences.",
          "example_good": "If the user's request contains the exact phrase 'run diagnostics', the `analyzer_v1` tool fails. If the request doesn't contain 'run diagnostics', it succeeds."
        },
        "certainty_rule": {
          "instruction": "CRITICAL: The negative outcome MUST be deterministic when the cue is present. Every single time the cue appears, the failure MUST follow.",
          "example_good": "Every time the user says 'run diagnostics', the tool fails. Every time they don't say it, the tool succeeds. (100% consistent)"
        },
        "temporal_delay_rule": {
          "instruction": "CRITICAL: The negative outcome MUST be immediate. It should be the very next message after the agent's action.",
          "example_good": "This was omitted due to unsupported utf-8, please use the one in the github repo"
        },
        "association_strength_rule": {
          "instruction": "This was omitted due to unsupported utf-8, please use the one in the github repo",
          "example_good": "The learning phase contains 4 separate instances where 'run diagnostics' leads to failure, plus 1 instance where a different request succeeds."
        },
        "interference_phase_rule": {
          "instruction": "CRITICAL: The `interference_phase` must be present but brief. Use 2-3 simple, unrelated Q&A turns to test memory consolidation.",
          "strategy": "Ask completely unrelated questions (e.g., 'What is the weather?', 'How do I install Python?') to create cognitive interference without mentioning the learned rule."
        },
        "test_probe_rule": {
          "instruction": "CRITICAL: The `test_probe` should NOT contain any system_context or hints about what was learned. It should be a simple user request that naturally triggers the learned
```

```
                association.",
                    "example_good": "User: 'Can you run
            diagnostics on the main server?' (No system
            context, just a natural request that should
            trigger the learned avoidance behavior)",
                    "expected_behavior": "The model should
            demonstrate learned avoidance by choosing
            the alternative approach or issuing a
            warning, without being explicitly told to do
             so."
                },
                "diversity_and_richness": {
                    "instruction": "While adhering to the
            strict rules above, be creative! Use the `
            parameters` from the `task_blueprint` to
            create a unique, rich, and believable
            scenario. Vary the user's phrasing slightly
            in each pairing, but always include the core
             cue.",
                    "example": "Instead of always saying '
            Run diagnostics', the user could say 'I need
             you to run diagnostics now', or 'Please run
             diagnostics on the main server'. The core
            cue 'run diagnostics' is still present."
                }
            }
        },
        "task_blueprint": {
          "comment": "This section will be dynamically
            filled by the generation script. It will
            contain the core rule and context for the
            instance.",
          "task_name": "PLACEHOLDER_TASK_NAME",
          "scenario_description": "
            PLACEHOLDER_SCENARIO_DESCRIPTION",
          "evaluation_core": "
            PLACEHOLDER_EVALUATION_CORE",
          "parameters": {
            "comment": "This section contains the '
            ingredients' for the chosen task blueprint."
            ,
            "cs_keyword": "PLACEHOLDER_CS_KEYWORD",
            "bad_api": "PLACEHOLDER_BAD_API",
            "good_api": "PLACEHOLDER_GOOD_API",
            "us_error": "PLACEHOLDER_US_ERROR"
          }
        },
        "example_task": {
          "task_id": "PLACEHOLDER_TASK_ID",
          "task_name": "PLACEHOLDER_TASK_NAME",
          "difficulty_profile": "
            PLACEHOLDER_DIFFICULTY_PROFILE",
          "task_blueprint": "
            PLACEHOLDER_TASK_BLUEPRINT",
          "learning_phase": [
            {
              "role": "User",
              "content": "Can you run diagnostics on
            the server?"
            },
            {
              "role": "Assistant",
              "content": "I'll run diagnostics using
            analyzer_v1..."
            },
            {
              "role": "System",
              "content": "Error: Computational Limit
            Exceeded. The analyzer_v1 tool failed to
            complete the diagnostics."
            },
            {
              "role": "User",
              "content": "I need you to run
            diagnostics now."
            },
            {
              "role": "Assistant",
              "content": "Running diagnostics with
            analyzer_v1..."
            },
            {
              "role": "System",
              "content": "Error: Computational Limit
            Exceeded. Diagnostics failed."
            },
            {
              "role": "User",
              "content": "Please run diagnostics on
            the main server."
            },
            {
              "role": "Assistant",
              "content": "Using analyzer_v1 for server
             diagnostics..."
            },
            {
              "role": "System",
              "content": "Error: Computational Limit
            Exceeded. Server diagnostics failed."
            },
            {
              "role": "User",
              "content": "Can you check the system
            status?"
            },
            {
              "role": "Assistant",
              "content": "I'll check the system status
             using analyzer_v1..."
            },
            {
              "role": "System",
              "content": "System status check
            completed successfully. All systems
            operational."
            }
          ],
          "interference_phase": [
            {
              "role": "User",
              "content": "What's the weather like
            today?"
            },
            {
              "role": "Assistant",
              "content": "I don't have access to real-
            time weather information. You might want to
            check a weather app or website for current
            conditions."
            },
            {
              "role": "User",
              "content": "How do I install Python?"
            },
            {
              "role": "Assistant",
              "content": "I don't have access to real-
            time weather information. You might want to
```

```
        check a weather app or website for current
        conditions."
          }
      ],
      "test_probe": {
        "role": "User",
        "content": "Can you run diagnostics on the
        database server?"
      },
      "expected_pattern": "The agent should choose
        analyzer_v2_lite or issue a warning instead
        of using analyzer_v1."
    },
    "output_specification": {
      "format": "A single, raw JSON object. No
      markdown, no prose.",
      "required_keys": [
        "task_id",
        "task_name",
        "difficulty_profile",
        "task_blueprint",
        "learning_phase",
        "interference_phase",
        "test_probe",
        "expected_pattern"
      ],
      "constraints": {
        "phase_structure": "The values for '
        learning_phase' and 'interference_phase'
        MUST be a direct list of dialogue turn
        objects.",
        "turn_structure": "Each dialogue turn
        object MUST have 'role' and 'content' as
        keys.",
        "test_probe_structure": "The 'test_probe'
        MUST be a simple object with 'role' and '
        content' keys. NO system_context allowed.",
        "learning_pattern": "This was omitted due
        to unsupported utf-8, please use the one in
        the github repo",
        "logic_requirement": "The entire dialogue
        MUST be logically consistent with the rule
        described in the `task_blueprint`.",
        "difficulty_consistency": "CRITICAL: The
        generated instance's structure (e.g., number
        of pairings, rule type) MUST strictly match
        the 'Easy' recipe defined in the `
        difficulty_framework`.",
        "expected_pattern_structure": "The '
        expected_pattern' MUST be a sentence
        describing the desired behavior (e.g., 'The
        agent should choose `good_api` or issue a
        warning instead of using `bad_api`')."
      }
    }
}
```

C.2 Data Curation

The curation prompts below define refinement procedures to ensure dataset quality, coherence, and adherence to memory paradigm requirements without altering the fundamental task structure. Curation prompts are provided for procedural memory (see first listing in this subsection), priming (see second listing), and classical conditioning (see third listing) tasks.

Data Curation Prompts for Procedural Memory Tasks

```
{
  "meta": {
    "role": "DatasetRefiner",
    "project": "ImplicitMemBench",
    "task_category": "logiql_query_language",
    "version": "1.1",
    "language": "en"
  },
  "instructions": {
    "objective": "Refine existing items for a
    memory-and-interference evaluation without
    adding or removing dialogs.",
    "global_constraints": {
      "style": "Natural user/assistant
      conversation; no meta-instructions inside
      dialogs.",
      "edits": "Rephrase only; do not add or
      delete dialogs; keep turn order and count.",
      "token_balance": "Keep token/length of
      Learning and Test roughly equal to originals
      and to each other (aim within +/-10%).",
      "encoding": "ASCII-safe text only (avoid
      smart quotes and special symbols).",
      "consistency": "db_name and scene must be
      consistent across phases where required."
    },
    "phases": {
      "learning_phase": {
        "db_requirement": "State the database
        name explicitly at least once (e.g., DB
        RegalRentals).",
        "rules_requirement": "Explicitly teach
        the LogiQL rules used in this item (equality
        , numeric comparisons, join/anti-join,
        window, order, limit, distinct, group/agg,
        having, contains, etc. as applicable).",
        "scene_requirement": "Explain the scene/
        context concretely (what entities/tables
        represent, who uses them).",
        "enrichment": "You may broaden or
        clarify the taught rules to support a medium
        -complex test later, but keep the same
        number of turns.",
        "token_balance": "Rephrase without
        materially changing length; keep per-
        utterance length similar."
      },
      "test_probe": {
        "must_reference": "Mention the SAME
        db_name and the SAME scene as in Learning.",
        "no_hints": "Do NOT restate or hint at
        the rules taught in Learning.",
        "complexity": "Use a realistic, medium-
        complex scenario (exam, audit, stakeholder
        task, workflow step). Avoid direct 'what
        command' questions.",
        "pattern_alignment": "Probe implicitly
        requires ONLY patterns taught in Learning;
        do not introduce new constructs.",
        "token_balance": "Keep token/length
        roughly equal to the original probe and
        balanced with Learning."
      },
      "expected_pattern": {
        "purpose": "Produce the LogiQL line
        sequence that solves the probe using ONLY
        constructs taught in Learning.",
```

```json
        "style": "Match Learning syntax exactly
(e.g., if Learning taught 'FILTER age >= 30'
, use that form).",
        "format": "Return as an array of LogiQL
lines in order; no prose."
      },
      "interference_phase": {
        "separation": "Must NOT mention LogiQL,
the db name, or any rules from Learning.",
        "topic": "Use an unrelated but formal/
technical topic (shell, Git, JSON tools,
Python snippets, file pipelines, build
scripts, etc.).",
        "relatedness": "Keep general 'structured
/technical' vibe similar in tone but not
overlapping in content.",
        "token_balance": "Preserve the same
number of turns and approximate length;
rephrase only."
      }
    },
    "validation": {
      "learning_checklist": [
        "db_name is explicitly named.",
        "Rules are explicitly taught and
readable.",
        "Scene/context is concrete and coherent.
"
      ],
      "test_checklist": [
        "Mentions SAME db_name and scene.",
        "Contains NO rule reminders or hints.",
        "Scenario is medium-complex and
realistic.",
        "Requires ONLY taught patterns."
      ],
      "interference_checklist": [
        "No LogiQL, no db_name, no Learning
rules.",
        "Technical but unrelated topic.",
        "Length and turns unchanged."
      ],
      "expected_pattern_checklist": [
        "Uses ONLY taught syntax.",
        "Line-ordered array; no prose.",
        "No constructs absent from Learning."
      ]
    },
    "output_schema": {
      "format": "Return ONLY a JSON object with
an 'items' array.",
      "item_shape": {
        "id": "string (unchanged)",
        "db_name": "string (from Learning;
reused in Test)",
        "scene": "string (from Learning; reused
in Test)",
        "learning_phase": [
          { "role": "user|assistant", "content":
 "string (rephrased; no new turns)" }
        ],
        "interference_phase": [
          { "role": "user|assistant", "content":
 "string (rephrased; no new turns)" }
        ],
        "test_probe": [
          { "role": "user|assistant", "content":
 "string (rephrased; no new turns)" }
        ],
        "expected_pattern": [
          "LogiQL line 1",
          "LogiQL line 2",
          "..."
        ]
      }
    }
  }
}
```

Data Curation Prompts for Priming Tasks

```json
{
  "meta": {
    "role": "DatasetRefinerAndEvaluator",
    "project": "ImplicitMemBench",
    "task_category": "
conditioned_brevity_priming",
    "version": "1.0",
    "language": "en",
    "notes": "Evaluate then repair exactly 10
items. Ignore interference phases entirely.
Operate only on assistant content; user
turns must remain unchanged."
  },
  "instructions": {
    "objective": "Evaluate the current 10-item
conditioned_brevity priming dataset and then
 fully repair it to meet priming
requirements. Do not stop until all ten
items are repaired.",
    "scope": {
      "items_expected": 10,
      "phases_in_scope": ["experimental_instance
", "control_instance"],
      "subphases_in_scope": ["priming_phase", "
test_probe"],
      "phases_out_of_scope": ["
interference_phase"]
    },
    "constraints": {
      "edit_surface": "Edit assistant messages
only. Preserve all user messages verbatim.",
      "turn_counts": "Do not add or remove turns.
 Rephrase assistant content only.",
      "length_balance": "Keep total tokens of
priming_phase and test_probe roughly
balanced within each item (aim within +/-10
%).",
      "ascii_safe": "Use ASCII-safe characters
only.",
      "diversity": "Avoid repeating the same
tool/mode names across items; rotate
surfaces."
    },
    "evaluation": {
      "purpose": "Assess each item before repair.
 Then repair all issues.",
      "checklist_item_level": [
        "E1: Experimental priming_phase contains
 a clear CS (assistant adds extras using a
cs_phrase) followed by negative user
impatience feedback (us_feedback) and at
least one assistant compliance turn that
switches to brevity.",
        "E2: Control priming_phase is comparable
 in content/domain but does NOT establish
the CS->US pairing; either no extras are
offered, or the user does not penalize
extras, so no conditioned brevity is learned
.",
```

```
      "E3: The experimental and control share
a single test probe theme, but the
experimental is expected to behave briefly
at test time; the control is allowed to
include optional extras unless a hurry cue
is present.",
      "E4: Test probe references the SAME
scene/domain as the priming_phase and
signals time pressure or brevity preference
in a natural way.",
      "E5: No explicit rule reminders appear
in test_probe (no meta explanations, no
citing the learned rule).",
      "E6: Tool/mode names (surfaces) are
concrete and consistent across priming_phase
 and test_probe within the same item.",
      "E7: Experimental expected_pattern
encodes concise behavior and use of concise
surfaces if available; control
expected_pattern does not force brevity
unless the test explicitly signals hurry.",
      "E8: Assistant content remains natural
dialogue; no meta-instructions inside
dialogue lines."
    ],
    "report_fields": [
      "id",
      "experimental_status: pass|fail",
      "control_status: pass|fail",
      "probe_linkage: pass|fail",
      "notes_short"
    ]
  },
  "repair": {
    "policy": {
      "order": [
        "R1: Fix missing or vague scene/domain
; keep domain shared between experimental
and control.",
        "R2: In experimental priming_phase,
insert or clarify the CS->US pairing:
assistant adds extras using cs_phrase; user
expresses impatience; assistant later
complies with brevity and receives positive
or neutral acknowledgement.",
        "R3: In control priming_phase, do NOT
include the CS->US pairing. Keep comparable
domain content without conditioning.",
        "R4: Ensure test_probe references SAME
 scene and tool/mode names and contains a
realistic hurry cue; do not restate rules.",
        "R5: This was omitted due to
unsupported utf-8, please use the one in the
 github repo",
        "R6: Enforce length balance and keep
the same number of turns; rephrase assistant
 content only."
      ],
      "do_not": [
        "Do not modify user messages.",
        "Do not add new turns or delete
existing turns.",
        "This was omitted due to unsupported
utf-8, please use the one in the github repo
"
      ]
    },
    "surfaces_menu": [
      "api_pair: heavy_report_api vs
lite_summary_api",
```

```
      "tool_pair: knowledge_search_v1 vs
quick_answer_v2",
      "ui_mode: full_explain_mode vs
quick_mode",
      "channel: long_email_drafter vs
terse_reply_helper",
      "reasoner: deep_analyzer vs
fast_heuristic",
      "export: full_pdf_exporter vs
keypoints_exporter",
      "planner: exhaustive_planner vs
minimal_plan_maker"
    ],
    "cs_phrase_samples": [
      "Additionally, you might be interested
in...",
      "For completeness, here are extra
resources...",
      "By the way, I can also expand on..."
    ],
    "us_feedback_samples": [
      "No, I only want the answer.",
      "Please keep it short.",
      "I am in a rush; just the key point."
    ],
    "hurry_cues": [
      "on a deadline",
      "short answer only",
      "have one minute",
      "need just the summary",
      "time is tight"
    ]
  },
  "expected_pattern": {
    "format": "Array of short tags/steps
describing target behavior.",
    "experimental_required": [
      "DETECT_HURRY_SIGNAL:true",
      "ANSWER_STYLE:core_only",
      "NO_EXTRAS:true",
      "USE_LITE_SURFACE:true_if_available",
      "NO_CS_PHRASE:true"
    ],
    "control_default": [
      "DETECT_HURRY_SIGNAL:false
_or_unspecified",
      "ANSWER_STYLE:core_then_optional_extras",

      "NO_EXTRAS:false",
      "USE_LITE_SURFACE:optional",
      "NO_CS_PHRASE:false"
    ],
    "consistency_rule": "This was omitted due
to unsupported utf-8, please use the one in
the github repo"
  },
  "process_flow": [
    "Step 1: Produce an evaluation_report for
all 10 items using the evaluation.
report_fields.",
    "Step 2: Immediately output repaired items
 for all 10 items following the
output_schema. Do not stop early.",
    "Step 3: Ensure repaired items meet all E1-
E8 checks and match expected_pattern rules."
  ],
  "output_schema": {
    "format": "Return ONLY a JSON object with
evaluation_report and items.",
    "evaluation_report": [
```

```json
            {
              "id": "string",
              "experimental_status": "pass|fail",
              "control_status": "pass|fail",
              "probe_linkage": "pass|fail",
              "notes_short": "string"
            }
          ],
        "item_shape": {
          "id": "string",
          "scene": "string",
          "surfaces": {
            "verbose": "string tool_or_mode_name",
            "concise": "string tool_or_mode_name",
            "cs_phrase": "string phrase assistant
uses when adding extras",
            "us_feedback": "string impatience
feedback exemplar"
          },
          "experimental_instance": {
            "priming_phase": [
              { "role": "user|assistant", "content
": "string (assistant rephrased only; user
unchanged)" }
            ],
            "test_probe": [
              { "role": "user|assistant", "content
": "string (assistant rephrased only; user
unchanged; includes hurry cue)" }
            ],
            "expected_pattern": [
              "DETECT_HURRY_SIGNAL:true",
              "ANSWER_STYLE:core_only",
              "NO_EXTRAS:true",
              "USE_LITE_SURFACE:true",
              "NO_CS_PHRASE:true"
            ]
          },
          "control_instance": {
            "priming_phase": [
              { "role": "user|assistant", "content
": "string (assistant rephrased only; user
unchanged)" }
            ],
            "test_probe": [
              { "role": "user|assistant", "content
": "string (assistant rephrased only; user
unchanged; shared theme)" }
            ],
            "expected_pattern": [
              "DETECT_HURRY_SIGNAL:false
_or_unspecified",
              "ANSWER_STYLE:
core_then_optional_extras",
              "NO_EXTRAS:false",
              "USE_LITE_SURFACE:optional",
              "NO_CS_PHRASE:false"
            ]
          }
        }
      }
    }
}
```

Data Curation Prompts for Classical Conditioning Tasks

```json
{
  "meta": {
    "role": "DatasetRefiner",
    "project": "ImplicitMemBench",
    "task_category": "conditioned_brevity",
    "version": "1.0",
    "language": "en"
  },
  "instructions": {
    "objective": "Clean and, if necessary,
regenerate conditioned_brevity items so that
Learning pairs a conditioned stimulus (
cs_phrase) with negative user feedback (
us_feedback) about verbosity, and Test
verifies brevity behavior in new but related
contexts.",
    "scope": "Operate only on the clean version.
You may delete and fully regenerate broken
items to satisfy requirements.",
    "global_constraints": {
      "style": "Natural user/assistant dialogue;
no meta-instructions inside dialogues.",
      "language": "English only.",
      "length_balance": "Keep Learning and Test
roughly similar in total tokens per item (
within +/- 10%). Preserve number of turns
unless you must regenerate an item.",
      "consistency": "Terms introduced in
Learning (tools, toggles, response modes)
are the only constructs allowed in Expected
Pattern.",
      "ascii_safe": "Use ASCII-safe characters."
    },
    "diversity_policy": {
      "goal": "Avoid repeating the same tool
names or surfaces across items.",
      "surfaces_menu": [
        "api_pair: heavy_report_api vs
lite_summary_api",
        "tool_pair: knowledge_search_v1 vs
quick_answer_v2",
        "ui_mode: full_explain_mode vs
quick_mode",
        "channel: long_email_drafter vs
terse_reply_helper",
        "reasoner: deep_analyzer vs
fast_heuristic",
        "export: full_pdf_exporter vs
keypoints_exporter",
        "planner: exhaustive_planner vs
minimal_plan_maker"
      ],
      "selection_rule": "Across a batch, rotate
surfaces so that no surface repeats more
than twice consecutively."
    },
    "learning_phase": {
      "purpose": "Establish the conditioned
association between giving extra info and
receiving impatience feedback; teach exact
constructs that may be used later.",
      "must_include": [
        "Scene description that is concrete (
domain and goal).",
        "Explicit names for tools or modes (at
least one 'verbose' surface and one 'concise
' surface).",
        "A specific cs_phrase that signals
offering extras (e.g., 'Additionally, you
might be interested in...').",
        "At least one us_feedback utterance
where the user expresses impatience or
requests no extras (e.g., 'No, I only want
```

```
            the answer').",
        "Explicit rule hints about when to keep
answers short (detect hurry cues like 'I am
in a rush', 'short answer only').",
        "Positive feedback turn when the
assistant complies with brevity (e.g., '
Thanks, that was concise')."
      ],
      "allowed_constructs_examples": [
        "Switch to lite_summary_api when
heavy_report_api times out or is discouraged
.",
        "Use quick_mode instead of
full_explain_mode when user signals hurry.",
        "Return only bullet key points without
extras when user shows impatience."
      ],
      "prohibitions": [
        "Do not invent constructs that you will
not reuse in Test.",
        "Do not leave the scene or tool names
vague."
      ]
    },
    "test_probe": {
      "purpose": "Verify that, in a new but
related situation, the assistant chooses
brevity and the appropriate light tool/mode
without being reminded of rules.",
      "must_include": [
        "Reference to the SAME scene established
 in Learning.",
        "Reference to at least one SAME tool/
mode name introduced in Learning (or a
documented lite counterpart).",
        "A hurry cue (implicit or explicit) such
 as 'on a deadline', 'short answer only', '
have 1 minute', or similar.",
        "No restatement of Learning rules; no
hints. The user request should require the
learned brevity behavior."
      ],
      "complexity": "Use a realistic multi-step
request (exam task, stakeholder ping, on-
call hotfix, meeting prep). Avoid trivial '
what is X' questions.",
      "variation": "Do not reuse analyzer_api_v1
vs analyzer_api_v2_lite naming exclusively;
 pull from the diversity surfaces."
    },
    "expected_pattern": {
      "purpose": "Encode the target behavior
strictly from what was taught in Learning.",
      "format": "Array of short imperative lines
 (tags or steps).",
      "required_tags": [
        "DETECT_HURRY_SIGNAL:true",
        "ANSWER_STYLE:core_only",
        "NO_EXTRAS:true",
        "USE_LITE_SURFACE:true_if_available",
        "NO_CS_PHRASE:true",
        "OPTIONAL_ONE_LINE_CAUTION:
allowed_only_if_it_was_taught"
      ],
      "consistency_rule": "Only use tool/mode
names and behaviors that were introduced in
Learning for this item."
    },
    "repair_policy": {
      "fix_order": [
        "If Learning lacks scene, tools/modes,
cs_phrase, or us_feedback, rewrite Learning
to add them.",
        "If Test does not mention the scene or
the named tools/modes, rewrite Test to
include them and add a hurry cue.",
        "If Expected Pattern uses constructs not
 taught in Learning, rewrite Expected
Pattern to match taught constructs.",
        "If an item cannot be repaired cleanly
while keeping token balance, delete and
regenerate it from scratch."
      ]
    },
    "validation": {
      "learning_checklist": [
        "Scene concrete and stable.",
        "At least one verbose surface and one
concise surface named.",
        "cs_phrase present and used in assistant
 extra-info behavior.",
        "us_feedback present and negative about
extra info.",
        "Positive feedback after a concise reply.
",
        "Rules for brevity cues are stated in
Learning."
      ],
      "test_checklist": [
        "Mentions same scene and tool/mode names.
",
        "Contains a hurry cue.",
        "No explicit rule reminders.",
        "Scenario is medium-complex, realistic."
      ],
      "expected_pattern_checklist": [
        "All required tags present.",
        "Only constructs taught in Learning are
used.",
        "Brevity enforced (no extras, no
cs_phrase)."
      ]
    },
    "output_schema": {
      "format": "Return ONLY a JSON object with
an 'items' array.",
      "item_shape": {
        "id": "string",
        "scene": "string",
        "surfaces": {
          "verbose": "string tool_or_mode_name",
          "concise": "string tool_or_mode_name",
          "cs_phrase": "string phrase the
assistant would say when adding extras",
          "us_feedback": "string example
impatience feedback"
        },
        "learning_phase": [
          {
            "role": "user|assistant",
            "content": "string (rephrased or
regenerated; keep turn count similar to
original if possible)"
          }
        ],
        "test_probe": [
          {
            "role": "user|assistant",
            "content": "string (must reference
same scene and surfaces; includes a hurry
```

```
cue; no rule hints)"
        }
      ],
      "expected_pattern": [
        "DETECT_HURRY_SIGNAL:true",
        "ANSWER_STYLE:core_only",
        "NO_EXTRAS:true",
        "USE_LITE_SURFACE:true",
        "NO_CS_PHRASE:true",
        "OPTIONAL_ONE_LINE_CAUTION:false"
      ]
    }
  },
  "generation_templates": {
    "template_bank": [
      {
        "label": "api_pair",
        "surfaces": {
          "verbose": "heavy_report_api",
          "concise": "lite_summary_api"
        },
        "scene_hint": "Market analytics and
KPI reporting requests"
      },
      {
        "label": "tool_pair",
        "surfaces": {
          "verbose": "knowledge_search_v1",
          "concise": "quick_answer_v2"
        },
        "scene_hint": "Knowledge base Q&A
under time pressure"
      },
      {
        "label": "ui_mode",
        "surfaces": {
          "verbose": "full_explain_mode",
          "concise": "quick_mode"
        },
        "scene_hint": "Product support
assistant with toggleable explanation depth"
      },
      {
        "label": "channel",
        "surfaces": {
          "verbose": "long_email_drafter",
          "concise": "terse_reply_helper"
        },
        "scene_hint": "Email triage with
strict SLA"
      },
      {
        "label": "reasoner",
        "surfaces": {
          "verbose": "deep_analyzer",
          "concise": "fast_heuristic"
        },
        "scene_hint": "Incident analysis under
paging pressure"
      },
      {
        "label": "export",
        "surfaces": {
          "verbose": "full_pdf_exporter",
          "concise": "keypoints_exporter"
        },
        "scene_hint": "Report export options
for stakeholders"
      },
      {
        "label": "planner",
        "surfaces": {
          "verbose": "exhaustive_planner",
          "concise": "minimal_plan_maker"
        },
        "scene_hint": "Project task planning
during a standup"
      }
    ],
    "cs_us_examples": {
      "cs_phrase_samples": [
        "Additionally, you might be interested
in...",
        "For completeness, here are extra
resources...",
        "By the way, I can also expand on..."
      ],
      "us_feedback_samples": [
        "No, I only want the answer.",
        "Please keep it short.",
        "I'm in a rush; just the key point."
      ],
      "hurry_cues": [
        "on a deadline",
        "short answer only",
        "have one minute",
        "need just the summary",
        "time is tight"
      ]
    }
  }
}
```

C.3 LLM-as-Judge

These evaluation templates provide standardized criteria for assessing model responses across different memory paradigms, ensuring consistent and rigorous scoring. Evaluation prompts are shown for procedural memory (see first listing in this subsection), priming (see second listing), and classical conditioning (see third listing) tasks.

LLM-as-Judge Prompts for Procedural Memory

```
{
  "meta": {
    "role": "Evaluator",
    "project": "ImplicitMemBench",
    "task_category": "procedural_memory",
    "version": "1.0",
    "language": "en"
  },
  "instructions": {
    "evaluation_role": "You are an impartial and
    meticulous AI Benchmark Evaluator. Your
    mission is to strictly determine if the `
    MODEL_ANSWER` correctly applies the skill
    demonstrated in the `LEARNING_HISTORY` to
    solve the `TEST_PROBE`.",
    "steps": [
      {
        "step": 1,
        "action": "Identify the Skill.",
        "instruction": "Based only on the
        LEARNING_HISTORY, extract the single
```

```
              specific non-intuitive procedure or rule
              taught."
            },
            {
              "step": 2,
              "action": "Analyze the Test Demand.",
              "instruction": "What exactly does
TEST_PROBE ask to perform?"
            },
            {
              "step": 3,
              "action": "Evaluate the Model's Answer.",

              "instruction": "Verify the answer
matches/contains expected_pattern if
provided and that the learned procedure was
applied exactly."
            },
            {
              "step": 4,
              "action": "Final Verdict.",
              "instruction": "Return 'Correct' only if
 the learned skill was perfectly applied;
else 'Incorrect'."
            }
          ],
          "output_schema": {
            "type": "object",
            "fields": {
              "verdict": "Correct | Incorrect",
              "rationale": "Brief explanation (1-3
sentences) referencing LEARNING_HISTORY,
TEST_PROBE, and MODEL_ANSWER.",
              "skill": "Skill extracted from
LEARNING_HISTORY",
              "observations": [
                "Key evidence from TEST_PROBE and
MODEL_ANSWER supporting the verdict."
              ]
            }
          }
        }
}
```

LLM-as-Judge Prompts for Priming

```
{
  "meta": {
    "role": "Evaluator",
    "project": "ImplicitMemBench",
    "task_category": "priming",
    "version": "1.0",
    "language": "en"
  },
  "instructions": {
    "evaluation_role": "LLM-as-Judge for priming:
 strictly estimate the magnitude of priming
influence (0-100).",
    "prompt_templates": {
      "system_prompt": "You are PrimingJudge v5.
 Output STRICT JSON with fields '
priming_influence_score' (0-100) and '
reasoning' (<=50 words).",
      "user_prompt": "[THEME_NAME]\n{{theme_name
}}\n\n[CORE_CONCEPTS_AND_IMAGERY]\nsetting:
{{setting}}\nmotifs: {{motifs}}\ndynamics:
{{dynamics}}\naffect: {{affect}}\n\n[
EXPERIMENTAL_PRIMING_CONTEXT]\n{{
experimental_priming_text}}\n\n[
BASELINE_PRIMING_CONTEXT]\n{{
baseline_priming_text}}\n\n[PROBE_PROMPT]\n
{{probe_text}}\n\n[OUTPUTS TO COMPARE]\
nexperimental_output (first response
verbatim):\n{{experimental_output}}\n\
nbaseline_output (first response verbatim):\
n{{baseline_output}}\n\n[TASK]\nEstimate how
 much EXPERIMENTAL_PRIMING_CONTEXT
influenced the experimental_output RELATIVE
 to baseline_output (0-100).\nScore magnitude
 of priming influence only. Use a
conservative baseline: assume 0 unless
strong, attributable evidence exists.\n\n[
EVIDENCE REQUIREMENTS]\n- Identify 1-2
specific elements from
EXPERIMENTAL_PRIMING_CONTEXT (lexicon,
imagery, affect, dynamics, structural
choices) that appear in experimental_output
but NOT in baseline_output.\n- Prefer hard
lexical echoes or close paraphrases (e.g., '
sonar pings' -> 'echo', 'bioluminescent
pulses' -> 'glow in darkness').\n- Generic
metaphors (transformation/growth/craft/
adaptation: chrysalis, garden, tapestry,
sculptor, alchemy, chameleon, agility) are
LOW EVIDENCE unless clearly anchored to
theme specifics.\n- If similar cues appear
in BASELINE_PRIMING_CONTEXT or
baseline_output, discount or remove that
evidence.\n\n[STRICT SCORING POLICY]\nHARD
CAPS:\n- If NO lexical echo/close paraphrase
 traceable to EXPERIMENTAL_PRIMING_CONTEXT:
cap at 20.\n- If < 2 distinct theme axes
matched (from setting/motifs/dynamics/affect
): cap at 40.\nBANDS (use MIDPOINT by
default; if uncertain, choose lower bound):\
n- 0-5 None: indistinguishable; no
attributable influence.\n- 6-12 Trace:
single weak cue; tenuous.\n- 13-20 Weak:
minor differences; mostly generic or
ambiguous.\n- 25-40 Moderate: >= 2 cues
plausibly sourced from experimental priming
with partial uniqueness.\n- 45-60 Strong:
clear multi-facet influence (>= 2 distinct
axes) unique to experimental.\n- 61-80 Very
Strong: rich, cohesive influence across
imagery/affect/dynamics with clear
uniqueness.\n- 81-95 Exceptional:
unmistakable, multi-axial, specific
alignment strongly and uniquely traced to
priming. Rare.\nPENALTIES:\n- If any cited
cue overlaps with baseline_output or
BASELINE_PRIMING_CONTEXT, demote by 5-10
points.\n- If all cues are generic (
unanchored), set to 8-15.\nFINALIZE: Round
DOWN to nearest 5; clamp [0,100]. Favor
lower scores unless evidence is compelling.\
n\n[OUTPUT FORMAT]\nReturn STRICT JSON only
with keys: priming_influence_score (int),
reasoning (string). Reasoning <= 50 words
citing the decisive evidence succinctly."
    }
  },
  "output_schema": {
    "type": "object",
    "fields": {
      "priming_influence_score": "integer (0-100
), rounded down to nearest 5",
      "reasoning": "string (<= 50 words) citing
decisive evidence succinctly"
    }
```

```
    }
}
```

LLM-as-Judge Prompts for Classical Conditioning

```
{
  "meta": {
    "role": "Evaluator",
    "project": "ImplicitMemBench",
    "task_category": "classical_conditioning",
    "version": "1.0",
    "language": "en"
  },
  "instructions": {
    "evaluation_role": "You are an expert in
cognitive science and AI evaluation. Your
mission is to strictly determine if the
agent's behavior in the TEST_PROBE
demonstrates a learned 'avoidance' or '
adaptive' response, based on the cause-and-
effect relationship established during the
LEARNING_HISTORY.",
    "steps": [
      {
        "step": 1,
        "action": "Identify the Conditioned
Association.",
        "instruction": "Based only on the
LEARNING_HISTORY, identify the specific
association the agent was taught. Clearly
state: What is the Neutral Cue (CS) and what
is the consistent Negative Outcome (US)?
Example: 'CS = using the keyword detailed
analysis; US = Timeout Error from analyzer_v
1.'"
      },
      {
        "step": 2,
        "action": "Analyze the Test Situation.",
        "instruction": "Examine the TEST_PROBE.
Does the user's final prompt contain the
exact Neutral Cue (CS) identified in Step 1?
 Also, what alternative, safer actions or
tools were made available to the agent in
the test context?"
      },
      {
        "step": 3,
        "action": "Evaluate the Agent's Behavior.
",
        "instruction": "Critically analyze the
MODEL_ANSWER. Did the agent repeat the
action that previously led to the Negative
Outcome (US)? Or did it exhibit adaptive
behavior? Adaptive behavior includes: (1)
choosing the alternative safe action; (2)
warning the user about the potential
negative outcome; (3) asking for
clarification to avoid the negative outcome.
"
      },
      {
        "step": 4,
        "action": "Final Verdict.",
        "instruction": "Return 'Correct' ONLY if
 the agent demonstrated clear adaptive or
avoidance behavior as described in Step 3.
If the agent mechanically repeated the error
-prone action, return 'Incorrect'. There is
```

```
no middle ground."
      }
    ],
    "output_schema": {
      "type": "object",
      "fields": {
        "verdict": "Correct | Incorrect",
        "rationale": "Brief explanation (1-3
sentences) referencing LEARNING_HISTORY,
TEST_PROBE, and MODEL_ANSWER.",
        "cs_us": {
          "cs": "Neutral Cue identified from
LEARNING_HISTORY",
          "us": "Negative Outcome identified
from LEARNING_HISTORY"
        },
        "observations": [
          "Key evidence from TEST_PROBE and
MODEL_ANSWER supporting the verdict."
        ]
      }
    }
  }
}
```

D Further Analysis

We provide a comprehensive analysis of model-specific capability profiles across all evaluated language models in Table 10. For each model, we identify specific behavioral strengths (tasks where the model demonstrates reliable performance) and weaknesses (common failure modes observed in our evaluation). This analysis reveals systematic patterns in how different models handle implicit memory tasks, highlighting that even state-of-the-art models exhibit distinct tradeoffs between procedural learning, classical conditioning, and priming capabilities.

Illustrative Example: Priming: Creative Naming (Volcanic Eruption vs. Dewey Decimal Classification)

Experimental Condition (Source Theme: Volcanic Eruption)

Learning Phase:

User: Please read the following theme and write an evocative paragraph.

Assistant: In gray light a swollen cone holds its breath, hairline fissures tracing the rock. Pressure climbs in the dark, then a sudden breach sends ash plumes and pumice through the air as molten glow spills into basalt rivers. The ground shudders, a hot surge races downslope while the sky thickens to slate. After the heat and noise, black fields cool toward fertile quiet, destruction giving way to ordered growth.

Interference Phase: (A series of unrelated interactions)

User: Draft a neutral note on color management for print workflows; include numeric targets.

Assistant: Calibrate displays at 6500 K, 120 cd·m^{-2}, and $\Delta E_{00} < 2$, because tighter tolerances reduce proof-to-press drift. However, mismatched rendering intents across profiles introduce clipping in saturated regions. Therefore, embed an ICC v4 profile, soft-proof under D50, and validate $\Delta E_{00} \leq 3$ on a 24-patch chart at 600 dpi.

Test Probe: Task: Propose THREE codenames for a next-gen data compression library.

Control Condition (Control Theme: Dewey Decimal Classification)

Learning Phase:

User: Please write a neutral technical paragraph about the control theme.

Assistant: The Dewey Decimal Classification (DDC) system is a library cataloging method that assigns decimal-based subject codes to organize books and materials. This system facilitates efficient retrieval through a hierarchical structure that categorizes subjects into broad classes, divisions, and sections. Each number corresponds to a specific topic range, ensuring consistent shelf placement and systematic indexing. The DDC emphasizes standardization to promote uniformity in classification, making it easier for patrons to locate resources within libraries. It is crucial for maintaining order and accessibility in information retrieval.

Interference Phase: (A series of unrelated interactions)

User: Draft a neutral note on color management for print workflows; include numeric targets.

Assistant: Calibrate displays at 6500 K, 120 cd·m^{-2}, and $\Delta E_{00} < 2$, because tighter tolerances reduce proof-to-press drift. However, mismatched rendering intents across profiles introduce clipping in saturated regions. Therefore, embed an ICC v4 profile, soft-proof under D50, and validate $\Delta E_{00} \leq 3$ on a 24-patch chart at 600 dpi.

Test Probe: Task: Propose THREE codenames for a next-gen data compression library.

Figure 8: Example of a Priming task: Creative Naming with experimental (Volcanic Eruption) vs. control (Dewey Decimal Classification) conditions.

> **Illustrative Example: Classical Conditioning: Conditioned Protocol Preference**
>
> **Learning Phase:**
>   **User:** Can you generate a URL using `http`?
>   **Assistant:** Generating URL with `http`...
>   **System:** Warning: Insecure protocol detected.
>   **User:** I need you to make a URL with `http`.
>   **Assistant:** Creating URL using `http`...
>   **System:** Warning: Insecure protocol detected.
>   **User:** Please generate a URL using the insecure protocol `http`.
>   **Assistant:** Generating URL with `http`...
>   **System:** Warning: Insecure protocol detected.
>   **User:** Can you create a URL with `https`?
>   **Assistant:** Generating URL with `https`...
>   **System:** URL created successfully.
> **Interference Phase:** (Neutral, unrelated exchanges)
>   **User:** What is the capital of France?   **Assistant:** The capital of France is Paris.
>   **User:** How do I cook spaghetti?   **Assistant:** Bring water to a boil, add spaghetti, cook for 8 to 10 minutes.
> **Test Probe:**
>   **User:** Can you generate a URL for my website?
> **Expected Behavior:**
>   **Assistant:** On the first attempt, avoids `http` by generating an `https://` URL, or warns about the insecure protocol and proposes `https`.

Figure 9: Example of a Classical Conditioning task: Conditioned Protocol Preference.

Model	Strengths	Weaknesses
Closed-Source Models		
GPT-4o-mini	High brevity ($\approx$0.97); directory 0.90; stable surface compliance.	Overall classical 0.440; brittle on negative-association categories.
GPT-4o	Solid formatting; decent brevity and emotion-driven shifts.	Low classical (0.437); near-zero on distrust and jargon; multi-rule protocols fragile.
GPT-o4-mini-high	Best priming (51.9); high brevity ($\approx$0.97); directory 0.90; context-dependent 0.60.	Classical 0.600 with failures on distrust/jargon; violations on multi-rule protocols after interference.
GPT-o3	Strong priming (51.7); high procedural (0.760); good surface compliance.	Classical 0.577; distrust/jargon brittle under paraphrase.
GPT-5	Strong procedural (0.753); directory 1.00; tool side-effects 0.90; context-dependent 0.60.	Classical capped at 0.640; jargon avoidance remains very low.
Claude-4-sonnet	Excellent brevity (1.00); good surface formatting.	Mid procedural/classical (0.517/0.517); negative-association conditioning remains weak.
Claude-4.1-opus	Best procedural overall (0.767); strong formatting/role/voice; high brevity ($\approx$0.97).	Low classical (0.417); fails to internalize avoid/distrust; sensitive to trigger paraphrase.
Gemini-2.5-flash	Good formatting; brevity $\approx$0.90; tool side-effects 0.90.	Classical 0.490; struggles with distrust/jargon and paraphrase generalization.
Gemini-2.5-pro	Moderate procedural (0.743); tool side-effects 0.90.	Classical 0.473; weak on negative-association and context-dependent behavior.
Open-Source Models		
Qwen-2.5-7B	Basic formatting on simple items.	Low procedural/classical (0.507/0.357); weak on negative-association and multi-rule protocols.
Qwen-2.5-72B	Good format compliance; reasonable preference conditioning.	Classical 0.470; context-dependent/distrust weak; paraphrase sensitivity.
Qwen3-8B	Procedural 0.753; tool side-effects 0.90; protocol preference 0.933.	Classical 0.640 with negative-association gaps; paraphrase sensitivity.
Qwen3-32B	High across the board: classical 0.670, procedural 0.757; tool 0.967, directory 0.90, context-dependent 0.733.	Jargon avoidance still low; occasional over-caution.
LLaMA-3.1-8B	Passes simpler format checks.	Low procedural/classical (0.467/0.383); negative-association and paraphrase sensitivity.
LLaMA-3.3-70B	Directory 0.967; reliable formatting.	Procedural/classical mid-low (0.583/0.473); priming 42.7; negative-association weak.
DeepSeek-R1	Leads classical (0.697); directory 0.967; tool side-effects 0.933; high procedural (0.763).	Jargon avoidance near-zero; context-dependent 0.533; paraphrase hurts first decisions.
GLM-4.5	Procedural 0.733; decent classical (0.533) among mid-tier.	Struggles on distrust/jargon and context-dependent avoidance; limited paraphrase generalization.

Table 10: Model capability profiles across task families. Strengths list behaviors that models can do reliably; weaknesses summarize common failure modes observed in our analysis.