Robust Imitation of a Few Demonstrations with a Backwards Model

Abstract

Behavior cloning of expert demonstrations can speed up learning optimal policies in a more sample-efficient way over reinforcement learning. However, the policy cannot extrapolate well to unseen states outside of the demonstration data, creating covariate shift (agent drifting away from demonstrations) and compounding errors. In this work, we tackle this issue by extending the region of attraction around the demonstrations so that the agent can learn how to get back onto the demonstrated trajectories if it veers off-course. We train a generative backwards dynamics model and generate short imagined trajectories from states in the demonstrations. By imitating both demonstrations and these model rollouts, the agent learns both the demonstrated paths and how to get back on to these paths. With optimal or near-optimal demonstrations, the learned policy will be both optimal and robust to deviations, with a wider region of attraction. On continuous control domains, we evaluate the robustness when starting from different initial states unseen in the demonstration data. While both our method and other imitation learning baselines can successfully solve the tasks for initial states in the training distribution, our method exhibits considerably more robustness to different initial states.

1 Introduction

While reinforcement learning (RL) has shown remarkable success in many challenging domains [19, 36, 34], tasks with sparse rewards and long horizons still remain extremely difficult to solve. In such tasks, a positive reward is only encountered after the RL agent reaches the goal after a long sequence of actions, meaning that it cannot learn any useful signals until this occurs (typically the agent must reach the goal several times to learn reliably as well). Furthermore, the learning signal decreases exponentially with the horizon, which combined with slow gradient-based updates, can lead to catastrophic forgetting even after the agent learns to reach the goal.

Expert demonstrations can help RL agents solve difficult tasks [28, 40, 20]. These demonstrations can be used in the supervised setting where the agent imitates the expert's behavior, termed imitation learning (IL). However, naively cloning (BC) of the expert's trajectories suffers from covariate shift: the agent's policy drifts away from the expert's, which leads to compounding errors due to RL's sequential nature. Furthermore, the distribution of states given in the demonstrations often has low-dimensional support with respect to the entire state space. As such, the agent cannot extrapolate correctly when outside of the demonstration data. Many approaches to solve this issue have been proposed [31, 37, 14], but such approaches require an interactive expert to query the correct actions.

Another way to use demonstrations is to combine imitation learning with reinforcement learning in a form of learning from demonstrations (LfD) [33, 12, 8]. In this case, demonstrations do not simply act as supervised labels and can guide the agent's exploration, and also act as augmentations to good data samples. These LfD approaches either use demonstrations to pretrain the policy [33, 8], use an

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

| (a) Training | (b) Evaluation | (c) BC | (d) BMIL |

Figure 1: **(a)**, **(b)**: Robustness: The policy is trained on a specified set of initial start and goal states and is evaluated at different start states. **(c)**, **(d)**: BMIL uses generated reverse-time rollouts from a backwards model (green arrows originating from the demonstration) to learn a wider region of attraction (green) around the demonstration data (orange) than BC.

auxiliary imitation loss in conjunction with the policy update [28, 20], or modify the reward function such that the agent is rewarded when it imitates the demonstrations [47, 29].

One primary concern of relying on demonstrations is that they are costly to obtain, especially in real-world applications. Requiring an operator providing corrections in-the-loop to handle covariate shift is often prohibitive as well. Given only a few offline trajectories demonstrating successful task completion, an agent ought to be able to replicate the behavior from similar starting conditions, even if there are small perturbations along the way, and correct itself when necessary. We are primarily interested in this setting. In this work, we aim to minimize the number of demonstrations necessary for sparse-reward tasks, while preserving successful task completion. To tackle covariate shift, we seek an approach that will be *robust*, in the sense of Figures 1a and 1b: the agent is only trained with a few demonstrations from a single start state, but at evaluation time, it must generalize its behavior to a variety of unseen start states. If the agent can successfully complete the task from states adjacent to the demonstrated trajectory, then it can recover from small deviations from the demonstration.

Inspired by the notion of "funnels" in robotics [18] and feedback control [2, 17], we introduce a reverse-time generative model that can generate possible paths leading the agent back onto the demonstrations. These reverse rollouts provide useful information because every rollout ends within the support of the demonstration data. Assuming that the demonstrations lead to the goal, imitating these generated reverse rollouts and the original demonstration data allow the agent to reach the goal from more starting conditions, including unseen ones. As illustrated in Figures 1c and 1d, typical behavior-cloning (BC) methods focus learning on the small number of demonstrated states, whereas our proposed approach, Backwards Model-based Imitation Learning (BMIL), uses the reverse rollouts to learn a wider region of attraction around the demonstration. We validate our approach on a number of long-horizon, sparse-reward continuous-control tasks. Even from 5–20 demonstrations, BMIL provides a significant increase in the region of attraction and robustness on many domains compared to BC, or to using a forward dynamics model.

We summarize our contributions as follows:

- We propose an imitation learning method that pairs a backwards dynamics model with a policy and train on both demonstrations and imagined model rollouts.

- In the restrictive setting of an offline expert and no access to environment interactions, we show that a backwards model can improve robustness over behavior cloning.

- Our experiments on a variety of long-horizon, sparse-reward domains demonstrate that BMIL can noticeably extend the region of attraction around the demonstration data, even when trained on very small subsets of the state space.

2   Related Work

Imitation learning has a long history [25, 33] and is well-studied, as documented in various surveys [1, 23, 10]. The challenges of covariate shift and compounding errors are also well-known [25, 30]. Most solutions involve on-policy imitation learning, where environment interaction and interactive querying of the expert allow for the agent's distribution to match that of the expert [31, 37]. More closely related to our approach are methods that modify or augment the demonstrations to increase robustness. Laskey et al. [14] inject noise into the supervisor's policy during training to force the demonstrator to provide corrections. Luo et al. [16] learn value function and dynamics model from demonstrations, using this to conservatively extrapolate a value function that encourages the agent to

return to the expert data distribution. Generative approaches have also been used in imitation learning [9, 43], but their focus is not on robustly following a few goal-reaching demonstrations.

Time-reversibility has been explored in RL, often as a form of regularization [38, 21, 46, 27, 32]. Reverse-time dynamics models, also called predecessor models, have also been used in RL [3, 5, 35, 13, 15, 45, 6]. However, in all cases, the reverse-time dynamics model is used as either an alternative to the forward-time dynamics model or as an auxiliary model in addition to the standard forward-time dynamics model, in order to mitigate model-compounding errors. The result is that the reverse-time dynamics model can accelerate RL and enable greater sample-efficiency. In this work, we take a different perspective where the reverse-time dynamics model is used to generate possible, unseen paths that can lead back to the expert demonstration and thus to the goal, thereby improving robustness in following the demonstration. Our work is also similar to [42], where a reverse-time dynamics model is used to generate possible trajectories; however, their focus is on offline RL, where the generated trajectories are used to connect distinct sets of states in the offline dataset.

3 Method

3.1 Preliminaries

We model the setting as a Markov Decision Process (MDP) with a continuous state space $\mathcal{S}$ and a continuous action space $\mathcal{A}$. $T : \mathcal{S} \times \mathcal{A} \mapsto \mathcal{S}$ is the transition function that defines the distributions of the next state $s_{t+1} \in \mathcal{S}$, given the current state $s_t \in \mathcal{S}$ and action $a_t \in \mathcal{A}$ taken at timestep t.

The objective of imitation learning is to learn a policy π_θ, parameterized by θ, that matches the expert's policy π_E. We assume that the expert generates demonstrations $\mathcal{D}_{demo}$ by rolling out its policy π_E in the environment. Note that we consider the more restrictive case of where demonstrations only consist of transitions (s, a, s') and not rewards, where s' is the next state and r is the reward.

Behavior cloning (BC) is a form of imitation learning where the policy π_θ learns to imitate expert actions via supervised learning. The policy learned by behavior cloning is found by minimizing the negative log-likelihood over the demonstration data

$$\mathcal{L}_{BC} = \mathbb{E}_{(s,a)\in\mathcal{D}_{demo}} \left[-\log \pi_\theta(a \mid s) \right].$$

Note that BC does not require environment interactions and can be considered to be offline. Furthermore, expert behavior is inferred only from demonstrations without access to the expert policy.

Compounding errors in behavior cloning   As pointed out in [30, 41], behavior cloning suffers from covariate shift, where errors in the policy can compound and lead the agent to states where it cannot recover. Intuitively, this occurs as states in the training data $\mathcal{D}_{demo}$ is a small subset of the entire state space $\mathcal{S}$ and it is difficult for the policy π_θ to learn the optimal action for states outside of the training data. If during a rollout, once the policy π_θ makes an error and leaves the $\mathcal{D}_{demo}$, it may encounter completely new states, leading to the compounding of errors. Furthermore, as the agent moves farther away from $\mathcal{D}_{demo}$, there is very little hope for it to make the correct action and move back onto the distribution of the training data.

3.2 Problem Setting

We consider the same setting as BC, where we do not assume access to the environment or the expert policy during training and only expert demonstrations with no rewards are given. Furthermore, we assume that the expert demonstrations are given in the MDP where the set of initial states $s_0 \in S_0$ and goals $g \in \mathcal{G}$ is restricted to a very small subset of the state space. An example of this scenario is a maze environment where the agent starts from the same initial state and tries to reach a fixed goal. Formally, we define the demonstration trajectories τ_{demo} as coming from a probability density

$$p(\tau_{demo} \mid \pi_E) = p(s_0) \prod_{t=0}^{T-1} \pi_E(s_t \mid a_t) p(s_{t+1} \mid s_t, a_t),$$

where $s_0 \in S_0$, and $s_T \in \mathcal{G}$. In all of our experiments, S_0 and $\mathcal{G}$ consist of a single start or goal state and the ε-ball of its neighborhood. As such, only a few demonstrations are required to learn a stable optimal policy. Note that this is different from domains in previous work [28, 4] which consider

random goal states, requiring many more demonstrations to learn optimal policies. We also assume that the expert policy is optimal in that all demonstrations successfully reach a goal. While this is not strictly necessary in our method, we assumed that there are no rewards in τ_{demo} and thus we cannot discern whether demonstrations are optimal. In order to use task completion success rates as an evaluation metric in our experiments, we consider optimal demonstrations.

Our objective is to learn a policy that is robust to policy errors when imitating expert behavior and can learn to reach the goal from a variety of initial states. This is different than the multi-goal or multi-task setting, where the agent learns to solve multiple goals or tasks, usually from a small number of initial states. More formally, the robustness of the policy $R(\pi_\theta)$ is defined as

$$R(\pi_\theta) = \mathbb{E}_{s_0 \in S_R} \left[\mathbb{1}\{\exists t \leq T, s_t \in \mathcal{G}\} \right],$$

where the expectation is taken over S_R, where S_R is a strict superset of S_0. Note that our measure of robustness is somewhat coarse, in that we do not consider the shortest path to reach the goal from every start state (which would probably require more information such as diverse trajectories or environment interactions). Instead, we seek to extend the region of attraction around $\mathcal{D}_{demo}$ such that the learned policy can still reach the goal.

As we consider continuous states in our work, we measure the robustness R using samples from S_R, either by sampling randomly or by using stratified random sampling over a discretized grid of the state space. For some domains like maze environments, we are primarily concerned with being able to learn robustness in terms of spatial coordinates such that the agent can learn to go back onto the optimal path. Thus we restrict the expectation to only the spatial dimensions for such domains. In other domains, we are interested in the policy's ability to recover from arbitrary initial states and so we vary the initial joint positions by adding uniformly random noise.

Throughout, we assume that there exists an action $a \in \mathcal{A}$ that allows the policy to go towards $\mathcal{D}_{demo}$ when in a state $s \notin \mathcal{D}_{demo}$. This scenario is true for many navigation and physics-based domains if we ignore the rare circumstances such as irrecoverable unsafe states or the breakdown of the agent. We exclude such cases and assume that state transitions are reversible.

3.3 Backwards Model-based Imitation Learning

In our work, we use a backwards dynamics model to provide more synthetic training data to the policy and therefore increase the policy's robustness. We call our method backwards model-based imitation learning or BMIL.

Backwards model The backwards model is a probabilistic generative model defined as $B = p(s_t, a_t \mid s_{t+1})$. This model estimates the conditional distribution of the reverse time dynamics. It takes in the next state and outputs the previous state and previous action. As we consider only continuous state and action spaces, we implement B as a conditional Gaussian, parameterized by ϕ.

The backwards model is decomposed into two functions $B = B_A \cdot B_S = p(a_t \mid s_{t+1}) \cdot p(s_t \mid a_t, s_{t+1})$, an action generator and previous state generator. The action generator B_A predicts which action was taken in order to land in the next state. There may be several such actions from different states that can lead to the next state. Thus the action generator implicitly encodes a backwards policy. It is important for this backwards policy to closely match the learned forward policy π but be different enough to generate diverse new rollouts for the policy to train on. The previous state generator B_S predicts the previous state given the next state and previous action taken. The goal of this generator is to accurately predict the backwards dynamics, which are learned using rollouts from the policy π.

As we consider the setting with no access to the expert or the environment, B is trained only on $\mathcal{D}_{demo}$. The action generator and previous state generator are jointly trained by maximum likelihood

$$\mathcal{L}_B = \sum_{t=0}^{T} \log p(a_t \mid s_{t+1}) + \log p(s_t \mid a_t, s_{t+1}), \tag{1}$$

where s_t, a_t, s_{t+1} is the state, action, and next state, respectively, at timestep t.

Model rollouts Given expert demonstrations τ_E, we use the backwards model to generate possible several short reverse rollouts or traces τ_B, starting from every state in τ_E. As all of these traces

end on states within the demonstration data $s \in \mathcal{D}_{demo}$ and as the demonstration reaches the goal, following these traces will eventually lead to the goal. For all $s_1, \ldots, s_T$ in τ_E, we generate K traces τ_B in a time-reversed manner, where we start from the last state action pair $(s_H, a_H) \in \mathcal{D}_{demo}$ and then predict (s_t, a_t) for timesteps $t = H - 1, \ldots, 1$. These traces are collected into a buffer $\mathcal{D}_M$. As we assumed that there are no irrecoverable states in our setting, the rollouts reflect possible paths that the agent could have taken to reach $s \in \mathcal{D}_{demo}$. If the reverse time model B is accurate and the previous action generator B_A gives sufficiently diverse actions, the traces τ_B are then samples from the region of attraction or "funnels" around every state along the demonstration. As we assume all demonstrations reach the goal, these samples from the funnels can be used to learn a robust policy π_θ, as it can follow the traces onto the optimal path.

Action selection strategy for B_A As the backwards model B is trained only on a limited number of expert demonstrations, it is likely that B can only learn accurate reverse-time dynamics for states contained within or close to the demonstration data $\mathcal{D}_{demo}$ [44]. Thus repeatedly rolling out B_A would only generate traces whose (s, a) pairs are contained within $\mathcal{D}_{demo}$ and would not help with learning robust policies. However, we would like to generate diverse traces with new unseen state-action pairs in order to robustify the policy. To balance the model misprediction accuracy with generating plausible state-action pairs, we slightly perturb the action generated from B_A for the first action only and use short horizon lengths for the traces. This amounts to choosing a good action selection strategy for B_A. A good action selection strategy would then place more probability closer to the support of the $\mathcal{D}_{demo}$, providing a "cover" of $p(a_E|s)$ but with enough of a wide tail to provide diverse rollouts. As our backwards model B is probabilistic (implemented as a conditional Gaussian with diagonal covariance), we can easily perturb $p(a_E|s)$ by increasing the distribution's variance.

Let $a \sim \mathcal{N}(\mu, \sigma^2) = B_{\phi_A}^A(a|s')$. We consider two ways to generate action a: 1) simple scaling of the σ and 2) resampling a noisy version of a by adding uniform noise, $a' = a + k, k = \mathcal{U}[-k, k]$, where k is a fixed hyperparameter. For the scaling strategy, we further scale σ by the entropy of the probability density as we wish to make the distribution "wider" for more peaky distributions.

Algorithm Our method BMIL is outlined in Algorithm 1. Given expert demonstrations of the form (s_t, a_t), we train the backwards model using Eqn. 1 to estimate the reverse-time dynamics $p(s_t, a_t \mid s_{t+1})$. We train our policy π_θ on both the demonstration data $\mathcal{D}_{demo}$ and the model traces τ_B by sampling from both at a fixed ratio and using maximum likelihood,

$$\mathcal{L} = p_d \mathcal{L}_{BC} + (1 - p_d)\mathbb{E}_{(s,a)\sim\tau_B} \left[-\log \pi_\theta(a \mid s) \right], \tag{2}$$

where p_d is the probability of sampling from $\mathcal{D}_{demo}$. As our aim is to learn a robust policy while still succeeding at the original start states and goals, we sample from the demonstrations a higher ratio than the model traces.

As we consider the limited case of an offline expert and no-reward demonstrations, we pair behavior cloning with the backwards model. Note that BMIL does not depend on the type of imitation learning policy; any algorithm can be used as long as the policy can be trained with samples of the form (s, a).

4 Experiment Design

4.1 Environments

We validate our approach on several continuous control domains: 1) the Fetch robotics environment [24], 2) maze navigation with two different agents, and 3) Adroit hand domain [28]. For the Fetch

---

Algorithm 1 Backwards Model-based Imitation Learning (BMIL)

1: **for** N epochs **do**
2:     Train backwards model parameters ϕ using Eqn. (1).
3:     Generate K model traces τ_B from every state $s \in \mathcal{D}_{demo}$ and store them in $\mathcal{D}_M$.
4:     **for** M steps **do**
5:         Sample mini-batch of (s, a) from $\mathcal{D}_{demo}$ and $\mathcal{D}_M$ at a fixed ratio.
6:         Update policy parameters θ using Eqn. (2).
7:     **end for**
8: **end for**

---

robotics environments, we consider the "Push" and "PickAndPlace" tasks where the objective is to control a Fetch end effector to either push an object to the goal or pick an object and place it at the target location. For the maze environments, we consider 3 mazes of increasing difficulty, where an agent must learn to move to the goal. We use both a simple point and 29-DoF ant agent. For the Adroit environments, we use the 'Relocate' task, where one must control a 24-DoF Adroit hand to pick up a ball and move it to a target location. All domains use the Mujoco simulator [39] for a total of 9 distinct domains. All environments also have sparse reward structures, where either only every step has a constant negative reward until the goal is reached (Fetch) or only the goal has a non-zero reward (Maze, Adroit). In particular, the maze and Adroit environments are quite challenging as they both consist of controlling the agent's joints to perform locomotion (maze) or dexterous manipulation (Adroit) over a long horizon. More detailed descriptions of each environment including its observation space are provided in Appendix A.

4.2 Demonstrations and Implementation Details

To generate demonstrations on the Fetch and Maze domains, we train an expert policy by adding the goal position to the state, as in goal-oriented learning. For the Adroit domain, we use a pre-trained policy from [28]. We use 5 demonstrations on the Push task and 10 on the PickAndPlace task, and 20 demonstrations for all maze and Adroit environments.

For the policy, we use neural networks with 3 fully connected hidden layers with 256 neurons and ReLU activations. For the backwards model, we use 4-layer MLPs with 256 hidden units for both the action predictor B_A and previous state predictor B_S and use diagonal Gaussian distributions. To train the policy, we use $p_d = 0.5$ for the Fetch environments, $p_d = 0.8 \sim 0.95$ for the Maze environments, and $p_d = 0.8$ for the Adroit environments. We find that higher demo ratios are necessary for longer-horizon and more complex domains. For the model rollouts, we use the variance scaling action selection strategy for the first action only and use increasing rollout lengths for all domains, similar to [11]. For a more detailed discussion of experiment details, see Appendix B.

4.3 Evaluation

We evaluate BMIL against behavior cloning (BC) and VINS [16]. VINS specifically aims to learn value functions robust to perturbations using negative sampling and the induced policy learns self-corrective behavior. VINS was chosen as it is most relevant to our setting; other methods such as DART [14] or SQIL [29] require either an online expert or environment interactions.

We use the same number of demonstrations for all methods and also keep the same policy network architecture and the total number of policy gradient steps equal across all methods. We train both the policy and backwards model until the backwards model loss converges. Note that our goal is not to solve the training task faster but rather to robustify the policy using the backwards model. Additionally, we wish to solve the task at various starting conditions while still being able to succeed at the original initial start-goal states.

To evaluate the robustness of the learned policy, we vary the initial states and compute task success rates. For Fetch, we fix the initial gripper, object, and goal position during training and vary the gripper's x and y position within the table boundaries during evaluation. We use 10000 samples during evaluation. For Maze, we initialize the agent to a random start position within a discretized grid of the maze. We sample 100 for each discrete grid cell and compute the success rate. Sampling points for each grid cell gives us an idea of which positions are easy for the agent to reach the goal. Intuitively, such positions would be those near the goal and the demonstrated path. For Adroit, we generate 10000 random initial states by adding uniform noise to the qpos of the hand (30-dim).

5 Results

Our experiments aim to answer the following questions: 1) how robust of a policy does BMIL learn? and 2) what components of BMIL are important to improve robustness?

			Robustness (%)			Relative to BC		
			BC	VINS	BMIL	BC	VINS	BMIL
FETCH	Push (5 demos)		$12.1_{\pm0.3}$	$12.8_{\pm0.4}$	$\mathbf{14.6}_{\pm0.6}$	1	1.06	**1.21**
	PickAndPlace (10 demos)		$4.1_{\pm0.1}$	$3.4_{\pm0.1}$	$\mathbf{17.5}_{\pm0.9}$	1	0.84	**4.31**
MAZE	Point (20 demos)	UMaze	$\mathbf{48.8}_{\pm2.0}$	$39.7_{\pm2.1}$	$47.9_{\pm3.6}$	**1**	0.81	0.98
		Room5x11	$36.3_{\pm3.2}$	$22.0_{\pm3.4}$	$\mathbf{43.8}_{\pm3.9}$	1	0.61	**1.21**
		Corridor7x7	$36.8_{\pm1.6}$	$37.5_{\pm1.4}$	$\mathbf{39.5}_{\pm1.9}$	1	**1.02**	1.07
	Ant (20 demos)	UMaze	$\mathbf{62.1}_{\pm1.2}$	$44.2_{\pm1.9}$	$64.9_{\pm1.4}$	**1**	0.71	1.04
		Room5x11	$\mathbf{32.9}_{\pm0.9}$	$30.2_{\pm0.7}$	$28.7_{\pm0.7}$	**1**	0.92	0.87
		Corridor7x7	$\mathbf{21.6}_{\pm0.5}$	$19.4_{\pm0.5}$	$17.7_{\pm0.5}$	**1**	0.90	0.82
ADROIT	Relocate (20 demos)		$7.9_{\pm0.7}$	-	$\mathbf{13.3}_{\pm1.0}$	1	-	**1.68**

Table 1: Robustness evaluation for Fetch, Maze, and Adroit environments over 400,100,100 trials, respectively. The bounds indicate 95% confidence intervals. BMIL improves robustness considerably over BC in most environments.

BC   BMIL   BC   BMIL

(a) Push   (b) PickAndPlace

Figure 2: Visualization of robustness on Fetch for BC and BMIL. We vary the gripper's x, y position to evaluate robustness. The green and gray points denote successful and unsuccessful initial positions. The red, orange, and blue points denote the initial start, object, and goal during training. BMIL learns a much larger region of attraction along the path from the initial start (red) to the goal position (blue) and even succeeds in some other areas much farther away.

5.1 Robustness evaluation

The robustness results are shown in Table 1. We note that the absolute robustness percentages are generally low for all methods because it is very difficult to extrapolate from limited demonstrations $(5 - 20)$ from a single pair of initial start and goal states. We therefore also include the relative improvement over BC.

In the Fetch environments, BMIL substantially increases robustness over BC and VINS. In particular, our method has an approximately 20% and 330% improvement over BC on Push and PickAndPlace, respectively. VINS on the other hand performs similarly to BC. We see a similar pattern on the harder Adroit environment, where BMIL improves robustness over BC by approximately 68%. For the Maze environments, BMIL generally outperforms BC for the Point agent, while the robustness is decreased for the Ant agent. Somewhat surprisingly, BC performs quite well on the long-horizon Maze domains. It may be that BC has some built-in extrapolation capabilities or that the backwards model may need better latent representations.

Empirically, we can see that having short reverse rollouts from the backwards model and using only slight perturbations still helps to increase robustness, even though the traces contain some model misprediction errors. We hypothesize that this is these traces do not necessarily need to be accurate in order to benefit the policy and simply need to be plausible paths that lead to the demonstrations. It may be that having the general correct direction contained in the traces is sufficient for the policy to eventually reach states in the demonstration data.

The success rates during training are shown in Table 5 in the Appendix. BMIL achieves success rates close to 1 for most domains, suggesting that increased robustness does not necessarily come at the cost of decreased performance on demonstrated start-goal states. On the other hand, VINS cannot consistently succeed during training, even though its robustness is similar to BC.

BC	BMIL	BC	BMIL
(a) PointRoom5x11		(b) PointCorridor7x7	

Figure 3: Visualization of robustness on PointRoom5x11 and PointCorridor7x7 for BC and BMIL. Positions in the domain is discretized into a grid and 100 random points are sampled as the initial state position. Bright yellow corresponds to 100% success rate while dark purple corresponds to 0%. The regions of attraction for both BC and BMIL are similar in size but BMIL succeeds more often within its region of attraction.

Visualization of robustness   Figure 2 shows which starting positions succeed during the robustness evaluation for Fetch. The green points correspond to successful episodes. We can see that both BC and BMIL succeed more frequently when starting from nearby the demonstration data (approximately a straight line from the start (red) to goal (blue)). However, we can see that BMIL learns a much larger region of attraction over BC and even succeeds at points that are much farther away from $\mathcal{D}_{demo}$. We hypothesize that instead of perturbing a single state within $\mathcal{D}_{demo}$ as done in VINS, learning a short reverse rollout from this state allows BMIL to learn optimal paths from states much farther away from $\mathcal{D}_{demo}$, leading to higher robustness values. Figure 3 shows a similar visualization for some Point maze environments where the agent's position is discretized into a grid. BMIL learns a region of attraction similar in size to that of BC but has a higher rate of success at each cell.

5.2   Additional Experiments

Forward vs Backward Dynamics   We first analyze the utility of a backwards vs a forward dynamics model. On the Fetch environments, we train BMIL with a forward dynamics model $p(s' \mid s, a)$ and compare it against the original backwards model $p(s, a \mid s')$. The forward model is implemented nearly identically to other n-step model-based RL algorithms (e.g. [11]), with the exception of no environment interactions. As with the backwards model, we generate rollouts from the forwards model starting from demonstrated states and train the policy on both the demonstrations and traces. To generate model rollouts from demonstration states, we use the action from the policy $a = \pi_\theta(s)$. The total number of parameters is kept approximately constant for the forwards and backwards models. As shown in Table 2, the forwards model offers little to no benefit over BC for both Push and PickAndPlace, suggesting that the backwards model is needed to produce a robust policy.

Action selection strategy   We ablate different action selection strategies in trace generation in Figure 4a (and Figure 9 in the Appendix). Compared to no perturbation (None), we see that either action selection strategy improves robustness as it can lead to more diverse trajectories unseen within the support of the demonstrations. We use the variance scaling strategy SC(30) for all Fetch experiments as it was more stable than SC(50).

Number of demonstrations   We also studied our method with varying numbers of demonstrations. As shown in Figure 4b, both BC and BMIL improve in robustness with more demonstrations, but BC plateaus at a much lower level. On the other hand, BMIL requires slightly more (10) demonstrations than needed (3 demonstrations are sufficient for BC to succeed during training) in order to train the backwards model (Figure 10 in the Appendix).

	Robustness (%)			Relative to BC		
	BC	BMIL (Forwards)	BMIL (Backwards)	BC	BMIL (Forwards)	BMIL (Backwards)
Push (5 demos)	$12.1_{\pm 0.3}$	$12.4_{\pm 0.6}$	$14.6_{\pm 0.6}$	1	1.03	1.21
PickAndPlace (10 demos)	$4.1_{\pm 0.1}$	$4.1_{\pm 0.2}$	$17.5_{\pm 0.9}$	1	1.03	4.31

Table 2: Forwards ($p(s' \mid s, a)$) vs Backwards ($p(s, a \mid s')$) dynamics model: The forwards dynamics model performs similarly to BC and does not increase robustness.

(a) Action selection strategy   (b) No. of demonstrations

Figure 4: **(a)** Action selection strategy: effect of no perturbation (None), resampling (RS), and scaling (SC) on robustness on PickAndPlace. The numbers in the brackets indicate coefficients. We see that perturbing the first action is beneficial compared to the no perturbation (None) method and allows the backwards model to generate diverse traces. **(b)** Number of demonstrations on PickAndPlace: more demonstrations increase robustness for BC and BMIL, but BC plateaus at a much lower level.

Computation budget As BMIL trains both the policy and the backwards model, it requires more total gradient updates than BC. On Fetch domains, BMIL uses approximately 5x more computation than BC. We train BC for more steps to match or exceed BMIL's computation budget, as shown in Figure 5 (BC given 1x–20x computation budget). However, more training for BC does not improve robustness and seems to have a harmful effect on robustness.

       Push   PickAndPlace

Figure 5: Computation budget: we increase the number of gradient steps for BC by $1 - 20$x for Fetch. BMIL has roughly 5 times more total gradient steps than BC(1x) due to the backwards model update. More BC gradient steps do not increase robustness.

Training model first and then the policy As an offline method, BMIL does not require the backwards model to be trained in a single loop along with the policy. We can first train the model first and then train the policy. We compare training the model first and then the policy with the process outlined in Algorithm 1. We find there are no noticeable differences when using this model first approach on the Fetch domains, as seen in Table 6.

6   Discussion

This work proposed a method to tackle the issue of covariate shift in imitation learning. We considered the restrictive setting where the expert is offline, where its behavior can only be inferred from demonstrations, and no access to additional environment interactions. Specifically, we show that pairing a generative backwards model with behavior cloning can allow a policy to learn a wider region of attraction around the demonstration data. By rolling out imagined traces from states within the demonstration and perturbing actions to generate diverse traces, BMIL learns a wider funnel than naive BC. Through experiments on several long-horizon, sparse-reward, continuous control domains, BMIL noticeably improves robustness when trained on a narrow set of initial start and goal states and evaluated at random starting positions. Future work will include applying BMIL to more difficult tasks and extending BMIL to allow for environment interactions and pairing with other imitation learning algorithms.

References

[1] Brenna D. Argall, Sonia Chernova, Manuela Veloso, and Brett Browning. A survey of robot learning from demonstration. *Robotics and Autonomous Systems*, 57(5):469–483, 2009. ISSN 0921-8890. doi: https://doi.org/10.1016/j.robot.2008.10.024. URL `https://www.sciencedirect.com/science/article/pii/S0921889008001772`.

[2] Robert R. Burridge, Alfred A. Rizzi, and Daniel E. Koditschek. Sequential composition of dynamically dexterous robot behaviors. *The International Journal of Robotics Research*, 18(6): 534–555, 1999.

[3] Ashley D. Edwards, Laura Downs, and James C. Davidson. Forward-backward reinforcement learning, 2018.

[4] Justin Fu, Aviral Kumar, Ofir Nachum, George Tucker, and Sergey Levine. D4rl: Datasets for deep data-driven reinforcement learning, 2020.

[5] Anirudh Goyal, Philemon Brakel, William Fedus, Soumye Singhal, Timothy Lillicrap, Sergey Levine, Hugo Larochelle, and Yoshua Bengio. Recall traces: Backtracking models for efficient reinforcement learning. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=HygsfnR9Ym`.

[6] Nathan Grinsztajn, Johan Ferret, Olivier Pietquin, Philippe Preux, and Matthieu Geist. There is no turning back: A self-supervised approach for reversibility-aware reinforcement learning. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL `https://openreview.net/forum?id=3X65eaS4PtP`.

[7] Tuomas Haarnoja, Aurick Zhou, Pieter Abbeel, and Sergey Levine. Soft actor-critic: Off-policy maximum entropy deep reinforcement learning with a stochastic actor. 2017.

[8] Todd Hester, Matej Vecerík, Olivier Pietquin, Marc Lanctot, Tom Schaul, Bilal Piot, Dan Horgan, John Quan, Andrew Sendonaris, Ian Osband, Gabriel Dulac-Arnold, John P. Agapiou, Joel Z. Leibo, and Audrunas Gruslys. Deep q-learning from demonstrations. In *AAAI*, 2018.

[9] Jonathan Ho and Stefano Ermon. Generative adversarial imitation learning. In D. Lee, M. Sugiyama, U. Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 29. Curran Associates, Inc., 2016. URL `https://proceedings.neurips.cc/paper/2016/file/cc7e2b878868cbae992d1fb743995d8f-Paper.pdf`.

[10] Ahmed Hussein, Mohamed Medhat Gaber, Eyad Elyan, and Chrisina Jayne. Imitation learning: A survey of learning methods. *ACM Comput. Surv.*, 50(2), apr 2017. ISSN 0360-0300.

[11] Michael Janner, Justin Fu, Marvin Zhang, and Sergey Levine. When to trust your model: Model-based policy optimization. In *Advances in Neural Information Processing Systems*, 2019.

[12] Beomjoon Kim, Amir-massoud Farahmand, Joelle Pineau, and Doina Precup. Learning from limited demonstrations. In C. J. C. Burges, L. Bottou, M. Welling, Z. Ghahramani, and K. Q. Weinberger, editors, *Advances in Neural Information Processing Systems*, volume 26. Curran Associates, Inc., 2013. URL `https://proceedings.neurips.cc/paper/2013/file/fd5c905bcd8c3348ad1b35d7231ee2b1-Paper.pdf`.

[13] Hang Lai, Jian Shen, Weinan Zhang, and Yong Yu. Bidirectional model-based policy optimization. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 5618–5627. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/lai20b.html`.

[14] Michael Laskey, Jonathan Lee, Roy Fox, Anca D. Dragan, and Ken Goldberg. DART: noise injection for robust imitation learning. In *1st Annual Conference on Robot Learning, CoRL 2017, Mountain View, California, USA, November 13-15, 2017, Proceedings*, volume 78 of *Proceedings of Machine Learning Research*, pages 143–156. PMLR, 2017. URL `http://proceedings.mlr.press/v78/laskey17a.html`.

[15] Kimin Lee, Younggyo Seo, Seunghyun Lee, Honglak Lee, and Jinwoo Shin. Context-aware dynamics model for generalization in model-based reinforcement learning. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 5757–5766. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/lee20g.html`.

[16] Yuping Luo, Huazhe Xu, and Tengyu Ma. Learning self-correctable policies and value functions from demonstrations with negative sampling. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rke-f6NKvS`.

[17] Anirudha Majumdar and Russ Tedrake. Funnel libraries for real-time robust feedback motion planning. *The International Journal of Robotics Research*, 36(8):947–982, 2017.

[18] Matthew T. Mason. The mechanics of manipulation. In *IEEE International Conference on Robotics and Automation*, 1985.

[19] Volodymyr Mnih, Koray Kavukcuoglu, David Silver, Andrei A Rusu, Joel Veness, Marc G Bellemare, Alex Graves, Martin Riedmiller, Andreas K Fidjeland, Georg Ostrovski, et al. Human-level control through deep reinforcement learning. *nature*, 518(7540):529–533, 2015.

[20] Ashvin Nair, Bob McGrew, Marcin Andrychowicz, Wojciech Zaremba, and Pieter Abbeel. Overcoming exploration in reinforcement learning with demonstrations. In *2018 IEEE International Conference on Robotics and Automation (ICRA)*, pages 6292–6299. IEEE, 2018.

[21] Suraj Nair, Mohammad Babaeizadeh, Chelsea Finn, Sergey Levine, and Vikash Kumar. Trass: Time reversal as self-supervision. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 115–121, 2020. doi: 10.1109/ICRA40945.2020.9196862.

[22] Soroush Nasiriany, Vitchyr Pong, Steven Lin, and Sergey Levine. Planning with goal-conditioned policies. In *NeurIPS*, pages 14814–14825, 2019. URL `https://proceedings.neurips.cc/paper/2019/hash/c8cc6e90ccbff44c9cee23611711cdc4-Abstract.html`.

[23] Takayuki Osa, Joni Pajarinen, Gerhard Neumann, J. Andrew Bagnell, Pieter Abbeel, and Jan Peters. An algorithmic perspective on imitation learning. *Foundations and Trends® in Robotics*, 7(1-2):1–179, 2018. ISSN 1935-8253. doi: 10.1561/2300000053. URL `http://dx.doi.org/10.1561/2300000053`.

[24] Matthias Plappert, Marcin Andrychowicz, Alex Ray, Bob McGrew, Bowen Baker, Glenn Powell, Jonas Schneider, Josh Tobin, Maciek Chociej, Peter Welinder, Vikash Kumar, and Wojciech Zaremba. Multi-goal reinforcement learning: Challenging robotics environments and request for research, 2018.

[25] Dean A. Pomerleau. Alvinn: An autonomous land vehicle in a neural network. In D. Touretzky, editor, *Advances in Neural Information Processing Systems*, volume 1. Morgan-Kaufmann, 1989. URL `https://proceedings.neurips.cc/paper/1988/file/812b4ba287f5ee0bc9d43bbf5bbe87fb-Paper.pdf`.

[26] Antonin Raffin. Rl baselines3 zoo. `https://github.com/DLR-RM/rl-baselines3-zoo`, 2020.

[27] Nasim Rahaman, Steffen Wolf, Anirudh Goyal, Roman Remme, and Yoshua Bengio. Learning the arrow of time for problems in reinforcement learning. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=rylJkpEtwS`.

[28] Aravind Rajeswaran, Vikash Kumar, Abhishek Gupta, Giulia Vezzani, John Schulman, Emanuel Todorov, and Sergey Levine. Learning Complex Dexterous Manipulation with Deep Reinforcement Learning and Demonstrations. In *Proceedings of Robotics: Science and Systems (RSS)*, 2018.

[29] Siddharth Reddy, Anca D. Dragan, and Sergey Levine. Sqil: Imitation learning via reinforcement learning with sparse rewards. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=S1xKd24twB`.

[30] Stephane Ross and Drew Bagnell. Efficient reductions for imitation learning. In Yee Whye Teh and Mike Titterington, editors, *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pages 661–668, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR. URL `https://proceedings.mlr.press/v9/ross10a.html`.

[31] Stephane Ross, Geoffrey Gordon, and Drew Bagnell. A reduction of imitation learning and structured prediction to no-regret online learning. In Geoffrey Gordon, David Dunson, and Miroslav Dudík, editors, *Proceedings of the Fourteenth International Conference on Artificial Intelligence and Statistics*, volume 15 of *Proceedings of Machine Learning Research*, pages 627–635, Fort Lauderdale, FL, USA, 11–13 Apr 2011. PMLR. URL `https://proceedings.mlr.press/v15/ross11a.html`.

[32] Harsh Satija, Philip Amortila, and Joelle Pineau. Constrained Markov decision processes via backward value functions. In Hal Daumé III and Aarti Singh, editors, *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 8502–8511. PMLR, 13–18 Jul 2020. URL `https://proceedings.mlr.press/v119/satija20a.html`.

[33] Stefan Schaal et al. Learning from demonstration. *Advances in neural information processing systems*, pages 1040–1046, 1997.

[34] Julian Schrittwieser, Ioannis Antonoglou, Thomas Hubert, Karen Simonyan, Laurent Sifre, Simon Schmitt, Arthur Guez, Edward Lockhart, Demis Hassabis, Thore Graepel, et al. Mastering atari, go, chess and shogi by planning with a learned model. *Nature*, 588(7839):604–609, 2020.

[35] Yannick Schroecker, Mel Vecerik, and Jon Scholz. Generative predecessor models for sample-efficient imitation learning. In *International Conference on Learning Representations*, 2019. URL `https://openreview.net/forum?id=SkeVsiAcYm`.

[36] David Silver, Aja Huang, Christopher J. Maddison, Arthur Guez, Laurent Sifre, George van den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, Sander Dieleman, Dominik Grewe, John Nham, Nal Kalchbrenner, Ilya Sutskever, Timothy Lillicrap, Madeleine Leach, Koray Kavukcuoglu, Thore Graepel, and Demis Hassabis. Mastering the game of go with deep neural networks and tree search. *Nature*, 529:484–503, 2016. URL `http://www.nature.com/nature/journal/v529/n7587/full/nature16961.html`.

[37] Wen Sun, Arun Venkatraman, Geoffrey J. Gordon, Byron Boots, and J. Andrew Bagnell. Deeply AggreVaTeD: Differentiable imitation learning for sequential prediction. In Doina Precup and Yee Whye Teh, editors, *Proceedings of the 34th International Conference on Machine Learning*, volume 70 of *Proceedings of Machine Learning Research*, pages 3309–3318. PMLR, 06–11 Aug 2017. URL `https://proceedings.mlr.press/v70/sun17d.html`.

[38] Pierre Thodoroff, Audrey Durand, Joelle Pineau, and Doina Precup. Temporal regularization for markov decision process. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL `https://proceedings.neurips.cc/paper/2018/file/4b0250793549726d5c1ea3906726ebfe-Paper.pdf`.

[39] Emanuel Todorov, Tom Erez, and Yuval Tassa. Mujoco: A physics engine for model-based control. In *2012 IEEE/RSJ International Conference on Intelligent Robots and Systems*, pages 5026–5033. IEEE, 2012.

[40] Mel Vecerik, Todd Hester, Jonathan Scholz, Fumin Wang, Olivier Pietquin, Bilal Piot, Nicolas Heess, Thomas Rothörl, Thomas Lampe, and Martin Riedmiller. Leveraging demonstrations for deep reinforcement learning on robotics problems with sparse rewards. *arXiv preprint arXiv:1707.08817*, 2017.

[41] Arun Venkatraman, Martial Hebert, and J. Andrew Bagnell. Improving multi-step prediction of learned time series models. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, AAAI'15, page 3024–3030. AAAI Press, 2015. ISBN 0262511290.

[42] Jianhao Wang, Wenzhe Li, Haozhe Jiang, Guangxiang Zhu, Siyuan Li, and Chongjie Zhang. Offline reinforcement learning with reverse model-based imagination, 2021.

[43] Ziyu Wang, Josh S Merel, Scott E Reed, Nando de Freitas, Gregory Wayne, and Nicolas Heess. Robust imitation of diverse behaviors. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL `https://proceedings.neurips.cc/paper/2017/file/044a23cadb567653eb51d4eb40acaa88-Paper.pdf`.

[44] Keyulu Xu, Mozhi Zhang, Jingling Li, Simon S Du, Ken-ichi Kawarabayashi, and Stefanie Jegelka. How neural networks extrapolate: From feedforward to graph neural networks. *arXiv preprint arXiv:2009.11848*, 2020.

[45] Tao Yu, Cuiling Lan, Wenjun Zeng, Mingxiao Feng, Zhizheng Zhang, and Zhibo Chen. Playvirtual: Augmenting cycle-consistent virtual trajectories for reinforcement learning. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021. URL `https://openreview.net/forum?id=GSHFVNejxs7`.

[46] Shangtong Zhang, Vivek Veeriah, and Shimon Whiteson. Learning retrospective knowledge with reverse reinforcement learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 19976–19987. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/e6cbc650cd5798a05dfd0f51d14cde5c-Paper.pdf`.

[47] Yuke Zhu, Ziyu Wang, Josh Merel, Andrei Rusu, Tom Erez, Serkan Cabi, Saran Tunyasuvunakool, JÃ¡nos KramÃ¡r, Raia Hadsell, Nando de Freitas, and Nicolas Heess. Reinforcement and imitation learning for diverse visuomotor skills. In *Proceedings of Robotics: Science and Systems*, Pittsburgh, Pennsylvania, June 2018. doi: 10.15607/RSS.2018.XIV.009.

A   Environments

Push   PickAndPlace

Figure 6: Fetch robotics environments. The gripper must move the object (black) near the goal (red). The initial gripper, object, and goal positions are fixed during training and the gripper position is varied during evaluation.

Fetch   These environments from [24] involve controlling the Fetch robotic arm. We consider two tasks: "Push" and "PickAndPlace" as shown in Figure 6. The objective of "Push" is to push the object on a table towards a fixed goal position using a closed gripper. The objective of "PickAndPlace" is to pick the object by controlling the gripper and move it towards the goal. The observation space is 25-dimensional and consists of the end effector coordinates and its linear velocity, the gripper's position and velocity, and the object's pose, velocities, and its relative position/velocity to the gripper. All Fetch environments have a fixed episode length of 50 and an episode is considered successful if the object is at the goal at the end of the episode.

Maze   There are 3 different maze environments of increasing difficulty and 2 different agents (Point, Ant) for each environment (c.f. Figure 7). The initial start and goal position is fixed and the objective is to control the agent to reach the goal (colored in red). The observation space is the agent's joint positions/velocities, the current timestep, and the agent's current Cartesian position. We use $dt = 0.02$ within the Mujoco [39] simulator and set the gear ratio for Ant to 10 to prevent it from falling over as in [22].

PointUMaze   PointRoom5x11   PointCorridor7x7

AntUMaze   AntRoom5x11   AntCorridor7x7

Figure 7: Maze environments. There are two agents: Point (top row) and Ant (bottom row). The agent must learn to move to the goal (red). Only the goal has a positive reward, all other states have a reward of zero.

Figure 8: Adroit environment. The goal is to pick up the ball and move it to the target (green).

Adroit   In this domain from [28], the goal is to control a 24-DoF Adroit hand to pick up a ball from the table and move it to a target location. The agent must manipulate each finger and wrist joint with dexterity to grasp the object correctly and learn the correct ball and target positions. An observation consists of hand joint angles, the object position/orientation, and the target position/orientation. We modify the original domain by fixing the initial qpos of the hand and by terminating the episode when the agent correctly solves the task.

B   Experiment Details

B.1   Expert demonstrations

To train an expert policy for the Fetch environments, we use pre-defined settings in [26] to train the expert policy. For the maze environments, we predefine a series of subgoals, and the position of the next subgoal is concatenated to the state. The reward is dense, using the negative Euclidean distance to the next subgoal and subsequent subgoals, and we use soft actor-critic [7] as the expert policy.

On the Fetch domains, we use 5 and 10 demonstrations for the Push and PickAndPlace tasks, respectively. As each episode is of length 50, this amounts to a total of a couple of hundred training samples. We thus make 10 identical copies of each demonstration in order to stably train the policy and backwards model (we do the same for all other methods). This has a similar effect of performing more gradient updates, but we found it is computationally cheaper. For both Maze and Adroit environments, we use 20 demonstrations and do not repeat the demonstrations as the episodes are sufficiently long.

B.2   Hyperparameters

All hyperparameter settings for BMIL are provided in Tables 3 and 4. For all experiments, we used an internal cluster with single GPU compute nodes, with 10 virtual CPU cores and a GPU with either an NVIDIA P100 or V100.

For all methods, we use the same number of policy gradient steps for a fair comparison. For VINS, we rely on the hyperparameter settings provided in the paper and run hyperparameter sweeps to find the best settings specific to our environments. As the Maze environments are new, we ran longer hyperparameter sweeps for VINS to find the best settings.

	Fetch		Adroit
	Push	PickAndPlace	Relocate
epochs	200		600
policy updates per epoch	100		50
batch size	64		
demonstrations	5	10	20
demonstration sampling ratio p	0.5		0.8
trace horizon length	1	$1 \to 3$ $(1 \to 200)$	$1 \to 10$ $(100 \to 600)$
action selection strategy	entropy		
action selection coefficient	30		3

Table 3: Hyperparameters for Fetch and Adroit environments. $x \to y(a \to b)$ denotes a thresholded linear function as used in [11], implemented as $f(e) = \min\left(\max\left(x + \frac{e-a}{b-a}(y-x), x\right), y\right)$ for epoch e.

	Point			Ant		
	UMaze	Room5x11	Corridor7x7	UMaze	Room5x11	Corridor7x7
epochs	800			400		
policy updates per epoch	250			500		
batch size	256					
demonstrations	20					
demonstration sampling ratio p	0.8			0.95	0.9	0.95
trace horizon length	$1 \to 10$ $(100 \to 800)$			$1 \to 10$ $(100 \to 400)$		
action selection strategy	entropy					
action selection coefficient	40	1		40	10	

Table 4: Hyperparameters for Maze environments. $x \to y(a \to b)$ denotes a thresholded linear function as used in [11], implemented as $f(e) = \min\left(\max\left(x + \frac{e-a}{b-a}(y-x), x\right), y\right)$ for epoch e.

C Results

C.1 Main results

			BC	VINS	BMIL
FETCH	Push (5 demos)		$99.8_{\pm 0.5}$	$98.1_{\pm 0.6}$	$99.5_{\pm 0.7}$
	PickAndPlace (5 demos)		$100_{\pm 0.0}$	$98.8_{\pm 0.8}$	$99.2_{\pm 0.8}$
MAZE	Point (20 demos)	UMaze	$94.8_{\pm 1.3}$	$6.0_{\pm 2.5}$	$71.6_{\pm 7.5}$
		Room5x11	$94.6_{\pm 2.4}$	$27.1_{\pm 5.9}$	$96.6_{\pm 2.3}$
		Corridor7x7	$88.2_{\pm 1.7}$	$66.7_{\pm 3.5}$	$89.8_{\pm 2.9}$
	Ant (20 demos)	UMaze	$100_{\pm 0.0}$	$19.8_{\pm 4.2}$	$100_{\pm 0.0}$
		Room5x11	$97.1_{\pm 0.7}$	$93.5_{\pm 1.1}$	$95.5_{\pm 0.9}$
		Corridor7x7	$94.9_{\pm 0.9}$	$88.2_{\pm 1.5}$	$90.6_{\pm 1.6}$
ADROIT	Relocate (20 demos)		$100_{\pm 0.0}$	-	$100_{\pm 0.0}$

Table 5: Success rates during training for Fetch, Maze, and Adroit environments over 400,100,100 trials, respectively. The bounds indicate 95% confidence intervals. BC and BMIL consistently solve the original task with the initial start and goal states for all environments, while the success rates for VINS fluctuate in the Maze environments.

Table 5 shows the success rates during training, on environments where the start and goal positions are unchanged. We see that both BC and BMIL achieve high success rates across all environments, while VINS does not for the Maze environments.

C.2 Additional Experiments

Figure 9: Action selection strategy on Push. We see a similar trend as in PickAndPlace, in that perturbing the action increases robustness over None.

Figure 9 shows the robustness of different action selection strategies on Fetch-Push. Here we see that all action selection strategies generally perform similarly, with possibly RS(0.3) and SC(50) a slight edge over the no strategy (None), though the error bars are fairly large.

Figure 10: Number of demonstrations: training success rates on PickAndPlace.

Figure 10 shows the success rates during training with a varying number of demonstrations on Fetch-PickAndPlace. We see that 3 demonstrations are sufficient for BC to achieve a 100% success rate on the original start and goal positions. However, BMIL requires at least 5 demonstrations to attain the same level of performance, as the backwards model requires at least a certain number of samples to train in a stable manner. We use 10 demonstrations in our experiments.

	Robustness (%)			Relative to BC		
	BC	BMIL	BMIL (model first)	BC	BMIL	BMIL (model first)
Push (5 demos)	$12.1_{\pm 0.3}$	$14.6_{\pm 0.6}$	$13.2_{\pm 1.0}$	1	1.21	1.09
PickAndPlace (10 demos)	$4.1_{\pm 0.1}$	$17.5_{\pm 0.9}$	$19.9_{\pm 2.4}$	1	4.31	4.85

Table 6: Training the backwards model first and then the policy produces similar results as training them together (BMIL).

Table 6 shows the results of training the backwards model first compared to BMIL which trains both the model and the policy in the same training loop. We use 100 trials in the Fetch environments. We find similar robustness values, where training the model first produces slightly lower values on Push and slightly higher values on PickAndPlace.