Automatic Organization of Neural Modules for Enhanced Collaboration in Neural Networks

Abstract

This work proposes a new perspective on the structure of Neural Networks (NNs). Traditional Neural Networks are typically tree-like structures for convenience, which can be predefined or learned by NAS methods. However, such a structure can not facilitate communications between nodes at the same level or signal transmissions to previous levels. These defects prevent effective collaboration, restricting the capabilities of neural networks. It is well-acknowledged that the biological neural system contains billions of neural units. Their connections are far more complicated than the current NN structure. To enhance the representational ability of neural networks, existing works try to increase the depth of the neural network and introduce more parameters. However, they all have limitations with constrained parameters. In this work, we introduce a synchronous graph-based structure to establish a novel way of organizing the neural units: the Neural Modules. This framework allows any nodes to communicate with each other and encourages neural units to work collectively, demonstrating a departure from the conventional constrained paradigm. Such a structure also provides more candidates for the NAS methods. Furthermore, we also propose an elegant regularization method to organize neural units into multiple independent, balanced neural modules systematically. This would be convenient for handling these neural modules in parallel. Compared to traditional NNs, our method unlocks the potential of NNs from tree-like structures to general graphs and makes NNs be optimized in an almost complete set. Our approach proves adaptable to diverse tasks, offering compatibility across various scenarios. Quantitative experimental results substantiate the potential of our structure, indicating the improvement of NNs.

1 Introduction

Neural Networks are often organized hierarchically in a tree-like fashion. However, this conventional approach obstructs effective communication among nodes and the structure can not facilitate information interaction between nodes at the same level or signal transmissions to previous levels. In fact, existing NN structures optimize in a limited space, significantly diminishing the potential of NNs, and impeding their full capabilities. Our work involves a reimagining of traditional NNs. We contend that the existing connectivity approaches inadequately capture the essence of neural networks. The nodes in an asynchronous tree-like structure lack the ability to establish connections, hindering information transfer between neural units and leading to deficiencies. To address this limitation, we introduce a method to build a synchronous graph structure for the nodes by the proposed Neural Modules, fostering collaboration among neural units. This innovative approach aims to overcome the shortcomings of the asynchronous tree-like structure, providing a more effective and interconnected framework for neural networks. Our framework progresses the structure of NN from tree-like structures to general graphs, providing more candidates for NAS methods.

For our framework. the concept of the Neural Module is defined as follows:

Definition 1. *A Neural Module is defined as a directed, connected subgraph and the absolute value of the weight for any edge in the subgraph exceeds the predefined threshold γ.*

$$\gamma = the\ kth\ largest\ value\ for\ the\ absolute\ value\ of\ the\ weights. \qquad (1)$$

Our method enables synchronous communication among any nodes within the neural module. This transformative adjustment enhances information transfer, thereby boosting the overall capacity of NN structures. By fostering a collaborative environment among nodes, our approach leverages their collective power to unlock NNs' capabilities. This design promotes collaboration among nodes, facilitating more accurate information transfer. It is noteworthy that the existing tree-like NNs are essentially a substructure of our designed general graph. In our framework, multiple neural units collaboratively execute precise functional implementations. Our innovation is poised to bridge the gap between artificial and more general structures like biological neural networks. Furthermore, our framework provides more candidates for NAS methods.

Designing such an architecture is a challenging task. While some similar works have made efforts, improvement is still needed. We found that the fixed point of the implicitly hidden layer is a solution. Instead of using an infinite structure of hidden layers, we organize it into a graph. However, for a larger number of nodes, the implicitly hidden layer imposes a heavier computational burden and increases the risk of overfitting. For example, the Deep equilibrium models(DEQ) encounter difficulties in finding the fixed point and calculating the Jacobian Matrix as well as its inverse matrix for a larger number of nodes, which may also lead to serious overfitting problems due to poor node organization. To address this, we propose a new regularization method to better organize these nodes into multiple proper neural modules that are independent and can be handled in parallel. This method allows nodes to form an automatic organization, enhancing the overall efficiency of the learning process as well as its performance by reducing overfitting,

Our learning process exhibits adaptability to larger search spaces and diverse tasks, effectively eliminating the structural bias that some nodes cannot transfer information due to the limitations of the current tree-like structure. We evaluate the effectiveness of our optimization method by conducting experiments on state-of-the-art networks, demonstrating its competitiveness compared to existing networks across various real-world tasks and datasets. The results from these experiments indicate the superiority of the learned connectivity in terms of performance and efficiency.

To sum up, our contributions to this study can be outlined as follows: We propose a method to generalize existing tree-like structures to learnable general graphs for NNs and we introduce a novel regularization method to organize the neural units into Neural Modules that help to enhance the efficiency of the structure as well as its performance by reducing overfitting.

2 RELATED WORKS

To progress the existing tree-like structure for NNs. Yuan (Kun Yuan & Yan, 2020) recently provided a topological perspective, highlighting the benefits of dense connections offered through shortcuts in optimization (Srivastava et al., 2015) (Sandler et al., 2018). Furthermore, sparsity constraints have also been proven effective in optimizing learned structures across various applications (Srivastava et al., 2015) (Chu et al., 2023) (Ahmed & Torresani, 2018) (He & Sun, 2016) (Huang & Weinberger, 2017). In their approach, the structure of NNs is organized as a DAG, whereas we organize it as a more general graph structure.

The fixed point of the implicitly hidden layer can also be served as a solution (Bai et al., 2019) (Tsuchida & Ong, 2022) (Chu et al., 2023) (Yang et al., 2022) (Heaton et al., 2021) (Zucchet & Sacramento, 2022), as demonstrated in the subsequent works (Bai et al., 2020) (Szekeres & Izsák, 2024) (Yang & Liu, 2023). Departing from the infinite structure of implicitly hidden layers (Chu et al., 2023) (Ling et al., 2023) (Ding et al., 2023) (Yang et al., 2022) (Liu et al., 2022), we organize it into a general graph structure. Furthermore, for larger NNs, we introduce a novel regularization method to organize neural units into multiple independent neural modules. Compared with implicitly hidden layers, our method can improve the efficiency by parallel computing as well as the performance by reducing overfitting. Furthermore, it enhances the interpretability of implicitly hidden layers.

Our process also involves compressing NNs. In recent years, various algorithms have been developed, including quantization (Kai Han & Xu, 2020) (Mingzhu Shen & Wang, 2019) (Yang He & Yang, 2018), low-rank approximation (Li & Shi, 2018) (Zhaohui Yang & Xu, 2019) (Xiyu Yu &

Tao, 2017), knowledge distillation (Shumin Kong & Xu, 2020) (Shan You & Tao, 2018), and network pruning (Pavlo Molchanov & Kautz., 2019), etc. The network pruning method we use in this work is weight pruning, which aims to eliminate weak connections. In addition, the method also involves filter pruning that removes entire redundant filters (Y Tang, 2020). We aim to improve weight pruning for our framework using a method similar to Tao Lin (2020), which evaluates the gradient at the pruned model and applies parameters' updates to the dense model. In our framework, this process coordinates with an elegant regularization to automatically allocate Neural Modules.

OptNet integrates optimization quadratic problems for nodes within the same layer (Amos & Kolter, 2017) (Yan & Zhang, 2021). However, this approach introduces bias and lacks an interpretable structure, affecting overall interpretability. Furthermore, OptNet uses parameters derived from quadratic problems for backpropagation. These parameters, determined by nodes from the previous layer, are difficult to manage in complexity. This complexity not only increases the computational burden but also exacerbates overfitting problems. Using a differentiable function for these parameters adds further bias.

Graph Neural Networks (GNNs) specially address the needs of geometric deep learning (Gori et al., 2005) (Fan et al., 2019) (Scarselli et al., 2008) (Abadal et al., 2021). GNNs adapt their structure to the input graph, capturing complex dependencies (Yong et al., 2007) (Abadal et al., 2021) (Fout et al., 2017) (Fan et al., 2019). This adaptability enables them to predict properties of geometric data, which primarily deal with graphs, our innovation involves evolving the tree-like structure into a general graph format for NNs, expanding their applicability and potential.

Such flexible graph structure has also been explored by works like Reservoir Computing (Lukoševicius & Jaeger, 2009) (Benjamin Schrauwen & Campenhout., 2007) (Leshno & Schocken, 1993b). These works are applied as a recurrent neural network in which neurons are connected at random. However, when it is initialized, these weights are fixed. Reservoir Computing benefits from a non-linear dynamical system. On the other hand, our Neural Module is modeled on a balanced system, and the weights as well as the structure can be learned in the processing which makes our framework have stronger capabilities compared with Reservoir Computing.

3 METHODOLOGY

3.1 RATIONALE FOR INTRODUCING THE STRUCTURE

NNs represent a type of information flow. However, tree-like structures maintain a hierarchical, nested form that limits information transfer, as each node can only be influenced by its precursor nodes. These structures are asynchronous and lack the flexibility to form cycles. Moreover, we observe that these structures are notably inferior in complexity compared to biological neural networks, which exhibit more intricate connectivity patterns beyond the simplicity of tree-like structures. The adoption of these structures is primarily due to their favorable mathematical properties, particularly in facilitating convenient forward and backward propagation.

Consider the traditional tree-like structure for an NN with m layers. Let N^0 be the nodes of the first layer and the input values feed into the first layer. Let N^m be nodes for the last layer and they feed for the output values. For any node in the other layers, $n_i^k \in N^k, 0 < k < m$, it represents the intermediate values. The parameters of the model are represented as the edges in the structure. Let $e_{i,j}^k \in E^k, 1 \le k \le m$ be the the edge connecting n_i^{k-1} and n_j^k. Then the traditional tree-like structure for NNs which is organized as an asynchronous hierarchical structure can be formalized as follows: $\mathcal{T} = \{N^0, E^1, N^1, ...E^m, N^m\}$.

In our work, we organize the intermediate structure as a general graph. The model is denoted by NM, $\mathcal{NM} = \{N^0, E^1, \mathcal{G}, E^m, N^m\}$, where $\mathcal{G} = \{E, N\}$ and $n_i \in N$ is the ith node in $\mathcal{G}$, $e_{i,j} \in E$ is the edge from n_i to n_j. Let the number of the nodes in N be p, the number of the nodes in N^0 be $|N^0|$ and the number of the nodes in N^m be $|N^m|$.

In this way, we would enhance the description of the NNs compared to traditional approaches.

3.2 MODEL STRUCTURE

In the traditional forward computation for a tree-like structure, each node in the first layer aggregates inputs and is then transformed by tensor flow. Following the provided definition of NM, our structure is constructed as follows: all the intermediate nodes are organized into a graph, as illustrated in Figure 1. In this arrangement, each node is influenced by all other nodes in the graph. This collective influence enables nodes to work together, significantly improving NNs' characterization.

In our framework, nodes are initially computed based on their input nodes, which solely distribute features. Additionally, each node is influenced by other nodes in the graph, creating mutual influence.

Figure 1: The first image shows the tree-like structure of a traditional NN. In the second depiction, for the intermediate nodes, our model NM introduces a graph. Note that, the nodes' spin part represents its bias for itself.

In the upcoming section, we elaborate on the process of calculating node values using both input nodes and the nodes within the graph $\mathcal{G}$.

3.3 FORWARD PROCESS

First, we discuss the case of the value for each node in the graph. Here in this paper, the value for each node is represented as x and the value for each edge is represented as w with the same corresponding index. As introduced in the previous section, these values depend on the nodes in N^0 as well as other nodes in $\mathcal{G}$. Hence, we need a synchronization method to address this. We treat the problem as a system of multivariate equations. For the value of the nodes in $\mathcal{G}$, we have the following:

$$
\begin{cases}
w_{1,1} + \sum_{j \neq 1} f(x_j) \cdot w_{j,1} + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,1}^1 = x_1 \\
w_{2,2} + \sum_{j \neq 2} f(x_j) \cdot w_{j,2} + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,2}^1 = x_2 \\
... \\
w_{p,p} + \sum_{j \neq p} f(x_j) \cdot w_{j,p} + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,p}^1 = x_p
\end{cases}
$$

In the above equations, $w_{1,1}$, $w_{2,2}$, ..., $w_{p,p}$ are the values of the self-spin edges for $\mathcal{G}$ and they represent the bias of the nodes. f is the activation function.

Let W^m be the weights of E^m and $X = \{x_1, x_2, ...\}$ be the values of the nodes in $\mathcal{G}$. Then, according to the definition of $\mathcal{NM}$, the output values $\tilde{Y} = X^m$ can be inferred by $X^m = g(f(X) \cdot W^{mT})$, where g is the activation function for output.

Existing numerical methods such as Newton-Raphson method, can effectively solve these above equations. In real-world applications, besides Newton's methods, the efficiency can be optimized by iterative methods, dichotomy, or secant methods. Note that, each variable is processed by an activation function f, making the transformation nonlinear. If we consider $\mathcal{G}$ as a Neural Module, we can introduce the following theorem.

Theorem 3.1 (Universal Neural Module Approximation Theorem). *Let $\mathcal{F}$ be an implicit function defined on a compact set, capable of being transformed into a continuous explicit function for all the variables. In such a case, there exists a Neural Module that can effectively approximate the function $\mathcal{F}$.*

According to Cybenko (1989) Hornik & White (1990) Leshno & Schocken (1993a), the theorem will be proved in the Appendix.

3.4 BACKWARD PROCESS

To determine the gradient of the nodes in the neural module, we consider the gradient of the output as the last layer $\nabla X^m = \nabla Y$. The same as the Forward Process, the nodes' gradients also interact with each other. Note that, each node has been processed by the activation function f. Then, we treat the gradient of the nodes in the graph as variables within the following system of equations.

$$\begin{cases} \sum_{j \neq 1} \nabla x_j \cdot f'(x_j) \cdot w_{1,j} + \sum_{j=1}^{|N^m|} \nabla x_j^m \cdot g'(x_j^m) \cdot w_{1,j}^m = \nabla x_1 \\ \sum_{j \neq 2} \nabla x_j \cdot f'(x_j) \cdot w_{2,j} + \sum_{j=1}^{|N^m|} \nabla x_j^m \cdot g'(x_j^m) \cdot w_{2,j}^m = \nabla x_2 \\ ... \\ \sum_{j \neq m} \nabla x_j \cdot f'(x_j) \cdot w_{p,j} + \sum_{j=1}^{|N^m|} \nabla x_j^m \cdot g'(x_j^m) \cdot w_{p,j}^m = \nabla x_p \end{cases}$$

Finally, we can compute the gradient of the edges of our NM. First, for the gradient of the edges in $\mathcal{G}$, according to the system of equations, we need to consider the gradient of each node. For any jth node in the graph, the weights of the incoming arc are represented by the jth$(1 \leq j \leq p)$ column of its adjacency matrix. For convenience, we introduce the following operator:

$$\mathcal{H}_j = [f(x_1), ..., f(x_{j-1}), 1, f(x_{j+1}), ..., f(x_p)] \,, \tag{2}$$

This operator is derived from the system of equations in the forward process. Then, by the gradient of the jth node, its corresponding gradient for $W_{:,j}^T, 1 \leq j \leq p$ in $\mathcal{G}$ can be formulated as follows:

$$\nabla W_{:,j}^T = \nabla x_j \cdot f'(x_j) \cdot \mathcal{H}_j \,. \tag{3}$$

Second, for the gradient for the edges in E^m, according to the forward process,

$$\nabla W^m = \nabla X^{mT} \cdot g'(X^{mT}) \cdot f(X) \,. \tag{4}$$

Third, for the gradient for the edges in E^1, according to the forward process,

$$\nabla W^1 = \nabla X^T \cdot X^0 \,. \tag{5}$$

3.5 NEURAL MODULE OPTIMIZATION

For convenience, we take $\mathcal{G}$ as a single neural module as stated earlier, this serves as a universal set for all possible connections. In our work, we optimize the structure to prioritize important connections. The optimization process typically involves emphasizing crucial connections in the graph. In this paper, we introduce parameter γ acting on the formation of Neural Modules as Definition 1. A larger γ generates sparser graphs and results in smaller Neural Modules. Here, we propose a new

regularization method to formalize multiple balance Neural Modules, as introduced earlier. And we term it as NM regularization.

The forward and backward process of the structure, as discussed earlier, involves solving a system of equations. Managing a large number of nodes would impose a considerable computational burden when dealing with such systems. However, we can address this challenge by optimizing the graph at any part using NM regularization, transforming the large graph into independent, smaller connected subgraphs that formalize Neural Modules, as previously introduced. As each Neural Module does not connect with others, we can calculate them in parallel. Compared with $L1$ regularization, NM regularization can get more balanced neural modules, which would bring additional benefits for efficiency as if it is calculated in parallel, the overall efficiency is determined by the largest Neural Module. This approach enables a significant reduction in computation. At the same time, it also promotes the performance by mitigating overfitting.

NM regularization considers the number of edges that have a connected path to each node. Here, we introduce operator:

$$\mathcal{Z} = [z_1, z_2, ..., z_p] \,, \tag{6}$$

For the element $z_k, 1 \leq k \leq p$ in $\mathcal{Z}$,

$$z_k = the\ number\ of\ edges\ connected\ to\ node\ n_k. \tag{7}$$

Let α be the parameter for regularization. By NM regularization, for the larger connected subgraph, there is an adaptive adjustment to increase α in each iteration. This adjustment results in the automatic organization of the graph into properly balanced subgraphs, forming rational neural modules that effectively utilize neuron units. For the kth node in $\mathcal{G}$, $1 \leq k \leq p$, the formulation of our NM regularization is as follows:

$$x_k = w_{k,k} + \sum_{j \neq k} f(x_j) \cdot w_{j,k} + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,k}^1 + \alpha \cdot z_k \cdot \sum_{j \neq k} norm(w_{j,k}), \tag{8}$$

where $norm$ denotes the regular function like $L1$ or $L2$ regularization. In this manner, for larger subgraphs, a larger value of z would cause the edges connected to these subgraphs to tend toward zero, as shown in Figure 2.

Figure 2: The effect of L1 and L2 regularization. The nodes in larger neural modules have more edges connected to them which introduces larger z and in turn, enhances the signal of regularization. They would pull the value toward zero with more powerful strength. Parameter γ helps to cut the edges with smaller weights, preventing the expansion of large neural modules and at the same time encouraging the development of small neural modules. That's why NM regularization helps to formulate balanced neural modules.

According to the results of $L1$ and $L2$ regularization, for the $L1$ norm case, the best value connected to the node n_k is

$$w_{j,k}^* = sgn(w_{j,k})(|w_{j.k}| - \alpha \cdot z_k)_+ \,, \tag{9}$$

where $_+$ takes the positive part of the value. For the $L2$ norm case, the best value connected to the node n_k is

$$w_{j,k}^* = \frac{1}{1 + \alpha \cdot z_k} \cdot w_{j,k} \ . \tag{10}$$

From equation 9 and equation 10, larger z would produce smaller weight and in turn, prevent the expansion of large neural modules by cutting parameter γ as introduced before. At the same time, the process also encourages the development of small neural modules by small z values. As a result, NM regularization helps to formulate balanced neural modules which bring benefits to parallel computing as introduced before.

Figure 3: If the node corresponds to a large connected subgraph, NM regularization increases its weight for regularization, making it more prone to tend towards zero. NM regularization opts to divide large neural modules into multiple smaller, independent, balanced ones. This approach confines the calculation for the system of equations to each subgraph, enabling parallelized solutions.

In this method, we only consider the absolute value of the weight for each edge larger than γ to solve the system of equations during both the forward and backward processes. With the aid of NM regularization, we achieve properly balanced neural modules. Employing this method involves solving large systems of equations into multiple smaller systems of equations. These smaller ones are independent and can be solved in parallel. This strategy enables the framework to handle a large number of nodes efficiently.

Lastly, we refer to the parameter γ as an approximation to solve the system of equations in the forward and backward process. This approximation significantly reduces the heaviest computational load. After obtaining the gradient of each node, we calculate the gradient for all edges including those whose absolute values are smaller than γ, and then update them. This ensures that while γ helps to approximate the solution to the system of equations, the update for edges is fully quantified and precise. In this way, our NM regularization achieves higher efficiency as well as better performance and robustness.

4 EXPERIMENTS

4.1 PERFORMANCE OF NEURAL MODULES

In this section, we present experiments conducted with our Neural Modules, comparing their performance with traditional NN methods, implicit hidden layers (DEQ), a topological perspective treating NN as a DAG, and recently introduced OPTNET. The results are tabulated for three real datasets, all of which are available in the UCI dataset. For the regular function $norm$, we use the absolute value of the wights.

The first dataset comprises codon usage frequencies in genomic coding DNA from a diverse sample of organisms obtained from different taxa in the CUTG database. The second dataset includes measurements from 16 chemical sensors exposed to six different gases at various concentration levels. The third dataset involves smartphone-based recognition of human activities and postural transitions, performing various activities. All these tasks represent classification problems, and we evaluate performance based on the error of each algorithm.

First, we assessed the effectiveness of our NMs and other methods across various node complexities. This evaluation allows us to understand how the NMs perform with different levels of complexity. The nodes were initially organized using NN, DEQ, DAG as well as OPTNET, and their percentage

Table 1: The error of algorithms for Codon Usage Dataset

	40 Nodes	60 Nodes	80 Nodes	100 Nodes	200 Nodes	300 Nodes
NN	0.2128	0.1917	0.1854	0.1964	0.1702	0.1839
DEQ	0.1714	0.1839	0.2136	0.1980	0.1714	0.2911
DAG	0.2410	0.2152	0.2027	0.2050	0.2074	0.1987
OPTNET	0.1792	0.1706	0.2152	0.2034	0.1745	0.1901
NMs	0.1761	0.1557	0.1643	0.1604	0.1792	0.1432
NMs&L1	0.1753	0.1549	0.1964	0.1591	0.1776	0.1549
NMs&NM	**0.1495**	**0.1510**	**0.1505**	**0.1549**	**0.1659**	**0.1408**

Table 2: The error of algorithms for Gases Concentration Dataset

	40 Nodes	60 Nodes	80 Nodes	100 Nodes	200 Nodes	300 Nodes
NN	0.1669	0.1293	0.1113	0.1414	0.1639	0.2391
DEQ	0.1188	0.1233	0.1323	0.1098	0.1278	0.1474
DAG	0.2677	0.1835	0.1248	0.1263	0.2857	**0.1293**
OPTNET	0.1308	0.1774	0.1248	0.1549	**0.1113**	0.2541
NMs	0.1023	0.1098	0602	0.0767	0.1714	0.2135
NMs&L1	0.0932	0.0992	0.0586	0.0602	0.1714	0.2075
NMs&NM	**0.0752**	**0.0962**	**0.0511**	**0.0301**	0.1684	0.1970

of error was observed. Our experiments involved comparing the performance of NMs, examining their performance with frequently-used $L1$ regularization and the proposed NM regularization, as introduced earlier. The results, as presented in the tables, reveal that our novel structure consistently achieves superior results in most cases. Additionally, the performance of NM regularization surpasses that of the benchmark, $L1$ regularization in most situations. With the optimal performance achieved with a suitable number of nodes, our NM regularization is shown to perform the best across all the datasets.

For all datasets and node variations within the graph, NN consistently exhibits improved results when nodes are organized into neural modules. The efficacy of our NMs can be further enhanced through regularization, as previously explained. Notably, even without regulation, our NMs outperform the traditional structure. After implementing NM regularization, our approach demonstrates enhanced performance.

4.2 EFFICIENCY OF NEURAL MODULES

In this section, we explore the process of optimizing the efficiency of Neural Modules using NM regularization. First as introduced before, every structure is a subgraph of a fully connected graph. The initial general graph serves as the search space for our model. Our NM regularization is an effective tool to optimize the structure. NM regularization helps to produce more effective and balanced neural modules. The performance of these neural modules for the nodes number lower than 300 has been shown in the last section. The results obtained have shown that it would yield better results. Here, to investigate the efficiency of our NM regularization, we display the running time of our model compared with DEQ on different complexity described by nodes' number that

Table 3: The error of algorithms for Postural Transitions Dataset

	40 Nodes	60 Nodes	80 Nodes	100 Nodes	200 Nodes	300 Nodes
NN	0.1062	0.1099	0.1008	0.1069	0.0811	0.1245
DEQ	0.1232	0.2755	0.0882	0.0889	0.0859	0.0658
DAG	0.1154	0.1130	0.1184	0.0937	0.1025	0.1639
OPTNET	0.1188	**0.1055**	0.0940	0.1164	0.0994	0.1639
NMs	0.1018	0.2559	0.0886	0.0699	0.1035	0.1059
NMs&L1	0.0865	0.2538	0.0821	0.0665	0.0787	0.0726
NML&NM	**0.0709**	0.2416	**0.0724**	**0.0570**	**0.0631**	**0.0635**

is lower than 300. As shown in Image A of Figure 4, We observed that the efficiency of NM regularization is much better than DEQ. Especially for a larger number of nodes, the running time of NM regularization performs well. This is because NM regularization helps to formulate multiple independent neural modules, which reduce the complexity of the computation efficiently.

For larger nodes' numbers, we can operate these Neural Modules in parallel to optimize the efficiency of our framework as introduced before. NM regularization helps to formulate multiple independent, balanced neural modules which is suitable for parallel computing natrually, especially, porting the process to GPU computing. Here we expand the number of nodes from 300 to 3000. And introduce GPU to compute the algorithms.

(a) Nodes' number up to 300. Neural modules vs.DEQ.

(b) Nodes' number up to 3000. Neural modules parallel vs. Neural modules.

Figure 4: Compared with DEQ, Neural modules can bring significant benefits to the efficiency of computing. Furthermore, by parallel computation, NM regularization brings a chance to enable this framework to be applied to larger applications.

For Image B of Figure 4, we compare the running time with Neural Modules in parallel and Neural Modules. Here we used 12 threads in our experiments. We found that NM regularization in parallel produces nearly 6 to 7 times the benefit in computation speed.

Furthermore, for more nodes' numbers, NM regularization in parallel also gets even better results, which have been shown in Figure 5. Here for the compared methods DEQ, DAG, and OPTNET, if the nodes' number is larger than 300, it usually produces over time. We use the average performance of these three models on their nodes' numbers within 300 as the baseline. However, we compared the NN structure as the accompanying runner in our experiments to see the performance of our framework on applications with larger node' numbers. And we found that our framework gets better results on larger models both in performance. The error of our framework is lower than the contrast models.

4.3 THE EFFECT OF NM REGULARIZATION

At last, Figure 6 presents examples of neural modules generated by our NM regularization, where each black square denotes a neural module. The image on the left shows the neural modules generated at the first iteration, where the effects of NM regulation are not yet apparent. The image on the right, at the 10000th iteration, illustrates how NM regulation achieves independence and balance within the generated neural modules. NM regularization helps break large neural modules into smaller, more manageable neural modules. This segmentation leads to improved performance and efficiency, as previously introduced.

5 CONCLUSION

This study introduces a novel general graph structure designed for the NNs, aiming to improve performance by facilitating significant information transfer. We address structural bias analysis for the current tree-like structure. Our model employs a synchronization method for the simultaneous calculation of node values, thereby fostering collaboration within neural modules. Additionally, we propose a novel NM regularization method that encourages the learned structure to prioritize critical

(a) Codon Usage Dataset   (b) Gases Concentration Dataset

(c) Postural Transitions Dataset

Figure 5: The performance on the 3 Datasets with nodes' number larger than 300.

(a) Codon Usage Dataset   (b) Gases Concentration Dataset   (c) Postural Transitions Dataset

Figure 6: Neural modules generated by our NM regularization for the Codon Usage Dataset, the Gases Concentration Dataset, and the Postural Transitions Transitions Dataset with each black square denoting a neural module. The left image depicts the neural modules at the first iteration, and the right image shows the neural modules at the 10000th iteration.NM regularization helps break large neural modules into smaller, more manageable neural modules.

connections and automatically formulate multiple independent, balanced neural structures, which would help to achieve better efficiency by calculation in parallel. This approach not only reduces the computational load associated with managing more nodes but also improves the performance by mitigating overfitting. Quantitative experimental results affirm the superiority of our proposed method over traditional structures for NNs.

REFERENCES

Sergi Abadal, Akshay Jain, Robert Guirado, Jorge López-Alonso, and Eduard Alarcón. Computing graph neural networks: A survey from algorithms to accelerators. *ACM Computing Surveys (CSUR)*, 54(9):1–38, 2021.

K. Ahmed and L. Torresani. Mask connect connectivity learning by gradient descent. In *ECCV*, 2018.

Brandon Amos and J Zico Kolter. Optnet: Differentiable optimization as a layer in neural networks. In *International Conference on Machine Learning*, pp. 136–145. PMLR, 2017.

Shaojie Bai, J. Zico Kolter, and Vladlen Koltun. Deep equilibrium models. In *NeurIPS*, 2019.

Shaojie Bai, Vladlen Koltun, and J Zico Kolter. Multiscale deep equilibrium models. *Advances in Neural Information Processing Systems*, 33:5238–5250, 2020.

David Verstraeten Benjamin Schrauwen and Jan Van Campenhout. An overview of reservoir computing: theory, applications and implementations. In *In Proceedings of the 15th european symposium on artificial neural networks. p. 471-482 2007, pages 471–482, 2007.*, 2007.

Haoyu Chu, Shikui Wei, and Ting Liu. Learning robust deep equilibrium models. *arXiv preprint arXiv:2304.12707*, 2023.

G.. Cybenko. Approximation by superpositions of a sigmoidal function. In *Mathematics of control, signals and systems*, 1989.

Shutong Ding, Tianyu Cui, Jingya Wang, and Ye Shi. Two sides of the same coin: Bridging deep equilibrium models and neural odes via homotopy continuation. *arXiv preprint arXiv:2310.09583*, 2023.

Wenqi Fan, Yao Ma, Qing Li, Yuan He, Eric Zhao, Jiliang Tang, and Dawei Yin. Graph neural networks for social recommendation. pp. 417–426, 2019.

Alex Fout, Jonathon Byrd, Basir Shariat, and Asa Ben-Hur. Protein interface prediction using graph convolutional networks. In *Neural Information Processing Systems*, 2017.

M. Gori, G. Monfardini, and F. Scarselli. A new model for learning in graph domains. In *IEEE International Joint Conference on Neural Networks*, 2005.

Zhang X. Ren S. He, K. and J. Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

Howard Heaton, Samy Wu Fung, Aviv Gibali, and Wotao Yin. Feasibility-based fixed point networks. *Fixed Point Theory and Algorithms for Sciences and Engineering*, 2021(1):1–19, 2021.

Stinchcombe M. Hornik, K. and H. White. Universal approximation of an unknown mapping and its derivatives using multilayer feedforward networks. In *Neural networks*, 1990.

Liu Z. VanDer Maaten L. Huang, G. and K.Q.. Weinberger. Densely connected convolutional networks. In *CVPR*, 2017.

Yixing Xu Chunjing Xu Enhua Wu Kai Han, Yunhe Wang and Chang Xu. Training binary neural networks through learning with noisy supervision. In *ICML*, 2020.

Jing Shao Kun Yuan, Quanquan Li and Junjie Yan. Learning connectivity of neural networks from a topological perspective. In *ECCV*, 2020.

Lin V.Y. Pinkus A. Leshno, M. and S. Schocken. Multilayer feedforward networks with a nonpolynomial activation function can approximate any function. In *Neuralnetworks*, 1993a.

Lin V.Y. Pinkus A. Leshno, M. and S. Schocken. Multilayer feedforward networks with a nonpolynomial activation function can approximate any function. In *Neuralnetworks*, 1993b.

Chong Li and CJ Richard Shi. Constrained optimization based low-rank approximation of deep neural networks. In *ECCV*, 2018.

Zenan Ling, Zhenyu Liao, and Robert C Qiu. On the equivalence between implicit and explicit neural networks: A high-dimensional viewpoint. *arXiv preprint arXiv:2308.16425*, 2023.

Jiaming Liu, Xiaojian Xu, Weijie Gan, Ulugbek Kamilov, et al. Online deep equilibrium learning for regularization by denoising. *Advances in Neural Information Processing Systems*, 35:25363–25376, 2022.

Mantas Lukoševicius and Herbert Jaeger. Reservoir computing approaches to recurrent neural network training. In *Computer Science Review, 3(3):127–149, 2009*, 2009.

Chunjing Xu Mingzhu Shen, Kai Han and Yunhe Wang. Searching for accurate binary neural architectures. In *IEEE International Conference on Computer Vision Workshops*, pp. 0–0, 2019, 2019.

Stephen Tyree Iuri Frosio Pavlo Molchanov, Arun Mallya and Jan Kautz. Importance estimation for neural network pruning. In *CVPR*, 2019.

Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang Chieh Chen. Mobilenetv2: Inverted residuals and linear bottlenecks. In *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Franco Scarselli, Marco Gori, Ah Chung Tsoi, Markus Hagenbuchner, and Gabriele Monfardini. The graph neural network model. *IEEE transactions on neural networks*, 20(1):61–80, 2008.

Chao Xu Shan You, Chang Xu and Dacheng Tao. Learning with single-teacher multi-student. In *AAAI*, 2018.

Shan You Shumin Kong, Tianyu Guo and Chang Xu. Learning student networks with few data. In *AAAI*, 2020.

Rupesh Kumar Srivastava, Klaus Greff, and Jürgen Schmidhuber. Highway networks. *Computer Science*, 2015.

Béla J Szekeres and Ferenc Izsák. On the computation of the gradient in implicit neural networks. *The Journal of Supercomputing*, 2024.

Luis Barba Daniil Dmitriev Martin Jaggi Tao Lin, Sebastian U. Stich. Dynamic model pruning with feedback. In *ICLR*, 2020.

Russell Tsuchida and Cheng Soon Ong. When are equilibrium networks scoring algorithms? In *NeurIPS 2022 Workshop on Score-Based Methods*, 2022.

Xinchao Wang Xiyu Yu, Tongliang Liu and Dacheng Tao. On compressing deep models by low rank and sparse decomposition. In *CVPR*, 2017.

Y Xu D Tao C Xu Y Tang, Y Wang. Scop: Scientific control for reliable neural network pruning. In *10.48550/arXiv.2010.10732*, 2020.

Yan J. Luo C. Chen L. Lin Q. Yan, K. and D. Zhang. A surrogate objective framework for prediction+optimization with soft constraints. 2021.

Li P. Pang T. Yang, Z. and Y. Liu. Improving adversarial robustness of deep equilibrium models with explicit regulations along the neural dynamics. In *ICML*, 2023.

Zonghan Yang, Tianyu Pang, and Yang Liu. A closer look at the adversarial robustness of deep equilibrium models. *Advances in Neural Information Processing Systems*, 35:10448–10461, 2022.

Xuanyi Dong Yanwei Fu Yang He, Guoliang Kang and Yi Yang. Soft filter pruning for accelerating deep convolutional neural networks. In *IJCAI*, 2018.

Sweah Liang Yong, Markus Hagenbuchner, Ah Chung Tsoi, Franco Scarselli, and Marco Gori. Document mining using graph neural network. In *Comparative Evaluation of XML Information Retrieval Systems: 5th International Workshop of the Initiative for the Evaluation of XML Retrieval, INEX 2006, Dagstuhl Castle, Germany, December 17-20, 2006, Revised and Selected Papers 5*, pp. 458–472. Springer, 2007.

Chuanjian Liu Hanting Chen Chunjing Xu Boxin Shi Chao Xu Zhaohui Yang, Yunhe Wang and Chang Xu. Legonet: Efficient convolutional neural networks with lego filters. In *ICML*, 2019.

Nicolas Zucchet and João Sacramento. Beyond backpropagation: bilevel optimization through implicit differentiation and equilibrium propagation. *Neural Computation*, 34(12):2309–2346, 2022.

A THE SIGNIFICANCE OF OUR STUDY

Particularly, what sets our research apart is its inspiration drawn from the intricate dynamics of biological neural systems with billions of neural units. Many units are influenced by each other and generate a collaborative effect. Unlike the traditional stacked unit approach, our approach mirrors the cooperative nature of biological neural modules. In these systems, multiple neural units work together to perform precise functional tasks, resulting in exquisite performance as illustrated in the 2nd image of Figure 8. Our innovation seeks to bridge the gap between artificial and biological neural networks, thus propelling NN structures toward the performance observed in their natural counterparts.

Figure 7: The left image illustrates the typical structure of an NN, while the right image depicts a biological neural network, showcasing its inherently more complex connectivity patterns.

The NNs structure in the current framework fails to incorporate a cyclic graph which indicates a synchronous structure that makes the collaboration of the neural units in NNs. The current tree-like structure is asynchronous, the cyclic graph would produce an infinite loop, as illustrated in Figure 9. Our framework facilitates collaborative interactions among neural units. In this paper, we present a method that enables synchronous communication among nodes within the neural module. This transformative adjustment enhances information processing and increases the overall capacity of NN structures.

Figure 8: Illustration of the limitations preventing the application of a cyclic graph which is a synchronous structure within the current tree-like NN structure.

B   THE CONNECTION WITH NNs

In this section, we argue that the existing tree-like NN structure in fact is a special case of our framework. The comparison is detailed in the following table, the asynchronous process for the current tree-like structure can also be formalized by our system of equations for our framework.

Table 4: table B

	NNs	NMs
Model	$\mathcal{T} = \{N^0, E^1, N^1, ..., E^m, N^m\}$	$\mathcal{NM} = \{N^0, E^1.\mathcal{G}, E^m, N^m\} = \{N^0, E^1.E, N, E^m, N^m\}$
Variables	$\mathcal{T} = \begin{pmatrix} \mathcal{X}^0 = [1, X^0] \\ \mathcal{W}^0 = [bias_1, W^1] \\ \mathcal{X}^1 = [1, X^1] \\ ... \\ \mathcal{W}^m = [bias_m.W^m] \\ X^m \end{pmatrix}$	$NM = \begin{pmatrix} X^0 \\ W^1 \\ W \\ X \\ W^m \\ X^m \end{pmatrix}$
FP	$\begin{cases} \mathcal{X}^0 \cdot \mathcal{W}^{1T} = X^1 \\ \mathcal{X}^1 \cdot \mathcal{W}^{2T} = X^2 \\ ... \\ \mathcal{X}^{m-1} \cdot \mathcal{W}^{mT} = X^m \end{cases}$	$\begin{cases} w_{1,1} + \sum\limits_{j \neq 1} f(x_j) \cdot w_{j,1} + \sum\limits_{j=1}^{|N^0|} x_j^0 \cdot w_{j,1}^1 = x_1 \\ w_{2,2} + \sum\limits_{j \neq 2} f(x_j) \cdot w_{j,2} + \sum\limits_{j=1}^{|N^0|} x_j^0 \cdot w_{j,2}^1 = x_2 \\ ... \\ w_{p,p} + \sum\limits_{j \neq p} f(x_j) \cdot w_{j,p} + \sum\limits_{j=1}^{|N^0|} x_j^0 \cdot w_{j,p}^1 = x_p \\ X \cdot W^{mT} = X^m \end{cases}$
BP	$\begin{cases} \nabla X^m \cdot g'(X^m) \cdot W^m = \nabla X^{m-1} \\ ... \\ \nabla X^2 \cdot f'(X^2) \cdot W^2 = \nabla X^1 \end{cases}$	$\begin{cases} \sum\limits_{j \neq 1} \nabla x_j \cdot f'(x_j) \cdot w_{1,j} + \sum\limits_{j=1}^{|N^m|} \nabla x_j^m \cdot g'(x_j^m) \cdot w_{1,j}^m = \nabla x_1 \\ \sum\limits_{j \neq 2} \nabla x_j \cdot f'(x_j) \cdot w_{2,j} + \sum\limits_{j=1}^{|N^m|} \nabla x_j^m \cdot g'(x_j^m) \cdot w_{2,j}^m = \nabla x_2 \\ ... \\ \sum\limits_{j \neq m} \nabla x_j \cdot f'(x_j) \cdot w_{p,j} + \sum\limits_{j=1}^{|N^m|} \nabla x_j^m \cdot g'(x_j^m) \cdot w_{p,j}^m = \nabla x_p \end{cases}$

From the table, we can see that the traditional NN structure represents a special case of our framework where the system of equations is solved asynchronously. In the tree-like structure, the coefficient matrix of the equations is composed of the parameter matrices for each level, and these coefficients are positioned near the diagonal. In contrast, our framework generalizes the coefficient to form a full matrix across the 1 to the $p-1$ level, indicating a transition from a tree-based structure to a general graph structure.

C   THE MOTIVATION OF REORGANIZING THE NEURAL NETWORKS FROM TREE-LIKE STRUCTURE TO GENERAL GRAPH STRUCTURE

For the traditional tree-like structure, the asynchronous forward and backward process can also be considered to solve a system of equations as shown in Table 4. In our framework, the feed-forward processes for traditional tree-like structures are essential to solve the equations as shown in Figure 9, which is similar to the backward process.

Take value related to the inputs and bias to the right. Take the values related to each node to the left. The equations become the following in Figure 10.

Then, the coefficient $\mathcal{C}$ for the tree-like structure in our framework would be as Image A in Figure 11.

This tree-like structure seems to be much restricted for each node in the structure. According to the Universal approximation theorem, the flexibility of NN depends on the number of neurons with a single hidden layer. That is, for any nodes in the tree structure, if it is only dependent on the neurons in the pre-layer, it would be severely restricted. Typically, for the nodes in the first layer, they are only represented as the linear transformation of the input values. Some existing work tries to generalize the structure to a DAG structure such as ResNet. Then these additional weights are added to the Lower Triangular of $\mathcal{C}$. Let these weights be represented by V. The $\mathcal{C}$ becomes Image B in Figure 11.

$$
\begin{cases}
w_1^1 + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,1}^1 = x_1^1 \\
w_2^1 + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,2}^1 = x_2^1 \\
... \\
w_{|N^1|}^1 + \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,|N^1|}^1 = x_{|N^1|}^1 \\
...... \\
w_1^{m-1} + \sum_{j=1}^{|N^{m-2}|} f(x_j^{m-2}) \cdot w_{j,1}^{m-1} = x_1^{m-1} \\
w_2^{m-1} + \sum_{j=1}^{|N^{m-2}|} f(x_j^{m-2}) \cdot w_{j,2}^{m-1} = x_2^{m-1} \\
... \\
w_{|N^{m-1}|}^{m-1} + \sum_{j=1}^{|N^{m-2}|} f(x_j^{m-2}) \cdot w_{j,|N^{m-1}|}^{m-1} = x_{|N^{m-1}|}^{m-1}
\end{cases}
$$

Figure 9: Tadition tree-like structure for NN is essentially to solve these equations in our framework.

$$
\begin{cases}
-x_1^1 = -w_1^1 - \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,1}^1 \\
-x_2^1 = -w_2^1 - \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,2}^1 \\
... \\
-x_{|N^1|}^1 = -w_{|N^1|}^1 - \sum_{j=1}^{|N^0|} x_j^0 \cdot w_{j,|N^1|}^1 \\
...... \\
\sum_{j=1}^{|N^{m-2}|} f(x_j^{m-2}) \cdot w_{j,1}^{m-1} - x_1^{m-1} = -w_1^{m-1} \\
\sum_{j=1}^{|N^{m-2}|} f(x_j^{m-2}) \cdot w_{j,2}^{m-1} - x_2^{m-1} = -w_2^{m-1} \\
... \\
\sum_{j=1}^{|N^{m-2}|} f(x_j^{m-2}) \cdot w_{j,|N^{m-1}|}^{m-1} - x_{|N^{m-1}|}^{m-1} = w_{|N^{m-1}|}^{m-1}
\end{cases}
$$

Figure 10: Take value related to the inputs and bias to the right. Take the values related to each node to the left. We can extract the coefficient $\mathcal{C}$ for our framework.

Such a Lower Triangular Coefficient matrix mines to the limit of the asynchronous structure. But for the values in the Upper Triangular matrix, they are still undeveloped. For our work, we generalize the asynchronous structure to synchronous ones. That breaks through the limit of the Lower Triangular and to the General for coefficient matrix $\mathcal{C}$. In our Neural Module framework, the $\mathcal{C}$ becomes Figure 12.

For our framework, we improved the representational ability of each neuron and in turn unlocked the ability of NN. At the same time, we also remove structural bias which typically needs to be predefined as traditional tree structure or DAG structure.

For large $\mathcal{C}$, solving to system of equations would be difficult. We proposed NM regularization to approximate $\mathcal{C}$ and introduced parallel computation. However, NM regularization is a kind of

$$\begin{pmatrix} -E^1 & 0 & 0 & 0 & ... & 0 & 0 \\ W^1 & -E^2 & 0 & 0 & ... & 0 & 0 \\ 0 & W^2 & -E^3 & 0 & ... & 0 & 0 \\ 0 & 0 & W^3 & -E^4 & ... & 0 & 0 \\ ...... \\ 0 & 0 & 0 & 0 & ... & W^{m-2} & E^{m-1} \end{pmatrix}$$

(a) The Coefficient $\mathcal{C}$ for the Tree-like Structure

$$\begin{pmatrix} -E^1 & 0 & 0 & 0 & ... & 0 & 0 \\ W^1 & -E^2 & 0 & 0 & ... & 0 & 0 \\ V^1 & W^2 & -E^3 & 0 & ... & 0 & 0 \\ V^1 & V^2 & W^3 & -E^4 & ... & 0 & 0 \\ ...... \\ V^1 & V^2 & V^3 & V^4 & ... & W^{m-2} & E^{m-1} \end{pmatrix}$$

(b) The Coefficient $\mathcal{C}$ for the ResNet Structure

Figure 11: The Coefficient $\mathcal{C}$ for traditional NN Structure

$$\begin{pmatrix} -1 & w_{2,1} & w_{3,1} & w_{4,1} & ... & w_{p-1,1} & w_{p,1} \\ w_{1,2} & -1 & w_{3,2} & w_{4,2} & ... & w_{p-1,2} & w_{p,2} \\ w_{1,3} & w_{2,3} & -1 & w_{4,3} & ... & w_{p-1,3} & w_{p,3} \\ w_{1,4} & w_{2,4} & w_{3,4} & -1 & ... & w_{p-1,4} & w_{p,4} \\ ...... \\ w_{1,p} & w_{2,p} & w_{3,p} & w_{4,p} & ... & w_{p-1,p} & -1 \end{pmatrix}$$

Figure 12: The Coefficient $\mathcal{C}$ for our NM Structure

approximation. Note that, it is approximated on the complete set of the coefficient $\mathcal{C}$ as introduced before.

D THE CONNECTION WITH DEQ

Previous research has observed the existence of a stable point in an infinite-level NN structure with identical weights. DEQ addresses this issue by modeling the problem across infinite levels and simplifying it to an implicit function. Specifically, achieving a fixed point is equivalent to solving the root of the implicit function. In our approach, we find that our general graph structure can also be managed by solving a system of functions.

In fact, DEQ focuses on infinite levels with the same weight. Suppose treating the infinite path as a circle. The essential research object of DEQ is also a cyclic graph. In this paper, we unveil the fundamental nature of the fixed point, recognizing its role as a solution within our synchronous neural module structure. Our neural module not only assists in finding its essence but also enables concurrent visualization of the implicit function as shown in Figure 10 and Figure 11.

Figure 13: For the infinite structure, DEQ abstracts an implicit function to solve the fixed point.

Figure 14: Our model tries to find the essence of the implicit function, a general graph structure.

Furthermore, adhering to the Universality of Single-layer DEQ, it is established that multiple implicitly hidden layers are tantamount to a single implicitly hidden layer. As a result, DEQ encounters limitations in managing multiple implicitly hidden layers.

Most importantly, DEQ struggles when managing a larger number of nodes as introduced in the paper. These layers must solve the implicit function. In our paper, by considering implicit hidden layers from infinite levels to elegant general graphs, we would organize the neural units well to optimize the efficiency as well as the performance of the model. To address this, we introduce NM regularization that organizes these nodes into neural modules. In contrast to the DEQ, our framework provides a methodology for handling multiple neural modules. Our analysis of the regularization encompasses both theoretical foundations and experimental parameters, enabling our framework to manage larger graphs effectively. Furthermore, the organized independent, balanced neural models achieve superior results on both efficiency and performance, as previously demonstrated. These neural modules improve performance by reducing overfitting and improving efficiency through parallel computation. Previous work like DEQ did not discuss how to organize the neural units to optimize efficiency and performance.

E   THE CONNECTION WITH OPTNET

In earlier research, OPTNET examines the interconnections among nodes within the same level in traditional tree-like structures. Their approach involves implementing Quadratic Programming within these nodes, which introduces significant bias. Furthermore, OptNet uses parameters derived from quadratic problems for backpropagation, determined by nodes from the previous layer which brings difficulties to regularization as illustrated before. The defects of OPTNET make it challenging to fine-tune its performance as well as overall efficiency.

In contrast, our neural module is nonlinear and exhibits sufficient flexibility to accommodate any compact function without introducing bias, as affirmed by the Universal Neural Module Approximation Theorem. Additionally, we can readily control the complexity of the parameters to enhance performance and efficiency simultaneously.

F   THE SUPPLEMENTARY MATERIALS FOR THE EXPERIMENTS

In this section, we outline the experimental environment as shown in Table 5. Furthermore, as demonstrated in the previous section, the parameters for our framework can be tuned.

In our experiments, for the regular function $norm$, we use the absolute value of the weights. Like $L1$ regularization, we select this function with the aim of expanding the neural module and focusing on several critical edges in each iteration. For larger neural modules, such critical edges might be rarer in the process of NM regularization.

In real applications, other regular functions can be tried for $norm$ to get better performance.

F.1   THE OPTIMIZATION OF THE NEURAL MODULES

In this section, we explore the process of optimizing the structure of Neural Modules using NM regularization. As discussed earlier, the results obtained have shown that NM regularization would yield better results. Here, we investigate the parameter-setting strategies for our NM regularization.

Table 5: Experimental Environment

CPU	Gen Intel(R) Core(TM) i9-12900H 2.90 GHz
Cores	12
Memory	32G
GPU	NVidia GeForce RTX 3060
Graphics Memory	12G

(a) Codon Usage Dataset   (b) Gases Concentration Dataset

(c) Postural Transitions Dataset

Figure 15: Parameter setting for NM regularization.

The images in Figure 15 illustrate the impact of different parameters on the error rates of our NM regulation across various percentages of approximations(controlled by parameter γ) for the Codon Usage Dataset. We found that the performance can be optimized by fine-tuning the NM regularization and the percentages of approximations(controlled by parameter γ). Higher approximation percentages and regularization parameters produce more Neural Modules, which help reduce overfitting problems and in turn, enhance performance as well as robustness. However, overly sparse NMs could introduce extra bias and degrade performance. After standardization, the NM regularization parameter with 100 nodes performs best at 0.2 and the approximation on top 0.05 edges by controlling parameter γ for the Codon Usage Dataset. However, more stable performance appears on the approximation of top 0.03 edges.

In Figure 15, we also offer this on the Gases Concentration Dataset and the Postural Transitions Dataset. We reached a similar conclusion that performance can be well optimized by tuning both the NM regularization and the parameters of approximation. We observe that for these two datasets, the higher parameter γ and NM regularization parameters result in better performance. NM regularization helps break large neural modules into smaller, more manageable neural modules. This segmentation leads to improved performance as previously introduced. However, compared with the Codeon Usage Data, the approximation can not to too large. On average, for 100 nodes, the NM regularization parameter usually performs best at 0.2 with the approximation on top 0.01 edges by controlling parameter γ.

F.2 THE EFFECT OF NM REGULARIZATION

From the experiments, NM regularization can better capture the trend of the weights in each iteration. It enables accurate weight regularization and formulates effectively balanced neural modules. More importantly, these independent, balanced neural modules bring additional benefits for efficiency. As previously mentioned, the overall efficiency is determined by the size of the largest neural module, especially when they are processed in parallel.

To analyze the effect of NM regularization, consider the probability of the edge's weight being lower than γ denoted as θ in the current iteration. For a neural module with q nodes, the probability of a new edge integrating into the neural module would be denoted as $1 - \theta^q$. In the case of a small q value, NM regularization seeks to increase the probability. Conversely, for larger q values, NM regularization works to decrease the probability. Thus, NM regularization endeavors to minimize the disparity in the probability of a new edge integrating into the neural modules with varying sizes. This effect is illustrated in the first image of Figure 4.

Figure 16: Image A shows the analysis of NM Regularization and image B displays the time-consumption for different sizes of neural modules which indicates parallel computing's advantage.

Image A in Figure 16 illustrates the analysis of NM Regularization and how balanced Neural Modules are formed through this process. Image B shows the time consumption associated with different sizes of neural modules. As previously mentioned, the neural modules generated are independent and can be calculated in parallel. For instance, if a neural module comprises 50 nodes, the time to solve the system of equations required would be reduced to just 10ms in our experiments. Thus, NM regularization enables sufficient management of larger node counts.

G NEURAL MODULE IS ONLY FOR APPROXIMATION TO SOLVE THE SYSTEM OF EQUATIONS

In the forward and backward process, the solution involves a system of nonlinear equations. The presence of numerous nodes in the neural module can lead to performance issues. To address this challenge, we propose NM regularization, which organizes multiple independent, balanced neural modules. Breaking down a large system of nonlinear equations into more manageable systems significantly reduces the computational burden. Furthermore, solving these equations in parallel would further enhance the overall efficiency.

Note that, we update all the edges in every iteration, which provides additional benefits such as enhanced robustness. For the absolute value of the edge's weight lower than γ, it also chance to grow larger than γ in the coming iteration. That means every edge in the graph has the opportunity to change, thereby retaining the dynamism of Neural Modules and exerting our model's performance.

H THE PROOF OF THE UNIVERSAL NEURAL MODULE APPROXIMATION THEOREM

Note that the array of equations involves an activation function. Therefore, in our model, the system of functions is non-linear and possesses sufficient flexibility to fit any appropriate function, according to our Universal Neural Module Approximation Theorem.

Proof. In the forward process, the system of equations constructs implicit functions across all nodes within the neural module. Subsequently, any node n_i can be transformed into an explicit function. According to the Universal Approximation Theorem (Cybenko, 1989) (Hornik & White, 1990) (Leshno & Schocken, 1993a), which states that for any continuous function on a compact set, there exists a one-hidden-layer feed-forward network capable of approximating the function, our system satisfies this condition. This is because our array of equations involves an activation function, fulfilling the requirement of the theorem. Therefore, the proof is complete. □