WHAT DO SELF-SUPERVISED VISION TRANSFORMERS LEARN?

ABSTRACT

We present comparative studies on how and why contrastive learning (CL) and masked image modeling (MIM) differ in their representations and performance on downstream tasks. In particular, self-supervised Vision Transformers (ViTs) have the following properties: (1) CL trains self-attentions to capture longer-range global patterns, such as the shape of an object, compared with MIM. This property of CL helps ViTs linearly separate images in their representation spaces. However, it also makes the self-attentions collapse into homogeneity for all heads, depths, and query tokens. Such homogeneity of self-attention reduces representations' diversity, resulting in worse scalability and dense prediction performance; (2) CL reduces the high-frequency signals of the representations, but MIM amplifies them. Since the low-frequency information stands for the shapes and the high frequencies represent the textures, CL is more shape-oriented, whereas MIM is more texture-oriented; (3) CL plays a crucial role in the later layers of ViT architecture, while MIM mainly focuses on the early layers. Upon these analyses, we find that CL and MIM can complement each other and observe that the simplest harmonization can enjoy the advantages of both methods.

1 INTRODUCTION

Contrastive Learning (CL) (He et al., 2020; Chen et al., 2020a;b; 2021) has been one of the most popular self-supervised learning methods until recently. It aims to learn the invariant semantics for two random views (Tian et al., 2020a;b) by making global projections of representations similar for positive samples or dissimilar for negative samples. Due to the global projection, CL can be deemed as an *"image-level"* self-supervised learning approach.

Deviating from CL, Masked Image Modeling (MIM) (Bao et al., 2022; Xie et al., 2022; He et al., 2022) has risen as a strong competitor with its impressive performances on downstream tasks in the era of Vision Transformers (ViTs) (Dosovitskiy et al., 2021). MIM trains ViTs by predicting or reconstructing the correct semantics of masked input patches. Contrary to CL, as it learns semantics of patch tokens, it can be deemed as *"token-level"* self-supervised learning. As MIM outperforms CL in fine-tuning accuracy, it seems that MIM is *prima facie* more effective than CL for the pre-training. However, for linear probing accuracy, it shows different trends; CL outperforms MIM (See Figure 1). For further exposition on CL and MIM, we refer the reader to Appendix B.

Then, which method should we use for the self-supervised learning of ViTs, MIM, or CL? Although they are widely used in practice, little is known about how they work and what they learn. In this paper, we raise questions to understand the nature of self-supervised learning more deeply and then find the answer that can influence future improvements. The questions we posed could be divided following the properties of Vision Transformers: the behavior of self-attentions, the transformation of the representations, and the position of the lead role components. The key questions and our findings are elaborated below.

How do self-attentions behave? (Section 2) Self-attentions of CL and MIM exhibit opposite behaviors. We observe that CL primarily captures global relationships while MIM captures local relationships. It implies that the representations of CL contain more global patterns, such as object shapes, than those of MIM. On the one hand, this property can be helpful in CL to recognize objects and distinguish images. However, on the other hand, it also suggests that CL is free from preserving local information, and ViT trained with CL lacks such information. In particular, we observe that

Figure 1: **CL outperforms MIM in linear probing and small model regimes.** In contrast, MIM excels in fine-tuning, large model regimes, and dense prediction. The blue (▲) represents MIM and red (■) means CL. We use the original papers' results. For scaling experiments, we report our reproduced results as MoCo† and SimMIM† with the official configurations but 100 epochs. By default, we report the performance of ViT-B trained or pre-trained on ImageNet-1K. *Left*: CL outperforms MIM in linear probing but underperforms in fine-tuning. *Middle*: CL outperforms MIM in small model regimes (ViT-Ti and ViT-S), and MIM shows superior scalability in large model regimes (ViT-L and ViT-H). *Right*: MIM outperforms CL in dense prediction, such as object detection with Mask R-CNN (He et al., 2017) on COCO (Lin et al., 2014).

all self-attentions for heads, depths, and query tokens collapse into homogeneous attention maps. In such cases, most self-attentions focus on object boundaries, which can capture object shapes but lose interaction diversity of self-attention. This results in CL and MIM having advantages for different tasks; CL works well for linear probing and classification tasks with smaller models. In contrast, MIM outperforms CL in fine-tuning and dense prediction tasks with larger models.

How are representations transformed? (Section 3) CL transforms representations to build image-level information. Thus, its self-attention collects object shape information over entire tokens. This aggregation process makes tokens similar rather than preserving token diversity. On the contrary, MIM preserves and amplifies token-level information. Thus, the self-attention for each token is substantially different and prohibits each token include repeated information. It can also be observed in our Fourier analysis: CL reduces high-frequency signals of representations, but MIM amplifies them. In short, self-supervised models with CL and MIM learn the representations in different levels of detail.

Which components play an important role? (Section 4) Analyses of the importance of each layer of CL and MIM demonstrate that the later layers in CL and early layers in MIM play key roles. We interpret this as a consistent observation since early layers are usually known to capture low-level features, e.g., local patterns, high-frequency signals, and texture information, and later layers capture global patterns, low-frequency signals, and shape information.

From the above analyses and insights, we find that CL and MIM can complement each other and show the simplest implementation, such as a linear combination of CL and MIM objectives, can take advantage of both methods in Section 5. Surprisingly, it outperforms the models pre-trained solely with CL or MIM in terms of fine-tuning and linear probing accuracy.

2   HOW DO SELF-ATTENTIONS BEHAVE?

As shown in Figure 1, we point out that both CL and MIM may not be a silver bullet for all tasks. The figure shows that the general tendency for CL outperforms MIM in linear probing, while MIM dominates CL in the fine-tuning scheme. However, when we dissect models' size, CL still outperforms MIM after fine-tuning for small models, while MIM performs better on large models. MIM yields effective representations for dense prediction tasks such as object detection, but CL falls short on those tasks. In this section, we explain these phenomena by investigating the behavior of self-attentions.

Our analyses mainly compare ViT-B/16 pre-trained on ImageNet-1K (Russakovsky et al., 2015) with MoCo v3 (Chen et al., 2021) and SimMIM (Xie et al., 2022). We use the ImageNet validation images for the experiments. We observe that DINO (Caron et al., 2021), BEiT (Bao et al., 2022), and MAE

Figure 2: **Self-attentions of CL (MoCo) capture global relationships, but they collapse into homogeneous attention maps for all heads, depths, and query tokens.** Self-attentions of MIM (SimMIM) focus on local areas. We visualize self-attention maps for two different query tokens at the beginning and the end layers. We omit the results for self-attention heads, which show consistent results. *Left*: Self-attentions of CL capture global patterns and the shape of an object. However, all the attention maps capture the same shape information regardless of the query tokens. *Middle*: Self-attentions of MIM capture local patterns near the query tokens. *Right*: Self-attentions of supervised pre-trained model capture local patterns at first, and global patterns at the end of models.

(He et al., 2022) have consistent properties (See Figure B.1). We also report the results of ViT-B/16 supervised with ImageNet-1K class labels, hereafter *supervised*, for comparison.

CL mainly captures global relations, but MIM does not. We measure the ranges of self-attentions via attention distance (Dosovitskiy et al., 2021) which is defined as the average distance between the query tokens and key tokens considering their self-attention weights. It conceptually corresponds to the receptive fields in CNNs. Figure 3 shows that the attention distance of CL (MoCo) is significantly higher than that of MIM (SimMIM) for all depths. This implies that the representations of CL contain global patterns and shape information, so it can help ViT distinguish between objects or images. Conversely, the self-attentions of MIM mainly capture local relationships, i.e., MIM may have difficulty recognizing whole objects and their shapes. The trend for the self-attentions of the supervised ViTs is shifting from local to global according to layer depth, which is consistent with the observations in Dosovitskiy et al. (2021); Zhou et al. (2021); Raghu et al. (2021).

Figure 3: **The effective receptive fields of CL are global, but those of MIM are local.** Data points represent the attention distance of heads as analogous to the size of the receptive field.

Self-attentions of CL collapse into homogeneity. We observe an interesting behavior of CL in Figure 2. It shows attention maps for query tokens from two different spatial locations. Surprisingly, the self-attentions of CL indicate *almost identical* object shapes for the two query tokens.

We describe this phenomenon as *attention collapse into homogeneity*. We observe the homogeneity trend in self-attentions of CL across all the layers, heads, and query tokens. In contrast, MIM shows more faithful self-attentions for two query tokens, as expected.

We use normalized mutual information (NMI) (Strehl & Ghosh, 2002) to measure the attention collapse. Let $p(q)$ be a distribution of query tokens, and assume they are uniformly distributed since a single query token is given for each spatial coordinate, i.e., $p(q) = 1/N$ where N is the number of the tokens. Then the joint distribution of query and key tokens is $p(q,k) = \pi(k|q)p(q)$ where $\pi(k|q)$ is softmax-normalized self-attention matrix. Thus, the normalized mutual information is $\frac{I(q,k)}{\sqrt{H(q)H(k)}}$ where

Figure 4: **Self-attentions of CL have little to do with query tokens.** CL's normalized mutual information is significantly lower than that of MIM.

(a) Between heads   (b) Between depths   (c) Between tokens

Figure 5: **CL lacks representational diversities.** We measure similarities of representations in self-attentions by using mini-batch CKA between the heads (left), depths (middle), and spatial coordinates (right). All the results show that the representational similarity of CL is significantly higher than that of MIM. In this figure, the data points represent the similarities between the two representations. *Left*: The similarity of representations from two heads in self-attention. *Middle*: The similarities of self-attention heads in the i-th Transformer layer and the $(i+1)$-th Transformer layer. *Right*: The similarities of representations at two spatial coordinates. The result indicates that the representation of CL is homogeneous with respect to spatial coordinates, which is consistent with Figure 4.

$I(\cdot, \cdot)$ is the mutual information and $H(\cdot)$ is the marginal entropy. The low mutual information value represents the attention map is less dependent on the query tokens implying the attention collapse into homogeneity. Conversely, the high the mutual information means the attention maps strongly depend on the query token.

Figure 4 shows the degree of attention collapse in terms of the normalized mutual information (NMI). The results show that the mutual information of CL is significantly lower than that of MIM, suggesting that self-attentions of CL collapse into nearly homogeneous distributions.

The attention collapse reduces representation diversity. We conjecture that the self-attention collapse into homogeneity eventually leads to homogeneous token representations. To support this argument, we measure representational similarities using mini-batch centered kernel alignment (CKA) (Nguyen et al., 2021). We use representation after self-attention layers for all similarity measures to ensure that the result is the consequence of the self-attention collapse. We design three similarities: between different self-attention heads (heads), between the previous and current layers (depths), and between different tokens (tokens).

Figure 5 shows the result reporting the representation similarities for heads, depths, and tokens. As expected, the similarities of CL are notably higher than those of MIM, indicating that the representations of CL have significant homogeneity in heads, depths, and tokens.

Implications of the behaviors we observed. In conclusion, the self-attention of CL captures global patterns and shapes of objects. However, CL suffers from the problem of attention collapse into homogeneity, which reduces the diversity of token representations. On the contrary, MIM does not suffer from the attention collapse problem by primarily capturing local patterns.

The behaviors mentioned above can explain the phenomena we observed in Figure 1:

- CL outperforms MIM in linear probing tasks because capturing shapes by CL helps recognize objects and distinguish images. Although MIM preserves texture and the diversity of representation, these are not strongly correlated with objects or content, compared to shapes.

- The attention collapse prohibits CL from fully exploiting heads, depths, and tokens of ViTs. Since homogeneous representations is not very helpful for improving token representations, ViTs trained with CL wastes a large part of network capability. Therefore, the fine-tuning accuracy of MIM with large models is significantly higher than that of CL.

- CL is not suitable for dense prediction since the token features are homogeneous with respect to their spatial coordinates.

(a) MoCo (one image)   (b) MoCo (two images)   (c) SimMIM (one image)

Figure 6: **Self-attention layers of CL and MIM transform representations differently.** We visualize 196 spatial representational tokens for an example validation image in representation space. The blue (•) and red (•) data points stand for the tokens before and after the first self-attention transformation. *Left*: The self-attentions of CL (e.g., MoCo) translate all the tokens equally, so the distances between tokens in an image do not change. *Middle*: However, CL makes the "centers of representations (represented by ×)" away from each other. Therefore, the image is linearly separable. The circle (•) and triangle (△) data represent tokens from different images. *Right*: The self-attentions of MIM (e.g., SimMIM) differently transform representations according to query tokens. Thus, the distances between tokens change. See Figure 7 for quantitative analyses.

We further investigate the self-attention's behavior with restricted receptive fields in Figure A.1. As shown in the experiment, locally restricted self-attentions lead to lower linear probing but higher fine-tuning accuracy, which is consistent with our observations.

3   HOW ARE REPRESENTATIONS TRANSFORMED?

In this section, we analyze the token representations of ViTs pre-trained with CL and MIM to demonstrate how the properties of self-attentions we observed in Section 2 affect the representations. We use the same official pre-trained ViT-B/16 models by default as well as we did in Section 2.

CL transforms all tokens in unison, while MIM's tokens are transformed individually. To show how CL and MIM transform token representations, we visualize them in representation space. Figure 6 represents 196 (14×14 patches) tokens before and after the first self-attention module from a single image of the ImageNet validation set. We use the top three singular vectors obtained via singular value decomposition (SVD) as the bases of the representation space.

Figure 6a visualizes the changes in the tokens of CL transformed by the self-attention module; it indicates that the self-attentions of CL translate all tokens in unison. This phenomenon occurs since the self-attention maps of CL are homogeneous, i.e., the self-attention is almost independent of the spatial coordinates and the query tokens. Therefore, the module adds near-constant to all the token representations. As a result, the inter-representation distance and the representations' volume remain almost invariant, which implies that CL cares less about individual tokens.

Nevertheless, self-attentions are essential for the discriminative power of CL. As shown in Figure 6b, they distinguish images by moving "the centers of the representation distribution (technically, the global average pooled tokens of an image)" away from each other. In sum, this figure suggests that CL makes the image linearly separable even though it loses the ability to distinguish tokens.

In contrast, MIM applies a different transform to individual tokens, as shown in Figure 6c, because the different self-attentions are assigned to the individual spatial tokens. Thus, MIM alters the distance between the tokens of a single image and the volume of the representation distribution.

We find consistent results in quantitative analysis. Inspired by Jing et al. (2022), we visualize singular value spectra for tokens and images in Figure 7. The singular value spectrum provides singular values of representation distribution obtained by SVD, so we can use it to analyze the effective volume of

(a) Singluar value spectum of tokens from a single image

(b) Singluar value spectum of images

Figure 7: **CL almost does not change the distribution volume of tokens from a single image.** Instead, it significantly changes the distribution volume of images. To demonstrate these properties, we visualize singular value spectra, the singular values of the distribution of representation sorted by the magnitude. The higher the singular value, the larger the volume of the distribution. The right of this figure is the 32-th highest singular value for depth. *Top*: Singular value spectrum of tokens from a single image. CL almost does not change the singular values of the tokens, but MIM does. *Bottom*: Singular value spectrum of images. CL significantly increases the volumes occupied by images, but MIM does not increase the volume significantly.

distribution in representation space. The higher the singular value in the spectrum, the larger the volume of the representation distribution.

Figure 7a shows the singular value spectra of tokens for a single image. We calculate it for each image in ImageNet validation set and report averaged singular values over the validation set. In this figure, the layers of CL hardly increase the singular value, and even the singular value of CL at the end of the model is smaller than that of MIM. Consistent with the explanation above, it implies that CL hardly distinguishes tokens. In contrast, MIM increases the singular value, so it changes the volume of tokens and can distinguish tokens.

Figure 7b shows the singular value spectra of images. We averaged all tokens in an image to build an image-level representation vector and conduct the singular value spectra over the collection of representations in the validation set. As opposed to the previous case, the representational volume of CL is larger than that of MIM, which implies that CL makes the image-level representation separable.

CL exploits low-frequencies, and MIM exploits high-frequencies. We hypothesize that CL captures low-frequency and MIM captures high-frequency information in spatial dimensions since CL provides image-level self-supervision to capture global patterns, while MIM provides token-level self-supervision to exploit local patterns. To support this argument from a frequency perspective, we conduct Fourier analysis on the representations as following Park & Kim (2022b). In particular, we report the relative log amplitude of Fourier transformed representation by calculating the amplitude difference between the representations' highest and lowest frequencies.

Figure 8: **CL reduces high-frequency, but MIM amplifies it**. White and gray areas are MLP and self-attention.

(a) Stylized ImageNet (b) Robustness for noise frequency

Figure 9: **CL is biased toward shape, whereas MIM is biased toward texture.** We report the predictive results of models for linear probing tasks. However, we observe consistent results for the fine-tuned models (Figure D.1b). *Left:* The classification results on Stylized ImageNet. It shows that CL is more shape-biased than MIM and even than the supervised pre-trained model. The vertical lines represent the averaged results for the shape categories. *Right:* The accuracy drop on images with frequency-based random noises. MIM shows a more significant amount of accuracy drop with high-frequency noises than CL, demonstrating MIM's texture-biased property compared to CL. The frequency window size is 0.1π for the frequency-based noise.

Figure 8 visualizes the relative amplitudes of CL and MIM. It shows that CL reduces the high-frequency components, suggesting that CL mainly utilizes low-frequency spatial information such as global structures and shapes. On the contrary, MIM amplifies them, which means that MIM usually uses high-frequency spatial information such as narrow structures and fine textures.

Another interesting finding is that the layers at the end of MIM reduce the high frequencies even though they only focus on the local areas (See Figure 3). We conjecture that MIM implicitly divides ViTs into the encoder-decoder structure and lets the intermediate layers have linearly separable information. In contrast, CL lets the last layer have it. This is further elaborated in Figure 11.

CL is shape-biased, but MIM is texture-biased. Based on the results of Fourier analysis, we assume that CL and MIM have a bias toward shape and texture, respectively. To demonstrate this claim, we use Stylized-ImageNet (Geirhos et al., 2019), a texture-altered dataset, by using AdaIN (Huang & Belongie, 2017). In Figure 9a, we report the linear probing results on Stylized-ImageNet to evaluate the shape and texture biases of pre-trained models. Compared to the model pre-trained with supervised learning, CL depends more on the shape of images to classify images, and MIM depends on texture. In other words, CL is robust to texture changes, and MIM is vulnerable to them.

Figure 9b shows the consistent results. In this experiment, we follow (Park & Kim, 2022a;b) and measure the decrease in accuracy on the ImageNet dataset with frequency-based random noise. The results suggest that CL is robust to high-frequency noises, but MIM is significantly more vulnerable to them. Since high-frequency noises harm the fine details of images, we arrive at the same conclusion that CL is more shape-biased and MIM is texture-biased.

4 WHICH COMPONENTS PLAY AN IMPORTANT ROLE?

In the previous sections, we consistently observe that CL exploits image-level global patterns and MIM captures token-level local patterns. This section analyzes pre-trained ViTs from the architecture perspective, e.g., module-wise (i.e., self-attention or MLP) and layer-wise (i.e., early layers or later layers) manners, and shows key components in CL and MIM are different.

Self-attentions in CL and MLPs in MIM are important. A previous study (Park & Kim, 2022b) reveals that self-attentions and MLPs exploit low-frequency and high-frequency information, respectively. As our observation supports that CL captures low-frequency and MIM captures high-frequency information, we claim that "self-attentions in CL" and "MLPs in MIM" play key roles.

The representational displacement, ℓ_2 distance between representations of previous and subsequent modules, represents the contribution of the residual block excluding the features from skip connection. Therefore, it can be used as a metric to measure the importance of the module. As expected, Figure 10 shows that self-attentions in CL and MLPs in MIM make large displacements compared to their counterparts. It also suggests that MIM is an appropriate method for fine-tuning purposes since self-attention is suitable for a data-specific fine-tuning process as Touvron et al. (2022) shows training self-attention layers greatly contribute to fine-tuning accuracy.

In addition, the displacement magnitude of CL gradually increases as the depth increases, but that of MIM decreases. It indicates that the later layers of CL and the early layers of MIM contribute more to building useful representations for fine-tuning.

Later layers of CL and early layers of MIM are important. According to studies on ViT architectures (Graham et al., 2021; Dai et al., 2021; Park & Kim, 2022b), the later layers use high-level information, and the early layers exploit low-level information. Since CL and MIM exploit global and local patterns, we expect that the later layers of CL and early layers of MIM play key roles.

To evaluate the importance of each layer, we measure the linear probing accuracy using the intermediate representations with the configuration of Table A.1. In Figure 11, we observe the following properties: First, the linear probing accuracy of MIM is higher than that of CL at the beginning. Conversely, CL outperforms MIM at the end of the model. This result indicates that later layers of CL and early layers of MIM play an important role in making linearly separable representations. Second, the accuracy of CL increases with increasing depth as expected, but surprisingly, the accuracy of MIM decreases at the end of the model, i.e., later layers of MIM are not very helpful in separating representations. We explain this as MIM methods with a shallow prediction head (e.g., SimMIM (Xie et al., 2022)) use later layers of the backbone as a decoder. Therefore, MIM with a deep self-attention decoder (e.g., MAE (He et al., 2022)) can be useful for linear probing performance; this is consistent with the ablation study in He et al. (2022). It also explains SimMIM's frequency drops at later layers as shown in Figure 8. For more detailed discussion on MAE, see Figure B.2. Third, the highest linear probing accuracy of MIM is lower than that of CL.

Figure 10: **Self-attentions in CL and MLPs in MIM mainly change representations**. We report representation displacement, ℓ_2 distance between representations of previous and subsequent modules. The larger the displacement, the larger the change in representation. White and gray areas are MLP and self-attention.

Figure 11: **Later layers of CL and early layers of MIM play a key role.** We report linear probing accuracies by using representations of the intermediate layer. CL outperforms MIM in later layers, and MIM outperforms CL in early layers.

5 CAN WE BENEFIT FROM BOTH ENDS?

We present comparative analyses on CL and MIM from three perspectives: self-attentions, representation transforms, and the position of the important layers. Our results consistently indicate that CL and MIM train ViTs differently. These differences naturally imply that combining CL and MIM might leverage the advantages from both ends.

Simple harmonization of CL and MIM. We introduce the simplest way to harmonize CL and MIM by linearly combining two losses, i.e., $\mathcal{L} = (1 - \lambda)\mathcal{L}_{\text{MIM}} + \lambda\mathcal{L}_{\text{CL}}$ where $\mathcal{L}_{\text{MIM}}$ and $\mathcal{L}_{\text{CL}}$ is the losses of MIM and CL, and λ is importance weight of CL. We find that the hybrid model trained

(a) Performance   (b) Self-attention   (c) Fourier analysis

Figure 12: **The simple linear combination of CL and MIM objectives outperforms the vanilla CL and MIM**. λ is importance weight of CL, so $\lambda = 0$ means SimMIM and $\lambda = 1$ means MoCo. *Left:* "CL + MIM" outperforms CL and MIM in both linear probing and fine-tuning accuracy. *Middle:* The mutual information of "CL + MIM" (correlation between self-attention and query token) decreases at the end of the model, suggesting that the self-attentions of later layers collapse into homogeneity and capture the same object shape information. *Right:* Fourier analysis shows that "CL + MIM" amplifies high-frequencies at the beginning and reduces them at the end. "CL + MIM" exploits high-frequency information at the beginning and low-frequency information at the end.

with combined losses efficiently exploits the strengths of both methods. Figure 12a shows the linear probing and fine-tuning accuracy on ImageNet with varying λ. Surprisingly, the hybrid models outperform MIM ($\lambda = 0$) and CL ($\lambda = 1$) in both aspects. Figure 12b and Figure 12c show the behaviors of the hybrid model ($\lambda = 0.2$) in terms of self-attentions in Section 2 and Fourier analysis in Section 3, respectively. They show that the hybrid model exploits the MIM's properties at the early layers and CL's properties at the later layers. In particular, Figure 12b shows that the self-attentions of the early layers are changed according to the query token, but those of the later layers are not. Likewise, Figure 12c shows that the early layers even increase the high-frequency information and capture fine textures, and the later layers reduce the high-frequency information.

6 CONCLUSION

We have conducted comparative studies highlighting various facets of two widely used self-supervised learning methods for vision transformers: contrastive learning and masked image modeling. The studies demonstrated many opposing properties of two methods: image information (image-level vs. token-level; as in Section 2), feature representations (low-frequency vs. high-frequency; as in Section 3), and different lead role components (later layers vs. early layers; as in Section 4). We further imagined the possible application exploiting only the benefits from both ends and showed how their mixture outperforms them.

Future directions.   Based on our study, diverse future directions can be explored. We believe there are better ways beyond a simple linear combination of CL and MIM objectives. For example, novel self-supervised learning can be considered, which applies CL for the later layers and MIM for the early layers. We may extend our findings on self-supervision for multi-stage ViTs, such as PiT (Heo et al., 2021) and Swin (Liu et al., 2021). Another interesting direction is to enhance the properties of CL or MIM. Techniques that help CL or MIM learn shapes or textures also may improve performance.

REPRODUCIBILITY STATEMENT

We will provide the code and experimental details for reproducing the results. The code will be released as open source. See Appendix A for detailed configurations.

REFERENCES

Hangbo Bao, Li Dong, and Furu Wei. Beit: Bert pre-training of image transformers. In *International Conference on Learning Representations*, 2022.

Mathilde Caron, Hugo Touvron, Ishan Misra, Hervé Jégou, Julien Mairal, Piotr Bojanowski, and Armand Joulin. Emerging properties in self-supervised vision transformers. In *International Conference on Computer Vision*, 2021.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning*, 2020a.

Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2021.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020b.

Xinlei Chen, Saining Xie, and Kaiming He. An empirical study of training self-supervised vision transformers. In *International Conference on Computer Vision*, 2021.

Ekin D Cubuk, Barret Zoph, Jonathon Shlens, and Quoc V Le. Randaugment: Practical automated data augmentation with a reduced search space. In *Advances in Neural Information Processing Systems*, 2020.

Zihang Dai, Hanxiao Liu, Quoc V Le, and Mingxing Tan. Coatnet: Marrying convolution and attention for all data sizes. *Advances in Neural Information Processing Systems*, 2021.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. 2021.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *International Conference on Learning Representations*, 2019.

Benjamin Graham, Alaaeldin El-Nouby, Hugo Touvron, Pierre Stock, Armand Joulin, Hervé Jégou, and Matthijs Douze. Levit: a vision transformer in convnet's clothing for faster inference. In *International Conference on Computer Vision*, 2021.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, et al. Bootstrap your own latent-a new approach to self-supervised learning. *Advances in neural information processing systems*, 2020.

Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, 2017.

Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

Kaiming He, Xinlei Chen, Saining Xie, Yanghao Li, Piotr Dollár, and Ross Girshick. Masked autoencoders are scalable vision learners. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2022.

Byeongho Heo, Sangdoo Yun, Dongyoon Han, Sanghyuk Chun, Junsuk Choe, and Seong Joon Oh. Rethinking spatial dimensions of vision transformers. In *International Conference on Computer Vision*, 2021.

Gao Huang, Yu Sun, Zhuang Liu, Daniel Sedra, and Kilian Q Weinberger. Deep networks with stochastic depth. In *European Conference on Computer Vision*, 2016.

Xun Huang and Serge Belongie. Arbitrary style transfer in real-time with adaptive instance normal-ization. In *Proceedings of the IEEE international conference on computer vision*, 2017.

Li Jing, Pascal Vincent, Yann LeCun, and Yuandong Tian. Understanding dimensional collapse in contrastive self-supervised learning. In *International Conference on Learning Representations*, 2022.

Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In *European conference on computer vision*, 2014.

Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *International Conference on Computer Vision*, 2021.

Thao Nguyen, Maithra Raghu, and Simon Kornblith. Do wide and deep networks learn the same things? uncovering how neural network representations vary with width and depth. 2021.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

Namuk Park and Songkuk Kim. Blurs behave like ensembles: Spatial smoothings to improve accuracy, uncertainty, and robustness. In *International Conference on Machine Learning*, 2022a.

Namuk Park and Songkuk Kim. How do vision transformers work? In *International Conference on Learning Representations*, 2022b.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems*, 2019.

Maithra Raghu, Thomas Unterthiner, Simon Kornblith, Chiyuan Zhang, and Alexey Dosovitskiy. Do vision transformers see like convolutional neural networks? *Advances in Neural Information Processing Systems*, 2021.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. *International Journal of Computer Vision (IJCV)*, 2015.

Alexander Strehl and Joydeep Ghosh. Cluster ensembles—a knowledge reuse framework for combin-ing multiple partitions. *Journal of machine learning research*, 2002.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. Rethinking the inception architecture for computer vision. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2016.

Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. In *European Conference on Computer Vision*, 2020a.

Yonglong Tian, Chen Sun, Ben Poole, Dilip Krishnan, Cordelia Schmid, and Phillip Isola. What makes for good views for contrastive learning? *Advances in Neural Information Processing Systems*, 33:6827–6839, 2020b.

Yuandong Tian, Xinlei Chen, and Surya Ganguli. Understanding self-supervised learning dynamics without contrastive pairs. In *International Conference on Machine Learning*, 2021.

Hugo Touvron, Matthieu Cord, Alaaeldin El-Nouby, Jakob Verbeek, and Hervé Jégou. Three things everyone should know about vision transformers. *arXiv preprint arXiv:2203.09795*, 2022.

Xinlong Wang, Rufeng Zhang, Chunhua Shen, Tao Kong, and Lei Li. Dense contrastive learning for self-supervised visual pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2021.

Chen Wei, Haoqi Fan, Saining Xie, Chao-Yuan Wu, Alan Yuille, and Christoph Feichtenhofer. Masked feature prediction for self-supervised visual pre-training. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2022a.

Yixuan Wei, Han Hu, Zhenda Xie, Zheng Zhang, Yue Cao, Jianmin Bao, Dong Chen, and Baining Guo. Contrastive learning rivals masked image modeling in fine-tuning via feature distillation. *arXiv preprint arXiv:2205.14141*, 2022b.

Zhenda Xie, Zheng Zhang, Yue Cao, Yutong Lin, Jianmin Bao, Zhuliang Yao, Qi Dai, and Han Hu. Simmim: A simple framework for masked image modeling. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2022.

Jiahui Yu, Zirui Wang, Vijay Vasudevan, Legg Yeung, Mojtaba Seyedhosseini, and Yonghui Wu. Coca: Contrastive captioners are image-text foundation models. *arXiv preprint arXiv:2205.01917*, 2022.

Sangdoo Yun, Dongyoon Han, Seong Joon Oh, Sanghyuk Chun, Junsuk Choe, and Youngjoon Yoo. Cutmix: Regularization strategy to train strong classifiers with localizable features. In *International Conference on Computer Vision*, 2019.

Hongyi Zhang, Moustapha Cisse, Yann N Dauphin, and David Lopez-Paz. mixup: Beyond empirical risk minimization. In *International Conference on Learning Representations*, 2018.

Daquan Zhou, Bingyi Kang, Xiaojie Jin, Linjie Yang, Xiaochen Lian, Zihang Jiang, Qibin Hou, and Jiashi Feng. Deepvit: Towards deeper vision transformer. *arXiv preprint arXiv:2103.11886*, 2021.

Jinghao Zhou, Chen Wei, Huiyu Wang, Wei Shen, Cihang Xie, Alan Yuille, and Tao Kong. ibot: Image bert pre-training with online tokenizer. *International Conference on Learning Representations*, 2022.

A SETUP

We build the configurations based on Xie et al. (2022) for fine-tuning and pre-training, and Caron et al. (2021) for linear probing. For data augmentation and regularization, we adopt widely used settings, e.g., Randaugment (Cubuk et al., 2020), label smoothing (Szegedy et al., 2016), mixup (Zhang et al., 2018), cutmix (Yun et al., 2019), stochastic depth (Huang et al., 2016). Layer decay (Bao et al., 2022) is also used. Table A.1 summarize the configurations. We use {1, 4, 8} NVIDIA A100 Tensor Core GPU for all experiments. Neural network models are implemented in PyTorch(Paszke et al., 2019); The code will be released publicly.

Table A.1: **Training settings.**

CONFIGURATION	Linear Probing	Fine-tuning	Pre-training
optimizer	sgd	adamw	adamw
base learning rate	1.0e-0	1.25e-3	1e-4
weight decay	0.05	0.05	0.05
batch size	1k	2k	1k
training epoch	50	100	100
learning rate schedule	cosine	cosine	multistep
warmup epoch	0	20	10
warmup schedule	·	linear	linear
randaugment	·	9, 0.5	9, 0.5
label smoothing	·	0.1	0.1
mixup	·	0.8	0.8
cutmix	·	1.0	1.0
stochastic depth	·	0.1	0.1
layer decay	·	0.65	1.0
gradient clip	·	5.0	5.0

B RELATED WORK

CL is a method based on comparing the global projection of two different random views. However, this approach usually suffers from the collapsing problem, where all representations collapse into constant solutions. To solve this problem, various methods such as negative samples and InfoNCE (Oord et al., 2018) have been proposed. Negative samples is an effective technique to avoid the collapsing problems, but they cause dimensional collapse (Jing et al., 2022) and require extra large batches (Chen et al., 2020a) or memory queues (He et al., 2020; Chen et al., 2020b) to retrieve them.

Some SSL methods, e.g. Grill et al. (2020); Caron et al. (2021), do not use negative samples and use the projections of their Siamese representations as the positives. Such self-distillation has been explored theoretically and empirically (Chen & He, 2021; Tian et al., 2021) to prevent the collapsing problem, but we do not discuss the distillation scheme in this paper. Wei et al. (2022b) shows that feature distillation improves the fine-tuning performance of CL by diversifying attention ranges; this observation is consistent with our

Figure A.1: **Restricted self-attention harms linear probing accuracy but improves fine-tuning accuracy.** We report the fine-tuning accuracy and linear probing accuracy of ViTs with restricted self-attention via attention mask.

(a) Attention distance   (b) Normalized MI

Figure B.1: **MIM family and CL family have consistent properties.** We visualize the behavior of self-attention in terms of attention distance, normalized mutual information (MI), and representational similarity for spatial tokens. *Left:* The attention distance of CL family, namely MoCo and DINO, is higher than that of MIM family, namely SimMIM, MAE, and BEiT. It suggests that CL family consistently capture global patterns. The attention distance of DINO is higher than that of MoCo, and we hypothesize that this is because DINO uses several techniques to prevent attention collapse, e.g., multi-crop training, not using negative samples, etc. *Right:* Likewise, the normalized MI of MIM is higher than that of CL, i.e., the self-attentions of MIM are correlated with query tokens.

(a) Fourier analysis   (b) Representation displacement

Figure B.2: **The explicit decoder architecture of MAE allows ViT to take the rich benefits of MIM.** We report the properties of the encoder and the decoder in terms of Fourier analysis and representational displacement as in Figure 8 and Figure 10. *Left:* Fourier analysis shows that decoder captures low-frequency information as shown in the right of Figure B.2a. Therefore, MIM backbone combined with a decoder utilizes higher frequency information as in the left of Figure B.2a. *Right:* In contrast to SimMIM, the magnitude of the displacement of MIM does not decrease with increasing depth. Moreover, unlike the backbone, self-attention modules dominates the change of representation in the decoder.

findings. While they focus on distillation to improve CL, we reveal the fundamental nature of self-supervised learning by rigorously comparing CL and MIM.

Compared with CL, MIM has been rarely explored. Various methods, such as histograms of oriented gradients (Wei et al., 2022a) and tokenization (Bao et al., 2022), have been proposed as part of porting masked language models to the image domain with ViTs. Among them, SimMIM (Xie et al., 2022) and MAE (He et al., 2022) are simple yet effective methods to reconstruct masked tokens without complicated pretext tasks. Because of its simplicity and superior performance in downstream operations, MIM is attracting attention as a promising technique in image processing.

Nevertheless, we find hints suggesting that CL and MIM utilize different aspects of the data, making them complementary. For example, Zhou et al. (2022); Wang et al. (2021); Yu et al. (2022) achieve high predictive performance by harmonizing the image-level and the token-level self-supervised learning.

(a) Stylized ImageNet (b) Robustness for noise frequency

Figure D.1: **Fine-tuned ViT inherits the robustness property against frequency-based noises.** Similar to Figure 9b, we measure the decrease in accuracy of ViTs fine-tuned with CL and MIM. *Left:* Even with fine-tuned ViTs, CL is shape-biased and MIM texture-biased when compared to each other. However, the performance gap is smaller than the result for the linear probing models. *Right:* Robustness against frequency-based random noise suggests the same conclusion: CL is robust against high-frequency noises, but MIM is not. In conclusion, the fine-tuning models inherits the properties of linear probing models.

C RESTRICTED SELF-ATTENTION

In Section 2, we demonstrate that the homogeneity of self-attention map, due to the attention collapse, helps ViT distinguish images but harms fine-tuning accuracy. One simple method to inject locality into self-attentions is to limit the receptive field of self-attention by using attention masks. Figure A.1 shows the predictive performance of ViT with restricted local self-attentions. As expected, the results are similar to the performance of MIM; As the kernel size decreases, the linear probing accuracy decreases but the fine-tuning accuracy increases. These results are consistent with our findings.

D CL TRAINS SELF-ATTENTIONS AND MIM TRAINS MLPS

CL captures low-frequency information and MIM captures high-frequency information. Moreover, self-attentions capture low-frequency information and MLPs capture high-frequency information (Park & Kim, 2022b). Therefore, we expect that CL mainly trains self-attentions and MIM trains MLPs.

To support this claim, we measure ℓ_2 distance between initial weight and optimized weight module-wisely. Table D.1 provides the result, indicating that the weight of self-attentions changes significantly in CL learning, and in MIM learning, the weight of MLP changes dominantly. This is consistent observation with Figures 10 and 11.

Table D.1: **CL primarily trains self-attention (Attn) and MIM trains MLP.** We measure ℓ_2 distance between initial weight and optimized weight module-wisely. The larger the distance, the more the method trained the module.

METHOD	Attn	MLP
MoCo	**286**	338
SimMIM	247	**375**

E THE ROLE OF DECODERS IN MASKED IMAGE MODELING

In Sections 3 and 4, we observe that the later layers of SimMIM implicitly play a role of decoder. Based on this insight, we expect that an explicit decoder, i.e., "adding the mask into the intermediate layer" and "deep ViT decoder", improves the performance of ViTs; MAE is such a model.

In Figure B.2, we analyze the token representations of MAE to understand its properties more deeply. Figure B.2a shows the result of Fourier analysis. In encoder, the token representations of MAE are higher frequency than SimMIM. Moreover, the relative amplitude does not decrease in the later layers, even though that of SimMIM decreases. Instead, the decoder of MAE utilizes low-

frequency information. As a result, the backbone of MAE does not have an unnecessary decoder part to linearly separate the token representations. Figure B.2b also shows the interesting properties of the decoder. Like SimMIM, MLP layers in encoder of MAE mainly change the token representations. On the contrary, the self-attention layers in the decoder primarily modify the token representations to reconstruct the masked tokens and interact with neighboring tokens.

F THE SHAPE-BIAS OF THE FINE-TUNED MODEL

In Figure 9, we demonstrate that linear probing model with CL is more shape-biased and that with MIM is texture-biased, compared with each other. As in the experiment, we calculate the classification results of ImageNet fine-tuned CL and MIM on Stylized-ImageNet, and measure the decrease in accuracy against frequency-based random noise. As we would expected, Figure D.1 shows that the property also extends to the fine-tuned model. Even though we still observe the difference between CL and MIM, the performance gap between CL and MIM is quite reduced compared to the gap between the linear probing models.