Efficient and Accurate Gradients for Neural SDEs

Abstract

Neural SDEs combine many of the best qualities of both RNNs and SDEs, and as such are a natural choice for modelling many types of temporal dynamics. They offer memory efficiency, high-capacity function approximation, and strong priors on model space. Neural SDEs may be trained as VAEs or as GANs; in either case it is necessary to backpropagate through the SDE solve. In particular this may be done by constructing a backwards-in-time SDE whose solution is the desired parameter gradients. However, this has previously suffered from severe speed and accuracy issues, due to high computational complexity, numerical errors in the SDE solve, and the cost of reconstructing Brownian motion. Here, we make several technical innovations to overcome these issues. First, we introduce the *reversible Heun method*: a new SDE solver that is algebraically reversible – which reduces numerical gradient errors to almost zero, improving several test metrics by substantial margins over state-of-the-art. Moreover it requires half as many function evaluations as comparable solvers, giving up to a $1.98\times$ speedup. Next, we introduce the *Brownian interval*. This is a new and computationally efficient way of exactly sampling *and reconstructing* Brownian motion; this is in contrast to previous reconstruction techniques that are both approximate and relatively slow. This gives up to a $10.6\times$ speed improvement over previous techniques. After that, when specifically training Neural SDEs as GANs (Kidger et al. 2021), we demonstrate how SDE-GANs may be trained through careful weight clipping and choice of activation function. This reduces computational cost (giving up to a $1.87\times$ speedup), and removes the truncation errors of the double adjoint required for gradient penalty, substantially improving several test metrics. Altogether these techniques offer substantial improvements over the state-of-the-art, with respect to both training speed and with respect to classification, prediction, and MMD test metrics. We have contributed implementations of all of our techniques to the `torchsde` library to help facilitate their adoption.

1 Introduction

Stochastic differential equations   Stochastic differential equations have seen widespread use in the mathematical modelling of random phenomena, such as particle systems [1], financial markets [2], population dynamics [3], and genetics [4]. Featuring inherent randomness, then in modern machine learning parlance SDEs are generative models.

Such models have typically been constructed theoretically, and are usually relatively simple. For example the Black–Scholes equation, widely used to model asset prices in financial markets, has only two scalar parameters: a fixed drift and a fixed diffusion [5].

Neural stochastic differential equations   Neural stochastic differential equations offer a shift in this paradigm. By parameterising the drift and diffusion of an SDE as neural networks, then modelling

capacity is greatly increased, and theoretically arbitrary SDEs may be approximated. (By the universal approximation theorem for neural networks [6, 7].) Several authors have now studied or introduced Neural SDEs; [8, 9, 10, 11, 12, 13, 14, 15, 16] amongst others.

Connections to recurrent neural networks Due to the timelike structure of an SDE, a numerically discretised (Neural) SDE may be interpreted as an RNN, whose input is random noise – Brownian motion – and whose output is a generated sample. Subject to a suitable loss function between distributions, such as the KL divergence [15] or Wasserstein distance [16], this may then simply be backpropagated through in the usual way.

Generative time series models SDEs are naturally random. In modern machine learning parlance they are thus generative models. As such we treat Neural SDEs as *generative time series models*.

The (recurrent) neural network-like structure offers high-capacity function approximation, whilst the SDE-like structure offers strong priors on model space, memory efficiency, and deep theoretical connections to a well-understood literature. Relative to the classical SDE literature, Neural SDEs have essentially unprecedented modelling capacity.

(Generative) time series models are of classical interest, with forecasting models such as Holt–Winters [17, 18], ARMA [19] and so on. It has also attracted much recent interest with (besides Neural SDEs) the development of models such as Time Series GAN [20], Latent ODEs [21], GRU-ODE-Bayes [22], ODE^{2}VAE [23], CTFPs [24], Neural ODE Processes [25] and Neural Jump ODEs [26].

1.1 Contributions

We study backpropagation through SDE solvers, in particular to train Neural SDEs, via continuous adjoint methods. We introduce several technical innovations to improve both model performance and the speed of training: in particular to reduce numerical gradient errors to almost zero.

First, we introduce the *reversible Heun method*: a new SDE solver, constructed to be *algebraically reversible*. By matching the truncation errors of the forward and backward passes, the gradients computed via continuous adjoint method are precisely those of the numerical discretisation of the forward pass. This overcomes the typical greatest limitation of continuous adjoint methods – and to the best of our knowledge, is the first algebraically reversible SDE solver to have been developed.

After that, we introduce the *Brownian Interval* as a new way of sampling *and reconstructing* Brownian motion. It is fast, memory efficient and exact. It has an average (modal) time complexity of $\mathcal{O}(1)$, and consumes only $\mathcal{O}(1)$ GPU memory. This is contrast to previous techniques requiring either $\mathcal{O}(T)$ memory, or a choice of approximation error $\varepsilon \ll 1$ and then a time complexity of $\mathcal{O}(\log(1/\varepsilon))$.

Finally, we demonstrate how the Lipschitz condition for the discriminator of an SDE-GAN may be imposed without gradient penalties – instead using careful clipping and the LipSwish activation function – so as to overcome their previous incompatibility with continuous adjoint methods.

Overall, multiple technical innovations provide substantial improvements over the state-of-the-art with respect to training speed, and with respect to classification, prediction, and MMD test metrics.

2 Background

2.1 Neural SDE construction

Certain minimal amount of structure Following Kidger et al. [16], we construct Neural SDEs with a certain minimal amount of structure. Let $T > 0$ be fixed and suppose we wish to model a path-valued random variable $Y_{\text{true}} \colon [0, T] \to \mathbb{R}^y$. The size of y is the dimensionality of the data.[1]

Let $W \colon [0, T] \to \mathbb{R}^w$ be a w-dimensional Brownian motion, and let $V \sim \mathcal{N}(0, I_v,)$ be drawn from a v-dimensional standard multivariate normal. The values w, v are hyperparameters describing the size of the noise. Let

$$\zeta_\theta \colon \mathbb{R}^v \to \mathbb{R}^x, \quad \mu_\theta \colon [0, T] \times \mathbb{R}^x \to \mathbb{R}^x, \quad \sigma_\theta \colon [0, T] \times \mathbb{R}^x \to \mathbb{R}^{x \times w}, \quad \ell_\theta \colon \mathbb{R}^x \to \mathbb{R}^y,$$

---

[1]In practice we will typically observe some discretised time series sampled from Y_{true}. For ease of presentation we will neglect this detail for now and will return to it in Section 2.3.

82 where ζ_θ, μ_θ and σ_θ are neural networks and ℓ_θ is affine. Collectively these are parameterised by θ.
83 The dimension x is a hyperparameter describing the size of the hidden state.

84 We consider Neural SDEs as models of the form

$$X_0 = \zeta_\theta(V), \qquad \mathrm{d}X_t = \mu_\theta(t, X_t)\,\mathrm{d}t + \sigma_\theta(t, X_t) \circ \mathrm{d}W_t, \qquad Y_t = \ell_\theta(X_t), \tag{1}$$

85 for $t \in [0, T]$, with $X \colon [0, T] \to \mathbb{R}^x$ the (strong) solution to the SDE.[2] The solution X is guaranteed
86 to exist given mild conditions: that μ_θ, σ_θ are Lipschitz, and that $\mathbb{E}_V \left[\zeta_\theta(V)^2 \right] < \infty$.

87 We seek to train this model such that $Y \overset{\mathrm{d}}{\approx} Y_{\text{true}}$. That is to say, the model Y should have approximately
88 the same distribution as the target Y_{true}, for some notion of approximate.

89 **RNNs as discretised SDEs** The minimal amount of structure is chosen to parallel RNNs. The
90 solution X may be interpreted as hidden state, and the ℓ_θ maps the hidden state to the output of the
91 model. In Appendix A we provide sample PyTorch [27] code computing a discretised SDE according
92 to the Euler–Maruyama method. The result is an RNN consuming random noise as input.

2.2   Training criteria for Neural SDEs

94 Equation (1) produces a random variable $Y \colon [0, T] \to \mathbb{R}^y$ implicitly depending on parameters θ. This
95 model must still be fit to data. This may be done by optimising a distance between the probability
96 distributions (laws) for Y and Y_{true}.

97 **SDE-GANs** The Wasserstein distance may be used by constructing a discriminator and training
98 adversarially, as in Kidger et al. [16]. Let $F_\phi(Y) = m_\phi \cdot H_T$, where

$$H_0 = \xi_\phi(Y_0), \qquad \mathrm{d}H_t = f_\phi(t, H_t)\,\mathrm{d}t + g_\phi(t, H_t) \circ \mathrm{d}Y_t, \tag{2}$$

99 for suitable neural networks ξ_ϕ, f_ϕ, g_ϕ and vector m_ϕ. This is a deterministic function of the generated
100 sample Y. Here $\cdot$ denotes a dot product. They then train with respect to

$$\min_\theta \max_\phi \left(\mathbb{E}_Y \left[F_\phi(Y) \right] - \mathbb{E}_{Y_{\text{true}}} \left[F_\phi(Y_{\text{true}}) \right] \right). \tag{3}$$

101 See Appendix B for additional details on this approach, and in particular how it generalises the
102 classical approach to fitting (calibrating) SDEs.

103 **Latent SDEs** Li et al. [15] instead optimise a KL divergence. This consists of constructing an
104 auxiliary process $\widehat{X}$ with drift ν_ϕ parameterised by ϕ, and optimising an expression of the form

$$\min_{\theta, \phi} \mathbb{E}_{W, Y_{\text{true}}} \left[\int_0^T (Y_t - \ell_\theta(\widehat{X}_t))^2 + \frac{1}{2} \left\| (\sigma_\theta(t, \widehat{X}_t))^{-1} (\mu_\theta(t, \widehat{X}_t) - \nu_\phi(t, \widehat{X}_t, Y_{\text{true}})) \right\|_2^2 \mathrm{d}t, \right]. \tag{4}$$

105 The full construction is moderately technical; see Appendix B for further details.

2.3   Discretised observations

107 Observations of Y_{true} are typically a discrete time series, rather than a true continuous-time path.
108 This is not a serious hurdle. If training an SDE-GAN, then equation (2) may be evaluated on an
109 interpolation Y_{true} of the observed data. If training a Latent SDE, then ν_ϕ in equation (4) may depend
110 explicitly on the discretised Y_{true}.

2.4   Backpropagation through SDE solves

112 Whether the loss for our generated sample Y is produced via a Latent SDE or via the discriminator of
113 an SDE-GAN, it is still required to backpropagate from the loss to the parameters θ, ϕ.

114 Here we use *the continuous adjoint method*. Also known as simply 'the adjoint method', or 'optimise-
115 then-discretise', this has recently attracted much attention in the modern literature on neural differ-
116 ential equations. This exploits the reversibility of a differential equation: as with invertible neural

---

[2]The notation '$\circ\,\mathrm{d}W_t$' denotes Stratonovich integration. Itô is less efficient; see Appendix C.

117 networks [28], intermediate computations such as X_t for $t < T$ are reconstructed from output
118 computations, so that they do not need to be held in memory.

119 Given some Stratonovich SDE

$$\mathrm{d}Z_t = \mu(t, Z_t)\, \mathrm{d}t + \sigma(t, Z_t) \circ \mathrm{d}W_t \quad \text{for } t \in [0, T], \tag{5}$$

120 and a loss $L \colon \mathbb{R}^z \to \mathbb{R}$ on its terminal value Z_T, then the adjoint process $A_t = \mathrm{d}L(Z_T)/\mathrm{d}Z_t \in \mathbb{R}^z$ is a
121 (strong) solution to

$$\mathrm{d}A_t^i = -A_t^j \frac{\partial \mu^j}{\partial Z^i}(t, Z_t)\, \mathrm{d}t - A_t^j \frac{\partial \sigma^{j,k}}{\partial Z^i}(t, Z_t) \circ \mathrm{d}W_t^k, \tag{6}$$

122 which in particular uses the same Brownian motion W as on the forward pass. Equations (5) and (6)
123 may be combined into a single SDE and solved backwards-in-time[3] from $t = T$ to $t = 0$, starting
124 from $Z_T = Z_T$ (computed on the forward pass) and $A_T = L(Z_T)/\mathrm{d}Z_T$. Then $A_0 = \mathrm{d}L(Z_T)/Z_0$ is the
125 desired backpropagated gradient.

126 Note that we assumed here that the loss L acts only on Z_T, not all of Z. This is not an issue in
127 practice. In both equations (3) and (4), the loss is an integral. As such it may be computed as part of
128 Z in a single SDE solve. This outputs a value at time T, the operation L simply extracts this term
129 from Z_T, and then this may be backpropagated through as described here.

130 The main issue is that the two numerical approximations to Z_t, computed in the forward and backward
131 passes of equation (5), are different. This means that the Z_t used as an input in equation (6) has some
132 discrepancy from the forward calculation, and the gradients A_0 suffer some error as a result. (Often
133 exacerbating an already tricky training procedure, such as the adversarial training of SDE-GANs.)

134 In Appendix C we provide further discussion on how an SDE solve may be backpropagated through.

2.5 Alternate constructions

136 There are other uses for Neural SDEs, beyond our scope here. For example Song et al. [30] combine
137 SDEs with score-matching, and Xu et al. [31] use SDEs to represent Bayesian uncertainty over
138 parameters. The techniques introduced in this paper apply to any backpropagation through an SDE
139 solve. (And therefore not to Song et al. [30], for example.)

3 Reversible Heun method

141 We introduce a new SDE solver, which we refer to as
142 the *reversible Heun method*. Its key property is algebraic
143 reversibility; moreover to the best of our knowledge it is
144 the first SDE solver to exhibit this property.

145 To fix notation, we consider solving the Stratonovich SDE
146

$$\mathrm{d}Z_t = \mu(t, Z_t)\, \mathrm{d}t + \sigma(t, Z_t) \circ \mathrm{d}W_t, \tag{7}$$

147 with known initial condition Z_0.

148 **Solver** We begin by selecting a step size Δt, and ini-
149 tialising $t_0 = 0$, $z_0 = \widehat{z}_0 = Z_0$, $\mu_0 = \mu(0, Z_0)$ and
150 $\sigma_0 = \sigma(0, Z_0)$. Let W denote a single sample path of
151 Brownian motion. It is important that the same sample
152 be used for both the forward and backward passes of the
153 algorithm; computationally this may be accomplished by
154 taking W to be a Brownian Interval, which we will introduce in Section 4.

Algorithm 1: Forward pass

Input: $t_n, z_n, \widehat{z}_n, \mu_n, \sigma_n, \Delta t, W$

$t_{n+1} = t_n + \Delta t$

$\Delta W_n = W_{t_{n+1}} - W_{t_n}$

$\widehat{z}_{n+1} = 2z_n - \widehat{z}_n + \mu_n \Delta t + \sigma_n \Delta W_n$

$\mu_{n+1} = \mu(t_{n+1}, \widehat{z}_{n+1})$

$\sigma_{n+1} = \sigma(t_{n+1}, \widehat{z}_{n+1})$

$z_{n+1} = z_n + \frac{1}{2}(\mu_n + \mu_{n+1})\Delta t$

$\qquad + \frac{1}{2}(\sigma_n + \sigma_{n+1})\Delta W_n$

Output: $t_{n+1}, z_{n+1}, \widehat{z}_{n+1}, \mu_{n+1}, \sigma_{n+1}$

---

155 We then iterate Algorithm 1. Suppose $T = N\Delta t$ so that $z_N, \widehat{z}_N, \mu_N, \sigma_N$ are the final output. Then
156 $z_N \approx Z_T$ is returned, whilst $z_N, \widehat{z}_N, \mu_N, \sigma_N$ are all retained for the backward pass.

157 Nothing else need be saved in memory for the backward pass: in particular no intermediate computa-
158 tions, as would otherwise be typical.

---

[3]Li et al. [15] give rigorous meaning to this via two-sided filtrations; for the reader familiar with rough path theory then Kidger et al. [29, Appendix A] also give an elegant pathwise interpretation. The reader familiar with neither of these should feel free to intuitively treat Stratonovich (but not Itô) SDEs like ODEs.

Algebraic reversibility The key advantage of the reversible Heun method, and the motivating reason for its use alongside continuous-time adjoint methods, is that it is algebraically reversible. That is, it is possible to reconstruct $(z_n, \widehat{z}_n, \mu_n, \sigma_n)$ from $(z_{n+1}, \widehat{z}_{n+1}, \mu_{n+1}, \sigma_{n+1})$ in closed form. (And without a fixed-point iteration.)

This crucial property will mean that it is possible to backpropagate through the SDE solve such that the gradients obtained from optimise-then-discretise *exactly match* the gradients obtained from discretise-then-optimise – subject only to floating point error – in doing so overcoming the greatest limitation of continuous adjoint methods.

To the best of our knowledge, the reversible Heun method is the first algebraically reversible SDE solver.

Computational efficiency A further advantage of the reversible Heun method is computational efficiency. The method requires only a single function evaluation (of both the drift and diffusion) per step. This is contrast to other Stratonovich solvers (such as the midpoint method or regular Heun's method), which require two function evaluations per step. This is now on a par with the Euler–Maruyama method (which, unfortunately for our purposes, converges to the Itô solution).

Algorithm 2: Backward pass

Input: $t_{n+1}, z_{n+1}, \mu_{n+1}, \sigma_{n+1}, \Delta t, W,$
$$\frac{\partial L(Z_T)}{\partial z_{n+1}}, \frac{\partial L(Z_T)}{\partial \widehat{z}_{n+1}}, \frac{\partial L(Z_T)}{\partial \mu_{n+1}}, \frac{\partial L(Z_T)}{\partial \sigma_{n+1}}$$

\# Reverse step
$$t_n = t_{n+1} - \Delta t$$
$$\Delta W_n = W_{t_{n+1}} - W_{t_n}$$
$$\widehat{z}_n = 2z_{n+1} - \widehat{z}_{n+1} - \mu_{n+1}\Delta t - \sigma_{n+1}\Delta W_n$$
$$\mu_n = \mu(t_n, \widehat{z}_n)$$
$$\sigma_n = \sigma(t_n, \widehat{z}_n)$$
$$z_n = z_{n+1} - \frac{1}{2}(\mu_n + \mu_{n+1})\Delta t$$
$$\qquad - \frac{1}{2}(\sigma_n + \sigma_{n+1})\Delta W_n$$

\# Local forward
$$z_{n+1}, \widehat{z}_{n+1}, \mu_{n+1}, \sigma_{n+1} = \text{Forward}(t_n, z_n, \widehat{z}_n, \mu_n,$$
$$\sigma_n, \Delta t, W)$$

\# Local backward
$$\frac{\partial L(Z_T)}{\partial(z_n, \widehat{z}_n, \mu_n, \sigma_n)} = \frac{\partial L(Z_T)}{\partial(z_{n+1}, \widehat{z}_{n+1}, \mu_{n+1}, \sigma_{n+1})}$$
$$\cdot \frac{\partial(z_{n+1}, \widehat{z}_{n+1}, \mu_{n+1}, \sigma_{n+1})}{\partial(z_n, \widehat{z}_n, \mu_n, \sigma_n)}$$

Output: $t_n, z_n, \mu_n, \sigma_n,$
$$\frac{\partial L(Z_T)}{\partial z_n}, \frac{\partial L(Z_T)}{\partial \widehat{z}_n}, \frac{\partial L(Z_T)}{\partial \mu_n}, \frac{\partial L(Z_T)}{\partial \sigma_n}$$

Convergence of the solver When applied to the Stratonovich SDE (7), the reversible Heun method exhibits strong convergence of order 0.5; the same as the usual Heun's method.

Theorem. *Let $\{z_n\}$ denote the numerical solution of (7) obtained by Algorithm 1 with a constant step size Δt and assume sufficient regularity of μ and σ. Then there exists a constant $C > 0$ so that*

$$\mathbb{E}\Big[\big\|z_N - Z_T\big\|_2\Big] \leq C\sqrt{\Delta t},$$

for small Δt. That is, strong convergence of order 0.5. If σ is constant, then this improves to order 1.

The key idea in the proof is to consider two adjacent steps of the SDE solver. Then the update $\widehat{z}_n \mapsto \widehat{z}_{n+2}$ becomes a step of a midpoint method, whilst $z_n \mapsto z_{n+1}$ is similar to Heun's method. This makes it possible to show that $\{\widehat{z}_n\}$ and $\{z_n\}$ stay close together: $\mathbb{E}\big[\|z_n - \widehat{z}_n\|_2^4\big] \sim O(\Delta t^2)$. With this $\mathbb{L}_4$ bound on $z - \widehat{z}$, we can then apply standard lines of argument from the numerical SDE literature. Chaining together local mean squared error estimates, we obtain $\mathbb{E}\big[\|z_N - Z_T\|_2^2\big] \sim O(\Delta t)$.

See Appendix D for the full proof. We additionally consider stability in the ODE setting. Whilst the method is not A-stable, we do show it has the same absolute stability region for a linear test equation as the (reversible) asynchronous leapfrog integrator proposed for Neural ODEs in Zhuang et al. [32].

Precise gradients The backward pass is shown in Algorithm 2. As the same numerical solution $\{z_n\}$ is recovered on both the forward and backward passes – exhibiting the same truncation errors – then the computed gradients are precisely the (discretise-then-optimise) gradients of the numerical discretisation of the forward pass.

This is unlike the case of solving equation (6) via standard numerical techniques, for which small or adaptive step sizes are necessary to obtain useful gradients [15].

Table 1: SDE-GAN on weights dataset; Latent SDE on air quality dataset. Mean $\pm$ standard deviation averaged over three runs.

Dataset, Solver	Label classification accuracy (%)	MMD ($\times 10^{-2}$)	Training time
Weights, Midpoint	—	4.38 ± 0.67	5.12 ± 0.01 days
Weights, Reversible Heun	—	$\mathbf{1.75 \pm 0.3}$	$\mathbf{2.59 \pm 0.05}$ days
Air quality, Midpoint	46.3 ± 5.1	0.591 ± 0.206	5.58 ± 0.54 hours
Air quality, Reversible Heun	$\mathbf{49.2 \pm 0.02}$	$\mathbf{0.472 \pm 0.290}$	$\mathbf{4.47 \pm 0.31}$ hours

3.1 Experiments

We validate the empirical performance of the reversible Heun method. For space, we present abbreviated details and results here. See Appendix F for details of the hyperparameter optimisation procedure, test metric definitions, and so on, and for further results on additional datasets and additional metrics.

Versus midpoint We begin by comparing the reversible Heun method with the midpoint method, which also converges to the Stratonovich solution. We train an SDE-GAN on a dataset of weight trajectories evolving under stochastic gradient descent, and train a Latent SDE on a dataset of air quality over Beijing.

See Table 1. Due to the reduced number of vector field evaluations, we find that training speed roughly doubles ($1.98\times$) on the weights dataset, whilst its numerically precise gradients substantially improve the test metrics (comparing generated samples to a held-out test set). Similar behaviour is observed on the air quality dataset, with substantial test metric improvements and a training speed improvement of $1.25\times$.

Figure 1: Samples (red) from Latent SDE on O_3 ozone channel of air quality dataset (blue).

Figure 2: Relative error in gradient calculation.

Samples We verify that samples from a model using reversible Heun resemble that of the original dataset: in Figure 1 we show the Latent SDE on the ozone concentration over Beijing.

Gradient error We investigate the numerical error made in the gradient calculation. We fix a test problem (differentiating a small Neural SDE) and vary the step size and solver; see Figure 2. Standard solvers produce large errors decreasing with step size, whilst the reversible Heun method produces results accurate to floating point error, unattainable by any standard solver.

4 Brownian Interval

Numerically solving an SDE, via the reversible Heun method or via any other numerical solver, requires sampling Brownian motion: this is the input W in Algorithms 1 and 2.

Brownian bridges Mathematically, sampling Brownian motion is straightforward. A fixed-step numerical solver may simply sample independent increments during its time stepping. An adaptive solver (which may reject steps) may use Lévy's Brownian bridge [33] formula to generate increments with the appropriate correlations: letting $W_{a,b} = W_b - W_a \in \mathbb{R}^w$, then for $u < s < t$,

$$W_{u,s} | W_{u,t} = \mathcal{N}\left(\frac{s-u}{t-u} W_{u,t} , \frac{(t-s)(s-u)}{t-u} I_w \right). \tag{8}$$

Brownian reconstruction However, there are computational difficulties. On the backward pass, the same Brownian sample as the forward pass must be used, and potentially at locations other than were measured on the forward pass [15].

Time and memory efficiency The simple but memory intensive approach would be to store every sample made on the forward pass, and then on the backward pass reuse these samples, or sample Brownian noise according to equation (8), as appropriate.

Li et al. [15] instead offer a memory-inefficient but time-intensive approach, by introducing the 'Brownian Tree'. This approximates the real line by a tree of dyadic points. Samples are approximate, and demand deep (slow) traversals of the tree.

Binary tree of (interval, seed) pairs In response to this, we introduce the 'Brownian Interval', which offers memory efficiency, exact samples, and fast query times, all at once. The Brownian Interval is built around a binary tree, each node of which is an interval and a random seed.

The tree starts as a stump consisting of the global interval $[0, T]$ and a randomly generated random seed. New leaf nodes are created as observations of the sample are made. For example, making a first query at $[s, t] \subseteq [0, T]$ (an operation that returns $W_{s,t}$) produces the binary tree shown in Figure 3a. Algorithm 4 in Appendix E gives the formal definition of this procedure. Making a subsequent query at $[u, v]$ with $u < s < v < t$ produces Figure 3b. Using a splittable PRNG [34, 35], each child node has a random seed deterministically produced from the seed of its parent.

The tree is thus designed to completely encode the conditional statistics of a sample of Brownian motion: $W_{s,t}, W_{t,u}$ are completely specified by $t, [s, u], W_{s,u}$, equation (8), and the random seed for $[s, u]$.

In principle this now gives a way to compute $W_{s,t}$; calculating $W_{s,u}$ recursively. Naïvely this would be very slow – recursing to the root on every query – which we cover by augmenting the binary tree structure with a fixed-size Least Recently Used (LRU) cache on the computed increments $W_{s,t}$.

Algorithm 3: Sampling the Brownian Interval

Type: Let *Node* denote a 5-tuple consisting of an interval, a seed, and three optional *Node*s, corresponding to the parent node, and two child nodes, respectively. (Optional as the root has no parent and leaves have no children.)

State: Binary tree with elements of type *Node*, with root $\widehat{I} = ([0, T], \widehat{s}, *, \widehat{I}_{\texttt{left}}, \widehat{I}_{\texttt{right}})$. A *Node* $\widehat{J}$.

Input: Interval $[s, t] \subseteq [0, T]$

\# The returned 'nodes' is a list of *Node*s whose
\# intervals partition $[s, t]$. Practically speaking
\# this will usually have only one or two elements.
\# $\widehat{J}$ is a hint for where in the tree we are.
nodes = `traverse`($\widehat{J}, [s, t]$)

def `sample`(I : *Node*)**:**
    if I is $\widehat{I}$ **then**
      | return $\mathcal{N}(0, T)$ sampled with seed $\widehat{s}$.
    Let $I = ([a, b], s, I_{\texttt{parent}}, I_{\texttt{left}}, I_{\texttt{right}})$
    Let $I_{\texttt{parent}} = ([a_p, b_p], s_p, I_{pp}, I_{lp}, I_{rp})$
    $W_{\texttt{parent}}$ = `sample`($I_{\texttt{parent}}$)
    if I_i is I_{rp} **then**
      | $W_{\texttt{left}}$ = `bridge`($a_p, b_p, a, W_{\texttt{parent}}, s$)
      | return $W_{\texttt{parent}} - W_{\texttt{left}}$
    else
      | return `bridge`($a_p, b_p, b, W_{\texttt{parent}}, s$)
`sample` = `LRUCache`(`sample`)

$\widehat{J} \leftarrow \text{nodes}[-1]$
$W_{s,t} = \sum_{I \in \text{nodes}}$ `sample`(I)
Output: $W_{s,t}$

(a)   (b)

Figure 3: Binary tree of intervals.

See Algorithm 3, where `bridge` denotes equation (8). The operation `traverse` traverses the binary tree to find or create the list of nodes whose disjoint union is the interval of interest, and is defined explicitly as Algorithm 4 in Appendix E.

Additionally see Appendix E for various technical considerations and extensions to this algorithm.

Advantages of the Brownian Interval The LRU cache ensures that queries have an average-case (modal) time complexity of only $\mathcal{O}(1)$: in SDE solvers, subsequent queries are typically close to (and thus conditional on) previous queries. Even given cache misses all the way up the tree, the worst-case time complexity will only be $\mathcal{O}(\log(1/s))$ in the average step size s of the SDE solver. This is in contrast to the Brownian Tree, which has an (average or worst-case) time complexity of $\mathcal{O}(\log(1/\varepsilon))$ in the approximation error $\varepsilon \ll s$.

Table 2: Brownian Tree against Brownian Interval on speed benchmarks, over 100 subintervals.

	SDE solve, speed (seconds)			Doubly sequential access, speed (seconds)		
	Size=1	Size=2560	Size=32768	Size=1	Size=2560	Size=32768
B. Tree	1.6×10^0	2.0×10^0	5.00×10^2	2.4×10^{-1}	3.9×10^{-1}	2.9×10^0
B. Interval	$\mathbf{8.2 \times 10^{-1}}$	$\mathbf{1.3 \times 10^0}$	$\mathbf{4.7 \times 10^1}$	$\mathbf{5.0 \times 10^{-2}}$	$\mathbf{8.0 \times 10^{-2}}$	$\mathbf{3.5 \times 10^{-1}}$

Meanwhile the (GPU) memory cost is only $\mathcal{O}(1)$, corresponding to the fixed and constant size of the LRU cache. There is the small additional cost of storing the tree structure itself, but this is held in CPU memory, which for practical purposes is essentially infinite. This is in contrast to simply holding all the Brownian samples in memory, which has a memory cost of $\mathcal{O}(T)$.

Finally, queries are exact because the tree aligns with the query points. This is contrast to the Brownian Tree, which only produces samples up to some discretisation of the real line at resolution ε.

4.1 Experiments

We benchmark the performance of the Brownian Interval against the Brownian Tree considered in Li et al. [15]. We include benchmarks corresponding to varying batch sizes, number of sample intervals, and access patterns. For space, just a subset of results are shown. Precise experimental details and further results are available in Appendix F.

See Table 2. We see that the Brownian Interval is uniformly faster than the Brownian Tree, ranging from $1.5\times$ faster on smaller problems to $10.6\times$ faster on larger problems. Moreover these speed gains are despite the Brownian Interval being written in Python, whilst the Brownian Tree is carefully optimised and written in C++.

5 Training SDE-GANs without gradient penalty

Kidger et al. [16] train SDEs as GANs, as discussed in Section 2.2, using a neural CDE as a discriminator as in equation (2). They found that only gradient penalty [36] was suitable to enforce the Lipschitz condition, given the recurrent structure of the discriminator.

However, gradient penalty requires a double-backward. This complicates the use of continuous adjoint methods: the double-continuous-adjoint introduces substantial truncation error at moderate step sizes; sufficient to obstruct training and requiring small step sizes to resolve.

Here we overcome this limitation, and moreover do so independently of the possibility of obtaining exact double-gradients via the reversible Heun method. For simplicity we now assume throughout that our discriminator vector fields f_ϕ, g_ϕ are MLPs, which is also the choice we make in practice.

Lipschitz constant one   The key point is that the vector fields f_ϕ, g_ϕ of the discriminator must not only be Lipschitz, but must have Lipschitz constant one.

Given vector fields with Lipschitz constant λ, then the recurrent structure of the discriminator means that the Lipschitz constant of the overall discriminator will be $\mathcal{O}(\lambda^T)$. Ensuring $\lambda \approx 1$ with $\lambda \leq 1$ thus enforces that the overall discriminator is Lipschitz with a reasonable Lipschitz constant.

Hard constraint   The exponential size of $\mathcal{O}(\lambda^T)$ means that λ only slightly greater than one is still insufficient for stable training. We found that this ruled out enforcing $\lambda \leq 1$ via soft constraints, via either spectral normalisation [37] or gradient penalty across just vector field evaluations.

Clipping   The first part of enforcing this Lipschitz constraint is careful clipping. Considering each linear operation from $\mathbb{R}^a \to \mathbb{R}^b$ as a matrix in $A \in \mathbb{R}^{a \times b}$, then after each gradient update we clip its entries to the region $[-1/b, 1/b]$. Given $x \in \mathbb{R}^a$, then this enforces $\|Ax\|_\infty \leq \|x\|_\infty$.

LipSwish activation functions   Next we must pick an activation function with Lipschitz constant at most one. It should additionally be at least twice continuously differentiable to ensure convergence of the numerical SDE solver (Appendix D). In particular this rules out the ReLU.

Table 3: SDE-GAN on OU dataset. Mean $\pm$ standard deviation averaged over three runs.

Solver	Test Metrics			
	Real/fake classification accuracy (%)	Prediction loss	MMD $(\times 10^{-1})$	Training time (hours)
Midpoint w/ gradient penalty	98.2 ± 2.4	2.71 ± 1.03	2.58 ± 1.81	55.0 ± 27.7
Midpoint w/ clipping	93.9 ± 6.9	1.65 ± 0.17	1.03 ± 0.10	32.5 ± 12.1
Reversible Heun w/ clipping	$\mathbf{67.7 \pm 1.1}$	$\mathbf{1.38 \pm 0.06}$	$\mathbf{0.45 \pm 0.22}$	$\mathbf{29.4 \pm 8.9}$

There remain several admissible choices; we use the LipSwish activation function introduced by Chen et al. [38], defined as $\rho(x) = 0.909\,x\,\mathrm{sigmoid}(x)$. This was carefully constructed to have Lipschitz constant one, and to be smooth. Moreover the SiLU activation function [39, 40, 41] from which it is derived has been reported as an empirically strong choice.

The overall vector fields f_ϕ, g_ϕ of the discriminator consist of linear operations (which are constrained by clipping), adding biases (an operation with Lipschitz constant one), and activation functions (taken to be LipSwish). Thus the Lipschitz constant of the overall vector field is at most one, as desired.

5.1 Experiments

We test the SDE-GAN on a dataset of time-varying Ornstein–Uhlenbeck samples. For space only a subset of results are shown; see Appendix F for further details of the dataset, optimiser, and so on.

See Table 3 for the results. We see that the test metrics substantially improve with clipping, over gradient penalty (which struggles due to numerical errors in the double adjoint). The lack of double backward additionally implies a computational speed-up. This reduces training time from 55 hours to just 33 hours. Switching to reversible Heun additionally and substantially improves the test metrics, and further reduces training time to 29 hours; a speed improvement of $1.87\times$.

6 Discussion

6.1 Available implementation in `torchsde`

To facilitate the use of the techniques introduced here – in particular without requiring a technical background in numerical SDEs – we have contributed implementations of both the reversible Heun method and the Brownian Interval to the open-source `torchsde` [42] package. (In which the Brownian Interval has already become the default choice, due to its speed.)

6.2 Limitations

The reversible Heun method, Brownian Interval, and training of SDE-GANs via clipping, all appear to be strict improvements over previous techniques. Across our experiments we have observed no limitations relative to previous techniques.

6.3 Ethical statement

No significant negative societal impacts are anticipated as a result of this work. A positive environmental impact is anticipated, due to the reduction in compute costs implied by the techniques introduced. See Appendix G for a more in-depth discussion.

7 Conclusion

We have introduced several improvements over the previous state-of-the-art for Neural SDEs, with respect to both training speed and test metrics. This has been accomplished through several novel technical innovations, including a first-of-its-kind algebraically reversible SDE solver; a fast, exact, and memory efficient way of sampling and reconstructing Brownian motion; and the development of SDE-GANs via careful clipping and choice of activation function.

References

[1] W. T. Coffey, Y. P. Kalmykov, and J. T. Waldron. *The Langevin Equation: With Applications to Stochastic Problems in Physics, Chemistry and Electrical Engineering*. World Scientifc, 2012.

[2] S. E. Shreve. *Stochastic Calculus for Finance II: Continuous-Time Models*. Springer Science & Business Media, 2004.

[3] K.-C. Chen, T.-Y. Wang, H.-H. Tseng, C.-Y. F. Huang, and C.-Y. Kao. A stochastic differential equation model for quantifying transcriptional regulatory network in saccharomyces cerevisiae. *Bioinformatics*, 21(12):2883–2890, 2005.

[4] T. Huillet. On Wright-Fisher diffusion and its relatives. *Journal of Statistical Mechanics: Theory and Experiment*, 11, 2007.

[5] F. Black and M. Scholes. The Pricing of Options and Corporate Liabilities. *Journal of Political Economy*, 81(3):637–654, 1973.

[6] A. Pinkus. Approximation theory of the MLP model in neural networks. *Acta Numerica*, 8: 143–195, 1999.

[7] P. Kidger and T. Lyons. Universal Approximation with Deep Narrow Networks. In *Proceedings of the 33rd Conference on Learning Theory*, pages 2306–2327, 2020.

[8] B. Tzen and M. Raginsky. Neural Stochastic Differential Equations: Deep Latent Gaussian Models in the Diffusion Limit. *arXiv:1905.09883*, 2019.

[9] B. Tzen and M. Raginsky. Theoretical guarantees for sampling and inference in generative models with latent diffusions. In *Proceedings of the 32rd Conference on Learning Theory*, pages 3084–3114, 2019.

[10] J. Jia and A. Benson. Neural Jump Stochastic Differential Equations. In *Advances in Neural Information Processing Systems 32*, pages 9847–9858, 2019.

[11] X. Liu, T. Xiao, S. Si, Q. Cao, S. Kumar, and C.-J. Hsieh. Neural SDE: Stabilizing Neural ODE Networks with Stochastic Noise. *arXiv:1906.02355*, 2019.

[12] L. Kong, J. Sun, and C. Zhang. SDE-Net: Equipping Deep Neural Networks with Uncertainty Estimates. In *Proceedings of the 37th International Conference on Machine Learning*, pages 5405–5415, 2020.

[13] L. Hodgkinson, C. van der Heide, F. Roosta, and M. Mahoney. Stochastic Normalizing Flows. *arXiv:2002.09547*, 2020.

[14] P. Gierjatowicz, M. Sabate-Vidales, D. Šiška, L. Szpruch, and Ž. Žurič. Robust Pricing and Hedging via Neural SDEs. *arXiv:2007.04154*, 2020.

[15] X. Li, T.-K. L. Wong, R. T. Q. Chen, and D. Duvenaud. Scalable Gradients and Variational Inference for Stochastic Differential Equations. *AISTATS*, 2020.

[16] P. Kidger, J. Foster, X. Li, H. Oberhauser, and T. Lyons. Neural SDEs as Infinite-Dimensional GANs. In *Proceedings of the 38th International Conference on Machine Learning*, 2021.

[17] C. Holt. Forecasting seasonals and trends by exponentially weighted moving averages. *ONR Research Memorandum, Carnegie Institute of Technology*, 52, 1957.

[18] P. Winters. Forecasting sales by exponentially weighted moving averages. *Management Science*, 6:324–342, 1960.

[19] E. J. Hannan and J. Rissanen. Recursive Estimation of Mixed Autoregressive-Moving Average Order. *Biometrika*, 69:81–94, 1982.

[20] J. Yoon, D. Jarrett, and M. van der Schaar. Time-series Generative Adversarial Networks. In *Advances in Neural Information Processing Systems 32*, 2019.

[21] Y. Rubanova, R. T. Q. Chen, and D. Duvenaud. Latent Ordinary Differential Equations for Irregularly-Sampled Time Series. In *Advances in Neural Information Processing Systems 32*, pages 5320–5330, 2019.

[22] E. De Brouwer, J. Simm, A. Arany, and Y. Moreau. GRU-ODE-Bayes: Continuous Modeling of Sporadically-Observed Time Series. In *Advances in Neural Information Processing Systems 32*, pages 7379–7390, 2019.

[23] C. Yildiz, M. Heinonen, and H. Lahdesmaki. ODE2VAE: Deep generative second order ODEs with Bayesian neural networks. In *Advances in Neural Information Processing Systems 32*, 2019.

[24] R. Deng, B. Chang, M. Brubaker, G. Mori, and A. Lehrmann. Modeling Continuous Stochastic Processes with Dynamic Normalizing Flows. In *Advances in Neural Information Processing Systems 33*, pages 7805–7815, 2020.

[25] A. Norcliffe, C. Bodnar, B. Day, J. Moss, and P. Liò. Neural ODE Processes. In *International Conference on Learning Representations*, 2021.

[26] C. Herrera, F. Krach, and J. Teichmann. Neural Jump Ordinary Differential Equations: Consistent Continuous-Time Prediction and Filtering. In *International Conference on Learning Representations*, 2021.

[27] A. Paszke, S. Gross, F. Massa, A. Lerer, J. Bradbury, G. Chanan, T. Killeen, Z. Lin, N. Gimelshein, L. Antiga, A. Desmaison, A. Kopf, E. Yang, Z. DeVito, M. Raison, A. Tejani, S. Chilamkurthy, B. Steiner, L. Fang, J. Bai, and S. Chintala. PyTorch: An Imperative Style, High-Performance Deep Learning Library. In *Advances in Neural Information Processing Systems 32*, pages 8024–8035, 2019.

[28] J. Behrmann, W. Grathwohl, R. T. Q. Chen, D. Duvenaud, and J.-H. Jacobsen. Invertible Residual Networks. In *Proceedings of the 36th International Conference on Machine Learning*, pages 573–582, 2019.

[29] P. Kidger, J. Foster, X. Li, H. Oberhauser, and T. Lyons. Neural SDEs Made Easy: SDEs are Infinite-Dimensional GANs. *OpenReview*, 2020.

[30] Y. Song, J. Sohl-Dickstein, D. P. Kingma, A. Kumar, S. Ermon, and B. Poole. Score-Based Generative Modeling through Stochastic Differential Equations. In *International Conference on Learning Representations*, 2021.

[31] W. Xu, R. T. Q. Chen, X. Li, and D. Duvenaud. Infinitely Deep Bayesian Neural Networks with Stochastic Differential Equations. *arXiv:2102.06559*, 2021.

[32] J. Zhuang, N. C. Dvornek, S. Tatikonda, and J. S. Duncan. MALI: A memory efficient and reverse accurate integrator for Neural ODEs. In *International Conference on Learning Representations*, 2021.

[33] D. Revuz and M. Yor. *Continuous martingales and Brownian motion*, volume 293. Springer Science & Business Media, 2013.

[34] J. K. Salmon, M. A. Moraes, R. O. Dror, and D. E. Shaw. Parallel random numbers: as easy as 1, 2, 3. *Proc. High Performance Computing, Networking, Storage and Analysis*, pages 1–12, 2011.

[35] K. Claessen and M. Pałka. Splittable pseudorandom number generators using cryptographic hashing. *ACM SIGPLAN Notices*, 48:47–58, 2013.

[36] I. Gulrajani, F. Ahmed, M. Arjovsky, V. Dumoulin, and A. Courville. Improved Training of Wasserstein GANs. In *Advances in Neural Information Processing Systems 30*, pages 5767–5777, 2017.

[37] T. Miyato, T. Kataoka, M. Koyama, and Y. Yoshida. Spectral Normalization for Generative Adversarial Networks. In *International Conference on Learning Representations*, 2018.

[38] R. T. Q. Chen, J. Behrmann, D. Duvenaud, and J.-H. Jacobsen. Residual Flows for Invertible Generative Modeling. In *Advances in Neural Information Processing Systems 32*, 2019.

[39] D. Hendrycks and K. Gimpel. Gaussian Error Linear Units (GELUs). *arXiv:1606.08415*, 2016.

[40] S. Elfwing, E. Uchibe, and K. Doya. Sigmoid-Weighted Linear Units for Neural Network Function Approximation in Reinforcement Learning. *arXiv:1702.03118*, 2017.

[41] P. Ramachandran, B. Zoph, and Q. Le. Swish: a Self-Gated Activation Function. *arXiv:1710.05941*, 2017.

[42] X. Li. torchsde, 2019. https://github.com/google-research/torchsde.

[43] R. T. Q. Chen, Y. Rubanova, J. Bettencourt, and D. Duvenaud. Neural Ordinary Differential Equations. In *Advances in Neural Information Processing Systems 31*, 2018.

[44] M. E. Sander, P. Ablin, M. Blondel, and G. Peyré. Momentum Residual Neural Networks. *arXiv:2102.07870*, 2021.

[45] P. Kidger, J. Morrill, J. Foster, and T. Lyons. Neural Controlled Differential Equations for Irregular Time Series. In *Advances in Neural Information Processing Systems 33*, pages 6696–6707, 2020.

[46] J. Morrill, C. Salvi, P. Kidger, J. Foster, and T. Lyons. Neural Rough Differential Equations for Long Time Series. In *Proceedings of the 38th International Conference on Machine Learning*, 2021.

[47] B. Chang, M. Chen, E. Haber, and E. H. Chi. AntisymmetricRNN: A dynamical system view on recurrent neural networks. *International Conference on Learning Representations*, 2019.

[48] T. Karras, S. Laine, M. Aittala, J. Hellsten, J. Lehtinen, and T. Aila. Analyzing and Improving the Image Quality of StyleGAN. In *Proc. CVPR*, 2020.

[49] P. Kidger. torchtyping, 2021. https://github.com/patrick-kidger/torchtyping.

[50] M. Arjovsky, S. Chintala, and L. Bottou. Wasserstein Generative Adversarial Networks. In *Proceedings of the 34th International Conference on Machine Learning*, pages 214–223, 2017.

[51] M. Giles and P. Glasserman. Smoking adjoints: Fast Monte Carlo greeks. *Risk*, 19:88–92, 2006.

[52] R. S. Hamilton. The inverse function theorem of Nash and Moser. *Bulletin of the American Mathematical Society*, 7(1):65–222, 1982.

[53] P. E. Kloeden and E. Platen. *Numerical Solution of Stochastic Differential Equations*. Springer, 1992.

[54] J. Foster, H. Oberhauser, and T. Lyons. An optimal polynomial approximation of Brownian motion. *SIAM Journal on Numerical Analysis*, 58(3):1393–1421, 2020.

[55] B. Leimkuhler, C. Matthews, and M. V. Tretyakov. On the long-time integration of stochastic gradient systems. *Proceedings of the Royal Society A*, 470(2170), 2014.

[56] L. F. Shampine. Stability of the leapfrog/midpoint method. *Applied Mathematics and Computation*, 208(1):293–298, 2009.

[57] A. Griewank. Achieving logarithmic growth of temporal and spatial complexity in reverse automatic differentiation. *Optimization Methods and Software*, 1(1):35–54, 1992.

[58] J. Gaines and T. Lyons. Variable step size control in the numerical solution of stochastic differential equations. *SIAM Journal on Applied Mathematics*, 57(5):1455–1484, 1997.

[59] A. Rößler. Runge-Kutta Methods for the Strong Approximation of Solutions of Stochastic Differential Equations. *SIAM Journal on Numerical Analysis*, 48(3):922–952, 2010.

[60] A. Dickinson. Optimal Approximation of the Second Iterated Integral of Brownian Motion. *Stochastic Analysis and Applications*, 25(5):1109–1128, 2007.

[61] J. Gaines and T. Lyons. Random Generation of Stochastic Area Integrals. *SIAM Journal on Applied Mathematics*, 54(4):1132–1146, 1994.

[62] A. Davie. KMT theory applied to approximations of SDE. In *Stochastic Analysis and Applications 2014*, pages 185–201. Springer, 2014.

[63] G. Flint and T. Lyons. Pathwise approximation of SDEs by coupling piecewise abelian rough paths. *arXiv:1505.01298*, 2015.

[64] J. Foster. *Numerical approximations for stochastic differential equations*. PhD thesis, University of Oxford, 2020.

[65] M. Wiktorsson. Joint characteristic function and simultaneous simulation of iterated Itô integrals for multiple independent Brownian motions. *Annals of Applied Probability*, 11(2):470–487, 2001.

[66] J. Mrongowius and A. Rößler. On the Approximation and Simulation of Iterated Stochastic Integrals and the Corresponding Lévy Areas in Terms of a Multidimensional Brownian Motion. *arXiv:2101.09542*, 2021.

[67] J. Foster and K. Habermann. Brownian bridge expansions for Lévy area approximations and particular values of the Riemann zeta function. *arXiv:2102.10095*, 2021.

[68] A. Gretton, K. M. Borgwardt, M. J. Rasch, B. Schölkopf, and A. Smola. A Kernel Two-Sample Test. *Journal of Machine Learning Research*, 13(1):723–773, 2013.

[69] F. Király and H. Oberhauser. Kernels for sequentially ordered data. *Journal of Machine Learning Research*, 20(31):1–45, 2019.

[70] C. Toth and H. Oberhauser. Bayesian Learning from Sequential Data using Gaussian Processes with Signature Covariances. In *Proceedings of the 37th International Conference on Machine Learning*, pages 9548–9560, 2020.

[71] P. Bonnier, P. Kidger, I. Perez-Arribas, C. Salvi, and T. Lyons. Deep Signature Transforms. In *Advances in Neural Information Processing Systems 32*, 2019.

[72] C. Salvi, T. Cass, J. Foster, T. Lyons, and W. Yang. The Signature Kernel is the solution of a Goursat PDE. *arXiv:2006.14794*, 2021.

[73] M. Lemercier, C. Salvi, T. Cass, E. V. Bonilla, T. Damoulas, and T. Lyons. SigGPDE: Scaling Sparse Gaussian Processes on Sequential Data. In *Proceedings of the 38th International Conference on Machine Learning*, 2021.

[74] P. Kidger and T. Lyons. Signatory: differentiable computations of the signature and logsignature transforms, on both CPU and GPU. In *International Conference on Learning Representations*, 2021. https://github.com/patrick-kidger/signatory.

[75] J. Morrill, A. Fermanian, P. Kidger, and T. Lyons. A generalised signature method for multivariate time series feature extraction. *arXiv:2006.00873*, 2020.

[76] Y. Li, K. Swersky, and R. Zemel. Generative Moment Matching Networks. In *Proceedings of the 32nd International Conference on Machine Learning*, pages 1718–1727, 2015.

[77] C.-L. Li, W.-C. Chang, Y. Cheng, Y. Yang, and B. Poczos. MMD GAN: Towards Deeper Understanding of Moment Matching Network. In *Advances in Neural Information Processing Systems 30*, pages 2203–2213, 2017.

[78] P. Kidger. torchcde, 2020. https://github.com/patrick-kidger/torchcde.

[79] R. T. Q. Chen. torchdiffeq, 2018. https://github.com/rtqichen/torchdiffeq.

[80] Ax. https://ax.dev.

[81] D. Kingma and J. Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

[82] M. D. Zeiler. ADADELTA: An Adaptive Learning Rate Method. *arXiv:1212.5701*, 2012.

[83] Y. Yazıcı, C.-S. Foo, S. Winkler, K.-H. Yap, G. Piliouras, and V. Chandrasekhar. The Unusual Effectiveness of Averaging in GAN training. In *International Conference on Learning Representations*, 2019.

[84] P. Izmailov, D. Podoprikhin, T. Garipov, D. Vetrov, and A. G. Wilson. Averaging Weights Leads to Wider Optima and Better Generalization. *Conference on Uncertainty in Artificial Intelligence*, 2018.

[85] D. Dua and C. Graff. UCI Machine Learning Repository, 2017. URL http://archive.ics.uci.edu/ml.

[86] S. Zhang, B. Guo, A. Dong, J. He, Z. Xu, and S. X. Chen. Cautionary tales on air-quality improvement in Beijing. *Proceedings of the Royal Society A*, 473(2205), 2017.