Learning Representations that Enable Generalization in Assistive Tasks

Abstract: Recent work in sim2real has successfully enabled robots to act in physical environments by training in simulation with a diverse "population" of environments (i.e. domain randomization). In this work, we focus on enabling generalization in *assistive tasks*: tasks in which the robot is acting to assist a user (e.g. helping someone with motor impairments with bathing or with scratching an itch). Such tasks are particularly interesting relative to prior sim2real successes because the environment now contains a *human who is also acting*. This complicates the problem because the diversity of human users (instead of merely physical environment parameters) is more difficult to capture in a population, thus increasing the likelihood of encountering out-of-distribution (OOD) human policies at test time. We advocate that generalization to such OOD policies benefits from (1) learning a good latent representation for human policies that test-time humans can accurately be mapped to, and (2) making that representation adaptable with test-time interaction data, instead of relying on it to perfectly capture the space of human policies based on the simulated population only. We study how to best learn such a representation by evaluating on purposefully constructed OOD test policies. We find that sim2real methods that encode environment (or population) parameters and work well in tasks that robots do in isolation, do not work well in *assistance*. In assistance, it seems crucial to train the representation based on the *history of interaction* directly, because that is what the robot will have access to at test time. Further, training these representations to then *predict human actions* not only gives them better structure, but also enables them to be fine-tuned at test-time, when the robot observes the partner act.

Keywords: assistive robots, representation learning, OOD generalization

1 Introduction

Our ultimate goal is to enable robots to assist people with day to day tasks. In the context of patients with motor impairments, this might mean assistance with scratching an itch, bathing, or dressing [1, 2, 3]. These are tasks in which doing reinforcement learning from scratch in the real world is not feasible, and so sim2real transfer is an appealing avenue of research. Sim2real methods for physical robot tasks in isolation typically work by constructing a diverse "population" of environments and training policies that can work with any member of the population (e.g. a range of parameters of a physics simulator or a range of lighting and textures) [4, 5, 6, 7, 8, 9, 10, 11].

Similarly, population-based (self-play) training has proven successful in zero-sum games against humans [12, 13, 14]. But unlike tasks the robot does in isolation, assistance requires coordinating with a human who is also acting. And unlike competitive settings, assuming the human to be optimal when they are not can result in dramatically poor performance [15]. Thus, in sim2real for assistance, we have to design a population of potential users and strategies to train with, akin to the physical environment parameters in typical sim2real tasks, rather than the standard population-based training

approaches used in competitive settings. But designing a population that is diverse and useful enough to enable generalization to test-time humans, each with their own preferences, strategies, and capabilities, remains very challenging, making it likely that test-time partners might lie outside of the distribution the population was drawn from. Therefore, sim2real methods for assistance will need to be ready to *generalize* to *out-of-distribution* partner policies.

In this work, we identify two principles as key to enabling better generalization. First is that we benefit from learning a latent space of partners that distills their policies down to a structure that is useful for the robot's policy *and* that makes it easy to identify partners at test time. Second is that we need to be prepared for this space to not perfectly capture the space of real human policies, and design it so that it is *adaptable* with real test-time interaction data.

We thus propose a framework that *learns a latent space directly from history of interaction by predicting the partner's actions*. Our framework allows a robot to capture the relevant information about the human partner that the robot can actually identify when starting to interact, and also enables test-time adaptation of the latent space itself when observing the partner's actions. When evaluated with partner policies we purposefully design to be out-of-distribution, we find that our approach leads to better generalization than prior methods which either do not learn a latent space at all [16], do not learn a latent space directly based on interaction history [7], or train a latent space based on other observables, like states or rewards [17, 18].

Our contributions are four-fold:

1. We introduce an assistive problem setting where the focus is explicitly on generalization to out-of-distribution partner policies.
2. We introduce a framework for training policies for this problem setting, Prediction-based Assistive Latent eMbedding (PALM). This enables us to study different methods for learning latent representations on how well they enable generalization.
3. We identify that the design choice of training a latent space by *predicting partner actions directly from history* outperforms (1) state-of-the-art sim2real approaches used in non-assistive tasks that are based on embedding environment parameters [7]; as well as (2) human-robot interaction approaches that train representations by predicting observed states or rewards [17, 18].
4. We propose to adapt the learned space at test time, upon observing the partner's actions, and show it leads to generalization performance gains.

2 The Assistive Personalization Problem

In this section, we introduce the personalization problem in an assistive context. In particular, our goal is to learn a robot policy π_R that can quickly adapt to and assist a novel human partner.

Two-player Dec-POMDP. An assistive task can be modeled as a two-agent, finite horizon decentralized partially-observable Markov decision process (Dec-POMDP) and is defined by a tuple $\langle S, \alpha, A_R, A_H, \mathcal{T}, \Omega_R, \Omega_H, O, R \rangle$. Here S is the state space and A_R, A_H are the human's and the robot's action spaces, respectively. The human and the robot share a real-valued reward function $R : S \times A_R \times A_H \to \mathbb{R}$; however, we assume that the reward function is not necessarily observed by the robot, i.e. its parameters (e.g. the location of the human has an itch) are in the hidden part of the state. $\mathcal{T} : S \times A_R \times A_H \times S \to [0, 1]$ is the transition function, which outputs the probability of the next state given the current state and all agents' actions. Ω_R and Ω_H are the sets of observations for the robot and human, respectively, and $O : S \times A_R \times A_H \to \Omega_R \times \Omega_H$ represents the observation probabilities. We denote the horizon of the MDP by T.

Observation Space and Hidden Information. We define the observation space for the robot and the human following [3]: the robot observes its own joint angles, and the human's joint positions in the world coordinate; the human observes her joint angles (proprioception) and the end-effector position of the robot. Crucially, we model the environment to hide the human characteristic information away from the robot, like the location of their itch, their capability, desired strategy, personal preferences, etc. Thus, when training with simulated humans, the robot gets a reward signal (which depends on

Figure 1: The framework for jointly learning the Personalized Latent Embedding Space and the robot policy. During training time, we train all components end-to-end to optimize the prediction loss and the policy loss. At test time, we execute the robot policy, which is highlighted in green.

privileged information), and has to use that signal to learn to implicitly identify enough about the human to be useful; at test time, the robot does not observe reward signal and must use what it has learned at training time to identify the human's privileged information and be helpful.

Distributions of Humans. Let function $\pi_H : \Omega_H^* \times A_H \to [0,1]$ be the human policy that maps from local histories of observations $\mathbf{o}^H = (o_1^H, \ldots, o_t^H)$ over Ω_H to actions. We define two distributions of human policies $\pi_H \in \mathscr{D}_{\text{train}}, \mathscr{D}_{\text{test}}$. In the assistive itch scratching, $\mathscr{D}_{\text{train}}$ can be a set of humans with different itch positions on their arms, which lead to their different movements. We refer to them as *in-distribution humans*. $\mathscr{D}_{\text{test}}$ contains *out-of-distribution* humans whose itch position differ from those in the $\mathscr{D}_{\text{train}}$. At training time, the robot has access to $\mathscr{D}_{\text{train}}$. Thus, it has ground-truth knowledge about the training human's privileged information, such as each human's itch position. At test time, we evaluate the robot policy by sampling humans $\pi_H \sim \mathscr{D}_{\text{test}}$ and directly pairing them with the robot policy. We evaluate the zero-shot and few-shot adaptation performance of the robot policy.

Objective. The main problem we study is how to leverage the training distribution to learn a robot policy $\pi_R : \Omega_R^* \to A_R$ such that we achieve the best performance on test humans. Concretely, we define the performance of the robot and human as

$$J(\pi_R, \pi_H) = \mathbb{E}\left[\sum_{t=0}^{T} R(s_t, \pi_R(\mathbf{o}_t^R), \pi_H(\mathbf{o}_t^H))\right], \tag{1}$$

Thus, only given access to $\mathscr{D}_{\text{train}}$, our objective is to find the robot policy π_R such that

$$\pi_R = \arg\max_{\pi} J(\pi, \pi_H), \pi_H \sim \mathscr{D}_{\text{test}}. \tag{2}$$

3 Learning Personalized Embeddings for Assistance with PALM

In this section, we present Prediction-based Assistive Latent eMbedding (PALM). We introduce the general framework of using a latent space to perform personalization in an assistive context. Finally, we describe how we can optimize PALM at test time to handle out-of-distribution humans.

3.1 Learning an Assistive Latent Space

Given a training distribution of humans $\mathscr{D}_{\text{train}}$, we would like to learn a robot policy that can successfully adapt to assist new users. To achieve that, a robot must learn to solve the task, while efficiently inferring the hidden component that differs across humans. One natural way to do so is to use a *learned latent space* that succinctly captures what differs across humans in a way that affects the robot's policy. When deployed on a test human, the robot must learn to infer this latent embedding. How do we learn such a latent space? We assume access to a population of training humans sampled from $\mathscr{D}_{\text{train}}$. We describe how we generate this distribution in Sec. 4.1.

Learning by prediction. We outline our method in Fig. 1. Given a history, $\tau_{1:t} = \left((o_1^R, a_1^H), \ldots (o_t^R, a_t^H)\right)$, of robot observation and human action[1] pairs up to time t, we embed

---

[1] We do not assume access to the person's raw action (e.g. joint torques), but track the change in the person's Cartesian pose.

this trajectory to a low-dimensional manifold. The goal is to extract information about the human policy π_H. Achieving this means that the vector z is representative of the trajectory so far and indicative of the person's future actions. In other words, we can use z to predict the person's action at $t+1$. We do this by training a decoder $\mathcal{D}_\phi$ parameterized by ϕ to predict the next action from the encoder's output $z \sim \mathcal{E}_\theta(z; \tau_{1:t})$.

$$\mathcal{L}_{\text{pred}} = \min_{\theta, \phi} ||\mathcal{D}_\phi(z) - a_{t+1}^H||^2 + c_{\text{KL}} \cdot KL(\mathcal{E}_\theta(z; \tau_{1:t})||\mathcal{N}(z)) \tag{3}$$

The encoder $\mathcal{E}$ is a recurrent neural network as an encoder parameterized by θ. Here the second term is a regularization term motivated by Variational Autoencoder [19, 20], that enforces the latent space to follow a normal distribution. This encourages nearby terms in the latent space to follow similar semantic meanings. In the context of assistive tasks, this helps us better cluster similar humans closer in the latent space, and we show a didactic example in Sec. 4.3.

Other forms of Prediction-based Human Embeddings Besides predicting actions, LILI [17] and RILI [18] are two prior methods that fit within the PALM framework and that learn to predict the next observations and rewards. These methods have been shown to work when the human is operating under a discrete number of dynamics and can be used for influencing human behaviours. Note, however, that both LILI and RILI assume access to the reward function at test time, and in the assistive setting, we do not have access to humans reward function — we don't know a-priori the preference and needs of a new user.

End-to-end training of latent space We apply standard policy optimization methods to learn π_R. Note that because base policy π_R and the latent space z are interdependent on each other — z is the input to π_R, and π_R decides the data distribution which leads to z, we need to train them jointly. We follow prior work [17, 18] and jointly learning the latent space and the robot policy by using the PPO [21] algorithm. In addition to the prediction loss $\mathcal{L}_{\text{pred}}$, we can optimize for the policy loss $\mathcal{L}_{\text{pol}}$ simultaneously. Because training with a population of humans with hidden information can be unstable, we also leverage Behaviour Cloning to stabilize our policy training. Expert policies can be separately trained, or obtained via co-optimization with the human population, which we describe in the appendix. We then use a standard behavioral cloning loss to minimize deviation from expert policies: $\mathcal{L}_{\text{BC}} = \sum_t ||a_t^{\text{exp}} - a_t^R||^2$. The overall policy optimization loss include three terms: latent prediction loss, PPO loss and the Behaviour Cloning loss:

$$\mathcal{L}_{\text{PALM}} = \mathcal{L}_{\text{pred}} + \mathcal{L}_{\text{PPO}} + \mathcal{L}_{\text{BC}} \tag{4}$$

3.2 Latent Space Adaptation at Test Time

At test time, as we work with a new user, we would like our encoding of the new user to match the true latent information, z^* of that user. In other words, we would like to minimize $||\mathcal{E}(\tau) - z^*||^2$. Because we do not know about the new users a-priori, we can only optimize for this objective via proxy, which we refer to as *test time adaptation*.

Because the PALM latent space is based on action prediction, we can adapt it to a new user by further optimizing the latent space. Note that because Eq. (3) requires only observation-action data, we do not need any additional label to perform test time adaptation. More formally, we collect a small dataset of test-time interaction trajectories, τ, and perform a few gradient steps to optimize for Eq. (3): $\theta \rightarrow \theta - \delta \nabla_\theta \mathcal{L}_{\text{pred}}(\mathcal{E}_\theta, \tau)$.

The idea of test-time optimization has been shown to improve perceptual robustness for grasping in sim2real research [22]. We follow a similar pipeline, where we can improve the latent encoding by collecting unsupervised action data from test users. Here the main difference is instead of perceptual differences, our goal is to reduce the domain gap on test users.

4 Experiments

In this section, we evaluate our method PALM (Prediction-based Assistive Latent eMbedding) in collaborative human-robot environments of varying tasks and varying populations of human models.

In particular, we focus on the out-of-distribution generalization by constructing different forms of out-of-distribution populations. We focus on empirically investigating the benefits of learning a latent space, the effect of different kinds of prediction on learning a useful latent space, the properties of learned latent spaces, and the gains from test-time adaptation to humans.

4.1 Environments

Here we introduce two environments where we study assistive personalization. In both environments, the robot has to infer some hidden information from the human in order to successfully solve the task.

Figure 2: Visualization of the assistive reacher environment.

Assistive Reacher (Fig. 2) is 2D collaborative environment where a two-link robot arm assisting a human agent, represented as a point particle, to get to the target position. This target is located at $(d\cos\alpha_H, d\sin\alpha_H)$, where d is a fixed value, and $\alpha_H \in [-\pi, \pi]$ is known to the human, but not the robot. The human agent is initialized randomly in the 2D plane with random hidden parameters α_H, k_H. The robot can only identify the target position by physically interacting with the human — once the robot initiates contact, the human applies a force $k_H \cdot (\cos\alpha_H + \frac{\pi}{2}, \sin\alpha_H + \frac{\pi}{2})$. Only by recognizing the human in terms of α_H, k_H can the robot compensate the force, and successfully move the human to the hidden target. We define $\mathscr{D}_{\text{train}}$ as 36 samples from $\alpha_H \in [-\pi, \frac{\pi}{2}], k_H \in [0.5, 1.5]$ and $\mathscr{D}_{\text{test}}$ as 12 samples from $\alpha_H \in [\frac{\pi}{2}, \pi], k_H \in [0.5, 1.5]$.

Assistive Itch Scratching (Fig. 1) is adapted from assistive gym [3]. It consists of a human and a wheelchair-mounted 7-dof Jaco robot arm. The human can move the 10 joints on her right arm and upper chest, and needs to collaborate with the robot to scratch the itch spot, which is randomly generated on her right arm. We modify the original environment such that the robot does not directly observe the itch spot, and has to rely on interaction with the human to infer the itch spot.

We use co-optimization to create $\mathscr{D}_{\text{train}}$ and $\mathscr{D}_{\text{test}}$ for Assistive Itch Scratching. A benefit of the co-optimization framework is that it naturally induces reward-seek behaviour from the human and the robot, which simulates assistance scenarios. For instance, to generate more inactive human policies, we can introduce a weighting term in the reward function for human action penalties $R_p = c_p \cdot ||\pi_H(s_t)||^2$ where c_p is a constant controlling the penalty. The overall objective becomes

$$\max_{\pi_H, \pi_R} \mathbb{E}\Big[\sum_t R\big(s_t, \pi_H(s_t), \pi_R(s_t)\big)\Big] + c_p \cdot ||\pi_H(s_t)||^2 \tag{5}$$

To generate diverse population in itch scratching task, we explore two sources of diversities: (1) we assign different human action penalty to be $c_p = 3, 3.5, 4$, where larger penalties lead to the human agent exerting less effort. (2) We simulate different itch positions on the human's arm and train co-optimized human and robot policies conditioned on them. This leads to qualitatively different strategies for the human and the robot. Note that this serves first step to understanding how different methods generalize, since we never expect to be able to capture the diversity in humans perfectly. For training, we use Proximal Policy Optimization (PPO) to optimize human and robot policies in an interleaving fashion. Note that we also keep the co-optimized robot policy and use it to obtain expert actions for assistive policy training (see Sec. 3.1 and supplement for full details).

To construct $\mathscr{D}_{\text{train}}$ and $\mathscr{D}_{\text{test}}$, we divide the two arms' areas into four equal portions, as shown in Fig. 5, and generate human policies conditioned on itch positions in these areas. $\mathscr{D}_{\text{train}}$ consists of three of the four portions and $\mathscr{D}_{\text{test}}$ consists of the remaining one. We then construct three distribution sets in increasing order of difficulties. In the first distribution $\mathscr{D}^1$, we confine itch positions from a line-shaped region. In $\mathscr{D}^2$, we sample from all the arm areas. Note that $\mathscr{D}^1$ and $\mathscr{D}^2$ are constructed by setting action penalty $c_p = 3$. In $\mathscr{D}^3$, we combine humans of $c_p = 3, 3.5, 4$, each trained with two different random seeds. This adds the extra complexity of human activity levels. We simulate 12

210 in-distribution humans from each of the three training portions under each action penalty. We denote
211 the size of $\mathscr{D}_{\text{train}}$ and $\mathscr{D}_{\text{test}}$ under each set in Fig. 5.

4.2 Baselines

213 We compare with baselines that do not learn an explicit latent space as well as existing methods for
214 adaptation via learning latent embeddings.

215 **MLP and RNN.** We follow [16] that trains sequential models to enable adaptation to simulated
216 humans. We explore using a recurrent neural network or a feed-forward network on concatenated
217 state-action histories. The models directly output robot action, and there is no latent space modeling.

218 **ID-based Human Embeddings.** In contrast to learning latent space from history, another class of
219 method studies encodes human-designed environment parameters [7, 23, 24]. We focus specifically on
220 RMA [7], a two-phased method that first learns to encode task-ID (phase I) and then trains a recurrent
221 network to regress to the embeddings from observation history (phase II). For training a quadruped
222 robot, RMA encodes the physical parameters (friction, payload, etc) of the environment. The first
223 stage trains a policy with ground-truth information, and the second phase performs environment
224 identification. While RMA is shown to be effective for learning policy for in-distribution environments,
225 it is unclear how well it generalizes to out-of-distribution environments. Furthermore, in assistive tasks,
226 it is unclear how to construct the "ground-truth ID" for phase I that quantifies the user characteristics.
227 We study **RMA-Vanilla** and **RMA-Onehot**, where we assign each training human a one-hot vector.
228 For RMA-Vanilla, we use a three-dimensional vector that includes the x, y position of the itch position
229 and the arm index. When there are multiple human activity levels as mentioned in Sec. 4.1, we
230 introduce a fourth dimension with an integer to indicate the action penalty c_{p}.

231 **LILI and RILI.** We consider two other methods of the
232 PALM framework: LILI [17] and RILI [18]. As mentioned
233 in Sec. 3.1, LILI jointly predicts future observation and
234 reward, and RILI predicts reward. Given that reward is
235 only available at training time, we cannot perform test time
236 optimization for LILI and RILI.

$c_{kl} = 0.01$ $c_{kl} = 0.1$

$c_{kl} = 1.0$ $c_{kl} = 3.0$

237 **Ablations of PALM.** Our method has several components:
238 we use a recurrent neural network to encode interaction
239 history, and use its output to minimize prediction loss $\mathcal{L}_{\text{pred}}$
240 and policy loss $\mathcal{L}_{\text{pol}}$. We also use the KL term in Eq. (3) to
241 regularize the human embeddings. To test the effectiveness
242 of our method, we separate different parts and create a
243 set of baselines. We hereby describe them in detail: (1)
244 No $\mathcal{L}_{\text{pred}}$: the model shares the same encoder and policy
245 network architecture, yet we don't optimize for $\mathcal{L}_{\text{pred}}$. By
246 removing the prediction loss in Fig. 1, the latent space is
247 not explicitly trained to contain human information. (2)

Figure 3: Latent space of PALM in the assistive reacher environment when we can sample humans $\alpha_{\text{H}} \in [-\pi \text{ (red)}, \pi \text{ (blue)}]$ continuously.

248 No c_{KL}: no regularization in the latent space. (3) Frozen embedding: instead of jointly training
249 embeddings and the policy network, we first train the encoder on expert data, freeze it, and then train
250 robot policy. We include an ablation study of our main experiments in the appendix.

4.3 Didactic Experiment in Assistive Reacher Environment

252 **Can PALM learn a meaningful distribution from the interaction?** Unlike other ID-based methods
253 like RMA, PALM does not have access to the human parameters at training time. We study whether
254 PALM can learn a meaningful latent space without explicitly knowing this information. We sample
255 training humans from $\alpha_{\text{H}} \in [-\pi, \pi]$ continuously. We train PALM with different amount of prior
256 regularization, c_{KL} from Eq. (3). We train using a recurrent window of length 4 and a batch size of
257 512 episodes. Additional training details can be found in the supplementary material.

Figure 4: Top left: evaluation of PALM and baselines on in-distribution (green) and out-of-distribution (pink) humans. Right and bottom: visualization of the latent embeddings of different methods. OOD humans are highlighted in red crosses. Best viewed electronically.

We then visualize the results in Fig. 4.3. Given that humans are parameterized by α_H, K_H, the ideal embedding space looks like a ring with a small blob in the center. The ring corresponds to the 2D projection of α_H and the blob denotes the initial part of interaction before contact, which is indistinguishable. We find that while PALM never observes the underlying parameter α_H, it can learn a latent space that characterizes α_H. Interestingly, varying the amount of regularization qualitatively affects the shape of the latent space. Setting the VAE regularization $c_{KL} = 0.1$ recovers a latent space that most resembles to the ideal latent space.

4.4 Assistive Reacher Main Experiment

Experiment Setting. We use the finite $\mathcal{D}_{\text{train}}$ described in Sec. 4.1 and train all baselines using Eq. (4) for 200 epochs with 512 batch size. We then evaluate the trained policies on $\mathcal{D}_{\text{test}}$. We normalize the resulting reward with respect to oracle reward.

Results. On in-distribution humans, we find that all methods successfully follow the right policy that assists the human to reach their goal. This shows that they all successfully predict the human latent information explicitly or implicitly. On out-of-distribution humans, the methods are no longer guaranteed to predict the correct embedding. PALM with action prediction significantly outperforms other methods. With test-time adaptation, PALM further improves.

Visualizing the latent space. We qualitatively study generalization by visualizing the latent space as well as the mapped embeddings of both in-distribution and out-of-distribution humans (in red crosses) in Fig. 4. Interestingly, only PALM with action prediction can infer the "ring" structure. RMA, RNN, LILI and RILI fail to do so. We hypothesize that because hand-crafted human IDs do not convey the information about human policy, RMA warped the IDs in arbitrary what that are harmful for generalization. The same happens with RILI and LILI. We hypothesize this is due to the inherent ambiguity in reward prediction: a low reward does not necessarily recover the human policy structure.

The visualization also offers some insight into why having c_{KL} regularization is helpful for generalization. Compare the latent space of PALM $c_{KL} = 0$ and PALM $c_{KL} = 0.1$, the latter induces a smoother distribution where test humans are better fitting in the "missing arc" of the "ring". Further more, we see that with test time optimization, the PALM latent space embeds the OOD human better, by filling in more of the arc.

4.5 Assistive Itch Scratch Main Experiment

Results. We follow a similar procedure as the reach environment to train itch scratching policy, and train for 240 epochs with 192 trajectories for batch size. As shown in Fig. 5, we observe PALM with action prediction has better generalization performance than other baselines. We see that in the

Figure 5: In assistive itch scratching, we sample humans by different itch positions and activity levels (varying action penalty c_p). We visualize the in- and out-of-distribution humans on the two-link arm figures. We also visualize the embedding space of PALM and RMA, where we color-code the embeddings of in-distribution humans. Here we leave the embeddings of other baselines to supplementary material.

simplified distribution $\mathscr{D}^1$, RILI and MLP have the best generalization performance among baselines, yet as the complexity of the training human distribution increases, they deteriorate. Detailed results of the ablation study are included in the appendix.

Visualizing the Latent Space We visualize the latent space of the "straight-line" distribution and provide visualization for the other two distributions in the supplementary material. As we see in Fig. 6, PALM can capture the line-like structure in these two clusters of humans, and also correctly position humans outside of the training distribution. RMA-based methods, on the other hand, can discover the structure of training humans. Yet they fail the correctly embed the humans out of distribution.

Figure 6: We visualize the embeddings of the OOD humans of $\mathscr{D}^2$ in red dots.

4.6 Limitations and Failure Cases

Although PALM achieves good average-case performance, it works best with humans sampled near the training distribution. If we pair the robot with an adversarial human, PALM is likely to fail as it lacks a fall-back safety policy.

The major limitation of PALM is the requirement of generating a human population. While we provide one way to generate human populations based on weighted human-robot co-optimization, we lack ways to systematically generate diverse and realistic human motions. One important direction for future work is to incorporate real user data to create training populations. Improving the realism of the training human population is likely a crucial step to supporting transfer to real partners.

5 Conclusion

Generalization is an important task for assistive robotics, and in this paper, we formulate a problem setting that focuses on Out-Of-Distribution users. To that end, we contribute a framework PALM for learning a robot policy that can quickly adapt to new partners at test time. PALM assumes a distribution of training humans and constructs an embedding space for them by learning to predict partner actions. We can further adapt this embedding at test time for new partners. Experiments show that PALM outperforms state-of-the-art approaches. We are excited by the potential of using PALM to enable robotic assistance in the future.

References

[1] D. P. Miller. Assistive robotics: an overview. *Assistive technology and artificial intelligence*, pages 126–136, 1998.

[2] S. W. Brose, D. J. Weber, B. A. Salatin, G. G. Grindle, H. Wang, J. J. Vazquez, and R. A. Cooper. The role of assistive robotics in the lives of persons with disability. *American Journal of Physical Medicine & Rehabilitation*, 89(6):509–521, 2010.

[3] Z. Erickson, V. Gangaram, A. Kapusta, C. K. Liu, and C. C. Kemp. Assistive gym: A physics simulation framework for assistive robotics. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pages 10169–10176. IEEE, 2020.

[4] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel. Domain randomization for transferring deep neural networks from simulation to the real world. In *2017 IEEE/RSJ international conference on intelligent robots and systems (IROS)*, pages 23–30. IEEE, 2017.

[5] J. Tan, T. Zhang, E. Coumans, A. Iscen, Y. Bai, D. Hafner, S. Bohez, and V. Vanhoucke. Sim-to-real: Learning agile locomotion for quadruped robots. *arXiv preprint arXiv:1804.10332*, 2018.

[6] W. Yu, V. C. Kumar, G. Turk, and C. K. Liu. Sim-to-real transfer for biped locomotion. In *2019 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pages 3503–3510. IEEE, 2019.

[7] A. Kumar, Z. Fu, D. Pathak, and J. Malik. Rma: Rapid motor adaptation for legged robots. *arXiv preprint arXiv:2107.04034*, 2021.

[8] J. Mahler, J. Liang, S. Niyaz, M. Laskey, R. Doan, X. Liu, J. A. Ojea, and K. Goldberg. Dex-net 2.0: Deep learning to plan robust grasps with synthetic point clouds and analytic grasp metrics. *arXiv preprint arXiv:1703.09312*, 2017.

[9] Y. Wu, W. Yan, T. Kurutach, L. Pinto, and P. Abbeel. Learning to manipulate deformable objects without demonstrations. *arXiv preprint arXiv:1910.13439*, 2019.

[10] D. Seita, A. Ganapathi, R. Hoque, M. Hwang, E. Cen, A. K. Tanwani, A. Balakrishna, B. Thananjeyan, J. Ichnowski, N. Jamali, K. Yamane, S. Iba, J. Canny, and K. Goldberg. Deep Imitation Learning of Sequential Fabric Smoothing From an Algorithmic Supervisor. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2020.

[11] J. Hietala, D. Blanco-Mulero, G. Alcan, and V. Kyrki. Closing the sim2real gap in dynamic cloth manipulation. *arXiv preprint arXiv:2109.04771*, 2021.

[12] D. Silver, T. Hubert, J. Schrittwieser, I. Antonoglou, M. Lai, A. Guez, M. Lanctot, L. Sifre, D. Kumaran, T. Graepel, et al. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

[13] D. Balduzzi, M. Garnelo, Y. Bachrach, W. Czarnecki, J. Perolat, M. Jaderberg, and T. Graepel. Open-ended learning in symmetric zero-sum games. In *International Conference on Machine Learning*, pages 434–443. PMLR, 2019.

[14] M. Jaderberg, W. M. Czarnecki, I. Dunning, L. Marris, G. Lever, A. G. Castaneda, C. Beattie, N. C. Rabinowitz, A. S. Morcos, A. Ruderman, et al. Human-level performance in 3d multiplayer games with population-based reinforcement learning. *Science*, 364(6443):859–865, 2019.

[15] M. Carroll, R. Shah, M. K. Ho, T. Griffiths, S. Seshia, P. Abbeel, and A. Dragan. On the utility of learning about humans for human-ai coordination. *Advances in neural information processing systems*, 32, 2019.

[16] D. Strouse, K. McKee, M. Botvinick, E. Hughes, and R. Everett. Collaborating with humans without human data. *Advances in Neural Information Processing Systems*, 34, 2021.

[17] A. Xie, D. P. Losey, R. Tolsma, C. Finn, and D. Sadigh. Learning latent representations to influence multi-agent interaction. *arXiv preprint arXiv:2011.06619*, 2020.

[18] S. Parekh, S. Habibian, and D. P. Losey. Rili: Robustly influencing latent intent. *arXiv preprint arXiv:2203.12705*, 2022.

[19] D. P. Kingma and M. Welling. Auto-encoding variational bayes, 2013. URL https://arxiv.org/abs/1312.6114.

[20] M. Watter, J. T. Springenberg, J. Boedecker, and M. A. Riedmiller. Embed to control: A locally linear latent dynamics model for control from raw images. *CoRR*, abs/1506.07365, 2015. URL http://arxiv.org/abs/1506.07365.

[21] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov. Proximal policy optimization algorithms. *arXiv preprint arXiv:1707.06347*, 2017.

[22] T. Yoneda, G. Yang, M. R. Walter, and B. C. Stadie. Invariance through latent alignment. *CoRR*, abs/2112.08526, 2021. URL https://arxiv.org/abs/2112.08526.

[23] E. Z. Liu, A. Raghunathan, P. Liang, and C. Finn. Decoupling exploration and exploitation for meta-reinforcement learning without sacrifices. In *International Conference on Machine Learning*, pages 6925–6935. PMLR, 2021.

[24] D. Kalashnikov, J. Varley, Y. Chebotar, B. Swanson, R. Jonschkowski, C. Finn, S. Levine, and K. Hausman. Mt-opt: Continuous multi-task robotic reinforcement learning at scale. *CoRR*, abs/2104.08212, 2021. URL https://arxiv.org/abs/2104.08212.