Cortical Transformers: Robustness and Model Compression with Multi-Scale Connectivity Properties of the Neocortex.

Abstract

Transformer architectures in deep learning are increasingly relied on across domains with impressive results, but the observed growth of model parameters may be unsustainable and failures in robustness limit application. Tasks that are targeted across domains by transformers are enabled in biology by the mammalian neocortex, yet there is no clear understanding of the relationship between processing in the neocortex and the transformer architecture. While the relationship between convolutional neural networks (CNNs) and the cortex has been studied, transformers have more complex computations and multi-scale organization, offering a richer foundation for analysis and co-inspiration. We introduce a framework for enabling details of cortical connectivity at multiple organizational scales (micro-, meso-, and macro-) to be related to transformer processing, and investigate how cortical connectivity principles affect performance, using the CIFAR-10-C computer vision robustness benchmark task. Overall, we demonstrate the efficacy of our framework and find that incorporating components of cortical connectivity at multiple scales can reduce learnable attention parameters by over an order of magnitude, while being more robust against the most challenging examples in computer vision tasks. The cortical transformer framework and design changes we investigate are generalizable across domains, may inform the development of more efficient/robust attention-based systems, and further an understanding of the relationship between cortical and transformer processing.

1 Introduction

Transformers (30) have enabled many recent successes, especially in computer vision (8; 20), but open challenges remain for increasing robustness and reducing model size (15). Tasks across domains typically targeted by transformers are enabled by the mammalian neocortex (24), which achieves efficient processing and real-world robustness. While some connections between transformer networks and principles of processing in biological networks have been made (31; 27), it is unknown how to leverage neocortical properties more explicitly into transformer networks. Relative to convolutional neural networks (CNNs) which have been studied (19; 17; 18), transformer networks offer many potential advantages in regards to connections to cortical processing yet remain under-explored. In particular, transformers 1) have a more complex multi-scale organization, with attention being calculated at the smallest scale as in the cortical microcircuit 2) enable the seamless incorporation of recurrence and feedback within and across levels of processing, and 3) naturally support multi-modal

Submitted to 4th Workshop on Shared Visual Representations in Human and Machine Visual Intelligence (SVRHM) at NeurIPS 2022. Do not distribute.

Figure 1: Incorporating multi-scale connectivity properties of the cortex. A. Macro-scale: 1) recurrent processing between cortical blocks, 2) sparsity, between-block connections have exponentially increasing levels of sparsity, 3) token-interactions (twisted arrows), learnable parameters are introduced for how tokens can interact to break the fixed spatial correspondence through subsequent layers. Meso-scale: model embeddings are parallelized between attention heads, with partial overlap based on a 2D structure. Micro-scale: attention-embeddings (A) are based on inhibitory (I) neurons with reduced population size and denser connections (dimensionality-reduction), while forward-embeddings (blue) are based on excitatory (E) neurons (sparser connectivity). B. Recursive processing of the model's latent space z_t (R regions, N tokens, D dimensionality per region), can support feedforward region connectivity (top), or support more complex region-to-region connectivity (bottom). Note: Macro-/Micro-Cortical Processing figure components adapted from (16) and (29) respectively.

33 processing. Additionally, while CNNs embody explicit inductive biases based on observed hierarchi-
34 cal properties of cortical neural responses, attention-based networks implicitly instantiate, replace,
35 and/or expand on these biases (5; 25; 14).

36 To investigate details of cortical processing for transformer networks, we focus across macro-, meso-,
37 and micro-scales. At the **macro-scale**, we make the comparison between cortical areas and successive
38 layers in a transformer network, extending the correspondences between areas and layers utilized
39 in CNN models of cortical processing (33; 19; 17). In this work, we focus on three macro-scale
40 connectivity principles: 1) *recurrence*: Standard transformer networks use purely feedforward layers,
41 which is starkly different than the recurrent and feedback processing that is observed between cortical
42 areas (16); 2) *sparsity*: Cortico-cortico connections between areas at varying hierarchical levels
43 become exponentially more sparse as distance between areas increases (22); 3) *token-interactions*:
44 Unlike the cortex where visual receptive fields vary considerably in size between areas (26), standard
45 transformer networks in vision (8) rely on a fixed set of patch-wise feature tokens with specific spatial
46 correspondences which are preserved throughout subsequent layers of processing.

47 At the **micro-scale**, we relate cortical micro-circuity properties (11) of excitatory neurons (which have
48 longer-range output connectivity) and inhibitory (29) neurons (which have shorter-range connectivity)
49 to the transformer attention head calculation. The computational role of inhibitory neurons can be
50 complex, especially in the case where inhibitory neurons, that synapse onto dendritic regions (e.g.,
51 Sst neurons), non-linearly and multiplicatively interact with patterns of excitatory input (28). In
52 the transformer's attention head, the attention-embeddings (Q, K) utilize non-linear, multiplicative
53 interactions whereas forward-embeddings (V) propagate only to downstream layers. We inform the
54 structure of these calculations with inhibitory and excitatory neuron population properties respectively.
55 In this work, we focus on two micro-scale connectivity principles: 1) dimensionality-reduction, where
56 excitatory neurons outnumber inhibitory neurons; 2) sparsity, where excitatory-excitatory connections
57 have greater sparsity than inhibitory-excitatory connections (10)).

58 Between the micro-/macro-scales lies a **meso-scale**, where neurons lie in the same area of the cortical
59 sheet, but still exhibit distance-dependent connectivity (22), which we implement by imposing a 2D
60 partially overlapping input to each attention head.

61 For experiments, while transformers have already shown impressive performance on standard vision
62 benchmarks (8; 32; 3), we consider dimensions of performance where biological vision is still domi-
63 nant. We examine the challenge of non-adversarial robustness where transformers have demonstrated
64 improvements over CNNs (2; 23) yet the robustness problem remains far from solved (9).

In this work, we first introduce the Cortical Transformer architecture which incorporates several multi-scale cortical connectivity properties across macro-, meso-, and micro-scales. In a series of computational experiments using the CIFAR-10-C (13) corruption benchmark, we demonstrate the efficacy of our model and investigate how these cortical properties affect robustness and model compression. We find that incorporating the investigated cortical properties improves performance on the most difficult image corruptions for baseline transformer networks while reducing model size.

2   Methods

To study the properties of cortical connectivity, we introduce a series of generalizations of the transformer networks across macro, micro, and meso scales which comprise a single Cortical Block. Stacking these Cortical Blocks depth-wise, produces our Cortical Transformer (CT).

Macro   At the macro-level, we introduce a recurrence-enabled generalization of the standard feedforward decoder-only transformer, where the latent space, $z_t \in \mathbb{R}^{N \times D \times R}$ is divided into R regions and processed recursively for each timestep t (with N tokens and D dimensionality per region). First, a multi-region self-attention (MRSA) is calculated, which is a generalization of multi-headed self attention (MHSA),

$$z'_t = MRSA(RN(z_{t-1})) + z_{t-1}, \tag{1}$$

where MHSA is calculated separately for the latent space in each region, $z_r \in \mathbb{R}^{N \times D}$, normalized using Region Normalization (RN), and concatenated, as further specified in the Appendix A. Next, a multi-region perceptron (MRP) is calculated, which is a generalization of the multi-layer perceptron, which allows interactions between regions,

$$z(t) = MRP(RN(z'_t)), \quad MRP(z) = \sum_{r=1}^{R} u(z_r B_r) + u(W^{M,r} g(z_r W^{1,r}) W^{2,r}) \tag{2}$$

The $MRP(.)$ calculation is performed in a parallel fashion for the latent space in each region, with learnable parameters for MLP weights ($W^{1,r} \in \mathbb{R}^{D \times D_{FF}}$, $W^{2,r} \in \mathbb{R}^{D_{FF} \times D}$) and $W^{M,r} \in \mathbb{R}^{NR \times N}$ enabling interactions between tokens in different regions. $B_r \in \mathbb{R}^{D \times DR}$ is a binary weight matrix that controls how the residuals propagate, $g(.)$, a GeLU nonlinearity, and $u(.)$ is an unstacking/reshaping operation of a matrix with a total of NDR elements to a tensor in $\in \mathbb{R}^{N \times D \times R}$ (applied to $z_r B_r \in \mathbb{R}^{N \times DR}$ and $W^{M,r} g(z_r W^{1,r}) W^{2,r} \in \mathbb{R}^{NR \times D}$).

When B_r and $W^{M,r}$ are frozen with identity matrix configurations further specified in Appendix A, (1) and (2) simplify to a standard feedforward transformer architecture with L layers when the total number or timesteps and number of regions both equal L. Alternatively, B_r and $W^{M,r}$ can be structured to enable different forms of region-to-region interactions and modeled on observed exponential drop-off cortical connectivity (See Appendix A). Furthermore, the number of timesteps can be increased to enable further levels of processing with a fixed number of parameters.

Micro   As further outlined in Appendix A, the self-attention calculation is parameterized by $W^Q \in \mathbb{R}^{D \times D_q}$, $W^K \in \mathbb{R}^{D \times D_q}$, and $W^V \in \mathbb{R}^{D \times D_v}$ for each of the H attention heads for each region and $W^0 \in \mathbb{R}^{D_v H \times D}$ for each region. These parameters can be sorted by use as either attention-embeddings (W^Q and W^K) or forward-embeddings (W^V and W^0). Dimensionality-reduction may be applied by reducing D_q relative to D_v by a factor of d and sparsity may be applied by initializing each element of W^V and W^0 to be sparse with probability s.

Meso   At the meso-scale we constrain the input dimensionality (D) of each attention head seperately. We decompose each of the $W^E, E \in \{Q, K, V\}$ attention embedding matrices, $W^{E,h} = S^h \tilde{W}^{E,h}$. The binary matrix $S^h \in \mathbb{R}^{D \times D_s}$, ($D_s < D$) has at most one non-zero element in each row so that that each head receives input from a different subset of elements along the dimensionality, D.

3   Experiments and Results

To investigate properties of cortical processing in transformer networks, we perform a series of computational experiments using the CIFAR-10-C benchmark. We utilize CCT (12) as a baseline

Figure 2: CIFAR-10-C accuracy and model compression with multi-scale cortical connectivity properties. A. Model accuracy on uncorrupted CIFAR-10. B. Model accuracy (relative to baseline) versus corruption difficulty. The 71 evaluated corruptions are binned by decile of baseline accuracy. C. Average model accuracy on the subset of the most difficult corruptions for the baseline model (corruptions that reduced baseline model accuracy by over 40%). All comparisons are run with 3 random intialization seeds. Error bars in A and C are min and max values, error bands in B are bootstrapped 95% confidence intervals.

network given its parameter efficiency and competitive performance on the standard CIFAR-10 benchmark compared to other vision transformers. We leverage the convolutional tokenizer from this architecture and replace the transformer backbone with our Cortical Blocks to evaluate cortical design principles. Additional model and training details are found in Appendix B.1. For both the CCT baseline and our Cortical Transformer, a baseline depth of four transformer layers/Cortical Blocks respectively is used, consistent with the four cortical regions associated with visual object recognition in the primate ventral stream (7).

Setup: For a general comparison of robustness performance and network size, we train networks with all cortical design principles on CIFAR-10 and evaluate them on CIFAR-10-C. We compare networks with macro+micro+meso and macro+micro cortical variations to a baseline transformer network as well as networks that achieve similar model compression with naive downscaling approaches (Fig. 2). For measuring robustness to corruptions, we quantify the difficulty of a corruption type and severity level as the baseline transformer performance (considering that corruption type has a considerable influence on the practical difficulty of a task in addition to the benchmark annotated severity level).

Macro-, Meso-, and Micro-Analysis We first examine how combinations of cortical principles (outlined in Section 2) impact performance. In aggregate, these cortical variations (which have a 5× and 15× compression in attention parameters) yield minor decreases in uncorrupted image accuracy, but as the corruption difficulty increases, the cortical variations have higher relative performance (Fig. 3). Naively reducing the dimensionality of W^Q, W^K, W^V, W^0 in standard transformers, by similar factors of 4 and 8, fails to improve accuracy for both the uncorrupted and most difficult corruptions. Thus, using the Cortical Transformer enables the number of attention parameters to be reduced by over an order of magnitude while having increased performance on the most difficult corruptions.

Ablation studies We perform additional ablation studies to quantify the contributions of the macro-/meso-/micro- design principles investigated (recurrence, sparsity, and token-interactions), summarized in Fig. 3. At the macro-level, adding recurrence increases the virtual depth of the network via additional processing steps but without increasing parameters. Here, added recurrence yields improved performance on the uncorrupted and most difficult corruptions data. Token-interactions improve average accuracy on difficult corruptions across all tested comparisons (with the strongest gains seen in the most compressed networks).

Micro-cortical connectivity principles are further examined with our framework through the lenses of dimensionality reduction and sparsity (see Section 2). Individually, dimensionality reduction has a positive effect on performance for difficult corruptions. In combination, the total number of attention parameters can be reduced by a factor of 5 with minimal impact on uncorrupted accuracy. We test a null control by switching the parameters for dimensionality-reduction ($\{W^Q, W^K\}$ to $\{W^V, W^0\}$) and sparsity ($\{W^V, W^0\}$ to $\{W^Q, W^K\}$) and find that the cortical variant clearly outperforms the null version only in the dimensionality reduction case.

Figure 3: Effect of individual connectivity properties on CIFAR-10-C accuracy and model compression. A-B. Macro analysis, C-D. Micro and Meso analysis. (A, C). Model accuracy on uncorrupted CIFAR-10. (B,D). Average model accuracy on the subset of the most difficult CIFAR-10-C corruptions for the baseline model (corruptions that reduced the baseline model accuracy by over 40%). Error bars signify min/max values for three seeds. Dotted lines signify baseline network averages. Feedforward macro results are with the same number of processing steps (8).

The investigated meso- cortical connectivity principles includes: 1) the input to each attention head is not the full model dimensionality and 2) the organization of the overlap to each attention head follows a two dimensional pattern of overlap (Fig. 3C-D). When the input to each attention head is completely parallelized, there is a reduction in learnable attention parameters by a factor of 3, but uncorrupted accuracy and accuracy on difficult corruptions is reduced. When there is a 2D organization of overlap, we see an increase in accuracy on difficult corruptions, while a decrease in accuracy on difficult corruptions is seen with a null 1D organization of overlap.

4 Discussion

In this work, we introduce a framework for relating cortical to transformer processing at multiple organizational scales: 1) (macro) between area-to-between block, 2) (meso) within area-to-within block, and 3) (micro) microcircuitry properties-to-within attention head calculation. We introduce a set of principles across these scales and generalizations of the transformer architecture to support them. Using a CIFAR-10-C robustness benchmark, we found that these principles could reduce learnable attention parameters by over an order of magnitude while increasing the performance on the most difficult corruptions.

For practitioners utilizing transformer networks, some of these investigated principles can be readily incorporated, such as micro-dimensionality-reduction or token-interactions, which had improvement in model compression and robustness respectively. Several of these principles are also related to existing design augmentations for transformer networks. For example, macro-sparsity is related to sparse transformer implementations (4) (which are applied to the token dimension as opposed to the model dimension). Additionally, the macro-recurrence extends recurrence approaches applied to encoder-decoder language processing models (6). Finally, the learned token-interactions introduced here are a flexible method of enabling hierarchical token representation, related to more rigid patch merging operations utilized in hierarchical vision transformers (20).

Our work also extends research into the relationship between visual cortical processing and convolution-based networks (19; 17) by 1) adding the ability to investigate the relationship at multiple spatial scales (including the calculation of attention in cortical microcircuitry) and 2) adding the ability to make comparisons with networks utilized across domains, such as language. Further investigation into the relationship between cortical processing across scales and transformer networks could also lead to additional experimental comparisons, for example by comparing properties of inhibitory neural responses to calculated attention masks. Overall, the framework, multi-scale connectivity principles, and computational experiments presented in this work have considerable room for further investigation to enable more compressed/robust transformer networks and to further an understanding of the relationship between cortical processing and modern deep learning approaches.

References

[1] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E Hinton. Layer normalization. *arXiv preprint arXiv:1607.06450*, 2016.

[2] Srinadh Bhojanapalli, Ayan Chakrabarti, Daniel Glasner, Daliang Li, Thomas Unterthiner, and Andreas Veit. Understanding robustness of transformers for image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10231–10241, 2021.

[3] Nicolas Carion, Francisco Massa, Gabriel Synnaeve, Nicolas Usunier, Alexander Kirillov, and Sergey Zagoruyko. End-to-end object detection with transformers. In *European conference on computer vision*, pages 213–229. Springer, 2020.

[4] Rewon Child, Scott Gray, Alec Radford, and Ilya Sutskever. Generating long sequences with sparse transformers. *arXiv preprint arXiv:1904.10509*, 2019.

[5] Jean-Baptiste Cordonnier, Andreas Loukas, and Martin Jaggi. On the relationship between self-attention and convolutional layers. *arXiv preprint arXiv:1911.03584*, 2019.

[6] Mostafa Dehghani, Stephan Gouws, Oriol Vinyals, Jakob Uszkoreit, and Łukasz Kaiser. Universal Transformers. *arXiv*, 2018.

[7] James J DiCarlo, Davide Zoccolan, and Nicole C Rust. How does the brain solve visual object recognition? *Neuron*, 73(3):415–434, 2012.

[8] Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. *arXiv preprint arXiv:2010.11929*, 2020.

[9] Nathan Drenkow, Numair Sani, Ilya Shpitser, and Mathias Unberath. Robustness in deep learning for computer vision: Mind the gap? *arXiv preprint arXiv:2112.00639*, 2021.

[10] Elodie Fino and Rafael Yuste. Dense inhibitory connectivity in neocortex. *Neuron*, 69(6):1188–1203, 2011.

[11] Kenneth D Harris and Gordon M G Shepherd. The neocortical circuit: themes and variations. *Nature Neuroscience*, 18(2):170–181, 2015.

[12] Ali Hassani, Steven Walton, Nikhil Shah, Abulikemu Abuduweili, Jiachen Li, and Humphrey Shi. Escaping the big data paradigm with compact transformers. *arXiv preprint arXiv:2104.05704*, 2021.

[13] Dan Hendrycks and Thomas Dietterich. Benchmarking Neural Network Robustness to Common Corruptions and Perturbations. *arXiv*, 2019.

[14] Siddhant M Jayakumar, Wojciech M Czarnecki, Jacob Menick, Jonathan Schwarz, Jack Rae, Simon Osindero, Yee Whye Teh, Tim Harley, and Razvan Pascanu. Multiplicative interactions and where to find them. In *International Conference on Learning Representations*, 2019.

[15] Salman Khan, Muzammal Naseer, Munawar Hayat, Syed Waqas Zamir, Fahad Shahbaz Khan, and Mubarak Shah. Transformers in vision: A survey. *ACM Computing Surveys (CSUR)*, 2021.

[16] Dwight J Kravitz, Kadharbatcha S Saleem, Chris I Baker, Leslie G Ungerleider, and Mortimer Mishkin. The ventral visual pathway: an expanded neural framework for the processing of object quality. *Trends in cognitive sciences*, 17(1):26–49, 2013.

[17] Jonas Kubilius, Martin Schrimpf, Kohitij Kar, Ha Hong, Najib J Majaj, Rishi Rajalingham, Elias B Issa, Pouya Bashivan, Jonathan Prescott-Roy, Kailyn Schmidt, Aran Nayebi, Daniel Bear, Daniel L K Yamins, and James J DiCarlo. Brain-Like Object Recognition with High-Performing Shallow Recurrent ANNs. *arXiv*, 2019.

[18] Zhe Li, Wieland Brendel, Edgar Y Walker, Erick Cobos, Taliah Muhammad, Jacob Reimer, Matthias Bethge, Fabian H Sinz, Xaq Pitkow, and Andreas S Tolias. Learning From Brains How to Regularize Machines. *arXiv*, 2019.

[19] Qianli Liao and Tomaso Poggio. Bridging the Gaps Between Residual Learning, Recurrent Neural Networks and Visual Cortex. *arXiv*, 2016.

[20] Ze Liu, Yutong Lin, Yue Cao, Han Hu, Yixuan Wei, Zheng Zhang, Stephen Lin, and Baining Guo. Swin transformer: Hierarchical vision transformer using shifted windows. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 10012–10022, 2021.

[21] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.

[22] Nikola T Markov, P Misery, Arnaud Falchier, C Lamy, J Vezoli, R Quilodran, MA Gariel, Pascale Giroud, Maria Ercsey-Ravasz, LJ Pilaz, et al. Weight consistency specifies regularities of macaque cortical networks. *Cerebral cortex*, 21(6):1254–1272, 2011.

[23] Katelyn Morrison, Benjamin Gilby, Colton Lipchak, Adam Mattioli, and Adriana Kovashka. Exploring corruption robustness: Inductive biases in vision transformers and mlp-mixers. *arXiv preprint arXiv:2106.13122*, 2021.

[24] Pasko Rakic. Evolution of the neocortex: a perspective from developmental biology. *Nature Reviews Neuroscience*, 10(10):724–735, 2009.

[25] Prajit Ramachandran, Niki Parmar, Ashish Vaswani, Irwan Bello, Anselm Levskaya, and Jon Shlens. Stand-alone self-attention in vision models. *Advances in Neural Information Processing Systems*, 32, 2019.

[26] Thomas Serre, Aude Oliva, and Tomaso Poggio. A feedforward architecture accounts for rapid categorization. *Proceedings of the national academy of sciences*, 104(15):6424–6429, 2007.

[27] Baifeng Shi, Yale Song, Neel Joshi, Trevor Darrell, and Xin Wang. Visual attention emerges from recurrent sparse reconstruction. *arXiv preprint arXiv:2204.10962*, 2022.

[28] R Angus Silver. Neuronal arithmetic. *Nature Reviews Neuroscience*, 11(7):474–489, 2010.

[29] Robin Tremblay, Soohyun Lee, and Bernardo Rudy. GABAergic Interneurons in the Neocortex: From Cellular Properties to Circuits. *Neuron*, 91(2):260–292, 2016.

[30] Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[31] James CR Whittington, Joseph Warren, and Tim EJ Behrens. Relating transformers to models and neural representations of the hippocampal formation. In *International Conference on Learning Representations*, 2021.

[32] Enze Xie, Wenhai Wang, Zhiding Yu, Anima Anandkumar, Jose M Alvarez, and Ping Luo. Segformer: Simple and efficient design for semantic segmentation with transformers. *Advances in Neural Information Processing Systems*, 34:12077–12090, 2021.

[33] Daniel LK Yamins and James J DiCarlo. Using goal-driven deep learning models to understand sensory cortex. *Nature neuroscience*, 19(3):356–365, 2016.

A Cortical Block

A.1 Macro Details

Multi-region self attention For the latent space in each region ($z_r \in \mathbb{R}^{N \times D}$), self-attention (SA) and multi-headed self-attention (MHSA) is calculated as in standard transformer networks (30),

$$q = z_r W^Q, k = z_r W^K, v = z_r W^V, A = softmax(qk^T/\sqrt{D}), SA(z_r) = Av \tag{3}$$

$$MHSA(z_r) = [SA_1(z_r); SA_1(z_r); ...; SA_H(z_r)]W_r^0 \tag{4}$$

For multi-region self-attention ($MRSA$), the MHSA is concatenated between all regions,

$$MRSA(z) = Concat(MHSA(z_{r=1}), MHSA(z_{r=2}), ..., MHSA(z_{r=R})). \tag{5}$$

Multi-region perceptron In Eq. 2, which specificies the calculation of the multi-region perceptron, there are learnable output token-interactions parameters for each regions, $W^{M,r} \in \mathbb{R}^{NR \times N}$. There is a block structure to $W^{M,r}$, which is created by stacking the effective token-interactions for each output region ($W^{r_{out}=1}, W^{r_{out}=2}, ..., W^{r_{out}=R}$), where $W^{r_{out}} \in \mathbb{R}^{N \times N}$. To enable a standard feedforward architecture, the block in $W^{r_{out}}$ where $r_{out} = r + 1$ is an identity matrix and the rest of $W^{M,r}$ is all zero. To enable fully recurrent interactions between regions, $W^{M,r}$ is fully learnable and non-zero. To model exponential drop-off in connectivity between regions, each element in $W^{r_{out}}$ is masked to zero with a probability $p_m = 1 - e^{(|r-r_{out}|)/\lambda}$, where λ controls the rate of exponential connectivity drop-off.

Similar to specification of $W^{M,r}$, configurations of residual propagation can be enabled with $B_r \in \mathbb{R}^{D \times DR}$, composed of stacked ($B^{r_{out}=1}, B^{r_{out}=2}, ..., B^{r_{out}=R}$) blocks, where $B^{r_{out}} \in \mathbb{R}^{D \times D}$. To enable a standard feedforward architecture, $B^{r_{out}}$ is an identity matrix at $r_{out} = r + 1$ and zero otherwise. To enable fully recurrent interactions, all $B^{r_{out}}$ blocks are an identity matrix. To model differences in connectivity between regions, the same calculation of p_m above is used to control the probability of masking elements to zero.

An additional variation of the multi-region perceptron can be formulated that enables region to region connectivity specification, but without token-interactions,

$$\tilde{MRP}(z) = \sum_{r=1}^{R} u(z_r B_r) + u(g(z_r W^{1,r})\tilde{W^{2,r}}), \tag{6}$$

where $\tilde{W^{2,r}} \in \mathbb{R}^{N \times DR}$ is configured in a block structure with blocks $\tilde{W}^{r_{out}} \in \mathbb{R}^{N \times D}$. In this case, a standard feedforward architecture is specified by making $\tilde{W}^{r_{out}}$ where $r_{out} = r + 1$ learnable and $\tilde{W}^{r_{out}}$ equal to zero in other blocks.

A.2 Meso details

When decomposing $W^{E,h} = S^h \tilde{W}^{j,h}$ for $E \in \{Q, K, V\}$, the learnable parameters, $\{\tilde{W}^Q \in \mathbb{R}^{D_s \times D_q}, \tilde{W}^K \in \mathbb{R}^{D_s \times D_q}, \tilde{W}^V \in \mathbb{R}^{D_s \times D_v}\}$ are lower dimensional than $W^{j,h}$ by a factor of D_s/D. When $D_s = D/H$, the input space can be completely parallelized between heads. When $D_s > D/H$, there can be overlap of input space between heads. To approximate a sheet-like two dimensional organization of the input space between heads, the D dimensions are reshaped to a two dimensional $D/m \times m$ matrix, M. The input of each attention head is parameterized with a center location ($x_{center}^h, y_{center}^h$) evenly distributed across M and a $width$, which controls the amount of input overlap between heads.

A.3 Region Normalization

Just as LayerNorm (1) plays a key role in standard Transformer layers, we consider normalization within and across regions in the context of our Cortical Transformer. For input x to the `RegionNorm` layer, we compute

$$z = \gamma \frac{x - \mu}{\sigma} + \beta \tag{7}$$

where γ and β are learnable parameters. Our `RegionNorm` differs from LayerNorm with respect to the calculation of μ, σ and the dimensions along which γ, β are learned and applied. In particular, we allow the dimensions for computing μ, σ to be decoupled from the learnable paramter dimensions for γ, β. Our intent was to allow for variations where the normalizing factors could be global or local to regions (via the shape of μ, σ) and the affine paramters could be global, by region, or elementwise (via the shape of γ, β).

In cases where μ, σ were computed globally, the regions become coupled. For instance, if activations in specific later regions are zero, then the activations in those regions will become non-zero (i.e., for region i, $z_i = \frac{-\mu}{\sigma}$ assuming $\gamma = 1, \beta = 0$ here). Our `RegionNorm` layer enables investigation of multiple interpretations of normalization in the context of cortical connectivity as they relate to within and across-region behavior. We explored many of these configurations, but for all experiments, we computed μ, σ along the token dimension only, and learn element-wise gains and biases (γ, β) for region and token dimensions.

B Experiment Details

B.1 Baseline Architecture

We utilize the CCT architecture (12) both as a baseline network and a foundation for our cortical transformer model. A primary motivation of CCT was to reduce the trainable parameters by replacing the patch-wise tokenization in ViTs (8) with a convolutional tokenizer implemented as:

$$x_0 = MaxPool(ReLU(Conv2D(x))) \tag{8}$$

for input image x and where $MaxPool, ReLU, Conv2D$ follow their standard implementations. The result is a decrease in the total number of parameters and an increase in the number of tokens. Following (12), we use the 3×2 tokenization which equates to two layers of 3×3 convolutional kernels with 3×3 (stride=1), and 3×3 pooling (stride=2). In the baseline and cortical transformer cases, convolutional layers were set to output feature maps with the channel dimension equal to 128. We utilize the Sequence Pooling operation from the original CCT formulation which uses attention-based pooling over the output tokens prior to a final classification layer. This considers the case that tokens may contain varying amounts of information and the learnable attention pooling parameters help to account for this variation.

B.2 Training Hyperparameters

For training, hyperparameters are described in Table 1. We use cosine annealing (21) to adjust the learning rate over all epochs.

Hyperparameter	Value
Base learning rate	5e-4
Batch size	64
Optimizer	AdamW
Weight decay	3e-2
Epochs	200

Table 1: Training Hyperparameters

B.3 Cortical Block Hyperparameters

Baseline The baseline configuration for all variants have the number of heads per region, H=4, the dimensionality per region, $D = 128$, and number of regions, $R = 4$.

Macro The rate of exponential drop-off, $\lambda = 0.5$.

Micro The investigated micro configurations dimensionality reduction by a factor of $d = 4$ and sparsity level, $s = 0.125$.

Meso For the tested meso variants, H is increased to 8 to investigate enhanced parallelization between heads. For specifying the investigated fully parallel configuration, $m = 8$ and $width = 4$. For the configuration investigating 2D overlap, $width = 6$. The null comparison with 1D input overlap is configured with $m = 1$, $width = 23$.

C Compute Resources

Experiments were run on an internal cluster containing NVIDIA v100 and a100 GPUs as well as additional g4dn.2xlarge AWS instances.

D Societal Impacts

We believe this work poses minimal societal risks as our primary objective is to make stronger connections between transformer architectures and cortical processing. We aim to improve model performance for challenging/corrupted inputs which should enable more positive uses of these models in real-world settings. Nonetheless, persisting failures of these models and/or their improved performance in the hands of bad actors which may put society at greater risk.