Towards Principled Test-Time Adaptation for Time Series Forecasting

Abstract

Test-time adaptation (TTA) has recently emerged as a promising approach for improving time series forecasting (TSF) under distribution shift. In TSF, forecasting targets become observable after predictions are made, allowing forecasters to adapt as new observations arrive. Existing TSF-TTA methods differ in when and how they reuse these revealed targets, leading to different adaptation protocols. To address this issue, we introduce a cleaner protocol using only matured ground truth, defined as targets from fully observed forecasting horizons. This reliance on delayed but complete feedback places greater emphasis on the adapter's ability to derive useful prediction corrections. We then examine the corrections produced by existing adapters and find that they are often smooth and weakly selective across frequencies. Driven by this observation, we propose Frequency-Aware Calibration (FAC), a lightweight calibration method that directly parameterizes prediction corrections in the frequency domain. Across diverse settings, FAC remains competitive while using substantially fewer trainable parameters than other TSF-TTA adapters.

1 Introduction

Time series forecasting (TSF) plays a critical role in a wide range of domains, including weather (Wu et al., 2023; Verma et al., 2024), energy (Maleki et al., 2024), traffic (Yin et al., 2022; Zhang et al., 2024), and finance (Tsay, 2010; Koa et al., 2026). Recent advances in deep learning-based architectures have substantially enhanced predictive performance across diverse time series forecasting settings (Zeng et al., 2023; Nie et al., 2023; Liu et al., 2024).

Despite this progress, deploying time series forecasters to real-world applications remains challenging due to the complex and evolving nature of temporal data. In particular, distribution shifts induced by non-stationarity pose a major obstacle to reliable forecasting (Granger, 2003; Du et al., 2021), especially in long-horizon settings. To address this issue, prior studies have mainly pursued two paradigms: introducing learnable normalization modules (Kim et al., 2022; Fan et al., 2023; Liu et al., 2023), which primarily operate during pre-training, or training forecasting models in an online manner (Pham et al., 2023; Zhang et al., 2023; Liang et al., 2024; Lau et al., 2025; Huang et al., 2026). While these approaches can partially mitigate the effects of distribution shift, they either focus largely on the training phase or require training an online forecaster from scratch. In light of these limitations, applying test-time adaptation (TTA) (Kim et al., 2025; Medeiros et al., 2025; Grover & Etemad, 2025; Im & Kwon, 2026) to a source forecaster has emerged as a promising alternative.

Existing TSF-TTA methods differ in how they utilize revealed targets, with some (Kim et al., 2025; Medeiros et al., 2025; Grover & Etemad, 2025) incorporating partially-observed ground truth (POGT) together with full ground truth, which we refer to as **matured ground truth** throughout this paper, to enable more proactive adaptation. At the mini-batch level, a past mini-batch is considered as matured when the full target horizon for every sample in that mini-batch has been completely observed. Intuitively, with respect to the current batch, matured supervision lies entirely to the left of the end of the first look-back window in the current mini-batch. In contrast, COSA (Im & Kwon, 2026) is presented under a streaming formulation based on revealed ground truth, where an output adapter is updated on the current mini-batch using targets

Figure 1: Comparison of adaptation supervision protocols in TSF-TTA. Here, L, H, and B_k denote the look-back length, forecasting horizon, and mini-batch size, respectively, and t_k denotes the time index immediately preceding the first target of mini-batch k. (a) Mixed supervision combines two temporally distinct sources: POGT from the current mini-batch, shown in blue and corresponding to $\mathcal{L}_k^{\text{POGT}}$ in Eq. 5, and full ground truth from the most recent matured mini-batch $m(k)$, shown in green and corresponding to $\mathcal{L}_{m(k)}^{\text{Matured}}$ in Eq. 6. Together, they form the mixed supervision objective in Eq. 4. (b) Streaming adaptation updates the adapter using current-mini-batch revealed-target supervision, indicated by the red shaded region and corresponding to $\mathcal{L}_k^{\text{stream}}$ in Eq. 11.

revealed for that mini-batch and lightweight context constructed from previously observed targets, without being explicitly framed in terms of matured ground truth. As illustrated in Figure 1, the key distinction between the two families lies in the timing and manner in which target observations are used for adaptation.

Despite these design differences, the protocol-level role of revealed targets in TSF-TTA remains insufficiently clarified. Our analysis demonstrates that existing TSF-TTA protocols lack a clearly unified account of how revealed targets should be used for adaptation. This ambiguity motivates us to revisit TSF-TTA from the perspective of protocol cleanliness. In particular, we advocate using matured ground truth as a cleaner and more principled adaptation signal in rolling forecasting settings. We further examine the prediction corrections of existing TSF-TTA methods in the frequency domain, finding that they often exhibit relatively smooth and weakly structured spectral patterns despite their different calibration designs. Based on this observation, we propose Frequency-Aware Calibration (FAC), which achieves competitive and consistent performance under the proposed protocol across diverse forecasting settings.

Our contributions are summarized as follows:

- We revisit how revealed targets are used in TSF-TTA and show that a cleaner protocol based on matured ground truth provides a more principled setting for adaptation.

- We provide a frequency-domain diagnosis of existing TSF-TTA methods, showing that their realized corrections often exhibit limited and weakly structured spectral modifications.

- We propose Frequency-Aware Calibration (FAC), a lightweight adapter that directly parameterizes calibration in the frequency domain and achieves competitive and consistent performance across diverse forecasting settings.

2 Related Work

2.1 Time Series Forecasting under Distribution Shift

A representative line of work addresses distribution shift in time series forecasting through learnable normalization or related distribution calibration mechanisms. RevIN (Kim et al., 2022) mitigates temporal distribution shift via reversible instance normalization and denormalization with learnable affine transformation. Dish-TS (Fan et al., 2023) characterizes both intra-space shift and inter-space shift, alleviating them through dual distribution modeling for the input and output spaces. SAN (Liu et al., 2023) further models non-stationarity by capturing statistical variation at the temporal-slice level. Although effective, these methods primarily improve robustness through training-time or architecture-level treatment of non-stationarity, rather than adapting a deployed source forecaster at test time.

Another line of work (Pham et al., 2023; Zhang et al., 2023; Liang et al., 2024; Lau et al., 2025; Huang et al., 2026) considers online time series forecasting (OTSF), where the forecasting model is continuously updated as new observations arrive. Recent studies (Liang et al., 2024; Lau et al., 2025) have pointed out that conventional OTSF protocols may suffer from evaluation leakage or unrealistic forecasting setups. In particular, Act-Now (Liang et al., 2024) and DSOF (Lau et al., 2025) revisit online forecasting protocols and advocate cleaner evaluation settings that avoid evaluating predictions on steps already used for model updates. Within this line of work, Act-Now (Liang et al., 2024) introduces a label decomposition model to tackle distribution shift, while DSOF (Lau et al., 2025) adopts a dual-stream teacher-student framework for online forecasting. ADAPT-Z (Huang et al., 2026) further studies the challenge of delayed-feedback online prediction and argues that distribution shift may be better addressed through feature-level adjustment. These approaches are related to TSF-TTA in spirit, but the primary objectives differ: OTSF focuses on training the online forecaster itself, while TSF-TTA adapts a frozen source forecaster at test time.

2.2 Test-Time Adaptation for Time Series Forecasting

Test-time adaptation (TTA) (Wang et al., 2021; 2022; Gong et al., 2023; Liang et al., 2025; Kim et al., 2026) has been widely studied in domains such as computer vision, where models are adapted at test time to improve robustness under distribution shift. Unlike conventional TTA methods (Wang et al., 2021; 2022; Gong et al., 2023; Kim et al., 2026), which typically rely on unlabeled test-time data, TSF-TTA can exploit forecasting targets that become sequentially revealed after prediction. As the pioneering work on TSF-TTA, TAFAS (Kim et al., 2025) incorporates both matured ground truth and partially observed ground-truth (POGT), aiming to enable earlier and more proactive adaptation. PETSA (Medeiros et al., 2025) further enhances parameter efficiency by introducing low-rank adapters together with a specialized adaptation loss. DynaTTA (Grover & Etemad, 2025) employs dynamic adaptation rates and shift-conditioned gating based on real-time estimation of distribution shift. In contrast, COSA (Im & Kwon, 2026) is presented under a streaming formulation based on revealed ground truth, where a single output adapter corrects the current mini-batch prediction using lightweight context from previously revealed targets and is updated directly against the targets of the current mini-batch. These methods therefore differ not only in adapter design, but also in when and how revealed targets are incorporated into adaptation.

3 Towards Cleaner Adaptation Protocols for TSF-TTA

3.1 Preliminaries: Rolling TSF-TTA Formulation

Existing TSF-TTA (Kim et al., 2025; Medeiros et al., 2025; Grover & Etemad, 2025; Im & Kwon, 2026) methods adopt a rolling test-time adaptation setting, in which a pre-trained source forecaster is deployed on temporally ordered test data under distribution shift. Following the "test mini-batch" terminology used

in TAFAS (Kim et al., 2025), a mini-batch in this paper refers to a contiguous, temporally ordered block of rolling windows from a single multivariate time series, rather than a shuffled training batch. Predictions are produced for all samples within each mini-batch. Let L and H denote the look-back length and forecasting horizon, respectively. We index rolling mini-batches by k, and let B_k denote the size of the k-th mini-batch. We further let t_k denote the global time index immediately preceding the first forecasted target of the k-th mini-batch. Since rolling windows are grouped consecutively, the next mini-batch starts after B_k shifts, yielding $t_{k+1} = t_k + B_k$. For the j-th sample of the k-th mini-batch, where $j \in \{1, \ldots, B_k\}$, the input window, the corresponding forecast, and the corresponding target vector are given by

$$\mathbf{X}_k^{[j]} = [\mathbf{x}_{t_k+j-L}, \ldots, \mathbf{x}_{t_k+j-1}], \quad \hat{\mathbf{Y}}_k^{[j]} = [\hat{\mathbf{y}}_{t_k+j}^{[j]}, \ldots, \hat{\mathbf{y}}_{t_k+j+H-1}^{[j]}], \quad \mathbf{Y}_k^{[j]} = [\mathbf{y}_{t_k+j}, \ldots, \mathbf{y}_{t_k+j+H-1}]. \quad (1)$$

where $\mathbf{x}_t \in \mathbb{R}^C$ denotes the multivariate observation at time step t, and $\hat{\mathbf{y}}_t^{[j]} \in \mathbb{R}^C$ denotes the prediction of the j-th sample at time step t. Note that $\hat{\mathbf{y}}_t^{[j]}$ differs for different samples in the mini-batch.

The forecasting target span of the k-th mini-batch can then be denoted as the union of all sample-level targets within the mini-batch:

$$\mathfrak{Y}_k = \bigcup_{j=1}^{B_k} \mathbf{Y}_k^{[j]} = \{\mathbf{y}_{t_k+1}, \ldots, \mathbf{y}_{t_k+H+B_k-1}\}. \quad (2)$$

3.2 A Closer Look at Existing Supervision Protocols

3.2.1 Mixed Supervision with POGT and Matured Ground Truth

A representative line of TSF-TTA methods (Kim et al., 2025; Medeiros et al., 2025; Grover & Etemad, 2025) adopts a mixed supervision protocol that combines POGT from the current mini-batch with supervision from the most recent matured mini-batch, as illustrated in Figure 1a. In these methods, the POGT length p_k is determined by the periodicity-aware adaptation scheduling (PAAS), with $p_k = B_k - 1$. For notational consistency, we will use $B_k - 1$ to denote the POGT length below.

Let $\mathcal{C}_{k-1}^{\text{in}}(\cdot)$ and $\mathcal{C}_{k-1}^{\text{out}}(\cdot)$ denote the input and output calibration modules available before adapting on the k-th mini-batch. For the j-th sample in that mini-batch, the calibrated prediction is

$$\hat{\mathbf{Y}}_k^{\text{cali},[j]} = \mathcal{C}_{k-1}^{\text{out}}(\mathcal{F}(\mathcal{C}_{k-1}^{\text{in}}(\mathbf{X}_k^{[j]}))) = [\hat{\mathbf{y}}_{t_k+j}^{\text{cali},[j]}, \ldots, \hat{\mathbf{y}}_{t_k+j+H-1}^{\text{cali},[j]}], \quad (3)$$

where $\mathcal{F}(\cdot)$ denotes the frozen source forecaster. Let $m(k)$ denote the index of the most recent matured mini-batch. Then the mixed supervision protocol can be abstractly written as

$$\mathcal{L}_k^{\text{mixed}} = \mathcal{L}_k^{\text{POGT}} + \mathcal{L}_{m(k)}^{\text{Matured}}, \quad (4)$$

with

$$\mathcal{L}_k^{\text{POGT}} = \text{MSE}\left(\{\hat{\mathbf{y}}_t^{\text{cali},[1]}\}_{t=t_k+1}^{t_k+B_k-1}, \{\mathbf{y}_t\}_{t=t_k+1}^{t_k+B_k-1}\right). \quad (5)$$

and

$$\mathcal{L}_{m(k)}^{\text{Matured}} = \text{MSE}\left(\{\hat{\mathbf{Y}}_{m(k)}^{\text{cali},[j]}\}_{j=1}^{B_{m(k)}}, \{\mathbf{Y}_{m(k)}^{[j]}\}_{j=1}^{B_{m(k)}}\right). \quad (6)$$

The prediction and target arguments in Eqs. 5 and 6 have dimensions $(B_k - 1) \times C$ and $B_{m(k)} \times H \times C$, respectively. Equation 4 combines two temporally distinct supervision signals: $\mathcal{L}_k^{\text{POGT}}$ enables timely adaptation using the revealed prefix of the current mini-batch, whereas $\mathcal{L}_{m(k)}^{\text{Matured}}$ provides complete-horizon supervision from the most recent matured mini-batch. In implementation, these two terms may be consumed in separate adaptation steps, but together they define the mixed supervision protocol. After adaptation, the calibration modules are updated to $\mathcal{C}_k^{\text{in}}(\cdot)$ and $\mathcal{C}_k^{\text{out}}(\cdot)$. The current mini-batch is then re-forecast using the updated calibration modules:

$$\hat{\mathbf{Y}}_k^{\text{adp},[j]} = \mathcal{C}_k^{\text{out}}\left(\mathcal{F}\left(\mathcal{C}_k^{\text{in}}(\mathbf{X}_k^{[j]})\right)\right). \quad (7)$$

The adjusted prediction keeps the already observed prefix from the original calibrated prediction and replaces the unobserved suffix with the re-forecasted one, which is given by

$$\tilde{\mathbf{y}}_{k,t}^{[j]} = \begin{cases} \hat{\mathbf{y}}_t^{\text{cali},[j]}, & t_k + j \le t \le t_k + B_k - 1, \\ \hat{\mathbf{y}}_t^{\text{adp},[j]}, & t_k + B_k \le t \le t_k + j + H - 1. \end{cases} \tag{8}$$

However, by the time POGT becomes available for adaptation, the same revealed values have already entered the look-back windows of later samples within the same mini-batch. **This raises a natural question: is it more beneficial to use these revealed values as supervision for adaptation, or simply as additional input context for later direct prediction?** To examine this, we compare the MSE on the shared overlapping horizon between the adjusted prediction of the first sample and the direct predictions of later samples within the same mini-batch.

As illustrated in Figure 2a, the endpoint comparison provides the most direct way to assess whether using the revealed values as supervision offers a meaningful advantage over simply using the same values as input context in later direct prediction. At the same time, this endpoint view is only the most intuitive illustration of a broader phenomenon within the mini-batch. To examine this more comprehensively, we compute the mean overlapping-region MSE at each sample position over the mini-batches with $B_k = 97$, since this is the most common mini-batch size induced by PAAS in our experiments.

Let $\mathcal{I}_{\{B_k=B\}}$ denote the set of mini-batches satisfying $B_k = B$. For the direct prediction of the j-th sample, we define the mean overlapping-region MSE as

$$\hat{M}_{\mathcal{I}_{\{B_k=B\}}}^{[j]} = \frac{1}{\left|\mathcal{I}_{\{B_k=B\}}\right|} \sum_{k \in \mathcal{I}_{\{B_k=B\}}} \text{MSE}\left([\hat{\mathbf{y}}_{t_k+B}^{[j]}, \dots, \hat{\mathbf{y}}_{t_k+H}^{[j]}], [\mathbf{y}_{t_k+B}, \dots, \mathbf{y}_{t_k+H}]\right). \tag{9}$$

The corresponding metric for the adjusted prediction, $\tilde{M}_{\mathcal{I}_{\{B_k=B\}}}^{[j]}$, is defined analogously by replacing $\hat{\mathbf{y}}^{[j]}$ with $\tilde{\mathbf{y}}^{[j]}$. Using the metrics computed for each sample j within the mini-batch, Figure 2b shows that the endpoint comparison reflects a broader pattern. Across multiple datasets, forecasting horizons and frozen source forecasters, the adjusted prediction of the first sample is generally inferior to the direct prediction of the last sample. In fact, the direct predictions from many intermediate samples already achieve comparable or lower overlapping-region MSE than the adjusted prediction of the first sample. These results indicate that using revealed values as supervision is not consistently more beneficial than simply using the same values as input context for later direct prediction.

3.2.2 Streaming Adaptation with Revealed Ground Truth

COSA (Im & Kwon, 2026) adopts a streaming adaptation protocol based on revealed ground truth, as illustrated in Figure 1b. Under this protocol, the current mini-batch is first predicted by the frozen source forecaster, after which an output adapter produces the final adapter-corrected prediction using a lightweight context vector constructed from previously revealed targets. Unlike the mixed-supervision protocol above, the output adapter is then updated directly by minimizing the MSE loss between these adapter-corrected predictions of the current mini-batch and the revealed ground truth of the current mini-batch.

Let $\mathcal{A}_{k-1}(\cdot, \cdot)$ denote the output adapter available before adapting on the k-th mini-batch, and let $\mathbf{c}_{k-1}$ denote the context vector constructed from previously revealed targets. For the j-th sample in the k-th mini-batch, the final streaming prediction is given by

$$\hat{\mathbf{Y}}_k^{\text{stream},[j]} = \mathcal{A}_{k-1}(\mathcal{F}(\mathbf{X}_k^{[j]}), \mathbf{c}_{k-1}). \tag{10}$$

After the targets of the current mini-batch are revealed, their summary statistic is added to the context memory, updating $\mathbf{c}_{k-1}$ to $\mathbf{c}_k$. The adapter is then optimized on the same mini-batch using the updated context; further implementation details are provided in Appendix B.2. Accordingly, the streaming adaptation objective can be written as

$$\mathcal{L}_k^{\text{stream}} = \frac{1}{B_k} \sum_{j=1}^{B_k} \text{MSE}(\hat{\mathbf{Y}}_k^{\text{stream},[j]}, \mathbf{Y}_k^{[j]}). \tag{11}$$

(a)

(b)

Figure 2: Comparison between the adjusted prediction of the first sample and later direct predictions within the same mini-batch. (a) Schematic illustration of the overlapping horizon shared by the first sample's adjusted prediction and the last sample's direct prediction. (b) Mean overlapping-region MSE at each sample position, averaged over mini-batches with $B_k = 97$ across representative datasets, horizons, and source forecasters. The blue and orange curves denote direct and adjusted predictions, respectively; the red dashed line marks the adjusted prediction of the first sample, and the green dashed line marks the direct prediction of the last sample. Additional results for $B_k = 25$ are provided in Appendix A.3.

Although the protocol is presented in terms of revealed ground truth, such supervision is not necessarily matured relative to subsequent rolling predictions. Recall that the target span of the k-th mini-batch is $\mathfrak{Y}_k = \{\mathbf{y}_{t_k+1}, \ldots, \mathbf{y}_{t_k+H+B_k-1}\}$. For the $(k+1)$-th mini-batch, since $t_{k+1} = t_k + B_k$, the prediction span of the j-th sample is

$$\hat{\mathbf{Y}}^{\text{stream},[j]}_{k+1} = [\hat{\mathbf{y}}^{\text{stream},[j]}_{t_k+B_k+j}, \ldots, \hat{\mathbf{y}}^{\text{stream},[j]}_{t_k+B_k+j+H-1}]. \tag{12}$$

When the forecasting horizon is sufficiently larger than the mini-batch size, the targets used to update on batch k may still overlap with the future prediction span of later mini-batches. For example, if $H \geq B_k + B_{k+1}$, then

$$\{t_k+1, \ldots, t_k+H+B_k-1\} \cap \{t_k+B_k+j, \ldots, t_k+B_k+j+H-1\} = \{t_k+B_k+j, \ldots, t_k+H+B_k-1\} \neq \emptyset. \tag{13}$$

This shows that the supervision used to update on batch k is not necessarily matured relative to subsequent rolling prediction spans.

3.3 A Cleaner Adaptation Protocol Based on Matured Ground Truth

The above examination of mixed supervision and streaming adaptation demonstrates the need for a cleaner protocol. In the mixed-supervision setting, the use of POGT naturally induces a comparison between using revealed values as supervision and using the same values as additional input context for later direct prediction. In the streaming setting, supervision based on revealed ground truth is not necessarily matured relative to subsequent rolling predictions. These observations motivate a cleaner protocol that restricts adaptation to matured ground truth only.

The cleaner protocol is defined by the temporal status of the supervision it permits, rather than by a unique implementation rule. For example, one may update based on any subset of available matured mini-batches. Formally, denote the index set of matured mini-batches available at mini-batch k as

$$\mathcal{M}_k := \{m < k : t_m + B_m + H - 1 \leq t_k\}. \tag{14}$$

Then a general adaptation objective based on matured ground truth may be written as

$$\mathcal{L}^{\text{clean}}_k = \sum_{m \in \mathcal{S}_k} \omega_{k,m} \mathcal{L}^{\text{matured}}_m, \qquad \mathcal{S}_k \subseteq \mathcal{M}_k, \tag{15}$$

where $\mathcal{S}_k$ denotes the subset of matured mini-batches selected for adaptation at mini-batch k, $\omega_{k,m} \geq 0$ are combination weights, and $\mathcal{L}^{\text{matured}}_m$ is defined by Eq. 6, with m replacing $m(k)$.

Under our proposed protocol based solely on matured ground truth, predictions may still be organized in mini-batches, but the role of the mini-batch becomes different. Conceptually, the protocol no longer depends on supervision drawn from the current mini-batch; instead, adaptation is triggered only by previously matured targets. In this sense, the mini-batch mainly serves as an implementation-level grouping for prediction and evaluation. Moreover, although predictions within a mini-batch still overlap due to the rolling construction, the comparison between earlier and later samples in the overlapped region is no longer central to the protocol itself, since adaptation for each sample no longer relies on POGT from the current mini-batch. Rather, adaptation can already be triggered using matured past supervision before later samples in the current mini-batch are generated.

4 Frequency-Aware Calibration

Having established a cleaner protocol for determining which target observations may be used for adaptation, we now turn to the design of the adaptation module. Under this protocol, adaptation no longer uses the timely feedback provided by POGT within the current mini-batch and instead relies solely on delayed supervision from matured mini-batches. This places greater emphasis on the adapter's ability to derive useful prediction corrections from the delayed supervision that remains available. Existing TSF-TTA adapters differ primarily in how they parameterize calibration. TAFAS (Kim et al., 2025) calibrates predictions through temporal-domain transformations, whereas PETSA (Medeiros et al., 2025) introduces spectral information through

a frequency-domain loss applied to a low-rank temporal calibration module. Although temporal-domain transformations can also realize global and frequency-selective corrections, these effects are represented indirectly through their temporal parameterization. Empirically, we observe that the resulting corrections are often relatively smooth and weakly selective across frequencies. This observation motivates Frequency-Aware Calibration (FAC), which directly parameterizes corrections in the frequency domain.

The key intuition behind FAC is that each Fourier basis function extends across the full temporal window, so modifying its coefficient induces coordinated changes across multiple temporal positions after the inverse Fourier transform. FAC parameterizes calibration through complex coefficients associated with individual Fourier components, making the amplitude and phase of each component directly adjustable. In this way, FAC can represent structured corrections through frequency-wise affine transformations without requiring a general dense transformation across temporal positions.

Figure 3: Overview of Frequency-Aware Calibration (FAC) under the proposed protocol. FAC uses input and output frequency-domain gated calibration modules (FreqGCMs), each applying a complex affine mask in the frequency domain followed by inverse FFT and gated residual correction. For simplicity, our implementation retrieves the most recent matured mini-batch for each update, after which the updated adapter is applied to re-forecast the current mini-batch. PAAS can optionally be used to determine the mini-batch size.

FAC adopts a minimalist design, since a central requirement for test-time adaptation in TSF is to keep the adapter lightweight. Figure 3 provides an overview. Similar to TAFAS (Kim et al., 2025) and PETSA (Medeiros et al., 2025), FAC places calibration modules before and after the frozen source forecaster. Each module performs a gated residual correction to the signal being calibrated, rather than directly replacing it. Specifically, FAC consists of an input and an output FreqGCM. Each FreqGCM first transforms the signal being calibrated into the frequency domain, applies a learnable complex affine mask, maps the frequency-domain correction back to the temporal domain through inverse FFT, and then controls the correction magnitude through a hyperbolic-tangent gate. On the input side, the input FreqGCM for the j-th sample in the k-th mini-batch is given by

$$
\begin{aligned}
\boldsymbol{\mathcal{X}}_k^{[j]} &= \mathrm{FFT}\left(\mathbf{X}_k^{[j]}\right), \\
\Delta \boldsymbol{\mathcal{X}}_k^{[j]} &= \boldsymbol{\mathcal{X}}_k^{[j]} \odot \boldsymbol{\mathcal{W}}_{\mathrm{in}} + \boldsymbol{\mathcal{B}}_{\mathrm{in}}, \\
\mathbf{X}_k^{\mathrm{FAC},[j]} &= \mathbf{X}_k^{[j]} + \tanh(\alpha_{\mathrm{in}})\, \mathrm{iFFT}\left(\Delta \boldsymbol{\mathcal{X}}_k^{[j]}\right).
\end{aligned}
\tag{16}
$$

The calibrated input is then passed to the frozen source forecaster as $\hat{\mathbf{Y}}_k^{[j]} = \mathcal{F}(\mathbf{X}_k^{\mathrm{FAC},[j]})$. The output FreqGCM follows the same form on $\hat{\mathbf{Y}}_k^{[j]}$ with output-side parameters $(\boldsymbol{\mathcal{W}}_{\mathrm{out}}, \boldsymbol{\mathcal{B}}_{\mathrm{out}}, \alpha_{\mathrm{out}})$, yielding the final

calibrated forecast $\hat{\mathbf{Y}}_k^{\mathrm{FAC},[j]}$. Let $F_{\mathrm{in}} = \lfloor L/2 \rfloor + 1$ and $F_{\mathrm{out}} = \lfloor H/2 \rfloor + 1$ denote the numbers of frequency components. The complex affine parameters satisfy $\boldsymbol{\mathcal{W}}_{\mathrm{in}}, \boldsymbol{\mathcal{B}}_{\mathrm{in}} \in \mathbb{C}^{F_{\mathrm{in}} \times C}$ and $\boldsymbol{\mathcal{W}}_{\mathrm{out}}, \boldsymbol{\mathcal{B}}_{\mathrm{out}} \in \mathbb{C}^{F_{\mathrm{out}} \times C}$, while $\alpha_{\mathrm{in}}, \alpha_{\mathrm{out}} \in \mathbb{R}^C$ are per-channel gates. We write FFT/iFFT for notational simplicity, while using rFFT/irFFT in implementation for real-valued time series. The element-wise affine form keeps FAC lightweight and frequency-wise interpretable: the multiplicative term rescales and phase-shifts Fourier coefficients, while the additive term can modify weak or near-zero components that purely multiplicative scaling may miss. The residual form preserves the original signal when the learned correction is small, and the tanh gate controls the overall correction strength.

Our protocol allows adaptation on any subset of matured ground truth; for simplicity, FAC uses the most recent matured mini-batch:

$$\mathcal{L}_{m(k)}^{\mathrm{FAC}} = \mathrm{MSE}\left(\{\hat{\mathbf{Y}}_{m(k)}^{\mathrm{FAC},[j]}\}_{j=1}^{B_{m(k)}}, \{\mathbf{Y}_{m(k)}^{[j]}\}_{j=1}^{B_{m(k)}} \right). \tag{17}$$

Although additional regularization terms could be added to this objective, we keep the adaptation loss as a simple MSE on matured ground truth. This isolates the effect of frequency-domain parameterization and avoids conflating it with additional regularization choices. After the FAC modules are updated, the current mini-batch is re-forecast with the updated input and output FreqGCMs to obtain recalibrated predictions.

5 Experiments

5.1 Experimental Settings

We conduct our primary evaluation on six multivariate TSF benchmark datasets: ETTh1, ETTh2, ETTm1, ETTm2, Weather, and Exchange. We use chronological train/validation/test splits for all datasets: the four ETT datasets use a ratio of $(0.6, 0.2, 0.2)$, while Weather and Exchange use $(0.7, 0.1, 0.2)$. The lookback length is set to $L = 96$, and the prediction horizon is chosen from $H \in \{96, 192, 336, 720\}$, except for Exchange, where we use $H \in \{96, 192, 336\}$ because the full target horizon for $H = 720$ does not mature before the end of the test sequence. Consistent with existing TSF-TTA studies, we evaluate five representative source forecasters on these primary datasets: iTransformer (Liu et al., 2024), PatchTST (Nie et al., 2023), DLinear (Zeng et al., 2023), OLS (Toner & Darlow, 2024), and FreTS (Yi et al., 2023) [1].

Recent forecasting benchmarks, such as GIFT-Eval, emphasize coverage across application domains and varying numbers of variates (Aksu et al., 2024). Motivated by these considerations, we additionally evaluate FAC on Electricity and Traffic (Zhou et al., 2021), two multivariate benchmarks from the energy and transportation domains. GIFT-Eval includes Electricity in its evaluation component and Traffic Hourly in its pretraining component. In our multivariate LTSF formulation, these datasets contain 321 and 862 variables, respectively, broadening the range of variable counts and application domains covered by our evaluation. We evaluate DLinear, FreTS, and iTransformer as three representative source forecasters spanning linear, MLP-based, and Transformer-based architectures, respectively. Each forecaster is evaluated on both datasets across $H \in \{96, 192, 336, 720\}$, yielding 24 model–horizon settings in total.

We compare FAC with the frozen source forecaster without TTA, TAFAS (Kim et al., 2025), and PETSA (Medeiros et al., 2025) under the proposed protocol based solely on matured ground truth [2]. For fairness and simplicity, only the most recent matured mini-batch is used for adaptation across methods. Since the current mini-batch does not provide supervision under this protocol, the POGT-based partial prediction adjustment in the original TAFAS protocol is no longer used. Instead, after the adapter is updated on the most recent matured mini-batch, the current mini-batch is re-forecast and the full prediction horizon is evaluated using the updated adapter. In particular, for the j-th sample in the k-th mini-batch, we use

$$\tilde{\mathbf{Y}}_k^{[j]} = \hat{\mathbf{Y}}_k^{\mathrm{adp},[j]}, \quad j = 1, \ldots, B_k, \tag{18}$$

---

[1] We omit MICN (Wang et al., 2023) from the main experiments because its architecture categorization is ambiguous in prior TSF-TTA comparisons. Although some studies group it with MLP-based forecasters, MICN is more accurately viewed as a multi-scale convolution-based model.

[2] We omit DynaTTA due to reproducibility issues with its officially released implementation; similar issues were also noted in COSA (Im & Kwon, 2026). We do not include a matured-only COSA variant because, unlike TAFAS and PETSA, its target-derived context and immediate streaming update do not admit a unique direct conversion to our protocol; see Appendix B for a detailed comparison.

rather than a partial stitching rule between pre-update and post-update predictions. Hyperparameters are taken from the officially released code whenever available. All experiments were conducted on an NVIDIA GeForce RTX 4070 Super 12GB and an NVIDIA GeForce RTX 4090 24GB.

5.2 Main Results

5.2.1 Forecasting Performance

Table 1: Forecasting performance under the proposed protocol using only matured ground truth. Lower MSE is better. The best result within each backbone and horizon is highlighted in red bold, and the second-best result is underlined.

Dataset	H	DLinear				FreTS				iTransformer				OLS				PatchTST			
		Base	TAFAS	PETSA	**FAC**	Base	TAFAS	PETSA	**FAC**	Base	TAFAS	PETSA	**FAC**	Base	TAFAS	PETSA	**FAC**	Base	TAFAS†	PETSA	**FAC**
ETTh1	96	0.4695	0.4617	0.4613	**0.4554**	0.4461	0.4391	0.4383	**0.4357**	0.4482	0.4421	**0.4394**	0.4400	0.4510	0.4428	0.4449	**0.4382**	0.4324	0.4270	0.4255	**0.4241**
	192	0.5213	0.5112	0.5123	**0.5089**	0.5022	0.4943	0.4960	**0.4934**	0.5091	0.5020	0.5014	**0.5010**	0.5045	0.4929	0.5007	**0.4921**	0.4900	0.4818	0.4818	**0.4797**
	336	0.5659	0.5595	0.5626	**0.5582**	0.5544	**0.5483**	0.5530	0.5498	0.5662	0.5624	0.5641	**0.5587**	0.5510	0.5427	0.5488	**0.5422**	0.5608	**0.5506**	0.5570	0.5525
	720	0.7117	0.6926	0.6938	**0.6891**	0.7181	**0.6857**	0.6908	0.7067	0.7007	0.6755	0.6763	**0.6687**	0.6996	**0.6704**	0.6805	0.6780	0.7112	**0.6807**	0.7019	0.7096
ETTh2	96	0.2323	0.2308	0.2312	**0.2288**	0.2385	0.2363	0.2366	**0.2338**	0.2642	0.2620	0.2602	**0.2561**	0.2306	0.2289	0.2293	**0.2274**	0.2385	0.2380	0.2383	**0.2374**
	192	0.2862	0.2830	0.2820	**0.2819**	0.2867	0.2830	0.2844	**0.2814**	0.3081	0.3004	0.3005	**0.2970**	0.2838	0.2821	0.2829	**0.2796**	0.2840	0.2752	0.2810	**0.2747**
	336	0.3252	0.3175	0.3190	**0.3144**	0.3318	0.3195	0.3250	**0.3172**	0.3402	0.3290	0.3312	**0.3284**	0.3257	0.3189	0.3240	**0.3137**	0.3233	0.3108	0.3190	**0.3079**
	720	0.4087	**0.3825**	0.3884	0.3825	0.4118	0.3814	0.3968	**0.3788**	0.4261	**0.3959**	0.4049	0.3982	0.4161	0.3859	0.3927	**0.3854**	0.4292	0.4065	0.4203	**0.4002**
ETTm1	96	0.3715	0.3504	0.3541	**0.3465**	0.3676	0.3559	0.3572	**0.3517**	0.3823	0.3680	0.3700	**0.3459**	0.3709	0.3542	0.3591	**0.3462**	0.4041	0.3826	0.3817	**0.3530**
	192	0.4438	0.4165	0.4192	**0.4139**	0.4325	0.4191	0.4189	**0.4183**	0.4407	0.4189	0.4189	**0.4087**	0.4437	0.4184	0.4252	**0.4140**	0.4515	0.4370	0.4405	**0.4213**
	336	0.5183	0.4801	0.4831	**0.4791**	0.5006	0.4810	**0.4793**	0.4836	0.5077	0.4800	0.4788	**0.4781**	0.5179	0.4811	0.4896	**0.4794**	0.5044	0.4864	0.4970	**0.4787**
	720	0.5929	0.5521	0.5600	**0.5494**	0.5703	**0.5472**	0.5523	0.5533	0.6021	0.5579	0.5615	**0.5460**	0.5923	0.5515	0.5594	**0.5497**	0.5608	0.5413	0.5479	**0.5399**
ETTm2	96	0.1598	0.1581	0.1583	**0.1560**	0.1582	0.1566	0.1569	**0.1563**	0.1647	0.1640	0.1640	**0.1613**	0.1602	0.1594	0.1595	**0.1563**	0.1581	0.1569	0.1569	**0.1558**
	192	0.1930	0.1917	0.1920	**0.1894**	0.1923	**0.1901**	0.1908	0.1901	0.2189	0.2164	0.2157	**0.2067**	0.1935	0.1924	0.1925	**0.1897**	0.2097	0.2058	0.2079	**0.1976**
	336	0.2324	0.2299	0.2303	**0.2286**	0.2320	**0.2291**	0.2312	0.2294	0.2808	0.2735	0.2653	**0.2623**	0.2331	0.2308	0.2316	**0.2289**	0.2482	0.2482	0.2473	**0.2422**
	720	0.3062	0.2993	**0.2984**	**0.2984**	0.3013	**0.2924**	0.2983	0.2955	0.3457	0.3303	**0.3263**	0.3290	0.3066	0.2996	0.3003	**0.2973**	0.3283	0.3218	0.3240	**0.3192**
Weather	96	0.1954	0.1803	0.1812	**0.1797**	0.1855	0.1757	0.1795	**0.1678**	0.1724	0.1662	0.1662	**0.1605**	0.1957	0.1825	0.1890	**0.1728**	0.1746	0.1700	0.1676	**0.1635**
	192	0.2403	0.2265	0.2308	**0.2231**	0.2309	0.2167	0.2229	**0.2114**	0.2239	0.2129	0.2165	**0.2103**	0.2406	0.2238	0.2293	**0.2171**	0.2188	0.2119	0.2120	**0.2050**
	336	0.2918	0.2726	0.2776	**0.2717**	0.2842	0.2661	0.2720	**0.2621**	0.2806	0.2629	0.2672	**0.2618**	0.2921	0.2729	0.2785	**0.2665**	0.2771	0.2659	0.2703	**0.2570**
	720	0.3643	0.3509	0.3557	**0.3426**	0.3599	0.3423	0.3550	**0.3376**	0.3563	0.3418	0.3470	**0.3357**	0.3645	0.3467	0.3598	**0.3401**	0.3555	0.3356	0.3529	**0.3341**
Exchange	96	0.0913	**0.0875**	0.0898	0.0875	0.0828	**0.0796**	0.0825	0.0810	0.0882	0.0873	0.0881	**0.0867**	0.0814	0.0799	0.0813	**0.0793**	0.0854	0.0816	0.0850	**0.0813**
	192	0.1827	**0.1732**	0.1787	0.1758	0.1734	**0.1654**	0.1729	0.1667	0.1841	0.1800	0.1820	**0.1773**	0.1727	0.1650	0.1719	**0.1648**	0.1774	**0.1666**	0.1765	0.1692
	336	0.3277	0.3052	0.3154	**0.2985**	0.3241	0.3180	0.3223	**0.3166**	0.3157	0.3014	0.3105	**0.2983**	0.3225	**0.2846**	0.3058	0.2924	0.3382	0.3048	0.3188	**0.3011**

Note. FAC denotes our proposed method. For PatchTST, TAFAS† follows the official PatchTST-specific implementation, using single-channel output calibration and bypassing input calibration. FAC instead uses the same input and output FreqGCM design as for the other source forecasters. Thus, the two methods are not architecturally identical, although both are evaluated under the same matured-only supervision protocol. PETSA uses multivariate calibration on PatchTST to match its frequency-domain and distributional adaptation objectives over multivariate forecasts.

Table 1 reports the MSE results from one experimental run for each forecasting setting. To assess robustness to adaptation randomness, we repeat each matched setting with five adaptation seeds while fixing the source-forecaster checkpoint, with the resulting means and standard deviations reported in Appendix A.1.

Overall, FAC achieves the best or second-best performance in most settings and often outperforms TAFAS and PETSA under the same protocol using only matured ground truth. In addition, all three adaptation methods generally improve over the frozen source forecaster, indicating that matured ground truth can serve as an effective adaptation signal for TSF-TTA. Consistent with these observations, dataset-wise MSE mean±standard deviation summaries show that FAC achieves the lowest average MSE on five of the six datasets, while paired Wilcoxon tests indicate statistically significant improvements over the frozen source forecaster and PETSA on all six datasets and over TAFAS on four; full results are provided in Appendix A.1.

We further examine whether FAC remains effective on datasets with larger numbers of variables. Table 2 summarizes the additional results on Electricity and Traffic.

Table 2: Summary of additional results on Electricity and Traffic over the common comparison set, comprising all 12 Electricity settings and the nine Traffic settings with $H \in \{96, 192, 336\}$. The MSE columns report averages of the setting-level mean MSEs across the included model–horizon settings of each dataset. "Wins (S/T/P)" denotes the number of included settings in which FAC achieves lower MSE than the frozen source forecaster, TAFAS, and PETSA, respectively. Lower MSE is better.

Dataset	# Settings	Source	TAFAS	PETSA	FAC	Wins (S/T/P)
Electricity	12	0.2137	0.2104	0.2122	**0.2078**	10/12, 10/12, 12/12
Traffic	9	0.5196	0.5160	0.5158	**0.5111**	9/9, 9/9, 9/9

Across the 21 settings in Table 2, FAC achieves lower MSE than the frozen source forecaster and TAFAS in 19 settings each, and lower MSE than PETSA in all 21 settings. FAC also outperforms all three alternatives in all nine summarized Traffic settings. The three Traffic settings at $H = 720$ are reported separately to maintain a common comparison set across source forecasters, since TAFAS exceeds the available GPU memory for FreTS and iTransformer. At $H = 720$, FAC achieves the lowest available MSE for FreTS and iTransformer and ties PETSA for DLinear at the reported precision. Overall, these results show that FAC remains effective on datasets with larger numbers of variables and across the additional energy and transportation domains. All available setting-level results, including means and standard deviations over five adaptation seeds, are provided in Appendix A.2.

5.2.2 Parameter and Runtime Efficiency

Table 3: Trainable parameter counts of different test-time adapters. For TAFAS, we report both the standard count and the PatchTST-specific count, since TAFAS uses channel dimension 1 for PatchTST but the number of variables C for other backbones. The smallest count in each row is highlighted in red bold, and the second smallest is underlined.

Dataset	H	TAFAS	TAFAS (PatchTST)	PETSA	FAC (Ours)
ETT (h1/2, m1/2)	96	130,382	18,626	25,934	**2,758**
	192	324,590	46,370	38,894	**4,102**
	336	857,822	122,546	58,334	**6,118**
	720	3,699,038	528,434	110,174	**11,494**
Weather	96	391,146	18,626	71,658	**8,274**
	192	973,770	46,370	107,466	**12,306**
	336	2,573,466	122,546	161,178	**18,354**
	720	11,097,114	528,434	304,410	**34,482**
Exchange	96	149,008	18,626	29,200	**3,152**
	192	370,960	46,370	43,792	**4,688**
	336	980,368	122,546	65,680	**6,992**

Besides forecasting error, parameter efficiency is a central consideration when designing a test-time adapter. This consideration is particularly relevant in larger-scale forecasting settings, where memory constraints may limit the applicability of some adaptation methods, as observed in the Traffic experiments reported in Appendix A.2. A direct way to measure parameter efficiency is to compare the number of trainable parameters in the calibration modules. Table 3 reports the trainable parameter counts of different adapters under our experimental settings. FAC consistently requires the fewest trainable parameters across datasets and horizons.

Table 4 summarizes how the adapter size scales with the look-back length L, prediction horizon H, number of variables C, and PETSA rank r. TAFAS scales quadratically with the sequence lengths due to its dense temporal calibration, whereas PETSA achieves rank-dependent linear scaling through low-rank adapters. FAC instead uses an element-wise frequency-domain affine parameterization, yielding linear scaling in C, L, and H without the rank factor.

Table 4: Parameter scaling of different test-time adapters.

Adapter	Parameter scaling
TAFAS	$O\big(C(L^2 + H^2)\big)$
TAFAS (PatchTST)	$O\big(L^2 + H^2\big)$
PETSA	$O(Cr(L + H))$
FAC (Ours)	$O(C(L + H))$

Trainable parameter count and wall-clock efficiency should be distinguished. Although FAC requires substantially fewer trainable parameters, this parameter efficiency does not always translate into lower wall-clock runtime under our current implementation. As detailed in Appendix A.6, FAC is not uniformly faster than TAFAS. The additional rFFT/iFFT operations and tensor transformations required by the current implementation likely contribute to the observed runtime overhead. This difference is particularly pronounced for PatchTST, where TAFAS uses its PatchTST-specific implementation with single-channel output calibration and bypasses input calibration, whereas FAC retains both input and output FreqGCMs.

5.3 Analysis

We further analyze two aspects of our design: whether POGT is necessary for effective adaptation, and how different adapters modify predictions in the frequency domain. The first analysis examines the role of supervision timing, while the second characterizes the structure of adaptation-induced corrections.

5.3.1 Is POGT Necessary for Effective Adaptation?

We first compare the original mixed-supervision TAFAS protocol with a matured-only variant to assess whether POGT provides a consistent empirical benefit. As shown in Table 5, the original TAFAS protocol often achieves slightly lower MSE, but the variant using matured ground truth remains close across source forecasters and prediction horizons. These results show that POGT is not consistently necessary for effective adaptation. Together with the protocol-level motivation, this supports using the matured-GT variant as a cleaner protocol for our main experiments. Complete results for TAFAS are provided in Appendix A.4.

Table 5: Original TAFAS vs. matured-only TAFAS on ETTh1. Lower MSE is better. The better result in each pair is highlighted in red bold.

H	DLinear		FreTS		iTransformer		OLS		PatchTST	
	Orig.	Matured	Orig.	Matured	Orig.	Matured	Orig.	Matured	Orig.	Matured
96	0.4618	**0.4617**	0.4394	**0.4391**	**0.4398**	0.4421	**0.4419**	0.4428	**0.4261**	0.4270
192	0.5117	**0.5112**	**0.4940**	0.4943	**0.5017**	0.5020	**0.4924**	0.4929	**0.4809**	0.4818
336	0.5604	**0.5595**	**0.5475**	0.5483	0.5643	**0.5624**	**0.5415**	0.5427	**0.5501**	0.5506
720	**0.6820**	0.6926	0.6872	**0.6857**	**0.6591**	0.6755	**0.6654**	0.6704	0.6815	**0.6807**

5.3.2 Frequency-Domain Behavior of Prediction Corrections

We further examine how different adapters modify the forecast in the frequency domain. We first characterize the frequency-domain structure of the induced prediction corrections, without directly measuring forecasting error. Specifically, we compute the difference between predictions before and after adaptation, apply rFFT along the forecasting horizon, and average the correction magnitude over samples and channels.

Figure 4 illustrates the resulting correction spectra for representative dataset–forecaster pairs at forecasting horizon $H = 720$, with more comprehensive results across horizons deferred to Appendix A.7. As shown in the figure, TAFAS and PETSA often produce relatively smooth frequency-domain corrections, with magnitudes changing gradually across frequencies. In contrast, FAC exhibits more localized peaks, showing that its corrections are more selective with respect to specific frequency components. This behavior is consistent with the motivation of FAC: by directly applying an element-wise complex affine mask in the frequency domain, FAC allows individual Fourier components to be adjusted separately, which can naturally lead to

Figure 4: Frequency-domain magnitude of prediction corrections under the matured-only protocol for forecasting horizon $H = 720$. The plotted spectra are computed from the differences between predictions after and before adaptation. The x-axis denotes frequency, while the y-axis shows the correction magnitude on a logarithmic scale. The figure characterizes adaptation-induced corrections rather than forecasting error; a larger magnitude does not necessarily indicate a more accurate forecast.

more localized spectral corrections. Therefore, the observed peaks should be interpreted as evidence of frequency-selective adaptation rather than as a direct measure of forecasting accuracy; a larger correction magnitude does not necessarily imply a more accurate forecast.

To examine whether these frequency-selective corrections correspond to forecasting improvements, we further measure residual-error reduction within low-, middle-, and high-frequency bands. We partition the one-sided rFFT frequency range into three contiguous equal-width bands over normalized frequency: $[0, 1/6)$, $[1/6, 1/3)$, and $[1/3, 1/2]$, respectively. Table 6 reports the resulting within-band reduction rates.

Table 6: Within-band residual-error reduction rates (%) for representative settings at $H = 720$. The Total column reports the reduction in residual energy over the complete frequency range. Higher values indicate larger error reduction. Within each setting, the best result in each column is highlighted in bold.

Setting	Method	Low	Middle	High	Total
ETTh1 + DLinear	TAFAS	2.930	0.110	0.170	2.692
	PETSA	2.730	0.220	0.400	2.524
	FAC	**3.300**	**2.570**	**0.780**	**3.183**
ETTh2 + FreTS	TAFAS	7.890	0.120	0.070	7.392
	PETSA	3.900	0.080	0.050	3.657
	FAC	**8.260**	**3.640**	**5.330**	**8.015**
ETTm1 + iTransformer	TAFAS	7.620	0.460	0.610	7.350
	PETSA	6.970	0.280	0.380	6.709
	FAC	**9.590**	**2.930**	**4.770**	**9.360**
ETTm2 + OLS	TAFAS	2.370	**0.045**	**0.037**	2.290
	PETSA	2.130	0.027	0.005	2.058
	FAC	**3.140**	0.017	0.017	**3.031**

The DC component is retained in the low-frequency band so that the three bands cover the complete residual spectral energy. For a prediction $\hat{\mathbf{Y}}$, let $E_b(\hat{\mathbf{Y}})$ denote its residual spectral energy in frequency band b, computed from the difference between the prediction and the corresponding forecasting target. We define the within-band error-reduction rate as

$$R_b = 100 \times \frac{E_b(\hat{\mathbf{Y}}) - E_b(\hat{\mathbf{Y}}^{\mathrm{adp}})}{E_b(\hat{\mathbf{Y}})}. \tag{19}$$

Positive values indicate residual-error reduction within band b.

As shown in Table 6, FAC achieves the largest total residual-error reduction in all four representative settings. It also yields substantially larger middle- and high-frequency reduction rates in the first three settings, consistent with the localized correction spectra in Figure 4. For ETTm2 with OLS, however, the middle- and high-frequency reductions remain small for all methods, and the overall improvement is driven primarily by the low-frequency band. These results indicate that FAC's frequency-selective corrections are associated with error reduction in the corresponding frequency bands, although the effect depends on the spectral structure of each forecasting setting.

The corresponding additive decomposition of total residual-error reduction across frequency bands is provided in Appendix A.8.

6 Conclusions, Limitations, and Future Work

Conclusions. We re-examine the adaptation protocols employed by existing TSF-TTA methods. Specifically, we revisit the mixed-supervision protocol that incorporates both POGT and matured ground truth, as well as the streaming adaptation protocol based on revealed targets, and discuss their potential protocol-level limitations. To enhance protocol cleanliness, we propose a more principled adaptation protocol that uses only matured ground truth. We further diagnose existing adapters in the frequency domain and propose FAC, a lightweight adapter that directly parameterizes prediction corrections in the frequency domain. Experimental results demonstrate that FAC achieves competitive and consistent forecasting performance across diverse settings while requiring substantially fewer trainable parameters.

Limitations. As discussed in Section 5.2.2 and detailed in Appendix A.6, FAC is not uniformly faster than TAFAS under our current implementation. The additional rFFT/iFFT operations and tensor transformations required by FAC likely contribute to the observed runtime overhead in some settings.

Although the additional experiments on Electricity and Traffic broaden the coverage of variable counts and application domains, our evaluation remains within the standard multivariate LTSF setting and does not cover the broader range of domains, frequencies, and forecasting tasks represented in benchmarks such as GIFT-Eval (Aksu et al., 2024).

Future Work. Future work could explore more flexible matured-supervision implementations that do not require waiting for the entire mini-batch to mature before using individual samples whose full target horizons have already matured. Another direction is to use multiple available matured mini-batches, as allowed by Eq. 15, instead of only the most recent one. When multiple matured mini-batches are used, cached frequency-domain representations of historical matured mini-batches may help reduce repeated FFT computations and enhance the runtime efficiency of frequency-aware adaptation. More generally, reducing redundant tensor transformations and other implementation overhead may further improve the wall-clock efficiency of FAC. Beyond these protocol and efficiency directions, the proposed protocol and FAC could be evaluated across a broader collection of datasets, forecasting settings, and adaptation objectives.

The present work instantiates FAC for deterministic point forecasting with an MSE adaptation loss; future work could explore other point-forecasting losses such as MAE or stabilized MAPE, as well as extensions to probabilistic or quantile forecasting, which would require additional design for distributional or multi-quantile outputs. Another useful direction is to characterize more systematically how FAC's effectiveness and learned corrections vary with the temporal and spectral structure of the data. Together, these directions could make adaptation based on matured ground truth more broadly applicable, timely, and efficient while preserving the cleanliness of the proposed protocol.

References

Taha Aksu, Gerald Woo, Juncheng Liu, Xu Liu, Chenghao Liu, Silvio Savarese, Caiming Xiong, and Doyen Sahoo. Gift-eval: A benchmark for general time series forecasting model evaluation, 2024. URL `https://arxiv.org/abs/2410.10393`.

Yuntao Du, Jindong Wang, Wenjie Feng, Sinno Pan, Tao Qin, Renjun Xu, and Chongjun Wang. Adarnn: Adaptive learning and forecasting of time series. In *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, CIKM '21, pp. 402–411, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450384469. doi: 10.1145/3459637.3482315. URL `https://doi.org/10.1145/3459637.3482315`.

Wei Fan, Pengyang Wang, Dongkun Wang, Dongjie Wang, Yuanchun Zhou, and Yanjie Fu. Dish-ts: A general paradigm for alleviating distribution shift in time series forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 37(6):7522–7529, Jun. 2023. doi: 10.1609/aaai.v37i6.25914. URL `https://ojs.aaai.org/index.php/AAAI/article/view/25914`.

Taesik Gong, Yewon Kim, Taeckyung Lee, Sorn Chottananurak, and Sung-Ju Lee. SoTTA: Robust test-time adaptation on noisy data streams. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=3bdXag2rUd`.

Clive W. J. Granger. Time series concepts for conditional distributions. *Oxford Bulletin of Economics and Statistics*, 65(s1):689–701, 2003. doi: 10.1046/j.0305-9049.2003.00094.x. URL `https://onlinelibrary.wiley.com/doi/abs/10.1046/j.0305-9049.2003.00094.x`.

Shivam Grover and Ali Etemad. Shift-aware test time adaptation and benchmarking for time-series forecasting. In *Second Workshop on Test-Time Adaptation: Putting Updates to the Test! at ICML 2025*, 2025. URL `https://openreview.net/forum?id=a399SmgWGl`.

Xiannan Huang, Shuhan Qiu, Jiayuan Du, and Chao Yang. Online time series prediction using feature adjustment. In *The Fourteenth International Conference on Learning Representations*, 2026. URL `https://openreview.net/forum?id=s4U2FWEMTU`.

Jeonghwan Im and Hyuk-Yoon Kwon. COSA: Context-aware output-space adapter for test-time adaptation in time series forecasting. In *The Fourteenth International Conference on Learning Representations*, 2026. URL `https://openreview.net/forum?id=L7Z5wBMPrW`.

Hyeongyu Kim, GeonHui Han, and Dosik Hwang. Buffer layers for test-time adaptation. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*, 2026. URL `https://openreview.net/forum?id=sSZ9OM08KT`.

HyunGi Kim, Siwon Kim, Jisoo Mok, and Sungroh Yoon. Battling the non-stationarity in time series forecasting via test-time adaptation. *Proceedings of the AAAI Conference on Artificial Intelligence*, 39 (17):17868–17876, Apr. 2025. doi: 10.1609/aaai.v39i17.33965. URL `https://ojs.aaai.org/index.php/AAAI/article/view/33965`.

Taesung Kim, Jinhee Kim, Yunwon Tae, Cheonbok Park, Jang-Ho Choi, and Jaegul Choo. Reversible instance normalization for accurate time-series forecasting against distribution shift. In *International Conference on Learning Representations*, 2022. URL `https://openreview.net/forum?id=cGDAkQo1COp`.

Kelvin J.L. Koa, Jan Chen, Yunshan Ma, Huanhuan Zheng, and Tat-Seng Chua. Reasoning on time-series for financial technical analysis. In *The Fourteenth International Conference on Learning Representations*, 2026. URL `https://openreview.net/forum?id=PcjIe5xNaY`.

Ying-yee Ava Lau, Zhiwen Shao, and Dit-Yan Yeung. Fast and slow streams for online time series forecasting without information leakage. In *The Thirteenth International Conference on Learning Representations*, 2025. URL `https://openreview.net/forum?id=I0n3EyogMi`.

Daojun Liang, Haixia Zhang, Jing Wang, Dongfeng Yuan, and Minggao Zhang. Act now: A novel online forecasting framework for large-scale streaming data. *arXiv preprint arXiv:2412.00108*, 2024. URL `https://arxiv.org/abs/2412.00108`.

Jian Liang, Ran He, and Tieniu Tan. A comprehensive survey on test-time adaptation under distribution shifts. *International Journal of Computer Vision*, 133(1):31–64, 2025. doi: 10.1007/s11263-024-02181-w. URL `https://doi.org/10.1007/s11263-024-02181-w`.

Yong Liu, Tengge Hu, Haoran Zhang, Haixu Wu, Shiyu Wang, Lintao Ma, and Mingsheng Long. itransformer: Inverted transformers are effective for time series forecasting. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=JePfAI8fah`.

Zhiding Liu, Mingyue Cheng, Zhi Li, Zhenya Huang, Qi Liu, Yanhu Xie, and Enhong Chen. Adaptive normalization for non-stationary time series forecasting: A temporal slice perspective. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=5BqDSw8r5j`.

Neda Maleki, Oxana Lundström, Arslan Musaddiq, John Jeansson, Tobias Olsson, and Fredrik Ahlgren. Future energy insights: Time-series and deep learning models for city load forecasting. *Applied Energy*, 374: 124067, 2024. doi: 10.1016/j.apenergy.2024.124067. URL `https://www.sciencedirect.com/science/article/pii/S0306261924014508`.

Heitor Rapela Medeiros, Hossein Sharifi-Noghabi, Gabriel L. Oliveira, and Saghar Irandoust. Accurate parameter-efficient test-time adaptation for time series forecasting. In *Second Workshop on Test-Time Adaptation: Putting Updates to the Test! at ICML 2025*, 2025. URL `https://openreview.net/forum?id=uFj4EL4GTB`.

Yuqi Nie, Nam H Nguyen, Phanwadee Sinthong, and Jayant Kalagnanam. A time series is worth 64 words: Long-term forecasting with transformers. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=Jbdc0vTOcol`.

Quang Pham, Chenghao Liu, Doyen Sahoo, and Steven Hoi. Learning fast and slow for online time series forecasting. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=q-PbpHD3EOk`.

William Toner and Luke Nicholas Darlow. An analysis of linear time series forecasting models. In *Forty-first International Conference on Machine Learning*, 2024. URL `https://openreview.net/forum?id=xl82CcbYaT`.

Ruey S. Tsay. *Analysis of Financial Time Series*. John Wiley & Sons, 3 edition, 2010. ISBN 9780470414354. doi: 10.1002/9780470644560.

Yogesh Verma, Markus Heinonen, and Vikas Garg. ClimODE: Climate and weather forecasting with physics-informed neural ODEs. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=xuY33XhEGR`.

Dequan Wang, Evan Shelhamer, Shaoteng Liu, Bruno Olshausen, and Trevor Darrell. Tent: Fully test-time adaptation by entropy minimization. In *International Conference on Learning Representations*, 2021. URL `https://openreview.net/forum?id=uXl3bZLkr3c`.

Huiqiang Wang, Jian Peng, Feihu Huang, Jince Wang, Junhui Chen, and Yifei Xiao. MICN: Multi-scale local and global context modeling for long-term series forecasting. In *The Eleventh International Conference on Learning Representations*, 2023. URL `https://openreview.net/forum?id=zt53IDUR1U`.

Qin Wang, Olga Fink, Luc Van Gool, and Dengxin Dai. Continual test-time domain adaptation. In *2022 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 7191–7201, 2022. doi: 10.1109/CVPR52688.2022.00706.

Haixu Wu, Hang Zhou, Mingsheng Long, and Jianmin Wang. Interpretable weather forecasting for worldwide stations with a unified deep model. *Nature Machine Intelligence*, 5(6):602–611, 2023. doi: 10.1038/ s42256-023-00667-9. URL `https://doi.org/10.1038/s42256-023-00667-9`.

Kun Yi, Qi Zhang, Wei Fan, Shoujin Wang, Pengyang Wang, Hui He, Ning An, Defu Lian, Longbing Cao, and Zhendong Niu. Frequency-domain MLPs are more effective learners in time series forecasting. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview. net/forum?id=iif9mGCTfy`.

Xueyan Yin, Genze Wu, Jinze Wei, Yanming Shen, Heng Qi, and Baocai Yin. Deep learning on traffic prediction: Methods, analysis, and future directions. *IEEE Transactions on Intelligent Transportation Systems*, 23(6), 2022.

Ailing Zeng, Muxi Chen, Lei Zhang, and Qiang Xu. Are transformers effective for time series forecasting? *Proceedings of the AAAI Conference on Artificial Intelligence*, 37(9):11121–11128, Jun. 2023. doi: 10. 1609/aaai.v37i9.26317. URL `https://ojs.aaai.org/index.php/AAAI/article/view/26317`.

Weijia Zhang, Le Zhang, Jindong Han, Hao Liu, Yanjie Fu, Jingbo Zhou, Yu Mei, and Hui Xiong. Irregular traffic time series forecasting based on asynchronous spatio-temporal graph convolutional networks. In *Proceedings of the 30th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, KDD '24, pp. 4302–4313, New York, NY, USA, 2024. Association for Computing Machinery. ISBN 9798400704901. doi: 10.1145/3637528.3671665. URL `https://doi.org/10.1145/3637528.3671665`.

Yi-Fan Zhang, Qingsong Wen, Xue Wang, Weiqi Chen, Liang Sun, Zhang Zhang, Liang Wang, Rong Jin, and Tieniu Tan. Onenet: Enhancing time series forecasting models under concept drift by online ensembling. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview. net/forum?id=Q25wMXsaeZ`.

Haoyi Zhou, Shanghang Zhang, Jieqi Peng, Shuai Zhang, Jianxin Li, Hui Xiong, and Wancai Zhang. Informer: Beyond efficient transformer for long sequence time-series forecasting. *Proceedings of the AAAI Conference on Artificial Intelligence*, 35(12):11106–11115, May 2021. doi: 10.1609/aaai.v35i12.17325. URL `https: //ojs.aaai.org/index.php/AAAI/article/view/17325`.

A Additional Experimental Results

A.1 Statistical Significance Analysis

We evaluate the consistency of the results in Table 1 using matched forecasting settings. For every dataset, source forecaster, forecasting horizon, and adaptation method, we repeat test-time adaptation with five random seeds while keeping the source-forecaster checkpoint fixed. Each setting is represented by its five-seed mean for statistical testing, and all comparisons are computed using full-precision values before rounding.

Tables A.1–A.3 report the complete setting-level results. Source gives the fixed source-forecaster MSE, while TAFAS, PETSA, and FAC are reported as MSE mean±standard deviation over five adaptation seeds. The lowest five-seed mean MSE in each setting is highlighted in bold.

Table A.1: Setting-level MSE results for DLinear and FreTS.

DLinear					
Dataset	H	Source	TAFAS	PETSA	FAC
ETTh1	96	0.4695	0.4617 ± 0.0000	0.4613 ± 0.0002	**0.4554 ± 0.0000**
	192	0.5213	0.5112 ± 0.0000	0.5121 ± 0.0003	**0.5089 ± 0.0000**
	336	0.5659	0.5595 ± 0.0000	0.5620 ± 0.0004	**0.5582 ± 0.0000**
	720	0.7117	0.6926 ± 0.0000	0.6932 ± 0.0005	**0.6891 ± 0.0000**
ETTh2	96	0.2323	0.2308 ± 0.0000	0.2312 ± 0.0001	**0.2288 ± 0.0000**
	192	0.2862	0.2830 ± 0.0000	0.2820 ± 0.0001	**0.2819 ± 0.0000**
	336	0.3252	0.3175 ± 0.0000	0.3190 ± 0.0000	**0.3144 ± 0.0000**
	720	0.4087	**0.3825 ± 0.0000**	0.3883 ± 0.0002	**0.3825 ± 0.0000**
ETTm1	96	0.3715	0.3504 ± 0.0000	0.3544 ± 0.0003	**0.3465 ± 0.0000**
	192	0.4438	0.4165 ± 0.0000	0.4197 ± 0.0003	**0.4139 ± 0.0000**
	336	0.5183	0.4801 ± 0.0000	0.4831 ± 0.0003	**0.4791 ± 0.0000**
	720	0.5929	0.5521 ± 0.0000	0.5598 ± 0.0005	**0.5494 ± 0.0000**
ETTm2	96	0.1598	0.1581 ± 0.0000	0.1583 ± 0.0001	**0.1560 ± 0.0000**
	192	0.1930	0.1917 ± 0.0000	0.1919 ± 0.0001	**0.1894 ± 0.0000**
	336	0.2324	0.2299 ± 0.0000	0.2304 ± 0.0001	**0.2286 ± 0.0000**
	720	0.3062	0.2993 ± 0.0000	0.2989 ± 0.0005	**0.2984 ± 0.0000**
Weather	96	0.1954	0.1803 ± 0.0000	0.1814 ± 0.0005	**0.1797 ± 0.0000**
	192	0.2403	0.2265 ± 0.0000	0.2308 ± 0.0003	**0.2231 ± 0.0000**
	336	0.2918	0.2726 ± 0.0000	0.2776 ± 0.0001	**0.2717 ± 0.0000**
	720	0.3643	0.3509 ± 0.0000	0.3559 ± 0.0004	**0.3426 ± 0.0000**
Exchange	96	0.0913	**0.0875 ± 0.0000**	0.0899 ± 0.0001	**0.0875 ± 0.0000**
	192	0.1827	**0.1732 ± 0.0000**	0.1786 ± 0.0003	0.1758 ± 0.0000
	336	0.3277	0.3052 ± 0.0000	0.3148 ± 0.0005	**0.2985 ± 0.0000**

FreTS					
Dataset	H	Source	TAFAS	PETSA	FAC
ETTh1	96	0.4461	0.4391 ± 0.0000	0.4380 ± 0.0004	**0.4357 ± 0.0000**
	192	0.5022	0.4943 ± 0.0000	0.4964 ± 0.0003	**0.4934 ± 0.0000**
	336	0.5544	**0.5483 ± 0.0000**	0.5529 ± 0.0002	0.5498 ± 0.0000
	720	0.7181	**0.6857 ± 0.0000**	0.6906 ± 0.0010	0.7067 ± 0.0000
ETTh2	96	0.2385	0.2363 ± 0.0000	0.2365 ± 0.0001	**0.2338 ± 0.0000**
	192	0.2867	0.2830 ± 0.0000	0.2845 ± 0.0001	**0.2814 ± 0.0000**
	336	0.3318	0.3195 ± 0.0000	0.3249 ± 0.0002	**0.3172 ± 0.0000**
	720	0.4118	0.3814 ± 0.0000	0.3967 ± 0.0006	**0.3788 ± 0.0000**
ETTm1	96	0.3676	0.3559 ± 0.0000	0.3566 ± 0.0005	**0.3517 ± 0.0000**
	192	0.4325	0.4191 ± 0.0000	0.4192 ± 0.0003	**0.4183 ± 0.0000**
	336	0.5006	0.4810 ± 0.0000	**0.4794 ± 0.0002**	0.4836 ± 0.0000
	720	0.5703	**0.5472 ± 0.0000**	0.5523 ± 0.0002	0.5533 ± 0.0000
ETTm2	96	0.1582	0.1566 ± 0.0000	0.1568 ± 0.0001	**0.1563 ± 0.0000**
	192	0.1923	**0.1901 ± 0.0000**	0.1908 ± 0.0001	**0.1901 ± 0.0000**
	336	0.2320	**0.2291 ± 0.0000**	0.2312 ± 0.0001	0.2294 ± 0.0000
	720	0.3013	**0.2924 ± 0.0000**	0.2983 ± 0.0002	0.2955 ± 0.0000
Weather	96	0.1855	0.1757 ± 0.0000	0.1791 ± 0.0002	**0.1678 ± 0.0000**
	192	0.2309	0.2167 ± 0.0000	0.2232 ± 0.0003	**0.2114 ± 0.0000**
	336	0.2842	0.2661 ± 0.0000	0.2720 ± 0.0002	**0.2621 ± 0.0000**
	720	0.3599	0.3423 ± 0.0000	0.3550 ± 0.0003	**0.3376 ± 0.0000**
Exchange	96	0.0828	**0.0796 ± 0.0000**	0.0819 ± 0.0001	0.0810 ± 0.0000
	192	0.1734	**0.1654 ± 0.0000**	0.1716 ± 0.0001	0.1667 ± 0.0000
	336	0.3241	0.3180 ± 0.0000	0.3171 ± 0.0007	**0.3166 ± 0.0000**

Table A.2: Setting-level MSE results for iTransformer and OLS.

Dataset	H	Source	TAFAS	PETSA	FAC
iTransformer					
ETTh1	96	0.4482	0.4423 ± 0.0001	$\mathbf{0.4397 \pm 0.0004}$	0.4401 ± 0.0002
	192	0.5091	0.5020 ± 0.0001	0.5011 ± 0.0003	$\mathbf{0.5010 \pm 0.0002}$
	336	0.5662	0.5625 ± 0.0001	0.5642 ± 0.0003	$\mathbf{0.5589 \pm 0.0002}$
	720	0.7007	0.6753 ± 0.0003	0.6768 ± 0.0008	$\mathbf{0.6684 \pm 0.0004}$
ETTh2	96	0.2642	0.2620 ± 0.0001	0.2599 ± 0.0003	$\mathbf{0.2557 \pm 0.0006}$
	192	0.3081	0.3006 ± 0.0002	0.3006 ± 0.0001	$\mathbf{0.2972 \pm 0.0003}$
	336	0.3402	$\mathbf{0.3289 \pm 0.0001}$	0.3313 ± 0.0001	0.3290 ± 0.0012
	720	0.4261	$\mathbf{0.3959 \pm 0.0001}$	0.4051 ± 0.0004	0.3999 ± 0.0017
ETTm1	96	0.3823	0.3681 ± 0.0001	0.3697 ± 0.0004	$\mathbf{0.3456 \pm 0.0004}$
	192	0.4407	0.4191 ± 0.0001	0.4189 ± 0.0003	$\mathbf{0.4089 \pm 0.0001}$
	336	0.5077	0.4798 ± 0.0002	0.4789 ± 0.0004	$\mathbf{0.4780 \pm 0.0002}$
	720	0.6021	0.5579 ± 0.0001	0.5615 ± 0.0005	$\mathbf{0.5459 \pm 0.0001}$
ETTm2	96	0.1647	0.1640 ± 0.0000	0.1640 ± 0.0001	$\mathbf{0.1608 \pm 0.0003}$
	192	0.2189	0.2164 ± 0.0001	0.2155 ± 0.0003	$\mathbf{0.2065 \pm 0.0003}$
	336	0.2808	0.2734 ± 0.0002	0.2669 ± 0.0017	$\mathbf{0.2619 \pm 0.0010}$
	720	0.3457	0.3300 ± 0.0001	$\mathbf{0.3256 \pm 0.0004}$	0.3291 ± 0.0010
Weather	96	0.1724	0.1662 ± 0.0001	0.1661 ± 0.0001	$\mathbf{0.1607 \pm 0.0002}$
	192	0.2239	0.2130 ± 0.0001	0.2163 ± 0.0004	$\mathbf{0.2102 \pm 0.0001}$
	336	0.2806	0.2627 ± 0.0001	0.2668 ± 0.0002	$\mathbf{0.2617 \pm 0.0002}$
	720	0.3563	0.3419 ± 0.0001	0.3472 ± 0.0002	$\mathbf{0.3357 \pm 0.0003}$
Exchange	96	0.0882	0.0873 ± 0.0001	0.0881 ± 0.0001	$\mathbf{0.0869 \pm 0.0004}$
	192	0.1841	0.1801 ± 0.0001	0.1820 ± 0.0001	$\mathbf{0.1776 \pm 0.0001}$
	336	0.3157	0.3009 ± 0.0002	0.3108 ± 0.0003	$\mathbf{0.2965 \pm 0.0029}$
OLS					
ETTh1	96	0.4510	0.4428 ± 0.0000	0.4452 ± 0.0003	$\mathbf{0.4382 \pm 0.0000}$
	192	0.5045	0.4929 ± 0.0000	0.5005 ± 0.0003	$\mathbf{0.4921 \pm 0.0000}$
	336	0.5510	0.5427 ± 0.0000	0.5488 ± 0.0002	$\mathbf{0.5422 \pm 0.0000}$
	720	0.6996	$\mathbf{0.6704 \pm 0.0000}$	0.6805 ± 0.0002	0.6780 ± 0.0000
ETTh2	96	0.2306	0.2289 ± 0.0000	0.2294 ± 0.0001	$\mathbf{0.2274 \pm 0.0000}$
	192	0.2838	0.2821 ± 0.0000	0.2829 ± 0.0000	$\mathbf{0.2796 \pm 0.0000}$
	336	0.3257	0.3189 ± 0.0000	0.3240 ± 0.0001	$\mathbf{0.3137 \pm 0.0000}$
	720	0.4161	0.3859 ± 0.0000	0.3928 ± 0.0002	$\mathbf{0.3854 \pm 0.0000}$
ETTm1	96	0.3709	0.3542 ± 0.0000	0.3599 ± 0.0008	$\mathbf{0.3462 \pm 0.0000}$
	192	0.4437	0.4184 ± 0.0000	0.4255 ± 0.0006	$\mathbf{0.4140 \pm 0.0000}$
	336	0.5179	0.4811 ± 0.0000	0.4893 ± 0.0002	$\mathbf{0.4794 \pm 0.0000}$
	720	0.5923	0.5515 ± 0.0000	0.5595 ± 0.0001	$\mathbf{0.5497 \pm 0.0000}$
ETTm2	96	0.1602	0.1594 ± 0.0000	0.1595 ± 0.0000	$\mathbf{0.1563 \pm 0.0000}$
	192	0.1935	0.1924 ± 0.0000	0.1925 ± 0.0001	$\mathbf{0.1897 \pm 0.0000}$
	336	0.2331	0.2308 ± 0.0000	0.2316 ± 0.0001	$\mathbf{0.2289 \pm 0.0000}$
	720	0.3066	0.2996 ± 0.0000	0.3002 ± 0.0001	$\mathbf{0.2973 \pm 0.0000}$
Weather	96	0.1957	0.1825 ± 0.0000	0.1894 ± 0.0004	$\mathbf{0.1728 \pm 0.0000}$
	192	0.2406	0.2238 ± 0.0000	0.2296 ± 0.0002	$\mathbf{0.2171 \pm 0.0000}$
	336	0.2921	0.2729 ± 0.0000	0.2785 ± 0.0001	$\mathbf{0.2665 \pm 0.0000}$
	720	0.3645	0.3467 ± 0.0000	0.3597 ± 0.0002	$\mathbf{0.3401 \pm 0.0000}$
Exchange	96	0.0814	0.0799 ± 0.0000	0.0811 ± 0.0001	$\mathbf{0.0793 \pm 0.0000}$
	192	0.1727	0.1650 ± 0.0000	0.1708 ± 0.0001	$\mathbf{0.1648 \pm 0.0000}$
	336	0.3225	$\mathbf{0.2846 \pm 0.0000}$	0.2967 ± 0.0006	0.2924 ± 0.0000

Table A.3: Setting-level MSE results for PatchTST.

Dataset	H	Source	TAFAS	PETSA	FAC
			PatchTST		
ETTh1	96	0.4324	0.4270 ± 0.0000	0.4253 ± 0.0002	$\mathbf{0.4242 \pm 0.0000}$
	192	0.4900	0.4818 ± 0.0000	0.4815 ± 0.0001	$\mathbf{0.4797 \pm 0.0001}$
	336	0.5608	$\mathbf{0.5506 \pm 0.0000}$	0.5569 ± 0.0004	0.5525 ± 0.0001
	720	0.7112	$\mathbf{0.6808 \pm 0.0001}$	0.7017 ± 0.0013	0.7092 ± 0.0003
ETTh2	96	0.2385	0.2380 ± 0.0000	0.2383 ± 0.0000	$\mathbf{0.2364 \pm 0.0001}$
	192	0.2840	0.2752 ± 0.0000	0.2807 ± 0.0002	$\mathbf{0.2747 \pm 0.0001}$
	336	0.3233	0.3107 ± 0.0001	0.3188 ± 0.0004	$\mathbf{0.3080 \pm 0.0001}$
	720	0.4292	0.4065 ± 0.0000	0.4202 ± 0.0004	$\mathbf{0.4004 \pm 0.0002}$
ETTm1	96	0.4041	0.3825 ± 0.0001	0.3819 ± 0.0010	$\mathbf{0.3528 \pm 0.0001}$
	192	0.4515	0.4371 ± 0.0001	0.4408 ± 0.0005	$\mathbf{0.4214 \pm 0.0001}$
	336	0.5044	0.4863 ± 0.0000	0.4970 ± 0.0006	$\mathbf{0.4786 \pm 0.0001}$
	720	0.5608	0.5414 ± 0.0001	0.5478 ± 0.0010	$\mathbf{0.5399 \pm 0.0001}$
ETTm2	96	0.1581	0.1569 ± 0.0000	0.1568 ± 0.0001	$\mathbf{0.1558 \pm 0.0001}$
	192	0.2097	0.2058 ± 0.0001	0.2077 ± 0.0001	$\mathbf{0.1977 \pm 0.0001}$
	336	0.2482	0.2482 ± 0.0000	0.2473 ± 0.0000	$\mathbf{0.2423 \pm 0.0001}$
	720	0.3283	0.3218 ± 0.0000	0.3240 ± 0.0003	$\mathbf{0.3193 \pm 0.0004}$
Weather	96	0.1746	0.1701 ± 0.0002	0.1676 ± 0.0004	$\mathbf{0.1635 \pm 0.0000}$
	192	0.2188	0.2118 ± 0.0001	0.2116 ± 0.0002	$\mathbf{0.2051 \pm 0.0001}$
	336	0.2771	0.2659 ± 0.0001	0.2704 ± 0.0005	$\mathbf{0.2571 \pm 0.0001}$
	720	0.3555	0.3354 ± 0.0005	0.3523 ± 0.0015	$\mathbf{0.3338 \pm 0.0002}$
Exchange	96	0.0854	0.0816 ± 0.0000	0.0841 ± 0.0001	$\mathbf{0.0813 \pm 0.0001}$
	192	0.1774	$\mathbf{0.1666 \pm 0.0000}$	0.1739 ± 0.0003	0.1694 ± 0.0001
	336	0.3382	0.3052 ± 0.0004	0.3071 ± 0.0008	$\mathbf{0.3025 \pm 0.0036}$

Across the five adaptation seeds, the run-to-run variation is small in most settings, supporting the stability of the comparisons across adaptation initializations. We next summarize performance within each dataset and evaluate paired significance across matched settings.

Table A.4: Dataset-wise MSE mean±standard deviation across matched source-forecaster and forecasting-horizon settings. Each ETT dataset and Weather contain 20 settings, while Exchange contains 15. The standard deviations characterize variation across forecasting settings. The lowest mean MSE in each row is highlighted in bold.

Dataset	# Settings	Source	TAFAS	PETSA	FAC
ETTh1	20	0.5557 ± 0.0993	$\mathbf{0.5432 \pm 0.0914}$	0.5464 ± 0.0944	0.5441 ± 0.0966
ETTh2	20	0.3196 ± 0.0674	0.3084 ± 0.0574	0.3124 ± 0.0613	$\mathbf{0.3063 \pm 0.0579}$
ETTm1	20	0.4788 ± 0.0790	0.4540 ± 0.0719	0.4578 ± 0.0734	$\mathbf{0.4478 \pm 0.0760}$
ETTm2	20	0.2312 ± 0.0615	0.2273 ± 0.0583	0.2274 ± 0.0581	$\mathbf{0.2245 \pm 0.0585}$
Weather	20	0.2652 ± 0.0674	0.2512 ± 0.0645	0.2565 ± 0.0678	$\mathbf{0.2460 \pm 0.0647}$
Exchange	15	0.1965 ± 0.1024	0.1853 ± 0.0938	0.1899 ± 0.0955	$\mathbf{0.1851 \pm 0.0930}$

FAC achieves the lowest average MSE on five of the six datasets and remains close to the best result on ETTh1.

At the dataset level, paired Wilcoxon tests indicate that FAC yields statistically significant reductions in MSE relative to the frozen source forecaster and PETSA on all six primary datasets. Relative to TAFAS, the reduction is statistically significant on ETTh2, ETTm1, ETTm2, and Weather, but not on ETTh1 or Exchange.

Table A.5: Dataset-wise one-sided paired Wilcoxon signed-rank tests over matched forecasting settings. Each entry reports wins/ties/losses from the perspective of FAC, followed by the corresponding p-value. Statistically significant results at $p < 0.05$ are highlighted in bold.

Dataset	FAC vs. Source	FAC vs. TAFAS	FAC vs. PETSA
ETTh1	**20/0/0, $p = 9.54 \times 10^{-7}$**	15/0/5, $p = 1.01 \times 10^{-1}$	**17/0/3, $p = 6.04 \times 10^{-3}$**
ETTh2	**20/0/0, $p = 9.54 \times 10^{-7}$**	**17/1/2, $p = 8.47 \times 10^{-4}$**	**20/0/0, $p = 9.54 \times 10^{-7}$**
ETTm1	**20/0/0, $p = 9.54 \times 10^{-7}$**	**18/0/2, $p = 3.54 \times 10^{-4}$**	**18/0/2, $p = 2.38 \times 10^{-5}$**
ETTm2	**20/0/0, $p = 9.54 \times 10^{-7}$**	**17/1/2, $p = 6.41 \times 10^{-4}$**	**19/0/1, $p = 1.31 \times 10^{-4}$**
Weather	**20/0/0, $p = 9.54 \times 10^{-7}$**	**20/0/0, $p = 9.54 \times 10^{-7}$**	**20/0/0, $p = 9.54 \times 10^{-7}$**
Exchange	**15/0/0, $p = 3.05 \times 10^{-5}$**	9/1/5, $p = 3.19 \times 10^{-1}$	**15/0/0, $p = 3.05 \times 10^{-5}$**

Table A.6: Aggregate one-sided paired Wilcoxon signed-rank tests across all 115 matched forecasting settings. Wins/ties/losses are reported from the perspective of FAC. This analysis provides complementary aggregate evidence to the dataset-wise tests in Table A.5.

Comparison	Wins/Ties/Losses	Wilcoxon p-value
FAC vs. Source	115/0/0	6.56×10^{-21}
FAC vs. TAFAS	96/3/16	3.50×10^{-11}
FAC vs. PETSA	109/0/6	9.43×10^{-18}

The aggregate results lead to the same conclusion as the dataset-wise analysis. FAC improves over the frozen source forecaster in all 115 matched settings and outperforms PETSA in 109 of 115 settings. Against TAFAS, FAC records 96 wins, 3 ties, and 16 losses. All three aggregate paired Wilcoxon tests are statistically significant, providing strong evidence that the overall improvements are systematic rather than being driven by a small number of forecasting settings.

A.2   Additional Results on Datasets with Larger Numbers of Variables

We report setting-level results on Electricity and Traffic, which broaden the range of variable counts and application domains covered by our primary evaluation. We evaluate DLinear, FreTS, and iTransformer with $H \in \{96, 192, 336, 720\}$ on both datasets. The source-forecaster checkpoint is fixed for each setting, while each completed adaptation method is repeated with five adaptation seeds.

Table A.7: Setting-level MSE results on Electricity and Traffic. Source denotes the fixed source-forecaster checkpoint. When available, TAFAS, PETSA, and FAC are reported as mean ± standard deviation over five adaptation seeds. Lower MSE is better. The best available result in each row is highlighted in bold, and the second-best available result is underlined. Ties at the reported precision are jointly highlighted in bold.

(a) Electricity					
Model	H	Source	TAFAS	PETSA	FAC
DLinear	96	0.2235	0.2171±0.0000	0.2188±0.0001	**0.2096±0.0000**
	192	0.2242	0.2183±0.0000	0.2201±0.0001	**0.2104±0.0000**
	336	0.2383	0.2329±0.0000	0.2357±0.0001	**0.2260±0.0000**
	720	0.2792	0.2795±0.0000	0.2843±0.0001	**0.2746±0.0000**
FreTS	96	0.1806	**0.1738±0.0000**	0.1763±0.0001	0.1758±0.0000
	192	0.1880	0.1820±0.0000	0.1844±0.0001	**0.1819±0.0000**
	336	0.2056	0.1999±0.0000	0.2028±0.0001	**0.1992±0.0000**
	720	**0.2482**	0.2513±0.0000	0.2513±0.0002	0.2491±0.0000
iTransformer	96	0.1662	0.1630±0.0001	0.1640±0.0001	**0.1608±0.0000**
	192	0.1791	**0.1760±0.0000**	0.1771±0.0000	0.1763±0.0000
	336	0.1960	0.1936±0.0000	0.1948±0.0001	**0.1932±0.0001**
	720	**0.2352**	0.2376±0.0000	0.2372±0.0002	0.2366±0.0001

(b) Traffic					
Model	H	Source	TAFAS	PETSA	FAC
DLinear	96	0.6467	0.6423±0.0000	0.6402±0.0001	**0.6289±0.0000**
	192	0.5996	0.5957±0.0000	0.5921±0.0001	**0.5871±0.0000**
	336	0.6071	0.6032±0.0000	0.5985±0.0003	**0.5983±0.0000**
	720	0.6457	0.6438±0.0000	**0.6433±0.0001**	**0.6433±0.0000**
FreTS	96	0.4854	0.4797±0.0000	0.4823±0.0001	**0.4764±0.0000**
	192	0.5065	0.5015±0.0000	0.5033±0.0002	**0.4979±0.0000**
	336	0.5206	0.5162±0.0000	0.5187±0.0002	**0.5160±0.0000**
	720	0.5575	–	0.5606±0.0003	**0.5557±0.0000**
iTransformer	96	0.4164	0.4150±0.0002	0.4145±0.0001	**0.4100±0.0001**
	192	0.4392	0.4372±0.0000	0.4381±0.0003	**0.4344±0.0001**
	336	0.4549	0.4534±0.0001	0.4541±0.0003	**0.4514±0.0000**
	720	0.4965	–	0.4921±0.0006	**0.4862±0.0000**

Note. For Traffic at $H = 720$, TAFAS exceeded the available 24 GB GPU memory for FreTS and iTransformer under the same experimental configuration. The corresponding entries are therefore marked with dashes.

Because two TAFAS entries at Traffic $H = 720$ are unavailable, the aggregate summary in Table 2 and the corresponding win counts in the main text are computed over the 21 settings. Among these settings, FAC achieves the lowest MSE in 17 cases, while its absolute gap from the best result is at most 0.0020 in the remaining four. In the additional Traffic settings at $H = 720$, FAC achieves the lowest available MSE for FreTS and iTransformer and ties PETSA at the reported precision for DLinear.

A.3 Additional Early-versus-Late Comparison

Figure A.1 provides an additional early-versus-late comparison for $B_k = 25$, which is the second most common mini-batch size induced by PAAS in our experiments after $B_k = 97$. Compared with the $B_k = 97$ setting, this smaller mini-batch size gives later samples less additional revealed context, making the comparison relatively more favorable to earlier adjusted predictions. Nevertheless, later direct predictions still generally achieve comparable or lower MSE than the adjusted predictions of earlier samples. This further supports our argument that using revealed values as POGT supervision is not consistently more beneficial than using the same values as input context in later rolling windows.

Figure A.1: Additional early-versus-late comparison with mini-batch size $B_k = 25$ on ETTh1 with DLinear and ETTh2 with FreTS. The curves show the average overlapping-region MSE across sample positions within a mini-batch. The dashed horizontal lines mark the adjusted prediction of the first sample and the direct prediction of the last sample as endpoint references.

A.4 Effect of Using Only Matured Ground Truth

Table A.8 provides the full comparison between the original TAFAS protocol and its variant using only matured ground truth. The original TAFAS protocol, which incorporates POGT through mixed supervision, often achieves slightly lower MSE. However, this advantage is not consistent across datasets, horizons, and source forecasters, and the matured-only variant remains close in most settings. These results complement the analysis in the main text and demonstrate that removing POGT-based supervision does not lead to substantial performance degradation, while yielding a cleaner adaptation protocol.

Table A.8: Original TAFAS versus its variant using only matured ground truth across datasets and source forecasters. Lower MSE is highlighted within each original/matured pair.

Dataset	Horizon	DLinear		FreTS		iTransformer		OLS		PatchTST	
		Orig.	Matured	Orig.	Matured	Orig.	Matured	Orig.	Matured	Orig.	Matured
ETTh1	96	0.4618	**0.4617**	0.4394	**0.4391**	**0.4398**	0.4421	**0.4419**	0.4428	**0.4261**	0.4270
	192	0.5117	**0.5112**	**0.4940**	0.4943	**0.5017**	0.5020	**0.4924**	0.4929	**0.4809**	0.4818
	336	0.5604	**0.5595**	**0.5475**	0.5483	0.5643	**0.5624**	**0.5415**	0.5427	**0.5501**	0.5506
	720	**0.6820**	0.6926	0.6872	**0.6857**	**0.6591**	0.6755	**0.6654**	0.6704	0.6815	**0.6807**
ETTh2	96	**0.2303**	0.2308	**0.2362**	0.2363	**0.2613**	0.2620	**0.2284**	0.2289	**0.2378**	0.2380
	192	0.2842	**0.2830**	**0.2828**	0.2830	**0.2984**	0.3004	**0.2817**	0.2821	**0.2743**	0.2752
	336	0.3185	**0.3175**	0.3204	**0.3195**	**0.3286**	0.3290	**0.3186**	0.3189	0.3119	**0.3108**
	720	0.3873	**0.3825**	0.3831	**0.3814**	0.3981	**0.3959**	0.3906	**0.3859**	**0.4023**	0.4065

Dataset	Horizon	DLinear		FreTS		iTransformer		OLS		PatchTST	
		Orig.	Matured	Orig.	Matured	Orig.	Matured	Orig.	Matured	Orig.	Matured
ETTm1	96	**0.3497**	0.3504	0.3574	**0.3559**	**0.3658**	0.3680	**0.3521**	0.3542	0.3912	**0.3826**
	192	0.4166	**0.4165**	0.4205	**0.4191**	**0.4182**	0.4189	**0.4164**	0.4184	**0.4366**	0.4370
	336	**0.4799**	0.4801	0.4816	**0.4810**	**0.4780**	0.4800	**0.4786**	0.4811	**0.4863**	0.4864
	720	**0.5488**	0.5521	0.5474	**0.5472**	**0.5529**	0.5579	**0.5479**	0.5515	0.5414	**0.5413**
ETTm2	96	0.1584	**0.1581**	0.1571	**0.1566**	**0.1639**	0.1640	**0.1592**	0.1594	0.1575	**0.1569**
	192	**0.1913**	0.1917	0.1907	**0.1901**	**0.2159**	0.2164	**0.1921**	0.1924	0.2063	**0.2058**
	336	**0.2289**	0.2299	0.2292	**0.2291**	0.2751	**0.2735**	**0.2299**	0.2308	0.2487	**0.2482**
	720	**0.2968**	0.2993	**0.2918**	0.2924	**0.3278**	0.3303	**0.2982**	0.2996	0.3223	**0.3218**
Weather	96	**0.1796**	0.1803	**0.1744**	0.1757	**0.1647**	0.1662	**0.1810**	0.1825	0.1715	**0.1700**
	192	**0.2244**	0.2265	**0.2151**	0.2167	**0.2119**	0.2129	**0.2221**	0.2238	0.2130	**0.2119**
	336	**0.2709**	0.2726	**0.2640**	0.2661	**0.2615**	0.2629	**0.2707**	0.2729	0.2660	**0.2659**
	720	**0.3500**	0.3509	**0.3400**	0.3423	**0.3410**	0.3418	**0.3443**	0.3467	0.3365	**0.3356**
Exchange	96	0.0885	**0.0875**	**0.0790**	0.0796	**0.0867**	0.0873	**0.0795**	0.0799	**0.0813**	0.0816
	192	0.1760	**0.1732**	**0.1639**	0.1654	**0.1760**	0.1800	**0.1643**	0.1650	0.1673	**0.1666**
	336	**0.2941**	0.3052	**0.2945**	0.3180	**0.2937**	0.3014	**0.2835**	0.2846	**0.2807**	0.3048

A.5 Is Output-Only Calibration Sufficient?

We compare the standard input-output calibration with an output-only variant across datasets, horizons, and source forecasters. The goal is to examine whether calibrating the look-back input window provides additional benefit beyond calibrating only the forecast output. Lower MSE is highlighted within each input-output versus output-only pair.

As shown in Table A.9, input-output calibration generally outperforms the output-only variant across TAFAS, PETSA, and FAC. This indicates that output-side calibration alone may not be sufficient in many test-time adaptation settings, even though it is a simpler design choice. Importantly, the additional parameter cost of input-side calibration is modest, especially for FAC.

Table A.10 reports the corresponding trainable parameter counts. For each dataset and method, the parameter difference between the input-output and output-only variants corresponds to the input adapter. Since the parameter count of the input adapter is determined by the look-back window rather than the prediction horizon, its relative cost becomes smaller as H increases.

Table A.9: Input-output versus output-only calibration across source forecasters. Lower MSE is highlighted within each input-output/output-only pair.

Dataset	Horizon	DLinear						FreTS					
		TAFAS		PETSA		FAC		TAFAS		PETSA		FAC	
		In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out
ETTh1	96	**0.4617**	0.4626	**0.4613**	0.4616	**0.4554**	0.4558	**0.4391**	**0.4391**	**0.4383**	**0.4383**	**0.4357**	0.4358
	192	**0.5112**	0.5115	**0.5123**	0.5128	0.5089	**0.5071**	**0.4943**	0.4945	**0.4960**	0.4961	0.4934	**0.4922**
	336	**0.5595**	0.5600	0.5626	**0.5622**	0.5582	**0.5555**	**0.5483**	0.5485	**0.5530**	**0.5530**	0.5498	**0.5468**
	720	**0.6926**	0.6970	**0.6938**	0.7003	**0.6891**	0.6918	0.6857	**0.6855**	**0.6908**	0.6937	0.7067	**0.7028**
ETTh2	96	**0.2308**	0.2315	**0.2312**	0.2316	**0.2288**	0.2302	**0.2363**	0.2366	**0.2366**	0.2370	**0.2338**	0.2341
	192	0.2830	**0.2818**	**0.2820**	0.2834	**0.2819**	0.2832	**0.2830**	0.2831	**0.2844**	0.2846	0.2814	**0.2810**
	336	**0.3175**	0.3180	**0.3190**	0.3202	**0.3144**	0.3165	**0.3195**	**0.3195**	**0.3250**	0.3252	**0.3172**	0.3180
	720	**0.3825**	0.3836	**0.3884**	0.3909	**0.3825**	0.3868	**0.3814**	**0.3814**	**0.3968**	0.3971	**0.3788**	0.3862
ETTm1	96	**0.3504**	0.3528	**0.3541**	0.3580	**0.3465**	0.3483	**0.3559**	0.3591	**0.3572**	0.3593	**0.3517**	0.3557
	192	**0.4165**	0.4172	**0.4192**	0.4226	**0.4139**	0.4160	**0.4191**	0.4200	**0.4189**	0.4201	**0.4183**	0.4187
	336	**0.4801**	0.4805	**0.4831**	0.4863	**0.4791**	0.4832	**0.4810**	0.4816	**0.4793**	0.4802	0.4836	**0.4826**
	720	**0.5521**	0.5526	**0.5600**	0.5618	**0.5494**	0.5517	**0.5472**	0.5475	**0.5523**	0.5526	0.5533	**0.5496**
ETTm2	96	**0.1581**	0.1586	**0.1583**	0.1587	**0.1560**	0.1569	**0.1566**	0.1571	**0.1569**	0.1575	**0.1563**	0.1565
	192	**0.1917**	0.1919	**0.1920**	0.1922	**0.1894**	0.1901	**0.1901**	0.1904	**0.1908**	0.1912	**0.1901**	0.1903
	336	**0.2299**	0.2301	**0.2303**	0.2304	0.2286	**0.2285**	**0.2291**	0.2293	**0.2312**	0.2314	0.2294	**0.2287**

Dataset	Horizon	DLinear						FreTS					
		TAFAS		PETSA		FAC		TAFAS		PETSA		FAC	
		In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out
	720	0.2993	**0.2987**	0.2984	**0.2968**	0.2984	**0.2980**	**0.2924**	0.2926	**0.2983**	0.2984	0.2955	**0.2934**
Weather	96	**0.1803**	0.1839	**0.1812**	0.1876	**0.1797**	0.1881	**0.1757**	0.1787	**0.1795**	0.1814	**0.1678**	0.1764
	192	**0.2265**	0.2282	**0.2308**	0.2313	**0.2231**	0.2298	**0.2167**	0.2186	**0.2229**	0.2240	**0.2114**	0.2175
	336	**0.2726**	0.2737	**0.2776**	0.2778	**0.2717**	0.2777	**0.2661**	0.2669	**0.2720**	0.2720	**0.2621**	0.2661
	720	**0.3509**	0.3542	**0.3557**	0.3565	**0.3426**	0.3482	**0.3423**	0.3426	**0.3550**	0.3554	**0.3376**	0.3392
Exchange	96	**0.0875**	0.0892	**0.0898**	0.0904	**0.0875**	0.0887	**0.0796**	0.0809	**0.0825**	0.0827	**0.0810**	0.0828
	192	**0.1732**	0.1758	**0.1787**	0.1802	0.1758	**0.1740**	**0.1654**	0.1673	**0.1729**	0.1731	0.1667	**0.1635**
	336	**0.3052**	0.3083	**0.3154**	0.3188	**0.2985**	0.3125	**0.3180**	0.3197	**0.3223**	0.3230	0.3166	**0.3017**

Dataset	Horizon	iTransformer						OLS						PatchTST					
		TAFAS		PETSA		FAC		TAFAS		PETSA		FAC		TAFAS (PatchTST)		PETSA		FAC	
		In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out
ETTh1	96	0.4421	**0.4420**	**0.4394**	0.4398	0.4400	**0.4378**	**0.4428**	0.4454	**0.4449**	0.4459	**0.4382**	0.4390	0.4270	**0.4260**	0.4255	**0.4253**	0.4241	**0.4238**
	192	0.5020	**0.5016**	**0.5014**	0.5017	0.5010	**0.4987**	**0.4929**	0.4951	**0.5007**	0.5016	**0.4921**	0.4926	0.4818	**0.4811**	**0.4818**	**0.4818**	0.4797	**0.4790**
	336	**0.5624**	0.5625	0.5641	**0.5639**	0.5587	**0.5561**	**0.5427**	0.5443	**0.5488**	0.5492	0.5422	**0.5405**	0.5506	**0.5505**	**0.5570**	0.5572	0.5525	**0.5495**
	720	**0.6755**	0.6772	**0.6763**	0.6783	**0.6687**	0.6718	**0.6704**	0.6747	**0.6805**	0.6835	**0.6780**	0.6832	0.6807	**0.6802**	0.7019	**0.7012**	0.7096	**0.6964**
ETTh2	96	**0.2620**	0.2623	0.2602	**0.2593**	**0.2561**	**0.2561**	**0.2289**	0.2296	**0.2293**	0.2299	**0.2274**	0.2280	0.2380	**0.2378**	**0.2383**	**0.2383**	**0.2374**	**0.2374**
	192	**0.3004**	0.3011	**0.3005**	0.3008	0.2970	**0.2955**	**0.2821**	0.2826	**0.2829**	0.2833	**0.2796**	0.2804	**0.2752**	0.2753	**0.2810**	0.2817	0.2747	**0.2737**
	336	0.3290	**0.3286**	0.3312	**0.3310**	0.3284	**0.3266**	**0.3189**	0.3201	**0.3240**	0.3245	**0.3137**	0.3163	**0.3108**	**0.3108**	**0.3190**	0.3200	**0.3079**	0.3103
	720	**0.3959**	0.3961	**0.4049**	0.4059	0.3982	**0.3952**	**0.3859**	0.3870	**0.3927**	0.3955	**0.3854**	0.3901	**0.4065**	0.4073	**0.4203**	0.4215	**0.4002**	0.4043
ETTm1	96	**0.3680**	0.3753	**0.3700**	0.3750	**0.3459**	0.3619	**0.3542**	0.3565	**0.3591**	0.3601	**0.3462**	0.3489	**0.3826**	0.3904	**0.3817**	0.3872	**0.3530**	0.3804
	192	**0.4189**	0.4238	**0.4189**	0.4238	**0.4087**	0.4159	**0.4184**	0.4203	**0.4252**	0.4266	**0.4140**	0.4171	0.4370	**0.4367**	0.4405	**0.4403**	**0.4213**	0.4269
	336	**0.4800**	0.4833	**0.4788**	0.4822	**0.4781**	0.4820	**0.4811**	0.4827	**0.4896**	0.4909	**0.4794**	0.4847	**0.4864**	0.4867	**0.4970**	0.4975	**0.4787**	0.4805
	720	**0.5579**	0.5595	**0.5615**	0.5622	**0.5460**	0.5506	**0.5515**	0.5524	**0.5594**	0.5603	**0.5497**	0.5535	0.5413	**0.5402**	**0.5479**	0.5485	**0.5399**	0.5420
ETTm2	96	**0.1640**	0.1642	**0.1640**	0.1642	0.1613	**0.1606**	**0.1594**	0.1595	**0.1595**	**0.1595**	**0.1563**	0.1573	0.1569	0.1571	**0.1569**	0.1573	**0.1558**	0.1562
	192	0.2164	**0.2163**	**0.2157**	0.2164	**0.2067**	0.2094	**0.1924**	0.1925	**0.1925**	0.1927	**0.1897**	0.1907	**0.2058**	0.2063	**0.2079**	0.2084	**0.1976**	0.2018
	336	**0.2735**	0.2758	**0.2653**	0.2748	**0.2623**	0.2700	**0.2308**	0.2309	**0.2316**	0.2318	**0.2289**	0.2293	**0.2482**	**0.2482**	**0.2473**	0.2476	**0.2422**	0.2458
	720	0.3303	**0.3295**	**0.3263**	0.3264	0.3290	**0.3251**	**0.2996**	**0.2996**	**0.3003**	**0.3003**	**0.2973**	0.2985	**0.3218**	0.3223	**0.3240**	0.3242	**0.3192**	0.3196
Weather	96	**0.1662**	0.1674	**0.1662**	0.1686	**0.1605**	0.1635	**0.1825**	0.1855	**0.1890**	0.1914	**0.1728**	0.1843	**0.1700**	0.1713	**0.1676**	0.1721	**0.1635**	0.1682
	192	**0.2129**	0.2136	**0.2165**	0.2171	**0.2103**	0.2113	**0.2238**	0.2255	**0.2293**	0.2304	**0.2171**	0.2249	**0.2119**	0.2130	**0.2120**	0.2137	**0.2050**	0.2088
	336	**0.2629**	0.2632	**0.2672**	0.2675	0.2618	**0.2599**	**0.2729**	0.2740	**0.2785**	**0.2785**	**0.2665**	0.2721	**0.2659**	0.2667	**0.2703**	0.2716	**0.2570**	0.2614
	720	**0.3418**	0.3422	**0.3470**	0.3474	**0.3357**	0.3365	**0.3467**	0.3475	**0.3598**	0.3604	**0.3401**	0.3424	0.3356	**0.3348**	**0.3529**	0.3543	**0.3341**	0.3357
Exchange	96	**0.0873**	0.0877	**0.0881**	**0.0881**	0.0867	**0.0863**	**0.0799**	0.0805	**0.0813**	**0.0813**	**0.0793**	0.0794	**0.0816**	0.0825	**0.0850**	0.0853	**0.0813**	0.0821
	192	**0.1800**	0.1820	**0.1820**	0.1836	0.1773	**0.1756**	**0.1650**	0.1669	**0.1719**	0.1722	**0.1648**	0.1677	0.1666	**0.1659**	**0.1765**	0.1769	**0.1692**	0.1718
	336	**0.3014**	0.3023	**0.3105**	0.3110	**0.2983**	0.3026	0.2846	**0.2823**	**0.3058**	0.3093	**0.2924**	0.3009	0.3048	**0.2763**	**0.3188**	0.3261	**0.3011**	0.3149

Table A.10: Trainable parameter counts for input-output and output-only calibration. For each method, "In+Out" denotes the standard input-output variant and "Out" denotes the output-only variant. The ETT datasets share the same parameter counts. For TAFAS, the PatchTST-specific implementation is listed separately.

Dataset	H	TAFAS		TAFAS (PatchTST)		PETSA		FAC (Ours)	
		In+Out	Out	In+Out	Out	In+Out	Out	In+Out	Out
ETT (h1/2, m1/2)	96	130,382	65,191	18,626	9,313	25,934	12,967	**2,758**	**1,379**
	192	324,590	259,399	46,370	37,057	38,894	25,927	**4,102**	**2,723**
	336	857,822	792,631	122,546	113,233	58,334	45,367	**6,118**	**4,739**
	720	3,699,038	3,633,847	528,434	519,121	110,174	97,207	**11,494**	**10,115**
Weather	96	391,146	195,573	18,626	9,313	71,658	35,829	**8,274**	**4,137**
	192	973,770	778,197	46,370	37,057	107,466	71,637	**12,306**	**8,169**
	336	2,573,466	2,377,893	122,546	113,233	161,178	125,349	**18,354**	**14,217**
	720	11,097,114	10,901,541	528,434	519,121	304,410	268,581	**34,482**	**30,345**
Exchange	96	149,008	74,504	18,626	9,313	29,200	14,600	**3,152**	**1,576**
	192	370,960	296,456	46,370	37,057	43,792	29,192	**4,688**	**3,112**
	336	980,368	905,864	122,546	113,233	65,680	51,080	**6,992**	**5,416**

A.6 Runtime and Parameter Efficiency

Table A.11: Runtime and parameter comparison on Weather with the longest forecasting horizon $H = 720$, a relatively demanding setting in our benchmark. Adaptation time, reported in milliseconds, includes calibration, loss computation, backward update, and period estimation, excluding the source forecaster forward pass. Overall runtime is reported in seconds. Results are averaged over 10 repeated runs.

Source Forecaster	Method	Trainable Parameters	MSE	Adaptation Time (ms)	Overall Runtime (s)
DLinear	TAFAS	11,097,114	0.3509	3.60 ± 0.25	3.49 ± 0.14
	PETSA	304,410	0.3557	6.88 ± 0.63	3.85 ± 0.23
	FAC (Ours)	**34,482**	**0.3426**	4.25 ± 0.41	3.55 ± 0.15
FreTS	TAFAS	11,097,114	0.3423	5.81 ± 0.18 ms	7.57 ± 0.18 s
	PETSA	304,410	0.3550	21.35 ± 0.56 ms	8.38 ± 0.24 s
	FAC (Ours)	**34,482**	**0.3376**	6.01 ± 0.39 ms	7.27 ± 0.24 s
iTransformer	TAFAS	11,097,114	0.3418	7.29 ± 1.15 ms	5.56 ± 0.12 s
	PETSA	304,410	0.3470	10.32 ± 0.58 ms	6.67 ± 1.50 s
	FAC (Ours)	**34,482**	**0.3357**	7.92 ± 1.35 ms	5.56 ± 0.22 s
OLS	TAFAS	11,097,114	0.3467	3.10 ± 0.31 ms	3.67 ± 0.29 s
	PETSA	304,410	0.3598	6.79 ± 0.46 ms	4.07 ± 0.15 s
	FAC (Ours)	**34,482**	**0.3401**	3.54 ± 0.28 ms	3.79 ± 0.23 s
PatchTST	TAFAS (PatchTST)	528,434	0.3356	2.97 ± 0.12 ms	20.76 ± 0.29 s
	PETSA	304,410	0.3529	95.70 ± 1.98 ms	27.78 ± 0.40 s
	FAC (Ours)	**34,482**	**0.3341**	18.16 ± 0.29 ms	27.21 ± 0.20 s

Note. TAFAS and PETSA are evaluated under the same protocol as FAC, where adaptation uses only matured ground truth. For PatchTST, TAFAS follows its original backbone-specific implementation, which uses single-channel output calibration and bypasses input calibration. For frequency-domain calibration methods, including FAC and our PETSA variant, we use multivariate calibration across variables.

Runtime efficiency is important in practice, but reducing the number of trainable parameters does not necessarily yield proportional wall-clock speedups. As shown in Table A.11, TAFAS generally has lower runtime overhead, whereas FAC achieves frequency-aware calibration with a substantially smaller number of trainable parameters. The additional Fourier-transform operations and tensor transformations used by FAC likely contribute to its higher runtime overhead in some settings. Compared with PETSA, FAC uses a simpler adaptation objective and achieves better forecasting accuracy with substantially fewer trainable parameters and lower runtime in most settings. The runtime difference relative to TAFAS is most pronounced for PatchTST, where TAFAS uses its lightweight backbone-specific implementation.

A.7 Additional Frequency-Domain Correction Spectra

We provide additional frequency-domain correction spectra across datasets and forecasting horizons to complement the analysis in Figure 4. Recall that these spectra are not intended to measure forecasting error. Instead, they characterize the magnitude and structure of the prediction changes induced by adaptation in the frequency domain.

For each adaptation method $q \in \{\text{FAC}, \text{TAFAS}, \text{PETSA}\}$, we first compute the correction for each collected prediction window. Specifically, we denote the correction as

$$\Delta \hat{\mathbf{Y}}^{q,[n]} = \hat{\mathbf{Y}}^{q,[n]} - \hat{\mathbf{Y}}^{[n]}, \qquad n = 1, \ldots, N,$$

where $\hat{\mathbf{Y}}^{[n]}$ denotes the prediction before adaptation and $\hat{\mathbf{Y}}^{q,[n]}$ denotes the prediction after applying method q to the n-th prediction window. We then concatenate the corrections from all prediction windows along the prediction-window dimension, yielding

$$\Delta \hat{\mathbf{Y}}^q \in \mathbb{R}^{N \times H \times C},$$

where N is the total number of prediction windows, H is the forecasting horizon, and C is the number of channels. Next, we apply rFFT along the forecasting-horizon dimension and take the magnitude as

$$\mathbf{A}^q = \left| \text{rFFT}_H \left(\Delta \hat{\mathbf{Y}}^q \right) \right| \in \mathbb{R}^{N \times F \times C},$$

where $F = \lfloor H/2 \rfloor + 1$ is the number of rFFT frequency components. The plotted curve is obtained by averaging over the prediction windows and channels as

$$\bar{\mathbf{a}}^q = \mathrm{Avg}_{N,C}\left(\mathbf{A}^q_{f>0}\right) \in \mathbb{R}^{F-1}.$$

Here, $f > 0$ indicates that the DC component is omitted.

Figure A.2: Additional frequency-domain correction spectra across forecasting horizons. For each adaptation method, we compute the correction, apply rFFT to this correction along the forecasting horizon, and plot the spectral magnitude averaged over prediction windows and channels. The DC component is omitted. Columns correspond to $H \in \{96, 192, 336, 720\}$, and rows correspond to dataset–forecaster pairs ordered alphabetically by dataset name. The y-axis is shown on a logarithmic scale. We omit Exchange because no matured mini-batch is available under the $H = 720$ setting in our protocol.

Figure A.2 shows that the qualitative behavior observed in the main text is not limited to a single forecasting horizon. Across diverse settings, FAC produces more localized spectral corrections than TAFAS and PETSA, whose corrections often vary more smoothly across frequencies. At the same time, some cases, such as Weather with PatchTST, show smaller differences among the methods, indicating that the spectral behavior also depends on the source forecaster and dataset.

A.8   Additive Frequency-Band Decomposition of Residual-Error Reduction

Using the frequency-band partition and residual spectral-energy definition introduced in the main text, we further decompose the total residual-error reduction into additive bandwise contributions. For adaptation method $q \in \{\text{FAC}, \text{TAFAS}, \text{PETSA}\}$, we define

$$\Delta_b^q = 100 \times \frac{E_b(\hat{\mathbf{Y}}) - E_b(\hat{\mathbf{Y}}^q)}{\sum_{b'} E_{b'}(\hat{\mathbf{Y}})}, \tag{20}$$

where all frequency bands share the same denominator. Consequently, their contributions are additive:

$$\Delta_{\text{total}}^q = \sum_{b \in \{\text{low}, \text{mid}, \text{high}\}} \Delta_b^q. \tag{21}$$

Table A.12: Additive decomposition of total residual-error reduction across frequency bands for representative settings at $H = 720$. Each band reports its percentage-point contribution to the total reduction in residual spectral energy. The three bandwise contributions sum to the Total value up to rounding. Within each setting, the largest value in each column is highlighted in bold.

Setting	Method	Low	Middle	High	Total
ETTh1 + DLinear	TAFAS	2.6809	0.0061	0.0050	2.6920
	PETSA	2.4999	0.0125	0.0114	2.5238
	FAC	**3.0137**	**0.1470**	**0.0222**	**3.1829**
ETTh2 + FreTS	TAFAS	7.3853	0.0041	0.0022	7.3916
	PETSA	3.6529	0.0029	0.0015	3.6572
	FAC	**7.7298**	**0.1262**	**0.1591**	**8.0151**
ETTm1 + iTransformer	TAFAS	7.3295	0.0106	0.0096	7.3496
	PETSA	6.6962	0.0063	0.0060	6.7085
	FAC	**9.2175**	**0.0672**	**0.0750**	**9.3597**
ETTm2 + OLS	TAFAS	2.2883	**0.0010**	**0.0005**	2.2897
	PETSA	2.0576	0.0006	0.0001	2.0582
	FAC	**3.0302**	0.0004	0.0002	**3.0308**

Table A.12 confirms that most of the absolute error reduction arises from the low-frequency band, where the residual spectral energy is concentrated. FAC nevertheless contributes more middle- and high-frequency reduction in the first three settings, whereas the improvement for ETTm2 with OLS is almost entirely low-frequency.

B   Protocol Compatibility under Matured-Only Supervision

B.1   Variants of TAFAS and PETSA under the Matured-Only Protocol

The original implementations of TAFAS and PETSA already separate adaptation using the most recent matured mini-batch from adaptation using POGT from the current mini-batch. Once a historical mini-batch matures, it is replayed and used to update the original calibration modules against its complete target horizon. Our matured-only variants therefore retain this existing matured-ground-truth branch while disabling the current-mini-batch POGT update branch. Using the notation of Section 3.2.1, for $q \in \{\text{TAFAS}, \text{PETSA}\}$, the retained adaptation objective is

$$\mathcal{L}_k^{q,\text{clean}} = \mathcal{L}_{m(k)}^{q,\text{Matured}}. \tag{22}$$

Here, $\mathcal{L}_{m(k)}^{q,\text{Matured}}$ denotes the loss used by each method on a fully matured mini-batch: MSE for TAFAS and the composite adaptation objective for PETSA. After updating the calibration modules, the complete current mini-batch is re-forecast and evaluated as

$$\tilde{\mathbf{Y}}_k^{q,[j]} = \hat{\mathbf{Y}}_k^{q,\text{adp},[j]} = \mathcal{C}_k^{q,\text{out}}\left(\mathcal{F}\left(\mathcal{C}_k^{q,\text{in}}(\mathbf{X}_k^{[j]})\right)\right), \qquad j = 1, \dots, B_k. \tag{23}$$

This replaces the POGT-dependent partial stitching rule in Eq. 8. Thus, the conversion from the mixed protocol to the proposed matured-only protocol is direct: it disables POGT supervision and its associated partial stitching, but does not redefine the calibration architecture, adapter input or trainable parameters.

B.2 Protocol Compatibility of COSA with Matured-Only Supervision

As discussed in Section 3.2.2, the streaming protocol implemented by COSA does not generally satisfy the matured-only criterion considered in this work. In particular, the target statistics entering its context are revealed but not necessarily matured relative to subsequent rolling predictions. When the forecasting horizon is large relative to the mini-batch size, statistics from a recently processed mini-batch may already enter the context of later predictions while its target span still overlaps with those prediction spans.

Furthermore, unlike TAFAS and PETSA, COSA uses target-derived information in two places: the complete targets provide adaptation supervision, while statistics computed from recently observed targets form part of the adapter input. Following the notation of COSA, let $\mathbf{Y}_t^{(0)}$ denote the frozen source-forecaster prediction at time t, and let $\mathbf{C}_t$ denote the context vector constructed from recently observed target statistics. COSA forms the adapter input

$$\mathbf{X}_t^{(a)} = [\mathbf{Y}_t^{(0)} \| \mathbf{C}_t], \tag{24}$$

and produces the corrected prediction as

$$\hat{\mathbf{Y}}_t = \mathbf{Y}_t^{(0)} + \tanh(g)\left(\mathbf{W}\mathbf{X}_t^{(a)} + \mathbf{b}\right). \tag{25}$$

In the official implementation, the predictions for the current mini-batch are first corrected using a context $\mathbf{C}_t^{\mathrm{pred}}$ constructed from the existing target-statistic memory. The target statistic computed from the complete target tensor of that mini-batch is then appended to the memory, producing an updated context $\mathbf{C}_t^{\mathrm{upd}}$, and the adapter is optimized on the same mini-batch. Hence, the adapter inputs used for prediction and adaptation are respectively

$$\mathbf{X}_t^{(a),\mathrm{pred}} = [\mathbf{Y}_t^{(0)} \| \mathbf{C}_t^{\mathrm{pred}}], \qquad \mathbf{X}_t^{(a),\mathrm{upd}} = [\mathbf{Y}_t^{(0)} \| \mathbf{C}_t^{\mathrm{upd}}], \tag{26}$$

where, in general, $\mathbf{C}_t^{\mathrm{pred}} \neq \mathbf{C}_t^{\mathrm{upd}}$. Consequently, the official implementation does not enforce the full-horizon maturation condition used in our protocol. A strict matured-only conversion would require delaying both the adapter update and the incorporation of target-derived statistics into the context, rather than simply disabling an existing update branch. We therefore do not include a matured-only COSA variant.