QUANTUM-INSPIRED TENSORIZED EMBEDDING WITH APPLICATION TO NODE REPRESENTATION LEARNING

ABSTRACT

Node representation learning a.k.a. network embedding (NE) is an essential technique for network analysis by representing nodes as vectors, which also serves downstream tasks or as initial input for GNN models. Most of existing NE algorithms require a space complexity linear to the multiplication of the number of nodes and embedding dimension to store embeddings. Such a conventional embedding paradigm has two defects: i) it brings challenge to the deployment of NE algorithms for large-scale networks on devices of limited memory/storage space; ii) model expressiveness is constrained due to the limited embedding dimension. Impressed and inspired by the large Hilbert space of quantum systems, we propose a brand new NE algorithm *node2ket* by imitating behaviors of quantum systems. Theoretically, we give analysis on how it unifies existing embedding methods including both conventional ones and tensorized ones, and explore the ultimate compressive power of the embedding model on the space complexity compared with conventional ones. Experiments are conducted on five public real-world networks where methods are evaluated through tasks of network reconstruction and link prediction. On BlogCatalog, our method achieves to outperform all baselines with 1/32 training parameters and 1/16 running time on the same machine. On DBLP, the reconstruction precision of node2ket achieves to be 3 times higher than the best baseline i.e. LouvainNE. Source code will be made publicly available.

Hilbert space is a big place!

– Carlton Morris Caves.

1 INTRODUCTION

Node representation learning, also known as network embedding (NE), has been well studied in decades. Borrowing idea from word embedding in NLP, deepwalk (Perozzi et al., 2014) first proposes to learn node embeddings for downstream tasks by feeding random walk sequences to word2vec (Mikolov et al., 2013). Afterwards, numerous NE methods for different types of networks (e.g. heterogeneous/multiplex networks) and for different purposes (e.g. preserving structural similarity) are proposed (see Sec. 2 for more). Despite the great success, the existing NE methods still suffer from the high space complexity for storing/training the embeddings whose size grows linearly to the multiplication of the number of nodes and the embedding dimension (Xiong et al., 2022) (see Appendix A for details). As a result, there is difficulty in deploying these methods on memory-limited devices for privacy-sensitive computing e.g. recommender system in social network on mobile phones. Meanwhile the expressiveness of the embedding vectors can be restricted.

Recently, inspired by quantum mechanics, word2ket (Panahi et al., 2020) was proposed for compressive word embedding by imitating the behaviors of quantum bits in quantum systems. By tensor entanglement, word2ket achieves both a high compressive ratio and experimental results comparable to conventional embeddings. Though providing many insights in generating embeddings, word2ket still faces difficulties transferring to embedding problems in other fields such as node representation learning (Hamilton et al., 2017b). These difficulties include: **i)** Word2ket generates embeddings from a fixed complete binary tree, which **neglects the latent structure of the input data and hence brings challenges to learning embeddings for data with explicit structures (e.g. networks). ii)** Word2ket adopts deep neural networks to decode the embedding and is trained in a supervised way, **which is rather different from many embedding methods** (Tang et al., 2015; Grover & Leskovec,

2016) that decode embeddings via simply inner product operation and train embeddings by optimizing the objective based on Noise Contrastive Estimation (NCE) (Gutmann & Hyvärinen, 2010) in a self-supervised (contrastive learning) style.

In this paper, we propose a novel network embedding paradigm with special concerns for the above two problems. **For the embedding generation,** we propose an embedding module named as *Tensorized Embedding Blocks* (TEBs) composed of columns of *Tensor Units* (TUs), each representing an embedding tensor. TEBs are able to unify the embedding layers in word2ket/word2ketXS by making changes in the way of indexing TUs (see Sec. 4.1 and Sec. 4.5). A good strategy of assigning TU indices to the embedded nodes will result in a model with both high expressiveness and space efficiency, which is proved by the experiments. **For the embedding learning,** we optimize the widely adopted NCE-based objective and succeed in learning node embeddings in a 2^{32}-dimensional Hilbert space in a stable and robust manner on a single machine (details in Sec. 4.2). Specifically, we propose two variants on different compressive levels, named as *node2ket* and *node2ket+*. The former is a preliminary baseline and the latter is more compressive by utilizing graph partition techniques. Furthermore, we give complexity analysis of the embedding modules in TEBs, and theoretically prove an upper bound of the minimum of the required space to store/train embeddings for node2ket and node2ket+ in Sec. 4.3 and Sec. 4.4 respectively. **Our contributions are listed as follows:**

1) We propose a novel architecture named as Tensorized Embedding Blocks (TEBs) to generate node embeddings by tensor product and entanglement, imitating behaviors of quantum systems. In this way, high-dimensional embeddings of high expressiveness in the Hilbert space can be generated via a small number of parameters. Our tensorized embedding architecture is a generalization of the recent method word2ket/word2ketXS. Rather than use a complete binary tree that treats the importance of each TEB to be equal to generate embeddings as done in these two methods, our model adopts a flexible design where the shape of TEBs can be freely defined while introducing learnable weights to improve expressiveness.

2) We take an initiative to adopt tensorized embedding on node representation learning based on Noise Contrastive Estimation. Specifically, we propose two variants on different compressive levels, *node2ket* and *node2ket+*, with the bound of compressive power proved respectively. Compared with the preliminary baseline node2ket, node2ket+ further utilizes graph partition techniques in the design of TEBs, in which way features on different levels of granularity are preserved and the embedding model becomes more compressive.

3) Experiments on network reconstruction and link prediction show the overwhelming performance of node2ket. Notably, in the network reconstruction experiments, it becomes the top method on BlogCatalog with 1/32 training parameters and 1/16 running time, and the precision on DBLP is more than 3 times higher than the best one of baselines i.e. LouvainNE (Bhowmick et al., 2020).

2 RELATED WORKS

Network Embedding. Here we mainly discuss the NE methods based on the language model word2vec (Mikolov et al., 2013), which are often designed for different types of networks, e.g. homogeneous networks (Perozzi et al., 2014; Grover & Leskovec, 2016; Tang et al., 2015), heterogeneous networks (Dong et al., 2017) and multiplex networks (Liu et al., 2017; Qu et al., 2017; Xiong et al., 2021). It also often aims to preserve specific types of information, e.g. low-order proximity (Tang et al., 2015), structure similarity (Ribeiro et al., 2017), versatile similarity measures (Tsitsulin et al., 2018), and cross-network alignment relations (Du et al., 2022). Apart from NE methods derived from word2vec, methods based on deep neural networks (Wang et al., 2016) especially graph neural networks (Hamilton et al., 2017a) are also influential in literature, which, however, are technically divergent to this paper.

Tensorized Embedding Model. Tensors are a generalization of vectors and matrices. Thanks to the capability of representing and manipulating high-dimensional subjects, tensor has been successfully applied to exploit complex physical systems (Nielsen & Chuang, 2002). The most crucial application is to understand the quantum many body systems and to make an efficient description of quantum states residing in the exponential growth of the Hilbert space (Bridgeman & Chubb, 2017). In addition, tensor networks composed of multiple tensors can also be used to understand many of the foundational results in quantum information (Orús, 2019). Utilizing the tensor network structure makes it reasonably possible to simplify the concept like quantum teleportation, purification, and the

church of the larger Hilbert space (Bridgeman & Chubb, 2017). Inspired by this, many tensorized embedding models try to take advantage of tensor operations like contraction and decomposition to handle large volumes of data and compress parameters, ranging from image classification (Stoudenmire & Schwab, 2016; Martyn et al., 2020; Selvan & Dam, 2020; Cheng et al., 2021) to natural language processing (Panahi et al., 2020; Ma et al., 2019; Liu et al., 2020; Qiu & Huang, 2015). It is anticipated that the tensor concept introduced by quantum physics will give us new perspectives on designing the structure of deep learning models and comprehending the learning capability of artificial neural networks (Levine et al., 2017).

3 PRELIMINARIES AND BACKGROUND

3.1 NETWORK EMBEDDING BASED ON NOISE CONTRASTIVE ESTIMATION

Given a network described by the node set $\mathcal{V}$ and the edge set $\mathcal{E}$, node representation learning or network embedding aims to represent each node $i \in \mathcal{V}$ as a fixed-length vector $\mathbf{x}_i \in \mathbb{R}^p$. To fully explore network structures for different purposes, a *corpus* $\mathcal{D}$ is usually created as the input data of embedding training. Typically, $\mathcal{D}$ can be the edge set (Tang et al., 2015), random walk sequences (Perozzi et al., 2014; Ribeiro et al., 2017; Du et al., 2022), etc.

Objective Function. Initially, the objective is to maximize the following log softmax function:

$$\sum_{(i,j)\in\mathcal{D}} \log \frac{\exp(\mathbf{x}_i^\top \mathbf{x}_j)}{\sum_{j'\in\mathcal{V}} \exp(\mathbf{x}_i^\top \mathbf{x}_{j'})}, \tag{1}$$

where the positive pairs (i, j) are sampled from $\mathcal{D}$. However, Eq. 1 is computationally intractable for a large $\mathcal{V}$, and thus surrogate objectives are proposed, including Hierarchical Softmax and Negative Sampling (Mikolov et al., 2013). In this paper, we only discuss a typical objective based on the widely adopted Negative Sampling:

$$\sum_{(i,j)\in\mathcal{D}} \left[\log \sigma(\mathbf{x}_i^\top \mathbf{x}_j) + \sum_{k=1}^{K} \mathbb{E}_{j'\sim\mathbb{P}_n} \log \sigma(-\mathbf{x}_i^\top \mathbf{x}_{j'}) \right], \tag{2}$$

where $\sigma(x) = 1/(1 + \exp(-x))$ is sigmoid function, K is the number of negative samples for each positive sampled pair, $\mathbb{P}_n$ is the distribution of negative samples j'.

3.2 QUANTUM MECHANICS AND TENSORIZED EMBEDDING

Quantum Mechanics. Quantum states are usually written in a 'bra-ket' notation. In matrix representations, **kets** are column vectors denoted as $|\psi\rangle$ (*where the name word/node2ket comes*) and **bras** are the conjugate transpose of the kets denoted as $\langle\psi|$. The state of a single quantum bit (qubit) $|\psi\rangle$ is defined in a 2-dimensional Hilbert space $\mathbb{C}^2$, described by a superposition of two orthonormal basis states $|0\rangle = (1, 0)^\top$ and $|1\rangle = (0, 1)^\top$, $|\psi\rangle = \alpha|0\rangle + \beta|1\rangle$, where $\alpha, \beta \in \mathbb{C}$ are probability amplitudes satisfying $|\alpha|^2 + |\beta|^2 = 1$. The state of an N-qubit quantum system is in the Hilbert space $\otimes_{i=1}^N \mathbb{C}^2$, where $\otimes$ denotes tensor product. Considering two quantum systems A and B with corresponding Hilbert spaces $\mathcal{H}_A$ and $\mathcal{H}_B$, the composite space of A and B is $\mathcal{H} = \mathcal{H}_A \otimes \mathcal{H}_B$. If we use $|\phi\rangle_A$ and $|\phi\rangle_B$ to denote states of system A and B respectively, then a state $|\phi\rangle \in \mathcal{H}$ that can be written as $|\phi\rangle = |\phi\rangle_A \otimes |\phi\rangle_B$ is called a **pure state**, otherwise it is an **entangled state**.

Tensorized Embedding by Word2ket. Word2ket (Panahi et al., 2020) conducts word embedding by imitating behaviors of quantum systems. Embedding of each word is represented as an entangled quantum state in the Hilbert space, which is the summation of several pure state embeddings. A pure state embedding is formed by tensor product between some lower-dimensional tensors. During the embedding procedure, some simplifications are adopted: i) real vectors are used as embeddings instead of complex ones in the quantum states; ii) the tensor product between tensors is implemented as the Kronecker product between vectors (it does not affect the results mathematically, since a vector can be seemed as a special tensor (Bridgeman & Chubb, 2016), and Kronecker product can be viewed as a form of vectorization of the tensor product); and iii) when imitating quantum entanglements, it uses learned tensors but not orthonormal basis states for implementation convenience, which means that a generated entangled state embedding may not be a strictly entangled one. These simplifications are also adopted by this paper.

Figure 1: A toy example to generate embedding from the given tensorized embedding blocks. To get the embedding $\mathbf{x}_i$, the first step is to look $r(i, c)$ up from the table at the left-hand side, and then pick the tensor units out from the TEBs and calculate the final embedding according to Eq. 3.

4 TENSORIZED NETWORK EMBEDDING

4.1 EMBEDDING VIA TENSORIZED EMBEDDING BLOCKS

Tensorized Embedding Blocks (TEBs). Before introducing how node2ket works, we first propose a novel embedding module named as Tensorized Embedding Blocks. A TEB is composed of a certain number of Tensor Units (TUs), and each TU represents an embedding vector in $\mathbb{R}^d$. A TEB has C columns where the c-th column has R_c TUs. We denote the embedding vector of the TU located at the r-th row and c-th column of the b-th block by $\mathbf{u}_{rc}^b$.

Embeddings Generation. We use B TEBs for embedding generation. Though more freedom can be added to the number of rows $\{R_c\}_{c=1}^C$ for different TEBs, we assume that they are the same without losing generality. For node i, we obtain the embedding $\mathbf{x}_i$ by:

$$\mathbf{x}_i = \sum_{b=1}^{B} w_{ib} \mathbf{x}_i^b, \quad \mathbf{x}_i^b = \bigotimes_{c=1}^{C} \mathbf{u}_{r(i,c)c}^b, \tag{3}$$

where $\mathbf{x}_i^b$ is the pure state embedding in a $\mathbb{R}^{d^C}$-dimensional Hilbert space given by the b-th TEB for node i, and w_{ib} is the corresponding block weight of node i on b-th TEB. The $r(i, c)$ in the subscription of TU embeddings $\mathbf{u}_{r(i,c)c}^b$ indicates that the row index r depends on the node i and the column index c. For better understanding, we give a toy example of TEBs and how to generate $\mathbf{x}_i$ according to the given $r(i, c)$ look-up table as shown in Fig. 1.

Complexity Analysis. There are three parts of parameters: i) the $r(i, c)$ table has $O(C|\mathcal{V}|)$ parameters, ii) the embeddings of TUs have $O(Bd \sum_{c=1}^{C} R_c)$ parameters, and iii) the block weights have $O(B|\mathcal{V}|)$ parameters. The used parameters is totally $O(Bd \sum_{c=1}^{C} R_c + C|\mathcal{V}| + B|\mathcal{V}|)$. For more detailed complexity analysis please see Sec. 4.3 and Sec. 4.4.

4.2 MODEL LEARNING

Gradient. During the model optimization, we do not need to calculate the full node embeddings. Instead, we compute the gradient and update TU embeddings directly without a complete procedure of forward propagation. Given two embeddings $\mathbf{x}_i$ and $\mathbf{x}_j$:

$$\mathbf{x}_i = \sum_{b=1}^{B} w_{ib} \bigotimes_{c=1}^{C} \mathbf{u}_{r(i,c)c}^b, \quad \mathbf{x}_j = \sum_{b=1}^{B} w_{jb} \bigotimes_{c=1}^{C} \mathbf{u}_{r(j,c)c}^b, \tag{4}$$

and the label l ($l = 1$ for positive samples and $l = 0$ otherwise), we have the gradients for TU embeddings according to the objective Eq. 2:

$$\frac{\partial \log \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)}{\partial \mathbf{u}_{r(i,c)c}^b} = w_{ib} \big[\mathbb{1}_l - \sigma(\langle \mathbf{x}_i, \mathbf{x}_j \rangle) \big] \sum_{b'=1}^{B} w_{jb'} \mathbf{u}_{r(j,c)c}^{b'} \prod_{c' \neq c} \langle \mathbf{u}_{r(i,c')c'}^b, \mathbf{u}_{r(j,c')c'}^{b'} \rangle, \tag{5}$$

where $\mathbb{1}_l$ is an indicator returning 1 if $l = 1$ and 0 otherwise. The gradients for block weights are:

$$\frac{\partial \log \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)}{\partial w_{ib}} = \left[\mathbb{1}_l - \sigma(\langle \mathbf{x}_i, \mathbf{x}_j \rangle) \right] \sum_{b'=1}^{B} w_{jb'} \prod_{c=1}^{C} \langle \mathbf{u}_{r(i,c)c}^b, \mathbf{u}_{r(j,c)c}^{b'} \rangle. \quad (6)$$

For detailed derivation of the gradients, please see Appendix C.1.

Model Training. We optimize the objective via Asynchronous Stochastic Gradient Descent (Recht et al., 2011) on CPUs as most works in NCE-based embedding (Mikolov et al., 2013; Tang et al., 2015) and the famous open-source library gensim[1] do. Technical details are in Appendix C.2.

4.3 NODE2KET: A PRELIMINARY BASELINE

For node2ket (n2k), we set $r(i,c) = i$ as constants, and $R_1 = R_2 = \cdots = R_C = |\mathcal{V}|$. It means we don't need space to store the $r(i,c)$ table. We give a constraint over the embedding dimension d in Assumption 1, according to which we can reach Theorem 1 where the ultimate compressive power is analyzed. The proof is given in Appendix D.

Assumption 1. [**Dimensional Assumption**] *If a p-dimensional final embedding is required, the dimension of generated embedding should not be smaller than p, i.e. $d^C \geq p$;*

Theorem 1. [**Compressive Power**] *Given node set $\mathcal{V}$ and the final embedding dimension p, when $r(i,c) = i$ are constants (indicating $R_c = |\mathcal{V}|, \forall 1 \leq c \leq C$) and use block weights as trainable parameters, the total number of parameters is #params $= B(C|\mathcal{V}|d + |\mathcal{V}|)$. Omiting the integer constraints of d, we have:*

$$\min \#params = B|\mathcal{V}|p^{1/\ln p} \ln p + B|\mathcal{V}|.$$

When the block weights are set as constants, #params $= BC|\mathcal{V}|d$, and we have:

$$\min \#params = B|\mathcal{V}|p^{1/\ln p} \ln p.$$

4.4 NODE2KET+: COMPRESSIVE EMBEDDING UTILIZING GRAPH PARTITION

To further compress node2ket, we propose node2ket+ (n2k+) utilizing graph partition techniques. Specifically, we set $r(i,c) = \mathrm{Par}_c(i)$ where $\mathrm{Par}_c(\cdot)$ is the c-th partition algorithm and $\mathrm{Par}_c(i)$ returns the index of the partition that node i belongs to. In this way, R_c is equal to the number of partitions given by the function Par_c. In the implementation, we use Louvain partition (Blondel et al., 2008) with different settings of resolution as the graph partition algorithm, which is a scalable algorithm aiming to maximize the modularity of the partitions. We control that $R_1 \leq R_2 \leq \cdots R_C$, hence the model is able to extract structure information on different levels of granularity. Theoretically, we further give Assumption 2 over the size of TEBs, and then give a bound of the ultimate compressive power of node2ket+ in Theorem 2 based on Assumption 1 and 2. The proof for the following Theorem 2 is presented in Appendix D by borrowing the tool of asymptotic analysis (Bender & Orszag, 2013), which is technically nontrivial and new to the network embedding community.

Assumption 2. [**Combinatorial Assumption**] *A TEB should be capable to generate at least $|\mathcal{V}|$ different pure state embeddings, which indicates $\prod_{c=1}^{C} R_c \geq |\mathcal{V}|$.*

Theorem 2. [**Compressive Power**] *Given the node set $\mathcal{V}$ and the final embedding dimension p, when node2ket utilizes both the $r(i,c)$ table and block weights, the total number of parameters is #params $= Bd \sum_{c=1}^{C} R_c + B|\mathcal{V}| + C|\mathcal{V}|$. We have:*

$$\min \#params < BC^*\big(p|\mathcal{V}|\big)^{1/C^*} + B|\mathcal{V}| + C^*|\mathcal{V}|,$$

where $C^* = \sqrt{\left[(\ln p|\mathcal{V}|)^2 - \frac{1}{2}\left(\ln p|\mathcal{V}| + \frac{1}{p|\mathcal{V}|}\right)\right]/(|\mathcal{V}|/B + 1)}$. When block weights are set as constants, we have:

$$\min \#params < BC^*\big(p|\mathcal{V}|\big)^{1/C^*} + C^*|\mathcal{V}|. \quad (7)$$

---

[1]https://radimrehurek.com/gensim/index.html

Figure 2: Comparison on BC. n2k-8/128 denotes n2k by C=2, d=4 and C=8, d=16 respectively.

4.5 RELATION TO OTHER EMBEDDING METHODS

Relation to Conventional Embedding. When $B = 1$ and $C = 1$, the embeddings of generated by node2ket becomes $\mathbf{x}_i = \mathbf{u}_{i1}^1$ where no tensor product or entanglement is utilized and the embedding degrades to the conventional embedding.

Relation to Word2ket/Word2ketXS. Both word2ke/word2ketXS and node2ket/node2ket+ generate embeddings from TEBs of different setting (detailed explanation for how to unify word2ket/word2ketXS in the model of TEBs is in Appendix B.1), while node2ket/node2ket+ has the following distinct features: i) adopt block weights (proved to have a positive influence in experiments when d is small); ii) TEBs are designed to have a flexible shape which makes TEBs easy to be tailored for structured data and also improves the space efficiency; iii) achieves to fully explore the large Hilbert space without obtaining the full embedding. The technical differences between word2ket/word2ketXS and node2ket/node2ket+ are explained in detail in Appendix B.2, and summarized in Table 6.

5 EXPERIMENTS

5.1 EXPERIMENTAL SETTINGS

All of the experiments are run on a single machine with Intel(R) Core(TM) i9-7920X CPU @ 2.90GHz with 24 logical cores and 128GB memory.

Datasets. We investigate five publicly available real-world datasets of different scales, different densities, and containing different types of information. All of the networks are processed as undirected ones. The detailed statistics of the networks are given in Table 7 in Appendix E.1. We give a brief introduction of the datasets as follows: **YouTube** (Tang & Liu, 2009b) is a social network with millions of users on youtube.com; **BlogCatalog** (Tang & Liu, 2009a) (BC) is a social network of bloggers who have social connections with each other; **PPI** (Breitkreutz et al., 2007) is a subgraph of the PPI network for Homo Sapiens; **Arxiv GR-QC** (Leskovec et al., 2007) is a collaboration network from arXiv and covers scientific collaborations between authors with papers submitted to General Relativity and Quantum Cosmology category; **DBLP** (Ley, 2002) is a citation network of DBLP, where each node denotes a publication, and each edge represents a citation.

Baselines. The investigated NE methods include: three based on NCE, two based on matrix factorization, and one based on community detection. Here we introduce them briefly: **LINE** (Tang et al., 2015) models first-order proximity (connection strengths) and second-order proximity (similarity of neighborhoods) of given networks, and technically feed the adjacency matrix to two types of NCE-based objectives to learn node embeddings; **node2vec** (Grover & Leskovec, 2016) designs a biased random walk algorithm to simultaneously preserve Bread-First Search information and Depth-Fisrt Search information, and feed the random walk sequences to word2vec; **VERSE** (Tsitsulin et al., 2018) feeds node similarities (Personalized PageRank, Adajcency Similarity, and SimRank) to the NCE-based objective; **NetSMF** (Qiu et al., 2019) obtains node embeddings by sparse matrix factorization on a sparsified dense random walk matrix; **ProNE** (Zhang et al., 2019) initializes node

embeddings by sparse matrix factorization, and then enhances the embeddings via spectral propagation; **LouvainNE** (Bhowmick et al., 2020) first adopts Louvain graph partition algorithm (Blondel et al., 2008) and then learn node embeddings from the partitions.

Parameter Settings. For all methods that can set the number of threads (node2ket and baselines except ProNE and LouvainNE), we use 8 threads as the default. For all baselines, embedding dimension is set to 128 as the default. For node2ket, we set the number of blocks $B = 1$, the number of negative samples $K = 1$ as the default. For more details of parameter settings of baselines and node2ket, please see Appendix E.2.

5.2 EXPERIMENTS ON NETWORK RECONSTRUCTION

Network reconstruction is used to measure an embedding model's abilitty to preserve nodes' origin local structure. In line with (Wang et al., 2016), for baseline methods, we measure the score of a pair of node embeddings by negative Euclidean distance. While computing the Euclidean distance between two embeddings in the d^C-dimensional Hilbert space is computationally intractable, we use the inner product instead. During the reconstruction process, we calculate the scores between all possible pairs of the embeddings, namely $|\mathcal{V}|(|\mathcal{V}| - 1)/2$ undirected node pairs. Then we sort the scores and select the top-$|\mathcal{E}|$ node pairs, denoted as $\mathcal{E}'$. Then the precision is defined as Precision $= |\mathcal{E} \cap \mathcal{E}'|/|\mathcal{E}|$. For large-scale networks, we use Prec@N to approximately measure the precision. First we sample $(N - 1)|\mathcal{E}|$ randomly matched node pairs as the noise node pairs, denoted as $\mathcal{E}^n$. Then we calculate the scores of edges in $\mathcal{E}^n \cup \mathcal{E}$ and select the top-$|\mathcal{E}|$ pairs as the reconstructed edges. Then the precision is calculated in the same way as the former case. For fair comparison, we fix the random seed the same in the evaluation for different methods.

Evaluation on Medium-scale Networks: We set the embedding dimension as 128 for all the baselines. For node2ket, we set $B = 1$, $C = 8$, and $d = 16$, which means that, to store the embeddings, the number of used parameters for each node is $BCd = 128$, the same as the baselines. For node2ket+, we also set $B = 1$, $C = 8$, and $d = 16$. Note that node2ket+ decreases the number of TUs but bring space consumption of the $r(i, c)$ table, so the average consumed space to store embedding for each node may not be equal to 128. The experimental results are given in Table 1, which shows that **i) both node2ket and node2ket+ achieve the precision that conventional embedding methods can hardly reach by efforts in feature engineering as most works do;** ii) even after decreasing the number of TUs, node2ket+'s performance does not decrease significantly compared with node2ket, indicating that further compressing the embedding model without sacrificing model's performance is still possible.

Evaluation on Large-scale Network (YouTube): We only evaluate baselines that are scalable and could be run on our machine. We set the embedding dimension as 4 for baselines. Since node2ket fails to generate embeddings because it requires TU dimensions $d \geq 4$ and $C \geq 2$, we only evaluate node2ket+, whose used space to store embeddings is a little less than baselines (compressive ratio=0.99). Results are given in Table 2, showing that node2ket+ outperforms baselines mostly and also converges faster compared with other NCE-based embedding methods.

Efficiency Evaluation and Scalability. We conduct the experiments on BlogCatalog. Two questions are raised: to outperform baselines, i) how many training parameters does node2ket need? and ii) how much time does node2ket take? Answers are in Fig. 2 – node2ket achieves to outperforms the best baselines **with 1/64 training parameters** in the evaluation of required training parameters, and with **1/32 training parameters and 1/16 running time** in in the evaluation of running time. The results show both the efficiency on space saving and time saving. The **scalability** has been proved in the experiments on YouTube (Table 2), where it takes about two minutes for the running of node2ket+ on a network of 1 million nodes with 8 CPU threads.

5.3 EXPERIMENTS ON LINK PREDICTION

We randomly mask 1% edges of the given network, and create the same amount of edges as noise edges by randomly connecting nodes in the network. Then, we conduct network embedding on the network where masked edges are removed, and predict the masked edges from the mixture of masked edges and noise edges. The used metric is the same as network reconstruction (Sec. 5.2). Experimental results in Table 3 show that node2ket outperforms all the baselines consistently.

Table 1: Network reconstruction precisions on medium-scale networks. The value between the brackets (e.g. 0.70 with superscript *) is the ratio of used parameters by node2ket+ to store embeddings compared with other methods.

dataset	LINE	node2vec	VERSE	NetSMF	ProNE	LouvainNE ‖	n2k	n2k+
GR-QC	54.19	66.38	56.08	30.26	56.37	43.47	**97.31**	92.43 (0.70*)
BC	4.80	21.16	10.96	7.64	10.10	6.79	**26.07**	25.06 (0.90)
DBLP	2.34	21.17	16.96	18.08	17.76	21.33	86.40	**86.62** (0.77)
PPI	15.18	48.13	27.59	17.14	24.02	17.77	74.07	**82.25** (1.00)

Table 2: Network reconstruction precision on the large-scale network, YouTube.

	Method	Prec@2	Prec@10	Prec@50	Running Time (s)
NCE-based	LINE (Tang et al., 2015)	71.35	36.54	16.92	502.67
	node2vec (Grover & Leskovec, 2016)	44.85	9.80	3.14	3979.52
	VERSE (Tsitsulin et al., 2018)	53.68	34.20	25.08	435.03
Others	ProNE (Zhang et al., 2019)	76.80	41.79	18.96	85.71
	LouvainNE (Bhowmick et al., 2020)	85.74	70.89	**63.12**	8.63
	node2ket+ (ours)	**87.51**	**74.75**	61.69	122.81

Figure 3: Ablation studies on B, C, d, and the adoption of block weights. Experiments of a) and b) are run on GR-QC.

Table 3: Link prediction precisions on medium-scale networks.

dataset	LINE	node2vec	VERSE	NetSMF	ProNE	LouvainNE ‖	node2ket
GR-QC	95.86	91.72	93.79	87.59	93.79	86.90	**97.24**
BC	53.08	77.58	33.35	59.34	75.27	57.99	**81.95**
DBLP	75.45	82.09	68.81	82.09	85.31	73.44	**91.95**
PPI	55.15	77.58	51.55	72.16	73.97	57.99	**79.12**

5.4 ABLATION STUDY

We conduct ablation studies on node2ket, while the conclusions are the same for node2ket+.

Number of TEBs B and Number of Columns C. Experiments of network reconstruction are conducted on GR-QC. We set $w_{ib} = 1/\sqrt{B}$ as constants, $d = 4$, and run node2ket with $C = 2, 4, 8$ and $B = 1, 2, 4$. Results are shown in Fig. 3 a), which shows that model performance improved when C or B increases when d is small. However, we also observe that when d is larger, increasing B will have a negative influence on model performance.

Use Block Weights w_{ib} as Trainable Parameters. Experiments of network reconstruction are conducted on GR-QC. We set $d = 4$, and run node2ket with $C = 2, 4, 8$ and $B = 2, 4$. In Fig. 3 b) we show the improved precision compared with setting w_{ib} as constants, which proves the positive roles of w_{ib} in improving model's expressiveness when d is small. However, when d is larger, trainable w_{ib} is likely to make a negative influence on model performance.

The experimental results for the above two studies when $d = 8$ are in Table 8 in Appendix E.3.

Figure 5: Visualization of the reconstructed adjacency matrix on different levels. A darker color represents a higher value. The subfigure a) is the input circular ladder graph. In b) and c), a color block at the i-th row and j-th column visualizes the sigmoid score of TUs on the two columns in the TEB, i.e. $\sigma\langle\mathbf{u}_{ic}^1, \mathbf{u}_{jc}^1\rangle$ mathematically. In d), a color block at the i-th row and j-th column visualizes the sigmoid score of node embeddings, i.e. $\sigma\langle\mathbf{x}_i, \mathbf{x}_j\rangle$. In e), we binarize the results given by d). And f) is the visualization of the ground-truth adjacency matrix of the graph in a).

Trade-off between Number of Columns C and Embedding Dimension d. Experiments of network reconstruction are conducted on all the medium-scale dataset. We fix $Cd = 64$ and run node2ket with $C = 1, 2, 4, 8, 16, 32$, and plot the results in Fig. 3 c). We see that **i) when $C = 1$, i.e. the tensorized embedding model is degraded to conventional embedding model, the model performance decreases,** and ii) when $d \leq 4$, the performance is also negatively influenced.

5.5 PARALLELIZABILITY AND INTERPRETABILITY

Parallelizability Study. We evaluate node2ket on DBLP. We set $C = 8$, $d = 8$, and run the same number of SGD iterations with the thread number varying from 1 to 16. We record the running time and precision as shown in Fig. 4. The results show that i) the model performance is stable under the setting of different numbers of threads, and ii) the running time t almost decrease linearly w.r.t. the number of threads when the number of threads is not larger than 16.

Figure 4: Parallelizability.

Interpretable Visualization. We conduct node embedding via node2ket on a circular ladder graph of 20 nodes, which is plotted in Fig. 5 a) and the adjacency matrix is visualized in Fig. 5 f). For node2ket, we set $B = 1$, $C = 2$, and $d = 4$. After obtaining the TUs' embeddings, we reconstruct the adjacency matrix from Column 1 and Column 2 of the TEB and visualize them in Fig. 5 b) and c). Then, from the final node embeddings, we compute the reconstructed adjacency matrix and visualize it in real-valued/binarized form as shown in Fig. 5 d) and e). From the results, we have the findings: i) by comparing Fig. 5 b), c), and d), we can see that column 1 and column 2 preserves structures in an approximately orthogonal manner, which means the extracted information is different among columns of a TEB, and ii) by comparing Fig. 5 e) with the ground truth f), node2ket fully reconstruct the input adjacency matrix. To compare the reconstruction performance of different methods on different data, we further investigate a Hypercube graph, 3D-Grid graph, and the real-world Karate Club graph in Appendix E.4. The results directly show the overwhelming performance of node2ket on the network reconstruction reconstruction task.

6 CONCLUSIONS AND FUTURE WORK

We have proposed network embedding methods *node2ket* and *node2ket+*, by training the embedding module *Tensorized Embedding Blocks* with an objective based on Noise Contrastive Estimation.

Limitation & future works. With the (possible) arrival of Noisy Intermediate Scale Quantum (NISQ) era (Preskill, 2018), the deployment of learning on quantum devices is becoming an ever-ubiquitous research topic (Cong et al., 2019). Our method can be explored for its implementation in a more quantum-friendly manner beyond the current quantum-inspired one, e.g. by variational quantum circuits (Cerezo et al., 2021), so that it will be more feasible on quantum device.

REFERENCES

Mohammadreza Armandpour, Patrick Ding, Jianhua Huang, and Xia Hu. Robust negative sampling for network embedding. *Proceedings of the AAAI Conference on Artificial Intelligence*, 33:3191–3198, 07 2019. doi: 10.1609/aaai.v33i01.33013191.

Carl M Bender and Steven A Orszag. *Advanced Mathematical Methods for Scientists and Engineers I: Asymptotic Methods and Perturbation Theory*. Springer Science & Business Media, 2013.

Ayan Kumar Bhowmick, Koushik Meneni, Maximilien Danisch, Jean-Loup Guillaume, and Bivas Mitra. Louvainne: Hierarchical louvain method for high quality and scalable network embedding. In *Proceedings of the 13th International Conference on Web Search and Data Mining*, 2020.

Vincent D Blondel, Jean-Loup Guillaume, Renaud Lambiotte, and Etienne Lefebvre. Fast unfolding of communities in large networks. *Journal of Statistical Mechanics: Theory and Experiment*, 2008(10), 2008.

Bobby-Joe Breitkreutz, Chris Stark, Teresa Reguly, Lorrie Boucher, Ashton Breitkreutz, Michael Livstone, Rose Oughtred, Daniel H Lackner, Jürg Bähler, Valerie Wood, et al. The biogrid interaction database: 2008 update. *Nucleic acids research*, 36(suppl_1):D637–D640, 2007.

Jacob Bridgeman and Christopher Chubb. Hand-waving and interpretive dance: An introductory course on tensor networks. *Journal of Physics A: Mathematical and Theoretical*, 50, 03 2016. doi: 10.1088/1751-8121/aa6dc3.

Jacob C Bridgeman and Christopher T Chubb. Hand-waving and interpretive dance: an introductory course on tensor networks. *Journal of physics A: Mathematical and theoretical*, 50(22):223001, 2017.

Marco Cerezo, Andrew Arrasmith, Ryan Babbush, Simon C Benjamin, Suguru Endo, Keisuke Fujii, Jarrod R McClean, Kosuke Mitarai, Xiao Yuan, Lukasz Cincio, et al. Variational quantum algorithms. *Nature Reviews Physics*, 3(9):625–644, 2021.

Song Cheng, Lei Wang, and Pan Zhang. Supervised learning with projected entangled pair states. *Physical Review B*, 103(12):125117, 2021.

Iris Cong, Soonwon Choi, and Mikhail D Lukin. Quantum convolutional neural networks. *Nature Physics*, 15(12):1273–1278, 2019.

Yuxiao Dong, Nitesh V. Chawla, and Ananthram Swami. metapath2vec: Scalable representation learning for heterogeneous networks. In *Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2017.

Xingbo Du, Junchi Yan, Rui Zhang, and Hongyuan Zha. Cross-network skip-gram embedding for joint network alignment and link prediction. *TKDE*, 2022.

Aditya Grover and Jure Leskovec. node2vec: Scalable feature learning for networks. In *KDD*, pp. 855–864. ACM, 2016.

Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, pp. 297–304, 2010.

Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *Advances in neural information processing systems*, pp. 1024–1034, 2017a.

William L Hamilton, Rex Ying, and Jure Leskovec. Representation learning on graphs: Methods and applications. *arXiv preprint arXiv:1709.05584*, 2017b.

Jure Leskovec, Jon Kleinberg, and Christos Faloutsos. Graph evolution: Densification and shrinking diameters. *ACM transactions on Knowledge Discovery from Data (TKDD)*, 1(1):2–es, 2007.

Yoav Levine, David Yakira, Nadav Cohen, and Amnon Shashua. Deep learning and quantum entanglement: Fundamental connections with implications to network design. *arXiv preprint arXiv:1704.01552*, 2017.

Michael Ley. The DBLP computer science bibliography: Evolution, research issues, perspectives. In *Proc. Int. Symposium on String Processing and Information Retrieval*, pp. 1–10, 2002.

Weiyi Liu, Pin-Yu Chen, Sailung Yeung, Toyotaro Suzumura, and Lingli Chen. Principled multi-layer network embedding. In *2017 IEEE International Conference on Data Mining Workshops (ICDMW)*, pp. 134–141. IEEE, 2017.

Xien Liu, Xinxin You, Xiao Zhang, Ji Wu, and Ping Lv. Tensor graph convolutional networks for text classification. In *Proceedings of the AAAI conference on artificial intelligence*, volume 34, pp. 8409–8416, 2020.

Xindian Ma, Peng Zhang, Shuai Zhang, Nan Duan, Yuexian Hou, Ming Zhou, and Dawei Song. A tensorized transformer for language modeling. *Advances in neural information processing systems*, 32, 2019.

John Martyn, Guifre Vidal, Chase Roberts, and Stefan Leichenauer. Entanglement and tensor networks for supervised image classification. *arXiv preprint arXiv:2007.06082*, 2020.

Tomas Mikolov, Ilya Sutskever, Kai Chen, Greg S Corrado, and Jeff Dean. Distributed representations of words and phrases and their compositionality. In *NIPS*, pp. 3111–3119, 2013.

Michael A Nielsen and Isaac Chuang. Quantum computation and quantum information, 2002.

Román Orús. Tensor networks for complex quantum systems. *Nature Reviews Physics*, 1(9):538–550, 2019.

Aliakbar Panahi, Seyran Saeedi, and Tom Arodz. word2ket: Space-efficient word embeddings inspired by quantum entanglement. In *International Conference on Learning Representations*, 2020.

Bryan Perozzi, Rami Al-Rfou, and Steven Skiena. Deepwalk: Online learning of social representations. In *KDD*, pp. 701–710. ACM, 2014.

John Preskill. Quantum computing in the nisq era and beyond. *Quantum*, 2:79, 2018.

Jiezhong Qiu, Yuxiao Dong, Hao Ma, Jian Li, Chi Wang, Kuansan Wang, and Jie Tang. Netsmf: Large-scale network embedding as sparse matrix factorization. In *The World Wide Web Conference*, pp. 1509–1520. ACM, 2019.

Xipeng Qiu and Xuanjing Huang. Convolutional neural tensor network architecture for community-based question answering. In *Twenty-Fourth international joint conference on artificial intelligence*, 2015.

Meng Qu, Jian Tang, Jingbo Shang, Xiang Ren, Ming Zhang, and Jiawei Han. An attention-based collaboration framework for multi-view network representation learning. In *CIKM*, 2017.

Benjamin Recht, Christopher Re, Stephen Wright, and Feng Niu. Hogwild: A lock-free approach to parallelizing stochastic gradient descent. In *NIPS*, pp. 693–701, 2011.

Leonardo FR Ribeiro, Pedro HP Saverese, and Daniel R Figueiredo. struc2vec: Learning node representations from structural identity. In *KDD*, pp. 385–394. ACM, 2017.

Raghavendra Selvan and Erik B Dam. Tensor networks for medical image classification. In *Medical Imaging with Deep Learning*, pp. 721–732. PMLR, 2020.

Edwin Stoudenmire and David J Schwab. Supervised learning with tensor networks. *Advances in Neural Information Processing Systems*, 29, 2016.

Jian Tang, Meng Qu, Mingzhe Wang, Ming Zhang, Jun Yan, and Qiaozhu Mei. Line: Large-scale information network embedding. In *Proceedings of the 24th International Conference on World Wide Web*, pp. 1067–1077. WWW, 2015.

Lei Tang and Huan Liu. Relational learning via latent social dimensions. In *KDD*, pp. 817–826. ACM, 2009a.

Lei Tang and Huan Liu. Scalable learning of collective behavior based on sparse social dimensions. In *CIKM*, pp. 1107–1116. ACM, 2009b.

Anton Tsitsulin, Davide Mottin, Panagiotis Karras, and Emmanuel Müller. Verse: Versatile graph embeddings from similarity measures. In *Proceedings of the 2018 World Wide Web Conference*, pp. 539–548. International World Wide Web Conferences Steering Committee, 2018.

Daixin Wang, Peng Cui, and Wenwu Zhu. Structural deep network embedding. In *KDD*, pp. 1225–1234. ACM, 2016.

Hao Xiong, Junchi Yan, and Li Pan. Contrastive multi-view multiplex network embedding with applications to robust network alignment. In *Proceedings of the 27th ACM SIGKDD Conference on Knowledge Discovery; Data Mining*, 2021.

Hao Xiong, Junchi Yan, and Zengfeng Huang. Learning regularized noise contrastive estimation for robust network embedding. *IEEE Transactions on Knowledge and Data Engineering*, pp. 1–1, 2022. doi: 10.1109/TKDE.2022.3148284.

Jie Zhang, Yuxiao Dong, Yan Wang, Jie Tang, and Ming Ding. Prone: Fast and scalable network representation learning. In *IJCAI*, 2019.

A ANALYSIS OF SPACE TO STORE/TRAIN EMBEDDINGS

NCE-based NE methods. In general, there are two most widely adopted objectives used network embedding (Armandpour et al., 2019; Xiong et al., 2022):

$$\text{NCE-x:} \quad \sum_{(i,j)\in\mathcal{D}} \Big[\log \sigma(\mathbf{x}_i^\top \mathbf{x}_j) + \sum_{k=1}^{K} \mathbb{E}_{j'\sim\mathbb{P}_n} \log \sigma(-\mathbf{x}_i^\top \mathbf{x}_{j'}) \Big], \quad (8)$$

and

$$\text{NCE-h:} \quad \sum_{(i,j)\in\mathcal{D}} \Big[\log \sigma(\mathbf{x}_i^\top \mathbf{h}_j) + \sum_{k=1}^{K} \mathbb{E}_{j'\sim\mathbb{P}_n} \log \sigma(-\mathbf{x}_i^\top \mathbf{h}_{j'}) \Big]. \quad (9)$$

The NCE-x objective tends to make positively sampled nodes close in the embedding space (when $\mathcal{D}$ is the edge set, it means first-order similarity (Tang et al., 2015)), while the NCE-h objective tends to make nodes with common positive samples close in the embedding space (when $\mathcal{D}$ is the edge set, it means second-order similarity (Tang et al., 2015)). One can see that mathematically NCE-h further utilizes hidden embedding $\mathbf{h}$ compared with NCE-x, and hence NCE-h double the number of training parameters compared with NCE-x. We list the number of parameters of the baseline methods in Table 4.

Table 4: Network embedding methods adopting different types of NCE-based objectives.

Methods	Objectives	Train Emb.	Store Emb.
VERSE (Tsitsulin et al., 2018)	NCE-x	$|\mathcal{V}|p$	
LINE (Tang et al., 2015)	NCE-x + NCE-h	$1.5|\mathcal{V}|p$	$|\mathcal{V}|p$
node2vec (Grover & Leskovec, 2016)	NCE-h	$2|\mathcal{V}|p$	

Node2ket. In this paper, our proposed node2ket adopts NCE-x as the objective, which, however, can be easily substituted with NCE-h by simply doubling the number of TEBs. We list the used parameters of different parts of node2ket in Table 5. Because of its NCE-x core, the numbers of parameters used to train/store embeddings are the same.

Table 5: The number of parameters used to train/store embeddings are the same for node2ket and node2ket+. In the table, 'opt.' is short for 'optional'.

	TU embeddings (TEBs) trainable	Block weights (opt.) trainable/constants	$r(i,c)$ table constants
Node2ket	$BdC|\mathcal{V}|$	$B|\mathcal{V}|$	/
Node2ket+	$Bd\sum_{c=1}^{C} R_c$		$C|\mathcal{V}|$

B RELATIONS TO WORD2KET AND WORD2KETXS

B.1 UNIFYING WORD2KET AND WORD2KETXS BY TEBS

Here we provide detailed explanation on how to use the language of Tensorized Embedding Blocks to describe word2ket and word2ketXS.

Word2ket generates embedding $\mathbf{x}_i$ by:

$$\mathbf{x}_i = \sum_{k=1}^{r} \bigotimes_{j=1}^{n} \mathbf{u}_c^b, \quad (10)$$

where r is the rank and n is the order. Comparing Eq. 10 with the embedding generated by Eq. 3, one can see that in the language of Tensorized Embedding Blocks, the rank is equal to the block number B, the order is equal to the column number C, with block weights $w_{ib} = 1$ set as constants. Though very similar to the way node2ket generates embeddings, it is worth noting that word2ket

requires that $n = 2^y$ because the embeddings are generated from leaf nodes of a complete binary tree thus computation of final embeddings can be speeded up, while in comparison, the column number C of node2ket can be any integer no less than 2.

Word2ketXS generates embedding from linear operators. The embeddings are written as:

$$X = \sum_{k=1}^{r} \bigotimes_{j=1}^{n} U_j^k, \tag{11}$$

where n, r has the same meaning as they are in the word2ket, X is the word embedding linear operator which can be understood as the embedding matrix of shape $p \times |\mathcal{V}|$. We write $X = \{\mathbf{x}_i\}_{i=0}^{|\mathcal{V}|-1}$ where $\mathbf{x}_i$ is i-th column of X and also the embedding of node i. U_j^k is also a linear operator which can be understood as a matrix of shape $q \times t$ ($q^n = p$ and $t^n = |\mathcal{V}|$), and we write it as a set of column vectors $U_j^k = \{\mathbf{u}_{vj}^k\}_{v=0}^{t-1}$. We define $X^k = \{\mathbf{x}_i^k\}_{i=0}^{|\mathcal{V}|-1} = \bigotimes_{j=1}^{n} U_j^k$. By the property of Kronecker product in Lemma 1 whose proof is obvious and omitted, we can find that:

$$\mathbf{x}_{v_1 t^{n-1} + v_2 t^{n-2} + \cdots v_n}^k = \bigotimes_{j=1}^{n} \mathbf{u}_{v_j j}^k, \tag{12}$$

and by $X = \sum_{k=1}^{r} X^b$, we have:

$$\mathbf{x}_{v_1 t^{n-1} + v_2 t^{n-2} + \cdots v_n} = \sum_{k=1}^{r} \bigotimes_{j=1}^{n} \mathbf{u}_{v_j j}^k, \quad v_j = 0, 1, \cdots, t-1. \tag{13}$$

So far we have achieved to write the embedding of word2ketXS in the language of TEBs. It is also worth noting that word2ketXS requires that $n = 2^y$. The reason is the same as word2ket.

Lemma 1 (**Property of Kronecker Product**). *Given two matrix $A^{p \times q} = \{\mathbf{a}_0, \mathbf{a}_1, \cdots, \mathbf{a}_{q-1}\}$, and $B^{m \times n} = \{\mathbf{b}_0, \mathbf{b}_1, \cdots, \mathbf{b}_{n-1}\}$, suppose C is the Kronecker product of A and B, i.e. $C = A \otimes B$, then $C^{pm \times qn} = \{\mathbf{c}_0, \mathbf{c}_1, \cdots, \mathbf{c}_{qn-1}\}$, where $\mathbf{c}_{sm+t} = \mathbf{a}_s \otimes \mathbf{b}_t$.*

B.2 TECHNICAL DIFFERENCES BETWEEN NODE2KET/NODE2KET+ AND WORD2KET/WORD2KETXS

Table 6: Technical differences between word2ket/word2ketXS and node2ket/node2ket+.

	TEBs for Emb. Gen.		Training				Input Data
	Block Weights	Flexible Shape	Decoder	Objective	Full Emb. Required	Emb. Dim.	
word2ket/ word2ketXS	✗	✗	NN	supervised	✔	8000*	sentences (unstructured data)
node2ket/ node2ket+	✔	✔	inner product	contrastive	✗	2^{32}	networks (structured data)

The dimension 8000* is reported in the official paper.

The differences are summarized in Table 6, which are mainly from the following three aspects:

i) The embedding generation. We have shown that both the embedding generation modules of word2ket/word2ketXS are special cases of TEBs in Appendix B.1, and know that the differences of word2ket and word2ketXS lie in the shape of TEBs (B, C, and $\{R_c\}_{c=1}^{C}$) and the definition of $r(i, c)$ indices. Then we can find that the differences between the embedding generation models of word2ket/word2ketXS and node2ket/node2ket+ are mainly whether block weights are adopted and whether the shape of TEBs is flexible to be re-designed. The adoption of block weights is proved to improve model expressiveness when d is small (Fig. 3 b)), and a flexible shape of TEBs is promised to make embedding model more compressive thus improving space efficiency.

ii) The training phase. Word2ket/word2ketXS train embeddings in a supervised way with an NN decoder, while node2ket/node2ket+ train embeddings by NCE (contrastive learning) which mainly cares about the inner product between the embeddings. In this way, full embeddings is required for word2ket/word2ketXS to feed into the decoder but is not a must for node2ket/node2ket+. Therefore,

node2ket/node2ket+ does not need further memory for the full embedding, and achieves to perform embedding in the Hilbert space of a very large dimension (2^{32} in experiments, which can be indeed more than 2^{128} on our machine).

iii) The input data. Word2ket accept sentences as the input data, which is a kind of unstructured data. In comparison, node2ket is designed to process networks which is highly structured, with effort on reshaping TEBs to improve both model expressiveness and space efficiency.

C TECHNICAL DETAILS

C.1 GRADIENT DERIVATION

We provide detailed gradient derivation of Eq. 5 and Eq. 6 here. Given two embeddings:

$$\mathbf{x}_i = \sum_{b=1}^{B} w_{ib} \bigotimes_{c=1}^{C} \mathbf{u}_{r(i,c)c}^b, \quad \mathbf{x}_j = \sum_{b=1}^{B} w_{jb} \bigotimes_{c=1}^{C} \mathbf{u}_{r(j,c)c}^b, \tag{14}$$

we have the inner product:

$$\langle \mathbf{x}_i, \mathbf{x}_j \rangle = \sum_{b}^{B} \sum_{b'=1}^{B} w_{ib} w_{jb'} \prod_{c=1}^{C} \langle \mathbf{u}_{r(i,c)c}^b, \mathbf{u}_{r(j,c)c}^{b'} \rangle, \tag{15}$$

from which we have the partial derivative:

$$\frac{\partial \langle \mathbf{x}_i, \mathbf{x}_j \rangle}{\partial \mathbf{u}_{r(i,c)c}^b} = w_{ib} \sum_{b'=1}^{B} w_{jb'} \mathbf{u}_{r(j,c)c}^{b'} \prod_{c' \neq c} \langle \mathbf{u}_{r(i,c')c'}^b, \mathbf{u}_{r(j,c')c'}^{b'} \rangle. \tag{16}$$

$$\frac{\partial \langle \mathbf{x}_i, \mathbf{x}_j \rangle}{\partial w_{ib}} = \sum_{b'=1}^{B} w_{jb'} \prod_{c=1}^{C} \langle \mathbf{u}_{r(i,c)c}^b, \mathbf{u}_{r(j,c)c}^{b'} \rangle. \tag{17}$$

When (i,j) is a positive sample with label $l = 1$, the objective is $\log \sigma \langle \mathbf{x}_i, \mathbf{x}_j \rangle$, and when it is a negative sample with label $l = 0$, the objective becomes $\log \sigma(-\langle \mathbf{x}_i, \mathbf{x}_j \rangle)$. We define an indicator function $\mathbb{1}_l$ which takes value 1 if $l = 1$ and 0 if $l = 0$, then the objective can be written as $\log \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)$. Then we have the following formula with Eq. 16:

$$
\begin{aligned}
&\frac{\partial \log \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)}{\partial \mathbf{u}_{r(i,c)c}^b} \\
=& \frac{1}{\sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)} \cdot \frac{\partial \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)}{\partial \mathbf{u}_{r(i,c)c}^b} \\
=& (1 - \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)) \frac{\partial \big[2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle\big]}{\partial \mathbf{u}_{r(i,c)c}^b} \\
=& \big[\mathbb{1}_l - \sigma(\langle \mathbf{x}_i, \mathbf{x}_j \rangle)\big] \frac{\partial \langle \mathbf{x}_i, \mathbf{x}_j \rangle}{\partial \mathbf{u}_{r(i,c)c}^b} \\
=& w_{ib} \big[\mathbb{1}_l - \sigma(\langle \mathbf{x}_i, \mathbf{x}_j \rangle)\big] \sum_{b'=1}^{B} w_{jb'} \mathbf{u}_{r(j,c)c}^{b'} \prod_{c' \neq c} \langle \mathbf{u}_{r(i,c')c'}^b, \mathbf{u}_{r(j,c')c'}^{b'} \rangle,
\end{aligned}
\tag{18}
$$

which is the result of Eq. 5.

For the gradient derivation of block weights w_{ib}, Then we have the following formula with Eq. 17:

$$
\begin{aligned}
\frac{\partial \log \sigma(2(\mathbb{1}_l - 0.5)\langle \mathbf{x}_i, \mathbf{x}_j \rangle)}{\partial w_{ib}} &= \big[\mathbb{1}_l - \sigma(\langle \mathbf{x}_i, \mathbf{x}_j \rangle)\big] \frac{\partial \langle \mathbf{x}_i, \mathbf{x}_j \rangle}{\partial w_{ib}} \\
&= \big[\mathbb{1}_l - \sigma(\langle \mathbf{x}_i, \mathbf{x}_j \rangle)\big] \sum_{b'=1}^{B} w_{jb'} \prod_{c=1}^{C} \langle \mathbf{u}_{r(i,c)c}^b, \mathbf{u}_{r(j,c)c}^{b'} \rangle,
\end{aligned}
\tag{19}
$$

which is the result of Eq. 6.

Algorithm 1: A thread of embedding learning via ASGD.

---

1 **Input**: TU embedding dimension d, number of negative samples (for each positive sample): K, node set $\mathcal{V}$, corpus $\mathcal{D}$, initial learning rate η (default 0.025);
  1: Initialize TU embeddings and block weights.
  2: **for all** sample a positive sample (i, j) from $\mathcal{D}$ **do**
  3:     Compute the gradients according to Eq. 5 and Eq. 6 (with regularization adopted) with label $l = 1$.
  4:     Update and normalize TU embeddings for node j.
  5:     **for** $n = 1, 2, \ldots, K$ **do**
  6:         Sample a negative node j';
  7:         Compute the gradients according to Eq. 5 and Eq. 6 with label $l = 0$.
  8:         Update and normalize TU embeddings for node j'.
  9:     **end for**
10:     Update and normalize TU embeddings for node i.
11: **end for**
12: **return** TU embedding set $\{\mathbf{u}^b_{rc}\}$ and block weights $\{w_{ib}\}$;

C.2 MODEL LEARNING

We give the pseudo-code of a thread of ASGD in Algorithm 1. The details of embedding regularization and normalization are in Appendix C.2.1.

C.2.1 EMBEDDING REGULARIZATION AND NORMALIZATION FOR TENSOR UNITS

The multi-column architecture of the Tensorized Embedding Blocks brings difficulties to embedding training. Following unexpected results are likely to happen without proper normalization: i) embeddings converge to zero vectors or vectors of infinite length, ii) embeddings converge to the same vector. We adopts embedding regularization and normalization in the implementation to improve the robustness of the algorithm, as shown in Fig. 6.

Regularization. (Fig. 6 a)) Distance penalty terms can be added to positive node pairs to accelerate model convergence and improve the ability to preserve node proximities (Xiong et al., 2022). In the implementation, we adopt Wasserstein-3 distance regularizaton term over TU embeddings of positive node pairs.

Normalization-1. (Fig. 6 b)) To increase the stability of embedding training, we make TU embeddings constrained by $\|\mathbf{u}_{rc}\| = 1$. In this way, TU embeddings won't converge to vectors of zero or infinite length.

Normalization-2. (Fig. 6 c)) During training, we move the axis towards $-\frac{1}{\sqrt{d}}\mathbf{1}$ for a step. In this way, most of the pairs of embeddings on the unit ball yield a positive inner product. We have known that the inner product of two embeddings $\mathbf{x}_i$ and $\mathbf{x}_j$ is determined by the inner product of the TUs, i.e. $\langle \mathbf{x}_i, \mathbf{x}_j \rangle = \sum_{b}^{B} \sum_{b'=1}^{B} w_{ib} w_{jb'} \prod_{c=1}^{C} \langle \mathbf{u}^b_{r(i,c)c}, \mathbf{u}^{b'}_{r(j,c)c} \rangle$ in Eq. 15. By making most of inner products between embedding pairs positive, we can mostly avoid the cases where two negative inner products of TUs finally yield a positive inner product of the node embeddings.

D PROOF TO THEOREMS

Theorem 1. *Given node set $\mathcal{V}$ and the final embedding dimension p, when $r(i, c) = i$ are constants (indicating $R_c = |\mathcal{V}|, \forall 1 \le c \le C$) and use block weights as trainable parameters, the total number of parameters is $\#params = B(C|\mathcal{V}|d + |\mathcal{V}|)$. Omiting the integer constraints of d, we have:*

$$\min \#params = B|\mathcal{V}|p^{1/\ln p} \ln p + B|\mathcal{V}|.$$

When block weights are set as constants, $\#params = BC|\mathcal{V}|d$, and we have:

$$\min \#params = B|\mathcal{V}|p^{1/\ln p} \ln p.$$

a) Regularization   b) Normalization-1   c) Normalization-2

Figure 6: Embedding regularization and normalization.

Proof. The number of parameters for embeddings is $Bd\sum_c R_c = BC|\mathcal{V}|d$, for block weights it is $B|\mathcal{V}|$. Then the total number of training parameters is:

$$\#\text{params} = BC|\mathcal{V}|d + B|\mathcal{V}| \geq B|\mathcal{V}|Cp^{1/C} + B|\mathcal{V}| := f(C), \tag{20}$$

where $\#\text{params} = f(C)$ iff $d = p^{1/C}$. Then we have the derivative:

$$\frac{\mathrm{d}f(C)}{\mathrm{d}C} = B|\mathcal{V}|p^{1/C}(1 - \frac{1}{C}\log p). \tag{21}$$

When $\frac{\mathrm{d}f(C)}{\mathrm{d}C} = 0$, we can reach the solution $C^* = \ln p$. And we have:

$$f(C^*) = B|\mathcal{V}|p^{1/\ln p}\ln p + B|\mathcal{V}| = \min f(C). \tag{22}$$

Now we can reach the conclusion, when $d = p^{1/C}$ and $C = \ln p$:

$$\min \#\text{params} = B|\mathcal{V}|p^{1/\ln p}\ln p + B|\mathcal{V}|. \tag{23}$$

Following the above proof, it is easy to reach the conclusion $\min \#\text{params} = B|\mathcal{V}|p^{1/\ln p}\ln p$ when block weights are set as constants. $\square$

Before proving Theorem 2, we introduce the following lemma which is obvious by Cauchy inequality:

Lemma 2. $\sum_{c=1}^{C} R_c \geq C(\prod_{c=1}^{C} R_c)^{1/C}$, when the equality holds, $R_1 = R_2 = \cdots = R_C$.

Theorem 2. *Given the node set $\mathcal{V}$ and the final embedding dimension p, when node2ket utilizes both the $r(i, c)$ table and block weights, the total number of parameters is $\#params = Bd\sum_{c=1}^{C} R_c + B|\mathcal{V}| + C|\mathcal{V}|$. We have:*

$$\min \#params < BC^*(p|\mathcal{V}|)^{1/C^*} + B|\mathcal{V}| + C^*|\mathcal{V}|,$$

where $C^* = \sqrt{\left[(\ln p|\mathcal{V}|)^2 - \frac{1}{2}\left(\ln p|\mathcal{V}| + \frac{1}{p|\mathcal{V}|}\right)\right]/(|\mathcal{V}|/B + 1)}$. When block weights are set as constants, we have:

$$\min \#params < BC^*(p|\mathcal{V}|)^{1/C^*} + C^*|\mathcal{V}|. \tag{24}$$

Proof. By Lemma 2, we have:

$$
\begin{aligned}
\#\text{params} &\geq BdC(\prod_{c=1}^{C} R_c)^{1/C} + B|\mathcal{V}| + C|\mathcal{V}| \\
&\geq Bp^{1/C}C(\prod_{c=1}^{C} R_c)^{1/C} + B|\mathcal{V}| + C|\mathcal{V}| \\
&\geq Bp^{1/C}C|\mathcal{V}|^{1/C} + B|\mathcal{V}| + C|\mathcal{V}| \\
&= BC(p|\mathcal{V}|)^{1/C} + B|\mathcal{V}| + C|\mathcal{V}| := f(C),
\end{aligned}
\tag{25}
$$

where the inequality on the first line comes from Lemma 2, the second line comes from $d \geq p^{1/C}$, and the third line comes form $\prod_{c=1}^{C} R_c \geq |\mathcal{V}|$. Then we have the derivative:

$$\frac{\mathrm{d}f(C)}{\mathrm{d}C} = B(p|\mathcal{V}|)^{1/C}\Big(1 - \frac{1}{C}\ln p|\mathcal{V}|\Big) + |\mathcal{V}|, \tag{26}$$

for which it is very hard to solve $\frac{\mathrm{d}f(C)}{\mathrm{d}C} = 0$. To give an approximate solution, we first do Taylor Expansion for $(p|\mathcal{V}|)^{1/C}$ as:

$$(p|\mathcal{V}|)^{1/C} = 1 + \frac{1}{C}\ln p|\mathcal{V}| + \frac{1}{2C^2}\Big(\ln p|\mathcal{V}| + \frac{1}{p|\mathcal{V}|}\Big) + O(\frac{1}{C^3}), \tag{27}$$

according to which we have:

$$\begin{aligned}\frac{\mathrm{d}f(C)}{\mathrm{d}C} &= B\Big[1 + \frac{1}{C}\ln p|\mathcal{V}| + \frac{1}{2C^2}\Big(\ln p|\mathcal{V}| + \frac{1}{p|\mathcal{V}|}\Big) + O(\frac{1}{C^3})\Big]\Big(1 - \frac{1}{C}\ln p|\mathcal{V}|\Big) + |\mathcal{V}| \\ &= B\Big\{1 + \frac{1}{C^2}\Big[\frac{1}{2}\Big(\ln p|\mathcal{V}| + \frac{1}{p|\mathcal{V}|}\Big) - (\ln p|\mathcal{V}|)^2\Big] + O(\frac{1}{C^3})\Big\} + |\mathcal{V}|.\end{aligned} \tag{28}$$

We let $\frac{\mathrm{d}f(C)}{\mathrm{d}C} \approx 0$ omitting the $O(1/C^3)$ term, then we get a solution:

$$C^* = \sqrt{\Big[(\ln p|\mathcal{V}|)^2 - \frac{1}{2}\Big(\ln p|\mathcal{V}| + \frac{1}{p|\mathcal{V}|}\Big)\Big]/(|\mathcal{V}|/B + 1)}, \tag{29}$$

by which $\frac{\mathrm{d}f(C)}{\mathrm{d}C}\Big|_{C=C^*} \approx 0$. Since C^* is an approximate solution, we have $f(C^*) > \min f(C)$, and hence:

$$\min \#\text{params} < f(C^*), \tag{30}$$

which is the first conclusion of the theorem. For the second one, we just need to remove the second $B|\mathcal{V}|$ term in $f(C)$, similar to the proof of Theorem 1. □

E EXPERIMENTS

E.1 STATISTICS OF DATASETS

The statistics of datasets are given in Table 7. All of them are public online.

Table 7: Statistics and network used in our experiments.

Dataset	YouTube	BlogCatalog (BC)	PPI	GR-QC	DBLP
$|\mathcal{V}|$	1,138,499	10,312	3,890	5,242	12,591
$|\mathcal{E}|$	2,990,443	333,983	76,584	14,496	49,627
Avg. degree	5.25	64.78	39.37	5.53	7.88
Type of info.	Social	Social	Biological	Academic	Academic

E.2 DETAILED EXPERIMENTAL SETTINGS

E.2.1 BASELINES

LINE[2] (Tang et al., 2015) models first-order and second-order proximity on the adjacency matrix, trains them separately with edge sampling, and concatenates the representations after normalization on node embedding. The number of samples is set as 1×10^8.

node2vec[3] (Grover & Leskovec, 2016) uses biased random walk to explore both breadth-first and depth-first structure, and train node embedding and hidden embedding by negative sampling. We set $p = 1$ and $q = 1$ in the experiments, and window size 10, walk length 80 and number of walks for each node 80.

---

[2]https://github.com/tangjianpku/LINE
[3]https://github.com/xgfs/node2vec-c

VERSE[4] (Tsitsulin et al., 2018) uses node similarity explicitly by Personalized PageRank (PPR), Adajcency Similarity, and SimRank, and learns node embedding by NCE-x. We use the default version with PPR similarity, damping factor $\alpha = 0.85$. We run 10^5 epochs for each node.

NetSMF[5] (Qiu et al., 2019) obtains node embeddings by sparse matrix factorization on a sparsified dense random walk matrix. We set rank as 512, window size as 10, rounds as 1000, which is the recommended setting by the official code for BlogCatalog.

ProNE[6] (Zhang et al., 2019) initializes embedding by sparse matrix factorization, and then enhances the embedding via spectral propagation. We run Python version in the repository with the default setting, i.e. the term number of the Chebyshev expansion $k = 10$, $\theta = 0.5$, and $\mu = 0.2$. We use the enhanced embedding as the node embedding result.

LouvainNE[7] (Bhowmick et al., 2020) first adopts Louvain graph partition al-gorithm (Blondel et al., 2008) and then learn node embeddings from the partitions. We use Louvain partition as the graph partition algorithm, and set the damping parameter a=0.01 which is the default value in the repository.

E.2.2 NODE2KET AND NODE2KET+

Experimental parameter setting of node2ket in Table 1 (network reconstruction). On **GR-QC**: we do 10M sampling iterations. On **BlogCatalog**: we do 100M sampling iterations. On **DBLP:** we do 20M sampling iterations. On **PPI**: we do 20M sampling iterations.

Experimental parameter setting of node2ket+ in Table 1 (network reconstruction). On **GR-QC**: we do 10M sampling iterations, Louvain graph partition adopts resolution $[800, 1000, 1200, 1400, 1600, 1800, -1, -1]$ (-1 means no parition) for the 8 columns in the TEBs, which results in the row number $[2229, 2495, 2656, 2861, 2978, 3113, 5242, 5242]$. On **BlogCatalog**: we do 100M sampling iterations, Louvain graph partition adopts resolution $[800, 1000, 1200, 1400, 1600, 1800, -1, -1]$ (-1 means no parition) for the 8 columns in the TEBs, which results in the row number $[7122, 7606, 7989, 8296, 8559, 8754, 10312, 10312]$. On **DBLP:** we do 20M sampling iterations, Louvain graph partition adopts resolution $[1000, 1500, 2000, 2500, 3000, -1, -1, -1]$ (-1 means no parition) for the 8 columns in the TEBs, which results in the row number $[4874, 5995, 6944, 7775, 8372, 12591, 12591, 12591]$. On **PPI**: we do 20M sampling iterations, Louvain graph partition adopts resolution $[2000, 2200, 2400, 2600, -1, -1, -1, -1]$ (-1 means no parition) for the 8 columns in the TEBs, which results in the row number $[3372, 3429, 3458, 3505, 3890, 3890, 3890, 3890]$.

Experimental parameter setting of node2ket+ in Table 2 (network reconstruction). We do 1500M sampling iterations, Louvain graph partition adopts resolution $[1500, 3000]$ for the 2 columns in the TEBs, which results in the row number $[81790, 142163]$.

Experimental parameter setting of node2ket and in Table 3 (link prediction). On **GR-QC**: we do 100M sampling iterations, we further sample from 2-hop neighbors for positive samples. On **BlogCatalog**: we do 100M sampling iterations. On **DBLP:** we do 50M sampling iterations, we further sample from 3-hop neighbors for positive samples. On **PPI**: we do 100M sampling iterations, we sample from 3-hop neighbors for positive samples.

E.3 FULL RESULTS OF ABLATION STUDY

The results are give in Table 8. When $B = 1$, w_{ib} becomes meaningless whether w_{ib} are constants or trainable parameters, so the reported results are the same. From the results we see that trainable w_{ib} and the increasing block number B may make a negative influence on the model. It is possibly because the increased number of parameters brings difficulties to model training.

---

[4]https://github.com/xgfs/verse

[5]https://github.com/xptree/NetSMF

[6]https://github.com/THUDM/ProNE

[7]https://github.com/maxdan94/LouvainNE

Table 8: Network reconstruction precisions on GR-QC with $d = 8$.

| | w_{ib} are constants | | | w_{ib} are trainable params | | |
	$C = 2$	$C = 4$	$C = 8$	$C = 2$	$C = 4$	$C = 8$
$B = 1$	71.32	87.04	96.20	71.32	87.04	96.20
$B = 2$	75.16	85.62	93.42	69.01	86.14	92.35
$B = 4$	71.57	79.05	89.43	72.84	83.76	89.39

E.4 VISUALIZATION OF RECONSTRUCTION RESULTS

We investigate a circular ladder graph, a 5-hypercube graph, a 3D-grid graph, and the Karate club graph, and we evaluate all the baselines. The results in Fig. 7 show overwhelming reconstruction ability of node2ket, compared with different methods. We also find that node2ket does not perfectly reconstruct the adjacency matrix for some complex networks, e.g. the 3D-Grid graph and the real-world Karate Club graph.

Settings. All baseline methods use 8-dim embedding. For node2ket we set $L = 1$, $C = 2$, and $d = 4$, whose number of parameters for storing embeddings is the same as baselines.

Figure 7: Visualization of reconstruction results of different embedding methods..