On Solving Class Incremental Learning in Continual Learning

Abstract

Continual learning (CL) is concerned with learning a sequence of tasks incrementally. There are two popular CL settings, *class incremental learning* (CIL) and *task incremental learning* (TIL). A major challenge of CL is *catastrophic forgetting* (CF). While a number of techniques are already available to effectively overcome CF for TIL, CIL remains to be highly challenging. So far, little study has been done to provide a theoretical guidance on how to solve the CIL problem. This paper performs such a study. It first shows that probabilistically, the CIL problem can be decomposed into two sub-problems: *within-task prediction* and *task-id prediction*. It further proves that task-id prediction is correlated to *out-of-distribution* (OOD) detection, which connects CIL and OOD detection and at the same time, offers a principled approach to solving CIL. Experiments have been conducted to empirically verify the theoretical result. Based on the result, new CIL methods are also designed, which outperform strong baselines by a large margin.[1]

1 Introduction

Continual learning aims to incrementally learn a sequence of tasks [1]. Each task consists of a set of classes to be learned together. A major challenge of CL is *catastrophic forgetting* (CF). Two main CL settings have been extensively studied: *class incremental learning* (CIL) and *task incremental learning* (TIL) [2]. In CIL, the learning process builds a single classifier for all tasks/classes learned so far. In testing, a test instance from any class may be presented for the model to classify. No prior task information (e.g., task-id) of the test instance is provided. Formally, CIL is defined as follows.

Class incremental learning (CIL). CIL learns a sequence of tasks, $1, 2, ..., T$. Each task k has a training dataset $\mathcal{D}_k = \{(x_k^i, y_k^i)_{i=1}^{n_k}\}$, where n_k is the number of data samples in task k, and $x_k^i \in \mathbf{X}$ is an input sample and $y_k^i \in \mathbf{Y}_k$ is its class label. All $\mathbf{Y}_k$'s are disjoint and $\bigcup_{k=1}^{T} \mathbf{Y}_k = \mathbf{Y}$. The goal of CIL is to construct a single predictive function or classifier $f : \mathbf{X} \rightarrow \mathbf{Y}$ that can identify the class label y of each given test instance x.

In the TIL setup, each task is a separate classification problem (e.g., one task could be to classify different breeds of dogs and another task could be to classify different types of birds). Here, one model is built for each task in a shared network. In testing, the task-id of each test instance is provided and the system uses only the specific model for the task (dog or bird classification) to classify the test instance. Formally, TIL is defined as follows.

Task incremental learning (TIL). TIL learns a sequence of tasks, $1, 2, ..., T$. Each task k has a training dataset $\mathcal{D}_k = \{((x_k^i, k), y_k^i)_{i=1}^{n_k}\}$, where n_k is the number of data samples in task $k \in \mathbf{T} = \{1, 2, ..., T\}$, and $x_k^i \in \mathbf{X}$ is an input sample and $y_k^i \in \mathbf{Y}_k \subset \mathbf{Y}$ is its class label. The goal of TIL is

---

[1]The code has been submitted in the Supplementary Materials.

to construct a predictor $f : \mathbf{X} \times \mathbf{T} \rightarrow \mathbf{Y}$ to identify the class label $y \in \mathbf{Y}_k$ for (x, k) (the given test instance x from task k).

Several techniques are already available to effectively overcome CF for TIL (with almost no CF) [3, 4]. However, CIL remains to be highly challenging. This work focuses on CIL. Before discussing the proposed work, let us recall the traditional machine learning (ML) paradigm, which builds a classifier based on the training data of a set of classes. The resulting classifier is then used to classify test instances of the same set of classes. This ML paradigm is said to make the *closed-world assumption*, meaning that the classes seen in testing must have been seen in training. However, in many real-life applications, there are unknowns in the testing or application environment, which is called the *open world*. In open world learning, the training (or known) classes are called *in-distribution* (IND) classes. A classifier built for the open world can (1) classify test instances of training/IND classes to their respective classes, which is called *IND prediction*, and also (2) detect test instances that do not belong to any of the IND/known classes but some unknown classes, called *out-of-distribution* (OOD) classes, which is called *OOD detection*. In fact, many OOD detection algorithms can perform both IND prediction and OOD detection [5].

This paper conducts a theoretical study of CIL. Instead of focusing on the traditional PAC generalization bound [6, 7], we focus on how to solve the CIL problem. We first decompose the CIL problem into two sub-problems in a probabilistic framework: *within-task IND prediction* (WIP) and *task-id prediction* (TP). WIP means that the prediction for a test instance is only done within the classes of the task to which the test instance belongs. TP simply predicts the task-id. TP is needed because in CIL, task-id is not provided in testing. This paper then proves based on the popular cross-entropy loss that (1) the CIL performance is bounded by WIP and TP performances, and (2) TP and task OOD detection performance bound each other (which connects CL and OOD detection). These theoretical results provide a principled approach to solving the CIL problem, i.e., designing algorithms that can achieve good WIP performance and TP performances.[2] Since WIP is basically IND prediction for each task and many OOD techniques perform both IND prediction and OOD detection, to achieve a good CIL performance, a strong OOD detection algorithm is needed. Any improvement in OOD detection performance means an improvement in CIL performance.

Based on the theoretical guidance, several new CIL methods are designed, including techniques based on the integration of a TIL method and an OOD detection method for CIL, which outperforms strong baselines by a large margin. This combination is particularly attractive because TIL has achieved no forgetting, and we only need a strong OOD technique that can perform both IND prediction and OOD detection to learn each task to achieve strong CIL performances.

2 Related Work

Despite the fact that numerous CL approaches have been proposed, little study has been done to provide a theoretical guidance on how to solve the problem. Most existing approaches belong to several categories. We briefly review a list of representative methods, but the list of citations is by no means exhaustive. Using regularization [8] and knowledge distillation [9] to minimize the change in previous models are two popular approaches [10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21]. Memorizing some old examples and using them to adjust the old models in learning a new task is another popular approach (called *replay*) [22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32]. Several systems learn to generate pseudo training data of old tasks and use them to jointly train the new task, called *pseudo-replay* [33, 34, 35, 36, 37, 38, 39, 40, 41]. Orthogonal projection learns each task in an orthogonal space to other tasks and thus have minimum interference [42, 43, 44]. Our theoretical analysis is applicable to any continually trained classification model. We try some representative methods from the categories to demonstrate our idea in experiment.

Parameter isolation is yet another popular approach, which makes different subsets (which may overlap) of the model parameters dedicated to different tasks using masks [3, 45] or finding a sub-network for each task by pruning [46, 4, 47]. This approach is particularly suited for the TIL setting. Several methods have almost completely overcome forgetting. HAT [3] and CAT [45] protect previous tasks by masking the important parameters. PackNet [46], CPG [47] and SupSup [4] find an isolated sub-network for each task and use it in inference. HyperNet [48] initializes task-specific parameters conditioned on task-id. ADP [49] decomposes parameters into shared and adaptive parts

---

[2]By no mean do we claim this is the only approach.

to construct an order robust TIL system. CCLL [50] uses task-adaptive calibration on convolution layers. A network of experts is proposed in [51]. We include several approaches in this category in our experiment to show the efficacy of our analysis.

Our methods designed based on the proposed theoretical results make use of two parameter isolation-based TIL methods and two OOD detection methods. The latest strong OOD detection method CSI in [5] helps produce very strong CIL methods. CSI is based on data augmentation [52] and contrastive learning [53]. Excellent surveys of OOD detection include [54, 55].

Some methods have been proposed to use a TIL method for CIL with an additional task-id prediction technique. iTAML [56] requires the test samples to come in batches and each batch must be from a single task. This is not practical as test samples usually come one by one. CCG [57] builds a separate network to predict the task-id. Expert Gate [51] constructs a separate autoencoder for each task. HyperNet [48] and PR-Ent [58] use entropy to predict the task id. Since none of these papers proposed a theoretical study, they did not know that a strong OOD detection algorithm is the key. Our methods based on OOD detection perform dramatically better.

Several theoretical studies have been made on lifelong/continual learning. However, they focus on traditional generalization bound. [6] proposes a PAC-Bayesian framework to provide a learning bound on expected error in future tasks by the average loss on the observed tasks. The work in [59] studies the generalization error by task similarity and [7] studies the dependence of generalization error on sample size or number of tasks including forward and backward transfer. [60] shows that orthogonal gradient descent gives a tighter generalization bound than SGD. Our work is very different as we focus on how to solve the CIL problem. Our work is thus orthogonal to the existing theoretical analysis. Our theoretical finding is applicable to tasks without any underlying relation in similarity.

3 CIL by Within-Task IND Prediction and Task Prediction

This section presents our theoretical study. It first shows that the CIL performance improves if the within-task IND prediction (WIP) performance and/or the task-id prediction (TP) performance improve, and then shows that TP and OOD detection bound each other, which indicates that CIL performance is controlled by WIP and OOD detection, which connects CL and OOD detection research. Finally, we study the necessary conditions for a good CIL model, which includes a good WIP, and a good TP (or a good OOD detection).

3.1 CIL Problem Decomposition

This sub-section first presents the assumptions made by CIL based on its definition and then proposes a decomposition of the CIL problem into two sub-problems. A CL system learns a sequence $\{T_i\}_{i=1}$ of tasks, where T_i is the domain of task i and each task consists of domains of classes as $T_i = \cup_j S_{i,j}$, where j indicates the jth class in task i. Based on the definition of class incremental learning (CIL) (see Section 1), the following assumptions are implied.[3]

Assumption 1. The domains of all classes of the same task are disjoint, i.e., $S_{i,j} \cap S_{i,j'} = \emptyset, \forall j \neq j'$.

Assumption 2. The domains of tasks are disjoint, i.e., $T_i \cap T_{i'} = \emptyset, \forall i \neq i'$.

For any ground event D, the goal of a CIL problem is to learn $\mathbf{P}(x \in S_{i,j}|D)$. This can be decomposed into two probabilities, *within-task IND prediction* (WIP) probability and *task-id prediction* (TP) probability. WIP probability is $\mathbf{P}(x \in S_{i,j}|x \in T_i, D)$ and TP probability is $\mathbf{P}(x \in T_i|D)$. We can rewrite the CIL problem using WIP and TP based on the two assumptions,

$$\mathbf{P}(x \in S_{i_0,j_0}|D) = \sum_{i=1,\ldots,n} \mathbf{P}(x \in S_{i,j_0}|x \in T_i, D)\mathbf{P}(x \in T_i|D) \tag{1}$$

$$= \mathbf{P}(x \in S_{i_0,j_0}|x \in T_{i_0}, D)\mathbf{P}(x \in T_{i_0}|D) \tag{2}$$

where i_0 means a particular task and j_0 a particular class in the task.

Remark 1. Eq. 2 shows that if we can improve either the WIP or TP performance, or both, we can improve the CIL performance.

---

[3]Note that the CIL definition and the subsequent analysis are applicable to tasks with any number of classes (including only one class) and to online CIL where the training data for each task or class comes gradually in a data stream and may also cross task boundaries as our analysis is based on an already-built CIL model.

In the following sub-sections, we develop this further concretely to derive the sufficient and necessary conditions for solving the CIL problem in the context of cross-entropy loss as it is used in almost all supervised CL systems.

3.2 CIL Improves as WIP and/or TP Improve

The study here is based on a *trained CIL model* and not concerned with the algorithm used in training the model. We use cross-entropy as the performance measure of a trained model as it is the most popular loss function used in supervised CL. For experimental evaluation, we use accuracy following classification papers. Denote the cross-entropy of two probability distributions p and q as

$$H(p,q) \stackrel{def}{=} -\mathbb{E}_p[\log q] = -\sum_i p_i \log q_i. \tag{3}$$

For any $x \in T$, let y to be the CIL ground truth label of x, where $y_{i_0,j_0} = 1$ if $x \in S_{i_0,j_0}$ otherwise $y_{i,j} = 0$. Let $\tilde{y}$ be the WIP ground truth label of x, where $\tilde{y}_{i_0,j_0} = 1$ if $x \in S_{i_0,j_0}$ otherwise $\tilde{y}_{i_0,j} = 0$. Let $\bar{y}$ be the TP ground truth label of x, where $\bar{y}_{i_0} = 1$ is $x \in T_{i_0}$ otherwise $\bar{y}_i = 0$. Denote

$$H_{WIP}(x) = H(\tilde{y}, \{\mathbf{P}(x \in S_{i_0,j} | x \in T_{i_0}, D)\}_j), \tag{4}$$

$$H_{CIL}(x) = H(y, \{\mathbf{P}(x \in S_{i,j} | D)\}_{i,j}), \tag{5}$$

$$H_{TP}(x) = H(\bar{y}, \{\mathbf{P}(x \in T_i | D)\}_i) \tag{6}$$

where H_{WIP}, H_{CIL} and H_{TP} are the cross-entropy values of WIP, CIL and TP, respectively. We now present our first theorem. The theorem connects CIL to WIP and TP, and suggests that by having a good WIP or TP, the CIL performance improves as the upper bound for the CIL loss decreases.

Theorem 1. *If $H_{TP}(x) \leq \delta$ and $H_{WIP}(x) \leq \epsilon$, we have $H_{CIL}(x) \leq \epsilon + \delta$.*

The detailed proof is given in Appendix A.1. This theorem holds regardless of whether WIP and TP are trained together or separately. When they are trained separately, if WIP is fixed and we let $\epsilon = H_{WIP}(x)$, $H_{CIL}(x) \leq H_{WIP}(x) + \delta$, which means if TP is better, CIL is better. Similarly, if TP is fixed, we have $H_{CIL}(x) \leq \epsilon + H_{TP}(x)$. When they are trained concurrently, there exists a functional relationship between ϵ and δ depending on implementation. But no matter what it is, when $\epsilon + \delta$ decreases, CIL gets better.

Theorem 1 holds for any $x \in T$ that satisfies $H_{TP}(x) \leq \delta$ or $H_{WIP}(x) \leq \epsilon$. To measure the overall performance under expectation, we present the following corollary.

Corollary 1. *Let $U(T)$ represents the uniform distribution on T. i) If $\mathbb{E}_{x \sim U(T)}[H_{TP}(x)] \leq \delta$, then $\mathbb{E}_{x \sim U(T)}[H_{CIL}(x)] \leq \mathbb{E}_{x \sim U(T)}[H_{WIP}(x)] + \delta$. Similarly, ii) $\mathbb{E}_{x \sim U(T)}[H_{WIP}(x)] \leq \epsilon$, then $\mathbb{E}_{x \sim U(T)}[H_{CIL}(x)] \leq \epsilon + \mathbb{E}_{x \sim U(T)}[H_{TP}(x)]$.*

The detailed proof is given in Appendix A.2. The corollary is a direct extension of Theorem 1 in expectation. The implication is that given TP performance, CIL is positively related to WIP. The better the WIP is, the better the CIL is as the upper bound of the CIL loss decreases. Similarly, given WIP performance, the better TP performance results in the better CIL performance. Due to the positive relation, we can improve CIL by improving either WIP or TP using their respective methods developed in each area.

3.3 Task Prediction (TP) to OOD Detection

Building on Eq. 2, we have studied the relationship of CIL, WIP and TP in Theorem 1. We now connect TP and OOD detection. They are shown to be dominated by each other to a constant factor.

We again use cross-entropy H to measure the performance of TP and OOD detection of a trained network as in Sec. 3.2. To build the connection between $H_{TP}(x)$ and OOD detection of each task, we first define the notations of OOD detection. We use $\mathbf{P}'_i(x \in T_i | D)$ to represent the probability distribution predicted by the ith task's OOD detector. Notice that the task prediction (TP) probability distribution $\mathbf{P}(x \in T_i | D)$ is a categorical distribution over n tasks, while the OOD detection probability distribution $\mathbf{P}'_i(x \in T_i | D)$ is a Bernoulli distribution. For any $x \in T$, define

$$H_{OOD,i}(x) = \begin{cases} H(1, \mathbf{P}'_i(x \in T_i | D)) = -\log \mathbf{P}'_i(x \in T_i | D), \ x \in T_i, \\ H(0, \mathbf{P}'_i(x \in T_i | D)) = -\log \mathbf{P}'_i(x \notin T_i | D), \ x \notin T_i. \end{cases} \tag{7}$$

In CIL, the OOD detection probability for a task can be defined using the output values corresponding to the classes of the task. Some examples of the function is a sigmoid of maximum logit value or a maximum softmax probability after re-scaling to 0 to 1. The following theorem shows that TP and OOD detection bound each other.

Theorem 2. *i)* If $H_{TP}(x) \leq \delta$, let $\mathbf{P}'_i(x \in T_i|D) = \mathbf{P}(x \in T_i|D)$, then $H_{OOD,i}(x) \leq \delta, \forall i = 1, \ldots, n$. *ii)* If $H_{OOD,i}(x) \leq \delta_i, i = 1, \ldots, n$, let $\mathbf{P}(x \in T_i|D) = \frac{\mathbf{P}'_i(x \in T_i|D)}{\sum_j \mathbf{P}'_j(x \in T_j|D)}$, then $H_{TP}(x) \leq (\sum_i \mathbf{1}_{x \in T_i} e^{\delta_i})(\sum_i 1 - e^{-\delta_i})$, where $\mathbf{1}_{x \in T_i}$ is an indicator function.

See Appendix A.3 for the proof. As we use cross-entropy, the lower the bound, the better the performance is. The first statement (i) says that the OOD detection performance improves if the TP performance gets better (i.e., lower δ). Similarly, the second statement (ii) says that the TP performance improves if the OOD detection performance on each task improves (i.e., lower δ_i). Besides, since $(\sum_i \mathbf{1}_{x \in T_i} e^{\delta_i})(\sum_i 1 - e^{-\delta_i})$ converges to 0 as δ_i's converge to 0 in order of $O(|\sum_i \delta_i|)$, we further know that H_{TP} and $\sum_i H_{OOD,i}$ are equivalent in quantity up to a constant factor.

In Theorem 1, we studied how CIL is related to WIP and TP. In Theorem 2, we showed that TP and OOD bound each other. Now we explicitly give the upper bound of CIL in relation to WIP and OOD detection of each task. The detailed proof can be found in Appendix A.4.

Theorem 3. *If $H_{OOD,i}(x) \leq \delta_i$, $i = 1, \ldots, n$ and $H_{WIP}(x) \leq \epsilon$, we have*

$$H_{CIL}(x) \leq \epsilon + (\sum_i \mathbf{1}_{x \in T_i} e^{\delta_i})(\sum_i 1 - e^{-\delta_i}),$$

where $\mathbf{1}_{x \in T_i}$ is an indicator function.

3.4 Necessary Conditions for Improving CIL

In Theorem 1, we showed that the good performance of WIP and TP is sufficient to guarantee a good performance of CIL. In Theorem 3, we showed that the good performance of WIP and OOD is sufficient to guarantee a good performance of CIL. For completeness, we study the necessary conditions of a well-performed CIL in this sub-section.

Theorem 4. *If $H_{CIL}(x) \leq \eta$, then there exist i) a WIP, s.t. $H_{WIP}(x) \leq \eta$, ii) a TP, s.t. $H_{TP}(x) \leq \eta$, and iii) an OOD detector for each task, s.t. $H_{OOD,i} \leq \eta$, $i = 1, \ldots, n$.*

The detailed proof is given in Appendix A.5. This theorem tells that if a good CIL model is trained, then a good WIP, a good TP and a good OOD detector for each task are always implied. More importantly, by transforming Theorem 4 into its contraposition, we have the following statements: If for any WIP, $H_{WIP}(x) > \eta$, then $H_{CIL}(x) > \eta$. If for any TP, $H_{TP}(x) > \eta$, then $H_{CIL}(x) > \eta$. If for any OOD detector, $H_{OOD,i}(x) > \eta$, $i = 1, \ldots, n$, then $H_{CIL}(x) > \eta$. Regardless of whether WIP, TP and OOD detection are defined explicitly or implicitly by a CIL algorithm, good WIP, good TP and good OOD detection are necessary for a good CIL performance.

Remark 2. It is important to note that our study in this section is based on a CIL model that has already been built. In other words, it tells the CIL designers what should be achieved in the final model. Clearly, one would also like to know how to design a strong CIL model based on the theoretical results, which also considers catastrophic forgetting (CF). One effective method is to make use of a strong existing TIL algorithm, which can already achieve no or little forgetting (CF), and combine it with a strong OOD detection algorithm (as mentioned earlier, most OOD detection methods can also perform WIP). Thus, any improved method from the OOD detection community can be applied to CIL to produce improved CIL systems (see Sections 4.3 and 4.4).

Recall in Section 2, we reviewed prior works that have tried to use a TIL method for CIL with a task-id prediction method [48, 51, 56, 57, 58]. However, since they did not know that the key to the success of this approach is a strong OOD detection algorithm, they are weak (see Section 4).

4 New CIL Techniques and Experiments

Based on Theorem 3, we have designed several new CIL methods, each of which integrates an existing CL algorithm and an OOD detection algorithm. The OOD detection algorithms that we use can perform both within-task IND prediction (WIP) and OOD detection. Our experiments have two

goals: (1) to show that a good OOD detection method can help improve the accuracy of an existing CIL algorithm, and (2) to fully compare two of these methods with strong baselines to show that they outperform the existing strong baselines considerably.

4.1 Datasets, CL Baselines and OOD Detection Methods

Datasets and CIL Tasks. Four popular benchmark image classification datasets are used, from which six CIL problems are created following the recent methods [20, 29, 21]. **(1)** *MNIST* consists of handwritten images of 10 digits with 60,000 examples for training and 10,000 examples for testing. We create a CIL problem (**M-5T**) by splitting it into 5 tasks where each task consists of 2 consecutive classes. **(2)** *CIFAR-10* consists of 32x32 color images of 10 classes in 60,000 samples with 50,000 training samples and 10,000 test samples. We create a CIL problem (**C10-5T**) by splitting it into 5 tasks with 2 consecutive classes per task. **(3)** *CIFAR-100* consists of 60,000 32x32 color images of which 50,000 are training and 10,000 are testing samples. We create two CIL problems by splitting 100 classes into 10 tasks (**C100-10T**) and 20 tasks (**C100-20T**), where each task has 10 and 5 classes, respectively. **(4)** *Tiny-ImageNet* has 120,000 64x64 color images of 200 classes with 500 images per class for training and 50 images per class for testing. We create two CIL problems by splitting 200 classes into 5 tasks (**T-5T**) and 10 tasks (**T-10T**), where each task has 40 and 20 classes, respectively.

Baseline CL Methods. We include different families of CL methods to verify our theoretical result: *regularization*, *orthogonal projection*, *replay*, and *parameter isolation*. EWC [8], MUC [20], and PASS [21] are regularization-based methods. OWM [42] is an orthogonal projection method. For replay methods, we use LwF [9], iCaRL [24], Mnemonics [61], BiC [27], DER++ [29], and Co^{2}L [32]. Finally, for parameter isolation, we use CCG [57], HyperNet [48], HAT [3], SupSup [4] (or Sup), and PR [58].[4] We use the official codes for the baselines except for Co^{2}L, CCG, and PR. For these three systems, we copy the results from their original papers as CCG does not released its code and we are unable to run Co^{2}L and PR on our machines.

OOD Detection Methods. Two OOD detection methods are used to verify the theoretical results by combining them with the above existing CL algorithms. Both these methods can also perform *within-task IND prediction* (WIP).

(1). ODIN: Researchers have proposed several methods to improve the OOD detection performance of a trained network by post-processing [62, 63, 64]. ODIN [64] is a representative method. It adds perturbation to input and applies a temperature scaling to the softmax output of a trained network.

(2). CSI: It is a recently proposed OOD detection technique [5] that is highly effective. It is based on data and class label augmentation and supervised contrastive learning [65]. Its rotation data augmentations create distributional shifted samples to act as negative data for the original samples for contrastive learning. We will discuss the details about CSI in Appendix D.

4.2 Training Details and Evaluation Metrics

Training Details. For backbone structure, we follow [21, 29, 4]. AlexNet-like architecture [66] is used for MNIST and ResNet-18 [67] is used for CIFAR-10. For CIFAR-100 and Tiny-ImageNet, ResNet-18 is also used as CIFAR-10, but the number of channels are doubled to fit more classes. All the methods use the same backbone architecture except for OWM and HyperNet, for which we use their original architectures. OWM uses AlexNet. It is not obvious how to apply the technique to the ResNet structure. HyperNet uses a fully-connected network and ResNet-32 for MNIST and other datasets, respectively. We are unable to change the structure due to model initialization arguments unexplained in the original paper. For the replay methods, we use memory buffer 200 for MNIST and CIFAR-10 and 2000 for CIFAR-100 and Tiny-ImageNet as in [24, 29]. We use the hyper-parameters suggested by the authors. If we could not reproduce the result, we use 10% of the training data as a validation set to grid-search for good hyper-parameters. For our proposed methods, we report the hyper-parameters in Appendix F. All the results are averages over 5 runs with random seeds.

Evaluation Metrics.

---

[4]**iTAML** [56] is not included as it requires a batch of test data from the same task to predict the task-id. When each batch has only one test sample, which is our setting, it is very weak. For example, iTAML CIL accuracy is only 33.5% on C100-10T. **Expert Gate** (EG) [51] is also very weak. For example, its CIL accuracy is only 43.2 on M-5T. Both iTAML and EG are much weaker than many baselines.

(1). *Average classification accuracy* over all classes after learning the last task. The final class prediction depends on implementation (see *Prediction Methods* below).

(2). *Average AUC* (Area Under the ROC Curve) over all task models for the evaluation of OOD detection. AUC is the main measure used in OOD detection papers. Using this measure, we show that a better OOD detection method will result in a better CIL performance. Let AUC_k be the AUC score of task k. It is computed by using only the model (or classes) of task k to score the test data of task k as the in-distribution (IND) data and the test data from other tasks as the out-of-distribution (OOD) data. The average AUC score is: $AUC = \sum_k AUC_k / n$, where n is the number of tasks.

Note that we don't study **forgetting rate** because to show that better WIP and TP (or OOD detection) result in better CIL performance (Sec. 4.3), we use existing systems and perform only post-processing using ODIN, which does not affect the original training and thus does not change their forgetting (CF) profile. It is not straightforward to change their existing training algorithms to include a new OOD detection method that needs training, e.g., CSI, except for the TIL (task incremental learning) methods, e.g., HAT and Sup. For these two TIL methods, we can simply switch their methods for learning each task with CSI (see Sec. 4.4). HAT and Sup have little or no forgetting.

Prediction Methods: The theoretical results in Sec. 3 states that we use Eq. 2 to perform the final prediction. The first probability (for WIP) in Eq. 2 is easy to get as we can simply use the softmax values of the classes in each task. However, the second probability in Eq. 2 (for TP) is trickier as each task is learned without the data of other tasks. There can be many options.

We take the following approaches for prediction (which are a special case of Eq. 2, see below):

(1). For those approaches that use a single classification head to include all classes learned so far, we predict as follows (which is also the approach taken by the existing papers.)

$$\hat{y} = \arg\max f(x) \tag{8}$$

where $f(x)$ is the logit output of the network.

(2). For multi-head methods (e.g., HAT, HyperNet, and Sup), which use one head for each task, we use the concatenated output as

$$\hat{y} = \arg\max \bigoplus_i f(x)_i \tag{9}$$

where $\bigoplus$ indicate concatenation and $f(x)_i$ is the output of task i.[5]

These methods (in fact, they are the same method used in two different settings) is a special case of Eq. 2 if we define OOD_i as $\sigma(\max f(x)_i)$, where σ is the sigmoid. Hence, the theoretical results in Sec. 3 are still applicable. We present a detailed explanation about this prediction method and some other options in Appendix C. These two approaches work quite well.

4.3 Better OOD Detection Produces Better CIL Performance

The key theoretical result in Sec. 3 is that better OOD detection will produce better CIL performance. Recall our considered methods ODIN and CSI can perform both WIP and OOD detection.

Applying ODIN: We first train the baseline models using their original algorithms, and then apply temperature scaling and input noise of ODIN at testing for each task (no training data needed). More precisely, the output of class j in task i changes by temperature scaling factor τ_i of task i as

$$s(x; \tau_i)_j = e^{f(x)_{ij}/\tau_j} / \sum_j e^{f(x)_{ij}/\tau_i} \tag{10}$$

and the input changes by the noise factor ϵ_i as

$$\tilde{x} = x - \epsilon_i \text{sign}(-\nabla_x \log s(x; \tau_i)_{\hat{y}}) \tag{11}$$

---

[5]**Sup** paper proposed an one-shot task-id prediction assuming that the test instances come in a batch and all belong to the same task like iTAML. We assume a single test instance per batch. its task-id prediction results in accuracy of 50.2 on C10-5T, which is much lower than 62.6 by using Eq. 9. The task-id prediction of **HyperNet** also does not work well. The accuracy by id prediction is 49.34 on C10-5T while it is 53.4 using Eq. 9. **PR** uses entropy to find task-id, and then performs within-task IND prediction. Among many variations of PR, we use the variations that perform the best at each dataset with memory free and single sample per batch at testing (i.e., no PR-BW).

where $\hat{y}$ is the class with maximum output value in task i. This is a positive adversarial example inspired by [68]. The values τ_i and ϵ_i are hyper-parameters and we use the same values for all tasks except for PASS, for which we had to use a validation set to tune τ_i (see Appendix B).

Tab. 1 shows the results on C100-10T. The CIL results clearly show that the CIL performance increases if the AUC increases with ODIN. For instance, the CIL of DER++ and Sup improves from 53.71 to 55.29 and 44.58 to 46.74, respectively, as the AUC increases from 85.99 to 88.21 and 79.16 to 80.58. It shows that when this method is incorporated into each task model in existing trained CIL network, the CIL performance of the original method improves. We note that ODIN does not always improve the average AUC. For those experienced a decrease in AUC, the CIL performance also decreases except LwF. The inconsistency of LwF is due to its severe classification bias towards later tasks as discussed in BiC [27]. The temperature scaling in ODIN has a similar effect as the bias correction in BiC, and the CIL of LwF becomes close to that of BiC after the correction. Regardless of whether ODIN improves AUC or not, the positive correlation between AUC and CIL (except LwF) verifies the efficacy of Theorem 3, indicating better OOD detection results in better CIL performances.

Applying CSI: We now apply the OOD detection method CSI. Due to its sophisticated data augmentation, supervised constrative learning and results ensemble, it is hard to apply CSI to other baselines without fundamentally change them except HAT and Sup (SupSup) as these methods are parameter isolation-based TIL methods. We can simply replace their model for training each task with CSI wholesale (the full detail is given Appendix D). As mentioned earlier, both HAT and SupSup as TIL methods have almost no forgetting.

Table 1: Performance comparison based on C100-10T between the original output and output post-processed with OOD detection technique ODIN. Note that ODIN is not applicable to iCaRL and Mnemonics as they are not based on softmax but some distance functions. The results for other datasets are reported in Appendix B.

Method	OOD	AUC	CIL
OWM	Original	71.31	28.91
	ODIN	70.06	28.88
MUC	Original	72.69	30.42
	ODIN	72.53	29.79
PASS	Original	69.89	33.00
	ODIN	69.60	31.00
LwF	Original	88.30	45.26
	ODIN	87.11	51.82
BiC	Original	87.89	52.92
	ODIN	86.73	48.65
DER++	Original	85.99	53.71
	ODIN	88.21	55.29
HAT	Original	77.72	41.06
	ODIN	77.80	41.21
HyperNet	Original	71.82	30.23
	ODIN	72.32	30.83
Sup	Original	79.16	44.58
	ODIN	80.58	46.74

Table 2 reports the results of using CSI and ODIN, where ODIN is a weaker OOD detection method than CSI. Both HAT and Sup improve greatly as the systems are equipped with a better OOD detection method CSI.

In summary, these experiment results empirically demonstrate the efficacy of Theorem 3, i.e., the CIL performance can be improved if a better OOD detection method is used.

Table 2: Average CIL and AUC of HAT and Sup with OOD detection methods ODIN and CSI. ODIN is a traditional OOD detection method while CSI is a recent OOD detection method known to be better than ODIN. As CL methods produce better OOD detection performance by CSI, their CIL performances are better than the ODIN counterparts.

CL	OOD	C10-5T		C100-10T		C100-20T		T-5T		T-10T	
		AUC	CIL	AUC	CIL	AUC	CIL	AUC	CIL	AUC	CIL
HAT	ODIN	82.5	62.6	77.8	41.2	75.4	25.8	72.3	38.6	71.8	30.0
	CSI	91.2	87.8	84.5	63.3	86.5	54.6	76.5	45.7	78.5	47.1
Sup	ODIN	82.4	62.6	80.6	46.7	81.6	36.4	74.0	41.1	74.6	36.5
	CSI	91.6	86.0	86.8	65.1	88.3	60.2	77.1	48.9	79.4	45.7

4.4 Full Comparison of HAT+CSI and Sup+CSI with Baselines

We now make a full comparison of the two strong systems (HAT+CSI and Sup+CSI) designed based on the theoretical results. These combinations are particularly attractive because both HAT and Sup are TIL systems and have little or no CF. Then a strong OOD method (that can also perform WIP

Table 3: Average accuracy after all tasks are learned. Memory free methods are italicized. † indicates that in their original papers, PASS and Mnemonics are pre-trained with the first half of the classes. Their results with pre-train are 50.1 and 53.5 on C100-10T, respectively, which are still much lower than the proposed HAT+CSI and Sup+CSI without pre-training. We do not use pre-training in our experiment for fairness. ∗ indicates that iCaRL and Mnemonics report average incremental accuracy in their original papers. We report average accuracy over all classes after all tasks are learned.

Method	M-5T	C10-5T	C100-10T	C100-20T	T-5T	T-10T
OWM	95.8±0.13	51.8±0.05	28.9±0.60	24.1±0.26	10.0±0.55	8.6±0.42
MUC	74.9±0.46	52.9±1.03	30.4±1.18	14.2±0.30	33.6±0.19	17.4±0.17
PASS†	76.6±1.67	47.3±0.98	33.0±0.58	25.0±0.69	28.4±0.51	19.1±0.46
LwF.R	85.5±3.11	54.7±1.18	45.3±0.75	44.3±0.46	32.2±0.50	24.3±0.26
iCaRL∗	96.0±0.43	63.4±1.11	51.4±0.99	47.8±0.48	37.0±0.41	28.3±0.18
Mnemonics†∗	96.3±0.36	64.1±1.47	51.0±0.34	47.6±0.74	37.1±0.46	28.5±0.72
BiC	94.1±0.65	61.4±1.74	52.9±0.64	48.9±0.54	41.7±0.74	33.8±0.40
DER++	95.3±0.69	66.0±1.20	53.7±1.30	46.6±1.44	35.8±0.77	30.5±0.47
Co²L			65.6			
CCG	97.3		70.1			
HAT	81.9±3.74	62.7±1.45	41.1±0.93	25.6±0.51	38.5±1.85	29.8±0.65
HyperNet	56.6±4.85	53.4±2.19	30.2±1.54	18.7±1.10	7.9±0.69	5.3±0.50
Sup	70.1±1.51	62.4±1.45	44.6±0.44	34.7±0.30	41.8±1.50	36.5±0.36
PR-Ent	74.1	61.9	45.2			
HAT+CSI	94.4±0.26	87.8±0.71	63.3±1.00	54.6±0.92	45.7±0.26	47.1±0.18
Sup+CSI	80.7±2.71	86.0±0.41	65.1±0.39	60.2±0.51	48.9±0.25	45.7±0.76
HAT+CSI+c	96.9±0.30	88.0±0.48	65.2±0.71	58.0±0.45	51.7±0.37	47.6±0.32
Sup+CSI+c	81.0±2.30	87.3±0.37	65.2±0.37	60.5±0.64	49.2±0.28	46.2±0.53

(within-task IND prediction)) will result in a strong CIL method. Since HAT and Sup are memory free CL methods, HAT+CSI and Sup+CSI also do not need to save any previous task data. Tab. 5 shows that HAT and Sup equipped with CSI outperform the baselines by large margins. DER++, the best replay method, achieves 66.0 and 55.3 on C10-5T and C100-10T, respectively, while HAT+CSI achieves 87.8 and 63.3 and Sup+CSI achieves 85.6 and 65.5. The large performance gap remains consistent in more challenging problems, T-5T and T-10T. We note that Sup works very poorly on M-5T, but Sup+CSI improved it drastically, although still very weak compared to HAT+CSI.

Due to the definition of OOD in the prediction method and the fact that each task is trained separately in HAT and Sup, the outputs $f(x)_i$ from different tasks can be in different scales, which will result in incorrect predictions. To deal with the problem, we can calibrate the output as $\alpha_i f(x)_i + \beta_i$ and use $OOD_i = \sigma(\alpha_i f(x)_i + \beta_i)$. The optimal α_i^* and β_i^* for each task i can be found by optimization with a memory buffer to save a very small number of training examples from previous tasks like that in the replay-based methods. We refer the calibrated methods as HAT+CSI+c and Sup+CSI+c. They are trained by using the memory buffer of the same size as the replay methods (see Section 4.2). Tab. 5 shows that the calibration improves from their memory free versions, i.e., without calibration. We provide the details about how to train the calibration parameters α_i and β_i in Appendix E.

5 Conclusion

This paper proposed a principled guidance on solving the highly challenging continual learning problem, *class incremental learning* (CIL). It decomposed the CIL prediction into *within-task in-distribution prediction* (WIP) and *task-id prediction* (TP). It further theoretically demonstrated that TP is correlated to *out-of-distribution* (OOD) detection, and showed that CIL problem can be solved by WIP, TP and/or OOD detection. It also proved that a good performance in the three is necessary for a good CIL model. Experimental results verified the efficacy of the theoretical results. Furthermore, based on the theoretical guidance, several new CIL methods have been designed. They outperform the strong baselines by large margins.

Limitations: There are many options to define WIP and TP (or OOD). This paper took a simple way. Although it performed well, in our future work, we will try to study how to optimize them.

References

[1] German Ignacio Parisi, Ronald Kemker, Jose L. Part, Christopher Kanan, and Stefan Wermter. Continual lifelong learning with neural networks: A review. *Neural Networks*, 2019.

[2] Gido M van de Ven and Andreas S Tolias. Three scenarios for continual learning. *arXiv preprint arXiv:1904.07734*, 2019.

[3] Joan Serrà, Dídac Surís, Marius Miron, and Alexandros Karatzoglou. Overcoming catastrophic forgetting with hard attention to the task. In *ICML*, 2018.

[4] Mitchell Wortsman, Vivek Ramanujan, Rosanne Liu, Aniruddha Kembhavi, Mohammad Rastegari, Jason Yosinski, and Ali Farhadi. Supermasks in superposition. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *NeurIPS*, 2020.

[5] Jihoon Tack, Sangwoo Mo, Jongheon Jeong, and Jinwoo Shin. Csi: Novelty detection via contrastive learning on distributionally shifted instances. In *NeurIPS*, 2020.

[6] Anastasia Pentina and Christoph Lampert. A pac-bayesian bound for lifelong learning. In *International Conference on Machine Learning*, pages 991–999. PMLR, 2014.

[7] Ryo Karakida and Shotaro Akaho. Learning curves for continual learning in neural networks: Self-knowledge transfer and forgetting. In *International Conference on Learning Representations*, 2022.

[8] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the national academy of sciences*, 114(13):3521–3526, 2017.

[9] Zhizhong Li and Derek Hoiem. Learning Without Forgetting. In *ECCV*, pages 614–629. Springer, 2016.

[10] Heechul Jung, Jeongwoo Ju, Minju Jung, and Junmo Kim. Less-forgetting learning in deep neural networks. *arXiv preprint arXiv:1607.00122*, 2016.

[11] Raffaello Camoriano, Giulia Pasquale, Carlo Ciliberto, Lorenzo Natale, Lorenzo Rosasco, and Giorgio Metta. Incremental robot learning of new objects with fixed update time. In *ICRA*, 2017.

[12] Friedemann Zenke, Ben Poole, and Surya Ganguli. Continual learning through synaptic intelligence. In *ICML*, pages 3987–3995, 2017.

[13] Hippolyt Ritter, Aleksandar Botev, and David Barber. Online structured laplace approximations for overcoming catastrophic forgetting. In *NeurIPS*, 2018.

[14] Jonathan Schwarz, Jelena Luketina, Wojciech M Czarnecki, Agnieszka Grabska-Barwinska, Yee Whye Teh, Razvan Pascanu, and Raia Hadsell. Progress & compress: A scalable framework for continual learning. *arXiv preprint arXiv:1805.06370*, 2018.

[15] Ju Xu and Zhanxing Zhu. Reinforced continual learning. In *NeurIPS*, 2018.

[16] Francisco M Castro, Manuel J Marín-Jiménez, Nicolás Guil, Cordelia Schmid, and Karteek Alahari. End-to-end incremental learning. In *ECCV*, pages 233–248, 2018.

[17] Prithviraj Dhar, Rajat Vikram Singh, Kuan-Chuan Peng, Ziyan Wu, and Rama Chellappa. Learning without memorizing. In *CVPR*, 2019.

[18] Kibok Lee, Kimin Lee, Jinwoo Shin, and Honglak Lee. Overcoming catastrophic forgetting with unlabeled data in the wild. In *CVPR*, 2019.

[19] Hongjoon Ahn, Sungmin Cha, Donggyu Lee, and Taesup Moon. Uncertainty-based continual learning with adaptive regularization. In *NeurIPS*, 2019.

[20] Yu Liu, Sarah Parisot, Gregory Slabaugh, Xu Jia, Ales Leonardis, and Tinne Tuytelaars. More classifiers, less forgetting: A generic multi-classifier paradigm for incremental learning. In *ECCV*, pages 699–716. Springer International Publishing, 2020.

[21] Fei Zhu, Xu-Yao Zhang, Chuang Wang, Fei Yin, and Cheng-Lin Liu. Prototype augmentation and self-supervision for incremental learning. In *CVPR*, 2021.

[22] Andrei A Rusu, Neil C Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks. *arXiv preprint arXiv:1606.04671*, 2016.

[23] David Lopez-Paz and Marc'Aurelio Ranzato. Gradient Episodic Memory for Continual Learning. In *NeurIPS*, pages 6470–6479, 2017.

[24] Sylvestre-Alvise Rebuffi, Alexander Kolesnikov, and Christoph H Lampert. iCaRL: Incremental classifier and representation learning. In *CVPR*, pages 5533–5542, 2017.

[25] Arslan Chaudhry, Marc'Aurelio Ranzato, Marcus Rohrbach, and Mohamed Elhoseiny. Efficient lifelong learning with a-gem. In *ICLR*, 2019.

[26] Saihui Hou, Xinyu Pan, Chen Change Loy, Zilei Wang, and Dahua Lin. Learning a unified classifier incrementally via rebalancing. In *CVPR*, pages 831–839, 2019.

[27] Yue Wu, Yinpeng Chen, Lijuan Wang, Yuancheng Ye, Zicheng Liu, Yandong Guo, and Yun Fu. Large scale incremental learning. In *CVPR*, 2019.

[28] David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P. Lillicrap, and Greg Wayne. Experience replay for continual learning. In *NeurIPS*, 2019.

[29] Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: a strong, simple baseline. In *NeurIPS*, 2020.

[30] Jathushan Rajasegaran, Munawar Hayat, Salman Khan, Fahad Shahbaz Khan, Ling Shao, and Ming-Hsuan Yang. An adaptive random path selection approach for incremental learning, 2020.

[31] Yaoyao Liu, Bernt Schiele, and Qianru Sun. Adaptive aggregation networks for class-incremental learning. In *CVPR*, 2021.

[32] Hyuntak Cha, Jaeho Lee, and Jinwoo Shin. Co2l: Contrastive continual learning. In *ICCV*, 2021.

[33] Alexander Gepperth and Cem Karaoguz. A bio-inspired incremental learning architecture for applied perceptual problems. *Cognitive Computation*, 8(5):924–934, 2016.

[34] Nitin Kamra, Umang Gupta, and Yan Liu. Deep Generative Dual Memory Network for Continual Learning. *arXiv preprint arXiv:1710.10368*, 2017.

[35] Hanul Shin, Jung Kwon Lee, Jaehong Kim, and Jiwon Kim. Continual learning with deep generative replay. In *NIPS*, pages 2994–3003, 2017.

[36] Chenshen Wu, Luis Herranz, Xialei Liu, Joost van de Weijer, Bogdan Raducanu, et al. Memory replay gans: Learning to generate new categories without forgetting. In *NeurIPS*, 2018.

[37] Ari Seff, Alex Beatson, Daniel Suo, and Han Liu. Continual learning in generative adversarial nets. *arXiv preprint arXiv:1705.08395*, 2017.

[38] Ronald Kemker and Christopher Kanan. FearNet: Brain-Inspired Model for Incremental Learning. In *ICLR*, 2018.

[39] Wenpeng Hu, Zhou Lin, Bing Liu, Chongyang Tao, Zhengwei Tao, Jinwen Ma, Dongyan Zhao, and Rui Yan. Overcoming catastrophic forgetting for continual learning via model adaptation. In *ICLR*, 2019.

[40] Mohammad Rostami, Soheil Kolouri, and Praveen K. Pilly. Complementary learning for overcoming catastrophic forgetting using experience replay. In *IJCAI*, 2019.

[41] Oleksiy Ostapenko, Mihai Puscas, Tassilo Klein, Patrick Jahnichen, and Moin Nabi. Learning to remember: A synaptic plasticity driven framework for continual learning. In *CVPR*, pages 11321–11329, 2019.

[42] Guanxiong Zeng, Yang Chen, Bo Cui, and Shan Yu. Continuous learning of context-dependent processing in neural networks. *Nature Machine Intelligence*, 2019.

[43] Yiduo Guo, Wenpeng Hu, Dongyan Zhao, and Bing Liu. Adaptive orthogonal projection for batch and online continual learning. In *Proceedings of AAAI-2022*, 2022.

[44] Arslan Chaudhry, Naeemullah Khan, Puneet K. Dokania, and Philip H. S. Torr. Continual learning in low-rank orthogonal subspaces, 2020.

[45] Zixuan Ke, Bing Liu, and Xingchang Huang. Continual learning of a mixed sequence of similar and dissimilar tasks. In *NeurIPS*, 2020.

[46] Arun Mallya and Svetlana Lazebnik. PackNet: Adding Multiple Tasks to a Single Network by Iterative Pruning. *arXiv preprint arXiv:1711.05769*, 2017.

[47] Ching-Yi Hung, Cheng-Hao Tu, Cheng-En Wu, Chien-Hung Chen, Yi-Ming Chan, and Chu-Song Chen. Compacting, picking and growing for unforgetting continual learning. In *NeurIPS*, volume 32, 2019.

[48] Johannes von Oswald, Christian Henning, João Sacramento, and Benjamin F Grewe. Continual learning with hypernetworks. *ICLR*, 2020.

[49] Jaehong Yoon, Saehoon Kim, Eunho Yang, and Sung Ju Hwang. Scalable and order-robust continual learning with additive parameter decomposition. In *ICLR*, 2020.

[50] Pravendra Singh, Vinay Kumar Verma, Pratik Mazumder, Lawrence Carin, and Piyush Rai. Calibrating cnns for lifelong learning. *NeurIPS*, 2020.

[51] Rahaf Aljundi, Punarjay Chakravarty, and Tinne Tuytelaars. Expert gate: Lifelong learning with a network of experts. In *CVPR*, 2017.

[52] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross Girshick. Momentum contrast for unsupervised visual representation learning. In *CVPR*, 2020.

[53] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *ICML*, 2020.

[54] Saikiran Bulusu, Bhavya Kailkhura, Bo Li, Pramod K Varshney, and Dawn Song. Anomalous instance detection in deep learning: A survey. *arXiv preprint arXiv:2003.06979*, 2020.

[55] Chuanxing Geng, Sheng-jun Huang, and Songcan Chen. Recent advances in open set recognition: A survey. *IEEE transactions on pattern analysis and machine intelligence*, 2020.

[56] Jathushan Rajasegaran, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Mubarak Shah. itaml: An incremental task-agnostic meta-learning approach. In *CVPR*, 2020.

[57] Davide Abati, Jakub Tomczak, Tijmen Blankevoort, Simone Calderara, Rita Cucchiara, and Ehteshami Bejnordi. Conditional channel gated networks for task-aware continual learning. In *CVPR*, pages 3931–3940, 2020.

[58] Christian Henning, Maria Cervera, Francesco D'Angelo, Johannes Von Oswald, Regina Traber, Benjamin Ehret, Seijin Kobayashi, Benjamin F Grewe, and João Sacramento. Posterior meta-replay for continual learning. *NeurIPS*, 34, 2021.

[59] Sebastian Lee, Sebastian Goldt, and Andrew Saxe. Continual learning in the teacher-student setup: Impact of task similarity. In *International Conference on Machine Learning*, pages 6109–6119. PMLR, 2021.

[60] Mehdi Abbana Bennani, Thang Doan, and Masashi Sugiyama. Generalisation guarantees for continual learning with orthogonal gradient descent. *Lifelong Learning Workshop at the ICML*, 2020.

[61] Yaoyao Liu, Yuting Su, An-An Liu, Bernt Schiele, and Qianru Sun. Mnemonics training: Multi-class incremental learning without forgetting. In *CVPR*, 2020.

[62] Weitang Liu, Xiaoyun Wang, John Owens, and Yixuan Li. Energy-based out-of-distribution detection. *Advances in Neural Information Processing Systems*, 2020.

[63] Kimin Lee, Kibok Lee, Honglak Lee, and Jinwoo Shin. A simple unified framework for detecting out-of-distribution samples and adversarial attacks. *Advances in neural information processing systems*, 31, 2018.

[64] Shiyu Liang, Yixuan Li, and R. Srikant. Enhancing the reliability of out-of-distribution image detection in neural networks. In *ICLR*, 2018.

[65] Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *arXiv preprint arXiv:2004.11362*, 2020.

[66] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NIPS*, 2012.

[67] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[68] Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. *ICLR*, 2015.

[69] Yang You, Igor Gitman, and Boris Ginsburg. Large batch training of convolutional networks. *arXiv preprint arXiv:1708.03888*, 2017.

[70] Ilya Loshchilov and Frank Hutter. Sgdr: Stochastic gradient descent with warm restarts. *arXiv preprint arXiv:1608.03983*, 2016.