Evaluating the Impact of Reviewer Guideline Design
on LLM-Based Automated Peer Review

Abstract

Peer review is an essential process in scientific research, yet the growing workload has made its automation increasingly necessary. In this study, we analyze how different types of *reviewer guidelines*, such as official conference guidelines and reviewer-imitating ones distilled from high-quality human reviews, affect automated peer review. Our experiments show that official conference guidelines produce review results most consistent with human judgments, suggesting that evaluation criteria refined through conference practice serve as effective guidance for automated reviewing as well. In contrast, reviewer-imitating guidelines, especially those enforcing strict rubric-style scoring, consistently degraded automated review performance, highlighting the importance of allowing subjective and holistic scoring.

1 Introduction

In recent years, the explosive growth in submissions to major machine learning conferences has placed an enormous burden on peer reviewers (Stelmakh et al., 2020; Zhang et al., 2022; Wei et al., 2025; Kim et al., 2025). The current human-based peer review system faces serious challenges including reviewer overload, inconsistent judgments, superficial evaluations, and delayed feedback. At the same time, as research automation advances, the importance of accurate evaluation has only increased, making the automation of the peer review process an urgent necessity.

One clear illustration comes from the ARR guidelines, which ask reviewers to "*Check for common review issues*"[1]. These items do not simply caution reviewers against mistakes, but establish concrete criteria for judging the scientific contribution of a paper: for example, a result should not be undervalued merely because it appears "unsurprising," nor should a contribution be dismissed solely because it contradicts prior beliefs. By formalizing such principles, ARR effectively provides operational indicators that define what counts as sound, novel, and impactful research. Such directions illustrate how, as noted by Seeber (2020), reviewer guidelines shape the nature and quality of peer review rather than serving as administrative notes.

While several studies have explored automated peer review using Large language models (LLMs) (Zhuang et al., 2025; Shin et al., 2025; Chen et al., 2025; Lin et al., 2025; Li et al., 2025; Weng et al., 2025), the impact of guidelines and rubrics that govern review policies on automated review performance has not been sufficiently investigated. Guidelines direct reviewers' attention to particular aspects and perspectives when evaluating a paper, and thus are crucial determinants of review quality. However, it remains unclear what types of guidelines are effective, and what types are ineffective, for automated peer review.

Broadly, two approaches can be considered for guideline design in automated peer review. One is to directly provide LLMs with existing, human-written guidelines established for each conference (e.g., official reviewer guideline from ARR) and have them conduct reviews. The other is a reviewer-imitating approach, where high-quality human-written reviews are used as input to a guideline generator (such as an LLM), which then extracts recurring evaluation patterns and key perspectives to generate new guidelines.

In this study, we systematically investigate how review quality is affected when LLMs conduct reviews under different guideline conditions. Specifically, we address the following research questions:

RQ1: Does providing guidelines improve the performance of automated peer review? **A:** We found that providing guidelines improves the

---

[1] https://aclrollingreview.org/reviewerguidelines

performance of automated peer review. In particular, using official conference guidelines, such as those from NeurIPS and ARR, proved to be more effective. This suggests that evaluation criteria refined over time by the research community serve as a strong foundation for automated reviewing as well (§3).

RQ2: Are reviewer-imitating guidelines effective? In particular, is it better for models to determine scores subjectively, or to compute them strictly using rubric-style criteria? **A:** We found that reviewer-imitating guidelines were not very effective, and that rubric-style formulations in particular further reduced alignment with human judgments. This suggests that allowing LLMs to determine scores subjectively may be more effective for automated peer review (§4).

2 Problem Formulation

Types of Reviewer Guidelines This study analyzes two approaches for automated peer review: (1) using human-created guidelines (e.g., official ICLR reviewer guidelines) directly provided to LLMs for reviewing, and (2) generating guidelines from high-quality human reviews using LLMs and then using these generated guidelines for review.

Guideline-Based Automated Review Both approaches follow a common input–output structure for automated review, as shown in the prompt template in Appendix (Listing 3). The **input** consists of: (i) a paper in text format[2], and (ii) review guidelines (either human-created or LLM-generated). The **output** is a numerical review score (typically on a 1-10 scale) along with textual justification.

Evaluation To evaluate the quality of automated reviews, we compute the root mean squared error (RMSE) between LLM-generated scores and human review scores for the same papers. A lower RMSE indicates that the model's ratings are numerically closer to human ratings. This metric allows us to assess how effectively an automated system approximates human peer review (Wei et al., 2025).

3 Effectiveness of Conference Reviewer Guidelines for Automated Review

This section evaluates how well reviewer guidelines improve automated peer review. We address

Model	No-Guideline	ARR	NeurIPS	ICLR
Official conference guidelines				
Qwen3-30B-A3B	3.06	3.18	**2.07**	2.91
DeepSeek-R1-32B	3.86	3.27	**2.72**	2.91
Qwen3-32B	3.58	3.32	**2.51**	2.89
Guidelines rewritten into instruction-style prompts				
Qwen3-30B-A3B	3.06	**2.97**	3.08	2.99
DeepSeek-R1-32B	3.86	3.06	3.18	**3.05**
Qwen3-32B	3.58	3.16	3.32	**3.09**

Table 1: RMSE of automated review scores under No-Guideline and official conference guidelines. Upper block shows results using official reviewer guidelines *verbatim*, while lower block uses the same content rewritten into *instruction-style prompts* (converted with ChatGPT). Best results are in **bold**, second-best are underlined. **Lower values are better**, indicating closer alignment with human scores.

whether providing guidelines improves accuracy and which venue's guidelines are most effective.

Setup We randomly sampled 1,500 submissions (papers and reviews) from the ICLR 2024 peer-review dataset[3]. For each paper, the human reference label is the average of its reviewers' overall rating. We evaluate three models: Qwen3-30B-A3B (MoE model)[4](Yang et al., 2025), DeepSeek-R1-Distill-Qwen3-32B[5](DeepSeek-AI et al., 2025), and Qwen3-32B[6](Yang et al., 2025). "No-Guideline" denotes prompting the model with the paper only (no guideline) to output an integer overall rating, as shown in Appendix B. We also evaluate using official reviewer guidelines from ICLR[7]/NeurIPS[8]/ARR[9]. Because official documents often include non-evaluative administrative notes and explanatory prose, we additionally test an instruction-style variant where the same evaluative content is rewritten as imperative, bullet-pointed instructions with explicit output requirements converted using ChatGPT 5. The prompts used for all guideline-based conditions is shown in

---

[2]Converted from PDF with references and appendices removed

[3]We collected data from ICLR 2024 submissions on OpenReview, including 7,262 paper PDFs and 28,028 open-access reviews from https://openreview.net/group?id=ICLR.cc/2024/Conference

[4]https://huggingface.co/Qwen/Qwen3-30B-A3B

[5]https://huggingface.co/deepseek-ai/DeepSeek-R1-Distill-Qwen3-32B

[6]https://huggingface.co/Qwen/Qwen3-32B

[7]https://iclr.cc/Conferences/2024/ReviewerGuide

[8]https://neurips.cc/Conferences/2024/ReviewerGuidelines

[9]https://aclrollingreview.org/reviewerguidelines

Appendix C.

Q1: Do guidelines improve automated reviewing? We compare No-Guideline to runs with conference guidelines. As shown in Table 1, RMSE consistently decreases when guidelines are provided. Using the official text, for example, Deepseek-R1-32B improves from No-Guideline = 3.86 to ICLR = 2.91, NeurIPS = 2.72, ARR = 3.27. The instruction-style prompts also outperform No-Guideline across all models, for example Deepseek-R1-32B shows 3.86 versus ICLR = 3.05, NeurIPS = 3.18, ARR = 3.06. Making evaluative criteria explicit, either by supplying the official text or by converting it into imperative instructions, improves agreement with humans.

Q2: Which conference guidelines are more effective? We next compare ICLR/NeurIPS/ARR against each other. With the official guideline text, all three models achieve the lowest RMSE under NeurIPS, followed by ICLR, then ARR (e.g., for Qwen3-30B-A3B: $2.07 < 2.91 < 3.18$). When the same content is converted into instruction-style prompts, the best venue varies by model: Qwen3-30B-A3B prefers ARR (2.97), while DeepSeek-R1-32B and Qwen3-32B prefer ICLR (3.05 and 3.09, respectively). In other words, beyond the guideline content, the presentation (verbatim policy text vs. instruction-style prompt) can alter model behavior and flip the relative ranking among venues.

4 Effectiveness of Reviewer-imitating Guidelines in Automated Peer Review

In addition to using human-written conference reviewer guidelines, another approach is to *construct* guidelines with an LLM. In this section, we examine whether *reviewer-imitating guidelines*, generated from human-written reviews, can improve automated peer review. We evaluate review quality using several indicators (such as review length) and extract common perspectives from high-quality reviews, which are then converted into guidelines by an LLM. Through this filtering process, we divide reviews into three groups: *Good Review*, *Middle*, and *Bad Review*. We generate guidelines from each group and compare automated review performance under these different settings.

Overview of Guideline Generation We generate reviewer-imitating guidelines and apply them to automated peer review through the following steps:

Listing 1: Example of reviewer-imitating guideline extracted from high-quality ("Good") reviews.

```
Provide the following based on the Peer Review
Behavior Checklist:

peer_review_behavior_checklist:
    good_paper:
    contribution_and_impact:
    - question: "Does the paper tackle a
significant and timely problem?"
        description: "Reviewers positively note
papers that address important and relevant
research topics, seeing it as a sign of
potential impact."
    - question: ...
    clarity_and_presentation: ...
    bad_paper:
    novelty_and_scholarship:
    - question: "Is the contribution
incremental or a re-implementation of existing
ideas?"
        description: "This is a frequent and
critical flaw. Reviewers are highly
knowledgeable and will reject papers they deem
to be minor variations of prior work, often
citing the specific papers."
    - question: ...
    clarity_and_soundness: ...
```

- **STEP1: Review Data Filtering**: To ensure that guidelines are distilled from high-quality reviews, we first filter the ICLR review data with several heuristic criteria. Each review is scored along some dimensions (e.g., length of the review text, whether the reviewer provides references to related work, etc.). Reviews satisfying more of these criteria are grouped as *Good Review*, those in the middle range as *Middle Review*, and those with the lowest scores as *Bad Review*. Details are provided in § A.1.

- **STEP2: Guideline Generation**: We provide the filtered reviews from each group (30 reviews) to Gemini 2.5 Pro (Google Gemini Team, 2025) to generate reviewer-imitating guidelines. The resulting guidelines are structured as a checklist, with separate items for positive aspects (good papers) and negative aspects (bad papers). They capture frequently mentioned criticisms, recurring evaluation criteria, and characteristic perspectives. For example, Listing 1 shows an actual generated guideline (excerpted for brevity). Further details are described in § A.3.

- **STEP3: Automated Review Using Guidelines**: This step follows the same procedure as in the conference guideline experiments.

Model	Setting	Good	Middle	Bad
Qwen3-30B-A3B	w/o Rubric	3.22	3.24	**3.14**
	w/ Rubric	4.42	**4.10**	4.28
DeepSeek-R1-32B	w/o Rubric	3.13	3.12	**3.06**
	w/ Rubric	4.26	3.92	4.26
Qwen3-32B	w/o Rubric	**3.48**	3.51	3.69
	w/ Rubric	4.57	**4.31**	4.62

Table 2: RMSE under reviewer-imitating guidelines, comparing settings with and without rubric. "Good" and "Bad" denote guidelines distilled from *high-quality* and *low-quality* human reviews, respectively, where review quality is determined by our filtering score (length of the review, reference quality, etc.).

The generated reviewer-imitating guidelines are given to the LLMs together with the paper text. The model then outputs an overall rating on a 1–10 scale and gives a brief justification.

Q1: Do reviewer-imitating guidelines outperform No-Guideline? We compare No-Guideline (the model uses only the paper) against reviewer-imitating guidelines from the Good/Bad groups. The effect varies by model: for Qwen3-30B-A3B, RMSE increases from No-Guideline (3.06) to Good (3.22) and Bad (3.14). For DeepSeek-R1-32B, RMSE improves from No-Guideline (3.86) to Good (3.13) and Bad (3.06). For Qwen3-32B, Good yields a slight improvement over No-Guideline (3.48 vs. 3.58), whereas Bad degrades performance (3.69). Thus, reviewer imitation helps some models but does not yield uniform gains.

Q2: How do reviewer-imitating guidelines compare to conference guidelines? We compare reviewer-imitating guidelines (Good/Bad) to official conference reviewer guidelines (ICLR, NeurIPS, ARR) under the same evaluation setup. Cross-referencing Table 1, conference guidelines consistently achieve lower RMSE than reviewer imitation. For example, with Qwen3-30B-A3B, Good = 3.22 and Bad = 3.14, while NeurIPS = 2.07 and ICLR = 2.91. These results suggest that the structural clarity and explicit requirements in official guidelines calibrate models more effectively than behavior-only signals distilled from reviews.

Q3: Does rubricizing reviewer-imitating guidelines help? We compare free-form (non-rubric) instructions to rubric-style scoring for reviewer-imitating guidelines. In the rubric setting, the LLM judges whether each checklist item (Listing 1) in the "good_paper" section is satisfied and assigns +1 point if so, while items in the "bad_paper" section contribute -1 point. The total score is then normalized to a 1–10 scale and used as the overall rating. As shown in Table 2, non-rubric consistently outperforms rubric. For Qwen3-30B-A3B, RMSE under non-rubric is Good = 3.22, Middle = 3.24, Bad = 3.14, whereas rubric yields Good = 4.42, Middle = 4.10, Bad = 4.28. Similar patterns hold for DeepSeek-R1-32B and Qwen3-32B, with correlations also lower under rubric. A simple additive checklist with equal weights appears to strip away the non-linear, context-dependent weighting present in human aggregate judgment, reducing alignment with humans.

5 Related Work

Automatic peer review research can be broadly categorized into two approaches: learning-based and prompt-based. The learning-based approach trains models to generate reviews or predict scores using task-specific supervision and intermediate reasoning. Early studies generated explainable reviews from structured evidence built through knowledge graphs (Gao et al., 2020). More recent work employs multi-stage pipelines that emulate expert analytical processes to train end-to-end review models (Zhu et al., 2025). In addition, recent surveys have organized datasets and tasks, helping to systematize what is learned and how models are evaluated (Yuan et al., 2022; Dycke et al., 2023). The prompt-based approach guides large language models during inference using rubrics or instructions. Studies on prompt-based automated reviewing have shown that well-designed evaluation criteria improve the fidelity and granularity of judgments (Kim et al., 2023). Benchmarking frameworks further standardize prompt formats and evaluation procedures (Zheng et al., 2023). These studies collectively highlight the importance of explicit instructions for LLMs. Building on this insight, we analyze how using reviewer guidelines, which serve as instructions to human reviewers, as prompts affects the quality of automated peer review. A related study (Kirtani et al., 2025) employs reviewer guidelines to evaluate the quality of LLM-generated reviews, whereas our work uses them to evaluate the quality of papers, making the two settings orthogonal.

Limitations

This study is limited in several aspects. First, we only analyze review data written in English, since the ICLR 2024 dataset we use contains exclusively English reviews. As a result, our findings may not generalize to reviews written in other languages. Extending the methodology to non-English contexts, where linguistic structures and cultural factors may influence review style and evaluation criteria, remains an important direction for future work.

References

Shiping Chen, Duncan Brumby, and Anna Cox. 2025. Envisioning the future of peer review: Investigating llm-assisted reviewing using chatgpt as a case study. In *Proceedings of the 4th Annual Symposium on Human-Computer Interaction for Work*, CHIWORK '25, New York, NY, USA. Association for Computing Machinery.

DeepSeek-AI, Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, and 181 others. 2025. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *Preprint*, arXiv:2501.12948.

Nils Dycke, Ilia Kuznetsov, and Iryna Gurevych. 2023. NLPeer: A unified resource for the computational study of peer review. In *Proceedings of ACL 2023 (Long Papers)*.

Xue Gao and 1 others. 2020. Reviewrobot: Explainable paper review generation based on knowledge graphs. In *Proceedings of INLG 2020*.

Google Gemini Team. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *arXiv preprint arXiv:2507.06261*. Technical Report / preprint.

Jaeho Kim, Yunseok Lee, and Seulki Lee. 2025. Position: The ai conference peer review crisis demands author feedback and reviewer rewards. *Preprint*, arXiv:2505.04966.

Seungone Kim, Jamin Shin, Yejin Cho, Joel Jang, Shayne Longpre, Hwaran Lee, Sangdoo Yun, Seongjin Shin, Sungdong Kim, James Thorne, and Minjoon Seo. 2023. Prometheus: Inducing fine-grained evaluation capability in language models. *Preprint*, arXiv:2310.08491.

Chhavi Kirtani, Madhav Krishan Garg, Tejash Prasad, Tanmay Singhal, Murari Mandal, and Dhruv Kumar. 2025. Revieweval: An evaluation framework for ai-generated reviews. *CoRR*, abs/2502.11736.

Ruochi Li, Haoxuan Zhang, Edward Gehringer, Ting Xiao, Junhua Ding, and Haihua Chen. 2025. Unveiling the merits and defects of llms in automatic review generation for scientific papers. *Preprint*, arXiv:2509.19326.

Tzu-Ling Lin, Wei-Chih Chen, Teng-Fang Hsiao, Hou-I Liu, Ya-Hsin Yeh, Yu Kai Chan, Wen-Sheng Lien, Po-Yen Kuo, Philip S. Yu, and Hong-Han Shuai. 2025. Breaking the reviewer: Assessing the vulnerability of large language models in automated peer review under textual adversarial attacks. *Preprint*, arXiv:2506.11113.

Marco Seeber. 2020. How do journals of different rank instruct peer reviewers? reviewer guidelines in the field of management. *Scientometrics*, 122(3):1387–1405.

Hyungyu Shin, Jingyu Tang, Yoonjoo Lee, Nayoung Kim, Hyunseung Lim, Ji Yong Cho, Hwajung Hong, Moontae Lee, and Juho Kim. 2025. Mind the blind spots: A focus-level evaluation framework for llm reviews. *Preprint*, arXiv:2502.17086.

Ivan Stelmakh, Nihar B. Shah, Aarti Singh, and Hal Daumé III. 2020. A novice-reviewer experiment to address scarcity of qualified reviewers in large conferences. *Preprint*, arXiv:2011.15050.

Qiyao Wei, Samuel Holt, Jing Yang, Markus Wulfmeier, and Mihaela van der Schaar. 2025. The ai imperative: Scaling high-quality peer review in machine learning. *Preprint*, arXiv:2506.08134.

Yixuan Weng, Minjun Zhu, Guangsheng Bao, Hongbo Zhang, Jindong Wang, Yue Zhang, and Linyi Yang. 2025. Cycleresearcher: Improving automated research via automated review. *Preprint*, arXiv:2411.00816.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 40 others. 2025. Qwen3 technical report. *CoRR*, abs/2505.09388.

Weizhe Yuan, Pengfei Liu, and Graham Neubig. 2022. Can we automate scientific reviewing? *Journal of Artificial Intelligence Research*, 75:171–212.

Yichi Zhang, Fang-Yi Yu, Grant Schoenebeck, and David Kempe. 2022. A system-level analysis of conference peer review. In *Proceedings of the 23rd ACM Conference on Economics and Computation*, EC '22, page 1041–1080, New York, NY, USA. Association for Computing Machinery.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, and 1 others. 2023. Judging LLM-as-a-judge with MT-bench and chatbot arena. *Preprint*, arXiv:2306.05685.

Minjun Zhu, Yixuan Weng, Linyi Yang, and Yue Zhang. 2025. Deepreview: Improving llm-based paper review with human-like deep thinking process. In *Proceedings of ACL 2025 (Long Papers)*.

Zhenzhen Zhuang, Jiandong Chen, Hongfeng Xu, Yuwen Jiang, and Jialiang Lin. 2025. Large language models for automated scholarly paper review: A survey. *Preprint*, arXiv:2501.10326.

A Detailed Description of the Reviewer-imitating Guideline

A.1 Review Data Collection and Filtering

We collected data from ICLR 2024 submissions on OpenReview, including 7,262 paper PDFs and 28,028 open-access reviews as mentioned in § 3. We selected ICLR due to the abundance of open-access data and its status as a representative conference in the machine learning field. Table 3 shows an example of review data used in our study. Each review includes the following elements: review summary, item-specific scores (soundness, presentation, contribution), strengths, weaknesses, questions, overall score, and confidence level. However, not all reviews are of high quality. Some reviews are too short, have unclear evidence, or have inconsistent scores and content. To generate guidelines from high-quality reviews, it is necessary to filter the review data as preprocessing. Filtering uses the following five criteria, based on our intuitions about what constitutes high-quality reviews.

1. **Submission Date**: Measures deviation from the average review submission date. We hypothesize that reviewers who submit reviews promptly are more conscientious and likely to produce higher quality reviews.

2. **Review Length**: Evaluation based on character count, with longer reviews assumed to indicate deeper engagement with the paper. We calculate scores based on multiples of the median length.

3. **Reference Quality**: Evaluates mention of one or more references, pointing out insufficient related work, and critical discussion of prior work (0-3 points). We expect that reviewers with higher domain expertise, evidenced by reference to relevant literature, produce better reviews. We use LLMs to score this criterion by inputting review data and prompting for assessment of reference usage.

4. **Content Consistency**: Evaluates consistency between review text tone and evaluation score, and alignment between justification and score (0-2 points). We assume that reviews with inconsistent tone and ratings (e.g., positive text with low scores or vice versa) indicate poor review quality. We employ LLMs to assess this consistency by analyzing the alignment between textual content and numerical scores.

5. **Subscore Consistency**: Evaluates consistency between item scores (soundness, presentation, contribution) and overall score, and alignment between each subscore and evaluation content (0-2 points). Similar to content consistency, we expect coherent scoring patterns to indicate higher review quality. LLMs evaluate this criterion by examining the coherence between different scoring components.

Filtering scores are distributed in the range of 3-17 points, with a median of 11 points. Based on this score, we create high-quality ("Good"), medium-quality ("Middle"), and low-quality ("Bad") review groups. We assume that reviews satisfying these criteria represent high-quality reviews. However, we empirically analyze whether these assumptions hold true and investigate which criteria positively (or potentially negatively, contrary to our intuition) correlate with automated review performance in our experiments.

A.2 Filtering Criteria Details

This section provides detailed calculation procedures for the five filtering criteria used to assess review quality.

Submission Date The submission date criterion evaluates the timing of review submission relative to the conference's review timeline. We calculate the deviation from the average review submission time across all reviews for the same conference. Let t_i be the submission timestamp for review i, and $\bar{t}$ be the average submission time across all reviews. The deviation score is calculated as $d_i = |t_i - \bar{t}|$. Reviews are scored based on their deviation from the average submission time:

- +5 point: $d_i \leq 2$ days from average
- +4 point: $2 < d_i \leq 5$ days from average
- +3 point: $5 < d_i \leq 10$ days from average
- +2 point: $10 < d_i \leq 20$ days from average

Field	Content
Summary	*This paper proposes a method for multimodal learning...*
Strengths	*(1) The motivation is clear... (2) ...*
Weaknesses	*(1) The novelty is limited... (2) ...*
Questions	*(1) How does the method scale with model size?... (2) ...*
Soundness	3 (good)
Presentation	3 (good)
Contribution	3 (good)
Overall Rating	8: accept, good paper
Confidence	4: You are confident in your assessment, ..
Submission Date	{Unix timestamp}

Table 3: Illustrative example of review data inspired by the ICLR 2024 peer review dataset (not from actual reviews). The content is paraphrased and does not reproduce any actual review text. To extract high-quality reviews for guideline generation, we filter this data using five predefined criteria: **(1) Submission Date** (uses timestamp to measure timing appropriateness), **(2) Review Length** (evaluates character count from textual fields), **(3) Reference Quality** (analyzes citation mentions in textual content), **(4) Content Consistency** (assesses alignment between textual tone and numerical scores), and **(5) Subscore Consistency** (checks coherence between item-specific and overall ratings). Our experiments also analyze which filtering criteria are most effective for extracting quality reviews.

- +1 point: $d_i > 20$ days from average

Review Length The review length criterion evaluates the total character count of the review text, including summary, strengths, weaknesses, and questions sections. Let l_i be the character count for review i, and M be the median character count across all reviews. The length score is determined as follows:

- +5 point: $l_i > 1.5 \times M$

- +4 point: $1.2 \times M < l_i \leq 1.5 \times M$

- +3 point: $0.8 \times M < l_i \leq 1.2 \times M$

- +2 point: $0.5 \times M < l_i \leq 0.8 \times M$

- +1 point: $l_i \leq 0.5 \times M$

Reference Quality Reference quality is evaluated using LLM assessment of how well the review engages with relevant literature. The scoring criteria (0-3 points) are:

- +1 point: Review mentions one or more relevant references

- +1 point: Review identifies missing or insufficient related work

- +1 point: Review provides critical discussion of prior work

Content Consistency Content consistency measures the alignment between the textual content of the review and the numerical scores provided. This is assessed using LLMs with the following criteria (0-2 points):

- +1 point: Review tone matches the numerical rating (positive tone with high scores, critical tone with low scores)

- +1 point: Justification provided in the text aligns with the overall score

Subscore Consistency Subscore consistency evaluates the coherence between item-specific scores (soundness, presentation, contribution) and the overall rating. LLMs assess this using the following criteria (0-2 points):

- +1 point: Overall score reasonably reflects the average of subscores

- +1 point: Each subscore aligns with the corresponding evaluation aspects discussed in the text

Score Distribution The combined filtering scores range from 3 to 17 points (sum of all five criteria). To analyze review quality, we sampled three groups of reviews based on their scores:

- **Good**: 30 reviews randomly sampled from those with a score of 17

- **Middle**: 30 reviews randomly sampled from those with a medium score of 11

- **Bad**: 30 reviews randomly sampled from those with scores of 6 or lower

A.3 Guideline Generation

We concatenate the filtered reviews into a single text prompt and input it to Gemini 2.5 Pro for guideline generation. The LLM analyzes the combined review text to identify common evaluation patterns, important perspectives, and judgment criteria, and then generalizes these findings to generate reviewer guidelines in a single inference step.

The LLM is prompted to generate guidelines by identifying the characteristics of "good papers" and "bad papers." This process results in guidelines that include evaluation principles such as "papers with high originality are good" or "papers with poor writing quality are bad." The generated guidelines are formatted as YAML checklists following the structure shown in Listing 1, with judgment criteria organized by evaluation category (e.g., clarity, experimental validity) in question format.

For review scoring, we consider two types of guideline formats: rubric-based and non-rubric-based. The rubric-based format specifies explicit scoring rules with defined point allocations, whereas the non-rubric-based format provides general evaluation guidance without a fixed scoring framework. This approach aims to extract generalized evaluation criteria from large-scale review data and to capture subtle patterns that may not be reflected in manually crafted guidelines.

B Prompt of No-guideline

For the non-guideline baseline, we used a minimal prompt that did not provide any reviewer guidelines. The LLM is simply asked to read the paper and assign an overall rating on a 1–10 scale, along with a brief justification. The full prompt is shown in Listing 2.

Listing 2: Prompt used in the Non-guideline condition

```
You are an expert paper reviewer. Please read
the following paper content and rate its quality.

# Paper
{content}

# Instructions
Provide:
- A numerical rating (1-10) for overall quality.
- A short justification for your score.
```

```
# Format
Output the integer overall rating as the
following format after your justification:
"Overall Rating: (Your Rating)"
```

C Prompt of Guideline-based Autoeted Peer Review

To ensure consistency across different reviewer guidelines, we designed a unified prompt template for automated peer review, as shown in Listing 3. Each experiment replaces the placeholder {reviewer_guideline} with the corresponding conference or reviewer-derived guideline (i.e., ICLR, ARR, NeurIPS, and Good/Middle/Bad reviewer style).

Listing 3: Prompt template for automated peer review using reviewer guidelines

```
You are an expert peer reviewer. Please read the
 following paper content and evaluate its
quality based on the following reviewer
guideline.

# Paper
{content}

# Reviewer Guideline
{reviewer_guideline}

# Final Output
Provide:
- A numerical overall rating (1-10):
      - 10 = Strong Accept
      - 8 = Accept
      - 6 = Weak Accept
      - 5 = Borderline
      - 3 = Weak Reject
      - 1 = Strong Reject
- A justification paragraph that summarizes the
key strengths and weaknesses underlying your
rating.

# Format
Output the integer overall rating as the
following format after your justification:
"Overall Rating: (Your Rating)"
```

Official Conference Guidelines For the official conference guidelines, we used the publicly available reviewer guidelines from each conference's official website without modification. For more details, please refer to the respective conference pages (ICLR[10], NeurIPS[11], and ARR[12]). We also em-

---

[10] https://iclr.cc/Conferences/2024/ReviewerGuide

[11] https://neurips.cc/Conferences/2024/ReviewerGuidelines

[12] https://aclrollingreview.org/reviewerguidelines

ployed ChatGPT-rewritten versions of these guidelines, reformatted into an instruction style suitable for LLM-based reviewing (Listing 4, Listing 5, and Listing 6).

Listing 4: ARR Reviewer Guideline (ChatGPT-refined version)

```
## Summary
Give a brief summary of the paper in your own
words. Highlight the key contributions and main
ideas.

## Strengths
List the main strengths of the paper, such as
novelty, clarity, strong empirical results,
theoretical insights, or broad relevance.

## Weaknesses
Point out the limitations, flaws, or missing
components (e.g., weak justification, incomplete
 experiments, lack of clarity, missing baselines,
 etc.).

## Assessment by Review Dimension
Please evaluate the paper based on the following
 criteria from the following guidelines:

- **Soundness/Correctness**: Are the claims
supported by the methodology and evidence? Are
proofs or derivations correct (if applicable)?
- **Originality/Novelty**: Does the paper offer
novel methods, insights, or results? Is the
contribution incremental or substantial?
- **Meaningful Comparison**: Does the paper
clearly position itself with respect to prior
work? Are comparisons (empirical or conceptual)
adequate?
- **Clarity**: Is the paper well-written and
easy to follow? Are key terms defined and claims
 clearly stated?
- **Impact/Potential**: Does the paper have the
potential to impact future research or practice
in its area?
- **Reproducibility**: Are datasets, code, and
hyperparameters provided or clearly described?
Could others replicate the results?
- **Ethics**: Are there any ethical
considerations raised by the paper (e.g., misuse
 potential, data issues, fairness)? Are these
discussed?

You may optionally assign per-dimension scores
if helpful, but they are not required.

## Suggestions for Improvement
Provide constructive feedback for the authors to
 help improve the work, regardless of your score.

---

Please be professional, specific, and
constructive. Your goal is to help both the
authors and the review community understand the
strengths, limitations, and suitability of the
paper.
```

Listing 5: NeurIPS Reviewer Guideline (ChatGPT-refined version)

```
Your evaluation should be structured into
several components.

### Summary
Briefly summarize the paper and its main
contributions in your own words. This summary
should be a neutral reflection that the authors
would agree with, not a critique or a copy of
the abstract.

---

### Strengths and Weaknesses
Provide a detailed assessment of the paper's
strengths and weaknesses. This section should
cover the primary reasons for your
recommendation to accept or reject the paper.
Evaluate the following dimensions:

* **Quality**: Assess the technical soundness of
 the submission. Are the claims well-supported
by theoretical analysis or experimental results?
 Are the methods appropriate? Does the work seem
 complete, and do the authors honestly evaluate
both its strengths and weaknesses?
* **Clarity**: Is the paper well-written and
organized? Is there enough information for an
expert to reproduce the results? Provide
constructive suggestions if clarity can be
improved.
* **Significance**: How impactful are the
results for the machine learning community? Is
the work likely to be used or built upon by
others? Does it advance the field by addressing
a difficult task, providing new insights, or
introducing a unique approach?
* **Originality**: Does the paper offer new
insights or a deeper understanding of existing
methods? How does it differ from previous work,
and are relevant citations included? Originality
 can come from a novel method, a novel
combination of techniques, or new insights from
evaluating existing methods.

---

### Numerical Ratings for Core Criteria
Based on your assessment in the "Strengths and
Weaknesses" section, provide a numerical rating
for each of the following categories on a scale
from 1 to 4.

* **Quality**:
    * 4: excellent
    * 3: good
    * 2: fair
    * 1: poor
* **Clarity**:
    * 4: excellent
    * 3: good
    * 2: fair
    * 1: poor
* **Significance**:
    * 4: excellent
    * 3: good
    * 2: fair
    * 1: poor
* **Originality**:
    * 4: excellent
```

```
    * 3: good
    * 2: fair
    * 1: poor

---

### Questions for the Authors
List 3-5 key, actionable questions or
suggestions for the authors. These should focus
on points where a response could clarify a
confusion, address a limitation, or potentially
change your evaluation. Clearly state the
criteria under which your score might change.

---

### Limitations and Societal Impact
Assess whether the authors have adequately
addressed the limitations of their work and its
potential negative societal impact. If they have,
 a simple "yes" is sufficient. If not, provide
constructive feedback for improvement. Remember
to reward authors for being transparent about
limitations.
```

Listing 6: ICLR Reviewer Guideline (ChatGPT-refined version)

```
## Justification and Detailed Review
Write a clear and concise review, addressing
each of the following dimensions from the
following review guidelines:

- **Strengths and Weaknesses**: Identify the
main strengths and weaknesses of the paper.
- **Significance**: Evaluate whether the paper
makes a meaningful contribution to the field.
Does it advance understanding, methods, or
applications in a way that would be interesting
to the review community?
- **Originality**: Assess whether the paper
presents new ideas, methods, or perspectives.
- **Technical Quality**: Are the methods
technically sound and well-justified? Are claims
 supported by theory or experiments?
- **Clarity**: Is the paper clearly written and
well-structured? Can a non-expert in the
subfield follow it?
- **Empirical Evaluation** (if applicable): Are
experiments well-designed? Are comparisons fair
and comprehensive? Are results convincing?
- **Reproducibility**: Does the paper provide
enough information (including code/data, if
applicable) for others to reproduce the results?
- **Ethics**: Are there any ethical concerns (e.
g., societal harm, bias, data misuse)? If yes,
how are they handled?

## Confidential Comments to Reviewers (Optional)
(Optional section) Note anything relevant for
area chairs, such as borderline decisions, meta-
considerations, or conflicts of interest.

---

Be objective, constructive, and concise. Focus
on helping the authors and the review community
understand the paper's strengths and limitations
 based on the review standards.
```

Reviewer-imitating Guidelines We additionally generated reviewer-imitating guidelines from ICLR 2024 reviews to capture common evaluation patterns and characteristic reasoning observed in human reviewers (Listing 7, Listing 8, and Listing 9). In non-rubric experiments, these guidelines were applied using the standard prompt template shown in Listing 3. For rubric-based experiments, we used the same reviewer-imitating guidelines (i.e., identical guideline for Good, Middle, and Bad) but replaced the prompt template with a scoring-oriented version (Listing 10) that specifies explicit point-allocation and normalization procedures.

Listing 7: Good Reviewer-Imitating Guideline (Non-rubric)

```
Provide the following based on the Peer Review
Behavior Checklist:

peer_review_behavior_checklist:
  good_paper:
    contribution_and_impact:
    - question: "Does the paper tackle a
significant and timely problem?"
      description: "Reviewers positively note
papers that address important and relevant
research topics, seeing it as a sign of
potential impact."
    - question: "Is the core idea clever,
insightful, or genuinely novel?"
      description: "A key strength noted is a
non-trivial insight or a unique approach that
distinguishes the work from incremental
improvements."
    clarity_and_presentation:
    - question: "Is the paper exceptionally
well-written and easy to follow?"
      description: "Reviewers frequently
praise clear writing, logical structure, and
understandable explanations as major strengths,
even in papers they have concerns about."
    - question: "Are the motivation and
contributions communicated unambiguously?"
      description: "A paper is viewed
favorably when its purpose and specific
contributions are stated clearly from the outset,
 leaving no room for interpretation."
    technical_and_empirical_soundness:
    - question: "Does the method achieve a
significant performance gain over strong,
relevant baselines?"
      description: "Convincing, large
improvements over well-established and widely-
used methods are a primary driver for a positive
 evaluation."
    - question: "Is the approach technically
sound and well-grounded?"
      description: "Reviewers value methods
that are built on solid theoretical foundations
or have clear, logical justifications for their
design choices."
    - question: "Are the experiments thorough,
 using standard benchmarks and insightful
ablations?"
```

```
        description: "A comprehensive evaluation
 across multiple standard datasets, including
ablation studies that validate specific design
choices, is a hallmark of a strong submission."
        - question: "Are the experimental
comparisons conducted fairly?"
        description: "This group of reviewers
values direct, fair comparisons where baselines
are properly tuned and experimental settings are
 consistent."
        - question: "Has the author provided
source code to support reproducibility?"
        description: "The inclusion of source
code is explicitly mentioned as a strength, as
it supports the paper's claims and aids
reproducibility."
        - question: "Could this work become a
standard method or open new research avenues?"
        description: "Reviewers are supportive
when they see potential for the work to be
widely adopted or to inspire future research."
  bad_paper:
    novelty_and_scholarship:
      - question: "Is the contribution
incremental or a re-implementation of existing
ideas?"
        description: "This is a frequent and
critical flaw. Reviewers are highly
knowledgeable and will reject papers they deem
to be minor variations of prior work, often
citing the specific papers."
      - question: "Does the paper fail to cite
or adequately discuss key related work?"
        description: "Missing citations for
highly relevant papers is a major red flag,
often interpreted as a lack of thoroughness or
an attempt to hide a lack of novelty."
    empirical_evaluation:
      - question: "Are the experiments conducted
 on weak, outdated, or insufficient benchmarks?"
        description: "Evaluation on a very
limited set of datasets or non-standard
benchmarks is a common reason for rejection, as
it fails to prove generalizability."
      - question: "Are the baselines weak,
poorly tuned, or missing SOTA competitors?"
        description: "Comparisons are considered
 unconvincing if the paper omits stronger
contemporary methods or appears to have
intentionally weakened the performance of its
baselines."
      - question: "Do the results actually
support the main claims made in the paper?"
        description: "Reviewers critically check
 if the conclusions drawn in the abstract and
introduction are truly backed up by the data
presented in the tables and figures."
    clarity_and_soundness:
      - question: "Is the paper poorly written,
confusing, or hard to follow?"
        description: "A lack of clarity in
writing, notation, or structure is a frequent
reason for rejection, as it prevents the
reviewer from understanding or verifying the
contribution."
      - question: "Are there critical flaws in
the methodology, assumptions, or logic?"
        description: "Fundamental errors in the
proposed method, unjustified assumptions, or
logical gaps in the analysis are considered
```

```
fatal flaws."
      - question: "Is there enough detail to
reproduce the work?"
        description: "Reviewers will reject a
paper if it lacks the necessary implementation
details, hyperparameters, or architectural
information required for another researcher to
reproduce the results."
      - question: "Is the problem motivation
weak or the contribution's significance unclear
?"
        description: "If the paper fails to
convincingly argue why the problem is important
or why the proposed solution is meaningful, it
is often rejected."
      - question: "Are the reported metrics
cherry-picked, inappropriate, or presented
without context?"
        description: "Reviewers are skeptical of
 results where the evaluation metrics seem
chosen to favor the proposed method or where
improvements are marginal without clear
statistical significance."
```

Listing 8: Middle Reviewer-Imitating Guideline (Non-rubric)

```
Provide the following based on the Peer Review
Behavior Checklist:

peer_review_behavior_checklist:
  good_paper:
    contribution_and_impact:
      - question: "Is the core idea presented as
 innovative or a novel application in its domain
?"
        description: "Reviewers consistently
highlight novelty, being the 'first' to tackle a
 problem, or proposing a unique approach as a
primary reason for acceptance."
      - question: "Is the research problem
itself framed as crucial, important, or
meaningful?"
        description: "Papers that address a
significant and recognized challenge in the
field are viewed more favorably, as this gives
the work inherent value."
    clarity_and_presentation:
      - question: "Is the paper praised for
being well-written, clear, and easy to follow?"
        description: "High writing quality,
clear organization, and comprehensible
explanations are frequently cited as key
strengths, suggesting reviewers value
accessibility."
      - question: "Does the paper include an
ablation study that clearly justifies each of
its components?"
        description: "Reviewers for good papers
often look for and praise ablation studies, as
they demonstrate a thorough understanding and
validation of the proposed architecture."
    evidence_and_validation:
      - question: "Are the experiments described
 as extensive, thorough, or comprehensive?"
        description: "Strong papers are expected
 to provide robust empirical validation across
multiple datasets, settings, or modalities to
solidify their claims."
```

```
      - question: "Do the results show a
significant and clear improvement over relevant,
 state-of-the-art baselines?"
        description: "It's not enough to conduct
 experiments; the results must demonstrate a
convincing performance gain against strong
competitors to be considered impactful."
      - question: "Does the paper provide
theoretical proofs or sound mathematical
derivations to support its claims?"
        description: "The inclusion of
theoretical grounding is seen as a major
strength that adds a layer of rigor and
credibility to the empirical results."
      - question: "Are sufficient implementation
 details or supplementary materials provided to
aid understanding and replication?"
        description: "Positive reviews often
note the inclusion of clear implementation
details or code, which enhances the paper's
integrity and perceived value."
    feedback_style:
      - question: "Are the identified weaknesses
 framed as requests for clarification or minor
additions?"
        description: "For papers they intend to
accept, reviewers tend to frame weaknesses as
constructive questions or suggestions for future
 work, rather than as critical flaws."
      - question: "Does the reviewer's summary
accurately capture the paper's core
contributions and strengths?"
        description: "A positive and accurate
summary at the beginning of the review often
signals that the reviewer has understood and
appreciated the paper's main message."
  bad_paper:
    contribution_and_impact:
      - question: "Is the contribution
criticized for being incremental, lacking
novelty, or a straightforward application of
existing work?"
        description: "A perceived lack of
novelty is one of the most common and critical
reasons for rejection in this review set."
      - question: "Are the paper's central
claims or motivation questioned as being
unsupported, grandiose, or unconvincing?"
        description: "Reviewers reject papers
where the motivation is unclear or the claims
are not sufficiently backed by the evidence
provided."
    evidence_and_validation:
      - question: "Are the experiments flagged
as insufficient, weak, or lacking necessary
comparisons?"
        description: "This is a primary reason
for rejection. Common issues include not
comparing against relevant baselines, using too
few datasets, or omitting ablation studies."
      - question: "Are the baseline comparisons
criticized as being unfair, weak, or
misrepresentative of prior work?"
        description: "Reviewers are critical of
evaluations that appear to use outdated or
poorly tuned baselines to inflate the perceived
performance of the proposed method."
      - question: "Are the reported performance
gains described as marginal, insignificant, or
within the margin of error?"
```

```
        description: "Even when experiments are
present, if the improvements are not substantial,
 the paper is often deemed not significant
enough for publication."
    clarity_and_presentation:
      - question: "Is the paper flagged as being
hard to follow, confusing, or poorly written?"
        description: "Severe issues with clarity,
 notation, or organization are critical flaws
that prevent reviewers from properly evaluating
the work, often leading to rejection."
      - question: "Does the reviewer point out a
 lack of essential details needed for
understanding or replication?"
        description: "The omission of crucial
methodological or experimental details is
treated as a major flaw that undermines the
paper's credibility."
    methodological_soundness:
      - question: "Are there fundamental flaws
identified in the proposed method's design,
assumptions, or logic?"
        description: "Reviewers will recommend
rejection if they find deep-seated problems in
the core methodology that invalidate the
approach."
      - question: "Is the method criticized for
being overly complex or a 'laundry list' of
disconnected components?"
        description: "Papers proposing
convoluted models without clear justification
for their complexity are viewed negatively."
      - question: "Is the method's robustness
questioned, for instance, due to high
sensitivity to hyperparameters?"
        description: "A lack of analysis on
hyperparameter sensitivity or robustness is a
common weakness cited in negative reviews."
periments, theory, or statistically significant
results (e.g., overlapping confidence intervals)
."
```

Listing 9: Bad Reviewer-Imitating Guideline (Non-rubric)

```
Provide the following based on the Peer Review
Behavior Checklist:

peer_review_behavior_checklist:
  good_paper:
    contribution_and_impact:
      - question: "Does the paper achieve state-
of-the-art or highly competitive results?"
        description: "Reviewers in this group
frequently highlight strong empirical
performance against established benchmarks as a
primary strength and a key reason for acceptance
."
      - question: "Is the problem being
addressed important and relevant to the
community?"
        description: "Papers are viewed more
favorably when they tackle a problem that is
clearly articulated as significant and timely
for the field."
      - question: "Is the core idea novel,
interesting, and well-motivated?"
        description: "Novelty and clear
motivation are consistently praised. Reviewers
look for a contribution that is not just an
```

incremental tweak but offers a new perspective
or useful framework."
        presentation_and_clarity:
        - question: "Is the paper well-written,
clearly organized, and easy to follow?"
            description: "High value is placed on
clarity. Reviews for good papers often
explicitly mention that the writing is good and
the method is easy to understand."
        - question: "Does the paper use effective
visualizations to explain its core ideas?"
            description: "The use of clear,
informative visualizations is noted as a
significant strength that enhances the reader's
understanding of the proposed concepts."
        evaluation_and_rigor:
        - question: "Are the experiments
comprehensive and the evaluations thorough?"
            description: "Accepted papers are often
praised for having sound, comprehensive
experiments with solid ablation studies that
justify their claims and design choices."
        - question: "Is the study complete and the
analysis insightful?"
            description: "Reviewers appreciate
papers that seem 'complete' in their
investigation, providing a full picture rather
than a preliminary exploration."
        - question: "Is the work reproducible, for
instance, by open-sourcing code and data?"
            description: "While not a universal
requirement, providing code is explicitly
mentioned as a positive factor that increases
the paper's value and reproducibility."
        - question: "Is the proposed solution
reasonable and well-justified for the problem?"
            description: "A logical and promising
connection between the problem statement and the
proposed solution is a key characteristic of
papers that receive positive feedback."
        - question: "Does the paper clearly
outperform relevant baselines?"
            description: "Demonstrating a clear and
significant improvement over existing, well-
chosen baselines is a very common and persuasive
strength."
    bad_paper:
        contribution_and_novelty:
        - question: "Is the contribution just a
combination of existing methods with limited
novelty?"
            description: "This is the most common
and critical flaw identified. Papers are
frequently criticized for lacking originality or
simply stitching together known components."
        - question: "Is the contribution too
simple, minor, or incremental to be significant
?"
            description: "Reviewers often reject
papers where the core idea, while perhaps
functional, is deemed too simplistic or its
contribution too marginal for a top-tier venue."
        - question: "Is the motivation for the
work unclear or is the problem framing
unconvincing?"
            description: "A frequent weakness is the
failure to clearly explain why the problem is
important or why the proposed approach is
necessary."
        experiments_and_evidence:
        - question: "Are the experiments weak,
insufficient, or conducted on overly simple
datasets?"
            description: "Papers are consistently
penalized for weak empirical validation, such as
using toy datasets, not running enough
experiments, or lacking sufficient detail like
random seeds."
        - question: "Does the paper fail to
compare against necessary SOTA or strong
baseline methods?"
            description: "An inadequate comparison
to the state of the art or relevant baselines is
a major red flag and a common reason for
rejection."
        - question: "Are key design choices left
unsubstantiated by ablation studies?"
            description: "Reviewers expect authors
to justify components of their method through
ablations; the absence of these studies is a
frequently cited weakness."
        - question: "Are the claims exaggerated or
not sufficiently supported by the evidence
provided?"
            description: "A mismatch between the
claims made in the text and the actual results
presented in the experiments is a critical flaw
."
        clarity_and_soundness:
        - question: "Is the paper poorly written,
hard to follow, or filled with jargon and typos
?"
            description: "Poor presentation,
including unclear language, logical gaps, and
typos, is a significant factor in negative
reviews."
        - question: "Does the method lack
theoretical justification, proofs, or guarantees
?"
            description: "For papers proposing new
algorithms, the absence of theoretical analysis
or justification is frequently pointed out as a
major weakness."
        - question: "Does the paper show a lack of
awareness of relevant prior work?"
            description: "Missing citations to
important and recent related work is seen as a
sign of poor scholarship and is a common point
of criticism."

Listing 10: Rubric-based Template for Reviewer-
Imitating Guidelines

```
You are an expert peer reviewer. Please read the
following paper content and evaluate its
quality based on the following instructions.

# Paper
{content}

# Reviewer Guideline
{reviewer_imitating_guideline}

# Scoring Procedure:
- For each of the 10 questions in the `
good_paper` section:
  - If the answer is Yes, assign +1 point, else
0.
```

```
- For each of the 10 questions in the `bad_paper
` section:
  - If the answer is Yes, assign -1 point, else
0.

Compute the temporary score by summing all the
above responses.
- This results in a value between -10 and +10.

Normalize the temporary score to a section
rating in the range 1 to 10 using the following
formula:
normalized_score = round(((temporary_score + 10)
 / 20) * 9 + 1)

This maps:
- -10 -> 1
- 0 -> 5
- +10 -> 10

# Section Rating

Provide:
- The temporary score (-10 to +10)
- The normalized section rating (1 to 10)
- A short explanation of the score based on your
 answers to the checklist

# Final Output

Provide:
- A numerical integer overall rating that is
same as the normalized section rating (1-10):
    - 10 = Strong Accept
    - 8 = Accept
    - 6 = Weak Accept
    - 5 = Borderline
    - 3 = Weak Reject
    - 1 = Strong Reject

- A justification paragraph summarizing the key
strengths and weaknesses of the paper

Finally, write the final score using the
following exact format (on its own line):
"Overall Rating: (Your Rating)"
```