Better Heads Do Not Guarantee Better Binarized Constituency Parsing

Abstract

We revisit punctuation-aware tree binarization for constituency parsing and ask whether dependency-induced headedness improves binary parser supervision. Although learned heads substantially outperform rule-based heads in intrinsic head prediction, they do not yield consistent parsing gains after debinarization. In particular, punctuation-conditioned evaluation shows that learned headedness underperforms rule-based binarization in macro-average punctuation-sensitive F_1, despite a small overall gain on CTB. Similar instability appears under cross-treebank transfer. These results suggest that linguistically grounded headedness is not necessarily parser-optimal when used as a binarization control signal. The paper presents a negative result: better head prediction does not imply better punctuation-sensitive constituency parsing.

1 Introduction

Tree binarization converts non-binary constituency trees into binary trees so that parsing algorithms can operate over uniform local branching decisions. It is central to chart-based parsing, including CKY-style algorithms (Cocke, 1969; Kasami, 1966; Younger, 1967), and it has also shaped transition-based constituency parsing, where parser actions are often defined over binary or incrementally binarized structures (Sagae and Lavie, 2005; Zhu et al., 2013). Because binarization is reversible, it is often treated as a technical preprocessing step whose effects disappear after debinarization.

This view is incomplete when binarized trees serve as parser training targets. A binary tree does not only encode the recoverable non-binary tree; it also specifies the order of local composition, the intermediate categories exposed to the learner, and the structural domains over which parsing decisions are trained. Different binary trees may debinarize to the same original tree while presenting different supervision signals. Binarization is therefore not merely an encoding convention, but an interface between treebank annotation and parsing architecture.

This interface is especially consequential for head-driven binarization. The selected head child anchors the binary spine of a constituent and determines how non-head material is composed around it. Since most constituency treebanks do not annotate head children, head-driven binarization has traditionally relied on hand-written head percolation rules (Collins, 1999), which encode treebank-specific projection conventions.

A natural alternative is to induce heads from aligned dependency annotation. For each constituency span, the head child can be defined as the child that dominates the dependency head of that span. This yields a linguistically grounded and independently evaluable head source. Recent work has also reconsidered head selection in neural constituency parsing by treating heads as dynamic or latent parser-internal decisions (Hou and Li, 2025). Our question is different: if heads are used not as latent model variables, but as control signals for constructing binary parser targets, does more accurate headedness yield better parsing supervision?

We test this question under punctuation-aware binarization. Punctuation is often ignored or removed under PARSEVAL and standard `evalb` conventions (Black et al., 1991), although it marks clause boundaries, appositive domains, coordination breaks, parentheticals, quotations, and sentence closure. Removing punctuation before binarization changes the local configurations from which binary trees are derived. We therefore construct binary targets that retain punctuation as boundary structure before binary branching is imposed, and compare rule-based heads with dependency-induced learned heads under otherwise identical parser training and debinarization conditions.

The motivating hypothesis is straightforward.

If punctuation supplies boundary information and dependency-induced heads better approximate syntactic projection, then punctuation-aware binarization with learned heads should provide better binary supervision. Our results do not support this hypothesis. Although learned heads substantially outperform rule-based heads in intrinsic head prediction, they do not yield consistent downstream parsing gains after debinarization. The learned-head condition is slightly better on CTB overall, but not on PTB, and this small gain disappears under punctuation-conditioned evaluation. There, learned headedness underperforms rule-based binarization in macro-average punctuation-sensitive F_1 on both treebanks. Similar instability appears under cross-treebank transfer.

The paper's main contribution is a negative result: head accuracy is not binarization utility. The child that best matches an independently annotated dependency analysis is not necessarily the child that yields the most learnable binary target for a constituency parser. Linguistically grounded headedness may make the binarization interface more explicit, but it is not automatically parser-optimal.

2 Tree binarization with punctuation

We define the binarization procedure used to construct parser targets from constituency trees whose terminals include lexical tokens and punctuation. Let T be such a tree, and let H specify the head child of each nonterminal node. The function $f_{\text{punct}}(T; H)$ maps T to a binary tree T^{bin} in two steps: punctuation is first retained in the local child sequence as boundary structure, and the resulting sequence is then binarized by head-driven composition. Thus, punctuation is present when binary structure is constructed, rather than removed before binarization and reattached afterward.

The transformation is reversible; formally, $f_{\text{punct}}^{-1}(f_{\text{punct}}(T; H)) = T$. The inverse removes only intermediate binarization nodes and restores the original ordered children, including punctuation. Punctuation-aware binarization therefore defines a reversible parser target, not a new annotation layer.

Punctuation as boundary structure Punctuation is treated as boundary structure, not as a phrasal head. It constrains the local domain in which non-punctuation material is grouped. Right-boundary punctuation, such as commas and periods, is grouped with the material to its left:

$(X\ \alpha\ \beta\ p) \Rightarrow (X\ (\text{@}X\ \alpha\ \beta)\ p)$, where p is right-boundary punctuation. Left-boundary punctuation, such as opening quotation marks and opening parentheses, is treated dually: $(X\ p\ \alpha\ \beta) \Rightarrow (X\ p\ (\text{@}X\ \alpha\ \beta))$. The @X node marks an intermediate constituent introduced by the transformation and records the boundary position of punctuation without treating punctuation as the projecting head.

Head-driven binary conversion After boundary positions have been fixed, the full child sequence is binarized. For a nonterminal node v with label X and ordered children $ch(v) = \langle v_1, \ldots, v_k \rangle$, let $h(v) = v_j$ be its designated head child. The conversion introduces @X intermediate nodes until the local branching factor is binary, while preserving v_j as the projection anchor of X. Because $h(v)$ is selected over the full child sequence, punctuation remains part of the local configuration used to construct the binary spine.

Reversibility Debinarization removes only the @-prefixed intermediate nodes and restores the original ordered children: $f_{\text{punct}}^{-1}(T^{\text{bin}}) = T$. Labels, spans, terminal order, and punctuation tokens are preserved. Recoverability alone does not determine parser supervision, since multiple binary trees may debinarize to the same original tree. Punctuation-aware binarization therefore requires punctuation to shape binary construction, not merely to survive debinarization.

Head sources We compare two head sources only as binarization controls. The rule-based condition uses Collins-style percolation rules. The learned condition uses a previously trained dependency-induced head selector, which predicts the child containing the dependency head of each constituent span. Head prediction itself is not a contribution of this paper; it is used only to test whether intrinsically stronger headedness yields better binary parser targets.

3 Experiments

We evaluate whether intrinsically stronger heads yield better binary parser targets under punctuation-aware binarization.

Intrinsic head accuracy Table 1 shows that the learned head selector substantially outperforms rule-based heads against dependency-induced gold heads. These heads are used only as binarization

controls in the parsing experiments.[1]

	$\mathcal{R}$	$\mathcal{L}$
PTB (Marcus et al., 1993)	67.89	98.54
CTB (Xue et al., 2005)	92.42	100.00

Table 1: Intrinsic head prediction accuracy against dependency-induced gold heads.

Parsing with punctuation-aware binarization For each head source, we binarize the training trees, train the same parser, and debinarize predicted trees before evaluation against the original gold trees. Thus, the parser and evaluation target are fixed; only the binary supervision changes. Table 2 reports labeled bracket F_1.[2]

		EVALB	JP-EVALB
PTB	$\mathcal{R}_\emptyset$	95.50	94.92
	$\mathcal{R}_p$	95.97	95.43
	$\mathcal{L}_p$	95.88	95.35
CTB	$\mathcal{R}_\emptyset$	92.17	90.29
	$\mathcal{R}_p$	94.26	92.40
	$\mathcal{L}_p$	94.46	92.56

Table 2: Parsing accuracy after deterministic debinarization.

Despite the large intrinsic advantage in Table 1, learned heads do not yield consistent gains after debinarization. They are slightly below rule-based punctuation-aware binarization on PTB and slightly above it on CTB. The overall scores therefore show that punctuation-aware targets remain trainable, but they do not show that better head prediction reliably gives better binary parser supervision.

Punctuation-sensitive evaluation Table 3 reports macro-average punctuation-conditioned F_1 with JP-EVALB; full punctuation-by-punctuation scores and gold counts appear in Appendix C.3. The learned-head condition underperforms both rule-based alternatives on both treebanks.

Cross-treebank binarization We further test whether transferred heads can construct punctuation-aware parser targets when target-specific head supervision is unavailable. A head

---

[1] $\mathcal{R}$ denotes rule-based head finding, and $\mathcal{L}$ denotes learned head finding.

[2] $\mathcal{R}_\emptyset$ denotes rule-based binarization without punctuation awareness, $\mathcal{R}_p$ rule-based punctuation-aware binarization, and $\mathcal{L}_p$ learned-head punctuation-aware binarization. evalb excludes punctuation from evaluation (Black et al., 1991), whereas JP-EVALB retains punctuation-bearing constituents (Jo et al., 2024).

	$\mathcal{R}_\emptyset$	$\mathcal{R}_p$	$\mathcal{L}_p$
PTB	92.63	92.43	92.27
CTB	94.22	93.99	93.50

Table 3: Macro-average punctuation-conditioned F_1 scores with JP-EVALB.

selector trained on a source treebank is applied to a target treebank after deterministic label normalization; the predicted heads are then used only to anchor the binary spine for punctuation-aware binarization. Parser training and evaluation follow the same debinarization-based protocol as above. This setting is intended to test whether head selection can be reused across resources, rather than whether transferred headedness is intrinsically optimal.

	$\mathcal{R}_p$	$\mathcal{T}_p$	$\mathcal{L}_p$
Sinica (Huang et al., 2000)	N/A	79.03	N/A
FTB (Abeillé et al., 2003)	88.65	86.82	88.92

Table 4: Cross-treebank parsing accuracy under punctuation-aware binarization with JP-EVALB. Transferred heads are predicted by a selector trained on CTB; Appendix B.3 details the transfer procedure.

Table 4 shows that transferred heads ($\mathcal{T}_p$) can provide usable binary targets, but they do not reliably match target-specific or resource-specific head sources. The degradation on FTB indicates that projection conventions remain treebank-sensitive even when the binarization procedure itself is fixed. This reinforces the main result: head selection is not a neutral preprocessing choice, but a control signal whose utility depends on the target annotation scheme.

4 Analysis

The experiments separate punctuation preservation, linguistic headedness, and parser-optimal binarization. Punctuation is syntactically meaningful, learned heads are more faithful to dependency projection, and the transformation is reversible. Yet these properties do not yield better punctuation-sensitive parsing. The negative result is therefore specific: better head prediction does not imply better binary supervision.

This does not weaken the linguistic status of punctuation. Earlier work showed that grammars retaining punctuation can outperform those that discard it (Jones, 1994), and that punctuation con-

tributes to syntactic analysis (Briscoe and Carroll, 1995; Jones, 1996). Nunberg's account of punctuation as a structured subsystem remains central here (Nunberg, 1990). Our result instead narrows the computational claim: punctuation should remain visible, but its presence does not determine which head source yields the most learnable binary target.

Head accuracy and binarization utility A dependency-induced head identifies the child containing the dependency head of a constituent span. A binarization head determines how that constituent's children are recursively grouped into a binary training target. These notions are related, but they optimize different objects. Intrinsic head evaluation rewards agreement with dependency projection; parser training rewards binary structures that are regular, learnable, and recover accurate constituent spans after debinarization.

Reversibility hides this distinction. Many binary trees can collapse to the same original constituent. Head choice may therefore change the intermediate composition order without changing the final bracket set. Since labeled bracket F_1 is computed after debinarization, it cannot reward a head source merely for being linguistically more faithful. The parser learns from intermediate structure, but evaluation largely removes it.

Punctuation and boundary-sensitive composition Punctuation-bearing constituents expose the mismatch because punctuation is boundary-sensitive rather than head-like. Commas, periods, quotation marks, parentheses, colons, and semicolons mark closure, interruption, apposition, quotation, coordination-like separation, parenthetical insertion, and sentence boundary. Their contribution is configurational: punctuation shapes the domain in which other material is composed.

Dependency heads do not necessarily encode this boundary function. In dependency annotation, punctuation is often attached to nearby lexical material or handled by conventions for dependency well-formedness. In constituency annotation, the same punctuation mark may delimit a larger phrasal or clausal domain. A learned head can therefore be correct for dependency projection while producing a binary spine that is less favorable for punctuation-sensitive constituency parsing.

This explains the punctuation-conditioned degradation. Rule-based heads impose stable category-based composition patterns. Learned heads introduce dependency-aligned variation into the binary

spine, and around punctuation this variation is not consistently useful. The result does not imply that punctuation is irrelevant. Instead, it shows that punctuation-sensitive parsing depends on the interaction between boundary structure and learnable composition order, not on head accuracy alone.

Binarization as a parser interface Punctuation-aware binarization is a parser interface, not a transparent encoding. Punctuation defines boundary-sensitive local domains; headedness selects projection anchors inside those domains. These roles cannot be collapsed into a single notion of linguistic correctness. A head source may be intrinsically better yet less useful as a binarization control signal. The choice of head source is therefore a modeling decision, mediated by learnability, regularity, and compatibility with the parser objective.

5 Conclusion

This paper presents a negative result for punctuation-aware binarization: learned heads that are substantially more accurate under dependency-induced head evaluation do not yield reliably better parser targets after debinarization. They give a small overall gain on CTB, but not on PTB, and underperform rule-based alternatives in macro-average punctuation-sensitive evaluation on both treebanks. The result does not diminish the syntactic relevance of punctuation; rather, it shows that punctuation-sensitive parsing cannot be reduced to better headedness. Punctuation defines boundary-sensitive composition domains, while headedness selects projection anchors within them. These dimensions interact, but they are not interchangeable: a dependency-motivated head may still induce a binary spine that is less regular, less learnable, or less aligned with punctuation-bearing constituency structure.

The broader implication is that binarization is not a transparent encoding of treebank structure. It is an interface through which annotation decisions become parser supervision. Reversibility guarantees recoverability, but not utility; linguistic explicitness guarantees interpretability, but not parser optimality. A parser-optimal binarization may therefore require punctuation-specific composition rules, parser-aware regularization, or direct optimization of binary targets, rather than reliance on intrinsically accurate head prediction alone.

Limitations

The learned heads used in our experiments are dependency-induced, but the dependencies are not fully independent of constituency annotation. For English and Chinese, the dependency representations are obtained from treebank conversion or closely related annotation pipelines. The learned heads should therefore not be interpreted as heads from an entirely separate syntactic theory. They provide an independently evaluable projection signal, but one still shaped in part by constituency-to-dependency conversion assumptions.

The evaluation is limited to a fixed parsing architecture. The negative result concerns the use of learned heads as binarization control signals under this parser and evaluation setting. Other parsers, especially models with different inductive biases over binary structure, may interact differently with the same binarized targets.

Punctuation-by-punctuation evaluation is sensitive to the distribution of punctuation marks. Frequent marks such as commas and periods provide relatively stable estimates, whereas rare marks yield less reliable scores. The analysis should therefore be read as evidence of uneven punctuation-sensitive behavior, not as a definitive claim about each individual punctuation symbol.

Finally, the punctuation-aware procedure uses a finite punctuation inventory and deterministic boundary conventions. This makes the transformation explicit and reversible, but it may not capture all uses of punctuation, especially in quotation, apposition, parenthetical insertion, and discourse-level segmentation. A more expressive approach may require punctuation-specific composition rules or parser-aware optimization of binary targets.

References

Anne Abeillé, Lionel Clément, and François Toussenel. 2003. Building a Treebank for French. In Anne Abeillé, editor, *Treebanks: Building and Using Parsed Corpora*, pages 165–188. Kluwer.

Ezra Black, Steven P. Abney, Dan Flickinger, Claudia Gdaniec, Ralph Grishman, Phil Harrison, Don Hindle, Robert Ingria, Frederick Jelinek, Judith Klavans, Mark Liberman, Mitch Marcus, Salim Roukos, Beatrice Santorini, and Tomek Strzalkowski. 1991. A Procedure for Quantitatively Comparing the Syntactic Coverage of English Grammars. In *Proceedings of a Workshop on Speech and Natural Language*, pages 306–311, Pacific Grove, California. Morgan Kaufmann.

Ted Briscoe and John Carroll. 1995. Developing and Evaluating a Probabilistic LR Parser of Part-of-Speech and Punctuation Labels. In *Proceedings of the Fourth International Workshop on Parsing Technologies*, pages 48–58, Prague and Karlovy Vary, Czech Republic. Association for Computational Linguistics.

John Cocke. 1969. *Programming Languages and Their Compilers: Preliminary Notes*. New York University, USA.

Michael Collins. 1999. *Head-Driven Statistical Models for Natural Language Parsing*. Ph.D. thesis, University of Pennsylvania.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.

Julia Hockenmaier and Mark Steedman. 2007. CCGbank: A Corpus of CCG Derivations and Dependency Structures Extracted from the Penn Treebank. *Computational Linguistics*, 33(3):355–396.

Yang Hou and Zhenghua Li. 2025. Dynamic Head Selection for Neural Lexicalized Constituency Parsing. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16141–16155, Vienna, Austria. Association for Computational Linguistics.

Chu-Ren Huang, Feng-Yi Chen, Keh-Jiann Chen, Zhaoming Gao, and Kuang-Yu Chen. 2000. Sinica Treebank: Design Criteria, Annotation Guidelines, and On-line Interface. In *Second Chinese Language Processing Workshop*, pages 29–37, Hong Kong, China. Association for Computational Linguistics.

Eunkyul Leah Jo, Angela Yoonseo Park, and Jungyeul Park. 2024. A Novel Alignment-based Approach for PARSEVAL Measures. *Computational Linguistics*, 50(3):1181–1190.

Bernard Jones. 1996. Towards Testing the Syntax of Punctuation. In *34th Annual Meeting of the Association for Computational Linguistics*, pages 363–365, Santa Cruz, California, USA. Association for Computational Linguistics.

Bernard E. M. Jones. 1994. Exploring the Role of Punctuation in Parsing Natural Text. In *COLING 1994 Volume 1: The 15th International Conference on Computational Linguistics*, Kyoto, Japan.

Tadao Kasami. 1966. An Efficient Recognition and Syntax-Analysis Algorithm for Context-Free Languages. Technical report, University of Illinois at Urbana-Champaign.

Nikita Kitaev, Steven Cao, and Dan Klein. 2019. Multilingual Constituency Parsing with Self-Attention and Pre-Training. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3499–3505, Florence, Italy. Association for Computational Linguistics.

Nikita Kitaev and Dan Klein. 2018. Constituency Parsing with a Self-Attentive Encoder. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2675–2685, Melbourne, Australia. Association for Computational Linguistics.

Mitchell P. Marcus, Mary Ann Marcinkiewicz, and Beatrice Santorini. 1993. Building a Large Annotated Corpus of English: The Penn Treebank. *Computational linguistics*, 19(2):313–330.

Geoffrey Nunberg. 1990. *The Linguistics of Punctuation*, csli edition. University of Chicago Press, Chicago, IL.

Kenji Sagae and Alon Lavie. 2005. A Classifier-Based Parser with Linear Run-Time Complexity. In *Proceedings of the Ninth International Workshop on Parsing Technology (IWPT2005)*, pages 125–132, Vancouver, British Columbia. Association for Computational Linguistics.

Nianwen Xue, Fei Xia, Fu-dong Chiou, and Marta Palmer. 2005. The Penn Chinese TreeBank: Phrase Structure Annotation of a Large Corpus. *Natural Language Engineering*, 11(2):207–238.

Daniel H. Younger. 1967. Recognition and parsing of context-free languages in time n3. *Information and Control*, 10(2):189–208.

Muhua Zhu, Yue Zhang, Wenliang Chen, Min Zhang, and Jingbo Zhu. 2013. Fast and Accurate Shift-Reduce Constituent Parsing. In *Proceedings of the 51st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 434–443, Sofia, Bulgaria. Association for Computational Linguistics.

A Background and motivation

Binarization as a representational interface
Constituency treebanks often contain flat or variably branching structures, whereas many parsing algorithms operate over binary branching trees. Binarization resolves this mismatch by replacing each non-binary constituent with a sequence of binary combinations. Although this transformation is reversible, its role changes when binarized trees are used as parser targets.

In that setting, binarization specifies an order of local composition. It determines which daughters combine first, which intermediate projections are introduced, and which local structural contrasts are exposed to the learner. Two binary trees may debinarize to the same original constituent while encoding different composition histories. Binarization is therefore a representational interface between treebank annotation and parser supervision, not only a lossless encoding convention.

Punctuation exclusion in parser preprocessing
Parser pipelines often inherit punctuation-exclusion conventions from PARSEVAL-style evaluation and standard evalb, where punctuation is typically omitted from labeled bracket scoring (Black et al., 1991). For evaluation, this reduces sensitivity to annotation-specific punctuation treatment. For binarization, however, the same convention changes the structural input to the transformation. If punctuation is removed before binarization, boundary-bearing tokens are absent precisely when local binary structure is constructed.

Punctuation marks are not merely orthographic residue. They delimit clause boundaries, appositive domains, parentheticals, quotations, coordination breaks, and sentence closure. Subsequent reinsertion may recover the terminal string, but it cannot recover the same composition history. This distinction becomes visible under punctuation-sensitive evaluation such as JP-EVALB, which retains punctuation-bearing constituents during scoring (Jo et al., 2024).

Figure 1 illustrates the contrast. A standard pipeline that excludes punctuation during binarization may later attach it near the root, yielding the structure in Figure 1b. The punctuation-aware alternative in Figure 1c keeps punctuation inside the local constituent configuration before binary branching is imposed.

Head selection and projection conventions
Head-driven binarization adds a further representational choice. When a constituent has more than two children, the selected head child anchors the binary spine and determines how non-head material is composed around it. Because most constituency treebanks do not annotate head children, this choice is usually supplied by hand-written percolation tables, such as Collins-style rules for the Penn Treebank (Collins, 1999). Such tables encode projection conventions that may be useful, but they need not match dependency-induced heads or transfer across treebanks.

Dependency-induced heads provide an explicit alternative. Given aligned constituency and dependency trees, the head child of a constituency

(a) Original tree with punctuation

(b) Standard binarization

(c) Punctuation-aware binarization

Figure 1: Standard binarization may construct binary structure after punctuation has been excluded, whereas punctuation-aware binarization preserves the boundary relation before binary branching is imposed.

node can be defined as the child that dominates the dependency head of the corresponding span. This makes head selection independently evaluable. The experiments in the main text ask whether this intrinsic advantage also improves binary parser supervision.

Why reversibility is not enough Reversibility is necessary but not sufficient. A binarized tree must debinarize to the original constituency tree, but many binary trees satisfy this condition. They collapse to the same non-binary structure while presenting different intermediate categories, attachment orders, and local decision contexts during training.

This distinction matters because parsers are trained on binary trees, not on their debinarized equivalence classes. A reversible binarization can preserve the final tree while changing the supervision signal. Punctuation exclusion and head-source mismatch illustrate this issue: the former removes boundary-bearing tokens before local composition is determined, while the latter supplies projection anchors that may not be optimal for parser learning.

B Head sources for binarization

This appendix describes the head sources used by $f_{\mathrm{punct}}(T; H)$. Headedness is not treated as an independent parsing task in this paper. For each nonterminal node, a head child is selected only to anchor the binary spine used as a parser training target.

B.1 Dependency-induced head supervision

Let $T = (V, E)$ be a rooted constituency tree with terminals $w_1, \ldots, w_n$, and let V_{NT} be the set of nonterminal nodes. For each $v \in V_{\mathrm{NT}}$, let

$$ch(v) = \langle v_1, \ldots, v_k \rangle$$

be its ordered children. A headed constituency tree assigns one head child to each nonterminal node:

$$h(v) \in ch(v).$$

Head supervision is induced from aligned dependency annotation. Let D be a dependency tree over terminals $\{1, \ldots, n\}$, with artificial root 0, and let

$$g : \{1, \ldots, n\} \to \{0, 1, \ldots, n\}$$

be the dependency governor function. For a nonterminal node v, let $yield(v)$ be the set of terminals dominated by v. The dependency span-head candidates are:

$$H(v) = \{ i \in yield(v) : g(i) \notin yield(v) \}.$$

If $H(v)$ contains exactly one token, that token is taken as the dependency head of the span. The gold head child is the unique immediate child of v that dominates this token. Nodes for which $H(v)$ is empty or non-singleton are excluded from supervised head learning and intrinsic evaluation.

This definition identifies the child that makes a constituency span compatible with the aligned dependency analysis. It supplies the head information required for head-driven binarization.

B.2 Head prediction model

Each training instance is a nonterminal node. The input is the parent label and the ordered sequence of child labels:

$$\ell(v), \ell(v_1), \ldots, \ell(v_k),$$

and the target is the head-child index j such that $h(v) = v_j$. The model is unlexicalized and receives no word forms, lexical embeddings, or dependency features. Phrase labels and part-of-speech tags are normalized by removing redundant functional or morphological suffixes.

The label sequence is encoded with a Transformer encoder (Devlin et al., 2019). A multilayer perceptron scores each child position, and the highest-scoring child is selected as the head. The model is trained with cross-entropy loss over valid child positions. The rule-based baseline uses Collins-style head percolation rules (Collins, 1999), as implemented in Stanford CoreNLP for English and Chinese.

B.3 Head transfer

For cross-treebank transfer, a selector trained on a source resource $\mathcal{R}_s$ is applied to a target resource $\mathcal{R}_t$. Because treebanks differ in phrase labels, part-of-speech tags, and annotation conventions, target labels are normalized into the source label space with deterministic mappings:

$$\phi : \Sigma_t^{\mathrm{ph}} \to \Sigma_s^{\mathrm{ph}}, \qquad \psi : \Sigma_t^{\mathrm{pos}} \to \Sigma_s^{\mathrm{pos}}.$$

The selector predicts a head-child index for the normalized target configuration, and the predicted index is interpreted in the original target tree.

Table 5 reports intrinsic transfer accuracy. The results show partial transfer across resources, with CTB $\to$ Sinica at 69.41%, PTB $\to$ FTB at 54.95%, and CTB $\to$ FTB at 64.70%. Transfer therefore depends not only on language identity, but also on compatibility between source and target projection conventions.

Transfer setting	Head accuracy
CTB $\to$ Sinica	69.41
PTB $\to$ FTB	54.95
CTB $\to$ FTB	64.70

Table 5: Intrinsic cross-treebank and cross-lingual transfer accuracy of learned headedness.

The main error source in PTB $\to$ FTB is PP headedness. Under the dependency-induced criterion, PTB PPs are overwhelmingly head-final, while FTB and CTB PPs are almost categorically head-initial. This convention mismatch explains why PTB $\to$ FTB transfers poorly, despite the apparent structural similarity of the resources.

C Additional experimental details

C.1 Data and alignment

The main experiments use the Penn Treebank 3 (Marcus et al., 1993) and the Penn Chinese Treebank 5.1 (Xue et al., 2005). For English, we use Sections 02–21 for training, Section 22 for development, and Section 23 for testing. For Chinese, we follow the standard CTB 5.1 constituency parsing split.[3]

For head learning, constituency and dependency trees are aligned at the terminal level. After normalization, we retain only sentences whose constituency and dependency representations have identical terminal sequences. This ensures that head supervision is induced only from tokenization-consistent structures. The same splits are used for parser training and evaluation.

C.2 Parser training and evaluation

We use the Berkeley Neural Parser (Kitaev and Klein, 2018; Kitaev et al., 2019). Rather than using its default binarization, we provide punctuation-aware binary trees as parser targets.

For each treebank, the original constituency trees are transformed under each head source:

$$\mathcal{T}_{\mathrm{rule}}^{\mathrm{bin}} = f_{\mathrm{punct}}(\mathcal{T}; H_{\mathrm{rule}}),$$
$$\mathcal{T}_{\mathrm{learn}}^{\mathrm{bin}} = f_{\mathrm{punct}}(\mathcal{T}; H_{\mathrm{learn}}).$$

The parser architecture, training configuration, intermediate-node convention, punctuation treatment, and debinarization procedure are identical across conditions. Only the head source used to construct the binary targets differs.

At test time, predicted binary trees are deterministically debinarized before evaluation against the original unbinarized gold trees. Thus, differences in parsing accuracy reflect differences in binary supervision, not differences in the final evaluation target. We report labeled bracket F_1 with both standard `evalb` and JP-EVALB (Jo et al., 2024), the latter retaining punctuation during constituent evaluation.

C.3 Punctuation-sensitive evaluation

For punctuation-sensitive analysis, we restrict evaluation to constituents containing a given punctuation mark and compute F_1 with JP-EVALB. Table 6 reports punctuation-conditioned scores for each

---

[3] https://github.com/nikitakit/self-attentive-parser/tree/master/data/ctb_5.1

mark. The row $\mathcal{G}$ gives the corresponding number of gold punctuation-bearing constituents. The macro-average columns are summarized in Table 3.

C.4 Structural comparison of binary targets

To measure how much the head source changes parser supervision before debinarization, we compare binary targets directly. For each original tree, we compare $T_{\text{rule}}^{\text{bin}}$ and $T_{\text{learn}}^{\text{bin}}$.

We report bracketing F_1 between the two binary trees and exact binary spine identity. Bracketing F_1 measures overlap in intermediate spans. Exact spine identity is stricter, requiring the full binary structure introduced for an original constituent to match. A high bracketing score with lower spine identity indicates local rotations within the same original constituent.

C.5 Cross-treebank head transfer

Cross-treebank transfer is used only to construct binary parser targets. The source and target label inventories are normalized with deterministic mappings, after which the source-trained head selector is applied to the target constituency trees. The resulting heads determine the projection anchor used by punctuation-aware binarization. This setting applies to constituency resources that lack aligned dependencies or resource-specific head rules.

C.6 Alignment with English CCGbank

We compare punctuation-aware PTB binary trees with aligned CCGbank derivations (Hockenmaier and Steedman, 2007). The comparison is conducted on Section 23 of the Penn Treebank. CCGbank provides derivations for 2,407 of the 2,416 original sentences. After exact terminal alignment, 1,858 sentences remain; most exclusions involve tokenization mismatches around punctuation and quotation marks.

To focus on structural correspondence rather than category inventory, we simplify both representations before evaluation. All nonterminal labels are replaced with `nt`, POS–word terminals are preserved, and type-raising unary rules are removed from CCGbank. Structural overlap is then evaluated with JP-EVALB, which retains punctuation during constituent evaluation.

The punctuation-aware PTB binary trees obtain $F_1 = 76.07$ against the simplified CCGbank derivations. The remaining mismatches mostly reflect different grammatical treatments of punctuation. In appositive expressions such as *the CEO,*

John Smith, our binarization attaches the comma to the preceding noun phrase to preserve local constituency. CCGbank often associates the comma with the appositive phrase and promotes it to a higher derivational position, giving it a role closer to coordination. These divergences reflect different assumptions about punctuation structure rather than annotation noise.

D Additional analysis

D.1 Algorithmic interpretation

Punctuation-aware binarization separates two operations that are easily conflated. First, punctuation-bearing boundary configurations are fixed inside the original local child sequence. Second, the resulting configuration is converted into a binary tree by head-driven composition. A procedure that only groups punctuation with neighboring material is therefore not yet a binarization procedure. Conversely, a head-driven binarization that operates after punctuation has been removed is not punctuation-aware in the relevant sense.

This distinction also explains why reversibility is too weak as a criterion. The identity

$$f_{\text{punct}}^{-1}(f_{\text{punct}}(T; H)) = T$$

states recoverability, but not usefulness as parser supervision. Many reversible transformations preserve the final tree while changing the intermediate structures on which the parser is trained. The relevant question is therefore whether punctuation participates in binary structure construction, not merely whether it can be restored after debinarization.

D.2 Punctuation-specific instability

The punctuation-conditioned results are uneven because the evaluation slices are not linguistically homogeneous. Sentence-final punctuation often marks a regular closure relation. Commas are frequent but functionally diverse, spanning coordination, apposition, clause linkage, parentheticals, and discourse-level segmentation. Quotation marks and brackets occur in paired constructions, where the left and right symbols have different configurational roles. Rare punctuation marks yield less stable scores, since a small number of local errors can substantially change F_1.

This heterogeneity weakens the expectation of uniform gains from a single head source.

	,	$	.	"	"	'	-RRB-	-LRB-	;	:	-LCB-	-RCB-	#	...	`	?	-	=	!	AVG
$\mathcal{R}_\emptyset$	91.38	92.77	97.35	92.15	91.99	95.42	89.89	90.32	94.29	88.19	92.68	92.68	95.56	87.64	87.72	74.07	93.75	83.33	100.00	92.63
$\mathcal{R}_p$	91.65	92.65	97.47	92.39	91.70	96.12	91.08	91.52	95.38	90.63	90.16	90.16	97.78	88.89	93.10	76.36	93.75	66.67	66.67	92.43
$\mathcal{L}_p$	91.37	92.57	97.51	91.81	91.13	95.42	88.16	88.45	93.81	91.12	90.32	90.32	97.78	91.11	88.14	69.09	93.75	83.33	0.00	92.27
$\mathcal{G}$	10067	2822	2439	1680	1283	346	309	307	162	125	65	65	45	43	29	29	15	6	1	19,838

(a) PTB

	,	、	。	"	"	(	)	《	》	;	—	:	——	!	AVG
$\mathcal{R}_\emptyset$	93.88	92.45	99.61	94.58	94.44	99.19	98.39	97.92	97.92	97.67	97.56	95.65	66.67	100.00	94.22
$\mathcal{R}_p$	93.89	92.39	99.61	94.63	93.92	99.19	98.39	92.93	92.93	97.67	85.71	95.65	70.59	100.00	93.99
$\mathcal{L}_p$	93.03	91.49	99.61	95.57	94.97	97.56	97.56	98.95	98.95	93.62	95.24	95.65	50.00	100.00	93.50
$\mathcal{G}$	1359	1009	256	102	90	62	62	47	47	22	20	11	10	1	3098

(b) CTB

Table 6: Punctuation-conditioned F_1 scores with JP-EVALB.

Dependency-induced heads may help when dependency projection and constituency boundary structure coincide, but hurt when punctuation functions as a delimiter independent of the lexical head. The punctuation-by-punctuation analysis is computed only with JP-EVALB, whose role is to keep punctuation-bearing constituents visible to evaluation. The observed degradation therefore indicates that punctuation-sensitive constituency structure is not reducible to headedness.