Identifiable Generative Models for Missing Not at Random Data Imputation

Abstract

Real-world datasets often have missing values associated with complex generative processes, where the cause of the missingness may not be fully observed. This is known as missing not at random (MNAR) data. However, many imputation methods do not take into account the missingness mechanism, resulting in biased imputation values when MNAR data is present. Although there are a few methods that have considered the MNAR scenario, their model's identifiability under MNAR is generally not guaranteed. That is, model parameters can not be uniquely determined even with infinite data samples, hence the imputation results given by such models can still be biased. This issue is especially overlooked by many modern deep generative models. In this work, we fill in this gap by systematically analyzing the identifiability of generative models under MNAR. Furthermore, we propose a practical deep generative model which can provide identifiability guarantees under mild assumptions, for a wide range of MNAR mechanisms. Our method demonstrates a clear advantage for tasks on both synthetic data and multiple real-world scenarios with MNAR data.

1 Introduction

Missing data is an obstacle in many data analysis problems, which may seriously compromise the performance of machine learning models, as well as downstream tasks based on these models. Being able to successfully recover/impute missing data in an unbiased way is the key to understanding the structure of real-world data. This requires us to identify the underlying data-generating process, as well as the probabilistic mechanism that decides which data is missing.

In general, there are three types of missing mechanisms [39]. The first type is missing completely at random (MCAR), where the probability of a data entry being missing is independent of both the observed and unobserved data (Figure 1 (a)). In this case, no statistical bias is introduced by MCAR.The second type is missing at random (MAR), which assumes that the missing data mechanism is independent of the value of unobserved data (Figure 1 (b)). Under this assumption, maximum likelihood learning methods without explicit modeling of the missingness mechanism can be applied by marginalizing out the missing variables [3, 21, 24]. However, both MCAR and MAR do not hold in many real-world applications, such as recommender systems [6, 12], healthcare [11], and surveys [46]. For example, in a survey, participants with financial difficulties are more likely to refuse to complete the survey about financial incomes. This is an example of missing not at random (MNAR), where the cause of the missingness (financial income) can be unobserved. In this case, ignoring the missingness mechanism will result in biased imputation, which will jeopardize down-stream tasks.

There are few works considering the MNAR setting in scalable missing value imputation. On the one hand, many practical methods for MNAR does not have identifiability guarantees [10, 6, 20].

Figure 1: Exemplar missing data situations. **(a)**: MCAR; **(b)**: MAR; **(c)-(i)**: MNAR.

That is, the parameters can not be uniquely determined, even with access to infinite samples [29, 38]. As a result, missing value imputation based on such parameter estimation could be biased. On the other hand, there are theoretical analyses on the identifiability in certain scenarios [34, 48, 30, 29, 31, 52, 50], but without associated practical algorithms for flexible and scalable settings (such as deep generative models). Moreover, MNAR data have many possible cases (Figure 1) based on different independence assumptions [34], making the discussion of identifiability difficult. This motivates us to fill this gap by extending identifiability results of deep generative models to different missing mechanisms, and provide a scalable practical solution.Our contribution are threefold:

- We provide a theoretical analysis of identifiability for generative models under different MNAR scenarios (Section 3). More specifically, we provide sufficient conditions, under which the ground truth parameters can be uniquely identified via maximum likelihood (ML) learning using observed information [20]. We also demonstrate how the assumptions can be relaxed in the face of real-world datasets. This provides foundation for practical solutions using deep generative models.

- Based on our analysis, we propose a practical algorithm model based on VAEs (Section 4), named GINA (deep generative imputation model for missing not at random). This enables us to apply flexible deep generative models in a principled way, even in the presence of MNAR data.

- We demonstrate the effectiveness and validity of our approach by experimental evaluations (Section 6) on both synthetic data modeling, missing data imputation in real-world datasets, as well as downstream tasks such as active feature selection under missing data.

2   Backgrounds

Model Identifiability Identifiablity is critical to analyzing model behaviour under missing data. We give the definition below [38, 15]:

Definition 2.1 (Model identifiability). *Assume $p_\theta(X)$ is a distribution of some random variable X, θ is its parameter that takes values in some parameter space Ω_θ. Then, if $p_\theta(X)$ satisfies $p_{\theta_1}(X) \neq p_{\theta_2}(X) \iff \theta_1 \neq \theta_2, \forall \theta_1, \theta_2 \in \Omega_\theta$, we say that p_θ is identifiable w.r.t. θ on Ω_θ.*

In other words, a model $p_\theta(X)$ is identifiable, if different parameter configurations implies a different probabilistic distributions over the observed variables. With identifiability guarantee, if the model assumption is correct, the true generation process can be recovered. Next, we introduce necessary notations and of missing data, and set up a concrete problem setting.

Basic Notation Similar to the notations introduced by [39, 10], let X be the complete set of variables in the system of interest. We call it *observable variables*. Let $\mathcal{I} = \{1, ..., D\}$ be the *index set* of all observable variables, i.e., $X = \{X_i | i \in \mathcal{I}\}$. Let X_o denote the set of actually *observed variables*, here $O \in \mathcal{I}$ is a index set such that $X_o \subset X$. We call O the *observable pattern*. Similarly, X_u denotes the set of *missing/unobserved variables*, and $X = X_o \bigcup X_u$. Additionally, we use R to denote the missing mask indicator variable, such that $R_i = 1$ indicates X_i is observed, and $R_i = 0$ indicates otherwise. We call a probabilistic distribution $p(X)$ on X the *reference distribution*, that

is, the distribution that we would have observed if no missing mechanism is present; and we call the conditional distribution $p(R|X)$ the *missing mechanism*, which decides the probability of each X_i being missing. Then, we can define the marginal distribution of *partially observed variables*, which is given by $\log p(X_o, R) = \log \int_{X_u} p(X_o, X_u, R) dX_u$. Finally, we will use lowercase letters to denote the *realized values* of the corresponding random variable. For example, $(x_o, r) \sim p(X_o, R)$ is the realization/samples of X_o and R, and the dimensionality of x_o may vary for each realizations.

Problem setting Suppose that we have a ground truth data generating process, denoted by $p_{\mathcal{D}}(X_o, R)$, from which we can obtain (partially observed) samples $(x_o, r) \sim p_{\mathcal{D}}(X_o, R)$. We also have a model to be optimized, denoted by $p_{(\theta, \lambda)}(X_o, X_u, R)$, where θ is the parameter of reference distribution $p_\theta(X)$, and λ the parameter of missing mechanism $p_\lambda(R|X)$. Our goal can then be described as follows:

- To establish the identifiability of the model $p_{(\theta, \lambda)}(X_o, R)$. That is, we wish to uniquely and correctly identify $\hat{\theta}$, such that $p_{\hat{\theta}}(X) = p_{\mathcal{D}}(X)$, given infinite amount of partially observed data samples from ground truth, $(x_o, r) \sim p_{\mathcal{D}}(X_o, R)$.
- Then, given the identified parameter, we will be able to perform missing data imputation, using $p_{\hat{\theta}}(X_u|X_o)$. If our parameter estimate is unbiased, then our imputation is also unbiased, that is, $p_{\hat{\theta}}(X_u|X_o) = p_{\mathcal{D}}(X_u|X_o)$ for all possible configurations of X_o.

Challenges in MNAR imputation Recall the three types of missing mechanisms: if data is MCAR, $p(R|X) = p(R)$; if if data is MAR, $p(R|X) = p(R|X_o)$; otherwise, we call it MNAR. When missing data is MCAR or MAR, missing mechanism can be ignored when performing maximum likelihood (ML) inference based only on the observed data [39], as:

$$\arg \max_\theta \mathbb{E}_{(x_o, r) \sim p_{\mathcal{D}}(X_o, R)} \log p_\theta(X_o = x_o) = \arg \max_\theta \mathbb{E}_{(x_o, r) \sim p_{\mathcal{D}}(X_o, R)} \log p_\theta(X_o = x_o, R = r)$$

where $\log p(X_o) = \log \int_{X_u} p(X_o, X_u) dX_u$. In practice, ML learning on X_o can done by EM algorithm [3, 20]. However, when missing data is MNAR, the above argument does not hold, and the missing data mechanism cannot be ignored during learning. Consider the representative graphical model example in Figure 1 (d), which has appeared in many context of machine learning. In this graphical model, X is the cause of R, and the connections between X and R are fully connected, i.e., each single node in R are caused by the entire set X. All nodes in R are conditionally independent from each other given X.

Clearly, this is an example of a data generating process with MNAR mechanism. In this case, Rubin proposed to jointly optimize both the reference distribution $p_\theta(X)$ and the missing data mechanism $p_\lambda(R|X)$, by maximizing:

$$\arg \max_{\theta, \lambda} \mathbb{E}_{(x_o, r) \sim p_{\mathcal{D}}(X_o, R)} \log p_{(\theta, \lambda)}(X_o = x_o, R = r) \tag{1}$$

This factorization is referred as *selection modeling* [20, 10]. There are multiple challenges if we want to Eq. 1 to obtain a practical model that provide unbiased imputation. First, we need model assumption to be consistent with the real-world data generation process, $p_{\mathcal{D}}(X_o, R)$. Given a wide range of possible MNAR scenarios, it is a challenge to design a general model. Secondly, the model need to be identifiable to enable the possibility to learn the underlying process which leads to unbiased imputation. Next, we will analyze the identifiablity of generative models and propose a pracical methods that can be used in MNAR with mild assumptions.

3 Establishing model identifiability under MNAR

One key issue of training probabilistic models under MNAR missing data is its identifiability. Recall that (Definition 2.1) model identifiability characterize the property that the mapping from parameter θ to the distribution $p_\theta(X)$ is one-to-one. This is often closely related to maximum likelihood learning. In fact, it is not hard to show that Definition 2.1 is equivalent to the following Definition 3.1:

Definition 3.1 (Equivalent definition of identifiability). *We say a model $p_\theta(X)$ is identifiable, if:*

$$\arg \max_{\theta \in \Omega_\theta} \mathbb{E}_{x \sim p_{\theta^*}(X)} \log p_\theta(X = x) = \theta^*, \quad \forall \theta^* \in \Omega_\theta \tag{2}$$

In other words, the "correct" model parameter θ^* can be identified via maximum likelihood learning (under complete data), and the ML solution is unbiased. Similarly, when MNAR missing mechanism

is present, we perform maximum likelihood learning on both X_o and R using Eq. 1. Thus, we need $\log p_{\theta,\lambda}(X_o, R)$ to be identifiable under MNAR, so that we can correctly identify the ground truth data generating process, and achieve unbiased imputation. The identifiability of $\log p_{\theta,\lambda}(X_o, R)$ under MNAR is usually not guaranteed, even in some simplistic settings [29]. In this section, we will give the sufficient conditions for model identifiability under MNAR, and study how these can be relaxed for real-world applications

3.1 Sufficient conditions for identifiability under MNAR

In this section, we give sufficient conditions where the model parameters θ can be uniquely identified by Rubin's objective, Eq. 1. Our aim is to i), find a set of model assumptions, so that it can cover many common scenarios and be flexible for practical interests; and ii), under those conditions, we want to show that its parameters can be uniquely determined by the partial ML solution Eq. 1. As shown in Figure 1, MNAR have many possible difference cases depending on its graphical structures. We want our results to cover every situation.

Instead of doing case by case analysis, we will start our identifiability anaylsis with one fairly general case as the example shown in Figure 1 (h) where the missingness can be caused by other partially observed variable, by itself (self-masking) or by latent variables. Then, we will discuss how these analysis can be applied to other MNAR scenarios in Section 3.2.

Data setting D1 Suppose the ground truth data generation process satisfies the following conditions: all variables X are generated from a shared latent confounder Z, and there are no connections among X; and the missingness indicator R variable can not be the parent of other variables. A typical example of such distribution is depicted in Figure 1 (h).We further assume that $p_{\mathcal{D}}(X_o, X_u, R)$ has the following parametric form: $p_{\mathcal{D}}(X_o, X_u, R) = \int_Z \prod_d p_{\theta_d^*}(X_d|Z)p(Z)p_{\lambda^*}(R|X, Z)dZ$, where $p_{\lambda^*}(R|X, Z) = \prod_d p_{\lambda_d^*}(R_d|X, Z)$, for some θ^*, λ^*.

Then, consider the following model:

Model assumption A1. We assume that our model has the same graphical representation, as well as parametric form as **data setting D1**, that is, our model can be written as:

$$p_{\theta,\lambda}(X_o, R) = \int_{X_u, Z} dX_u dZ \prod_d p_{\theta_d}(X_d|Z) \prod_d p_{\lambda_d}(R_d|X, Z)p(Z) \tag{3}$$

Here, $(\theta, \lambda) \in \Omega$ are learnable parameters that belong to some parameter space $\Omega = \Omega_\theta \times \Omega_\lambda$. Each θ is the parameter that parameterizes the conditional distribution that connects X_d and Z, $p_{\theta_d}(X_d|Z)$. Assume that the ground truth parameter of $p_{\mathcal{D}}$ belongs to the model parameter space, $(\theta^*, \lambda^*) \in \Omega$.

Given such a model, our goal is to correctly identify the ground truth parameter settings given partially observed samples from $p_{\mathcal{D}}(X_o, X_u, R)$. That is, let $(\hat{\theta}, \hat{\lambda}) = \arg\max_{(\theta,\lambda)\in\Omega} \mathrm{E}_{(x_o,r)\sim p_{\mathcal{D}}(X_o,R)} \log p_{(\theta,\lambda)}(X_o = x_o, R = r)$, we would like to achieve $\hat{\theta} = \theta^*$. In order to achieve this, we must make additional assumptions.

Assumption A2. Subset identifiability: There exist a partition[1] of $\mathcal{I}$, denoted by $\mathcal{A}_{\mathcal{I}} = \{O_s\}_{1 \leq s \leq S}$, such that: for all $O_s \in \mathcal{A}_{\mathcal{I}}$, $p_\theta(X_{O_s})$ is identifiable on a subset of parameters $\{\theta_d | d \in O_s\}$.

This assumption basically formalizes the idea of divide and conquer: we partition the whole index set into several smaller subsets $\{O_s\}_{1 \leq s \leq S}$, on which each reference distribution $p_\theta(X_{O_s})$ is only responsible for the identifiability on a subset of parameters.

Assumption A3. There exists a collection of observable patterns, denote by $\bar{\mathcal{A}}_{\mathcal{I}} := \{O'_l\}_{1 \leq l \leq L}$, such that: 1), $\bar{\mathcal{A}}_{\mathcal{I}}$ is a cover [1] of $\mathcal{I}$; 2), $p_{\mathcal{D}}(X, R_{O'_l} = 1, R_{\mathcal{I}\setminus O'_l}) > 0$ for all $1 \leq l \leq L$; and 3), for all index $c \in O'_l$, there exists $O_s \in \mathcal{A}_{\mathcal{I}}$ defined in **A2**, such that $c \in O_s \subset O'_l$.

This assumption is about the strict positivity of the ground truth data generating process, $p_{\mathcal{D}}(X_o, X_u, R)$. Instead of assuming that complete case data are available as in [34], here we assumes we should at least have some observations, $p_{\mathcal{D}}(X, R_o = 1, R_u = 0) > 0$ for $O \in \hat{\mathcal{A}}_{\mathcal{I}}$, on which $p_\theta(X_o)$ is identifiable.

To summarize, **A1** ensures that our model has the same graphical representation/parametric forms as the ground truth; **A2** $p_\theta(X_o) = \int_{X_u} p_\theta(X_o, X_u)dX_u$ should be at least identifiable for a collection

---

[1] It can be arbitrary partition in the set theory sense.

166 of observable patterns that forms a partition of $\mathcal{I}$; and **Assumption A3** ensures that $p_{\mathcal{D}}(X_o, X_u, R)$
167 should be positive for certain *important* patterns (i.e., those on which $p_\theta(X_o)$ is identifiable). Given
168 these assumptions, we have the following proposition (See Appendix C for proof.):

169 **Proposition 1** (Sufficient conditions for identifiability under MNAR). *Let $p_{\theta,\lambda}(X_o, X_u, R)$ be a*
170 *model on the observable variables X, and missing pattern R, and $p_{\mathcal{D}}(X_o, X_u, R)$ be the ground*
171 *truth distribution. Assume that they satisfies **Data setting D1**, **Assumptions A1, A2 and A3**.*

172 *Let $\Theta = \arg\max_{(\theta,\lambda)\in\Omega} \mathrm{E}_{(x_o,r)\sim p_{\mathcal{D}}(X_o,R)} \log p_{(\theta,\lambda)}(X_o = x_o, R = r)$ be the set of ML solutions of*
173 *Equation 1. Then, we have $\Theta = \{\theta^*\} \times \Theta_\lambda$. That is, the ground truth model parameter θ^* can be*
174 *uniquely identified via (partial) maximum likelihood learning.*

175 **Missing value imputation as inference** Given a model $p_{(\theta)}(X_o, X_u)$, the missing data imputation
176 problem can be then formularized by the Bayesian inference problem $p_\theta(X_u|X_o) \propto p_\theta(X_u, X_o)$.
177 If the assumptions of Proposition 2 are satisfied, it enables us to correctly identify the ground truth
178 reference model parameter, θ^*. Therefore, the imputed values sampled from the posterior $p_{\theta^*}(X_u|X_o)$
179 will be unbiased, and can be used for down stream decision making tasks.

180 **Remark:** Note that Proposition 1 can be extended to the case where model identifiability is defined
181 by equivalence classes [14, 48]. See Appendix F for details.

3.2 Relaxing "correctness of parametric model" assumption (A1)

183 In this section, we further extend our previous results to the general MNAR cases including all
184 different examples in Figure 1. In particular, we would like to see the if the same model setting
185 in Section 3.1 can be applied to scenarios where $p_{\mathcal{D}}(X_o, X_u, R)$ and $p_{\theta,\lambda}(X_o, X_u, R)$ might have
186 different parametric forms, or even different graphical representations.

To start with, we would like to point out that the mismatch between $p_{\mathcal{D}}(X_o, X_u, R)$ and the model
$p_{\theta,\lambda}(X_o, X_u, R)$ can be, to a certain extend, modeled by the *mappings between spaces of parameters*.
Let $\Omega \subset \mathbb{R}^I$ denote the parameter domain of our model, $p_{\theta,\lambda}(X_o, X_u, R)$. Suppose we have a
mapping $\Phi : \underline{\Omega} \subset \mathbb{R}^I \mapsto \mathbb{R}^J$, such that $(\theta, \lambda) \in \underline{\Omega} \subset \Omega$ is mapped to another parameter space
$(\tau, \gamma) = \Phi(\theta, \lambda) \in \Xi \subset \mathbb{R}^J$ via $\Phi(\cdot)$. Here, $\underline{\Omega}$ is a subset of Ω on which Φ is defined. Then, the
re-parameterized $p_{\theta,\lambda}(X_o, X_u, R)$ on parameter space Ξ can be rewritten as:

$$\tilde{p}_{\tau,\gamma}(X_o, X_u, R) := p_{\Phi^{-1}(\tau,\gamma)}(X_o, X_u, R)$$

187 Assuming that the inverse mapping Φ^{-1} exists. Then trivially, if $p_{\theta,\lambda}(X_o, R)$ is identifiable with
188 respect to θ and λ, then $\tilde{p}_{\tau,\gamma}(X_o, R)$ should be also identifiable with respect to τ and γ:

189 **Proposition 2.** *Let $\Omega \subset \mathbb{R}^I$ be the parameter domain of the model $p_{\theta,\lambda}(X_o, R)$. Assume that*
190 *the mapping $\Phi : (\theta, \lambda) \in \underline{\Omega} \subset \mathbb{R}^I \mapsto (\tau, \gamma) \in \Xi \subset \mathbb{R}^J$ is one-to-one on $\underline{\Omega}$ (equivalently, the inverse*
191 *mapping $\Phi^{-1} : \Xi \mapsto \underline{\Omega}$ is injective, and $\underline{\Omega}$ is its image set). Consider the induced distribution with*
192 *parameter space Ξ, defined as $\tilde{p}_{\tau,\gamma}(X_o, R) := p_{\Phi^{-1}(\tau,\gamma)}(X_o, R)$. Then, $\tilde{p}$ is identifiable w.r.t. (τ, γ),*
193 *if $p_{\theta,\lambda}(X_o, R)$ is identifiable w.r.t. θ and λ.*

194 Proposition 2 basically shows that if two distributions $p_{\theta,\lambda}(X_o, R)$ and $\tilde{p}_{\tau,\gamma}(X_o, R)$ are related by a
195 mapping Φ with nice properties, than the identifiability will translate between them. This already
196 covers many scenarios of the data-model mismatch. For example, consider the case where ground
197 truth data generation process satisfies the following assumption:

198 **Data setting D2** Suppose the ground truth $p_{\mathcal{D}}(X_o, X_u, R)$ satisfies: X are all generated by shared la-
199 tent confounders Z (as in **D1**), and R cannot be the cause of any other variables as in [34, 51].
200 Typical examples are given by any of the cases in Fig 1(excluding (j) where R_1 is the cause
201 of R_2). Furthermore, the ground truth data generating process is given by the parametric form
202 $p_{\mathcal{D}}(X_o, X_u, R) = \tilde{p}_{\tau^*,\gamma^*}(X_o, X_u, R)$, where $\Xi = \Xi_\tau \times \Xi_\gamma$ denotes its parameter space.

203 Then, for such ground truth data generating process, we can show that we can always find a model in
204 the form of Equation 3, such that there exists some mapping Φ, that can model their relationship:

205 **Lemma 1.** *Suppose the ground truth data generating process $\tilde{p}_{\tau^*,\gamma^*}(X_o, X_u, R)$ satisfies **setting***
206 ***D2**. Then, there exists a model $p_{\theta,\lambda}(X_o, X_u, R)$, such that: 1), $p_{\theta,\lambda}(X_o, X_u, R)$ can be written*
207 *in the form of Equation 3 (i.e., **Assumption A1**; and 2), there exists a mapping Φ as described in*
208 *Proposition 2, such that $\tilde{p}_{\tau,\gamma}(X_o, R) = p_{\Phi^{-1}(\tau,\gamma)}(X_o, R)$, for all $(\tau, \gamma) \in \Xi$.*

Model identification under data-model mismatch. Since we showed the identifiability can be preserved under the parameter space mapping (Proposition 2), next we will prove that if the model $p_{\theta,\lambda}(X_o, X_u, R)$ is trained on partially observed data points sampled from $\tilde{p}_{\tau,\lambda}(X_o, X_u, R)$ that satisfies **data setting D2**, then the ML solution is still unbiased. For this purpose, inspired by Lemma 1, we work with the following additional assumption:

Model Assumption A4 Let $\tilde{p}_{\tau^*, \gamma^*}(X_o, X_u, R)$ denote our ground truth data generating process that satisfies **data setting D2**. Then, we assume our model $p_{\theta,\lambda}(X_o, X_u, R)$ is the one that satisfies the description given by Lemma 1. That is, its parametric form is given by Equation 3, and there exists a mapping Φ as described in Proposition 2, such that $\tilde{p}_{\tau,\gamma}(X_o, R) = p_{\Phi^{-1}(\tau,\gamma)}(X_o, R)$.

Then, we have the following proposition:

Proposition 3 (Sufficient conditions for identifiability under MNAR and data-model mismatch)**.** *Let $p_{\theta,\lambda}(X_o, X_u, R)$ be a model on the observable variables X and missing pattern R, and $p_{\mathcal{D}}(X_o, X_u, R)$ be the ground truth distribution. Assume that they satisfies **Data setting D2**, **Assumption A2, A3,** and **A4**. Let $\Theta = \arg\max_{(\theta,\lambda) \in \underline{\Omega}} \mathrm{E}_{(x_o,r) \sim p_{\mathcal{D}}(X_o,R)} \log p_{(\theta,\lambda)}(X_o = x_o, R = r)$ be the set of ML solutions of Equation 1. Then, we have $\Theta = \{\Phi_\tau^{-1}(\tau^*)\} \times \Theta_\lambda$. Namely, the ground truth model parameter τ^* of $p_{\mathcal{D}}$ can be uniquely identified (as $\Phi(\theta^*)$) via ML learning.*

Remark: practical implications Proposition 3 allows us to deal with the cases where the parameterization of ground truth data generating process and model distribution are related through a set of mappings, $\{\Phi_o\}$. In general, the graphical structure of $p_{\mathcal{D}}(X_o, X_u, R)$ can be any cases in Figure 1 excluding (j). Then, in those cases, we are still able to use a model that corresponds to Equation 3 (Fig 1 (h)) to perform ML learning, provided that our model is flexible enough (**Assumption A4**). This greatly improves the applicability of our identifiability results, and we can build a practical algorithm based on Equation 3 to handle many practical MNAR cases.

4 GINA: A Practical Imputation Algorithm for MNAR

In Section 3, we only focused on the general model form. In this section, utilizing the results above, we propose GINA, a deep generative imputation model for MNAR data (Figure 2). GINA fulfill identifiability assumptions above, and can handle general MNAR case as discussed in section 3.2.

The parametric form of GINA We use utilize the flexibility of deep generative models to model the data generating process. We assume that the reference model $p_\theta(X)$ is parameterized by an identifiable VAE [14] to satisfy Assumption A2. That is, $p_\theta(X|U) = \int_Z dZ p_\epsilon(X - f(Z))p(Z|U)$, where U is some fully observed auxiliary inputs. The decoder $p_\epsilon(X - f_\theta(Z))$ is parameterized by a neural network, $f : \mathbb{R}^H \mapsto \mathbb{R}^D$. For convenience, we will drop the input U to $p_\theta(X|U)$, and simply use $p_\theta(X)$ to denote $p_\theta(X|U)$. Finally, for the missing model $p_\lambda(R|X, Z)$, we use a Bernoulli likelihood model, $p_\lambda(R|X, Z) := \prod_d \pi_d(X, Z)^{R_d}(1 - \pi_d(X, Z))^{1-R_d}$, where $\pi_d(X, Z)$ is parameterized by a neural network.

Figure 2: Graphical representations of our GINA.

In Appendix G, we show that GINA fulfill the required assumptions of Proposition 1 and 3. Thus, we can use GINA to identify the ground truth data generating process, and perform missing value imputation under MNAR.

Learning and imputation In practice, the joint likelihood in Equation 1 is intractable. Similar to the approach proposed in [10], we introduce a variational inference network, $q_\phi(Z|X_o)$, which enable us to derive a importance weighted lower bound of $\log p_{\theta,\lambda}(X_o, R)$:

$$\log p_{\theta,\lambda}(X_o, R) \geq \mathcal{L}_K(\theta, \lambda, \phi, X_o, R) := \mathbf{E}_{z^1,\ldots,z^K, x_u^1,\ldots,x_u^K \sim p_\theta(X_u|Z)q_\phi(Z|X_o)} \log \frac{1}{K} \sum_k w_k$$

where $w_k = \frac{p_\lambda(R|X_o, X_u = x_u^k, Z = z^k)p_\theta(X_o, Z = z^k)}{q_\phi(Z = z^k|X_o)}$ is the importance weights. Note that we did not notate the missing pattern R as additional input to q_ϕ, as this information is already contained in X_o. Then, we can optimize the parameters θ, λ, ϕ by solving the following optimization problem

$$\theta^*, \lambda^*, \phi^* = \arg\max_{\theta,\lambda,\phi} \mathbb{E}_{(x_o,r) \sim p_{\mathcal{D}}(X_o,R)} \mathcal{L}_K(\theta, \lambda, \phi, X_o = x_o, R = r)$$

Given $\theta^*, \lambda^*, \phi^*$, we can impute missing data by solving the approximate inference problem:

$$p_\theta(X_u|X_o) = \int_Z p_\theta(X_u|Z)p_\theta(Z|X_o)dZ \approx \int_Z p_\theta(X_u|Z)q_\phi(Z|X_o)dZ.$$

5 Related works

We mainly review recent works for handling MNAR data. In Appendix A, we provide a brief review of traditional methods that deal with MCAR and MAR.

When the missing data is MNAR, a general framework is to learn a joint model on both observable variables and missing patterns [20], in which a model of missing data is usually assumed [47, 9]. This approach is also widely adopted in imputation tasks. For example, in the field of recommender systems, different probabilistic models are used within such a framework [6, 26, 53, 19, 18]. A similar approach has also been taken in the context of causal approach to imputation [55, 54, 17]. Similar to the use of the missing model, they have used an explicit model of exposure and adopted a causal view, where MNAR is treated as a confounding bias. Apart from these, inverse probability weighting methods are also used to debias the effect of MNAR [43, 53, 25] for imputation.

One issue that is often ignored by many MNAR methods is the model identifiability. Identifiability under MNAR has been discussed for certain cases ([30, 29, 31, 52, 50, 48]). For example, [52] proposed the instrumental variable approach to help the identification of MNAR data. [29] investigated the identifiability of normal and normal mixture models, and showed that identifiability for parametric models is highly non-trivial under MNAR. [30] studied conditions for nonparametric identification using shadow variable technique. Despite the resemblance to the auxiliary variable in our approach, [29, 30] mainly considers the supervised learning (multivariate regression) scenario. [34, 33, 45] also discussed a similar topic based on a graphical and causal approach in a non-parametric setting. Although the notion of recoverability has been extensively discussed, their methods do not directly lead to practical imputation algorithms in a scalable setting. On the contrary, our work takes a different approach, in which we handle MNAR with a parametric setting, by dealing with learning and inference in latent variable models. We step aside from the computational burden with the help of recent advances in deep generative models for scalable imputation.

There has been a growing interest in applying deep generative models to missing data imputation. In [24, 21, 36], scalable methods for training VAEs under MAR have been proposed. Similar methods have also been advocated in the context of importance weighted VAEs, multiple imputation [28], and heterogeneous tabular data imputation [36, 22, 23]. Generative adversarial networks (GANs) have also been applied to MCAR data [58, 16]. More recently, deep generative models under MNAR have been studied [10], where selection modeling [39, 5] has been combined with partial variational inference for training VAEs. However, the model identifiability remains unclear for such an approach, and the posterior distribution of missing data conditioned on observed data might be biased.

6 Experiments

We study the empirical performance of the proposed algorithm of Section 4 with both synthetic data (Section 6.1) and two real-world datasets with music recommendation (Section 6.2) and personalized education (Section 6.3) . The experimental setting details can be found in Appendix B.

6.1 Synthetic MNAR dataset

We first consider 3D synthetic MNAR datasets. We generate three synthetic datasets with nonlinear data generation process (shown in Appendix B.1). For all datasets, X_1, X_2, X_3 are generated via the latent variables, Z_1, Z_2, Z_3 ,where X_1 are fully observed and X_2 and X_3 are MNAR. For dataset A, we apply *self-masking*(similar to Figure 1(c)): X_i will be missing if $X_i > 0$. For datasets B and C, we apply *latent-dependent self-masking*: X_i will be missing, if $g(X_i, Z_1, Z_2, Z_3) > 0$, where g is a linear mapping whose coefficients are randomly chosen.

We train GINA and baseline models with partially observed data. Then, we use the trained models to generate random samples. By comparing the generated samples with the ground truth data density, we can evaluate whether $p_\mathcal{D}(X)$ is correctly identified. Results are visualized in Figure 3. In addition,

Figure 3: Visualization of generated X_2 and X_3 from synthetic experiment. **Row-wise (A-C)** plots for dataset A, B, and C, respectively; **Column-wise (i-iv):** training set (only displays fully observed samples), PVAE samples, Not-MIWAE samples, and GINA samples, respectively. **Contour plot**: kernel density estimate of ground truth density of complete data;

we show the imputation results in Appendix I. Across three datasets, PVAE performs poorly, as it does not account for the MNAR mechanism. Not-MIWAE performs better than PVAE, as it is able to generate samples that are closer to the mode. However, it is still biased more towards the observed values. On the other hand, GINA is much more aligned to ground truth, and is able to recover the ground truth from partially observed data. This experiment showed the clear advantage of our method under different MNAR situations.

6.2 Recommender dataset imputation with random test set

Method	Test MSE
Matrix Factorization Methods	
PMF	1.401
IPW-PMF	1.375
Deconfounded-PMF	1.329
PMF-MNAR	1.483
PMF-MAR	1.480
VAE-based models	
PVAE	1.259±0.003
PVAE w/o IW	1.261±0.004
Not-MIWAE	1.078±0.000
GINA	**1.052±0.002**
Others	
CPTv-MNAR	1.056
Logitvd-MNAR	1.141
AutoRec	1.199
Oracle-test	1.057

Table 1: Test MSE on Yahoo! R3

Next, we apply our models to recommendation systems on Yahoo! R3 dataset [26, 55] for user-song ratings which is designed to evaluate MNAR imputation. It contains an MNAR training set of more than 300K self-selected ratings from 15,400 users on 1,000 songs, and an MCAR test set of randomly selected ratings from 5,400 users on 10 random songs. We train all models on the MNAR training set, and evaluate on MCAR test set. This is repeated 10 times with different random seeds. Both the missing model for GINA ($p(R|X, Z)$) and Not-MIWAE ($p(R|X)$) are parameterized by linear neural nets with Bernoulli likelihood functions. The decoders for GINA, PVAE, and Not-MIWAE uses Gaussian likelihoods with the same network structure. See Appendix B for implementation details and network structures.

We compare to the following baselines: 1), probabilistic matrix factorization (PMF) [32]; 2), inverse probability weighted PMF [43]; 3), Deconfounded PMF [55]; 4), PMF with MNAR/MAR data [6]; 5), CPTv and Logitv models for MNAR rating [26]; 6), Oracle [6]: predicts ratings based on their marginal distribution in the test set; and 7) AutoRec [44]: Autoencoders that ignores missing data.

Results are shown in Table 1. Our method (GINA) gives the best performance among all methods. Also, VAE-based methods are consistently better than PMF-based methods, and MNAR-based models consistently outperform their MAR versions. More importantly, among VAE-based models, our

GINA outperforms its non-identifiable counterpart (Not-MIWAE), and MAR counterpart (PVAE), where both models can not generate unbiased imputation.

6.3 Missing data imputation and active question selection on Eedi education dataset

Finally, we apply our methods to the Eedi education dataset [56], one of the largest real-world education response datasets. We consider the Eedi competition task 3 dataset, which contains over 1 million responses from 4918 students to 948 multiple-choice diagnostic questions. Each diagnostic question is a multiple-choice question. We consider predicting whether a student answers a question correctly or not. Over 70% of the entries are missing. The dataset also contains student metadata which we use as the auxiliary variables. In this experiment, we randomly split the data in a 90% train/ 10% test/ 10% validation ratio, and train our models on the response outcome data.

We evaluate our model on two tasks. Firstly, we perform missing data imputation, where different methods perform imputation over the test set. As opposed to Yahoo! R3 dataset, now the test set is MNAR, thus we use the evaluation method suggested by [55], where we evaluate the average per-question MSE For each question, over all students with non-empty response. Then, the MSEs of all questions averaged. We call this metric the debiased MSE. While regular MSE might be biased toward questions with more responses, the debiased MSE treats all questions equally, and can avoid selection bias to a certain degree. We report results for 10 repeats in the first column in Table 2. We can see that our proposed GINA achieves significantly improved results comparing to the baselines.

Secondly, we evaluate personalized education through active question selection [24] on the test set which is task 4 from this competition dataset. The procedure is as follows: for each student in the test set, at each step, the trained generative models are used to decide which is the most informative missing question to collect next. This is done by maximizing the information reward as in [24] (see Appendix H for details).Since at each step, different students might collect different questions, there isn't a simple way to debias the predictive MSE as in the imputation task. Alternatively, we evaluate each method with the help of *question meta data* (difficulty level, which is a scalar).Intuitively, when the student response to the previously collected question is correct, we expect the next diagnostic question which has higher difficulty levels, and vice versa.Thus, we can evaluate the mean level change after correct/incorrect responses, and expect them to have significant differences. We also perform t-test between the level changes after incorrect/correct responses and report the p-value. We

Table 2: Performance on Eedi education dataset (with standard errors)

Method	Debiased MSE	Level change (correct)	Level change (incorrect)	p-value
PVAE	0.194±0.001	0.131±0.138	-0.101±0.160	0.514
Not-MIWAE	0.192±0.000	0.062±0.142	-0.073±0.179	0.561
GINA	**0.188±0.001**	**0.945±0.151**	**-0.353±0.189**	$\mathbf{1.01 \times 10^{-7}}$

can see in Table 2, GINA is the only method that reports a significant p-value (<0.05) between the level changes of next collected questions after incorrect/correct responses which are desired. This further indicates that our proposed GINA predicts the unobserved answer with the desired behavior.

7 Conclusion

In this paper, we provide a analysis of identifiability for generative models under MNAR, and studies sufficient conditions of identifiability under different scenarios. We provide sufficient conditions under which the model parameters can be uniquely identified, via joint maximum likelihood learning on X_o and R. Therefore, the learned model can be used to perform unbiased missing data imputation. We proposed a practical algorithm based on VAEs, which enables us to apply flexible generative models that is able to handle missing data in a principled way. The main limitation of our proposed pracitical algorithm is the need for auxiliary variables (meta feature) which is inherited from identifiable VAE models [14]. In practice, they may not be always available. For future work, we will investigate how to address such limitation, and how to extend to more complicated scenarios.

References

[1] Paul D Allison. *Missing data*. Sage publications, 2001.

[2] James L Arbuckle, George A Marcoulides, and Randall E Schumacker. Full information estimation in the presence of incomplete data. *Advanced structural equation modeling: Issues and techniques*, 243:277, 1996.

[3] Arthur P Dempster, Nan M Laird, and Donald B Rubin. Maximum likelihood from incomplete data via the em algorithm. *Journal of the Royal Statistical Society: Series B (Methodological)*, 39(1):1–22, 1977.

[4] Craig K Enders and Deborah L Bandalos. The relative performance of full information maximum likelihood estimation for missing data in structural equation models. *Structural equation modeling*, 8(3):430–457, 2001.

[5] James J Heckman. Sample selection bias as a specification error. *Econometrica: Journal of the econometric society*, pages 153–161, 1979.

[6] José Miguel Hernández-Lobato, Neil Houlsby, and Zoubin Ghahramani. Probabilistic matrix factorization with non-random missing data. In *International Conference on Machine Learning*, pages 1512–1520. PMLR, 2014.

[7] Nicholas J Horton and Stuart R Lipsitz. Multiple imputation in practice: comparison of software packages for regression models with missing variables. *The American Statistician*, 55(3):244–254, 2001.

[8] Daniel G Horvitz and Donovan J Thompson. A generalization of sampling without replacement from a finite universe. *Journal of the American statistical Association*, 47(260):663–685, 1952.

[9] Joseph G Ibrahim, Stuart R Lipsitz, and M-H Chen. Missing covariates in generalized linear models when the missing data mechanism is non-ignorable. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 61(1):173–190, 1999.

[10] Niels Bruun Ipsen, Pierre-Alexandre Mattei, and Jes Frellsen. not-miwae: Deep generative modelling with missing not at random data. *arXiv preprint arXiv:2006.12871*, 2020.

[11] Janus Christian Jakobsen, Christian Gluud, Jørn Wetterslev, and Per Winkel. When and how should multiple imputation be used for handling missing data in randomised clinical trials–a practical guide with flowcharts. *BMC medical research methodology*, 17(1):1–10, 2017.

[12] Dietmar Jannach, Markus Zanker, Alexander Felfernig, and Gerhard Friedrich. *Recommender systems: an introduction*. Cambridge University Press, 2010.

[13] Phimmarin Keerin, Werasak Kurutach, and Tossapon Boongoen. Cluster-based knn missing value imputation for dna microarray data. In *2012 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, pages 445–450. IEEE, 2012.

[14] Ilyes Khemakhem, Diederik Kingma, Ricardo Monti, and Aapo Hyvarinen. Variational autoencoders and nonlinear ica: A unifying framework. In *International Conference on Artificial Intelligence and Statistics*, pages 2207–2217. PMLR, 2020.

[15] Daphne Koller and Nir Friedman. *Probabilistic graphical models: principles and techniques*. MIT press, 2009.

[16] Steven Cheng-Xian Li, Bo Jiang, and Benjamin Marlin. Misgan: Learning from incomplete data with generative adversarial networks. *arXiv preprint arXiv:1902.09599*, 2019.

[17] Dawen Liang, Laurent Charlin, and David M Blei. Causal inference for recommendation.

[18] Dawen Liang, Laurent Charlin, James McInerney, and David M Blei. Modeling user exposure in recommendation. In *Proceedings of the 25th international conference on World Wide Web*, pages 951–961, 2016.

[19] Guang Ling, Haiqin Yang, Michael R Lyu, and Irwin King. Response aware model-based collaborative filtering. *arXiv preprint arXiv:1210.4869*, 2012.

[20] Roderick JA Little and Donald B Rubin. *Statistical analysis with missing data*, volume 793. John Wiley & Sons, 2019.

[21] Chao Ma, Wenbo Gong, José Miguel Hernández-Lobato, Noam Koenigstein, Sebastian Nowozin, and Cheng Zhang. Partial vae for hybrid recommender system.

[22] Chao Ma, Sebastian Tschiatschek, José Miguel Hernández-Lobato, Richard Turner, and Cheng Zhang. Vaem: a deep generative model for heterogeneous mixed type data. *arXiv preprint arXiv:2006.11941*, 2020.

[23] Chao Ma, Sebastian Tschiatschek, Yingzhen Li, Richard Turner, Jose Miguel Hernandez-Lobato, and Cheng Zhang. Hm-vaes: a deep generative model for real-valued data with heterogeneous marginals. In *Symposium on Advances in Approximate Bayesian Inference*, pages 1–8. PMLR, 2020.

[24] Chao Ma, Sebastian Tschiatschek, Konstantina Palla, José Miguel Hernández-Lobato, Sebastian Nowozin, and Cheng Zhang. Eddi: Efficient dynamic discovery of high-value information with partial vae. *arXiv preprint arXiv:1809.11142*, 2018.

[25] Wei Ma and George H Chen. Missing not at random in matrix completion: The effectiveness of estimating missingness probabilities under a low nuclear norm assumption. *arXiv preprint arXiv:1910.12774*, 2019.

[26] Benjamin M Marlin and Richard S Zemel. Collaborative prediction and ranking with non-random missing data. In *Proceedings of the third ACM conference on Recommender systems*, pages 5–12, 2009.

[27] Herbert W Marsh. Pairwise deletion for missing data in structural equation models: Nonpositive definite matrices, parameter estimates, goodness of fit, and adjusted sample sizes. *Structural Equation Modeling: A Multidisciplinary Journal*, 5(1):22–36, 1998.

[28] Pierre-Alexandre Mattei and Jes Frellsen. Miwae: Deep generative modelling and imputation of incomplete data sets. In *International Conference on Machine Learning*, pages 4413–4423. PMLR, 2019.

[29] Wang Miao, Peng Ding, and Zhi Geng. Identifiability of normal and normal mixture models with nonignorable missing data. *Journal of the American Statistical Association*, 111(516):1673–1683, 2016.

[30] Wang Miao, Lan Liu, Eric Tchetgen Tchetgen, and Zhi Geng. Identification, doubly robust estimation, and semiparametric efficiency theory of nonignorable missing data with a shadow variable. *arXiv preprint arXiv:1509.02556*, 2015.

[31] Wang Miao and Eric Tchetgen Tchetgen. Identification and inference with nonignorable missing covariate data. *Statistica Sinica*, 28(4):2049, 2018.

[32] Andriy Mnih and Russ R Salakhutdinov. Probabilistic matrix factorization. *Advances in neural information processing systems*, 20:1257–1264, 2007.

[33] Karthika Mohan and Judea Pearl. Graphical models for recovering probabilistic and causal queries from missing data. Technical report, CALIFORNIA UNIV LOS ANGELES COGNITIVE SYSTEMS LAB, 2014.

[34] Karthika Mohan, Judea Pearl, and Jin Tian. Graphical models for inference with missing data. *Advances in neural information processing systems*, 26:1277–1285, 2013.

[35] Jared S Murray et al. Multiple imputation: a review of practical and theoretical findings. *Statistical Science*, 33(2):142–159, 2018.

[36] Alfredo Nazabal, Pablo M Olmos, Zoubin Ghahramani, and Isabel Valera. Handling incomplete heterogeneous data using vaes. *Pattern Recognition*, 107:107501, 2020.

[37] James M Robins, Andrea Rotnitzky, and Lue Ping Zhao. Estimation of regression coefficients when some regressors are not always observed. *Journal of the American statistical Association*, 89(427):846–866, 1994.

[38] Thomas J Rothenberg. Identification in parametric models. *Econometrica: Journal of the Econometric Society*, pages 577–591, 1971.

[39] Donald B Rubin. Inference and missing data. *Biometrika*, 63(3):581–592, 1976.

[40] Donald B Rubin. Formalizing subjective notions about the effect of nonrespondents in sample surveys. *Journal of the American Statistical Association*, 72(359):538–543, 1977.

[41] Donald B Rubin. An overview of multiple imputation. In *Proceedings of the survey research methods section of the American statistical association*, pages 79–84. Citeseer, 1988.

[42] Donald B Rubin. *Multiple imputation for nonresponse in surveys*, volume 81. John Wiley & Sons, 2004.

[43] Tobias Schnabel, Adith Swaminathan, Ashudeep Singh, Navin Chandak, and Thorsten Joachims. Recommendations as treatments: Debiasing learning and evaluation. *arXiv preprint arXiv:1602.05352*, 2016.

[44] Suvash Sedhain, Aditya Krishna Menon, Scott Sanner, and Lexing Xie. Autorec: Autoencoders meet collaborative filtering. In *Proceedings of the 24th international conference on World Wide Web*, pages 111–112, 2015.

[45] Ilya Shpitser, Karthika Mohan, and Judea Pearl. Missing data as a causal and probabilistic problem. Technical report, CALIFORNIA UNIV LOS ANGELES DEPT OF COMPUTER SCIENCE, 2015.

[46] Fiona M Shrive, Heather Stuart, Hude Quan, and William A Ghali. Dealing with missing data in a multi-question depression scale: a comparison of imputation methods. *BMC medical research methodology*, 6(1):1–10, 2006.

[47] Aude Sportisse, Claire Boyer, and Julie Josse. Imputation and low-rank estimation with missing not at random data. *Statistics and Computing*, 30(6):1629–1643, 2020.

[48] Aude Sportisse, Claire Boyer, and Julie Josses. Estimation and imputation in probabilistic principal component analysis with missing not at random data. *Advances in Neural Information Processing Systems*, 33, 2020.

[49] Daniel J Stekhoven and Peter Bühlmann. Missforest—non-parametric missing value imputation for mixed-type data. *Bioinformatics*, 28(1):112–118, 2012.

[50] Gong Tang, Roderick JA Little, and Trivellore E Raghunathan. Analysis of multivariate missing data with nonignorable nonresponse. *Biometrika*, 90(4):747–764, 2003.

[51] Ruibo Tu, Cheng Zhang, Paul Ackermann, Karthika Mohan, Hedvig Kjellström, and Kun Zhang. Causal discovery in the presence of missing data. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pages 1762–1770. PMLR, 2019.

[52] Sheng Wang, Jun Shao, and Jae Kwang Kim. An instrumental variable approach for identification and estimation with nonignorable nonresponse. *Statistica Sinica*, pages 1097–1116, 2014.

[53] Xiaojie Wang, Rui Zhang, Yu Sun, and Jianzhong Qi. Doubly robust joint learning for recommendation on data missing not at random. In *International Conference on Machine Learning*, pages 6638–6647. PMLR, 2019.

[54] Yixin Wang and David M. Blei. The blessings of multiple causes, 2019.

[55] Yixin Wang, Dawen Liang, Laurent Charlin, and David M Blei. The deconfounded recommender: A causal inference approach to recommendation. *arXiv preprint arXiv:1808.06581*, 2018.

[56] Zichao Wang, Angus Lamb, Evgeny Saveliev, Pashmina Cameron, Yordan Zaykov, José Miguel Hernández-Lobato, Richard E Turner, Richard G Baraniuk, Craig Barton, Simon Peyton Jones, Simon Woodhead, and Cheng Zhang. Diagnostic questions: The neurips 2020 education challenge. *arXiv preprint arXiv:2007.12061*, 2020.

[57] Ian R White, Patrick Royston, and Angela M Wood. Multiple imputation using chained equations: issues and guidance for practice. *Statistics in medicine*, 30(4):377–399, 2011.

[58] Jinsung Yoon, James Jordon, and Mihaela Schaar. Gain: Missing data imputation using generative adversarial nets. In *International Conference on Machine Learning*, pages 5689–5698. PMLR, 2018.