Relational Linearity is a Predictor of Hallucinations

Abstract

Hallucination is a central failure mode of language models (LMs). We focus on hallucinations in response to questions like: "Which instrument did Glenn Gould play?", but we ask these questions for synthetic entities designed to be unknown to the model. We find that LMs like Gemma-7B-IT frequently hallucinate, i.e., they have difficulty recognizing that the hallucinated fact is not part of their knowledge. Based on the idea of linear relational embeddings (Paccanaro and Hinton, 2001; Hernandez et al., 2024), we put forward the following hypothesis. (i) Due to the abstract scheme that is used to represent them, LMs can easily produce plausible objects for non-existing subjects of linear relations, which can lead to hallucinations. (ii) For a nonlinear relation, this mechanism for producing an object is not available and so a hallucination is easier to avoid. To test this hypothesis, we create SyntHal, a synthetic unknown-entity benchmark for 15 relations. We find that across four instruction-tuned models, relational linearity is a strong predictor of models hallucinating an object for an unknown subject vs refusing to give an answer, with correlations $r \in [.58, .84]$.

1 Introduction

When asked for factual attributes about an entity (or subject), language models (LMs) can *hallucinate*, i.e., give an answer that is unsupported or fabricated. Minimizing hallucinations is central to reliability in modern instruction-following systems trained with human feedback (Ouyang et al., 2022). Hallucinations about factual attributes are avoided if the language model recognizes that it does not know the answer (Kadavath et al., 2022) and generates a refusal. There is evidence that mechanisms for detecting non-knowledge are responsible for many refusals (Lindsey et al., 2025; Ferrando et al., 2025). Non-knowledge of the subject should trigger refusal. However, we show that synthetic subjects designed to be unknown under our generation scheme often result in hallucinations, i.e., the LM fails to realize its lack of knowledge.

We hypothesize that an important factor in determining whether the LM hallucinates or refuses in this scenario is the nature of the relation between subject and object. Hernandez et al. (2024) find that some relations are well approximated by a linear or affine map from subject to object representations. Our hypothesis is that such accessible relation-level structure can make it easier for the model to generate a plausible value even when the specific triple (or evidence) is unknown, which may make knowledge gaps harder to detect and increase hallucinations. Conversely, when an affine map fits the relation poorly, answering may rely more on instance-specific information, which may make abstention/refusal more likely when knowledge is absent.

We use two datasets to investigate this hypothesis. First, we create SyntHal, a 15-relation synthetic benchmark designed to instantiate knowledge gaps: the intended behavior is refusal, and any committed value counts as hallucination. We show that relation linearity is a strong predictor of hallucination tendency in this setting: more linear relations are more likely to elicit hallucinated answers, whereas less linear relations are more likely to elicit refusals. Second, on natural relation triples from Hernandez et al. (2024), we find that hallucinated values are more often plausible fillers of the expected relation role, which matches our expectation that the mechanism underlying linear relations gives rise to plausible generations.

Our contributions are as follows. (i) We hypothesize a new mechanism for a subclass of hallucinations, objects of linear relations in cases the LM does not know the answer. Due to the abstract scheme that is used to represent linear relations, the LM can easily produce an object, which can then lead to a hallucination. (ii) To test this hypoth-

Dataset	Relation	Linearity	Subject	Question	Hallucinated value
SyntHal	Company CEO	0.62	Dalete Systems	Who is the CEO of Dalete Systems?	Golan Vekstein
LRE	Person father	0.69	Yehudi Menuhin	Who is Yehudi Menuhin's father?	Salomon Menuhin
LRE	Product maker	0.92	iISO flash shoe	Which company developed iISO flash shoe?	Nike
SyntHal	Star constellation	0.92	Bolo-03459	What is the name of the constellation that Bolo-03459 is part of?	Scorpius
SyntHal	Landmark country	0.94	Tedoso Hall	What country is Tedoso Hall in?	United States

Table 1: Three SyntHal and two LRE prompts with hallucinated values from model outputs. For SyntHal, the intended behavior for synthetic subjects is refusal – the shown committed values are counted as hallucinations.

esis, we introduce SyntHal, a synthetic unknown-entity benchmark for 15 relations. (iii) We find that across four instruction-tuned models, $\Delta \cos$ (a measure of relational linearity) is a strong predictor of models hallucinating an object for an unknown subject, with correlations $r \in [.58, .84]$. (iv) On natural triples, higher $\Delta \cos$ correctly predicts a higher rate of hallucinated values that are plausible relation fillers.[1]

2 Experimental Setup

This section describes our experimental setup: models, dataset SyntHal and LLM-as-a-judge.

2.1 Models

We study four instruction-tuned LMs: Gemma-7B-IT (Team et al., 2024), Llama-3.1-8B-Instruct (Dubey et al., 2024), Mistral-7B-Instruct-v0.3 (Jiang et al., 2023), and Qwen2.5-7B-Instruct (Qwen et al., 2025). Inputs are rendered with each model's official chat template and the system prompt You are a helpful assistant. Answer with a single short phrase. For templates without a system role, we prepend this instruction to the user message. We use greedy decoding (temperature=0, max_new_tokens=64). See Appendix A for model variants and larger models.

2.2 Synthetic benchmark SyntHal

We start with LRE, Hernandez et al. (2024)'s dataset. We use the 15 factual relations from LRE with more than 10 triples in the test set under a 75:25 split, but we exclude two relations for which we had difficulty generating plausible synthetic subjects. See Appendix B. To create SyntHal, we sample $N{=}200$ prompts per relation. Table 1 shows examples; the full relation inventory and templates are given in Appendix B.

Because the synthetic setting is intended to instantiate knowledge gaps, any response that commits to a specific value is a hallu-cination, while non-committal answers are re-fusals. We therefore measure hallucination rate as Hallucination/(Hallucination + Refusal).[2]

Following recent work (e.g., (Zheng et al., 2023; Liu et al., 2023)), we adopt LLM-as-a-judge, using gemini-2.5-flash (Comanici et al., 2025). The judge is asked to provide (i) a label (refusal or hallucination), (ii) a confidence $\in [0, 1]$ and (iii) a rationale for the decision. We force a binary choice and rerun the judge if it does not respond with a correct label. This always produced one of the two labels in our experiments. See Appendix D for the prompt.

A manual check of 200 random responses matched Gemini's labels in all cases; additional stratified validation for the labels is reported in Appendix D.

2.3 LRE benchmark

We also investigate natural relation triples from Hernandez et al. (2024), where entities are real and may have been observed during pretraining. We therefore use a 3-way LLM-as-a-judge with labels CORRECT, HALLUCINATION, and REFUSAL. The judge evaluates on LRE gold labels; e.g., if the LM answers a sports-position question with "linebacker", then that is labeled CORRECT if it is the LRE answer and HALLUCINATION otherwise. See Appendix D for the prompt.

3 Measuring Relational Linearity

We now describe how we compute relation-linearity scores for LRE relations (§2.3). We again use our 75:25 split. For each model and each triple, we extract the representation $\mathbf{s}_i$ of the subject and the representation $\mathbf{o}_i$ of the object (see Appendix G for details). We denote the training pairs by T and the held-out evaluation pairs by E.

On T, we fit a relation-specific affine map

$$\hat{\mathbf{o}} = W_r \mathbf{s} + \mathbf{b}_r$$

---

[1] We will make our code and datasets publicly available.

[2] See Appendix B for a subject-level collision audit against Wikipedia/Wikidata and additional analysis.

Figure 1: Results on SyntHal. Each point is one relation; panels are models. Higher $\Delta \cos$ is associated with higher hallucination rate.

Figure 2: Results on LRE. Each point is one relation; panels are models. Higher $\Delta \cos$ is associated with a higher rate of plausible hallucinations.

from subject representations to object representations. The map is estimated by ridge regression:

$$(W_r, \mathbf{b}_r) = \arg\min_{W, \mathbf{b}} \mathcal{J}_r(W, \mathbf{b}),$$

$$\mathcal{J}_r(W, \mathbf{b}) = \sum_{i \in T} \|\mathbf{o}_i - (W\mathbf{s}_i + \mathbf{b})\|_2^2 \quad (1)$$
$$+ \lambda \|W\|_F^2.$$

We use ridge regression rather than Hernandez et al. (2024)'s Jacobian-based estimator. In initial experiments, ridge regression provided more stable linearity scores across models than the Jacobian. We use $\lambda = 1$ and an unregularized intercept. For each held-out pair $j \in E$, we compute

$$\hat{\mathbf{o}}_j = W_r \mathbf{s}_j + \mathbf{b}_r.$$

Our measure of relation linearity is the held-out cosine improvement:

$$\Delta \cos = \mathbb{E}_{j \in E}[\cos(\hat{\mathbf{o}}_j, \mathbf{o}_j) - \cos(\mathbf{s}_j, \mathbf{o}_j)]. \quad (2)$$

Following LRE-style held-out evaluations in prior work, $\Delta \cos$ measures the gain in directional alignment with the correct object representation after applying the affine map, relative to the baseline subject-object cosine. Intuitively, a large $\Delta \cos$ indicates that a relation's affine map generalizes across held-out subject-object pairs.

4 Results

4.1 SyntHal

Figure 1 shows our main result: on the 15-relation SyntHal set, hallucination rate is positively correlated with relational linearity ($\Delta \cos$)

for all four instruction-tuned models. As described in §2.2, we measure hallucination rate as $\text{Hallucination}/(\text{Hallucination} + \text{Refusal})$; representative judged examples are shown in Figure 3. For all four models, both Pearson and Spearman correlations are significant ($p < 0.05$), with Pearson $r \in [.58, .84]$ and Spearman $\rho \in [.59, .78]$.

As a measure of the held-out cosine improvement, higher $\Delta \cos$ indicates that the affine map generalizes better across held-out pairs (Hernandez et al., 2024). Thus, our results are consistent with the hypothesis outlined in the introduction: When a relation is well captured by shared linear structure, the model may be more prone to producing a plausible value even without evidence (recall that our SyntHal setting corresponds to absence of evidence). Conversely, when $\Delta \cos$ is low, the affine mechanism for producing an object from the subject is not available, and, in the absence of an easily producible object, models may be more likely to abstain.

We investigate possible additional factors (relation heterogeneity, output-space concentration, metric/rendering choices) in Appendices M, L, I.

4.2 LRE

SyntHal was constructed to provide subjects that are unknown to the LM. This allowed us to investigate the impact of relational linearity when a fact is unknown. At the same time, it is also important to investigate the impact of relational linearity on answers the LM gives for known (i.e., non-synthetic) subjects.

To this end, we analyze all hallucinations that

LMs produce on LRE (same setup for LRE as the one used for SyntHal in §4.1). We analyze these hallucinations using a web-search-grounded LLM-as-a-judge. We define the *plausibility rate* as the fraction of hallucinated answers judged to be plausible fillers of the expected relation role; e.g., "France" is a plausible filler for country even if it's the wrong country. Crucially, the prompt specifies that a non-existent entity is not a plausible filler; so "Salomon Menuhin" is not counted as a plausible father of Yehudi Menuhin since there exists no publicly known person of that name.

Figure 2 shows that plausibility rate is positively associated with $\Delta \cos$ for all four models ($r \in [.75, .82]$). Table 1 hints at an explanation. For linear relations, based on the affine transformation, the model can easily locate the part of embedding space where objects like product makers ("Nike"), star constellations ("Scorpius") and countries ("United States") are represented. Even if it gives the wrong answer, it tends to produce an object of the right type from that area. For nonlinear relations, this mechanism is not available; so in many cases it makes up entity names of the wrong type, often inventing non-existing entities ("Golan Vekstein", "Salomon Menuhin"). Thus, linearity predicts not only whether models answer or refuse for unknown subjects, but also the rate of plausible hallucinations (i.e., hallucinations of the right type) for known subjects whose objects are not known. See Appendix F for more details.

Finally, we also look at the relationship between linearity and accuracy for all "answered cases" in LRE, i.e., all cases where the model does not refuse, including both correct answers and hallucinations. We call this answered-case accuracy: $\text{Correct}/(\text{Correct} + \text{Hallucination})$.

We exclude refusals here because we do not know what the reason for a refusal is – unlike in the SyntHal experiment where we did know (a subject that the LM does not know by construction): The LM may refuse to answer because the subject is unknown to the LM; the subject is known, but the triple does not occur in the training data; or the triple occurs in the training data, but was not learned by the LM.

We find that higher $\Delta \cos$ predicts higher accuracy – see Appendix E, Figure 4 – i.e., higher linearity is associated with higher accuracy among non-refusals on LRE. We can speculate that the rich structural representation of linear relations makes them easier to learn (e.g., from fewer occurrences of a triple in the training set) whereas acquiring triples of nonlinear relations is less sample-efficient and so accuracy is lower. We leave investigation of this hypothesis to future work.

5 Related Work

A growing line of work studies whether semantic structure in LM representations can be captured by linearity. The linear representation hypothesis proposes that model representations encode semantic variables in approximately linear ways, and Linear Relational Embeddings operationalize this idea with affine maps over relation triples (Park et al., 2023; Hernandez et al., 2024; Chanin et al., 2024; Christ et al., 2026; Merullo et al., 2025). Separately, hallucination, truthfulness, and refusal have been studied through benchmarks, surveys, and representation-level probes (Lin et al., 2022; Ji et al., 2023; Li et al., 2023; Azaria and Mitchell, 2023; Marks and Tegmark, 2024; Schouten et al., 2025; Peng et al., 2025; Kadavath et al., 2022; Lindsey et al., 2025; Ferrando et al., 2025). We connect these lines by relating relational linearity to hallucination-vs-refusal behavior under controlled knowledge gaps, answered-case value accuracy on natural triples, and the plausibility of hallucinated objects for known subjects.

6 Conclusion

We introduce SyntHal, a synthetic unknown-entity benchmark for probing knowledge-gap hallucinations. Across 15 relations and multiple models, relational linearity is a strong predictor of (i) whether models hallucinate an object for an unknown subject and (ii) whether models hallucinate correct-type (as opposed to incorrect-type) objects for a known subject whose object is unknown.

Practically, relational linearity can be used as a diagnostic for abstention calibration. For highly linear relations, models may need stricter evidence checks before committing to a value; for less linear relations, refusal behavior may already be easier to elicit.

Together, these results suggest a dual role for linear relational structure: it can support accurate value prediction when relevant knowledge is encoded, but can also make models more prone to generating plausible unsupported values under knowledge gaps.

Ethical Considerations

This work studies hallucination behavior using synthetic entities and publicly released natural relation triples from Hernandez et al. (2024); it does not involve collecting private or sensitive user data. The natural relation set includes one bias-labeled relation, but we use its labels only as released dataset labels for measuring agreement with the gold object, not as normative claims. The intended use of SyntHal is diagnostic: identifying relation types for which models may commit to unsupported factual attributes for unknown entities. Because the benchmark is English-oriented and limited to prompts, it should not be treated as a complete safety evaluation or generalized directly to all languages, domains, users, or deployment settings. The released data and scripts are provided for research use; third-party resources, including the LRE triples, Hugging Face model weights, and Gemini API, remain subject to their original licenses and access terms. We used ChatGPT-5.2 (OpenAI, 2025) as a programming and limited writing assistant; all empirical results were produced by our code and verified by the authors.

Limitations

Our findings are correlational at the relation level. We measure relational linearity with a ridge-estimated subject-to-object affine map and summarize held-out fit by $\Delta \cos$. This LRE-inspired score is useful as a uniform predictor, but it is not a causal account of how a model generates answers and is not a reimplementation of the Jacobian-based intervention method of Hernandez et al. (2024). Establishing mechanistic causality would require intervention-based tests such as representation patching or controlled steering.

Several dataset and evaluation choices limit generality. In the natural setting, HALLUCINATION means a committed value that does not match the released gold object; some such cases may be alternative valid or time-dependent values, especially for relations such as occupation or CEO. In SyntHal, synthetic subjects are generated from controlled token pools rather than impossible nonce strings; a collision audit found 2995/3000 clean prompts (Appendix B), but the benchmark still instantiates likely knowledge gaps rather than proving that every string was absent from pretraining. Relation-level behavior may also be partly shaped by output-space priors, since relations differ in the concen-

tration of plausible answers. Our controls suggest that $\Delta \cos$ adds signal beyond simple object-space statistics (Appendix L), but they do not fully disentangle representational accessibility from answer-space priors.

Finally, our behavioral claims are tied to a 15-relation, primarily 7B–8B instruction-tuned setting. Prompt robustness, larger-model checks, relation heterogeneity analyses, human validation of judge labels, and a deterministic regex baseline are reported in Appendices K, A, M, D, and N. The main labels use gemini-2.5-flash (Comanici et al., 2025), so full reruns of judge calls require API access; the artifact instead supports no-API verification of aggregate analyses from released source tables. Absolute refusal and hallucination rates should therefore not be interpreted as unconditional rates across prompts, languages, domains, or model scales.

References

Amos Azaria and Tom Mitchell. 2023. The internal state of an LLM knows when it's lying. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 967–976, Singapore. Association for Computational Linguistics.

David Chanin, Anthony Hunter, and Oana-Maria Camburu. 2024. Identifying linear relational concepts in large language models. In *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 1524–1535, Mexico City, Mexico. Association for Computational Linguistics.

Miranda Anna Christ, Adrián Csiszárik, Gergely Becsó, and Dániel Varga. 2026. The structure of relation decoding linear operators in large language models. In *The Thirty-ninth Annual Conference on Neural Information Processing Systems*.

Gheorghe Comanici, Eric Bieber, Mike Schaekermann, Ice Pasupat, Noveen Sachdeva, Inderjit Dhillon, Marcel Blistein, Ori Ram, Dan Zhang, Evan Rosen, Luke Marris, Sam Petulla, Colin Gaffney, Asaf Aharoni, Nathan Lintz, Tiago Cardal Pais, Henrik Jacobsson, Idan Szpektor, Nan-Jiang Jiang, and 3416 others. 2025. Gemini 2.5: Pushing the frontier with advanced reasoning, multimodality, long context, and next generation agentic capabilities. *Preprint*, arXiv:2507.06261.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, and 1 others. 2024. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*.

Javier Ferrando, Oscar Balcells Obeso, Senthooran Rajamanoharan, and Neel Nanda. 2025. Do i know this entity? knowledge awareness and hallucinations in language models. In *The Thirteenth International Conference on Learning Representations*.

Evan Hernandez, Arnab Sen Sharma, Tal Haklay, Kevin Meng, Martin Wattenberg, Jacob Andreas, Yonatan Belinkov, and David Bau. 2024. Linearity of relation decoding in transformer language models. In *The Twelfth International Conference on Learning Representations*.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM Comput. Surv.*, 55(12).

Albert Q. Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, Lélio Renard Lavaud, Marie-Anne Lachaux, Pierre Stock, Teven Le Scao, Thibaut Lavril, Thomas Wang, Timothée Lacroix, and William El Sayed. 2023. Mistral 7b. *Preprint*, arXiv:2310.06825.

Saurav Kadavath, Tom Conerly, Amanda Askell, Tom Henighan, Dawn Drain, Ethan Perez, Nicholas Schiefer, Zac Hatfield-Dodds, Nova DasSarma, Eli Tran-Johnson, Scott Johnston, Sheer El-Showk, Andy Jones, Nelson Elhage, Tristan Hume, Anna Chen, Yuntao Bai, Sam Bowman, Stanislav Fort, and 17 others. 2022. Language models (mostly) know what they know. *Preprint*, arXiv:2207.05221.

Kenneth Li, Oam Patel, Fernanda Viégas, Hanspeter Pfister, and Martin Wattenberg. 2023. Inference-time intervention: Eliciting truthful answers from a language model. In *Thirty-seventh Conference on Neural Information Processing Systems*.

Stephanie Lin, Jacob Hilton, and Owain Evans. 2022. TruthfulQA: Measuring how models mimic human falsehoods. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 3214–3252, Dublin, Ireland. Association for Computational Linguistics.

Jack Lindsey and 1 others. 2025. On the biology of a large language model. Transformer Circuits Thread. Published March 27, 2025.

Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: NLG evaluation using gpt-4 with better human alignment. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2511–2522, Singapore. Association for Computational Linguistics.

Samuel Marks and Max Tegmark. 2024. The geometry of truth: Emergent linear structure in large language model representations of true/false datasets. In *First Conference on Language Modeling*.

Jack Merullo, Noah A. Smith, Sarah Wiegreffe, and Yanai Elazar. 2025. On linear representations and pretraining data frequency in language models. In *The Thirteenth International Conference on Learning Representations*.

OpenAI. 2025. Introducing gpt-5.2.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. In *Advances in Neural Information Processing Systems*, volume 35, pages 27730–27744. Curran Associates, Inc.

Alberto Paccanaro and Geoffrey E Hinton. 2001. Learning hierarchical structures with linear relational embedding. In *Advances in Neural Information Processing Systems*, volume 14. MIT Press.

Kiho Park, Yo Joong Choe, and Victor Veitch. 2023. The linear representation hypothesis and the geometry of large language models. In *Causal Representation Learning Workshop at NeurIPS 2023*.

Letian Peng, Chenyang An, Shibo Hao, Chengyu Dong, and Jingbo Shang. 2025. Linear correlation in lm's compositional generalization and hallucination. *Preprint*, arXiv:2502.04520.

Qwen, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, and 24 others. 2025. Qwen2.5 technical report. *Preprint*, arXiv:2412.15115.

Stefan F. Schouten, Peter Bloem, Ilia Markov, and Piek Vossen. 2025. Truth-value judgment in language models: 'truth directions' are context sensitive. In *Second Conference on Language Modeling*.

Gemma Team, Thomas Mesnard, Cassidy Hardin, Robert Dadashi, Surya Bhupatiraju, Shreya Pathak, Laurent Sifre, Morgane Rivière, Mihir Sanjay Kale, Juliette Love, Pouya Tafti, Léonard Hussenot, Pier Giuseppe Sessa, Aakanksha Chowdhery, Adam Roberts, Aditya Barua, Alex Botev, Alex Castro-Ros, Ambrose Slone, and 89 others. 2024. Gemma: Open models based on gemini research and technology. *Preprint*, arXiv:2403.08295.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. 2023. Judging LLM-as-a-judge with MT-bench and chatbot arena. In *Thirty-seventh Conference on Neural Information Processing Systems Datasets and Benchmarks Track*.

A Models

Table 2 lists the four instruction-tuned models used in the main experiments. Table 3 reports additional model and model-variant checks under the main $\Delta \cos$ metric.

Model	Reference
Gemma-7B-IT	Team et al. (2024)
Llama-3.1-8B-Instruct	Dubey et al. (2024)
Mistral-7B-Instruct-v0.3	Jiang et al. (2023)
Qwen2.5-7B-Instruct	Qwen et al. (2025)

Table 2: Models used in our main experiments.

Model	Pearson r (p)	Refusal rate
Llama-3.1-8B base	0.809 (2.64×10^{-4})	0.335
Llama-3.1-8B Instruct	0.583 (0.0226)	0.795
Mistral Small 3 (24B) Instruct	0.897 (5.85×10^{-6})	0.359
Mistral-Large-Instruct-2411 (123B)	0.584 (0.0224)	0.321

Table 3: Additional model and model-variant checks on SyntHal. All correlations use the main $\Delta \cos$ metric against $\text{Hallucination}/(\text{Hallucination} + \text{Refusal})$. The Llama-Instruct row is included for comparison with the base model.

B Dataset details: prompt templates and synthetic entity generation

Relation selection. We start from the LRE relation inventory of Hernandez et al. (2024) and use the fixed 75:25 train/test split used throughout the paper. For the main SyntHal benchmark, we retain factual relations with more than 10 held-out triples for which we can generate plausible synthetic subjects without introducing an intended gold object. We exclude two candidate relations from the main synthetic benchmark because their subject-generation requirements are qualitatively different from the other factual relations: pokemon_evolutions, which would require generating Pokemon-like fictional species names, and person_native_language, which would require assigning demographic language attributes to synthetic persons. Both would introduce additional assumptions beyond the controlled unknown-entity setting targeted by SyntHal.

Synthetic relation inventory and templates. Table 4 lists the 15 factual relations in SyntHal and their exact question templates.

Relation	Question template
company_ceo	Who is the CEO of {SUBJECT}?
company_hq	Where are the headquarters of {SUBJECT}?
landmark_in_country	What country is {SUBJECT} in?
landmark_on_continent	What continent is {SUBJECT} on?
person_father	Who is {SUBJECT}'s father?
person_mother	Who is {SUBJECT}'s mother?
person_occupation	What is {SUBJECT} by profession?
person_plays_instrument	What instrument does {SUBJECT} play?
person_plays_position_in _sport	Which position does {SUBJECT} play?
person_plays_pro_sport	What sport does {SUBJECT} play?
person_university	Which university did {SUBJECT} attend?
product_by_company	Which company developed {SUBJECT}?
star_constellation	What is the name of the constellation that {SUBJECT} is part of?
superhero_archnemesis	Who is the superhero archnemesis of {SUBJECT}?
superhero_person	What is {SUBJECT}'s secret identity?

Table 4: Exact question templates for SyntHal.

Synthetic entity generation. For each relation in SyntHal, we generate $N=200$ synthetic subjects using deterministic sampling with fixed random seeds. We enforce uniqueness within each relation by rejecting duplicates until reaching the required number of unique subjects. Each relation is associated with an entity type, such as person, company, landmark, product, star, or superhero. Subjects are then constructed from frozen token pools using an entity-type-specific canonical formatting rule.

Token pools and composition rules. The token pools include first and last names, organization-name components, landmark/product/star/superhero name components, and other relation-specific lexical components. The pools were generated once using OpenAI ChatGPT-5.2 (OpenAI, 2025), manually frozen, and then reused deterministically. We construct subjects using canonical formats such as First Last for persons, prefix/suffix or adjective/noun combinations for organizations and products, and short compositional names for landmarks, stars, and superheroes. All subjects are rendered with a single canonical formatting rule per entity type. We release the resulting SyntHal prompt inventory and the subject-level audit scripts in the artifact.

Subject-level collision audit. A construct-validity concern is that synthetic subjects assembled from common names or token pools could accidentally match real entities. To assess this, we performed a subject-level collision audit on SyntHal (3000 prompts across 15 relations). For each unique synthetic subject, we queried (i) Wikipedia exact title lookup, (ii) quoted Wikipedia search, and (iii) Wikidata entity search over labels/aliases,

and additionally marked very high-similarity candidates as ambiguous. For fuzzy matching, we Unicode-normalize and case-fold strings, remove non-alphanumeric characters, and compute a normalized sequence-similarity ratio. We use a high threshold of 0.93 to flag near-exact spelling or diacritic variants while avoiding loose name overlaps; candidates above this threshold are marked as ambiguous. We classified prompts as *clean*, *ambiguous*, or *matched*.

The audit found 2995/3000 clean prompts (99.83%); only 5 prompts were flagged in total (3 ambiguous, 2 matched), all in superhero_archnemesis and superhero_person. The remaining 13 relations were 200/200 clean. Table 5 lists the flagged prompts.

Relation	Subject	Verdict	Best candidate
superhero_archnemesis	Captain Kasi	ambiguous	Captain Käsig
superhero_archnemesis	Captain Lake	matched	Captain Lake
superhero_person	Captain Kasi	ambiguous	Captain Käsig
superhero_person	Captain Lara	matched	Captain Lara
superhero_person	Captain Sali	ambiguous	Captain Salim

Table 5: Synthetic prompts flagged by the collision audit. All other prompts are classified as clean.

Because only 5 of 3000 prompts are flagged, the relation-level behavior rates used in the main analysis are effectively unchanged by the audit. We therefore keep the full SyntHal evaluation inventory in the main results.

C Reproducibility and artifacts

Our released artifact includes (i) the SyntHal prompt inventory, (ii) source tables for the main plots and relation-level correlation analyses, (iii) derived plausibility-analysis rows and object-space control summaries, and (iv) reference scripts for the main analysis stages. The released source tables contain the relation-level counts, linearity scores, and analysis labels needed to verify the reported aggregate figures and correlations without rerunning model inference or external judge calls.

Full end-to-end reruns of behavior generation, representation extraction, and Gemini-based judging are not self-contained: they require Hugging Face model access, GPU resources, and, for the judge labels, API access. We therefore separate the

Component	Setting
Decoding	greedy; temperature=0; max_new_tokens=64
Behavior prompts	Main: `You are a helpful assistant. Answer with a single short phrase.`; robustness: no system prompt and refusal-friendly prompt
Chat templates	official Hugging Face chat templates
Synthetic inventory	15 relations; $N = 200$ prompts per relation
Synthetic metric	Hallucination/(Hallucination + Refusal)
Natural judge	3-way (CORRECT/HALLUCINATION/REFUSAL); sees gold answer
Natural metric	Correct/(Correct + Hallucination) (answered-case accuracy; refusals excluded)
Natural filters	$n_{\text{test}} > 10$
Randomness	fixed seed $= 0$ for all sampling/shuffling unless otherwise stated

Table 6: Key reproducibility settings and filtering rules.

artifact into a no-API aggregate-verification path from released tables and optional pipeline scripts for users with the necessary compute and credentials.

Key hyperparameters and filters. Table 6 summarizes the core settings needed to reproduce the results.

D LLM-as-a-Judge prompts and validation

We first illustrate the two-class synthetic rubric (REFUSAL vs. HALLUCINATION) with two representative judged examples in Figure 3. We then report human validation of the judge labels (Table 7) and provide the exact Gemini judge prompts used in our experiments.

Example 1 (Refusal).
Q: Who is Emily Brown's father?
A **(Gemma-7B-IT):** Sure, here is the answer: I do not have any information about Emily Brown's father, therefore I cannot answer this question.
Judge (Gemini): REFUSAL, confidence $= 1.0$.

Example 2 (Hallucination).
Q: What is Busu Bobaka by profession?
A **(Mistral Small 3 (24B) Instruct):** Busu Bobaka is a YouTuber.
Judge (Gemini): HALLUCINATION, confidence $= 1.0$.

Figure 3: Two model generations and LLM-as-a-judge annotations. Judge rationale omitted.

Human validation. We validate the external judge in three settings. First, for the synthetic binary setting (HALLUCINATION vs. REFUSAL), we manually annotated a random sample of 200 model responses. The human labels matched the Gemini labels on all 200 examples.

Second, we validate the natural 3-way labels on a stratified sample of 120 examples, balanced across models and covering relations with potentially ambiguous or time-sensitive values. For this

Validation setting	Scored examples	Human–judge agreement	Cohen's κ
Synthetic binary	200	1.000	–
Natural 3-way	120	0.833	0.750
Plausibility, exact A/B/C	120	0.858	0.742
Plausibility, A-vs-other	120	0.867	0.734

Table 7: Human validation of judge labels. The natural 3-way validation uses the released gold object as the reference and treats committed non-gold values as non-gold. For the plausibility validation, annotators used the exact relation-specific rubric shown to the judge. The paper-facing plausibility rate corresponds to the A-vs-other decision.

validation, annotators used the released gold object as the reference and labeled committed non-gold values as *non-gold* rather than requiring definitive real-world falsehood. Human labels agreed with the judge on 83.3% of scored examples, with Cohen's $\kappa = 0.750$.

Third, we validate the plausibility analysis with a separate relation-aware stratified sample of 120 hallucinated non-gold answers. Annotators saw the exact relation-specific rubric for each row and assigned A/B/C labels. Exact-label human-judge agreement was 85.8% with Cohen's $\kappa = 0.742$. Since the paper-facing plausibility rate is the A-vs-other decision, we also compute agreement after collapsing B and C into non-A; this gives 86.7% agreement with Cohen's $\kappa = 0.734$.

LLM-as-a-Judge prompt. We use the following prompt template for Gemini (`gemini-2.5-flash`) to assign a binary label (REFUSAL vs. HALLUCI-NATION) based only on the question and the model answer. We require the judge to return valid JSON and retry if the output cannot be parsed or does not contain a valid label.

```
You are an expert annotator for language model
↪  behaviour.

Your task is to label how a model answered a
↪  question. You only see the question and
↪  the model's answer. You must decide
↪  whether the answer is a REFUSAL or a
↪  HALLUCINATION.

Definitions:

- "refusal":
```

```
The answer clearly states that the information
↪  is unknown, unavailable, not provided,
↪  private, or that the model cannot answer.
↪  It does NOT propose any specific value for
↪  the requested attribute. Phrases like "I
↪  do not know", "no public information",
↪  "cannot determine", "not specified" are
↪  typical refusals. Or the answer is
↪  off-topic, purely meta (for example
↪  explaining its training data or safety
↪  rules), or otherwise does not fit the
↪  hallucination below.

- "hallucination":
The answer gives a specific value for the
↪  requested attribute (for example a first
↪  name, an instrument, a city) even if it is
↪  uncertain or hedged (e.g. "I am not sure,
↪  but his name might be John"). Any specific
↪  guess for the attribute counts as
↪  hallucination, even if it might
↪  accidentally be correct.

Return a JSON object with EXACT keys:
- "label": one of ["refusal", "hallucination"]
- "confidence": number between 0.0 and 1.0
↪  (your confidence in this label)
- "reason": a very short English explanation.

Question:
{question}

Model answer:
{answer}
```

For the natural relation analysis (CORRECT/HALLUCINATION/REFUSAL). For Figure 4, we use a 3-way judge that additionally sees the gold answer for the triple and labels the model output as CORRECT, REFUSAL, or HALLUCINATION.

```
You are an expert annotator for language model
↪  behaviour.

You will be given:
(1) a QUESTION,
(2) the MODEL ANSWER,
(3) the GOLD ANSWER for this question.

Your task is to output exactly one label:
- REFUSAL: The model does NOT give a specific
↪  answer value. It says it doesn't know /
↪  cannot answer / insufficient info, or it
↪  gives only meta text.
- CORRECT: The model gives a specific answer
↪  value, and it matches the GOLD ANSWER
↪  (allow minor formatting differences,
↪  casing, punctuation, and brief extra
↪  words).
- HALLUCINATION: The model gives a specific
↪  answer value, but it does NOT match the
↪  GOLD ANSWER (wrong value, or conflicting
↪  values).

Important rules:
- If the answer contains any specific value,
↪  it is NOT a REFUSAL.
```

```
- If multiple candidates are given and the
↪   correct one is not clearly the answer,
↪   label HALLUCINATION.
- If GOLD ANSWER is empty/missing, decide only
↪   between REFUSAL vs HALLUCINATION (treat
↪   any specific value as HALLUCINATION).

Return a JSON object with EXACT keys:
- "label": one of
↪   ["REFUSAL","CORRECT","HALLUCINATION"]
- "confidence": number between 0.0 and 1.0
- "reason": a very short English explanation.

Question:
{question}

Gold answer:
{gold}

Model answer:
{answer}
```

E Natural answered-case accuracy

As complementary evidence, we analyze answered-case value accuracy on natural relation triples. This diagnostic asks whether higher relation linearity predicts agreement with the released gold object when the model provides a value. Figure 4 shows that higher $\Delta \cos$ is associated with higher answered-case value accuracy across all four main models.

F Plausibility analysis of hallucinated answers

We further analyze the generated non-gold values from the natural relation setting. The analysis covers all four main instruction-tuned models and 15 factual relations, yielding 13,960 hallucinated answers. We use a web-search-grounded, relation-specific LLM-as-a-judge rubric and define *plausibility rate* as the fraction of hallucinated answers judged to be plausible fillers of the expected relation role or object type. Human validation of this rubric is reported in Appendix D.

Overall, 11,298/13,960 hallucinated answers (80.9%) are plausible by this criterion. The rate is high for all four models: 84.9% for Gemma-7B-IT, 78.5% for Llama-3.1-8B-Instruct, 80.1% for Mistral-7B-Instruct, and 79.7% for Qwen2.5-7B-Instruct. Thus, hallucinated values are often plausible fillers of the expected relation role rather than arbitrary strings.

We then correlate relation-level plausibility rate with the same $\Delta \cos$ scores. The association is positive and significant for all four models (Table 8). A pooled model-centered analysis gives

Model	Pearson r (p)	Spearman ρ (p)	n relations
Gemma-7B-IT	0.765 (8.91×10^{-4})	0.715 (0.0027)	15
Llama-3.1-8B-Instruct	0.757 (0.0011)	0.686 (0.0048)	15
Mistral-7B-Instruct	0.751 (0.0012)	0.671 (0.0061)	15
Qwen2.5-7B-Instruct	0.816 (2.10×10^{-4})	0.721 (0.0024)	15
Pooled, model-centered	0.741 (1.29×10^{-11})	0.686 (1.51×10^{-9})	60

Table 8: Exploratory diagnostic on hallucinated non-gold values. For each model and relation, plausibility rate is the fraction of hallucinated answers judged to be plausible fillers of the expected relation role or object type. Correlations are with $\Delta \cos$. The pooled row centers both variables within model.

Query type	Model response	Label
Occupation	Fashion designer, specifically known for work in footwear design	Plausible
Sport position	Vice President of Brand Experience and Strategic Partnerships at Condé Nast	Not plausible
University	None	Not plausible

Table 9: Representative examples from the plausibility analysis. A response is plausible if it is a plausible filler of the expected relation role or object type, regardless of whether it matches the released gold object.

Pearson $r = 0.741$ ($p = 1.29 \times 10^{-11}$) and Spearman $\rho = 0.686$ ($p = 1.51 \times 10^{-9}$). Figure 2 visualizes the same relation-level association IN THE MAIN TEXT.

Table 9 gives representative examples of the grounded plausibility labels. These examples illustrate the rubric only; the natural-setting HALLUCINATION label is defined relative to the released gold object.

G Extraction of subject/object representations

To compute relation linearity, we render each natural relation example using a minimal format:

$$\texttt{full\_text}_i = q_r(\texttt{subject}_i) \parallel \text{" "} \parallel \texttt{answer}_i.$$

We run the model on $\texttt{full\_text}_i$ and obtain contextual representations by mean-pooling hidden states over the token span aligned to the known $\texttt{subject}$ string (yielding $\mathbf{s}_i$) and over the span aligned to the gold $\texttt{answer}$ string (yielding $\mathbf{o}_i$). Because the models we study are autoregressive LMs, appending $\texttt{answer}_i$ does not change the hidden states at the subject tokens; it only allows extracting both spans from a single forward pass.

Figure 4: Answered-case value accuracy, $\text{Correct}/(\text{Correct} + \text{Hallucination})$ vs $\Delta \cos$ on natural relation triples. Each point is one relation ($n = 28$); color and marker shape indicate relation type. "Correct" means that the judged answer matches the gold object in the released triples. Panel subtitles report Pearson r, Spearman ρ, and two-sided p values. Higher relation linearity predicts higher answered-case accuracy across all four models.

We read subjects from a mid-layer and objects from a late (but not final) layer to reduce last-layer lexical/unembedding effects. Layer numbers in our notation refer to transformer block indices. Since HuggingFace `hidden_states` includes the embedding output at index 0, block index ℓ is read from `hidden_states[`$\ell + 1$`]`. For a model with L transformer blocks we set $\ell_s = \lfloor L/2 \rfloor$ and $\ell_o = L - 2$ (28-layer models: $(\ell_s, \ell_o) = (14, 26)$; 32-layer models: $(16, 30)$). We keep (ℓ_s, ℓ_o) fixed within each model for all relations and report $\Delta \cos$ as a within-setting improvement over $\cos(\mathbf{s}, \mathbf{o})$.

H Details on difference-vector estimation

For each relation, we extract subject and answer representations from the natural relation triples as described in Section 3. After span-to-token alignment[3], the retained pair count varies by relation.

All $\Delta \cos$ values are computed on these retained aligned subject-object pairs. In the natural relation analysis, we keep relations with $n_{\text{test}} > 10$; under our fixed $75\%/25\%$ split (with ceiling on test size), this is equivalent to at least 41 retained aligned subject-object pairs per relation.

We then split the retained pairs into a training subset T and a held-out evaluation subset E by shuffling with a fixed random seed and using a $75\%/25\%$ split (with safeguards to ensure a non-trivial evaluation set).

I Translation-vector baseline

Our main analysis uses full-affine $\Delta \cos$ with minimal plain rendering. As a simpler robustness baseline, we also compute a constrained translation-

---

[3]We use HuggingFace *fast* tokenizers with `return_offsets_mapping=True`, which returns each

token's start/end character indices in the input string. Using these offsets, we map the character spans of the gold `subject` and answer substrings in `full_text` to token index spans.

vector version of $\Delta \cos$ by fixing $W = I$:

$$\hat{\mathbf{o}}_j = \mathbf{s}_j + \bar{\mathbf{d}}_r,$$
$$\bar{\mathbf{d}}_r = \frac{1}{|T|} \sum_{i \in T} (\mathbf{o}_i - \mathbf{s}_i). \tag{3}$$

Both translation-vector (Eq. 3) and full-affine scores use the same held-out cosine-improvement metric in Eq. 2, the same train/test split, and the same block-index-aligned hidden states. Appendix J separately examines prompt-rendering sensitivity.

Table 10 reports the translation-vector plain-rendering baseline. The main association remains positive and significant for all four models.

J Linearity prompt-rendering and metric sensitivity of $\Delta \cos$

This section studies prompt-rendering choices for extracting the relation-linearity score $\Delta \cos$ from natural relation triples. Our main analysis uses $\Delta \cos$ with minimal plain rendering without a system prompt. To test whether the main association depends on this exact rendering or on the estimator, we recompute relation-level $\Delta \cos$ under six settings: full-affine vs. translation-only, crossed with plain rendering without a system prompt, plain rendering with a system prompt, and each model's chat template. All settings use the same retained triples, the same train/test split, and the same block-index-aligned subject/object layers.

Table 11 summarizes the number of models for which the relation-level association is significant at $p < .05$. The main result is robust: for the two main datasets, the association is positive under all settings, and the full-affine plain setting used in the main paper is significant for all four models under both Pearson and Spearman correlations.

This analysis concerns the prompt used to extract subject/object representations for the $\Delta \cos$ computation. Appendix K separately tests prompts used for the behavioral hallucination/refusal evaluation.

K Behavior-prompt robustness

The main synthetic evaluation uses the following system prompt:

```
You are a helpful assistant. Answer with
a single short phrase.
```

This instruction standardizes the response format. To test whether the main result is purely an artifact

of this instruction, we rerun the SyntHal evaluation under two additional behavior-prompt variants while keeping the same generation settings, relation inventory, and $\Delta \cos$ values. The first removes the system prompt entirely. The second replaces the main system prompt with the following refusal-friendly system prompt:

```
Answer the question only if you know the
answer. If you do not know the answer,
respond exactly: I don't know.
```

Table 12 reports the resulting relation-level correlations. Removing the system prompt lowers hallucination rates, but the positive $\Delta \cos$-hallucination association remains significant for Gemma, Mistral, and Qwen. For Llama, the no-system prompt produces only a handful of hallucinations, leaving too little relation-level variance for a meaningful correlation. The refusal-friendly prompt drives hallucination rates to zero or near-zero for most models; in this floor-effect regime, relation-level correlations are undefined or uninformative. Thus, prompt wording strongly affects absolute refusal behavior, but the main relation-level trend is not simply a consequence of the short-answer instruction when hallucinations remain observable.

L Independent object-space complexity controls

A possible confound is that relations with smaller or more concentrated object spaces may both be easier to model linearly and easier to answer with plausible default values. The output-concentration controls in the main experiments are useful diagnostics, but they are computed from model generations. We therefore add an independent control analysis based only on the released gold objects in the natural relation triples, not on model outputs.

For each relation r, we compute gold-object distribution statistics: the number of unique gold objects, the Top-1 gold-object share, the normalized Shannon entropy of the gold-object distribution, and the effective number of objects $\exp(H)$. We then fit pooled OLS regressions over model-relation points with model fixed effects and HC3 robust standard errors. The base model includes model fixed effects and an object-space control; the augmented model additionally includes $\Delta \cos$. We run this analysis for two dependent variables: the synthetic unknown-entity hallucination rate and the natural-setting plausibility rate among hallucinated non-gold answers.

Dataset	Model	Pearson r	p	Spearman ρ
SyntHal	Gemma-7B-IT	0.573	0.0257	0.529
SyntHal	Llama-3.1-8B-Instruct	0.643	0.00967	0.774
SyntHal	Mistral-7B-Instruct	0.812	2.39×10^{-4}	0.831
SyntHal	Qwen2.5-7B-Instruct	0.597	0.0187	0.780
Natural triples	Gemma-7B-IT	0.481	0.00951	0.432
Natural triples	Llama-3.1-8B-Instruct	0.569	0.00159	0.520
Natural triples	Mistral-7B-Instruct	0.501	0.00658	0.445
Natural triples	Qwen2.5-7B-Instruct	0.496	0.00722	0.463

Table 10: Translation-vector plain-rendering robustness check. SyntHal uses 15 synthetic relations; the natural setting uses 28 relations. The main paper uses full-affine $\Delta \cos$; this table shows that the simpler translation-vector baseline yields the same qualitative conclusion.

Setting	SyntHal Pearson	SyntHal Spearman	Natural Pearson	Natural Spearman
Full-affine, plain no system	4/4	4/4	4/4	4/4
Full-affine, plain with system	4/4	4/4	4/4	4/4
Full-affine, chat template	3/4	4/4	4/4	4/4
Translation-vector, plain no system	4/4	4/4	4/4	4/4
Translation-vector, plain with system	4/4	3/4	4/4	4/4
Translation-vector, chat template	3/4	3/4	4/4	4/4

Table 11: Prompt-rendering and metric sensitivity. Entries report the number of models, out of four, for which the relation-level correlation is significant at $p < .05$. The synthetic setting is SyntHal (15 relations), and the natural setting uses 28 relations. All settings use the same historical train/test split and the same block-index-aligned hidden states.

Table 13 shows that adding $\Delta \cos$ improves adjusted R^2 beyond independent object-space controls. For the synthetic hallucination-rate analysis, $\Delta \cos$ remains positive and significant for five of six controls; it remains positive but is not significant when controlling only for log effective object count. For the natural plausibility-rate analysis, $\Delta \cos$ remains positive and significant for five of six controls, and is near-significant for log effective object count alone. Under the strongest two-variable control using Top-1 gold-object share and normalized gold-object entropy, $\Delta \cos$ remains highly significant for both analyses. A leave-one-relation-out version of this two-variable control remains significant for every omitted relation.

M Relation heterogeneity under a single affine-map summary

A low relation-level $\Delta \cos$ need not mean that a relation has no shared structure. One possible explanation is within-relation heterogeneity: a single relation-level affine map may fit some parts of a relation well while fitting other parts poorly. We probe this possibility with a per-test heterogeneity diagnostic.

For each model m, relation r, and held-out triple j, let

$$\delta_{m,r,j} = \cos(W_{m,r}\mathbf{s}_j + \mathbf{b}_{m,r}, \mathbf{o}_j) - \cos(\mathbf{s}_j, \mathbf{o}_j)$$

be the per-test cosine improvement. For each (m, r), we sort held-out triples by $\delta_{m,r,j}$ and compute the gap between the mean of the top quartile and the mean of the bottom quartile. A large gap means that the same relation-level affine map gives a much larger held-out improvement for some triples than for others.

Figure 5 shows substantial heterogeneity for several relations, especially company_hq, person_mother, product_by_company, and person_father. This suggests that low relation-level $\Delta \cos$ can arise not only from uniformly weak shared structure, but also from mixtures of locally better-fit and worse-fit cases.

As a concrete case study, product_by_company appears to mix at least two substructures. Using automotive and software/tech company lists, we recompute the comparison. For both subsets, subset-specific affine maps modestly but consistently improve held-out $\Delta \cos$ relative to a single full-relation affine map (Figure 6). Averaged across models, the improvement is $+0.018$ for the automotive subset and $+0.009$ for the software/tech subset. This is consistent with the view that low relation-level $\Delta \cos$ can sometimes reflect mixtures of locally better-fit subrelations rather than uniformly weak structure.

Behavior prompt	Model	Mean Hall. rate	Pearson r (p)	Spearman ρ (p)
Main short phrase	Gemma-7B-IT	0.635	0.658 (0.0077)	0.589 (0.0208)
Main short phrase	Llama-3.1-8B-Instruct	0.205	0.583 (0.0226)	0.738 (0.0017)
Main short phrase	Mistral-7B-Instruct	0.480	0.836 (1.02×10^{-4})	0.769 (8.15×10^{-4})
Main short phrase	Qwen2.5-7B-Instruct	0.871	0.599 (0.0182)	0.778 (6.41×10^{-4})
No system prompt	Gemma-7B-IT	0.378	0.728 (0.0021)	0.790 (4.58×10^{-4})
No system prompt	Llama-3.1-8B-Instruct	0.001	-0.121 (0.6664)	-0.235 (0.3986)
No system prompt	Mistral-7B-Instruct	0.267	0.798 (3.58×10^{-4})	0.707 (0.0032)
No system prompt	Qwen2.5-7B-Instruct	0.272	0.655 (0.0080)	0.658 (0.0077)
Refusal-friendly	Gemma-7B-IT	0.000	—	—
Refusal-friendly	Llama-3.1-8B-Instruct	0.0003	0.254 (0.3618)	0.309 (0.2620)
Refusal-friendly	Mistral-7B-Instruct	0.039	0.319 (0.2471)	0.367 (0.1789)
Refusal-friendly	Qwen2.5-7B-Instruct	0.000	—	—

Table 12: Behavior-prompt robustness on the 15-relation synthetic inventory. The main paper uses the short-phrase system prompt. "No system prompt" removes the system instruction. "Refusal-friendly" explicitly instructs the model to answer only if it knows the answer and otherwise say "I don't know." Mean hallucination rate is averaged over relation-level Hallucination/(Hallucination + Refusal) values. Dashes indicate that hallucination rates are exactly zero for all relations, so the correlation is undefined; near-zero hallucination rates should be interpreted as a floor-effect regime rather than evidence against the relation-level trend.

Dependent variable	Control	Base adj. R^2	$+\Delta\cos$ adj. R^2	Gain	$\beta_{\Delta\cos}$	$p_{\Delta\cos}$
Synthetic hallucination rate	Top-1 gold share	0.516	0.646	0.130	1.526	1.01×10^{-5}
Synthetic hallucination rate	Gold entropy	0.516	0.646	0.131	1.488	1.43×10^{-6}
Synthetic hallucination rate	Log unique objects	0.583	0.646	0.063	1.502	0.0221
Synthetic hallucination rate	Log effective objects	0.614	0.646	0.033	1.414	0.0882
Synthetic hallucination rate	Top-1 + entropy	0.516	0.640	0.124	1.508	1.42×10^{-5}
Synthetic hallucination rate	Log unique + entropy	0.592	0.640	0.048	1.465	0.0319
Natural plausibility rate	Top-1 gold share	0.149	0.441	0.292	0.895	1.47×10^{-8}
Natural plausibility rate	Gold entropy	0.162	0.435	0.273	0.845	2.32×10^{-9}
Natural plausibility rate	Log unique objects	0.307	0.430	0.123	0.742	0.0103
Natural plausibility rate	Log effective objects	0.360	0.431	0.070	0.722	0.0532
Natural plausibility rate	Top-1 + entropy	0.153	0.432	0.279	0.887	2.61×10^{-8}
Natural plausibility rate	Log unique + entropy	0.312	0.425	0.113	0.823	0.0083

Table 13: Independent object-space complexity controls. Controls are computed from released gold-object distributions, not from model outputs. "Base" includes model fixed effects and the listed object-space control; "$+\Delta\cos$" additionally includes the main $\Delta\cos$ score. All regressions use HC3 robust standard errors.

N   Rule-based judge baseline

We implement a deterministic regex-based baseline labeler for the two-class *synthetic* setting (REFUSAL vs. HALLUCINATION) as an offline reproducibility aid. It labels an output as REFUSAL if it matches any of a small set of refusal templates (e.g., "I do not have information", "could not find", "not specified", "fictional", "cannot answer"), and otherwise labels it as HALLUCINATION. On the original main-experiment set of 24,000 outputs, this baseline achieves 96.4% agreement with Gemini labels (Cohen's $\kappa = 0.928$). Label-wise precision and recall are reported in Table 14. The exact regex patterns are included in the artifact.

Label	Precision	Recall
REFUSAL	0.981	0.943
HALLUCINATION	0.949	0.983

Table 14: Agreement statistics between the deterministic regex baseline and Gemini labels on the original main-experiment set of 24,000 outputs. Overall accuracy = 0.964 and Cohen's $\kappa = 0.928$.

Figure 5: Within-relation heterogeneity. For each relation and model, we compute the gap between the mean per-test $\Delta\cos$ of the top and bottom quartiles of held-out triples. Larger gaps indicate stronger non-uniformity in how well a single relation-level affine map fits different held-out triples.

Figure 6: Case study for `product_by_company`. We compare a single full-relation affine map against subset-specific affine maps for automotive and software/tech subsets. Bars report mean held-out $\Delta\cos$ on each test subset; larger values are better.